

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409574
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Blatter; Alan et al.

Razor cartridge

Abstract

A razor cartridge has a housing with a blade mounting region between a guard and a cap. A first, second and third razor blade are sequentially mounted in the blade mounting region. An over-guard is secured over the blades. The cutting edges of the blades have an as-defined increased sharpness. The blades are mounted at a reduced angle between each blade portion bearing the cutting edge and a reference plane tangential to the cutting edges of the first and third blade. Individual longitudinal members of the over-guard that lie over each blade and have a progressively decreasing height above the reference plane in a front to back direction of the razor cartridge. A further longitudinal member is forward of the first blade and has a height above the reference plane.

Inventors:	Blatter; Alan (Sandy Hook, CT), Chasen; James (West Haven, CT), Fernald; Christopher (Fairfield, CT)
Applicant:	Edgewell Personal Care Brands, LLC (Chesterfield, MO)
Family ID:	80937311
Assignee:	Edgewell Personal Care Brands, LLC (Chesterfield, MO)
Appl. No.:	18/550199
Filed (or PCT Filed):	March 07, 2022
PCT No.:	PCT/US2022/019118
PCT Pub. No.:	WO2022/192127
PCT Pub. Date:	September 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240157591 A1	May. 16, 2024

Related U.S. Application Data

us-provisional-application US 63160029 20210312

Publication Classification

Int. Cl.: B26B21/40 (20060101)

U.S. Cl.:

CPC B26B21/4018 (20130101); B26B21/4031 (20130101); B26B21/4037 (20130101);

Field of Classification Search

CPC: B26B (21/4018); B26B (21/4031); B26B (21/4037)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5369885	12/1993	Ferraro	30/41	B26B 21/4012
2003/0159291	12/2002	Clark	30/41	B26B 21/4068
2012/0317818	12/2011	Oglesby	30/77	B26B 21/4018
2012/0324737	12/2011	Howell	30/50	B26B 21/4018
2017/0197322	12/2016	Drori	N/A	B26B 21/42
2019/0047164	12/2018	Lee	N/A	B26B 21/4043
2019/0255720	12/2018	Galanis	N/A	B26B 21/4037
2019/0270210	12/2018	Coresh	N/A	B29C 66/30321
2020/0031006	12/2019	Kim	N/A	B26B 21/4031
2020/0338770	12/2019	Moustakas	N/A	B26B 21/4031
2020/0398449	12/2019	Claus	N/A	B26B 21/565
2021/0016458	12/2020	Peterson	N/A	B26B 21/4012
2021/0031389	12/2020	Bozikis	N/A	B26B 21/565

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3689559	12/2019	EP	N/A
199411163	12/1993	WO	N/A
199735693	12/1996	WO	N/A
2010039749	12/2009	WO	N/A
2018019951	12/2017	WO	N/A

OTHER PUBLICATIONS

International Search Report mailed on Jun. 15, 2022, by the International Searching Authority for International Application No. PCT/US2022/019118. cited by applicant

Written Opinion mailed on Jun. 15, 2022, by the International Searching Authority for International Application No. PCT/US2022/019118. cited by applicant

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to International Application No. PCT/US2022/019118, filed on Mar. 7, 2022, which claims priority to U.S. Provisional Patent Application No. 63/160,029, filed Mar. 12, 2021, the contents of which are incorporated herein for reference in their entirety.

BACKGROUND

1. Technical Field

(1) The present disclosure relates to safety razors in general and, more particularly, to a razor cartridge having a protective over-guard.

2. Background

(2) Some shavers suffer from skin conditions such as pseudofolliculitis barbae (PFB) and acne. These users would like to be able to shave successfully without irritation(s) or worsening their pre-existing conditions. Some other users prefer an appearance of having a permanent “5 o'clock shadow” and would like to be able to shave to maintain this look.

SUMMARY

(3) The present disclosure has for its objective to substantially alleviate the limitations of the prior art razor cartridges by providing a razor cartridge having an over-guard. The razor cartridge has a housing with a guard at a front region of the housing, a cap at a rear region of the housing, and opposed end walls connecting the guard and the cap. The housing defines a blade mounting region between the guard and the cap. A first, second and third razor blade are sequentially mounted in the blade mounting region with the first blade closest the guard, and each razor blade having a cutting edge. A reference plane is tangential to the cutting edge of the first razor blade and the cutting edge of the third razor blade, and each blade body portion bearing the cutting edge being at an angle to the reference plane. An over-guard is secured over the blades and includes a first longitudinal member in advance of the first blade, and a second, third and fourth longitudinal member lying respectively over the first, second and third razor blades. Each first, second, third and fourth longitudinal member has a respective height above the reference plane.

(4) In some aspects the over-guard has front to back extending slots in the first, second and third longitudinal member. In some aspects of this aspect the slots are aligned in a front to back direction of the razor cartridge. In other aspects the slots can be omitted.

(5) In some aspects the over-guard further has a front to back cross rib extending from the first member to the fourth member.

(6) In some aspects the cutting edges of each razor blade have a cut-force sharpness, as defined herein in a range about 5-6.5 N.

(7) In some aspects the angle between the blade body portions bearing the cutting edges and the reference plane is 20.5 degrees.

(8) In some aspects the heights of the second third and fourth members above the reference plane progressively decrease in a front to back direction of the razor cartridge. In some aspects the height of the second member above the reference plane is in a range about 0.287 to 0.212 mm. The height of the third member above the reference plane is in a range about 0.150 to 0.129 mm. The height of the fourth member above the reference plane is about 0.039 mm. The height of the first longitudinal member above the reference plane is equivalent to the height of the second longitudinal member above the reference plane (200).

(9) The razor cartridge in use in a defined manner will not provide a typical “close” shave but will

provide adequate comfort. The above features and advantages will be more fully understood with reference to the following detailed description when taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is an upper perspective view of a razor cartridge of the present disclosure;
- (2) FIG. 2 is a transverse sectional view of the cartridge;
- (3) FIG. 3 is a detailed portion of FIG. 2; and
- (4) FIG. 4 is a perspective view of another over-guard of the present disclosure.

DETAILED DESCRIPTION

(5) Referring now to the drawings and in particular FIG. 1, a razor cartridge **20** is depicted. The cartridge **20** has a housing **30** with a guard **40** at a front region of the housing **30** and a cap **50** at a rear region of the housing **30**. The guard **40** can optionally be provided with skin-engaging fins, as depicted, e.g. elastomeric fins. In the context of the present disclosure the terms front, forward, leading etc., and rear, aft, trailing etc. are used relative to a direction of motion of the razor cartridge **20** in use. The term longitudinal is used relative to an elongated direction **32** of the housing. The housing has opposed end walls **60** connecting the guard **40** and cap **50**. The housing defines a blade mounting region **70** (see FIG. 2) between the guard **40** and the cap **50**. A first razor blade **80**, closest the guard **40**, a second, immediately trailing razor blade **90**, and a third rearmost razor blade **100** are mounted in the blade mounting region **70**. Each razor blade **80**, **90**, **100** has a respective cutting edge **82**, **92**, **102** (see FIGS. 2 & 3). Three razor blades **80**, **90**, **100** are described as being mounted in the cartridge **20** of the present disclosure however this quantity should not be limiting and fewer (e.g. two) or more (e.g. four, five etc) razor blades can usefully be employed. An over-guard **120**, being a separate component part of the assembly of the cartridge **20** is positioned over the blades **80**, **90**, **100**. A retainer **130**, e.g. one or more aluminum clips, is formed around the housing **30** to retain the blades **80**, **90**, **100** and over-guard **120** to the housing **30**. In the embodiment depicted in FIG. 1 certain elements of the over-guard **120** are provided with hair-aligning slots **122** in the skin-engaging surfaced. The slots **122** can have a width 0.8 mm, a depth 0.52 mm deep, and a pitch 1.6 mm. The slots **122** can be aligned in a front to back direction of the cartridge **20**, or can be offset.

(6) The housing **30** is manufactured by injection molding a suitable thermoplastic polymer. For example, the housing **30** can be formed from ABS (acrylonitrile butadiene styrene) for benefits of chemical resistance (to substances typically found in use), impact resistance, and dimensional stability.

(7) The over-guard is manufactured from a material having a tensile modulus 1.4-210 GPa. For example, the over-guard **120** can be injection molded ABS or POM. The over-guard **120** can be die-cast zinc alloy. The over-guard **120** can be (stainless) steel, e.g. formed in a perforation tool, or can be particulate stainless steel that is sintered to provide a solid body.

(8) Referring now to FIG. 2, a transverse cross section of the cartridge **20** is depicted. The over-guard **120** for a three-blade cartridge **20** comprises essentially four longitudinally extending members. A first member **140** is in advance of the first blade **80** and has a leg **142** providing structural (stiffness) benefits. Members **150**, **160**, **170** lie respectively over the three blades **80**, **90**, **100**, and have respective legs **152**, **162**, **172** also for structural (stiffness) benefits. Referring back to FIG. 1, the over-guard **120** is provided with a front to back cross rib **180**, extending from member **140** to member **170** for further structural stability benefits.

(9) In FIG. 4 another over-guard **120** is depicted, omitting the slots **122** of FIG. 1. In this FIG. it can be seen that all four longitudinally extending members are interconnected at opposed elongated

ends of the over-guard **120**.

(10) Referring now to FIG. 3, a detailed portion of FIG. 2 is depicted. A reference plane 200 is tangential to the cutting edges **82**, **102** of the first and last (e.g. third) blades **80**, **100**. The plane 200 can also be tangential to the cutting edge **92** of the other (e.g. second) blade(s) **90**, especially in embodiments where the razor cartridge has two blades. The blade cutting edges are spaced apart by a span dimension along plane 200 by spans S1, S2 equal to 2.72 mm. Each blade cutting edge **82**, **92**, **102** is spaced from the respective immediately next-forward longitudinal member **140**, **150**, **160** by a distance **202**, **212**, **222** respectively in a range 0.8-0.9 mm. The distances **202**, **212**, **222** being measured from the respective cutting edge to the next-forward skin engaging tangent point of the over-guard **120**. The longitudinal members **150**, **160**, **170** have a height H1, H2, H3 respectively from the upper respective skin engaging surface to the reference plane 200. The first longitudinal member **140** has a height from the upper skin engaging surface to the reference plane 200 that is equivalent to height H1. The blades **80**, **90**, **100** are each positioned such that the blade body portion bearing the cutting edge is at an angle A having a value about 20.5 degrees (e.g. in a range 19 to 21.5 degrees) to the reference plane 200. The angle A can be defined between the reference plane 200 and one (i.e. upper or lower) outer surface of the blade body portion, or can be defined (as shown) between the reference plane 200 and a notional center plane of the blade body portion. This value is slightly lower than the angle found in many typical modern wet shaving cartridges, which can be in a range 22-28 degrees, and has been found beneficial when used in the present device in conjunction with blade cutting edges having increased sharpness, as described below.

(11) The cutting edges **82**, **92**, **102** of the blades **80**, **90**, **100** can have conventional sharpness, as generally found in typical modern wet shaving cartridges, i.e. about 7-14 N, with a median value about 10-10.5 N as measured in a cut force test, as described below. More preferably the blades have increased sharpness, e.g. about 5-6.5 N. In the cut force test the blades are cut perpendicularly (relative to the medium being cut) 15 times into fully water saturated WHATMAN cellulose chromatography paper, having thickness 0.9 mm and width 25.4 mm. The cutting speed is 15 mm/min and cutting depth into the paper is 0.8 mm. The above-mentioned sharpness cut force is the average plateau force from cut no. 7 to cut no. 9.

(12) In experimental arrangements, cartridges having the following heights H1, H2, H3 were evaluated:

(13) TABLE-US-00001

	H1 (mm)	H2 (mm)	H3 (mm)	
Example 1	0.287	0.212	0.116	Example 2
0.150	0.129	0.069		Example 3
	0.039	0.039	0.037	

(14) The values of H1, H2, H3 progressively decrease in a front to back direction of the cartridge. In controlled shaving test, the Applicants of the present disclosure have found the combination of “sharper” blade cutting edges, plus “reduced” blade body to reference plane angles, plus greater over-guard longitudinal member heights above a reference plane (e.g. of examples 2, and 1) provide benefits to sufferers of PFB, and also provide controlled beard length trimming for a permanent “5 o'clock shadow” appearance for the user.

(15) While various embodiments have been described above it should be understood that they have been presented by way of example only, and not limitation. For instance, modifications or changes as can be made within the scope of the attached claims and features disclosed in connection with any one embodiment can be used alone or in combination with each feature of the respective other embodiments. Thus, the breadth and scope of any embodiment should not be limited by any of the above-described exemplary embodiments but should be defined only in accordance with the following claims and their equivalents.

Claims

1. A razor cartridge, comprising: a housing having a guard at a front region of the housing, a cap at a rear region of the housing, and opposed end walls connecting the guard and the cap, the housing defining a blade mounting region between the guard and the cap; a first razor blade closest to the guard, a next-adjacent second razor blade, and a last third razor blade mounted in the blade mounting region, each having a respective cutting edge having a sharpness; a reference plane tangential to the cutting edge of the first razor blade and the cutting edge of the third razor blade, each blade body portion bearing the cutting edge being at an angle to the reference plane; an over-guard secured over the razor blades and including a first longitudinal member in advance of the first razor blade, and a second a third and a fourth longitudinal member lying respectively over the razor blades, each second, third and fourth members having a respective height above the reference plane.
 2. The razor cartridge of claim 1, wherein the over-guard has front to back extending slots in the first, second and third member.
 3. The razor cartridge of claim 1, wherein the over-guard further includes a front to back cross rib, extending from the first member to the fourth member.
 4. The razor cartridge of claim 1, wherein the cutting edge of each razor blade has a cut-force sharpness in a range of about 5-6.5 N.
 5. The razor cartridge of claim 1, wherein the angle is about 20.5 degrees.
 6. The razor cartridge of claim 1, wherein each height progressively decrease in a front to back direction of the razor cartridge.
 7. The razor cartridge of claim 1, wherein the height of the second member is in a range about 0.287 to 0.212 mm.
 8. The razor cartridge of claim 1, wherein the height of the third member is in a range about 0.150 to 0.129 mm.
 9. The razor cartridge of claim 1, wherein the height of the fourth member above is about 0.039 mm.
 10. The razor cartridge of claim 1, wherein the height of the first member is equivalent to the height of the second member.
-