

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                           |
|----------------------|---------------------------|
| United States Patent | 12409884                  |
| Kind Code            | B2                        |
| Date of Patent       | September 09, 2025        |
| Inventor(s)          | Naik; Anand Pradip et al. |

---

### Methods and apparatus to improve electronic power assisted steering in a vehicle

---

#### Abstract

Methods, apparatus, systems and articles of manufacture are disclosed to improve electronic power assisted steering in a vehicle. An example apparatus includes memory and a processor to execute instructions to determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determine a steering column torque derivative based on a derivative of the steering column torque, determine a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjust a steering response of the steering column based on the compliance compensation torque.

---

**Inventors:** Naik; Anand Pradip (Royal Oak, MI), Recker; Darrel Alan (Ypsilanti, MI), Nehls; Oliver (Düsseldorf, DE)

**Applicant:** Ford Global Technologies, LLC (Dearborn, MI)

**Family ID:** 80473924

**Assignee:** Ford Global Technologies, LLC (Dearborn, MI)

**Appl. No.:** 17/026111

**Filed:** September 18, 2020

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20220089211 A1          | Mar. 24, 2022           |

---

#### Publication Classification

**Int. Cl.:** B62D5/04 (20060101); H02P6/08 (20160101); H02P6/17 (20160101)

## U.S. Cl.:

CPC     **B62D5/0463** (20130101); **H02P6/08** (20130101); **H02P6/17** (20160201); B62D5/0409 (20130101); B62D5/0424 (20130101); H02P2205/05 (20130101)

## Field of Classification Search

**CPC:**     B62D (5/0409); B62D (5/0424); B62D (5/0463); H02P (2205/05); H02P (6/08)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name    | U.S. Cl. | CPC         |
|--------------|-------------|------------------|----------|-------------|
| 8903606      | 12/2013     | Kleinau et al.   | N/A      | N/A         |
| 9889878      | 12/2017     | Konieczny et al. | N/A      | N/A         |
| 2017/0066472 | 12/2016     | Wang             | N/A      | B62D 5/0463 |
| 2020/0290668 | 12/2019     | Moreillon        | N/A      | B62D 6/005  |

---

*Primary Examiner:* Han; Charles J

*Attorney, Agent or Firm:* Hanley, Flight & Zimmerman, LLC

---

## Background/Summary

### FIELD OF THE DISCLOSURE

(1) This disclosure relates generally to vehicles and, more particularly, to methods and apparatus to improve electronic power assisted steering assist in a vehicle.

### BACKGROUND

(2) Modern vehicles typically include electronic power assisted steering (“EPAS”) systems that provide powered assistance (e.g., power-assisted torque and/or power-assisted momentum) to a steering assembly of the vehicle to increase the ease with which a portion of the steering assembly (e.g., a steering wheel) may be rotated and/or otherwise moved by an occupant (e.g., a driver) of the vehicle. Conventional EPAS systems include an EPAS controller that controls an EPAS motor to provide the above-described powered assistance to the steering assembly.

### SUMMARY

(3) Methods and apparatus to improve electronic power assisted steering in a vehicle are disclosed. An example apparatus includes memory, and a processor to execute instructions to determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determine a steering column torque derivative based on a derivative of the steering column torque, determine a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjust a steering response of the steering column based on the compliance compensation torque.

(4) An example non-transitory computer readable storage medium including instructions that, when executed, cause a machine to at least determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determine a steering column torque derivative based on a derivative of the steering column torque, determine a compliance compensation torque based on the steering column torque and the steering column

torque derivative, and adjust a steering response of the steering column based on the compliance compensation torque.

(5) An example method includes determining a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determining a steering column torque derivative based on a derivative of the steering column torque, determining a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjusting a steering response of the steering column based on the compliance compensation torque.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an illustration of an example environment including an example vehicle including an example electronic power assisted steering (EPAS) system and an example EPAS controller.

(2) FIG. 2 is a first example implementation of the EPAS system of FIG. 1.

(3) FIG. 3 is a second example implementation of the EPAS system of FIG. 1.

(4) FIG. 4 is a block diagram of an example implementation of the EPAS controller of FIG. 1.

(5) FIG. 5 is a block diagram of another example implementation of the EPAS controller of FIG. 1 including example compliance compensation torque logic.

(6) FIG. 6 is a block diagram of an example implementation of the compliance compensation torque logic of FIG. 5.

(7) FIG. 7 is a flowchart representative of example machine readable instructions that may be executed to implement the example EPAS controller of FIGS. 1, 4, 5, and/or 6 to adjust an example steering response of the example vehicle of FIG. 1.

(8) FIG. 8 is a flowchart representative of example machine readable instructions that may be executed to implement the example EPAS controller of FIGS. 1, 4, 5, and/or 6 to determine an example compliance compensation torque.

(9) FIG. 9 is a block diagram of an example processing platform structured to execute the example machine readable instructions of FIGS. 7-8 to implement the example EPAS controller of FIGS. 1, 4, 5, and/or 6.

(10) FIG. 10 is a block diagram of an example software distribution platform to distribute software (e.g., software corresponding to the example computer readable instructions of FIGS. 7-8) to example vehicles.

### DETAILED DESCRIPTION

(11) The figures are not to scale. In general, the same reference numbers will be used throughout the drawing(s) and accompanying written description to refer to the same or like parts. As used herein, connection references (e.g., attached, coupled, connected, and joined) may include intermediate members between the elements referenced by the connection reference and/or relative movement between those elements unless otherwise indicated. As such, connection references do not necessarily infer that two elements are directly connected and/or in fixed relation to each other.

(12) Unless specifically stated otherwise, descriptors such as “first,” “second,” “third,” etc., are used herein without imputing or otherwise indicating any meaning of priority, physical order, arrangement in a list, and/or ordering in any way, but are merely used as labels and/or arbitrary names to distinguish elements for ease of understanding the disclosed examples. In some examples, the descriptor “first” may be used to refer to an element in the detailed description, while the same element may be referred to in a claim with a different descriptor such as “second” or “third.” In such instances, it should be understood that such descriptors are used merely for identifying those elements distinctly that might, for example, otherwise share a same name.

(13) Modern vehicles typically include electronic power assisted steering (“EPAS”) systems that

provide powered assistance (e.g., power-assisted torque and/or power-assisted momentum) to a steering assembly of the vehicle to increase the ease with which a portion of the steering assembly (e.g., a steering wheel) may be rotated and/or otherwise moved by an occupant (e.g., a driver) of the vehicle. Conventional EPAS systems include an EPAS controller that controls an EPAS motor to provide the above-described powered assistance to the steering assembly.

(14) Some EPAS systems are rack EPAS systems that transmit rotational force of a motor (e.g., an EPAS motor) to a rack via a driver pulley, a belt, a driven pulley, and a ball nut assembly (BNA). In such rack EPAS systems, the BNA is rotationally supported to an inner circumferential surface of a housing via ball bearings. In some conventional rack EPAS systems, manufacturers may introduce a compliant spring between the BNA and the housing to allow an additional degree of freedom to rock, move, etc., because of tight tolerances in manufacturing amongst other factors, such as overcoming a rack force. Such a rack force can be generated responsive to wheels of a vehicle pushing against the rack. In such instances, the EPAS motor must overcome the rack force when attempting to turn to rotate the wheels.

(15) In some instances, the compliant spring remains compliant on-center and bottoms out as the BNA moves off-center. This additional compliance on the on-center region can lead to various tradeoffs between system stability, disturbance rejection capability, and steering feel to an operator (e.g., a driver). Such additional compliance may be added to achieve a desired mechanical stiffness. However, the additional compliance is static and cannot be changed after manufacturing. Further, challenges exist to provide the desired mechanical stiffness to each vehicle during manufacturing due to variations in manufacturing tolerances from vehicle-to-vehicle.

(16) Examples disclosed herein improve EPAS systems by dynamically assisting and/or otherwise invoking EPAS motors to overcome mechanical compliance and to reduce degradation of the on-center feel response. In some disclosed examples, an EPAS controller generates a command to add compliance compensation torque to an EPAS base torque to overcome mechanical compliances in the EPAS systems, such as rack forces. In some disclosed examples, the EPAS controller obtains measurements associated with the EPAS systems, such as a torque of a steering column, a vehicle speed, a velocity of an EPAS motor, a position of the EPAS motor, etc. In such disclosed examples, the EPAS controller maps ones of the measurements and derivatives of one(s) of the measurements to tunable lookup tables to generate the command to output a desired or intended compliance compensation torque.

(17) Advantageously, the example EPAS controller can dynamically adjust the EPAS base torque during operation of the vehicle based on the measurements, the derivative(s) of the measurement(s), etc., and/or a combination thereof. Advantageously, the example EPAS controller can determine the compliance compensation torque that is tailored and/or otherwise customized for a vehicle based on the manufacturing tolerances of the vehicle without adjusting the vehicle during manufacturing to account for the manufacturing tolerances.

(18) FIG. 1 is an illustration of an example environment **100** including an example vehicle system **102**, example external computing system(s) **104**, and an example network **106**. In this example, the vehicle system **102** includes an example vehicle **108**, which includes an example EPAS system **110**, an example EPAS controller **112**, and example electronic control unit(s) (ECU(s)) **114**.

Alternatively, the EPAS system **110** may include the EPAS controller **112**.

(19) The vehicle **108** is a truck. Alternatively, the vehicle **108** may any other type of automobile or motored vehicle, such as a sedan, a van, industrial motored vehicle, etc. Alternatively, the vehicle **108** may be an all-terrain vehicle (ATV) (e.g., a 3-wheeler ATV, a 4-wheeler ATV, etc.).

(20) The EPAS system **110** includes a motor (e.g., an EPAS motor) to actuate and/or otherwise adjust a steering system (e.g., a column steering system, a rack or rack-and-pinion steering system, etc.) as an operator (e.g., a human driver, a computer-based driver (e.g., a computing device executing machine readable instructions) to facilitate autonomous driving, etc.) turns a steering wheel of the vehicle **108**.

(21) In some examples, the EPAS system **110** implements a column EPAS system when the EPAS motor is coupled to the steering column and/or is otherwise column mounted. In some examples, the EPAS system **110** implements a rack EPAS system when the EPAS motor is coupled to the rack and/or is otherwise rack mounted. The EPAS motor provides powered assistance (e.g., power-assisted torque and/or power-assisted momentum) to a steering assembly of the vehicle **108** to increase the ease with which a portion of the steering assembly (e.g., a steering wheel) may be rotated and/or otherwise moved by the operator of the vehicle **108**. The degree and/or extent to which the EPAS motor provides such powered assistance to the steering assembly increases as the current to the EPAS motor is ramped in based on command(s), control signal(s), etc., generated by the EPAS controller **112**.

(22) In some examples, the EPAS controller **112** determines a first or baseline amount of powered assistance (e.g., an EPAS base assist, an EPAS base assist torque, an EPAS assistance torque, etc.) to deliver to the EPAS motor. For example, the EPAS controller **112** can determine the EPAS base assist and output a control signal to the EPAS motor to deliver the EPAS base assist. In such examples, the control signal causes a first torque to be applied to the EPAS motor.

(23) In some examples, the EPAS controller **112** determines a second or compliance compensation amount of powered assistance (e.g., an EPAS compliance assist) to deliver to the EPAS motor. For example, the EPAS controller **112** can determine that the EPAS base assist is insufficient due to mechanical stiffnesses present in the EPAS system **110**, and/or, more generally, the vehicle **108**. Advantageously, the EPAS controller **112** can boost and/or otherwise increase the EPAS base assist with the EPAS compliance assist to generate a final EPAS assist to be delivered to the EPAS motor.

(24) In some examples, the EPAS controller **112** determines the EPAS compliance assist based on measurements (e.g., sensor measurements), data (e.g., sensor data), etc., obtained from sensors monitoring the EPAS system **110**, and/or, more generally, the vehicle **108**. In such examples, the EPAS controller **112** can obtain the measurements from one(s) of the sensor(s), from one(s) of the ECU(s) **114**, etc., and/or a combination thereof. In this example, the ECU(s) **114** include(s) one or more ECUs. In this example, the ECU(s) **114** are hardware that may control different function(s), operation(s), etc., of the vehicle **108**. For example, a first one of the ECU(s) **114** can control an engine or electric motor of the vehicle **108**, a second one of the ECU(s) **114** can control a transmission of the vehicle **108**, etc.

(25) In some examples, the EPAS controller **112** obtains the sensor data including a column torque of the steering column (e.g., from a torque sensor), a motor velocity of the EPAS motor (e.g., from a speed sensor), a motor position of the EPAS motor (e.g., from a position sensor), a speed of the vehicle **108** (e.g., from a speed sensor, from the ECU(s) **114**, etc.), etc. In such examples, the EPAS controller **112** can determine a derivative of the column torque to determine a column torque derivative.

(26) In some examples, the EPAS controller **112** determines the EPAS compliance assist based on at least one of ones of the measurements or the column torque derivative. In some examples, the EPAS controller **112** outputs a control signal to the EPAS motor to deliver the final EPAS assist based on the EPAS base assist and the EPAS compliance assist. In such examples, the control signal can cause a second torque to be applied to the EPAS motor, which is greater than the first torque if only the EPAS base assist is applied. Advantageously, the EPAS controller **112** can dynamically determine the final EPAS assist to overcome mechanical compliance in the EPAS system **110**, and/or, more generally, the vehicle **108**.

(27) In the illustrated example of FIG. **1**, the EPAS controller **112**, the ECU(s) **114**, and/or, more generally, the vehicle system **102**, is/are in communication with the external computing system(s) **104** via the network **106**. In this example, the network **106** is the Internet. However, the network **106** may be implemented using any suitable wireless network(s) including, for example, one or more wireless data buses, one or more wireless Local Area Networks (WLANs), one or more cellular networks, one or more private networks, one or more public networks, etc. In this example,

the external computing system(s) **104** correspond(s) to, is/are representative of, and/or otherwise include(s) one or more computer servers, data facilities, cloud services (e.g., a public or private cloud provider, a cloud-based repository, etc.), etc.

(28) In some examples, the external computing system(s) **104** implement a software distribution platform that delivers, provides, and/or otherwise transmits machine readable instructions executable to the EPAS controller **112** and/or the ECU(s) **114**. For example, the external computing system(s) **104** can implement an over-the-air (OTA) firmware and/or software update of processor platform(s) included in the vehicle system **102**.

(29) In some examples, the external computing system(s) **104** determine(s) a firmware, software, and/or hardware version associated with the ECU(s) **114** and/or the EPAS controller **112**. In such examples, the external computing system(s) **104** can trigger and/or otherwise invoke an update of the firmware and/or software of the EPAS controller **112** and/or the ECU(s) **114**. In such examples, the machine readable instructions, when executed by the EPAS controller **112**, can cause the EPAS controller **112** to determine the EPAS base assist, the EPAS compliance assist, etc., to control the EPAS system **110**.

(30) FIG. 2 is an example rack EPAS system **200**. For example, the rack EPAS system **200** of FIG. 2 can implement the EPAS system **110** of FIG. 1. In this example, the rack EPAS system **200** includes the example EPAS controller **112** of FIG. 1, a first example steering wheel **202**, a first example EPAS motor **204**, an example coupling belt system **206**, a first example pinion **208**, a first example rack **210**, a first example wheel assembly **212**, a first example torque sensor **214**, and a first example steering column **216**. In this example, one or more of the first steering wheel **202**, the first EPAS motor **204**, the coupling belt system **206**, the first pinion **208**, the first rack **210**, the first wheel assembly **212**, the first torque sensor **214**, and/or the first steering column **216** defines a first steering system of the vehicle **108** of FIG. 1.

(31) In the illustrated example of FIG. 2, the first steering wheel **202** is coupled to first steering column **216**. The first steering column **216** is coupled to the first rack **210** through the first pinion **208**. The first rack **210** is coupled to the first wheel assembly **212**. The first rack **210** is coupled to the first EPAS motor **204** through the coupling belt system **206**. In this example, the coupling belt system **206** implements a pulley, a belt, a driven pulley, and a ball nut assembly (BNA). Alternatively, the coupling belt system **206** may be implemented using any other type of belt and/or pulley system.

(32) In this example, an operator can turn the first steering wheel **202**, which can cause the first steering column **216** and the first pinion **208** to turn. In this example, the turning of the first pinion **208** causes the first rack **210** to translate in a first direction or a second direction opposite the first direction to cause the first wheel assembly **212** and a second wheel assembly opposite the first wheel assembly **212** to turn in unison toward the first direction or the second direction.

(33) In this example, the first torque sensor **214** measures a torque (e.g., a steering wheel torque, a steering column torque, etc.) applied by an operator to the first steering wheel **202** and/or, more generally, the first steering column **216**. For example, the first torque sensor **214** can output torque data (e.g., steering wheel torque data, steering column torque data, etc.) representative of a sensed column torque, or a torque applied to the first steering column **216** via the first steering wheel **202**. In this example, the first torque sensor **214** outputs the torque data to the EPAS controller **112** and the first EPAS motor **204**. In this example, the EPAS controller **112** transmits control signal(s) to the first EPAS motor **204** to control operation of the first EPAS motor **204**.

(34) In this example, the EPAS controller **112** generates the control signal(s) based on at least one of the EPAS base assist or the EPAS compliance assist. For example, the EPAS controller **112** can generate and/or otherwise determine the control signal(s) to adjust a steering response of the rack EPAS system **200**. In such examples, the EPAS controller **112** can adjust an EPAS base assist torque with a compliance compensation torque to compensate for mechanical stiffness associated with at least one of the coupling belt system **206**, the first pinion **208**, or the first rack **210**.

Advantageously, the EPAS controller **112** can adjust the EPAS base assist (e.g., increase the EPAS base assist) of the rack EPAS system **200** to improve the provision of powered assistance to the first steering assembly of the vehicle **108**, drivability for the operator, and/or the level of customer (e.g., driver, operator, etc.) satisfaction associated with the experience of driving the vehicle **108**.

(35) FIG. **3** is an example column EPAS system **300**. For example, the column EPAS system **300** of FIG. **3** can implement the EPAS system **110** of FIG. **1**. In this example, the column EPAS system **300** includes the example EPAS controller **112** of FIG. **1**, a second example steering wheel **302**, a second example EPAS motor **304**, an example coupling gear **306**, a second example pinion **307**, a third example pinion **308**, a second example rack **310**, a second example wheel assembly **312**, a second example torque sensor **314**, and a second example steering column **316**. In this example, one or more of the second steering wheel **302**, the second EPAS motor **304**, the coupling gear **306**, the second pinion **307**, the third pinion **308**, the second rack **310**, the second wheel assembly **312**, the second torque sensor **314**, and/or the second steering column **316** defines a second steering assembly of the vehicle **108** of FIG. **1**.

(36) In the illustrated example of FIG. **3**, the second steering wheel **302** is coupled to second steering column **316**. The second steering column **316** is coupled to the second rack **310** through the third pinion **308**. The second rack **310** is coupled to the second wheel assembly **312**. The second steering wheel **302** is coupled to the second EPAS motor **304** through the coupling gear **306** and the second pinion **307**.

(37) In this example, an operator can turn the second steering wheel **302**, which can cause the second steering column **316** and the coupling gear **306** to turn. In this example, the turning of the coupling gear **306** causes the third pinion **308** to turn. In this example, the turning of the third pinion **308** can cause the second rack **310** to translate in a first direction or a second direction opposite the first direction to cause the second wheel assembly **312** and a third wheel assembly opposite the second wheel assembly **312** to turn in unison toward the first direction or the second direction.

(38) In this example, the second torque sensor **314** measures a torque (e.g., a steering wheel torque, a steering column torque, etc.) applied by an operator to the second steering wheel **302** and/or, more generally, the second steering column **316**. For example, the second torque sensor **314** can output torque data (e.g., steering wheel torque data, steering column torque data, etc.) representative of a sensed column torque, or a torque applied to the second steering column **316** via the second steering wheel **302**. In this example, the second torque sensor **314** outputs the torque data to the EPAS controller **112**. In this example, the EPAS controller **112** transmits control signal(s) to the second EPAS motor **304** to control operation of the second EPAS motor **304**. For example, the second EPAS motor **304** can rotate the second pinion **307** to provide torque assistance to the turning of the steering shaft through the coupling gear **306**.

(39) In this example, the EPAS controller **112** generates the control signal(s) based on at least one of the EPAS base assist or the EPAS compliance assist. For example, the EPAS controller **112** can generate and/or otherwise output the control signal(s) to adjust a steering response of the column EPAS system **300**. In such examples, the EPAS controller **112** can adjust an EPAS base assist torque with a compliance compensation torque to compensate for mechanical stiffness associated with at least one of the coupling gear **306**, the second pinion **307**, the third pinion **308**, or the second rack **310**. In some such examples, the EPAS controller **112** can adjust the steering response by adding the compliance compensation torque to an EPAS system of the vehicle **108** to enable an operator of the vehicle **108** to move and/or otherwise rotate a steering wheel, such as the first steering wheel **202** of FIG. **2** and/or the second steering wheel **302** of FIG. **3**, with increased ease compared to an example without adding the compliance compensation torque.

(40) Advantageously, the EPAS controller **112** can adjust the EPAS base assist (e.g., increase the EPAS base assist) of the column EPAS system **300** to improve the provision of powered assistance to the second steering assembly of the vehicle **108**, drivability for the operator, and/or the level of

customer (e.g., driver, operator, etc.) satisfaction associated with the experience of driving the vehicle **108**.

(41) FIG. **4** is a block diagram of an example system **400** including an example implementation of the EPAS controller **112** of FIG. **1**. In this example, the system **400** includes the external computing system(s) **104** of FIG. **1** and the network **106** of FIG. **1**. In this example, the EPAS controller **112** includes an example network interface **410**, an example sensor interface **420**, an example derivative determiner **430**, an example alternate approach determiner **440**, an example lookup table mapper **450**, an example compliance compensation torque determiner **460**, an example command generator **470**, an example datastore **480**, and an example bus (e.g., a data bus) **490**. In this example, the datastore **480** includes and/or otherwise stores example sensor data **482** and example lookup table(s) **484**.

(42) In the illustrated example of FIG. **4**, the EPAS controller **112** includes the network interface **410** to obtain information from and/or transmit information to the network **106**. For example, the network interface **410** can obtain information including the lookup table(s) **484**, executable(s), machine readable instructions, etc., from the external computing system(s) **104**. In such examples, the network interface **410** can implement a data format and/or protocol such as a HyperText Transfer Protocol (HTTP), an HTTP secure (HTTPS) protocol, a simple message transfer protocol (SMTP), etc.

(43) In the illustrated example of FIG. **4**, the EPAS controller **112** includes the sensor interface **420** to obtain information including the sensor data **482** from sensor(s) included in the vehicle **108** of FIG. **1**, the sensor data **482** from the ECU(s) **114** of FIG. **1**, etc. For example, the sensor interface **420** can obtain torque data from the first torque sensor **214** of FIG. **2**, the second torque sensor **314** of FIG. **3**, a vehicle speed from the ECU(s) **114**, etc.

(44) In some examples, the sensor interface **420** implements a bus server (e.g., a controller area network (CAN) bus link or data bus, an SAE J1939 link or data bus, etc.) that (i) receives the sensor data **482** from an the ECU(s) **114** or other device(s) communicatively coupled to the network **106** and/or (ii) transmits the sensor data **482** to the ECU(s) **114** or other device(s) communicatively coupled to the network **106**. In such examples, the sensor data **482** can have a data format and/or otherwise be based on a protocol such as a CANopen protocol, a CAN in Automation (CiA) protocol, a Society of Automotive Engineers (SAE) J1939 protocol, HTTP, HTTPS protocol, SMTP, etc.

(45) In the illustrated example of FIG. **4**, the EPAS controller **112** includes the derivative determiner **430** to calculate and/or otherwise determine a derivative of a function (e.g., a mathematical function). In some examples, the derivative determiner **430** can determinate the derivative of a function of a real variable to measure the sensitivity to change of the function value (e.g., the output value) with respect to a change in its argument (e.g., the input value). In such examples, the derivative determiner **430** can execute and/or otherwise implement a differentiation function on a function of interest (e.g., an EPAS base assist, column torque, motor velocity, motor position, and/or vehicle speed determination function(s)). In some examples, the derivative determiner **430** determines a derivative by applying a derivate filter on a measurement (e.g., a sensed column torque) to determine a measurement derivative (e.g., a sensed column torque derivative). For example, the derivative determiner **430** can determine a derivative of a sensed column torque to determine a sensed column torque derivative. In some examples, the derivative determiner **430** can determine a derivative of a position of the first EPAS motor **204** of FIG. **2** to determine a velocity of the first EPAS motor **204**.

(46) In the illustrated example of FIG. **4**, the EPAS controller **112** includes the alternate approach determiner **440** to determine whether to determine a velocity of an EPAS motor (e.g., a motor velocity), such as the first EPAS motor **204** or the second EPAS motor **304**, based on a measurement of the motor velocity from the EPAS motor or a derivative of a position of the EPAS motor (e.g., a motor position). For example, the alternate approach determiner **440** can determine to



determine the motor velocity based on the measurement in response to determining that the EPAS motor is outputting a valid measurement (e.g., a sensor measuring the velocity is responsive and/or otherwise functioning properly). In other examples, the alternate approach determiner **440** can determine to determine the motor velocity based on the derivative of the motor position in response to determining that the EPAS motor is not outputting a valid measurement (e.g., a sensor measuring the velocity is not responsive and/or otherwise not functioning properly).

(47) In the illustrated example of FIG. 4, the EPAS controller **112** includes the lookup table mapper **450** to map one or more values to one or more multidimensional performance maps, such as lookup tables (LUTs). In some examples, the lookup table mapper **450** maps at least one of a sensed column torque or a sensed column torque derivative to a first torque (e.g., a first torque value having units of measure in newton-meters (N.Math.m)) using a first two-dimensional (2-D) LUT. In some examples, the lookup table mapper **450** maps at least one of a motor velocity or a sensed motor position to a second torque (e.g., a second torque in N.Math.m) using a second 2-D LUT. In some examples, the lookup table mapper **450** maps a vehicle speed to a factor or value (e.g., a scale factor or value, a scaling factor or value, an adjusting factor or value, etc.) (e.g., a numerical factor or value in a range of 0 to 1) using a one-dimensional (1-D) LUT. In such examples, the lookup table(s) **484** stored in the datastore **480** can implement at least one of the first 2-D LUT, the second 2-D LUT, or the 1-D LUT.

(48) In the illustrated example of FIG. 4, the EPAS controller **112** includes the compliance compensation torque determiner **460** to determine a compliance compensation torque based on at least one of a sensed column torque, a sensed column torque derivative, a vehicle speed, a motor velocity, or a sensed motor position. For example, the compliance compensation torque determiner **460** can determine the compliance compensation torque based on at least one of the first torque, the second torque, or the scaling factor as determined by the lookup table mapper **450**. In such examples, the compliance compensation torque determiner **460** can determine a first portion of the compliance compensation torque based on a first multiplication of the first torque and the scaling factor. In some such examples, the compliance compensation torque determiner **460** can determine a second portion of the compliance compensation torque based on a second multiplication of the second torque and the scaling factor. In some such examples, the compliance compensation torque determiner **460** can determine the compliance compensation torque determiner **460** based on a sum of the first portion and the second portion.

(49) In the illustrated example of FIG. 4, the EPAS controller **112** includes the command generator **470** to output and/or otherwise generate control signal(s) to an EPAS motor, such as the first EPAS motor **204** of FIG. 2 and/or the second EPAS motor **304** of FIG. 3. In some examples, the command generator **470** implements the control signal(s) by outputting a current, a voltage, etc., that corresponds to a desired or intended output torque of the EPAS motor. In such examples, the command generator **470** can output the control signal(s) to command, direct, instruct, invoke, and/or otherwise cause the EPAS motor **204**, **304** to rotate at a desired or intended rotational speed to output a desired or intended torque.

(50) In some examples, the command generator **470** determines and/or generates a control signal to implement a final EPAS assist representative of a final EPAS assist torque to an EPAS motor. For example, the command generator **470** can determine the final EPAS assist torque based on an EPAS base assist torque and a compliance compensation torque. In such examples, the command generator **470** can determine the final EPAS assist torque based on a sum of the EPAS base assist torque and the compliance compensation torque.

(51) In the illustrated example of FIG. 4, the EPAS controller **112** includes the datastore **480** to store data (e.g., the sensor data **482**, the lookup table(s) **484**, etc.). In this example, the datastore **480** may be implemented by a volatile memory (e.g., a Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS® Dynamic Random Access Memory (RDRAM®), etc.) and/or a non-volatile memory (e.g., flash memory). The

example datastore **480** may additionally or alternatively be implemented by one or more double data rate (DDR) memories, such as DDR, DDR2, DDR3, DDR4, mobile DDR (mDDR), etc. The example datastore **480** may additionally or alternatively be implemented by one or more mass storage devices such as hard disk drive(s), compact disk (CD) drive(s), digital versatile disk (DVD) drive(s), solid-state disk drive(s), etc. While in the illustrated example the datastore **480** is illustrated as a single database, the datastore **480** may be implemented by any number and/or type(s) of databases. Furthermore, the data stored in the datastore **480** may be in any data format such as, for example, binary data, comma delimited data, tab delimited data, structured query language (SQL) structures, etc.

(52) In the illustrated example of FIG. **4**, the network interface **410**, the sensor interface **420**, the derivative determiner **430**, the alternate approach determiner **440**, the lookup table mapper **450**, the compliance compensation torque determiner **460**, the command generator **470**, and/or the datastore **480** are in communication with the bus **490**. For example, the bus **490** corresponds to, is representative of, and/or otherwise implements at least one of an Inter-Integrated Circuit (I2C) bus, a Serial Peripheral Interface (SPI) bus, a Peripheral Component Interconnect (PCI) bus, a CAN bus, an SAE J1939 bus, etc.

(53) While an example manner of implementing the EPAS controller **112** of FIGS. **1-3** is illustrated in FIG. **4**, one or more of the elements, processes and/or devices illustrated in FIG. **4** may be combined, divided, re-arranged, omitted, eliminated and/or implemented in any other way. Further, the example network interface **410**, the example sensor interface **420**, the example derivative determiner **430**, the example alternate approach determiner **440**, the example lookup table mapper **450**, the example compliance compensation torque determiner **460**, the example command generator **470**, the example datastore **480**, the example sensor data **482**, the example lookup table(s) **484**, the example bus **490**, and/or, more generally, the example EPAS controller **112** of FIGS. **1-3** may be implemented by hardware, software, firmware and/or any combination of hardware, software and/or firmware. Thus, for example, any of the example network interface **410**, the example sensor interface **420**, the example derivative determiner **430**, the example alternate approach determiner **440**, the example lookup table mapper **450**, the example compliance compensation torque determiner **460**, the example command generator **470**, the example datastore **480**, the example sensor data **482**, the example lookup table(s) **484**, the example bus **490**, and/or, more generally, the example EPAS controller **112** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), graphics processing unit(s) (GPU(s)), digital signal processor(s) (DSP(s)), application specific integrated circuit(s) (ASIC(s)), programmable logic device(s) (PLD(s)) and/or field programmable logic device(s) (FPLD(s)). When reading any of the apparatus or system claims of this patent to cover a purely software and/or firmware implementation, at least one of the example network interface **410**, the example sensor interface **420**, the example derivative determiner **430**, the example alternate approach determiner **440**, the example lookup table mapper **450**, the example compliance compensation torque determiner **460**, the example command generator **470**, the example datastore **480**, the example sensor data **482**, the example lookup table(s) **484**, and/or the example bus **490** is/are hereby expressly defined to include a non-transitory computer readable storage device or storage disk such as a memory, a DVD, a CD, a Blu-ray disk, etc. including the software and/or firmware. Further still, the example EPAS controller **112** of FIGS. **1-3** may include one or more elements, processes and/or devices in addition to, or instead of, those illustrated in FIG. **4**, and/or may include more than one of any or all of the illustrated elements, processes and devices. As used herein, the phrase “in communication,” including variations thereof, encompasses direct communication and/or indirect communication through one or more intermediary components, and does not require direct physical (e.g., wired) communication and/or constant communication, but rather additionally includes selective communication at periodic intervals, scheduled intervals, aperiodic intervals, and/or one-time events.

(54) FIG. 5 is a block diagram of example EPAS logic **500**. In this example, the EPAS logic **500** can implement the EPAS controller **112** of FIGS. 1, 2, 3, and/or 4. In some examples, the EPAS logic **500** is implemented by hardware, software, and/or firmware. For example, the EPAS logic **500** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), GPU(s), DSP(s), ASIC(s), PLD(s), and/or FPLD(s).

(55) In the illustrated example of FIG. 5, the EPAS logic **500** determines an example final EPAS assist **502** to be provided to an EPAS motor, such as the first EPAS motor **204** of FIG. 2 and/or the second EPAS motor **304** of FIG. 3, based on an example EPAS base assist **504** and an example compliance compensation torque **506**. In this example, the EPAS logic **500** determines a value of the EPAS base assist **504**. For example, the EPAS logic **500** can determine a torque value of the EPAS base assist **504** based on sensor measurement(s), such as a sensed column torque, a vehicle speed, etc., and/or a combination thereof. In some examples, the EPAS base assist **504** has a value in a range of 0 to 15 N.Math.m. Alternatively, the EPAS base assist **504** may have a different value and/or have a value in a different range.

(56) In this example, the EPAS logic **500** obtains measurement(s) of example sensed column torque **508**. For example, the EPAS logic **500** can obtain the measurement(s) of the sensed column torque **508** from a sensor, such as the first torque sensor **214** of FIG. 2 and/or the second torque sensor **314** of FIG. 3. In other examples, the EPAS logic **500** can obtain the measurement(s) of the sensed column torque **508** from an ECU via a bus, such as the bus **490** of FIG. 4. In some examples, the EPAS logic **500** implements the sensor interface **420** of FIG. 4 by obtaining the measurement(s) of the sensed column torque **508**.

(57) In the illustrated example of FIG. 5, the EPAS logic **500** obtains measurement(s) of example sensed motor velocity **510**, which is representative of a velocity of an EPAS motor, such as the first EPAS motor **204** and/or the second EPAS motor **304**. For example, the EPAS logic **500** can obtain the measurement(s) of the sensed motor velocity **510** from a speed sensor (e.g., a proximity switch, a quadrature sensor, etc.) monitoring the EPAS motor and/or, more generally, from the EPAS motor. In other examples, the EPAS logic **500** can obtain the measurement(s) of the sensed motor velocity **510** from an ECU via a bus, such as the bus **490** of FIG. 4. In some examples, the EPAS logic **500** implements the sensor interface **420** of FIG. 4 by obtaining the measurement(s) of the sensed motor velocity **510**.

(58) In this example, the EPAS logic **500** determines measurement(s) of example sensed motor position **512**, which is representative of a position of an EPAS motor, such as the first EPAS motor **204** and/or the second EPAS motor **304**. For example, the EPAS logic **500** can obtain the measurement(s) of the sensed motor position **512** from a position sensor (e.g., an encoder (e.g., a capacitive encoder, an optical encoder, a rotary encoder, etc.), a resolver, a Hall-effect device, etc.) monitoring the EPAS motor and/or, more generally, from the EPAS motor. In other examples, the EPAS logic **500** can obtain the measurement(s) of the sensed motor position **512** from an ECU via a bus, such as the bus **490** of FIG. 4. In some examples, the EPAS logic **500** implements the sensor interface **420** of FIG. 4 by obtaining the measurement(s) of the sensed motor position **512**.

(59) In the illustrated example of FIG. 5, the EPAS logic **500** obtains measurement(s) of example vehicle speed **514**, which can be representative of a speed of the vehicle **108** of FIG. 1. For example, the EPAS logic **500** can obtain the measurement(s) of the vehicle speed **514** from a speed sensor (e.g., a proximity switch, a quadrature sensor, etc.) monitoring an engine, a motor, etc., of the vehicle **108** and/or, more generally, the vehicle **108**. In other examples, the EPAS logic **500** can obtain the measurement(s) of the vehicle speed **514** from an ECU via a bus, such as the bus **490** of FIG. 4. In some examples, the EPAS logic **500** implements the sensor interface **420** of FIG. 4 by obtaining the measurement(s) of the vehicle speed **514**.

(60) In this example, the EPAS logic **500** includes example compliance compensation torque logic **516** to determine the compliance compensation torque **506**. In some examples, the compliance compensation torque logic **516** implements the lookup table mapper **450**, the compliance

compensation torque determiner **460**, and/or the lookup table(s) **484** of FIG. 4.

(61) In this example, the compliance compensation torque logic **516** obtains the sensed column torque **508**, the sensed motor position **512**, the vehicle speed **514**, an example sensed column torque derivative **518**, and example motor velocity **520** to determine the compliance compensation torque **506**. In this example, the EPAS logic **500** determines the sensed column torque derivative **516** by applying a first example derivative function **522** on the sensed column torque **508**. For example, the first derivative function **522** is implemented by a derivative filter of

$$(62) \frac{s}{s + 2 * * fd1} \cdot$$

In this example, the term fd1 is a first calibration factor (e.g., a first calibration scaling factor), a first calibration value, etc. In some examples, the fd1 is tunable and/or otherwise configurable (e.g., dynamically configurable). In such examples, the term fd1 can have a value in a range of 80 to 200. Alternatively, the term fd1 may have any other value and/or otherwise have a value in any other value range. In some examples, the term fd2 is static and/or otherwise predetermined, preprogrammed, preconfigured, etc. In some examples, the first derivative function **522** implements the derivative determiner **430** of FIG. 4.

(63) In the illustrated example of FIG. 5, the EPAS logic **500** determines the motor velocity **520** responsive to a determination by example alternate approach logic **524**. In this example, the alternate approach logic **524** is implemented by a switch. For example, the switch can be hardware implemented by a latch, a relay, a transistor, etc. In other examples, the switch can be implemented by firmware and/or software. In some examples, the alternate approach logic **524** switches to a first position to output the motor velocity **520** based on the sensed motor velocity **510**. For example, the alternate approach logic **524** can determine to output the sensed motor velocity **510** as the motor velocity **520** in response to determining that the sensed motor velocity **510** is valid and/or is otherwise received from a sensor that is responsive, functioning properly or as expected, etc.

(64) In some examples, the alternate approach logic **524** switches to a second position to output the motor velocity **520** based on a derivative of the sensed motor position **512**, (e.g., a sensed motor position derivative). For example, the alternate approach logic **524** can determine to output the sensed motor position derivative as the motor velocity **520** in response to determining that the sensed motor velocity **510** is not valid and/or is otherwise received from a sensor that is not responsive, functioning improperly or not as expected (e.g., a damaged or broken sensor), etc. In such examples, a second example derivative function **523** can determine the motor velocity **520** based on the sensed motor position **512**. In some examples, the alternate approach logic **524** implements the alternate approach determiner **440** of FIG. 4.

(65) In this example, the EPAS logic **500** can determine the motor velocity **520** via the alternate approach logic **524** by applying a second example derivative function **523** on the sensed motor position **512**. For example, the second derivative function **523** is implemented by a derivative filter of

$$(66) \frac{s}{s + 2 * * fd2} \cdot$$

In this example, the term fd2 is a second calibration factor (e.g., a second calibration scaling factor), a second calibration value, etc. In some examples, the fd2 is tunable and/or otherwise configurable (e.g., dynamically configurable). In such examples, the term fd2 can have a value in a range of 80 to 200. Alternatively, the term fd2 may have any other value and/or otherwise have a value in any other value range. In some examples, the term fd2 is static and/or otherwise predetermined, preprogrammed, preconfigured, etc. In some examples, the second derivative function **523** implements the derivative determiner **430** of FIG. 4. In some examples, the first calibration factor is the same as the second calibration factor. Alternatively, the first calibration factor may be different from the second calibration factor.

(67) In some examples, the compliance compensation torque logic **516** determines the compliance compensation torque **506** by applying one or more inputs to the compliance compensation torque **506** to one or more lookup tables. For example, the compliance compensation torque logic **516** can

determine a value of the compliance compensation torque **506** to be in a range of 0 to 3 N.Math.m. Alternatively, the compliance compensation torque logic **516** may have a different value and/or have a value in a different range. In such examples, the compliance compensation torque **506** is less than the EPAS base assist **504**.

(68) In the example of FIG. 5, the compliance compensation torque logic **516** outputs the compliance compensation torque **506** to example final EPAS assist determination logic **526**. For example, the final EPAS assist determination logic **526** can determine and/or otherwise output the final EPAS assist **502** based on a sum of the EPAS base assist **504** and the compliance compensation torque **506**. In such examples, the final EPAS assist determination logic **526** can determine the final EPAS assist **502** to be 7.5 N.Math.m based on a sum of 6 N.Math.m for the EPAS base assist **504** and 1.5 N.Math.m for the compliance compensation torque **506**. In some examples, the final EPAS assist determination logic **526** implements the command generator **470** of FIG. 4. For example, the final EPAS assist determination logic **526** can generate and/or otherwise output a command to the EPAS motor **204**, **304** of FIGS. 2 and/or 3 representative of delivering 7.5 N.Math.m of torque to the system **200**, **300** of FIGS. 2 and/or 3.

(69) FIG. 6 is a block diagram of an example implementation of the compliance compensation torque logic **516** of FIG. 5. In some examples, the compliance compensation torque logic **516** is implemented by hardware, software, and/or firmware. For example, the compliance compensation torque logic **516** could be implemented by one or more analog or digital circuit(s), logic circuits, programmable processor(s), programmable controller(s), GPU(s), DSP(s), ASIC(s), PLD(s), and/or FPLD(s).

(70) In the illustrated example of FIG. 6, the compliance compensation torque logic **516** includes a first example LUT **602**, a second example LUT **604**, a third example LUT **606**, first example multiplication logic **608**, second example multiplication logic **610**, and example sum logic **612**. In this example, the first LUT **602** is a 2-D LUT that maps the sensed column torque **508** and the sensed column torque derivative **518** of FIG. 5 to a first example torque value **614**. In this example, the second LUT **604** is a 2-D LUT that maps the sensed motor position **512** and the motor velocity **520** of FIG. 5 to a second example torque value **616**. In this example, the third LUT **606** is a 1-D LUT that maps the vehicle speed **514** of FIG. 5 to an example scaling factor **618**. For example, the scaling factor **618** can be a value in a range of 0 to 1. Alternatively, the scaling factor **618** may be a value in any other range.

(71) In this example, the first multiplication logic **608** determines and/or otherwise outputs a first example adjusted torque value **620** based on a multiplication of the first torque value **614** from the first LUT **602** and the scaling factor **618** from the third LUT **606**. In this example, the second multiplication logic **610** determines and/or otherwise outputs a second example adjusted torque value **622** based on a multiplication of the second torque value **616** from the second LUT **604** and the scaling factor **618** from the third LUT **606**. In this example, the sum logic **612** determines and/or otherwise outputs the compliance compensation torque **506** based on a sum of the first adjusted torque value **620** and the second adjusted torque value **622**. Advantageously, the compliance compensation torque logic **516** can output the compliance compensation torque **506** to be used to adjust and/or otherwise modify the EPAS base assist **504** of FIG. 5 to compensate for mechanical stiffness in the rack EPAS system **200** of FIG. 2 and/or the column EPAS system **300** of FIG. 3.

(72) Flowcharts representative of example hardware logic, machine readable instructions, hardware implemented state machines, and/or any combination thereof for implementing the EPAS controller **112** of FIGS. 1-4 and/or the EPAS logic **500** of FIG. 5 are shown in FIGS. 7-8. The machine readable instructions may be one or more executable programs or portion(s) of an executable program for execution by a computer processor and/or processor circuitry, such as the processor **912** shown in the example processor platform **900** discussed below in connection with FIG. 9. The program may be embodied in software stored on a non-transitory computer readable storage

medium such as a CD-ROM, a floppy disk, a hard drive, a DVD, a Blu-ray disk, or a memory associated with the processor **912**, but the entire program and/or parts thereof could alternatively be executed by a device other than the processor **912** and/or embodied in firmware or dedicated hardware. Further, although the example program is described with reference to the flowcharts illustrated in FIGS. **7-8**, many other methods of implementing the example EPAS controller **112** and/or the EPAS logic **500** may alternatively be used. For example, the order of execution of the blocks may be changed, and/or some of the blocks described may be changed, eliminated, or combined. Additionally or alternatively, any or all of the blocks may be implemented by one or more hardware circuits (e.g., discrete and/or integrated analog and/or digital circuitry, an FPGA, an ASIC, a comparator, an operational-amplifier (op-amp), a logic circuit, etc.) structured to perform the corresponding operation without executing software or firmware. The processor circuitry may be distributed in different network locations and/or local to one or more devices (e.g., a multi-core processor in a single machine, multiple processors distributed across a server rack, etc.).

(73) The machine readable instructions described herein may be stored in one or more of a compressed format, an encrypted format, a fragmented format, a compiled format, an executable format, a packaged format, etc. Machine readable instructions as described herein may be stored as data or a data structure (e.g., portions of instructions, code, representations of code, etc.) that may be utilized to create, manufacture, and/or produce machine executable instructions. For example, the machine readable instructions may be fragmented and stored on one or more storage devices and/or computing devices (e.g., servers) located at the same or different locations of a network or collection of networks (e.g., in the cloud, in edge devices, etc.). The machine readable instructions may require one or more of installation, modification, adaptation, updating, combining, supplementing, configuring, decryption, decompression, unpacking, distribution, reassignment, compilation, etc., in order to make them directly readable, interpretable, and/or executable by a computing device and/or other machine. For example, the machine readable instructions may be stored in multiple parts, which are individually compressed, encrypted, and stored on separate computing devices, wherein the parts when decrypted, decompressed, and combined form a set of executable instructions that implement one or more functions that may together form a program such as that described herein.

(74) In another example, the machine readable instructions may be stored in a state in which they may be read by processor circuitry, but require addition of a library (e.g., a dynamic link library (DLL)), a software development kit (SDK), an application programming interface (API), etc. in order to execute the instructions on a particular computing device or other device. In another example, the machine readable instructions may need to be configured (e.g., settings stored, data input, network addresses recorded, etc.) before the machine readable instructions and/or the corresponding program(s) can be executed in whole or in part. Thus, machine readable media, as used herein, may include machine readable instructions and/or program(s) regardless of the particular format or state of the machine readable instructions and/or program(s) when stored or otherwise at rest or in transit.

(75) The machine readable instructions described herein can be represented by any past, present, or future instruction language, scripting language, programming language, etc. For example, the machine readable instructions may be represented using any of the following languages: C, C++, Java, C#, Perl, Python, JavaScript, HyperText Markup Language (HTML), Structured Query Language (SQL), Swift, etc.

(76) As mentioned above, the example processes of FIGS. **7-8** may be implemented using executable instructions (e.g., computer and/or machine readable instructions) stored on a non-transitory computer and/or machine readable medium such as a hard disk drive, a flash memory, a read-only memory, a compact disk, a digital versatile disk, a cache, a random-access memory and/or any other storage device or storage disk in which information is stored for any duration (e.g., for extended time periods, permanently, for brief instances, for temporarily buffering, and/or

for caching of the information). As used herein, the term non-transitory computer readable medium is expressly defined to include any type of computer readable storage device and/or storage disk and to exclude propagating signals and to exclude transmission media.

(77) “Including” and “comprising” (and all forms and tenses thereof) are used herein to be open ended terms. Thus, whenever a claim employs any form of “include” or “comprise” (e.g., comprises, includes, comprising, including, having, etc.) as a preamble or within a claim recitation of any kind, it is to be understood that additional elements, terms, etc., may be present without falling outside the scope of the corresponding claim or recitation. As used herein, when the phrase “at least” is used as the transition term in, for example, a preamble of a claim, it is open-ended in the same manner as the term “comprising” and “including” are open ended. The term “and/or” when used, for example, in a form such as A, B, and/or C refers to any combination or subset of A, B, C such as (1) A alone, (2) B alone, (3) C alone, (4) A with B, (5) A with C, (6) B with C, and (7) A with B and with C. As used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing structures, components, items, objects and/or things, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. As used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A and B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B. Similarly, as used herein in the context of describing the performance or execution of processes, instructions, actions, activities and/or steps, the phrase “at least one of A or B” is intended to refer to implementations including any of (1) at least one A, (2) at least one B, and (3) at least one A and at least one B.

(78) As used herein, singular references (e.g., “a”, “an”, “first”, “second”, etc.) do not exclude a plurality. The term “a” or “an” entity, as used herein, refers to one or more of that entity. The terms “a” (or “an”), “one or more”, and “at least one” can be used interchangeably herein. Furthermore, although individually listed, a plurality of means, elements or method actions may be implemented by, e.g., a single unit or processor. Additionally, although individual features may be included in different examples or claims, these may possibly be combined, and the inclusion in different examples or claims does not imply that a combination of features is not feasible and/or advantageous.

(79) FIG. 7 is a flowchart representative of example machine readable instructions **700** that may be executed to implement the example EPAS controller **112** of FIGS. 1-4 and/or the EPAS logic **500** of FIG. 5 to adjust an example steering response of the rack EPAS system **200** of FIG. 2, the column EPAS system **300** of FIG. 3, and/or, more generally, the vehicle **108** of FIG. 1. The machine readable instructions **700** of FIG. 7 begin at block **702**, at which the EPAS controller **112** and/or the EPAS logic **500** determine a steering column torque associated with a steering column of an electric power assisted steering system (EPAS) in a vehicle. For example, the sensor interface **420** (FIG. 4) can obtain the steering column torque from the first torque sensor **214** of FIG. 2 and/or the second torque sensor **314** of FIG. 3. In such examples, the sensor interface **420** can store the steering column torque in the datastore **480** (FIG. 4) as the sensor data **482** (FIG. 4).

(80) At block **704**, the EPAS controller **112** and/or the EPAS logic **500** determine a steering column torque derivative based on the steering column torque. For example, the derivative determiner **430** (FIG. 4) can execute a derivative function on the steering column torque to determine a steering column torque derivative. In other examples, the first derivative function **522** (FIG. 5) can output the sensed column torque derivative **518** (FIG. 5) based on the sensed column torque **508** (FIG. 5).

(81) At block **706**, the EPAS controller **112** and/or the EPAS logic **500** determine a motor velocity. For example, the alternate approach determiner **440** (FIG. 4) can determine the motor velocity of

the vehicle **108** based on a sensed motor velocity or a derivative of the sensed motor velocity. In other examples, the alternate approach logic **524** (FIG. 5) can determine the motor velocity **520** (FIG. 5) based on the sensed motor velocity **510** (FIG. 5) or a derivative of the sensed motor position **512** (FIG. 5).

(82) At block **708**, the EPAS controller **112** and/or the EPAS logic **500** determine the motor position. For example, the sensor interface **420** can obtain the motor position from a sensor monitoring the first EPAS motor **204** and/or the second EPAS motor **304**. In such examples, the sensor interface **420** can store the motor position in the datastore **480** as the sensor data **482**.

(83) At block **710**, the EPAS controller **112** and/or the EPAS logic **500** determine the vehicle speed. For example, the sensor interface **420** can obtain the vehicle speed from a sensor monitoring an engine, a motor, etc., of the vehicle **108**. In such examples, the sensor interface **420** can store the vehicle speed in the datastore **480** as the sensor data **482**.

(84) At block **712**, the EPAS controller **112** and/or the EPAS logic **500** determine a compliance compensation torque. For example, the compliance compensation torque determiner **460** (FIG. 4) can determine a compliance compensation torque to overcome and/or otherwise compensate for mechanical compliance in the rack EPAS system **200** and/or the column EPAS system **300**. In other examples, the compliance compensation torque logic **516** (FIG. 5) can output the compliance compensation torque **506** (FIG. 5). An example process that may be executed to implement block **712** is described below in connection with FIG. 8.

(85) At block **714**, the EPAS controller **112** and/or the EPAS logic **500** determine an EPAS assist torque based on an EPAS base assist torque and the compliance compensation torque. For example, the command generator **470** (FIG. 4) can output a torque, such as a final EPAS assist torque, to the first EPAS motor **204** and/or the second EPAS motor **304**, based on the compliance compensation torque.

(86) At block **716**, the EPAS controller **112** and/or the EPAS logic **500** adjusts a steering response of the steering column based on the EPAS base assist torque. For example, the command generator **470** can output control signal(s) representative of the final EPAS assist torque to the first EPAS motor **204** to adjust the steering response of the first steering column **216**, the first steering wheel **202**, etc., of FIG. 2. In other examples, the final EPAS assist determination logic **526** (FIG. 5) can output control signal(s) representative of the final EPAS assist **502** to the second EPAS motor **304** to adjust the steering response of the second steering column **316**, the second steering wheel **302**, etc., of FIG. 3. In response to adjusting a steering response of the steering column based on the EPAS base assist torque at block **716**, the machine readable instructions **700** of FIG. 7 conclude.

(87) FIG. 8 is a flowchart representative of example machine readable instructions **800** that may be executed to implement the example EPAS controller **112** of FIGS. 1-4 and/or the EPAS logic **500** of FIG. 5 to determine an example compliance compensation torque. In some examples, the machine readable instructions **800** of FIG. 8 are executed to implement block **712** of the machine readable instructions **700** of FIG. 7. The machine readable instructions **800** of FIG. 8 begin at block **802**, at which the EPAS controller **112** and/or the EPAS logic **500** determine a first torque based on mapping of column torque and column torque derivative to first lookup table. For example, the lookup table mapper **450** (FIG. 4) can map a measurement of column torque and a derivative of the measure to a first torque value using one of the lookup table(s) **484** (FIG. 4). In other examples, the compliance compensation torque logic **516** (FIG. 5) can map the sensed column torque **508** (FIGS. 5-6) and the sensed column torque derivative **518** (FIGS. 5-6) to the first torque value **614** (FIG. 6) using the first lookup table **602** (FIG. 6).

(88) At block **804**, the EPAS controller **112** and/or the EPAS logic **500** determine a second torque based on a mapping of motor velocity and motor position to a second lookup table. For example, the lookup table mapper **450** can map a measurement of motor velocity and either (1) a measurement of motor position or (2) a derivative of the measurement of motor velocity to a second torque value using one of the lookup table(s) **484**. In other examples, the compliance



compensation torque logic **516** can map the motor velocity **520** (FIGS. 5-6) and the sensed motor position **512** (FIGS. 5-6) to the second torque value **616** (FIG. 6) using the second lookup table **604** (FIG. 6).

(89) At block **806**, the EPAS controller **112** and/or the EPAS logic **500** adjust the first torque based on vehicle speed to determine an adjusted first torque. For example, the compliance compensation torque determiner **460** (FIG. 4) can map a measurement of the speed of the vehicle **108** of FIG. 1 to a scaling factor using one of the lookup table(s) **484**. In such examples, the compliance compensation torque determiner **460** can adjust the first torque value with the scaling factor to determine an adjusted first torque value. In other examples, the compliance compensation torque logic **516** can map the vehicle speed **514** (FIGS. 5-6) to the scaling factor **618** (FIG. 6) with the third lookup table **606** (FIG. 6). In such examples, the compliance compensation torque logic **516** can invoke the first multiplication logic **608** (FIG. 6) to multiply the first torque value **614** and the scaling factor **618** to calculate and/or otherwise determine the first adjusted torque value **620**.

(90) At block **808**, the EPAS controller **112** and/or the EPAS logic **500** adjust the second torque based on vehicle speed to determine an adjusted second torque. For example, the compliance compensation torque determiner **460** can map a measurement of the speed of the vehicle **108** of FIG. 1 to a scaling factor using one of the lookup table(s) **484**. In such examples, the compliance compensation torque determiner **460** can adjust the second torque value with the scaling factor to determine an adjusted second torque value. In other examples, the compliance compensation torque logic **516** can map the vehicle speed **514** to the scaling factor **618** with the third lookup table **606**. In such examples, the compliance compensation torque logic **516** can invoke the second multiplication logic **610** (FIG. 6) to multiply the second torque value **616** and the scaling factor **618** to calculate and/or otherwise determine the second adjusted torque value **622**.

(91) At block **810**, the EPAS controller **112** and/or the EPAS logic **500** determine a compliance compensation torque based on a sum of the adjusted first and second torques. For example, the compliance compensation torque determiner **460** can determine a compliance compensation torque (e.g., an EPAS compliance compensation torque assist) based on a sum of the first adjusted torque and the second adjusted torque. In other examples, the compliance compensation torque logic **516** can invoke the sum logic **612** to calculate the compliance compensation torque **506** (FIGS. 5-6) based on a sum of the first adjusted torque value **620** and the second adjusted torque value **622**. In response to determining the compliance compensation torque based on the sum of the adjusted first and second torques, control returns to block **714** of the machine readable instructions **700** of FIG. 7 to determine an EPAS assist torque based on an EPAS base assist torque and the compliance compensation torque.

(92) FIG. 9 is a block diagram of an example processor platform **900** structured to execute the instructions of FIGS. 7-8 to implement the EPAS controller **112** of FIGS. 1-4 and/or the EPAS logic **500** of FIG. 5. The processor platform **900** can be, for example, an ECU (e.g., an automotive or vehicle ECU), a self-learning machine (e.g., a neural network), or any other type of computing device.

(93) The processor platform **900** of the illustrated example includes a processor **912**. The processor **912** of the illustrated example is hardware. For example, the processor **912** can be implemented by one or more integrated circuits, logic circuits, microprocessors, GPUs, DSPs, or controllers from any desired family or manufacturer. The hardware processor may be a semiconductor based (e.g., silicon based) device. In this example, the processor **912** implements the example derivative determiner **430**, the example alternate approach determiner **440**, the example lookup table mapper **450**, the example compliance compensation torque determiner **460**, and the example command generator **470** of FIG. 4. In this example, the alternate approach determiner **440** is represented as “ALT APPROACH DETERMINER” and the compliance compensation torque determiner **460** is represented as “CC TORQUE DETERMINER.”

(94) The processor **912** of the illustrated example includes a local memory **913** (e.g., a cache). The

processor **912** of the illustrated example is in communication with a main memory including a volatile memory **914** and a non-volatile memory **916** via a bus **918**. In some examples, the bus **918** implements the example bus **490** of FIG. 4. The volatile memory **914** may be implemented by SDRAM, DRAM, RDRAM®, and/or any other type of random access memory device. The non-volatile memory **916** may be implemented by flash memory and/or any other desired type of memory device. Access to the main memory **914**, **916** is controlled by a memory controller.

(95) The processor platform **900** of the illustrated example also includes an interface circuit **920**. The interface circuit **920** may be implemented by any type of interface standard, such as an Ethernet interface, a universal serial bus (USB), a Bluetooth® interface, a near field communication (NFC) interface, and/or a PCI express interface. In this example, the interface circuit **920** implements the example network interface **410** and the example sensor interface **420** of FIG. 4.

(96) In the illustrated example, one or more input devices **922** are connected to the interface circuit **920**. The input device(s) **922** permit(s) a user to enter data and/or commands into the processor **912**. The input device(s) can be implemented by, for example, an audio sensor, a microphone, a camera (still or video), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, an isopoint device, and/or a voice recognition system.

(97) One or more output devices **924** are also connected to the interface circuit **920** of the illustrated example. The output devices **924** can be implemented, for example, by display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display (LCD), an in-place switching (IPS) display, a touchscreen, etc.), a tactile output device, a printer and/or speaker. The interface circuit **920** of the illustrated example, thus, typically includes a graphics driver card, a graphics driver chip and/or a graphics driver processor.

(98) The interface circuit **920** of the illustrated example also includes a communication device such as a transmitter, a receiver, a transceiver, a modem, a residential gateway, a wireless access point, a protocol gateway (e.g., an industrial protocol gateway), and/or a network interface to facilitate exchange of data with external machines (e.g., computing devices of any kind) via a network **926**. For example, the network **926** of FIG. 9 can implement the network **106** of FIG. 1. The communication can be via, for example, an Ethernet connection, a digital subscriber line (DSL) connection, a telephone line connection, a coaxial cable system, a satellite system, a line-of-site wireless system, a cellular telephone system, etc.

(99) The processor platform **900** of the illustrated example also includes one or more mass storage devices **928** for storing software and/or data. Examples of such mass storage devices **928** include floppy disk drives, hard drive disks, compact disk drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, and DVD drives. In this example, the one or more mass storage devices **928** implement the example datastore **480** of FIG. 4, which stores the example sensor data **482** and the example lookup tables **484** of FIG. 4.

(100) The machine executable instructions **932** of FIGS. 7-8 may be stored in the mass storage device **928**, in the volatile memory **914**, in the non-volatile memory **916**, and/or on a removable non-transitory computer readable storage medium such as a CD or DVD.

(101) A block diagram illustrating an example software distribution platform **1005** to distribute software such as the example computer readable instructions **932** of FIG. 9 to third parties is illustrated in FIG. 10. The example software distribution platform **1005** may be implemented by any computer server, data facility, cloud service, etc., capable of storing and transmitting software to other computing devices. The third parties may be customers of the entity owning and/or operating the software distribution platform. For example, the entity that owns and/or operates the software distribution platform may be a developer, a seller, and/or a licensor of software such as the example computer readable instructions **932** of FIG. 9. The third parties may be consumers, users, retailers (e.g., a car dealership, a vehicle repair facility, etc.), OEMs (e.g., a vehicle manufacturer, a vehicle service or part supplier, etc.), etc., who purchase and/or license the software for use and/or

re-sale and/or sub-licensing. In the illustrated example, the software distribution platform **1005** includes one or more servers and one or more storage devices. The storage devices store the computer readable instructions **932**, which may correspond to the example computer readable instructions **700, 800** of FIGS. **7-8**, as described above. The one or more servers of the example software distribution platform **1005** are in communication with a network **1010**, which may correspond to any one or more of the Internet and/or any of the example networks **106, 926** described above. In some examples, the one or more servers are responsive to requests to transmit the software to a requesting party as part of a commercial transaction. Payment for the delivery, sale and/or license of the software may be handled by the one or more servers of the software distribution platform and/or via a third party payment entity. The servers enable purchasers and/or licensors to download the computer readable instructions **932** from the software distribution platform **1005**. For example, the software, which may correspond to the example computer readable instructions **700, 800** of FIGS. **7-8**, may be downloaded to the example processor platform **900**, which is to execute the computer readable instructions **932** to implement the EPAS controller **112** of FIGS. **1-4** and/or the EPAS logic **500** of FIG. **5**. In some example, one or more servers of the software distribution platform **1005** periodically offer, transmit, and/or force updates to the software (e.g., the example computer readable instructions **932** of FIG. **9**) to ensure improvements, patches, updates, etc. are distributed and applied to the software at the end user devices.

(102) From the foregoing, it will be appreciated that example systems, methods, apparatus, and articles of manufacture have been disclosed that improve EPAS in a vehicle. The disclosed systems, methods, apparatus, and articles of manufacture modify an EPAS base torque to aide an EPAS motor to overcome mechanical compliance and improve the degradation in the on-center feel response associated with a steering wheel of the vehicle. Advantageously, the disclosed systems, methods, apparatus, and articles of manufacture offer a performance benefit over conventional EPAS systems that rely upon the EBAS base torque for purposes of providing an EPAS assist to an operator of the vehicle. As a result of the aforementioned advantages and/or benefits, the disclosed systems, methods, apparatus, and articles of manufacture improve the provision of powered assistance to the steering assembly of the vehicle, improves drivability for the operator, and improves the level of customer (e.g., driver, operator, etc.) satisfaction associated with the experience of driving the vehicle.

(103) Example methods, apparatus, systems, and articles of manufacture to improve EPAS in a vehicle are disclosed herein. Further examples and combinations thereof include the following:

(104) Example 1 includes an apparatus comprising memory, and a processor to execute instructions to determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determine a steering column torque derivative based on a derivative of the steering column torque, determine a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjust a steering response of the steering column based on the compliance compensation torque.

(105) Example 2 includes the apparatus of example 1, wherein the EPAS system is a column EPAS system or a rack EPAS system, and the processor is to obtain the steering column torque from a sensor of the column EPAS system or the rack EPAS system.

(106) Example 3 includes the apparatus of example 1, wherein the processor is to increase a first EPAS assistance torque by the compliance compensation torque to generate a second EPAS assistance torque, and deliver the second EPAS assistance torque to a motor of the EPAS system, the steering response adjusted in response to the delivering of the second EPAS assistance torque.

(107) Example 4 includes the apparatus of example 1, wherein the processor is to determine a position of a motor included in the EPAS system, and determine a velocity of the motor based on (i) a derivative of the position of the motor or (ii) sensor data from a sensor measuring the velocity of the motor.

(108) Example 5 includes the apparatus of example 1, wherein the processor is to determine a value

based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table, and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(109) Example 6 includes the apparatus of example 1, wherein the processor is to determine a value based on a mapping of (i) a velocity of a motor included in the EPAS system and (ii) a position of the motor to the value in a lookup table, and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(110) Example 7 includes the apparatus of example 1, wherein the processor is to determine a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the first value in a first lookup table, determine a first adjusted value based on a first multiplication of the first value and a speed of the vehicle, determine a second value based on a second mapping of (iii) a velocity of a motor included in the EPAS system and (iv) a position of the motor to the second value in a second lookup table, determine a second adjusted value based on a second multiplication of the second value and the speed of the vehicle, and determine a sum of the first adjusted value and the second adjusted value, the compliance compensation torque based on the sum.

(111) Example 8 includes a non-transitory computer readable storage medium comprising instructions that, when executed, cause a machine to at least determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determine a steering column torque derivative based on a derivative of the steering column torque, determine a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjust a steering response of the steering column based on the compliance compensation torque.

(112) Example 9 includes the non-transitory computer readable storage medium of example 8, wherein the EPAS system is a column EPAS system or a rack EPAS system, and the instructions, when executed, cause the machine to obtain the steering column torque from a sensor of the column EPAS system or the rack EPAS system.

(113) Example 10 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the machine to increase a first EPAS assistance torque by the compliance compensation torque to generate a second EPAS assistance torque, and deliver the second EPAS assistance torque to a motor of the EPAS system, the steering response adjusted in response to the delivering of the second EPAS assistance torque.

(114) Example 11 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the machine to determine a position of a motor included in the EPAS system, and determine a velocity of the motor based on (i) a derivative of the position of the motor or (ii) sensor data from a sensor measuring the velocity of the motor.

(115) Example 12 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the machine to determine a value based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table, and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(116) Example 13 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the machine to determine a value based on a mapping of (i) a velocity of a motor included in the EPAS system and (ii) a position of the motor to the value in a lookup table, and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(117) Example 14 includes the non-transitory computer readable storage medium of example 8, wherein the instructions, when executed, cause the machine to determine a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the

first value in a first lookup table, determine a first adjusted value based on a first multiplication of the first value and a speed of the vehicle, determine a second value based on a second mapping of (iii) a velocity of a motor included in the EPAS system and (iv) a position of the motor to the second value in a second lookup table, determine a second adjusted value based on a second multiplication of the second value and the speed of the vehicle, and determine a sum of the first adjusted value and the second adjusted value, the compliance compensation torque based on the sum.

(118) Example 15 includes a method comprising determining a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, determining a steering column torque derivative based on a derivative of the steering column torque, determining a compliance compensation torque based on the steering column torque and the steering column torque derivative, and adjusting a steering response of the steering column based on the compliance compensation torque.

(119) Example 16 includes the method of example 15, wherein adjusting the steering response includes increasing a first EPAS assistance torque by the compliance compensation torque to generate a second EPAS assistance torque, and delivering the second EPAS assistance torque to a motor of the EPAS system.

(120) Example 17 includes the method of example 15, further including determining a position of a motor included in the EPAS system, and determining a velocity of the motor based on (i) a derivative of the position of the motor or (ii) sensor data from a sensor measuring the velocity of the motor.

(121) Example 18 includes the method of example 15, further including determining a value based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table, and determining an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(122) Example 19 includes the method of example 15, further including determining a value based on a mapping of (i) a velocity of a motor included in the EPAS system and (ii) a position of the motor to the value in a lookup table, and determining an adjusted value based on a multiplication of the value and a speed of the vehicle, the compliance compensation torque based on the adjusted value.

(123) Example 20 includes the method of example 15, further including determining a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the first value in a first lookup table, determining a first adjusted value based on a first multiplication of the first value and a speed of the vehicle, determining a second value based on a second mapping of (iii) a velocity of a motor included in the EPAS system and (iv) a position of the motor to the second value in a second lookup table, determining a second adjusted value based on a second multiplication of the second value and the speed of the vehicle, and determining a sum of the first adjusted value and the second adjusted value, the compliance compensation torque based on the sum.

(124) Although certain example systems, methods, apparatus, and articles of manufacture have been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all systems, methods, apparatus, and articles of manufacture fairly falling within the scope of the claims of this patent.

(125) The following claims are hereby incorporated into this Detailed Description by this reference, with each claim standing on its own as a separate embodiment of the present disclosure.

## Claims

1. An apparatus comprising: memory; and a processor configured to: determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in

a vehicle, the steering column torque having a first torque direction that causes a wheel of the vehicle to turn in a first direction; determine a position of a motor included in the EPAS system based on first sensor data from a motor position sensor; determine whether a motor velocity sensor is functioning properly; after determining the motor velocity sensor is not functioning properly, determine a velocity of the motor based on a derivative of the position of the motor; after determining the motor velocity sensor is functioning properly, determine the velocity of the motor based on second sensor data from the motor velocity sensor; determine a steering column torque derivative by calculating a derivative of the steering column torque; determine a compliance compensation torque based on the steering column torque and the steering column torque derivative; and adjust a steering response of the steering column by applying the compliance compensation torque via the EPAS system, the compliance compensation torque having the first torque direction or a second torque direction that causes the wheel of the vehicle to turn in the first direction, application of the compliance compensation torque overcoming a resistance to torque associated with the EPAS system.

2. The apparatus of claim 1, wherein the EPAS system is a column EPAS system or a rack EPAS system, and the processor is configured to obtain the steering column torque from a sensor of the column EPAS system or the rack EPAS system.

3. The apparatus of claim 1, wherein the processor is configured to: generate a second EPAS assistance torque by increasing a first EPAS assistance torque by the compliance compensation torque; and deliver the second EPAS assistance torque to the motor of the EPAS system, the steering response adjusted in response to the delivering of the second EPAS assistance torque.

4. The apparatus of claim 1, wherein the processor is configured to: determine a value based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table; and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

5. The apparatus of claim 1, wherein the processor is configured to: determine a value based on a mapping of (i) the velocity of the motor included in the EPAS system and (ii) the position of the motor to the value in a lookup table; and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

6. The apparatus of claim 1, wherein the processor is configured to: determine a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the first value in a first lookup table; determine a first adjusted value based on a first multiplication of the first value and a speed of the vehicle; determine a second value based on a second mapping of (iii) the velocity of the motor included in the EPAS system and (iv) the position of the motor to the second value in a second lookup table; determine a second adjusted value based on a second multiplication of the second value and the speed of the vehicle; and determine a sum of the first adjusted value and the second adjusted value, and wherein the compliance compensation torque is further determined based on the sum.

7. A non-transitory computer readable storage medium comprising instructions that, when executed, cause a machine to at least: determine a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, the steering column torque having a first torque direction that causes a wheel of the vehicle to turn in a first direction; determine a position of a motor included in the EPAS system based on first sensor data from a motor position sensor; determine whether a motor velocity sensor is functioning properly; after determining the motor velocity sensor is not functioning properly, determine a velocity of the motor based on a derivative of the position of the motor; after determining the motor velocity sensor is functioning properly, determine the velocity of the motor based on second sensor data from the motor velocity sensor; determine a steering column torque derivative by calculating a

derivative of the steering column torque; determine a compliance compensation torque based on the steering column torque and the steering column torque derivative; and adjust a steering response of the steering column by applying the compliance compensation torque via the EPAS system, the compliance compensation torque having the first torque direction or a second torque direction that causes the wheel of the vehicle to turn in the first direction, application of the compliance compensation torque overcoming a resistance to torque associated with the EPAS system.

8. The non-transitory computer readable storage medium of claim 7, wherein the EPAS system is a column EPAS system or a rack EPAS system, and the instructions, when executed, cause the machine to obtain the steering column torque from a sensor of the column EPAS system or the rack EPAS system.

9. The non-transitory computer readable storage medium of claim 7, wherein the instructions, when executed, cause the machine to: generate a second EPAS assistance torque by increasing a first EPAS assistance torque by the compliance compensation torque; and deliver the second EPAS assistance torque to the motor of the EPAS system, the steering response adjusted in response to the delivering of the second EPAS assistance torque.

10. The non-transitory computer readable storage medium of claim 7, wherein the instructions, when executed, cause the machine to: determine a value based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table; and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

11. The non-transitory computer readable storage medium of claim 7, wherein the instructions, when executed, cause the machine to: determine a value based on a mapping of (i) the velocity of the motor included in the EPAS system and (ii) the position of the motor to the value in a lookup table; and determine an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

12. The non-transitory computer readable storage medium of claim 7, wherein the instructions, when executed, cause the machine to: determine a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the first value in a first lookup table; determine a first adjusted value based on a first multiplication of the first value and a speed of the vehicle; determine a second value based on a second mapping of (iii) the velocity of the motor included in the EPAS system and (iv) the position of the motor to the second value in a second lookup table; determine a second adjusted value based on a second multiplication of the second value and the speed of the vehicle; and determine a sum of the first adjusted value and the second adjusted value, and wherein the compliance compensation torque is determined based on the sum.

13. A method comprising: determining a steering column torque associated with a steering column of an electronic power assisted steering (EPAS) system in a vehicle, the steering column torque having a first torque direction that causes a wheel of the vehicle to turn in a first direction; determining a position of a motor included in the EPAS system based on first sensor data from a motor position sensor; determining whether a motor velocity sensor is functioning properly; after determining the motor velocity sensor is not functioning properly, determining a velocity of the motor based on a derivative of the position of the motor; after determining the motor velocity sensor is functioning properly, determine the velocity of the motor based on second sensor data from the motor velocity sensor; determining a steering column torque derivative by calculating a derivative of the steering column torque; determining a compliance compensation torque based on the steering column torque and the steering column torque derivative; and adjusting a steering response of the steering column by applying the compliance compensation torque via the EPAS system, the compliance compensation torque having the first torque direction or a second torque

direction that causes the wheel of the vehicle to turn in the first direction, application of the compliance compensation torque overcoming a resistance to torque associated with the EPAS system.

14. The method of claim 13, wherein adjusting the steering response includes: generating a second EPAS assistance torque by increasing a first EPAS assistance torque by the compliance compensation torque; and delivering the second EPAS assistance torque to the motor of the EPAS system.

15. The method of claim 13, further including: determining a value based on a mapping of the steering column torque and the steering column torque derivative to the value in a lookup table; and determining an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

16. The method of claim 13, further including: determining a value based on a mapping of (i) the velocity of the motor included in the EPAS system and (ii) the position of the motor to the value in a lookup table; and determining an adjusted value based on a multiplication of the value and a speed of the vehicle, and wherein the compliance compensation torque is further determined based on the adjusted value.

17. The method of claim 13, further including: determining a first value based on a first mapping of (i) the steering column torque and (ii) the steering column torque derivative to the first value in a first lookup table; determining a first adjusted value based on a first multiplication of the first value and a speed of the vehicle; determining a second value based on a second mapping of (iii) the velocity of the motor included in the EPAS system and (iv) the position of the motor to the second value in a second lookup table; determining a second adjusted value based on a second multiplication of the second value and the speed of the vehicle; and determining a sum of the first adjusted value and the second adjusted value, and wherein the compliance compensation torque is determined based on the sum.

---