

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409965
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	He; Yuhua et al.

Tensioning mechanism

Abstract

The present invention provides a tensioning mechanism, which is installed in a portable packaging machine, the tensioning mechanism is provided with a rotation direction control and rotation angle keeping mechanism, a non-return mechanism and a rocker arm, the rotation direction control and rotation angle keeping mechanism being connected to the non-return mechanism and the rocker arm, and the rocker arm being provided with a toothed structure matching the tensioning wheel. The present invention is compact in structure, and is capable of realizing the handleless operation of the portable packaging machine from a tensioned state to a non-tensioned state without operating a handle.

Inventors:	He; Yuhua (Zhejiang, CN), Jiang; Shuibo (Zhejiang, CN)
Applicant:	TAIZHOU YONGPAI PACK EQUIPMENT CO., LTD. (Zhejiang, CN)
Family ID:	80354535
Assignee:	ZHEJIANG WEIPAI PACKAGING EQUIPMENT CO., LTD. (Taizhou, CN)
Appl. No.:	18/042917
Filed (or PCT Filed):	August 12, 2021
PCT No.:	PCT/CN2021/112171
PCT Pub. No.:	WO2022/042315
PCT Pub. Date:	March 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230294859 A1	Sep. 21, 2023

Foreign Application Priority Data

CN	202010860740.8	Aug. 25, 2020
CN	202021798720.4	Aug. 25, 2020
CN	202011228003.2	Nov. 06, 2020
CN	202022555482.0	Nov. 06, 2020

Publication Classification

Int. Cl.: B65B13/22 (20060101); B65B13/02 (20060101); B65B13/18 (20060101)

U.S. Cl.:

CPC B65B13/22 (20130101); B65B13/025 (20130101); B65B13/187 (20130101);

Field of Classification Search

CPC: B65B (13/22); B65B (13/025); B65B (13/187)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2015/0210411	12/2014	Finzo	100/32	B65B 13/22
2016/0107775	12/2015	Amacker	100/29	B65B 13/327

Primary Examiner: Alawadi; Mohammed S.

Attorney, Agent or Firm: Muncy, Geissler, Olds & Lowe, P.C.

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to a tensioning mechanism, particularly to a tensioning mechanism of a portable packaging machine.

BACKGROUND OF THE INVENTION

(2) A portable packaging machine is a portable device that can be easily carried to the relevant work point for bundling items. The tightening mechanism is used to tighten the packing strip after wrapping around the item, and its actuator adopts a tightening wheel. The previous portable packaging machine adopts a structure with a handle, by operating the handle, the portable packaging machine switches from a tensioned state to a non-tensioned state (as a working state of placing or removing the packaging strip), and the operation is not automatic enough.

SUMMARY OF THE INVENTION

(3) An object of the present invention is to provide a tensioning mechanism, which is suitable for being mounted in a portable packaging machine and realizes the handleless operation of the portable packaging machine from a tensioned state to a non-tensioned state. To achieve this object, the present invention adopts the following technical solutions:

- (4) A tensioning mechanism, which is installed in a portable packaging machine provided with a tensioning wheel and a tensioning wheel driving electric motor; wherein a gear connecting mechanism is arranged between the driving electric motor and the tensioning wheel, and the tensioning mechanism is also provided with a rotation direction control and rotation angle keeping mechanism, a non-return mechanism and a rocker arm, the rotation direction control and rotation angle keeping mechanism being connected to the non-return mechanism and the rocker arm, and the rocker arm being provided with a toothed structure matching the tensioning wheel, by means of matching the rotation direction control and rotation angle keeping mechanism and a second reset mechanism, the rocker arm is driven to rotate, and the angle after the rocker arm rotates in place is kept, such that the toothed structure and the tensioning wheel are in a tensioned matching state or a loosened state; and by means of matching the rotation direction control and rotation angle keeping mechanism and a first reset mechanism, the non-return mechanism is driven to be in a non-return matching state or released from the non-return matching state, the gear connecting mechanism is connected to the non-return mechanism, and when the non-return mechanism is in the non-return matching state, the tensioning wheel can only be driven to rotate in a single direction and cannot rotate reversely, and the single direction is the direction of rotation to tension a packaging strip.
- (5) The rotation direction control and rotation angle keeping mechanism adopts a steering engine. Further, the non-return mechanism comprises a non-return mechanism connecting gear, a ratchet coaxially connected with the non-return mechanism connecting gear and a pawl matching the ratchet, the pawl can be driven by a first connecting gear by means of matching a first connecting structure and a first connecting gear, and the rocker arm can be driven by a second connecting gear by means of matching a second connecting structure and a second connecting gear, and the rotation direction control and rotation angle keeping mechanism drives the first connecting gear and the second connecting gear.
- (6) Further, the first connecting gear and the second connecting gear are in mesh connection with rotate synchronously, the second connecting gear is larger than the first connecting gear and has a lower rotational speed than the first connecting gear.
- (7) Further, the second connecting structure comprises a driving part driven by the second connecting gear and a rotating connecting part, the rotating connecting part is provided with an acted part matching the active part, and the rotating connecting part is also provided with a structure connected to the rocker arm. The rotating connecting part is further provided with a part connected to the second reset mechanism.
- (8) Further, the rotating connecting part is in the shape of a ring, and the rotation center line thereof is collinear with the rotation center line of the tensioning wheel, and the gear connecting structure is provided with a planetary gear reduction mechanism, the ring-shaped rotating connecting piece is mounted on the planetary gear reduction mechanism through a bearing.
- (9) Further, the pawl arm is mounted on the shaft of the second connecting gear and can rotate relative to the shaft of the second connecting gear, and the active part and the shaft of the second connecting gear are fixedly connected or in a whole.
- (10) Further, the gear connecting mechanism comprises a planetary gear reduction mechanism and a connecting gear between the driving electric motor and the planetary gear reduction mechanism. The planetary gear reduction mechanism can be provided with one or more stages.
- (11) Further, a preferred embodiment is: the steering engine and the tensioning wheel driving electric motor are arranged in parallel, the steering engine is located above the side of the tensioning wheel and the tensioning wheel driving electric motor; the steering engine is connected with the first connecting gear through the driving gear, and the first connecting gear is in mesh connection with the second connecting gear, and the second connecting gear is larger than the first connecting gear and has a lower rotational speed than the first connecting gear;
- (12) the non-return mechanism comprises a non-return mechanism connecting gear, a ratchet coaxially connected with the non-return mechanism connecting gear and a pawl matching the

ratchet, the pawl is connected with the first connecting gear through the first connecting structure, and the rocker arm is connected with the second connecting gear through the second connecting structure;

(13) the second connecting structure comprises a driving part driven by the second connecting gear and a rotating connecting part, the rotating connecting part is provided with an acted part matching the active part, and the rotating connecting part is also provided with a structure connected to the rocker arm;

(14) the rotating connecting part is in the shape of a ring, and the rotation center line thereof is collinear with the rotation center line of the tensioning wheel, and the gear connecting structure is provided with a planetary gear reduction mechanism, the ring-shaped rotating connecting piece is mounted on the planetary gear reduction mechanism through a bearing, the tensioning wheel is provided with a ring gear, and the output gear coaxial with the sun gear of the planetary gear reduction mechanism is connected with the ring gear through a connecting gear;

(15) the non-return mechanism is arranged in front of the planetary gear reduction mechanism;

(16) the non-return mechanism connecting gear is mounted on the shaft of the ratchet through a one-way bearing, when the tensioning mechanism is tightening, the non-return mechanism is in a non-return matching state, in the corresponding tensioning rotation direction of the tensioning wheel, the one-way bearing allows the non-return mechanism connecting gear to rotate relative to the ratchet, and when the tensioning wheel driving electric motor stops rotating, the non-return mechanism connecting gear is prohibited from rotating relative to the ratchet in an opposite direction, and both must rotate together.

(17) Furthermore, the ring gear is coaxially arranged with the sun gear of the planetary gear reduction mechanism; the tensioning wheel and the planetary gear reduction mechanism are arranged close to each other in the axial direction, so as to further reduce the connecting parts and reduce the size of the machine and facilitate the use of the portable packaging machine.

(18) Further, the first gear and the sun gear of the planetary gear reduction mechanism are coaxially connected together to further simplify the connecting structure. Alternatively, the first gear and the sun gear can also be connected via an intermediate gear instead of connected coaxially.

(19) Further, the planetary gear carrier of the planetary gear reduction mechanism and the planetary gear are arranged on the side of the mounting plate facing the driving electric motor, the rotating shaft of the planetary gear carrier of the planetary gear reduction mechanism is connected with the output gear, and the output gear is on the other side of the mounting plate, and the ring gear is on the periphery thereof. A plurality of connecting gears surrounding the output gear are arranged between the output gear and the ring gear, and the connecting gear axis is fixed on the mounting plate.

(20) Further, the connection between the connecting gear and the output gear is a deceleration connection.

(21) Further, the tensioning mechanism is provided with a belt pressing mechanism, and the belt pressing mechanism is arranged on the rocker arm of the portable packaging machine, and the belt pressing mechanism comprises a first elastic mechanism and a belt pressing part, the first elastic mechanism pushes the belt pressing part downward, allows the belt pressing part to retract and provides an elastic force for the belt pressing part to return downward, and the height of the lower end of the belt pressing part is lower than the upper end of the toothed plate arranged at the inner bottom of the rocker arm, which is close to the side of the belt pressing mechanism.

(22) Further, the belt pressing part adopts a rolling element.

(23) Further, the portable packaging machine is provided with a packaging strip limiting structure on the inner side of the rocker arm.

(24) Further, the belt pressing mechanism is provided with a rotatable mounting block, the first elastic mechanism and the belt pressing part are arranged in the mounting block, through the rotation of the mounting block, the belt pressing part is adapted to the lifting of the packaging strip

when the belt is tightened at the vacated height, and the mounting block is connected to the second elastic mechanism.

(25) Further, the belt pressing mechanism is provided with a spacer and a connecting screw, the spacer is connected with the mounting block, and the connecting screw connects the mounting block with the rocker arm.

(26) Further, the first elastic mechanism adopts a compression spring, the mounting block is provided with a mounting hole inside, the belt pressing part adopts a steel ball, the compression spring and the steel ball are arranged in the mounting hole, and the lower end orifice of the mounting hole is smaller than the diameter of the steel ball.

(27) Further, the second elastic mechanism adopts a torsion spring, and the torsion spring is sleeved between the spacers and connected between the rocker arm and the mounting block.

(28) Further, the mounting block is provided with a connecting hole, the spacer is provided with a part inserted into the connecting hole, and the connecting screw passes through the connecting hole and the spacer to connect with the rocker arm; the mounting block is provided with a hole orthogonally passing through the connecting hole, the lower part of the connecting hole is used as a mounting hole, the belt pressing part adopts a steel ball, the compression spring and the steel ball are arranged in the mounting hole, the lower end orifice of the mounting hole is smaller than the diameter of the steel ball, and the inserting part of the spacer serves as a supporting part of the compression spring.

(29) Further, the spacer is provided with a portion inserted into the connecting hole and serves as a rotation axis of the mounting block.

(30) Further, a concave area is provided on the outer side of the rocker arm, and the mounting block is correspondingly disposed in the concave area.

(31) Due to the adoption of the technical solutions of the present invention, the present invention is compact in structure and is suitable for being applied to a portable packaging machine, and realizes the handleless operation of the portable packaging machine from a tensioned state to a non-tensioned state without operating a handle. Furthermore, for the tensioning mechanism that uses the exclusive driving electric motor of the tensioning wheel, the worm gear structure is avoided, and meanwhile, the compact assembly relationship of adjacent and concentric inclusion can be realized, and the volume is reduced, such that the planetary gear is suitable for use in the limited and applicable space of the portable packaging machine and the non-return mechanism is configured, which is small in size and is portable for users conveniently, and has low energy consumption.

(32) The present invention will be further described in detail below in conjunction with the accompanying drawings and specific embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a schematic perspective view of an embodiment of the present invention.

(2) FIG. 2 is a schematic perspective view of another angle of an embodiment of the present invention.

(3) FIG. 3 is a front view of an embodiment of the present invention with the motor mounting base hidden.

(4) FIG. 4 is an exploded view of a non-return mechanism and surrounding structures thereof.

(5) FIG. 5 is an exploded view of a non-return mechanism and a planetary gear mechanism.

(6) FIG. 6 is an exploded view of an embodiment of a portable packaging machine of the present invention.

(7) FIG. 7 is a schematic diagram of an embodiment of a handleless portable packaging machine applying a belt pressing mechanism of the present invention.

(8) FIG. 8 is a front view of a swing arm provided with a belt pressing mechanism in the embodiment shown in FIG. 7.

(9) FIG. 9 is a perspective view of a swing arm provided with a belt pressing mechanism in the embodiment shown in FIG. 7.

(10) FIG. 10 is an exploded view of the structure shown in FIG. 9.

DETAILED DESCRIPTION

(11) Referring to FIGS. 1 to 6, the present invention provides a tensioning mechanism, which is installed in a portable packaging machine. The portable packaging machine is provided with a tensioning wheel **100** and a tensioning wheel driving electric motor **200**. The drive motor **200** is mounted on the mounting plate **203** thereof, and the mounting plate **203** is fixedly connected to a mounting base **400**. A gear connecting mechanism is arranged between the driving electric motor **200** and the tensioning wheel **100**, the gear connecting mechanism comprises a planetary gear reduction mechanism and a connecting gear between the driving electric motor **200** and the planetary gear reduction mechanism.

(12) The tensioning mechanism is also provided with a rotation direction control and rotation angle keeping mechanism, a non-return mechanism and a rocker arm **300**, the rotation direction control and rotation angle keeping mechanism can adopts a steering engine **6**. The steering engine **6** is connected with the non-return mechanism and the rocker arm **300**, the rocker arm **300** is rotatably mounted on the mounting base **400** and is at the periphery of the tensioning wheel **100**; the rocker arm **300** is provided with a toothed structure **301** matching the tensioning wheel **100**, by means of matching the steering engine **6** and a second reset mechanism, the rocker arm **300** is driven to rotate, and the angle after the rocker arm **300** rotates in place is kept, wherein the second reset mechanism adopts a compression spring **62**, such that the toothed structure **301** and the tensioning wheel **100** are in a tensioned matching state or a loosened state; and by means of matching the steering engine **6** and a first reset mechanism, the non-return mechanism is driven to be in a non-return matching state or released from the non-return matching state, wherein the first reset mechanism adopts a compression spring **61**, the gear connecting mechanism is connected to the non-return mechanism, and when the non-return mechanism is in the non-return matching state, the tensioning wheel **100** can only be driven to rotate in a single direction and cannot rotate reversely, and the single direction is the direction of rotation to tension a packaging strip.

(13) The non-return mechanism comprises a non-return mechanism connecting gear **21**, a ratchet **22** coaxially connected with the non-return mechanism connecting gear **21** and a pawl **23** matching the ratchet, the pawl **23** can be driven by a first connecting gear by means of matching a first connecting structure and a first connecting gear **71**, and the rocker arm **300** can be driven by a second connecting gear by means of matching a second connecting structure and a second connecting gear **72**.

(14) The steering engine **6** and the tensioning wheel driving electric motor **200** are arranged in parallel, the steering engine **6** is located above the side of the tensioning wheel **100** and the tensioning wheel driving electric motor **200**; the steering engine **6** is connected with the first connecting gear **71** through the driving gear **73**, and the first connecting gear **71** is in mesh connection with the second connecting gear **72**. The axes of the driving gear **73**, the first connecting gear **71** and second connecting gear **72** are parallel to the axis of tensioning wheel, the pawl arm **230** is arranged on the shaft **720** of the second connecting gear **72**, and can rotate relative to the shaft **720** of second connecting gear **72**, the first connecting gear **71** and second connecting gear **72** rotate synchronously. The second connecting gear **72** is larger than the first connecting gear **71** and has a lower rotational speed than the first connecting gear **71**, such that the center of gravity of the portable packaging machine is more stable, the action of pawl **23** is more sensitive and the rocker arm **300** has a suitable rotation angle; additionally, the first connecting gear **71** is also larger than the driving gear, and is in a deceleration matching relationship.

(15) The first connecting structure comprises a first cam **711** arranged on the first connecting gear

shaft **710** and a second cam **231** arranged on the pawl arm **230**, the first cam **711** matches with the second cam **231**, and the pawl arm **230** is connected with a reset spring **61**. The positive rotation of the steering engine **6** plays a role in driving the pawl to disengage from the ratchet through the matching of the cam. The reset spring **61** is not only used to drive the pawl **23** to reset and form a meshed matching with the ratchet **22**, but also to make the second cam **231** lean towards the first cam **711**.

(16) The two ends of the shaft **220** of the ratchet **22** are respectively mounted on the mounting plate **203** and the mounting base **400** through the bearings **25**. The connecting gear **21** is mounted on the shaft of the ratchet **22** through a one-way bearing **27**, and the direction of the one-way bearing **27** is as follows: when the tensioning mechanism is tightening, the connecting gear **21** is allowed to rotate relative to the ratchet **22** driven by the first gear **1**, and when the tensioning wheel driving electric motor **200** stops rotating, the connecting gear **21** is prohibited from rotating relative to the ratchet in the opposite direction and both must rotate together.

(17) The second connecting structure comprises a driving part **721** driven by the second connecting gear and a rotating connecting part **8**, the rotating connecting part **8** is provided with an acted part **81** matching the active part **721**, and the rotating connecting part is also provided with a structure **82** connected to the rocker arm and a part **83** connected to the second reset mechanism. The driving part **721** and the shaft **720** of the second connecting gear **72** are fixedly connected or integrated as a whole, and the forward rotation of the steering engine, through the action of the driving part **721** on the acted part **81**, makes the rotating connecting part **8** to rotate, and by means of the structure **82** connected to the rocker arm, the rotation makes the rocker arm **300** to move an angle toward the loosening direction, and the rocker arm **300** can be provided with a bayonet **302** that matches the structure **82**. When the steering engine rotates reversely, the driving part **721** rotates in the opposite direction to give way, and through the action of the compression spring **62**, the rotating connecting part **8** rotates in the opposite direction, and the rocker arm **300** generates an angle towards the tightening direction, and the toothed structure **301** and tensioning wheel **100** are in a tensioned matching state.

(18) The rotating connecting part **8** is in the shape of a ring, and the rotation center line thereof is collinear with the rotation center line of the tensioning wheel **100**, and the ring-shaped rotating connecting part **8** is mounted on the mounting plate **500** of the planetary gear reduction mechanism through the bearing. Since the steering engine **6** is located obliquely above the tensioning wheel **100**, and the driving gear **73**, the first connecting gear **71** and the second connecting gear **72** are parallel to the axis of the tensioning wheel, the shaft **720** of the second connecting gear **72** is arranged in parallel above the ring-shaped rotating connecting part **8**, such that the driving part **721** utilizes the feature that its rotating diameter is smaller than that of the ring-shaped rotating connecting part **8** above the ring-shaped rotating connecting part **8**, the rocker arm can rotate a smaller angle, improving the working speed and the precision of the machine.

(19) The tensioning wheel **100** is provided with a ring gear **101**, and the output gear **4** coaxial with the sun gear **31** of the planetary gear reduction mechanism is connected with the ring gear **101** through a connecting gear **5**; the ring gear **101** is set concentrically with the sun gear **31** of the planetary gear reduction mechanism, and their rotation centers are on the same axis; the tensioning wheel **100** and the planetary gear reduction mechanism are arranged close to each other in the axial direction.

(20) The non-return mechanism is arranged in front of the planetary gear reduction mechanism, and the driving gear **202** is arranged on the output shaft **201** of the driving electric motor **200**, and the driving gear **202** is in mesh connection with a first gear **1** in a deceleration connection relationship; the first gear **1** is just in front of the planetary gear reduction mechanism, the first gear **1** is connected with the planetary gear reduction mechanism, and the first gear **1** is also in transmission connection with the non-return mechanism (mesh connection with the connecting gear **21**).

(21) The shafts of the first gear **1** and the sun gear **31** of the planetary gear reduction mechanism

are the same shaft or integrated as whole, and the shaft is mounted on the mounting base **400** through the bearing **11**.

(22) The present invention also provides an embodiment of a reduction mechanism with a simple structure and a small volume for easy assembly. The planetary gear reduction mechanism comprises the sun gear **31**, three planetary gears **32**, a planetary gear carrier **33** and an annulus **34**. The annulus **34** is arranged on the mounting plate **500**, the mounting plate **500** is fixed on the mounting base **400**, wherein the gear shafts of the three planetary gears **32** are mounted on the planetary gear carrier **33**, and the rotating shaft **35** of the planetary gear carrier **33** passes through the mounting hole on the mounting plate **500** and is rotatably mounted on the mounting plate **500**. The planetary gear carrier **33** and the planetary gear **32** are arranged on the side of the mounting plate **500** facing the driving electric motor **200**, the rotating shaft **35** of the planetary gear carrier **33** of the planetary gear reduction mechanism is connected with the output gear **4**, and the output gear **4** is on the other side of the mounting plate **500**, the ring gear **101** is on the periphery of the output gear **4**, and there are multiple connecting gears **5** around the output gear **4**. The axis of the connecting gear **5** is fixed on the mounting plate **500**, and the number of connecting gears **5** is generally three. The connection between the connecting gear **5** and the output gear **4** is also a deceleration connection.

(23) The following examples refer to FIGS. 7 to 10.

(24) The belt pressing mechanism **601** provided in this embodiment is arranged on the rocker arm **300** of the portable packaging machine, and the reference numeral **100** is the tensioning wheel of the portable packaging machine. The rocker arm **300** is bent and is arranged around the tensioning wheel **100** on one side of the tensioning wheel **100**, and the inner bottom of the rocker arm **300** is provided with a toothed plate **301**, after the rocker arm **300** turns to close with the tensioning wheel **100**, the toothed plate **301** matches the tensioning wheel **100**, gets the packaging strip **700** stuck, and when the tensioning wheel **100** rotates, the packaging strip **700** is tightened to the right (based on the placement position of the portable packaging machine in FIG. 7).

(25) The belt pressing mechanism comprises a first elastic mechanism and a belt pressing part, the first elastic mechanism adopts a compression spring **610**, and the belt pressing part adopts a steel ball **601**, which is convenient for installation and has a small frictional resistance to the packaging strip **700**; the compression spring **610** pushes the steel ball **601** downward, and allows the steel ball **601** to retract and provides an elastic force for the steel ball **601** to return downward, and the height of the lower end of the steel ball **601** is lower than the upper end **303** of the toothed plate **301** arranged at the inner bottom of the rocker arm, which is close to the side of the belt pressing mechanism. When the curved rocker arm **300** and the tensioning wheel **100** are in an open state and the packing strip **700** is put in, the belt pressing part (steel ball **601**) can press the packing belt **700** downward; when the rocker arm **300** is rotated in the closing direction, the state of the packing tape **700** can be effectively maintained and prevented from falling out.

(26) The portable packaging machine is provided with a packaging strip limiting structure on the inner side of the rocker arm, which can ensure that the position of the packaging strip **700** in the width direction is appropriate when it is put in, and is convenient for the belt pressing part to play the role of pressing the strip. The packaging strip limiting structure can adopt a limiting block **605** or a limiting plate, etc.

(27) The belt pressing mechanism is provided with a rotatable mounting block **602**, and the rotation axis of the mounting block **602** is orthogonal to the rotation axis of the rocker arm **300**. Through this rotation, the belt pressing part (steel ball **601**) on the mounting block **602** changes in height. Through the rotation of the mounting block **602**, the belt pressing part is adapted to the lifting of the packing belt when the belt is tightened at the vacated height, so that the pressing strip and the tightening strip of the portable packaging machine are more coordinated, which not only ensures the strip pressing effect, but also makes the process of tightening the belt smooth.

(28) The mounting block **602** is provided with a mounting hole **621**, the compression spring **610**

and the steel ball **601** are provided in the mounting hole **621**, and the lower end orifice **6211** of the mounting block **621** is smaller than the diameter of the steel ball **601**.

(29) The belt pressing mechanism is provided with a spacer **603** and a connecting screw **604**, the spacer **603** has an insertion end **631**, the mounting block **602** is provided with a connecting hole **623**, the insertion end **631** is inserted into the connecting hole **623**, and the screw **604** is connected to the rocker arm **300** through the connecting hole **623** and the spacer **603**. The reference numeral **304** is the screw connecting hole on the swing arm that is matched with the screw **604**; the mounting block **602** is provided with a hole orthogonally passing through the connecting hole **623**, the lower part of the connecting hole is used as a mounting hole **621**, the upper hole **622** is used as a via hole for mounting the compression spring **610** and the steel ball **601**, and can be blocked with a plug. The insertion end **631** of the spacer serves as a rotation axis of the mounting block **602** and as a supporting part of the compression spring **610**.

(30) The mounting block **602** is connected to the second elastic mechanism, the second elastic mechanism adopts a torsion spring **620**, and the torsion spring **620** is sleeved between the spacers **603** and connected between the rocker arm **300** and the mounting block **602**.

(31) A concave area **305** is provided on the outer side of the rocker arm **300**, and the mounting block **601** is correspondingly disposed in the concave area **305**, to facilitate the arrangement of the belt pressing part.

(32) In this embodiment, the belt pressing mechanism is adopted, which can prevent the packaging strip from falling out to the outside through a certain degree of strip pressure when the swing arm and the tensioning wheel are closed, and when the packaging strip is stretched and the packaging strip is lifted up, elastic vacation is adaptive, which does not hinder the work of the tensioning strip, and facilitates the automatic operation of the portable packaging machine.

(33) The description only describes the specific embodiments of the present invention, but the structural features of the present invention are not limited thereto. Any changes or modifications made by those skilled in the art within the field of the present invention shall fall within the scope of protection of the present invention.

(34) It should be noted that the terms “comprising” and “having” in the description and claims of the present invention and the accompanying drawings, as well as any modifications thereof, are intended to cover non-exclusive inclusion. The terms “installed/mounted”, “arranged”, “set”, “connected”, “sleeved” should be construed broadly. For example, it may be a fixed connection, a detachable connection, or an integral structure; it may be a mechanical connection, or an electrical connection; it may be directly connected, or indirectly connected through an intermediary, or between two devices, elements, or internal communication between components. For those of ordinary skill in the art, the specific meanings of the above terms in the present invention can be understood according to specific situations.

(35) It should be understood that, in the description of the present invention, the orientation or positional relationship indicated by the terms “one end”, “another end”, “outside”, “inside”, “horizontal”, “end”, “length”, “outer end”, “left”, “right”, etc. is based on the orientation or positional relationship shown in the figures, and is only for the convenience of describing the present invention and simplifying the description, rather than indicating or implying that the indicated device or element must have the particular orientation, construction and operation in the particular orientation, therefore, it cannot be construed as limitations of the present invention. The terms “first”, “second” are used for brevity of description only, and do not indicate or imply relative importance.

(36) Furthermore, variations to the disclosed embodiments can be understood and effected by those skilled in the art in practicing the claims of the invention, from a study of the drawings, the disclosure, and the appended claims. Furthermore, in the claims, words such as “comprising”, “containing” and the like do not exclude other elements or steps, and non-plural nouns do not exclude their plurals.

Claims

1. A tensioning mechanism, which is installed in a portable packaging machine, comprising a tensioning wheel, a tensioning wheel driving electric motor, a gear connecting mechanism arranged between the driving electric motor and the tensioning wheel, wherein the tensioning mechanism is provided with a rotation direction control and rotation angle keeping mechanism, a non-return mechanism and a rocker arm, the rotation direction control and rotation angle keeping mechanism being connected to the non-return mechanism and the rocker arm, and the rocker arm being provided with a toothed structure matching the tensioning wheel, by means of matching the rotation direction control and rotation angle keeping mechanism and a second reset mechanism, the rocker arm is driven to rotate, and an angle after the rocker arm rotates in place is kept, such that the toothed structure and the tensioning wheel are in a tensioned matching state or a loosened state; and by means of matching the rotation direction control and rotation angle keeping mechanism and a first reset mechanism, the non-return mechanism is driven to be in a non-return matching state or released from the non-return matching state, the gear connecting mechanism is connected to the non-return mechanism, and when the non-return mechanism is in the non-return matching state, the tensioning wheel is only driven to rotate in a single direction and cannot rotate reversely, and the single direction is a direction of rotation to tension a packaging strip.
2. The tensioning mechanism according to claim 1, wherein the rotation direction control and rotation angle keeping mechanism adopts a steering engine.
3. The tensioning mechanism according to claim 1, wherein the non-return mechanism comprises a non-return mechanism connecting gear, a ratchet coaxially connected with the non-return mechanism connecting gear and a pawl matching the ratchet, the pawl is driven by a first connecting gear by means of matching a first connecting structure and a first connecting gear, and the rocker arm is driven by a second connecting gear by means of matching a second connecting structure and a second connecting gear, and the rotation direction control and rotation angle keeping mechanism drives the first connecting gear and the second connecting gear.
4. The tensioning mechanism according to claim 3, wherein the first connecting gear and the second connecting gear are in mesh connection with rotate synchronously, the second connecting gear is larger than the first connecting gear, and the second connecting gear has a lower rotational speed than the first connecting gear.
5. The tensioning mechanism according to claim 3, wherein the first connecting structure comprises a first cam arranged on a first connecting gear shaft of the first connecting gear and a second cam arranged on a pawl arm of the pawl, the first cam matches with the second cam, and the pawl arm is connected with the first reset mechanism.
6. The tensioning mechanism according to claim 5, wherein the second connecting structure comprises a driving part driven by the second connecting gear and a rotating connecting part, the rotating connecting part is provided with an acted part matching the driving part, and the rotating connecting part is provided with a structure connected to the rocker arm.
7. The tensioning mechanism according to claim 6, wherein the rotating connecting part is provided with a part connected to the second reset mechanism.
8. The tensioning mechanism according to claim 6, wherein the rotating connecting part is in a shape of a ring, and a rotation center line of the rotating connecting part is collinear with a rotation center line of the tensioning wheel, and the gear connecting structure is provided with a planetary gear reduction mechanism, the rotating connecting part is mounted on the planetary gear reduction mechanism through a bearing.
9. The tensioning mechanism according to claim 5, wherein the pawl arm is mounted on a shaft of the second connecting gear and the pawl arm is rotated relative to the shaft of the second connecting gear, and the driving part and the shaft of the second connecting gear are fixedly

connected or in a whole.

10. The tensioning mechanism according to claim 3, wherein the rotation direction control and rotation angle keeping mechanism adopts a steering engine and the steering engine and the tensioning wheel driving electric motor are arranged in parallel, the steering engine is located above a side of the tensioning wheel and the tensioning wheel driving electric motor; the steering engine is connected with the first connecting gear through a driving gear, and the first connecting gear is in mesh connection with the second connecting gear, and the second connecting gear is larger than the first connecting gear, and the second connecting gear has a lower rotational speed than the first connecting gear; the pawl is connected with the first connecting gear through the first connecting structure, and the rocker arm is connected with the second connecting gear through the second connecting structure; the second connecting structure comprises a driving part driven by the second connecting gear and a rotating connecting part, the rotating connecting part is provided with an acted part matching the driving part, and the rotating connecting part is provided with a structure connected to the rocker arm; the rotating connecting part is in a shape of a ring, and a rotation center line of the rotating connecting part is collinear with a rotation center line of the tensioning wheel, and the gear connecting structure is provided with a planetary gear reduction mechanism, the rotating connecting part is mounted on the planetary gear reduction mechanism through a bearing, the tensioning wheel is provided with a ring gear, and a output gear coaxial with a sun gear of the planetary gear reduction mechanism is connected with the ring gear through a connecting gear; the non-return mechanism is arranged in front of the planetary gear reduction mechanism; the non-return mechanism connecting gear is mounted on a shaft of the ratchet through a one-way bearing, when the tensioning mechanism is tightening, the non-return mechanism is in a non-return matching state, in a corresponding tensioning rotation direction of the tensioning wheel, the one-way bearing allows the non-return mechanism connecting gear to rotate relative to the ratchet, and when the tensioning wheel driving electric motor stops rotating, the non-return mechanism connecting gear is prohibited from rotating relative to the ratchet in an opposite direction, and both of the non-return mechanism connecting and the ratchet must rotate together.

11. The tensioning mechanism according to claim 1, wherein a belt pressing mechanism is provided, and the belt pressing mechanism is arranged on the rocker arm, and the belt pressing mechanism comprises a first elastic mechanism and a belt pressing part, the first elastic mechanism pushes the belt pressing part downward, allows the belt pressing part to retract and provides an elastic force for the belt pressing part to return downward, and a height of a lower end of the belt pressing part is lower than an upper end of a toothed plate arranged at an inner bottom of the rocker arm, which the inner bottom of the rocker arm is close to a side of the belt pressing mechanism.

12. The tensioning mechanism according to claim 11, wherein the belt pressing part adopts a rolling element.

13. The tensioning mechanism according to claim 11, wherein the belt pressing mechanism is provided with a rotatable mounting block, the first elastic mechanism and the belt pressing part are arranged in the mounting block, through a rotation of the mounting block, the belt pressing part is adapted to a lifting of the packaging strip when the belt pressing part is tightened at a vacated height, and the mounting block is connected to a second elastic mechanism.

14. The tensioning mechanism according to claim 13, wherein the belt pressing mechanism is provided with a spacer and a connecting screw, the spacer is connected with the mounting block, and the connecting screw connects the mounting block with the rocker arm.

15. The tensioning mechanism according to claim 14, wherein the second elastic mechanism adopts a torsion spring, and the torsion spring is sleeved by the spacer and connected between the rocker arm and the mounting block.

16. The tensioning mechanism according to claim 14, wherein the first elastic mechanism adopts a compression spring, the mounting block is provided with a connecting hole, the spacer is provided with a part inserted into the connecting hole, and the connecting screw passes through the

connecting hole and the spacer to connect with the rocker arm; the mounting block is provided with a hole orthogonally passing through the connecting hole, a lower part of the connecting hole is used as a mounting hole, the belt pressing part adopts a steel ball, the compression spring and the steel ball are arranged in the mounting hole, a lower end orifice of the mounting hole is smaller than a diameter of the steel ball, and an inserting part of the spacer serves as a supporting part of the compression spring.

17. The tensioning mechanism according to claim 16, wherein the spacer is provided with a portion inserted into a connecting hole and serves as a rotation axis of the mounting block.

18. The tensioning mechanism according to claim 13, wherein the first elastic mechanism adopts a compression spring, the mounting block is provided with a mounting hole inside, the belt pressing part adopts a steel ball, the compression spring and the steel ball are arranged in the mounting hole, and a lower end orifice of the mounting hole is smaller than a diameter of the steel ball.

19. The tensioning mechanism according to claim 13, wherein a concave area is provided on an outer side of the rocker arm, and the mounting block is correspondingly disposed in the concave area.
