

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410881
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Newman; Stephen Christopher et al.

Non-intrusive tracking of objects in pipelines and wellbores

Abstract

Systems and methods of the present disclosure relate to non-intrusive tracking of objects in a conduit from a single location. A system comprises a component positioned to control flow into or out of the conduit to induce pressure waves in the conduit; a pressure transducer in fluid communication with the conduit, the pressure transducer positioned to measure pressure responses in the conduit due to contact of the pressure waves with the object; and a system controller operable to: receive pressure data from the pressure transducer, wherein the pressure data includes the pressure responses to the pressure waves; and determine a distance of the object in the conduit, relative to the component or the pressure transducer, based on the pressure responses.

Inventors:	Newman; Stephen Christopher (Aberdeen, GB), Jack; Graham Peter (Newburgh, GB)
Applicant:	Halliburton Energy Services, Inc. (Houston, TX)
Family ID:	80777033
Assignee:	Halliburton Energy Services, Inc. (Houston, TX)
Appl. No.:	17/916463
Filed (or PCT Filed):	December 18, 2020
PCT No.:	PCT/US2020/065902
PCT Pub. No.:	WO2022/060391
PCT Pub. Date:	March 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230220944 A1	Jul. 13, 2023

Related U.S. Application Data

us-provisional-application US 63080431 20200918

Publication Classification

Int. Cl.: **F16L55/48** (20060101); **E21B43/12** (20060101); **E21B47/047** (20120101); **E21B47/095** (20120101); **F16L55/38** (20060101); **F16L101/12** (20060101); **F16L101/30** (20060101); **G01F23/2962** (20220101); **G01S15/08** (20060101); **G01V1/46** (20060101)

U.S. Cl.:

CPC **F16L55/48** (20130101); **E21B47/047** (20200501); **E21B47/095** (20200501); **F16L55/38** (20130101); **G01F23/2962** (20130101); **G01S15/08** (20130101); **G01V1/46** (20130101); **E21B43/126** (20130101); **F16L2101/12** (20130101); **F16L2101/30** (20130101)

Field of Classification Search

CPC: E21B (47/047); E21B (47/09); E21B (47/095); F16L (55/48)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4590799	12/1985	Brown et al.	N/A	N/A
5417112	12/1994	Rosenberg	N/A	N/A
5549000	12/1995	Brown et al.	N/A	N/A
6401814	12/2001	Owens et al.	N/A	N/A
6710720	12/2003	Carstensen et al.	N/A	N/A
6993963	12/2005	Gudmundsson	N/A	N/A
7222549	12/2006	Abney	N/A	N/A
8973444	12/2014	Hill et al.	N/A	N/A
9535039	12/2016	Farqu��et al.	N/A	N/A
9599272	12/2016	Hartog et al.	N/A	N/A
9828847	12/2016	Vavik	N/A	N/A
2014/0182846	12/2013	Fischer et al.	N/A	N/A
2014/0262245	12/2013	Hill	166/250.03	E21B 47/047
2015/0323119	12/2014	Giunta et al.	N/A	N/A
2015/0331007	12/2014	Giunta et al.	N/A	N/A
2017/0234713	12/2016	McCoy	N/A	N/A
2017/0268714	12/2016	Giron et al.	N/A	N/A
2017/0307462	12/2016	Barron	N/A	E21B 41/0007
2019/0129047	12/2018	Clark	N/A	E21B 47/095
2020/0072042	12/2019	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1062946	12/2000	CN	N/A
108374654	12/2022	CN	N/A
2462096	12/2009	GB	F16L 55/48
2506838	12/2016	GB	N/A
H0586792	12/1992	JP	N/A
H06129942	12/1993	JP	N/A
20170038574	12/2016	KR	N/A
20170050045	12/2016	KR	N/A
WO-9950586	12/1998	WO	F16L 55/46
2006054054	12/2005	WO	N/A
2011070343	12/2010	WO	N/A
WO-2020162964	12/2019	WO	F16L 55/46

OTHER PUBLICATIONS

Brazilian Office Action for BR Patent Application No. 112022025087-8 dated Apr. 19, 2024 with Search Report and Opinion dated Nov. 14, 2023. English Machine Translation with Original Untranslated Version, PDF file. 11 pages. cited by applicant

European Patent Office Extended European Search Report for EPO Application No. 20954313.1 dated Mar. 4, 2024. PDF file. 8 pages. cited by applicant

Technical Research Centre of Finland, Timo Siikonen, Computer Program TMOC for Calculating of Pressure Transients in Fluid Filled Piping Networks. cited by applicant

Durali, Mohammad; Fazeli, Amir; Nabi, Ali (2007). [ASME ASME 2007 International Mechanical Engineering Congress and Exposition—Seattle, Washington, USA (Nov. 11-15, 2007)] vol. 9: Mechanical Systems and Control, Parts A, B, and C—Investigation of Dynamics and Vibration of Pig in Oil and Gas Pipelines. , (), 2015-2024. cited by applicant

Sensors, Renan Pires de Araujo, et al., Pipeline Inspection Gauge's Velocity Simulation Based on Pressure Differential Using Artificial Neural Networks, 2018. cited by applicant

Downhole Diagnostic, Acoustic Fluid Level Surveys. Available at <https://www.downholediagnostic.com/fluid-level>. Accessed Dec. 14, 2020. cited by applicant

Circor, Pipeline Blockage Detection—ACOUSTEK®. Available at <https://www.circor.com/services/pipeline-blockage-detection-acoustek>. Accessed Dec. 14, 2020. cited by applicant

Paradigm Flow Services, Locate Blockages of Was, Asphaltene, Sand, Scale, Hydrates and Stuck Pigs. Available at <https://www.paradigm.eu/flow/technology/find-block>. Accessed Dec. 14, 2020. cited by applicant

PPS—InnerVue, Available at https://www.ppsa-online.com/directory-of-members?company_id=191. Accessed Dec. 14, 2020. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2020/065902, dated Jun. 8, 2021. cited by applicant

Schlumberger Energy Glossary. Definition of well bore. Company Website, <https://glossary.slb.com/en/terms/w/wellbore>. Accessed Jun. 26, 2024. cited by applicant

Schlumberger Energy Glossary. Definition of pipeline. Company Website, <https://glossary.slb.com/en/terms/p/pipeline>. Accessed Jun. 26, 2024. cited by applicant

Schlumberger Energy Glossary. Definition of casing Company Website, <https://glossary.slb.com/en/terms/c/casing>. Accessed Jun. 28, 2024. cited by applicant

Schlumberger Energy Glossary. Definition of pigging Company Website, <https://glossary.slb.com/en/terms/p/pigging>. Accessed Jun. 26, 2024. cited by applicant

Background/Summary

BACKGROUND

- (1) Pipelines may experience a range of issues such as a build-up of deposits or full blockages and stuck pigs due to these build ups. The pigs may be propelled through the pipeline via flowing fluid and may serve various functions, including cleaning the pipeline to remove obstructions, inspecting the interior of the pipeline, and/or providing a barrier to separate different fluids in the pipeline.
- (2) If the location of a pig is not known and the pig gets stuck in the pipeline for example, downtime required to displace the pig from the pipeline can be costly. Additionally, if a velocity of the pig cannot be tracked, pig overspeed may occur. Existing technologies may require numerous pieces of equipment on the pig as well as outside and inside of the pipeline for estimating the pig's location such as pig signalers at set locations.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These drawings illustrate certain aspects of some examples of the present disclosure and should not be used to limit or define the disclosure.
- (2) FIG. 1A illustrates a pipeline with an object disposed downstream to a pressure transducer, in accordance with examples of the present disclosure;
- (3) FIG. 1B illustrates a pipeline with an object disposed upstream to the pressure transducer, in accordance with examples of the present disclosure;
- (4) FIG. 2 illustrates a flow chart for locating and tracking of moving or stationary objects within pipelines and/or wellbores, in accordance with examples of the present disclosure;
- (5) FIG. 3 illustrates a pressure response during object tracking, in accordance with examples of the present disclosure;
- (6) FIG. 4 illustrates a measured pressure response with noise, in accordance with examples of the present disclosure; and
- (7) FIG. 5 illustrates a map illustrating tracking of an object, in accordance with examples of the present disclosure.

DETAILED DESCRIPTION

- (8) The present disclosure generally relates to systems and methods for monitoring objects within conduits such as pipelines or wellbores, for example. The objects may be moving or stationary. The systems and methods of the present disclosure may allow for non-intrusive location tracking of pipeline pigs or hydrates, among other objects. In some examples, the hydrates may be tracked during hydrate remediation operations.
- (9) The tracking of an object in a conduit may occur in real-time via an analysis of an induced pressure wave and its corresponding response that may travel along the conduit back to the origin or source of the pressure wave inducement. The tracking may be performed by creating or inducing a pressure wave in the conduit and analyzing a pressure response to determine a real-time location, such as a depth or a distance of the object within the conduit, relative to a position of the source of the pressure wave inducement.
- (10) In some examples, at least two pressure waves may be induced to elicit or cause at least two

corresponding pressure responses that may reflect off of a desired target or object, and travel as pressure responses back to the source of the pressure wave inducement for analysis by a system controller. An interaction due to contact between the induced pressure waves and the desired target may result in the pressure responses. The analysis may be automated and repeated to track the objects, and locations of the objects may be indicated on a map that may be accessible via a web portal, for example.

(11) The systems and methods may provide for increased accuracy and distance capability over other acoustic methods. For example, numerous sensors positioned along a pipeline to track the pig, such as microphones or externally mounted pig-tracking devices are not required. Rather, flow rates and pressure losses in the conduit may be measured at or near a pig launching station (“pig launcher”) or a pig receiving station (“pig receiver”), using two or more pressure waves.

(12) Further, tracking of objects along an entire length of a conduit may occur, rather than only progress or movement past set locations. The real-time tracking may allow for an accurate assessment of time duration for operating a pig in the pipeline (“pigging”).

(13) In some examples, a system controller and a pressure measurement device may be operatively coupled to existing infrastructure such as at an end of a pipeline that may include the pig receiver or the pig launcher. A device for inducing the pressure waves by controlling flow of a fluid, may be a component of the existing infrastructure, such as a valve, a pump, and/or a supply vessel, for example. Each of the components may be positioned to control a flow of fluid within a conduit to induce pressure waves.

(14) FIG. 1A illustrates a conduit **100** with an object **101** disposed upstream of a pressure transducer **104**, in accordance with examples of the present disclosure. The conduit **100** may represent a pipeline or a wellbore, in certain examples. The pressure transducer **104** may be in fluid communication with contents of the conduit **100** to indicate an internal pressure of the conduit **100**. The pressure transducer **104** may sample data at a rate of at least 1 kilohertz (kHz), such as 1-4 kHz or higher, for example. In some examples, the pressure transducer **104** may measure pressures up to about 10,000 pounds per square inch (psi) or about 690 bar.

(15) The object **101** may include a variety of debris **102** (e.g., hydrates) that may impede a flow of fluid(s) therethrough. Additionally, the object **101** may include a pipeline pig **106**, in some examples. The conduit **100** may also include a passage (e.g., valve **108**) to control flow such as an ingress or egress of fluid. Rapid opening and closing of the valve **108** may induce pressure waves within the conduit **100**. The valve **108** may open and close within seconds. In some examples, longer durations may also be utilized work, but interpretation of the reflected waves may be more difficult. In some examples, 5 seconds may be the maximum open time. In other examples, the valve **108** may remain open for 1 second or less before it is closed. In some examples, the pressure transducer **104** and the valve **108** may be disposed downstream to the object at an end of the conduit **100** such as at or adjacent to a pig receiver **109**. It should be noted that the pressure transducer **104** and the valve **108** may alternatively be disposed upstream to the object such as at or adjacent to a pig launcher (not shown). In particular examples, multiple pressure transducers and valves may be utilized in both upstream and/or downstream directions.

(16) The pressure waves may include positive and/or negative pressure waves which may be induced by manipulation of the valve **108**, for example. In certain examples, a negative pressure wave may be induced within the conduit **100**. In addition to the valve **108**, a number of suitable techniques may be used for inducing the pressure waves. For example, reciprocating pump **113** may remove fluid from the conduit **100** to induce a negative pressure wave. By way of further example, fluid may be released from the conduit **100** into an expansion vessel **115**. In some examples, a valve **119** may be used to bleed of fluid from the conduit **100**.

(17) In addition to or in combination with the negative pressure, a positive pressure wave may also be induced in the conduit **100**. In some examples, the valve **108** may be utilized to induce the positive pressure wave. In additional examples, a supply tank or a supply vessel **117** may supply

fluid into the conduit **100** to induce the positive pressure wave in the conduit **100**. In some examples, the supply vessel **117** may utilize a pump **118** to move fluid into the conduit **100**. The supply vessel **117** may provide any suitable fluids into the conduit **100**. Non-limiting examples may include gas such as nitrogen into a gas system, or water (or other suitable liquid) into a liquid system. By way of further example, fluid such as nitrogen may be flowed into the conduit **100** via the supply vessel **117**.

(18) The reciprocating pump **113** and the vessels **115** and **117** may be in fluid communication with the conduit **100** via valves **121** and/or conduits **123**. It should be noted that mechanisms to induce pressure waves such as those described herein, for example, may be disposed at various locations along the conduit **100**. The locations may be upstream and/or downstream to the object **101** or a desired target. The pressure waves may be induced at regular intervals, or the intervals may be variable. In some examples, there may be multiple objects at multiple locations in the conduit **100**. In particular examples, sonic waves may be induced at regular or variable intervals and may be utilized in accordance with examples of the present disclosure. In some examples, the inducement of the pressure waves may occur manually. In other examples, the inducement of pressure waves may be automated via a system controller.

(19) In some examples, a system controller **110** may control fluid flow into and out from the conduit **100**. For example, the system controller **110** may be operable to control the valve **108**, the pumps **113** and **118**, and/or the valves **121** to induce the pressure waves that may travel through the conduit **100** eliciting a pressure response. The pressure response includes a reflected pressure wave that has been reflected off the object **101** (or the desired target) back to the source of the pressure wave inducement. The reflected pressure wave or response may be measured by the pressure transducer **104** and recorded at an ultra-high rate (e.g., at least 1 kHz, such as 1-4 kHz or higher) by the system controller **110** for analysis, such as determining pressure profiles of single phase and multi-phase fluids in the conduit **100** and/or determining a location of an object in the conduit **100**. Upon manipulating a component (e.g., a valve, pump, and/or vessel) of a hydraulic system, a fluid flow may temporarily be stopped or restricted to induce a pressure wave in the conduit **100**, and a pressure in the conduit **100** may be continuously recorded at a point upstream to the component, using the Joukowsky equation, for example:

$$\Delta p_{\text{sub.a}} = \rho u a \quad (1)$$

(20) where $\Delta p_{\text{sub.a}}$ represents a surge pressure; ρ represents a fluid density, u represents a fluid flowing velocity and a represents the speed of sound in the fluid, to estimate the magnitude of the water hammer and using the Darcy-Weisbach equation:

$$(21) \quad p_f = \left(\frac{f}{2}\right) \left(\frac{L}{d}\right) \rho u^2 \quad (2)$$

(22) where f is the friction factor, L is a pipe length, d is a pipe diameter, ρ is fluid density and u is fluid velocity, to determine the frictional pressure drop, thereby obtaining a time-log of the pressure change in the conduit. A distance-log of pressure change may be obtained from the time-log and an estimate of the speed of sound in the actual multiphase flow media, using the formula:

$$\Delta L = 0.5 a \Delta t \quad (3)$$

(23) to obtain the relation between time (Δt) and distance (ΔL). This technique may be useful for detecting, tracking, and/or locating leakages, inflow, deposits, and collapses, various objects and/or blockages, for example. In some examples, a system controller may determine the location of the object in a pipeline or wellbore relative to a location of a measured pressure response or a location of the pressure wave inducement via Equations 1 to 3. For example, the system controller may calculate a distance from a pressure transducer to the object as half the distance a pressure wave travels from the time of the pressure wave inducement to the time the pressure response is measured or received by the pressure transducer. The distance between the pressure transducer and the object may be utilized to calculate a distance to the object relative to a pressure inducement location such as a valve or pump, for example.

(24) The system controller **110** may include a display, a storage unit, and/or any instrumentality or aggregate of instrumentalities operable to compute, estimate, classify, process, transmit, receive, retrieve, originate, switch, store, display, manifest, detect, record, reproduce, handle, or utilize any form of information, intelligence, or data for business, scientific, control, or other purposes. For example, the system controller **110** may be a computer, a network storage device, or any other suitable device and may vary in size, shape, performance, functionality, and price. The system controller **110** may include a processing unit (e.g., microprocessor, central processing unit, programmable logic controller (PLC), etc.) that may process data by executing software or instructions obtained from a local non-transitory computer readable media (e.g., optical disks, magnetic disks). The non-transitory computer readable media may store software or instructions of the methods described herein. Non-transitory computer readable media may include any instrumentality or aggregation of instrumentalities that may retain data and/or instructions for a period of time. The non-transitory computer readable media may include, for example, storage media such as a direct access storage device (e.g., a hard disk drive or floppy disk drive), a sequential access storage device (e.g., a tape disk drive), compact disk, CD-ROM, DVD, RAM, ROM, electrically erasable programmable read-only memory (EEPROM), and/or flash memory; as well as communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing.

(25) The system controller **110** may also include input device(s) (e.g., keyboard, mouse, touchpad, etc.) and output device(s) (e.g., monitor, printer, etc.). The input device(s) and output device(s) provide a user interface. For example, the system controller **110** may enable an operator to select and perform analysis, view collected data, view analysis results, and/or perform other tasks. The system controller **110** may be in communication (e.g., wire or wireless) with various components via communication paths **127**. In some examples, the system controller **110** may be operated remotely (e.g., wirelessly) via a device **125** which may include a personal computer, tablet, smartphone, or other digital device. The system controller **110** may be in communication (e.g., wire or wireless) with various components via communication paths **127**. In some examples, the system controller **110** may be battery-powered (e.g., rechargeable lithium-ion battery) with up to 10 hours of operation time and may include piezoelectric switches. In other examples, the system controller **110** may be powered by an electric grid and/or a portable generator.

(26) In some examples, observed pressure, calculated distance traveled, pressure variations in the conduit **100**, and flow lost through or around the object **101** may be calibrated. After the calibration, a pressure measurement near a pig launcher or the pig receiver **109** may be continuously monitored and used to calculate the object's location in real time.

(27) FIG. 1B illustrates an alternate configuration of the pressure transducer **104** relative to the object **101** in the conduit **100**, in accordance with examples of the present disclosure. The configuration of FIG. 1B may be similar to that of FIG. 1A, however, the pressure transducer **104** and the valve **108** may be disposed upstream to the object **101** such as at a pig launcher **111**, rather than downstream at the pig receiver **109**, as shown on FIG. 1A, for example. The upstream and downstream configurations of the pressure transducer **104** and/or the valve **108** may facilitate tracking the object **101** from either an upstream direction or a downstream direction. It should be noted that any suitable pig, pig launcher or pig receiver may be utilized.

(28) FIG. 2 illustrates a flow chart for locating and tracking of moving or stationary objects within pipelines and/or wellbores, in accordance with examples of the present disclosure. At step **200**, at least two pressure waves may be induced within a conduit (e.g., the conduits **100** and **130** and sections thereof, shown on FIGS. 1A and 1B). As previously described, the pressure waves may be induced within the conduit by controlling flow into or out of the conduit. The pressure waves may have similar or different properties such as frequencies and/or amplitudes, in some examples. The pressure waves may travel along a bore of the conduit to an object (e.g., the objects **101**, **124**, and **146**, shown on FIGS. 1A and 1B) and reflect back to an end of the pipeline where the waves were

induced or the source of the pressure wave inducement. The reflected pressure waves may be considered pressure responses in the conduit **100**.

(29) At step **202**, the pressure responses in the conduit may be measured. In some examples, the pressure waves may be induced before either pressure response is measured. In other examples, a first response may be measured before a second response is measured. The response waves may be measured by a pressure transducer (e.g., the pressure transducer **104** shown on FIGS. **1A** and **1B**). The pressure transducer may measure the response waves, for example, at an ultra-high sampling rate. The measured pressure response (e.g., response waves) may be measured by a data recorder (e.g., the system controller **110** shown on FIGS. **1A** and **1B**), which may be a high frequency data recorder in some examples.

(30) At step **204**, the preceding steps may be repeated at an interval to provide continuous real-time location updates using Equations 1-3, for example. The analysis of the pressure responses may occur on site or the pressure responses may be transmitted offsite for analysis. A current location may be compared to a previous location to determine a velocity of the object in the conduit. An automated warning system (e.g., the system controller **110** shown on FIGS. **1A** and **1B**) may send a message (e.g., text, email) to a user when an object velocity fails to satisfy a threshold or is deemed to be too high or too low. In certain examples, a flow rate of fluid in a pipeline may be adjusted by an operating plant to decrease or increase the velocity of the object (e.g., pig), as desired.

(31) The automated warning system may also communicate (e.g., email, text message) to a user when the pig or object velocity is zero, indicating that the object is stuck or stationary. In some examples, the interval may be variable or set. A time period for each interval may include any interval longer than the time required for a wave to travel the entire length of the conduit and return to the data recorder (e.g., the pressure transducer **104**). This may be calculated on a case-by-case basis, and kept as short as possible, such as, for example, 1 minute for a 30-kilometer conduit full of water.

(32) Location updates or location information may be transmitted to a web portal to provide a map and live tracking of the object. In some examples, the analysis may be performed on multiple pipelines and resulting data may be cross-referenced to ensure accuracy.

(33) FIGS. **3** and **4** illustrate pressure responses during object tracking, in accordance with examples of the present disclosure. As shown on FIG. **3**, a pressure wave **300** may be induced to contact the object and elicit a pressure response **302** (e.g., a reflection of the pressure wave **300**) and corresponding residual data **304** such as residual pressure waves, for example. The residual data **304** may not be relied upon to track the object. As previously noted, the speed of sound in the fluid and the time from the pressure wave inducement to the first pressure response (e.g., the pressure response **302**) may be calculated. Also, a distance from a pressure transducer to the object in a pipeline or wellbore may be calculated via Equations 1 to 3. For example, the distance to the object from the pressure transducer, may be determined as half the distance the pressure wave **300** travels from the time of the pressure wave inducement to the time the pressure response **302** is measured or received by a pressure transducer. The distance between the pressure transducer and the object may be utilized to calculate a distance to the object relative to a pressure inducement location such as a valve or pump, for example. In some examples, as illustrated on FIG. **4**, measured pressures may include an induced wave **400**, noise **402**, and a pressure response **404**.

(34) In certain examples, systems and methods of the present disclosure may be applicable to either a temporary installation or a permanent installation. For the permanent installation, the system or method may be triggered by a pig signaler or detector, or by an operator manually initiating the techniques described herein with a button or software interface, for example.

(35) FIG. **5** illustrates a map **500** illustrating tracking of an object **502** along a pipeline **504**, in accordance with examples of the present disclosure. The map **500** may be accessed by a user via a web portal and may be accessible via the system controller **110** (e.g., shown on FIGS. **1A** and **1B**), for example. Additionally, information such as distance traveled; time of launch; object velocity;

and object estimated time of arrival may be displayed and also accessed via the web portal. Onsite requirement for processing data may include a 240-volt or 110-volt power supply; internet connection; and a tie-in point for the pressure transducer into the pipeline at the pig launcher or at the pig receiver.

(36) In certain examples, data that may be required for implementation of the techniques described herein may include pipeline route data for maps and estimated time of arrival (ETA) calculations; gas properties; flow rate; and temperature profile(s).

(37) Accordingly, the systems and methods of the present disclosure may allow for identification of objects in conduits such as pipelines and/or wellbores. Additionally, the systems and methods may provide real-time location data for the object; object speed in a conduit; estimated arrival times; and automated warning of the object speed. The systems and methods may include any of the various features disclosed herein, including one or more of the following statements.

(38) Statement 1. A system for non-intrusively tracking an object in a conduit, the system comprising: a component positioned to control flow into or out of a conduit to induce pressure waves in the conduit; a pressure transducer in fluid communication with the conduit, the pressure transducer positioned to measure pressure responses in the conduit due to contact of pressure waves with the object that is in the conduit; and a system controller operable to: receive pressure data from the pressure transducer, wherein the pressure data includes pressure responses to the pressure waves; and determine a distance of the object in the conduit, relative to the component or the pressure transducer, based on the pressure responses.

(39) Statement 2. The system of the statement 1, wherein the pressure transducer is located at a pig launcher that is in fluid communication with the conduit.

(40) Statement 3. The system of the statement 1 or the statement 2, wherein the pressure transducer is located at a pig receiver that is in fluid communication with the conduit.

(41) Statement 4. The system of any one of the preceding statements, wherein a sampling rate of the pressure transducer is 1 kilohertz or higher.

(42) Statement 5. The system of any one of the preceding statements, wherein the component comprises a valve.

(43) Statement 6. The system of any one of the preceding statements, wherein the component comprises a pump.

(44) Statement 7. A method for non-intrusively tracking a pig in a pipeline, the method comprising: controlling a flow into or out of the pipeline to induce pressure waves in the pipeline; measuring, with a pressure transducer, pressure responses in the pipeline due to contact of the pressure waves with the pig; and determining a distance of the pig relative to a location of the pressure transducer or a location of pressure wave inducement, based on the pressure responses.

(45) Statement 8. The method of the statement 7, further comprising measuring pressure responses induced by a reciprocating pump that removes fluid from the pipeline to induce at least two negative pressure waves in the pipeline.

(46) Statement 9. The method of the statement 7 or the statement 8, further comprising inducing at least two negative pressure waves in the pipeline via a release of fluid from the pipeline or inducing at least two positive pressure waves in the pipeline via an addition of fluid into the pipeline.

(47) Statement 10. The method of any one of the statements 7-9, further comprising inducing at least two positive pressure waves in the pipeline via an addition of fluid into the pipeline.

(48) Statement 11. The method of any one of the statements 7-10, further comprising providing continuous real-time location updates of the pig in the pipeline.

(49) Statement 12. The method of any one of the statements 7-11, further comprising allowing access to a map that provides a location of the pig in real-time.

(50) Statement 13. The method of any one of the statements 7-12, further comprising determining at least a velocity, a distance traveled, a time of launch, pig velocity, or an estimated time of arrival for the pig.

- (51) Statement 14. The method of any one of the statements 7-13, further comprising communicating a warning based on a velocity of the pig in the pipeline.
- (52) Statement 15. The method of any one of the statements 7-14, further comprising recording pressure data at a frequency ranging from 1 kilohertz (kHz) to 4 kHz.
- (53) Statement 16. A method for non-intrusively tracking an object in a conduit, the method comprising: controlling a flow into or out of the conduit to induce pressure waves in the conduit; measuring pressure responses in the conduit due to contact of the pressure waves with the object; and determining a distance of the object relative to a wave inducement location, based on the pressure responses.
- (54) Statement 17. The method of the statement 16, further comprising determining at least a velocity, a distance traveled, a time of launch, object velocity, or an estimated time of arrival for the object in real time.
- (55) Statement 18. The method of the statement 16 or 17, further comprising sampling the pressure data at a rate ranging from 1 kHz or higher.
- (56) Statement 19. The method of any one of the statements 16-18, further comprising indicating a location of the object in real-time with a map.
- (57) Statement 20. The method of any one of the statements 16-19, further comprising communicating a warning based on a velocity of the object.
- (58) Although the present disclosure and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations may be made herein without departing from the spirit and scope of the disclosure as defined by the appended claims. The preceding description provides various examples of the systems and methods of use disclosed herein which may contain different method steps and alternative combinations of components. It should be understood that although individual examples may be discussed herein, the present disclosure covers all combinations of the disclosed examples, including, without limitation, the different component combinations, method step combinations, and properties of the system. It should be understood that the compositions and methods are described in terms of “comprising,” “containing,” or “including” various components or steps, the compositions and methods can also “consist essentially of” or “consist of” the various components and steps. Moreover, the indefinite articles “a” or “an,” as used in the claims, are defined herein to mean one or more than one of the elements that it introduces.
- (59) For the sake of brevity, only certain ranges are explicitly disclosed herein. However, ranges from any lower limit may be combined with any upper limit to recite a range not explicitly recited, as well as, ranges from any lower limit may be combined with any other lower limit to recite a range not explicitly recited, in the same way, ranges from any upper limit may be combined with any other upper limit to recite a range not explicitly recited. Additionally, whenever a numerical range with a lower limit and an upper limit is disclosed, any number and any included range falling within the range are specifically disclosed. In particular, every range of values (of the form, “from about a to about b,” or, equivalently, “from approximately a to b,” or, equivalently, “from approximately a-b”) disclosed herein is to be understood to set forth every number and range encompassed within the broader range of values even if not explicitly recited. Thus, every point or individual value may serve as its own lower or upper limit combined with any other point or individual value or any other lower or upper limit, to recite a range not explicitly recited.
- (60) Therefore, the present examples are well adapted to attain the ends and advantages mentioned as well as those that are inherent therein. The particular examples disclosed above are illustrative only and may be modified and practiced in different but equivalent manners apparent to those skilled in the art having the benefit of the teachings herein. Although individual examples are discussed, the disclosure covers all combinations of all of the examples. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. Also, the terms in the claims have their plain, ordinary meaning

unless otherwise explicitly and clearly defined by the patentee. It is therefore evident that the particular illustrative examples disclosed above may be altered or modified and all such variations are considered within the scope and spirit of those examples. If there is any conflict in the usages of a word or term in this specification and one or more patent(s) or other documents that may be incorporated herein by reference, the definitions that are consistent with this specification should be adopted.

Claims

1. A system for non-intrusively tracking a pipeline pig in a pipeline, the system comprising: a component positioned to control flow into or out of the pipeline configured to induce a first pressure wave and a second pressure wave in the pipeline, wherein the first pressure wave and the second pressure wave have different frequencies, amplitudes, or both; a pressure transducer in fluid communication with the pipeline, the pressure transducer positioned to measure a first pressure wave response and a second pressure wave response in the pipeline due to contact of the first pressure wave and the second pressure wave with the pipeline pig that is in the pipeline; and a system controller operable to: receive pressure data from the pressure transducer, wherein the pressure data includes the first pressure wave response and the second pressure wave response; and determine a distance of the pipeline pig in the pipeline, relative to the component or the pressure transducer, based on the first pressure wave response and the second pressure wave response.
2. The system of claim 1, wherein the pressure transducer is located at a pig launcher that is in fluid communication with the pipeline.
3. The system of claim 1, wherein the pressure transducer is located at a pig receiver that is in fluid communication with the pipeline.
4. The system of claim 1, wherein a sampling rate of the pressure transducer is 1 kilohertz or higher.
5. The system of claim 1, wherein the component comprises a valve.
6. A method for non-intrusively tracking a pipeline pig in a pipeline, the method comprising: controlling a flow into or out of the pipeline to induce a first pressure wave and thereafter a second pressure wave in the pipeline, wherein the first pressure wave and the second pressure wave have different frequencies, amplitudes, or both; measuring, with a pressure transducer, a first pressure response corresponding to the first pressure wave and thereafter a second pressure response corresponding to the second pressure wave in the pipeline due to contact of the first pressure wave and the second pressure wave with the pipeline pig, wherein the pressure transducer is in fluid communication with a fluid in the pipeline; and determining a distance of the pipeline pig in the pipeline relative to a location of the pressure transducer or a location of pressure wave inducement, based on the first pressure response and the second pressure response.
7. The method of claim 6, further comprising measuring pressure responses induced by a reciprocating pump that removes fluid from the pipeline to induce at least two negative pressure waves in the pipeline.
8. The method of claim 6, further comprising inducing at least two negative pressure waves in the pipeline via a release of fluid from the pipeline.
9. The method of claim 6, further comprising inducing at least two positive pressure waves in the pipeline via an addition of fluid into the pipeline.
10. The method of claim 6, further comprising providing continuous real-time location updates of the pipeline pig in the pipeline.
11. The method of claim 10, further comprising allowing access to a pipeline map that provides a location of the pipeline pig in real-time, and wherein the pipeline map is continuously updating with the location of the pipeline pig within the pipeline.
12. The method of claim 11, further comprising determining at least a velocity, a distance traveled,

a time of launch, pig velocity, or an estimated time of arrival for the pipeline pig.

13. The method of claim 6, further comprising communicating a warning based on a velocity of the pipeline pig in the pipeline.

14. The method of claim 6, further comprising recording pressure data at a frequency ranging from 1 kilohertz (kHz) to 4 kHz.

15. A method for non-intrusively tracking a pipeline pig in a pipeline, the method comprising: controlling a flow into or out of the pipeline to induce a first pressure wave and thereafter a second pressure wave in the pipeline, wherein the first pressure wave and the second pressure wave have different frequencies, amplitudes or both; measuring a first pressure response corresponding to the first pressure wave and thereafter a second pressure response corresponding to the second pressure wave in the pipeline due to contact of the first pressure wave and the second pressure wave with the pipeline pig using a pressure transducer in fluid communication with a fluid in the pipeline; determining a distance and velocity of the pipeline pig relative to a wave inducement location based on the first pressure response and the second pressure response; and adjusting a flow rate of fluid in the pipeline wherein the adjusting comprises either increasing the velocity of the pipeline pig above a threshold or decreasing the velocity of the below a threshold.

16. The method of claim 15, further comprising determining at least a distance traveled, a time of launch, object velocity, or an estimated time of arrival for the pipeline pig in real time.

17. The method of claim 15, further comprising sampling pressure data at a rate of 1 kilohertz or higher.

18. The method of claim 15, further comprising indicating a location of the pipeline pig in real-time with a map.

19. The method of claim 15, further comprising communicating a warning based on a velocity of the pipeline pig.
