

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412099
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ueda; Masashi

Noise waveform removing device, model training device, noise waveform removing method, model training method, generation model, and wearable device

Abstract

A noise waveform removing device includes one or more processors that are configured to obtain noise-containing movement waveform data; use a trained generation model, to determine a filter contribution rate based on the noise-containing movement waveform data; and generate noise-free movement waveform data, based on the determined filter contribution rate and the noise-containing movement waveform data.

Inventors:	Ueda; Masashi (Tokyo, JP)
Applicant:	CASIO COMPUTER CO., LTD. (Tokyo, JP)
Family ID:	80646017
Assignee:	CASIO COMPUTER CO., LTD. (Tokyo, JP)
Appl. No.:	17/474981
Filed:	September 14, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220092434 A1	Mar. 24, 2022

Foreign Application Priority Data

JP	2020-157821	Sep. 18, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: G10K11/16 (20060101); **G06N3/045** (20230101); **G06N3/088** (20230101); **G10K15/02** (20060101)

U.S. Cl.:

CPC G06N3/088 (20130101); **G06N3/045** (20230101); **G10K11/16** (20130101); **G10K15/02** (20130101);

Field of Classification Search

CPC: G06N (3/088); G06N (3/045); G10K (11/16); G10K (15/02)

USPC: 381/71.1; 381/71.8

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0064397	12/2017	Horikawa et al.	N/A	N/A
2019/0187297	12/2018	Li	N/A	G01S 19/49

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
111564160	12/2019	CN	N/A
111564160	12/2021	CN	G10L 21/0208
2006034479	12/2005	JP	N/A
2016133088	12/2015	WO	N/A

OTHER PUBLICATIONS

Japanese Office Action (and an English language translation thereof) dated Apr. 25, 2023, issued in counterpart Japanese Application No. 2020-157821. cited by applicant

Chinese Office Action (and an English language translation thereof) dated May 29, 2023, issued in counterpart Chinese Application No. 202111083636.3. cited by applicant

Primary Examiner: Hamid; Ammar T

Attorney, Agent or Firm: Holtz, Holtz & Volek PC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application is based upon and claims the benefit of priority under 35 USC § 119 of Japanese Patent Application No. 2020-157821 filed on Sep. 18, 2020, the entire contents of which, including the description, claims, drawings, and abstract, are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present disclosure relates to a noise waveform removing device, a model training device, a noise waveform removing method, a model training method, a generation model, and a wearable device.

2. Description of the Related Art

(3) WO2016/133088 discloses that, in order to detect movement states of a user during exercise such as running or walking, an acceleration sensor is used. By carrying a wearable device such as a smartphone or the like having such a sensor built in, the user can confirm a movement state that is analyzed based on movement waveform data indicating the movement state obtained by the device.

(4) Meanwhile, when carrying such a wearable device, the user may carry the wearable device in a portable bag such as a pouch.

BRIEF SUMMARY OF THE INVENTION

(5) According to an aspect of the present disclosure, a noise waveform removing device includes one or more processors, wherein the one or more processors are configured to obtain noise-containing movement waveform data; use a trained generation model, to determine a filter contribution rate based on the noise-containing movement waveform data; and generate noise-free movement waveform data, based on the determined filter contribution rate and the noise-containing movement waveform data.

(6) Also, according to another aspect of the present disclosure, a model training device includes one or more processors; and one or more memories, wherein the one or more memories are configured to store training data including noise-containing movement waveform data for training and noise-free movement waveform data for training, and wherein the one or more processors are configured to train a generation model that determines a filter contribution rate based on the noise-containing movement waveform data for training, and a discrimination model that discriminates, from the training data, pseudo noise-free movement waveform data generated based on the filter contribution rate and the noise-containing movement waveform data for training, according to a GAN (Generative Adversarial Network).

Description

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

- (1) FIG. 1 is a schematic diagram illustrating a noise waveform removing device and a model training device according to an embodiment in the present disclosure;
- (2) FIGS. 2A-2B are diagrams illustrating a noise-containing movement waveform and a noise-free movement waveform according to an embodiment in the present disclosure;
- (3) FIG. 3 is a block diagram illustrating a hardware configuration of a noise waveform removing device according to an embodiment in the present disclosure;
- (4) FIG. 4 is a block diagram illustrating a hardware configuration of a model training device according to an embodiment in the present disclosure;
- (5) FIG. 5 is a schematic diagram illustrating a noise waveform removing process according to an embodiment in the present disclosure;
- (6) FIG. 6 is a block diagram illustrating a functional configuration of a noise waveform removing device according to an embodiment in the present disclosure;
- (7) FIG. 7 is a flow chart illustrating a noise waveform removing process according to an embodiment in the present disclosure;
- (8) FIG. 8 is a block diagram illustrating a functional configuration of a model training device according to an embodiment in the present disclosure;
- (9) FIG. 9 is a schematic diagram illustrating a model training process according to an embodiment in the present disclosure;
- (10) FIG. 10 is a schematic diagram illustrating a model training process according to another

embodiment in the present disclosure; and

(11) FIG. 11 is a flow chart illustrating a model training process according to an embodiment in the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

(12) Conventionally, movement waveform data detected by a wearable device includes not only waveforms caused by landing impacts as desired data, but also waveforms caused by non-landing impacts as noise, and thereby, the wearable device cannot correctly determine the moving state of the user from the movement waveform data obtained by the inertial sensor.

(13) According to the present disclosure, such noise can be removed from such movement waveform data including the noise. In the following embodiments, a noise waveform removing device that uses a trained generation model, to generate noise-free movement waveform data in which noise caused by non-landing impacts is removed from noise-containing movement waveform data; and a model training device that uses a discrimination model, to train the generation model according to a GAN (Generative Adversarial Network), are disclosed.

(14) [Overview of the Present Disclosure]

(15) To summarize the embodiments to be described below, as illustrated in FIG. 1, a noise waveform removing device **100** inputs noise-containing movement waveform data including noise caused by non-landing impacts into a trained generation model, to obtain a filter contribution rate from the trained generation model. The noise waveform removing device **100** executes filtering according to the filter contribution rate, to remove noise from the noise-containing movement waveform data, so as to generate the noise-free movement waveform data. For example, if noise-containing movement waveform data caused by pouch impacts as illustrated in FIG. 2A is detected by a wearable device to detect movement waveforms, as illustrated in FIG. 2B, the noise waveform removing device **100** executes filtering according to the filter contribution rate output from the trained generation model, to generate noise-free movement waveform data in which noise in a dashed-line oval in FIG. 2A is removed as in a solid-line oval in FIG. 2B.

(16) The generation model is trained by the model training device **200** according to a GAN. In other words, the model training device **200** obtains training data or correct answer data constituted with a pair of noise-containing movement waveform data for training and noise-free movement waveform data for training from a training data database **50**, to train the generation model and the discrimination model corresponding to the generation model, according to the GAN. The generation model generates a filter contribution rate from the noise-containing movement waveform data for training, and the model training device **200** applies filtering to the noise-containing movement waveform data for training according to the output filter contribution rate, to obtain pseudo noise-free movement waveform data.

(17) Once having obtained, as input data, any one of the pseudo noise-free movement waveform data, the noise-containing movement waveform data for training, or the noise-free movement waveform data for training, the discrimination model discriminates whether the input data is pseudo data generated by the generation model, or training data, and further discriminates whether the input data includes noise. The model training device **100** trains the discrimination model so as to output correct discriminated results, and trains the generation model so as to output false discriminated results, according to the GAN.

(18) According to the present disclosure, unlike normal GAN-based learning, instead of generating an output waveform directly, an application strength level of the low-pass filter is generated at each time. Compared to the variety of output waveforms themselves, the variety of the application strength level of the low-pass filter is lower; therefore, the generation model can be trained with a small number of training data items. Also, by adopting the filter contribution rate instead of noise-free movement waveform data as the output of the generation model, the problem of what-is-called mode collapse inherent to the GAN, namely, the problem that the generation model outputs specific data that deceives the discrimination model regardless of the input data, can be avoided.

(19) [Hardware Configuration]

(20) Here, the noise waveform removing device **100** may be installed, for example, in a wearable device, and have a hardware configuration as illustrated in FIG. 3. In other words, the noise waveform removing device **100** includes a CPU (Central Processing Unit) **101**, a memory device **102**, an auxiliary storage device **103**, a sensor **104**, a communication device **105**, and an operation unit **106**.

(21) Various computer programs in the noise waveform removing device **100** including programs or instructions that implement various functions and processes as will be described later, are installed in the auxiliary storage device **103**, and in the case of receiving a start command of the noise waveform removing device **100**, the memory device **102** reads programs and data from the auxiliary storage device **103**, to load them. The auxiliary storage device **103** and the memory device **102** are implemented as non-transitory computer-readable recording media that store programs or instructions. The CPU **101** that functions as a processor executes various functions and processes of the noise waveform removing device **100**, based on sensor data obtained from the sensor **104**, according to programs and various items of data such as parameters necessary to execute the programs, stored in the memory device **102**. The sensor **104** may be an acceleration sensor, a gyro sensor, or the like, to detect various items of data associated with movement of the user. The communication device **105** transmits sensor data to other information terminals such as smartphones, smartwatches, and the like. The operation unit **106** may be a switch for turning on/off the wearable device that has the noise waveform removing device **100** installed; a lamp for indicating a power on/off state; a setting button; a display panel; and the like.

(22) On the other hand, the model training device **200** may be a computer device, for example, a personal computer, server, or the like, and includes a drive device **201**, an auxiliary storage device **202**, a memory device **203**, a CPU **204**, an interface device **205**, and a communication device **206** mutually connected via a bus B.

(23) Various computer programs in the model training device **200** including programs or instructions that implement various functions and processes as will be described later, may be provided with a recording medium **207** such as a CD-ROM (Compact Disk-Read-Only Memory). Once the recording medium **207** on which the programs are recorded is set in the drive device **201**, the programs are installed in the auxiliary storage device **202** from the recording medium **207** via the drive device **201**. However, installation of the programs does not need to be executed with the recording medium **207**; the programs may be downloaded from any external device via a network or the like. The auxiliary storage device **202** stores the installed programs, together with necessary files, data, and the like. In response to receiving a start command of a program, the memory device **203** reads the program and data from the auxiliary storage device **202**, to load them. The auxiliary storage device **202** and the memory device **203** are implemented as non-transitory computer-readable recording media that store programs or instructions. The CPU **204** that functions as a processor executes various functions and processes of the model training device **200**, according to programs and various items of data such as parameters necessary to execute the programs, stored in the memory device **203**. The interface device **205** includes an input device such as a keyboard and a mouse, an output device such as a display and the like, to be used as a user interface with the user. The communication device **206** executes various communication processes for communicating with an external device.

(24) However, the noise waveform removing device **100** and the model training device **200** are not limited to having the hardware configuration described above; for example, the devices may be implemented with any other suitable hardware configuration such as one or more circuits that implement one or more of the functions and processes executed by the noise waveform removing device **100** and the model training device **200**.

(25) [Noise Waveform Removing Device]

(26) Next, with reference to FIGS. 5 and 6, the noise waveform removing device **100** according to

an embodiment in the present disclosure will be described. FIG. 5 is a schematic diagram illustrating a noise waveform removing process according to the embodiment in the present disclosure.

(27) As illustrated in FIG. 5, when noise-containing movement waveform data is detected by an inertial sensor (e.g., an acceleration sensor, gyro sensor, etc.), the noise waveform removing device **100** inputs the noise-containing movement waveform data that includes waveform parts caused by landing impacts and waveform parts caused by non-landing impacts caused by contacts with a pouch including the wearable device, into the trained generation model, and applies low-pass filtering to the entire waveform. In the present embodiment, although low-pass filtering is applied as a filtering technique, the present disclosure is not limited as such; any other appropriate type of filtering that is suitable for noise to be removed may be adopted.

(28) The generation model according to the present disclosure predicts a low-pass filter contribution rate that indicates to what extent low-pass filtering needs to be applied to the noise-containing movement waveform data to remove noise at that time, from sampling data of the noise-containing movement waveform data caused by non-landing impacts.

(29) The noise waveform removing device **100** derives first intermediate movement waveform data by multiplying low-pass filtered noise-containing movement waveform data by the low-pass filter contribution rate R , and further derives second intermediate movement waveform data by multiplying the noise-containing movement waveform data by $(1-R)$. Then, the noise waveform removing device **100** calculates the sum of the first intermediate movement waveform data and the second intermediate movement waveform data, to obtain noise-free movement waveform data in which the noise caused by the pouch impact as illustrated in the figure is removed.

(30) FIG. 6 is a block diagram illustrating a functional configuration of the noise waveform removing device **100** according to an embodiment in the present disclosure. As illustrated in FIG. 6, the noise waveform removing device **100** includes a measurement data obtaining unit **110**, a low-pass filter contribution rate determination unit **120**, and a noise removing unit **130**.

(31) The measurement data obtaining unit **110** obtains noise-containing movement waveform data. Specifically, the measurement data obtaining unit **110** detects movement waveform data of the user from the inertial sensor (e.g., an acceleration sensor, gyro sensor, etc.) carried by the user, namely, noise-containing movement waveform data, and provides the low-pass filter contribution rate determination unit **120** and the noise removing unit **130** with the detected data. For example, the movement waveform data is constituted with acceleration data and/or angular velocity data.

(32) The low-pass filter contribution rate determination unit **120** uses a trained generation model, to determine the low-pass filter contribution rate based on the noise-containing movement waveform data. Specifically, the low-pass filter contribution rate determination unit **120** inputs the noise-containing movement waveform data extracted at a predetermined sampling rate into the trained generation model, to determine the low-pass filter contribution rate R ($0 \leq R \leq 1$) for low-pass filtering to be applied for removing noise caused by non-landing impacts from the noise-containing movement waveform data.

(33) The low-pass filter contribution rate R takes a value indicating the extent or strength level of application of low-pass filtering; with a value of R closer to 1, stronger low-pass filtering is applied to the noise-containing movement waveform data, and with a value of R closer to 0, weaker low-pass filtering is applied to the noise-containing movement waveform data. For example, a value of R closer to 1 is assigned for a waveform part caused by a non-landing impact as a non-desired waveform so as to apply stronger low-pass filtering, whereas a value of R closer to 0 is assigned for a waveform part caused by a landing impact as a desired waveform so as to apply weaker low-pass filtering.

(34) The noise removing unit **130** generates noise-free movement waveform data based on the determined low-pass filter contribution rate and the noise-containing movement waveform data. Specifically, the noise removing unit **130** applies low-pass filtering to the noise-containing

movement waveform data, according to the low-pass filter contribution rate determined by the low-pass filter contribution rate determination unit **120**, and more strongly applies filtering to waveform parts corresponding to the non-landing impacts, to generate pseudo noise-free movement waveform data in which waveform parts corresponding to the landing impacts are maintained. In other words, the noise-free movement waveform data output by the noise removing unit **130** may correspond with movement waveform data in which noise caused by impacts other than the landing impacts of the user and detected by the inertial sensor, is removed from the noise-containing movement waveform data.

(35) In one embodiment, the noise removing unit **130** may generate first intermediate movement waveform data by applying the low-pass filter contribution rate R to the low-pass filtered noise-containing movement waveform data; generate second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data; and synthesize the first intermediate movement waveform data and the second intermediate movement waveform data, to generate pseudo noise-free movement waveform data. In other words, as illustrated in FIG. 5, the noise removing unit **130** applies low-pass filtering to the entire noise-containing movement waveform data obtained from the measurement data obtaining unit **110**, to obtain low-pass filtered noise-containing movement waveform data as illustrated in the figure. Then, the noise removing unit **130** multiplies the low-pass filtered noise-containing movement waveform data by the low-pass filter contribution rate R obtained from the trained generation model, to obtain the first intermediate movement waveform data. Also, the noise removing unit **130** multiplies the noise-containing movement waveform data that is not low-pass filtered, by $(1-R)$, to obtain the second intermediate movement waveform data. Then, the noise removing unit **130** calculates the sum of the first intermediate movement waveform data and the second intermediate movement waveform data, to obtain waveform parts corresponding to non-landing impacts, namely, pseudo noise-free movement waveform data in which the noise is low-pass filtered. Note that measures for obtaining the pseudo noise-free movement waveform data described in the present embodiment is not limited to the method as described above, and the calculation method may be changed, for example, by changing the size of the low-pass filter, or by setting the coefficient of the low-pass filter contribution rate R to a range other than $0 \leq R \leq 1$. For example, the pseudo noise-free movement waveform data may be obtained by setting a coefficient of the contribution rate R' of the low-pass filter to $0 < R \leq 1$, to determine the contribution rate R' by the low-pass filter contribution rate determination unit **120**, and based on a low-pass filtering strength level in the case of applying low-pass filtering to the entirety of noise-containing movement data and the contribution rate R' .

(36) [Noise Waveform Removing Process]

(37) Next, with reference to FIG. 7, a noise waveform removing process according to an embodiment in the present disclosure will be described. The noise waveform removing process is implemented by the noise waveform removing device **100** described above, and may be implemented by, for example, a processor executing a program or instructions. FIG. 7 is a flow chart illustrating a noise waveform removing process according to an embodiment in the present disclosure.

(38) As illustrated in FIG. 7, at Step **S101**, the noise waveform removing device **100** obtains noise-containing movement waveform data. Specifically, the noise waveform removing device **100** obtains movement waveform data from an inertial sensor, such as an acceleration sensor or a gyro sensor, installed in a wearable device carried by the user. The movement waveform data may include not only waveform parts corresponding to landing impacts but also waveform parts corresponding to non-landing impacts caused by contacts between the wearable device having the inertial sensor installed, and a pouch containing the wearable device. The movement waveform data may include movement waveform data items with respect to three axes in a space to be detected by the acceleration sensor.

(39) At Step **S102**, the noise waveform removing device **100** extracts noise-containing movement

waveform data items in a dimension to be processed. For example, in the case where the noise-containing movement waveform data is constituted with movement waveform data items with respect to the respective three axes in the space, the noise waveform removing device **100** may execute the following Steps **S102** to **S106** for each axis.

(40) At Step **S103**, the noise waveform removing device **100** applies low-pass filtering to the extracted noise-containing movement waveform data. Specifically, the noise waveform removing device **100** applies the low-pass filtering to the entire waveform of the noise-containing movement waveform data.

(41) At Step **S104**, the noise waveform removing device **100** inputs the noise-containing movement waveform data at a reference time into the trained generation model, to determine a low-pass filter contribution rate R ($0 \leq R \leq 1$) at the reference time. For example, with a value of R closer to 1, stronger low-pass filtering is applied to the waveform part, and with a value of R closer to 0, weaker low-pass filtering is applied to the waveform part.

(42) At Step **S105**, the noise waveform removing device **100** multiplies the low-pass filtered noise-containing movement waveform data by R , to obtain first intermediate movement waveform data. Also, the noise waveform removing device **100** multiplies the noise-containing movement waveform data by $(1-R)$, to obtain second intermediate movement waveform data. Then, the noise waveform removing device **100** synthesizes the first intermediate movement waveform data and the second intermediate movement waveform data, to obtain noise-free movement waveform data in which waveform parts caused by landing impacts are maintained, and waveform parts caused by non-landing impacts have been filtered out.

(43) At Step **S106**, the noise waveform removing device **100** determines whether all dimensions to be processed have been processed. If all the dimensions have been processed (YES at Step **S106**), the noise waveform removing process is terminated; or if there remains a dimension yet to be processed (NO at Step **S106**), the noise waveform removing device **100** repeats Steps **S102** to **S106**.

(44) [Model Training Device]

(45) Next, with reference to FIGS. **8** to **10**, a model training device **200** according to an embodiment in the present disclosure will be described. The model training device **200** trains a generation model to be provided for the noise waveform removing device **100** described above. Specifically, the model training device **200** trains the generation model that determines a low-pass filter contribution rate from noise-containing movement waveform data, according to a GAN. In other words, corresponding to the generation model, the model training device **200** obtains, as input data, either one of training data or output data from the generation model, to prepare a discrimination model to discriminate whether the input data is the training data or the output data. Then, the model training device **200** trains the discrimination model so as to output correct discriminated results, and trains the generation model so as to output false discriminated results, according to the GAN. In the present embodiment, although low-pass filtering is applied as a filtering technique, the present disclosure is not limited as such; any other appropriate type of filtering that is suitable for noise to be removed may be adopted.

(46) FIG. **8** is a block diagram illustrating a functional configuration of the model training device **200** according to an embodiment in the present disclosure. As illustrated in FIG. **8**, the model training device **200** includes a training data storage unit **210** and a model training unit **220**.

(47) The training data storage unit **210** stores training data including noise-containing movement waveform data for training and noise-free movement waveform data for training. The training data may be referred to as correct answer data. For example, when the user, who carries a wearable device contained in a pouch together with another wearable device attached to the user without being contained in the pouch, performs exercise such as walking, jogging, or the like, movement waveform data is collected simultaneously by the two wearable devices, and thereby, noise-containing movement waveform data for training can be obtained from an inertial sensor of one of

the wearable devices, and noise-free movement waveform data for training can be obtained from an inertial sensor of the other wearable device.

(48) The model training unit **220** trains a generation model that determines a low-pass filter contribution rate based on the noise-containing movement waveform data for training, and a discrimination model that discriminates pseudo noise-free movement waveform data generated based on the low-pass filter contribution rate and the noise-containing movement waveform data for training, according to the GAN.

(49) Specifically, as illustrated in FIG. **9**, the model training unit **220** inputs the noise-containing movement waveform data for training into the generation model to be trained, to obtain the low-pass filter contribution rate R . For example, the generation model may be implemented by a neural network. The model training unit **220** applies low-pass filtering to the entirety of the noise-containing movement waveform data for training, and based on the obtained low-pass filter contribution rate R and the low-pass filtered noise-containing movement waveform data for training, obtains pseudo noise-free movement waveform data. For example, the model training unit **220** may generate first intermediate movement waveform data by applying the low-pass filter contribution rate R to the low-pass filtered noise-containing movement waveform data for training; generate the second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data for training; and synthesize the first intermediate movement waveform data and the second intermediate movement waveform data, to generate the pseudo noise-free movement waveform data.

(50) Then, the model training unit **220** obtains, as input data, either one of the pseudo noise-free movement waveform data output from the generation model, the noise-containing movement waveform data for training, or the noise-free movement waveform data for training, to discriminate whether the input data is pseudo data (False) or training data (Real), and trains the discrimination model to be trained, to become capable of discriminating whether the input data is noise-free (Normal) or not (Noise).

(51) Specifically, in the case where the discrimination model obtains pseudo noise-free movement waveform data as input data, the model training unit **220** trains the discrimination model so as to output discriminated results indicating that the input data is pseudo data (False).

(52) Also, in the case where the discrimination model obtains noise-containing movement waveform data for training as input data, the model training unit **220** trains the discrimination model so as to output discriminated results indicating that the input data is training data (Real) and contains noise (Noise).

(53) Also, in the case where the discrimination model obtains noise-free movement waveform data for training as input data, the model training unit **220** trains the discrimination model so as to output discriminated results indicating that the input data is training data (Real) and noise-free (Normal).

(54) Note that in practice, a discriminated result does not need to be Boolean values of Real/False and Noise/Normal, and may be a real number value that indicates a confidence factor.

(55) On the other hand, the model training unit **220** trains the generation model so as to output discriminated results indicating that pseudo noise-free movement waveform data is training data (Real) and is noise-free (Normal) by the discrimination model. In other words, the generation model is trained so that the discrimination model outputs false discriminated results.

(56) For example, in the case where the generation model and the discrimination model are constituted with neural networks, the model training unit **220** may update parameters of the discrimination model so that the discrimination model outputs correct discriminated results, and update parameters of the generation model so that the discrimination model outputs false discriminated results, according to an error backpropagation method.

(57) Then, until the termination condition is satisfied, the model training unit **220** may repeat the model training process described above. The termination condition may be specified, for example,

such that the model training process has been performed with all prepared training data items.

(58) According to the present embodiment, unlike normal GAN-based learning, instead of generating an output waveform directly, the application strength level of a low-pass filter is generated at each time. Compared to the variety of output waveforms themselves, the variety of the application strength level of the low-pass filter is lower; therefore, the generation model can be trained with relatively fewer training data items, and by having the generation model output a low-pass filter contribution rate instead of the noise-free movement waveform data, the problem of mode disruption inherent to the GAN, namely, the problem that specific data that deceives the discrimination model is output continuously regardless of the input data, can be avoided.

(59) In one embodiment, the model training unit **220** may train the generation model and the discrimination model, based on discriminated results of the discrimination model and a total sum TR of low-pass filter contribution rates at respective times. Specifically, as illustrated in FIG. **10**, for noise-containing movement waveform data for training sampled at a predetermined sampling rate, once having obtained low-pass filtered contribution rates corresponding to the respective samples, the model training unit **220** sums up the obtained low-pass filter contribution rates, to calculate the total sum TR of the low-pass filter contribution rates. The model training unit **220** may train the generation model and the discrimination model, so as to make the total sum TR of the low-pass filtered contribution rates smaller. According to the present embodiment, for waveform parts that are not affected by noise, the effect of low-pass filtering can be suppressed.

(60) [Model Training Process]

(61) Next, with reference to FIG. **11**, a model training process according to an embodiment in the present disclosure will be described. The model training process is implemented by the model training device **200** described above, and may be implemented by, for example, a processor executing a program or instructions. FIG. **11** is a flow chart illustrating the model training process according to the embodiment in the present disclosure.

(62) As illustrated in FIG. **11**, at Step **S201**, the model training device **200** applies low-pass filtering to the entirety of noise-containing movement waveform data for training.

(63) At Step **S202**, the model training device **200** inputs the noise-containing movement waveform data for training into the generation model to be trained, to obtain a low-pass filter contribution rate.

(64) At Step **S203**, the model training device **200** multiplies the noise-containing movement waveform data for training by the low-pass filter contribution rate, to generate pseudo noise-free movement waveform data.

(65) At Step **S204**, the model training device **200** inputs either one of the pseudo noise-free movement waveform data or the training data as input data into a discrimination model to be trained, to obtain discriminated results to determine whether the input data is pseudo data or training data.

(66) At Step **S205**, the model training device **200** trains the discrimination model so that the discrimination model outputs correct discriminated results, and trains the generation model so that the discrimination model outputs false discriminated results. Specifically, in the case where the generation model and the discrimination model are implemented by neural networks, the model training device **200** updates parameters of the discrimination model so that the discrimination model outputs correct discriminated results, and updates parameters of the generation model so that the discrimination model outputs false discriminated results.

(67) At Step **S206**, the model training device **200** determines whether a termination condition has been satisfied. The termination condition may be specified, for example, such that a predetermined number of training data items have been processed. If the termination condition is not satisfied (NO at Step **S206**), the model training device **200** repeats Steps **S201** to **S206** for the next training data item. On the other hand, if the termination condition is satisfied (YES at Step **S206**), the model training device **200** terminates the processing, and provides the noise waveform removing device

100 with the obtained generation model as a trained generation model.

(68) As above, the embodiments according to the present inventive concept have been described in detail; note that the present inventive concept is not limited to the specific embodiments described above, and various modifications and alterations are possible within the scope of the subject matter according to the present inventive concept as set forth in the claims.

Claims

1. A noise waveform removing device comprising: at least one processor, the at least one processor being configured to: obtain noise-containing movement waveform data; using a trained generation model, determine a filter contribution rate based on the noise-containing movement waveform data; generate first intermediate movement waveform data by applying the filter contribution rate denoted as R to filtered noise-containing movement waveform data, the filtered noise-containing movement waveform data being obtained by applying low-pass filtering to the noise-containing movement waveform data; generate second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data; and synthesize the first intermediate movement waveform data and the second intermediate movement waveform data, to generate noise-free movement waveform data.
2. The noise waveform removing device as claimed in claim 1, wherein the at least one processor is configured to obtain the noise-containing movement waveform data from an inertial sensor carried by a user.
3. The noise waveform removing device as claimed in claim 2, wherein the noise-free movement waveform data corresponds to movement waveform data in which noise is removed from the noise-containing movement waveform data, the noise being caused by impacts other than landing impacts of the user and detected by the inertial sensor.
4. A model training device comprising: at least one processor; and at least one memory, wherein: the at least one memory is configured to store training data including noise-containing movement waveform data for training and noise-free movement waveform data for training, the at least one processor is configured to: train a generation model that determines a filter contribution rate based on the noise-containing movement waveform data for training; train a discrimination model that discriminates, from the training data, pseudo noise-free movement waveform data generated based on the filter contribution rate and the noise-containing movement waveform data for training, according to a GAN (Generative Adversarial Network); generate first intermediate movement waveform data by applying the filter contribution rate denoted as R to filtered noise-containing movement waveform data for training, the filtered noise-containing movement waveform data for training being obtained by applying a low-pass filter to the noise-containing movement waveform data for training; generate second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data for training, and synthesize the first intermediate movement waveform data and the second intermediate movement waveform data, to generate the pseudo noise-free movement waveform data.
5. The model training device as claimed in claim 4, wherein: the discrimination model takes, as input data, one of the pseudo noise-free movement waveform data, the noise-containing movement waveform data for training, or the noise-free movement waveform data for training, and the at least one processor is configured to discriminate, based on the discrimination model, whether the input data is pseudo data or training data, and whether the input data contains noise or is noise-free.
6. A model training device as claimed in claim 4, comprising: at least one processor; and at least one memory, wherein: the at least one memory is configured to store training data including noise-containing movement waveform data for training and noise-free movement waveform data for training, the at least one processor is configured to train a generation model that determines a filter contribution rate based on the noise-containing movement waveform data for training, and to train

- a discrimination model that discriminates, from the training data, pseudo noise-free movement waveform data generated based on the filter contribution rate and the noise-containing movement waveform data for training, according to a GAN (Generative Adversarial Network), and the at least one processor is configured to train the discrimination model so as to output correct discriminated results, and to train the generation model so as to output false discriminated results.
7. The model training device as claimed in claim 5, wherein the at least one processor is configured to train the discrimination model so as to output correct discriminated results, and to train the generation model so as to output false discriminated results.
8. A model training device comprising: at least one processor; and at least one memory, wherein: the at least one memory is configured to store training data including noise-containing movement waveform data for training and noise-free movement waveform data for training, the at least one processor is configured to train a generation model that determines a filter contribution rate based on the noise-containing movement waveform data for training, and to train a discrimination model that discriminates, from the training data, pseudo noise-free movement waveform data generated based on the filter contribution rate and the noise-containing movement waveform data for training, according to a GAN (Generative Adversarial Network), and the at least one processor is configured to train the generation model and the discrimination model, based on discriminated results of the discrimination model and a total sum of filter contribution rates at respective times.
9. A noise waveform removing method executed by at least one processor, the method comprising: obtaining noise-containing movement waveform data; using a trained generation model, determining a filter contribution rate based on the noise-containing movement waveform data; generating first intermediate movement waveform data by applying the filter contribution rate denoted as R to filtered noise-containing movement waveform data, the filtered noise-containing movement waveform data being obtained by applying low-pass filtering to the noise-containing movement waveform data; generating second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data; and synthesizing the first intermediate movement waveform data and the second intermediate movement waveform data, to generate noise-free movement waveform data.
10. A model training method executed by at least one processor, the method comprising: storing, in a memory, training data including noise-containing movement waveform data for training and noise-free movement waveform data for training; training a generation model that determines a filter contribution rate based on the noise-containing movement waveform data for training; training a discrimination model that discriminates, from the training data, pseudo noise-free movement waveform data generated based on the filter contribution rate and the noise-containing movement waveform data for training, according to a GAN (Generative Adversarial Network); generating first intermediate movement waveform data by applying the filter contribution rate denoted as R to filtered noise-containing movement waveform data for training, the filtered noise-containing movement waveform data for training being obtained by applying a low-pass filter to the noise-containing movement waveform data for training; generating second intermediate movement waveform data by applying $(1-R)$ to the noise-containing movement waveform data for training; and synthesizing the first intermediate movement waveform data and the second intermediate movement waveform data, to generate the pseudo noise-free movement waveform data.
11. A wearable device comprising: an inertial sensor; and the noise waveform removing device as claimed in claim 1.
-