

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412195
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Liu; Lu

Advertisement display method and electronic device

Abstract

The method includes: An electronic device **100** obtains first personal data (S**1001**); the electronic device **100** constructs a personal knowledge graph based on the first personal data (S**1002**); the electronic device **100** obtains parameter information of first advertisement content from an advertisement server **200** (S**1003**); the electronic device **100** obtains parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph (S**1004**); the electronic device **100** obtains the second advertisement content based on the parameter information of the second advertisement content (S**1005**); and the electronic device **100** displays the second advertisement content on a display (S**1006**).

Inventors:	Liu; Lu (Shenzhen, CN)
Applicant:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Family ID:	80776457
Assignee:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Appl. No.:	18/027040
Filed (or PCT Filed):	September 13, 2021
PCT No.:	PCT/CN2021/117991
PCT Pub. No.:	WO2022/057764
PCT Pub. Date:	March 24, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230325884 A1	Oct. 12, 2023

Foreign Application Priority Data

Publication Classification**Int. Cl.:** G06Q30/00 (20230101); G06N5/022 (20230101); G06Q30/0251 (20230101)**U.S. Cl.:****CPC** G06Q30/0269 (20130101); G06N5/022 (20130101);**Field of Classification Search****USPC:** None

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2009/0063475	12/2008	Pendse	707/999.005	G06F 21/6245
2011/0066497	12/2010	Gopinath	705/14.53	G06Q 30/02
2013/0268396	12/2012	Agevik	705/26.7	G06Q 30/0631
2015/0112818	12/2014	Lombriser	705/14.73	G06Q 30/0277
2016/0180402	12/2015	Sabah	705/14.66	G06F 16/24578
2017/0024375	12/2016	Hakkani-Tur	N/A	G06F 16/337
2017/0255862	12/2016	Li et al.	N/A	N/A
2018/0181996	12/2017	Matthews	N/A	G06Q 30/0269
2020/0065857	12/2019	Lagi	N/A	G06Q 30/0254
2020/0118010	12/2019	Lee	N/A	G06Q 30/0201
2021/0042796	12/2020	Khoury	N/A	G06Q 30/0272
2021/0334857	12/2020	Stoica	N/A	G06Q 30/0242
2022/0067115	12/2021	Zheng	N/A	G06N 5/04

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
106997549	12/2016	CN	N/A
109447713	12/2018	CN	N/A
109800300	12/2018	CN	N/A
110059249	12/2018	CN	G06F 16/9035

110458641	12/2018	CN	G06F 16/367
111291191	12/2019	CN	N/A
111768231	12/2019	CN	G06F 16/367
112102002	12/2019	CN	G06F 16/367
112287125	12/2020	CN	N/A
112805743	12/2020	CN	G06F 21/6245

OTHER PUBLICATIONS

Safavi, Tara, et al. "Personalized knowledge graph summarization: From the cloud to your pocket." 2019 IEEE International Conference on Data Mining (ICDM). IEEE, 2019. (Year: 2019). cited by examiner

Novak, Jasminko, et al. "Discovering, visualizing, and sharing knowledge through personalized learning knowledge maps." International Symposium on Agent-Mediated Knowledge Management. Berlin, Heidelberg: Springer Berlin Heidelberg, 2003. (Year: 2003). cited by examiner

Faber, Lukas, et al. "Adaptive personalized knowledge graph summarization." MLG Workshop (with KDD). 2018. (Year: 2018). cited by examiner

Jiayu Wen: "Research on Personalized Advertising Recommendation Based on Email Platform." Feb. 20, 2020, total 138 pages. cited by applicant

Siraj Munir et al: "An integrated approach: using knowledge graph and network analysis for harnessing digital advertisement." Jan. 22, 2022, total 16 pages. cited by applicant

Primary Examiner: Bekerman; Michael

Attorney, Agent or Firm: Slater Matsil, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is a national stage of International Application No. PCT/CN2021/117991, filed on Sep. 13, 2021, which claims priority to Chinese Patent Application No. 202010990422.3, filed on Sep. 19, 2020. Both of the aforementioned applications are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

(2) This application relates to the field of data processing technologies, and in particular, to an advertisement display method and an electronic device.

BACKGROUND

(3) In recent years, with the progress of network technologies, the Internet has become an important part in people's life. With rapid development of the Internet, advertisement content and an advertisement placement manner have changed greatly.

(4) Currently, for the advertisement placement manner, a crowd-targeted, product-oriented, and technology-based placement mode has been formed. A server first collects service data of a user group. For example, the service data may be a type of an advertisement viewed by the user group and viewing duration, and an operation record of closing or ignoring an advertisement by the user group. The server performs group profiling for the user group based on the service data of the user group. A group profiling result may be a type of an advertisement viewed by the user group for a largest quantity of times, a type of an advertisement that the user group is not interested in, or the like. The server screens a plurality of advertisements in an advertisement pool based on the group profiling result. The server sends a ranked advertisement to an electronic device of a user.

(5) In the foregoing advertisement placement manner, an advertisement is pushed by using behavioral characteristics of a large quantity of user groups, but differences between individual users are not considered, for example, the individual users have different preferences and requirements. In the advertisement recommendation manner, there is a recommendation homogeneity problem, and an optimal advertisement placement effect cannot be achieved.

SUMMARY

(6) This application provides an advertisement display method and an electronic device, to implement an advertisement recommendation solution in which a terminal side and a server side cooperate with each other. In this way, an advertisement placement effect of an advertisement provider is optimized, so that advertisement placement by the advertisement provider is more accurate, to increase economic benefits of the advertisement provider. In addition, a personal knowledge graph of a user is constructed by using personal data stored on the terminal side, and therefore the personal knowledge graph of the user can comprehensively describe a behavioral characteristic of the user, and the personal knowledge graph of the user is constructed on the terminal side, and therefore security of private information of the user is protected.

(7) According to a first aspect, this application provides an advertisement display method. The method includes: An electronic device obtains first personal data of a user, where the first personal data is personal information of the user; the electronic device constructs a personal knowledge graph based on the first personal data, where the personal knowledge graph includes the first personal data and a time at which the first personal data is generated; the electronic device obtains parameter information of first advertisement content from an advertisement server, where the parameter information includes types of the first advertisement content and a link address of the first advertisement content, the first advertisement content is obtained by the advertisement server by screening a plurality of advertisements based on group data, and the first advertisement content includes one or more advertisements; the electronic device obtains parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph; the electronic device obtains the second advertisement content based on the parameter information of the second advertisement content, where the second advertisement content includes one or more advertisements; and the electronic device displays the second advertisement content on a display.

(8) The electronic device may obtain the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph in one or more of the following manners: Manner 1: The electronic device retains parameter information of all advertisements in the parameter information of the first advertisement content, and the electronic device only ranks the first advertisement content in descending order of predicted preference values of the user for types of the advertisements, to obtain the parameter information of the second advertisement content. Manner 2: The electronic device selects parameter information of some advertisements from the parameter information of the first advertisement content, to obtain the parameter information of the second advertisement content. Specifically, the electronic device ranks the first advertisement content in descending order of predicted preference values of the user for types of advertisements, and retains only parameter information of an advertisement whose predicted preference value of the user is greater than a first threshold, to obtain the parameter information of the second advertisement content.

(9) In the method, the electronic device sends an advertisement recommendation request to the advertisement server; the electronic device receives the parameter information of the first advertisement content returned by the advertisement server; and then the electronic device further screens the parameter information of the first advertisement content, to obtain the parameter information of the second advertisement content.

(10) Specifically, the electronic device constructs the personal knowledge graph of the user by using the obtained personal data, and trains a re-ranking model based on the personal knowledge

graph; after the electronic device sends the advertisement recommendation request to the advertisement server, the electronic device receives the parameter information of the first advertisement content sent by the advertisement server; then the electronic device further screens the parameter information of the first advertisement content based on the re-ranking model, to obtain the parameter information of the second advertisement content; and the electronic device obtains the second advertisement content based on the parameter information of the second advertisement content, and recommends the second advertisement content to the user for viewing.

(11) The method implements an advertisement recommendation solution in which a terminal side and a server side cooperate with each other. In this way, an advertisement placement effect of an advertisement provider is optimized, so that advertisement placement by the advertisement provider is more accurate, to increase economic benefits of the advertisement provider. In addition, the personal knowledge graph of the user is constructed by using the personal data stored on the terminal side, and therefore the personal knowledge graph of the user can comprehensively describe a behavioral characteristic of the user, and the personal knowledge graph of the user is constructed on the terminal side, and therefore security of private information of the user is protected.

(12) With reference to the first aspect, in a possible implementation of the first aspect, that the electronic device constructs a personal knowledge graph based on the first personal data specifically includes: The electronic device obtains second personal data from the first personal data, where the second personal data includes relationship knowledge, event knowledge, and entity knowledge; the electronic device stores the relationship knowledge, the event knowledge, and the entity knowledge based on a predetermined structure; and the electronic device constructs the personal knowledge graph of the user based on the relationship knowledge of the predetermined structure, the event knowledge of the predetermined structure, and the entity knowledge of the predetermined structure. In this way, the personal knowledge graph is a data structure that graphically displays an association between personal data. In addition, the personal knowledge graph includes the first personal data and the time at which the first personal data is generated, and the personal knowledge graph may represent a relationship between the personal data and the time, so that the electronic device subsequently updates the personal knowledge graph based on the time.

(13) With reference to the first aspect, in a possible implementation of the first aspect, the first advertisement content is any one or more of the following: a picture, a video, text, and audio. The first advertisement content may further include other content. This is not limited herein in this application.

(14) With reference to the first aspect, in a possible implementation of the first aspect, the electronic device obtains the first personal data of the user at regular intervals. In this way, the electronic device may obtain new first personal data of the user at regular intervals, and add the new first personal data to the personal knowledge graph, to update the personal data of the user in the personal knowledge graph.

(15) With reference to the first aspect, in a possible implementation of the first aspect, the predetermined structure is a 5-tuple structure; and that the electronic device stores the relationship knowledge based on a predetermined structure specifically includes: The electronic device stores the relationship knowledge based on a first 5-tuple structure, where the first 5-tuple structure is “first entity-relationship-second entity-first time point-first time interval”, the relationship represents a relationship between the first entity and the second entity, the first time point is a time at which the relationship is established between the first entity and the second entity, and the first time interval is a time interval between the first time point and a current time point. In this way, the electronic device stores the relationship knowledge of the user as the predetermined structure, to facilitate subsequent construction of the personal knowledge graph. In addition, the first 5-tuple that represents the relationship knowledge includes the first time point and the first time interval, and the electronic device may update the relationship knowledge of the user based on the first time

point and the first time interval.

(16) With reference to the first aspect, in a possible implementation of the first aspect, the predetermined structure is a 5-tuple structure; and that the electronic device stores the event knowledge based on a predetermined structure specifically includes: The electronic device stores the event knowledge based on a second 5-tuple structure, where the second 5-tuple structure is “event-argument-logical relationship-second time point-second time interval”, the argument is an occurrence action of the event, the logical relationship represents a relationship between the event and the argument, the second time point is a time at which the event occurs, and the second time interval is a time interval between the second time point and a current time point. In this way, the electronic device stores the event knowledge of the user as the predetermined structure, to facilitate subsequent construction of the personal knowledge graph. In addition, the second 5-tuple that represents the event knowledge includes the second time point and the second time interval, and the electronic device may update the event knowledge of the user based on the second time point and the second time interval.

(17) With reference to the first aspect, in a possible implementation of the first aspect, the predetermined structure is a 5-tuple structure; and that the electronic device stores the entity knowledge based on a predetermined structure specifically includes: The electronic device stores the entity knowledge based on a third 5-tuple structure, where the third 5-tuple structure is “third entity: third time point-first association weight-fourth entity-second association weight-fifth entity”, the third time point is a time at which the third entity occurs, the first association weight is a degree of association between the third entity and the fourth entity, and the second association weight is a degree of association between the fourth entity and the fifth entity. In this way, the electronic device stores the entity knowledge of the user as the predetermined structure, to facilitate subsequent construction of the personal knowledge graph. In addition, the third 5-tuple that represents the entity knowledge includes the third time point and the third time interval, and the electronic device may update the entity knowledge of the user based on the third time point and the third time interval.

(18) With reference to the first aspect, in a possible implementation of the first aspect, the electronic device deletes the relationship knowledge whose first time interval is greater than a first threshold from the personal knowledge graph; and/or the electronic device deletes the event knowledge whose second time interval is greater than the first threshold from the personal knowledge graph; and/or the electronic device determines a third time interval between the third time point and the current time point based on the third time point; and the electronic device deletes the entity knowledge whose third time interval is greater than the first threshold from the personal knowledge graph. In this way, the electronic device may delete user knowledge whose time interval is greater than the first threshold from the personal knowledge graph based on time, and remove user knowledge in an early time period. Therefore, the personal knowledge graph can better represent a behavioral characteristic of the user in a recent time period.

(19) With reference to the first aspect, in a possible implementation of the first aspect, after the electronic device constructs the personal knowledge graph based on the first personal data of the user, the method further includes: The electronic device obtains a historical behavior of the user and historical advertisement information displayed by the electronic device; the electronic device uses the historical advertisement information and the personal knowledge graph as an input to the re-ranking model, where the re-ranking model outputs a first result; and the electronic device compares the first result with the historical behavior of the user, and modifies a parameter of the re-ranking model until the first result that is output by the re-ranking model falls within a preset range, to obtain a first model; and that the electronic device obtains parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph specifically includes: The electronic device obtains the parameter information of the second advertisement content from the parameter information of the first

advertisement content based on the first model. In this way, the electronic device trains the re-ranking model based on the personal knowledge graph, to obtain the first model. The electronic device may obtain the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the first model.

(20) With reference to the first aspect, in a possible implementation of the first aspect, that the electronic device obtains the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the first model specifically includes: The electronic device ranks the types of the first advertisement content in descending order of predicted preference values of the user based on the first model, to obtain the parameter information of the second advertisement content; or the electronic device ranks the types of the first advertisement content in descending order of predicted preference values of the user based on the first model, and obtains a type of an advertisement whose predicted preference value of the user is greater than the first threshold, to obtain the parameter information of the second advertisement content. In this way, the electronic device obtains the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the predicted preference value of the user, so that the advertisement displayed by the electronic device better meets a preference of the user. In this way, an advertisement recommendation effect can be improved.

(21) With reference to the first aspect, in a possible implementation of the first aspect, before the electronic device obtains the second personal data from the first personal data, the method further includes: The electronic device converts the first personal data into text information; and the electronic device performs sentence segmentation, word segmentation, and part-of-speech tagging on the text information; and that the electronic device obtains second personal data from the first personal data specifically includes: The electronic device obtains a word that belongs to a preset part of speech from the text information. In this way, the electronic device removes data that cannot represent the behavioral characteristic of the user from the first personal data. The electronic device removes useless data, so that the obtained second personal data can better describe the behavioral characteristic of the user, and the constructed personal knowledge graph can more accurately represent the behavioral characteristic of the user.

(22) With reference to the first aspect, in a possible implementation of the first aspect, after the electronic device obtains the word that belongs to the preset part of speech from the text information, the method further includes: The electronic device obtains a word that appears once in the text information; and if two or more same words appear in the text information, the electronic device obtains one of the two or more same words that appear in the text information, to obtain the second person data. In this way, the electronic device removes repeated data, to reduce data redundancy.

(23) With reference to the first aspect, in a possible implementation of the first aspect, the personal information of the user includes one or more of the following: a gender, an age, a personality, a hobby, an interpersonal relationship, income, contacts information, a call record, a short message service message, memo information, a residence address, and a weather condition at the residence address.

(24) With reference to the first aspect, in a possible implementation of the first aspect, that the electronic device displays the second advertisement content in an advertisement display area of a display specifically includes: The electronic device plays the one or more advertisements in the second advertisement content in descending order of predicted preference values of the user in the second advertisement content; the electronic device plays an advertisement that corresponds to a largest predicted preference value of the user in the second advertisement content; or the electronic device plays the one or more advertisements in the to-be-placed advertisement in descending order of predicted preference values of the user in the second advertisement content, and blocks one or more advertisements played by the electronic device in a first time period in the second

advertisement content. In this way, the electronic device plays the one or more advertisements in the second advertisement content in descending order of the predicted preference values of the user, or plays the advertisement that corresponds to the largest predicted preference value of the user, to better meet a preference of the user. Therefore, there is a higher possibility that the user views the advertisement. In addition, the electronic device blocks the one or more advertisements played by the electronic device in the first time period, to avoid a case in which user experience is affected because a same advertisement is repeatedly recommended in a short time period.

(25) With reference to the first aspect, in a possible implementation of the first aspect, after the electronic device displays the second advertisement content in the advertisement display area of the display, the method further includes: The electronic device obtains viewing data of the user for the second advertisement content, where the viewing data includes advertisement types of one or more advertisements viewed by the user in the second advertisement content and advertisement types of one or more advertisements closed by the user in the second advertisement content; and the electronic device updates the first model based on the viewing data. In this way, the electronic device updates the first model based on the data of viewing an advertisement by the user, so that the first model recommends an advertisement of a type viewed by the user for a largest quantity of times to the user when recommending an advertisement to the user next time, to better meet a requirement of the user.

(26) According to a second aspect, this application provides an electronic device. The electronic device includes one or more processors, one or more memories, and a display. The one or more memories and the display are coupled to the one or more processors. The one or more memories are configured to store computer program code. The computer program code includes computer instructions. The one or more processors invoke the computer instructions, so that the electronic device performs the advertisement display method provided in any one of the first aspect and the implementations of the first aspect.

(27) According to a third aspect, this application provides a computer storage medium. The computer-readable storage medium stores a computer program. When the computer program is executed by a processor, the processor performs the advertisement display method provided in any one of the first aspect and the implementations of the first aspect.

(28) According to a fourth aspect, an embodiment of this application provides a computer program product. A computer-readable storage medium stores a computer program. When the computer program is executed by a processor, the processor performs the advertisement display method provided in any one of the first aspect and the implementations of the first aspect.

(29) In the method, the electronic device constructs the personal knowledge graph of the user by using the obtained personal data, and trains the re-ranking model based on the personal knowledge graph; after the electronic device sends the advertisement recommendation request to the advertisement server, the electronic device receives the parameter information of the first advertisement content sent by the advertisement server; then the electronic device further screens the parameter information of the first advertisement content based on the re-ranking model, to obtain the parameter information of the second advertisement content; and the electronic device obtains the second advertisement content based on the parameter information of the second advertisement content, and recommends the second advertisement content to the user for viewing.

(30) The method implements an advertisement recommendation solution in which a terminal side and a server side cooperate with each other. In this way, an advertisement placement effect of an advertisement provider is optimized, so that advertisement placement by the advertisement provider is more accurate, to increase economic benefits of the advertisement provider. In addition, the personal knowledge graph of the user is constructed by using the personal data stored on the terminal side, and therefore the personal knowledge graph of the user can comprehensively describe a behavioral characteristic of the user, and the personal knowledge graph of the user is

constructed on the terminal side, and therefore security of private information of the user is protected.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a schematic diagram of an advertisement recommendation system according to an embodiment of this application;
- (2) FIG. 2 is a schematic diagram of a structure of an electronic device **100** according to an embodiment of this application;
- (3) FIG. 3 is a block diagram of a software structure of an electronic device **100** according to an embodiment of this application;
- (4) FIG. 4 is a schematic diagram of a hardware structure of an advertisement server **200** according to an embodiment of this application;
- (5) FIG. 5 is a schematic architectural diagram of another advertisement recommendation system according to an embodiment of this application;
- (6) FIG. 6A to FIG. 6E are diagrams of a group of application interfaces according to an embodiment of this application;
- (7) FIG. 7 is a schematic flowchart of an advertisement display method according to an embodiment of this application;
- (8) FIG. 8 is a schematic diagram of graphically representing a constructed personal knowledge graph according to an embodiment of this application;
- (9) FIG. 9A to FIG. 9C are diagrams of a group of UIs according to an embodiment of this application;
- (10) FIG. 10 is a schematic flowchart of another advertisement display method according to an embodiment of this application;
- (11) FIG. 11A to FIG. 11C are diagrams of another group of UIs according to an embodiment of this application;
- (12) FIG. 12 is a schematic architectural diagram of another system according to an embodiment of this application; and
- (13) FIG. 12A is a diagram of a UI according to an embodiment of this application.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

(14) The technical solutions in embodiments of this application are clearly and completely described below with reference to the accompanying drawings. In the description of embodiments of this application, “/” means “or” unless otherwise specified. For example, A/B may represent A or B. In this specification, “or” describes only an association relationship between associated objects, and represents that three relationships may exist. For example, A or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. In addition, in the description of embodiments of this application, “a plurality of” means two or more.

(15) The terms “first” and “second” in the following are merely intended for a purpose of description, and should not be understood as an indication or implication of relative importance or an implicit indication of a quantity of indicated technical features. Therefore, a feature limited by “first” or “second” may explicitly or implicitly include one or more features. In the description of embodiments of this application, unless otherwise specified, “a plurality of” means two or more.

(16) A term “user interface (user interface, UI)” in this specification, claims, and accompanying drawings of this application is a medium interface for interaction and information exchange between an application or an operating system and a user, and implements conversion between an internal form of information and a form acceptable to the user. A user interface of an application is source code written in a specific computer language, for example, Java or an extensible markup

language (extensible markup language, XML). The interface source code is parsed and rendered on a terminal device, and is finally presented as content that can be recognized by a user, for example, a control such as a picture, text, or a button. A control (control) is also referred to as a widget (widget), and is a basic element of a user interface. Typical controls include a toolbar (toolbar), a menu bar (menu bar), a text box (text box), a button (button), a scrollbar (scrollbar), a picture, and text. An attribute and content of a control in the interface are defined by using a tag or a node. For example, the control included in the interface is defined in the XML by using a node, for example, <TextView>, <ImageView>, or <VideoView>. One node corresponds to one control or one attribute in the interface. After being parsed and rendered, the node is presented as content visible to a user. In addition, interfaces of many applications such as a hybrid application (hybrid application) usually further include a web page. A web page, also referred to as a page, may be understood as a special control embedded in an interface of an application. The web page is source code written in a specific computer language, for example, a hypertext markup language (hypertext markup language, HTML), cascading style sheets (cascading style sheets, CSS), or JavaScript (JavaScript, JS). The web page source code may be loaded and displayed as content that can be recognized by a user by a browser or a web page display component that has a function similar to a function of a browser. Specific content included on the web page is defined by using a tag or a node in the web page source code. For example, an element and an attribute of the web page are defined in the HTML by using <p>, , <video>, or <canvas>.

(17) A user interface is usually represented in a form of a graphical user interface (graphical user interface, GUI), and is a user interface that is related to a computer operation and that is graphically displayed. The user interface may be an interface element such as an icon, a window, or a control displayed on a display of an electronic device. The control may include a visual interface element such as an icon, a button, a menu, a tab, a text box, a dialog box, a status bar, a navigation bar, or a widget.

(18) For ease of understanding this application, terms in this application are explained below.

(19) File system: The file system is used to store unstructured personal data generated in a running process of each application in an electronic device. The unstructured personal data is data that cannot be represented by using a two-dimensional logic table. The unstructured personal data may be data such as a document, a picture, a video, or text. For example, the unstructured personal data may be data generated in a running process of a camera application. A picture and a video captured by the camera application are stored in the file system. Therefore, the picture and the video captured by the camera application are unstructured personal data.

(20) Data service: The data service is used to store structured personal data generated in a running process of each application in an electronic device. The structured personal data is data that can be represented by using a uniform structure. For example, the structured personal data may be data generated in a running process of a contacts application. For example, in the data service, a user contact name and a user contact phone number stored in the contacts application are stored in a one-to-one correspondence. The user contact name and the user contact phone number are structured personal data.

(21) Personal data: The personal data includes personal privacy-related data.

(22) Specifically, the personal data may be personal privacy-related data generated in a process in which an electronic device runs each application, and the data generated in the process of each application is stored in a file system and/or a data service. The personal data may further be personal privacy-related data that is directly obtained by the electronic device from each application after obtaining authorization from a user, for example, a communication application, a messaging application, a contacts application, a memo application, a weather application, or a shopping application.

(23) The data generated in the running process of each application in the electronic device is stored in the data service and/or the file system, and the electronic device may obtain the personal data of

the user from the data service and/or the file system.

(24) In addition, the application in the electronic device may obtain authorization from the user, and after obtaining authorization from the user, the electronic device may obtain the personal data of the user from each application. It should be noted that the personal data of the user directly obtained by the electronic device from the application may be classified into structured personal data and unstructured personal data.

(25) Group data: The group data includes data that is of a plurality of users in a user group and that is not related to user privacy, for example, service data generated when the user views an advertisement. For example, one or more of the following may be included: an advertisement frequently tapped by the user, an advertisement never tapped by the user, duration of viewing an advertisement by the user, and an advertisement closed by the user.

(26) Personal knowledge graph: The personal knowledge graph is a data structure that is constructed based on personal data of a user and that graphically displays an association between the personal data.

(27) Personal data of different users is different, and therefore personal knowledge graphs of the different users are different.

(28) Currently, a group knowledge graph is constructed based on group data of a user group, that is, the knowledge graph is a data structure that represents an association between the group data of the user group. The group knowledge graph cannot represent a behavioral characteristic of an individual user.

(29) In this application, an electronic device may construct a personal knowledge graph of each user based on personal data of the user. For a specific process of constructing the personal knowledge graph, refer to detailed description in subsequent method embodiments. Details are not described herein.

(30) Group profile: The group profile is a label generated based on group data for a user group.

(31) The label of the user group may include but is not limited to a type of an advertisement that the user group likes to browse, a type of an advertisement ignored by the user group for a largest quantity of times, a type of an advertisement closed by the user group for a largest quantity of times, or a type of an advertisement reported by the user group for a largest quantity of times.

(32) In some embodiments, the user group is a set of all users regardless of gender, age, and area.

(33) In some embodiments, user groups may be classified based on a gender. For example, the user groups may be classified into a female user group and a male user group. Alternatively, the user groups may be classified into user groups of various age groups, or the like.

(34) For example, when the user groups are classified into a female user group and a male user group, group profiles may be classified into a female user group profile and a male user group profile. Specifically, the group data may be classified into data of the male user group and data of the female user group. The male user group is profiled based on the data of the male user group, that is, the male user group is labeled. For example, the male user group is most interested in a vehicle advertisement, and is not interested in a makeup advertisement. The female user group is profiled based on the data of the female user group, that is, the female user group is labeled. For example, the female user group is interested in a clothing advertisement and a makeup advertisement, and is not interested in a sports advertisement.

(35) For example, when the user groups are classified into user groups of various age groups, the user groups of various age groups may be profiled based on the user groups. Specifically, the group data may be classified based on an age group. For example, data of a user group of users aged between 0 and 20 is classified into one type, data of a user group of users aged between 21 and 35 is classified into one type, data of a user group of users aged between 36 and 50 is classified into one type, and data of a user group of users aged between 51 and 70 is classified into one type. The user groups of various age groups are respectively profiled based on data of the user groups of various age groups, that is, the user groups of various age groups are labeled. For example, the user

group aged between 0 and 20 is most interested in a toy advertisement, the user group aged between 21 and 35 is most interested in an electronic product advertisement, the user group aged between 36 and 50 is most interested in a skin care and hair care advertisement, and the user group aged between 51 and 70 is most interested in a health care advertisement.

(36) Advertisement: The advertisement is a means of spreading information to the public. Advertisements may be classified into a public service advertisement and a for-profit advertisement. The public service advertisement is a non-profit advertising activity that provides free services to the society. The for-profit advertisement may include promotion of various applications, products, or some brands. For example, the for-profit advertisement may be a makeup advertisement, a food advertisement, a music preview recommendation advertisement, a video recommendation advertisement, a novel recommendation advertisement, a movie recommendation advertisement, or an application download recommendation advertisement.

(37) Currently, an advertisement placement procedure may include the following steps:

(38) An advertisement server first receives an advertisement recommendation request sent by an application server, and in response to the advertisement recommendation request, the advertisement server sends an advertisement obtaining request to a vendor server (for example, a mobile phone vendor server).

(39) A function of the advertisement server is to obtain advertisements from vendors and screen the advertisements, and then the advertisement server sends an advertisement obtained through screening to each application for display.

(40) There may be a plurality of vendor servers, for example, the mobile phone vendor server, a vehicle vendor server, and a makeup brand vendor server. The plurality of vendor servers receive the advertisement obtaining request sent by the advertisement server, and when any one of the plurality of vendor servers has a to-be-sent advertisement, the any vendor server may send the to-be-sent advertisement to the advertisement server.

(41) The advertisement server receives advertisements sent by any vendor server, and the advertisement server screens the plurality of advertisements (for example, screens the advertisements in descending order of prices of the advertisements), to obtain an advertisement set.

(42) In some embodiments, the advertisements sent by the any vendor server to the advertisement server may include a repeated advertisement, and the advertisement server may further deduplicate the obtained advertisements to avoid a repeated advertisement.

(43) The advertisement server further screens advertisements in the advertisement set based on group data of a user group, to obtain an advertisement list. The advertisement server sends the advertisement list to the application, and the application displays an advertisement in the advertisement list.

(44) Pre-ranked advertisement: The pre-ranked advertisement is a set of one or more advertisements. The pre-ranked advertisement is obtained by an advertisement server by screening a large quantity of advertisements based on a degree of interest of a user group in the advertisement.

(45) To-be-placed advertisement: The to-be-placed advertisement is a set of one or more advertisements, and is obtained by an electronic device by screening pre-ranked advertisements based on personal data of a user and a probability that the user may tap an advertisement. A quantity of to-be-placed advertisements may be the same as a quantity of pre-ranked advertisements. Alternatively, a quantity of to-be-placed advertisements may be less than a quantity of pre-ranked advertisements. This is because the electronic device may filter out some advertisements from the pre-ranked advertisements based on the personal data of the user.

(46) For ease of understanding this application, an advertisement recommendation system is described below.

(47) FIG. 1 is a schematic diagram of an advertisement recommendation system. The system **10** may include an electronic device **100**, an advertisement server **200**, and an application server **300**

shown in FIG. 1.

(48) The electronic device **100** may be configured to detect a user operation, and in response to the user operation, the electronic device **100** sends a user request to the application server **300**.

(49) For example, the user operation may be that the electronic device **100** detects that a user starts an application or the electronic device **100** detects that a user slides to a current browsing interface of a next video in an application (for example, the electronic device **100** detects that the user slides down to the current browsing interface of the next video with a single finger). In this case, the electronic device **100** sends the user request to the application server **300**.

(50) The application server **300** may be configured to receive and respond to the user request, and the application server **300** sends an advertisement recommendation request to the advertisement server **200**.

(51) The advertisement server **200** may be configured to screen advertisements in an advertisement set based on a group profile of the user, to obtain a pre-ranked advertisement.

(52) The advertisement server **200** may be further configured to send the pre-ranked advertisement to the electronic device **100**.

(53) The electronic device **100** may be further configured to: receive the pre-ranked advertisement sent by the advertisement server **200**, and further screen the pre-ranked advertisement, to obtain a to-be-placed advertisement. Then, the electronic device **100** recommends the to-be-placed advertisement to the user for viewing.

(54) It should be noted that the advertisement recommendation system architecture in FIG. 1 is merely an example implementation in embodiments of this application, and an advertisement recommendation system architecture in embodiments of this application includes but is not limited to the foregoing advertisement recommendation system architecture.

(55) Currently, there are usually two advertisement placement manners. Manner 1: An application server collects service data of viewing an advertisement by a plurality of users, and uploads the service data of the user group to an advertisement server. The advertisement server screens a plurality of advertisements based on the service data of the user group, to obtain a list of advertisements that the user group is interested in. The advertisement server sends the advertisement that the user group is interested in to the user. In this advertisement placement manner, an advertisement is recommended by using the service data of the user group. In this advertisement push manner, differences between individual users are not considered, and there is a recommendation homogeneity problem. Manner 2: An application server collects search information and browsing information of an individual user, and the application server extracts a keyword in the search information and the browsing information to recommend content to the individual user. For example, the individual user searches a shopping application for an item (for example, a headset) that the individual user wants to buy, and when the individual user uses the shopping application next time, the shopping application recommends a plurality of types of headset item information to the individual user. In this recommendation manner, the search information and the browsing information of the user are collected, and for the user, personal privacy of the user is disclosed.

(56) To resolve the foregoing problem, the following embodiments of this application provide an advertisement display method. In the method, an electronic device may receive a user operation. In response to the user operation, the electronic device sends a user request to an application server, the application server sends an advertisement recommendation request to an advertisement server, and the electronic device receives a pre-ranked advertisement (first advertisement content) returned by the advertisement server. Then, the electronic device further screens the pre-ranked advertisement, to obtain a to-be-placed advertisement (second advertisement content). There may be one or more pre-ranked advertisements and one or more to-be-placed advertisements.

(57) In some embodiments, the electronic device may directly receive a pre-ranked advertisement (first advertisement content) returned by an advertisement server. Then, the electronic device

further screens the pre-ranked advertisement, to obtain a to-be-placed advertisement (second advertisement content). The electronic device does not need to send the user request to the application server. This is not limited herein in this application.

(58) Specifically, the electronic device constructs a personal knowledge graph of a user by using obtained personal data, and trains a re-ranking model based on the personal knowledge graph; after the application server sends the advertisement recommendation request to the advertisement server, the electronic device receives the pre-ranked advertisement sent by the advertisement server; then the electronic device further screens the pre-ranked advertisement based on the re-ranking model, to obtain the to-be-placed advertisement; and the electronic device recommends the to-be-placed advertisement to the user for viewing.

(59) In some embodiments, the electronic device may receive parameter information of the first advertisement content from the advertisement server. The parameter information may be information such as a type, a link address, and a size of the first advertisement content. The electronic device obtains parameter information of the second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph. The electronic device obtains the second advertisement content from the advertisement server based on the parameter information of the second advertisement content. This is not limited herein in this application.

(60) The method implements an advertisement recommendation solution in which a terminal side and a server side cooperate with each other. In this way, an advertisement placement effect of an advertisement provider is optimized, so that advertisement placement by the advertisement provider is more accurate, to increase economic benefits of the advertisement provider. In addition, the personal knowledge graph of the user is constructed by using the personal data stored on the terminal side, and therefore the personal knowledge graph of the user can comprehensively describe a behavioral characteristic of the user, and the personal knowledge graph of the user is constructed on the terminal side, and therefore security of private information of the user is protected.

(61) A hardware architecture of an electronic device in embodiments of this application is described below.

(62) FIG. 2 is a schematic diagram of a structure of an electronic device **100**.

(63) This embodiment is described below in detail by using the electronic device **100** as an example. A device type of the electronic device **100** may include a mobile phone, a television, a tablet computer, a sound box, a watch, a desktop computer, a laptop computer, a handheld computer, a notebook computer, an ultra-mobile personal computer (ultra-mobile personal computer, UMPC), a netbook, a personal digital assistant (personal digital assistant, PDA), an augmented reality (augmented reality, AR) device/a virtual reality (virtual reality, VR) device, or the like. The device type of the electronic device **100** is not specially limited in this embodiment of this application.

(64) It should be understood that the electronic device **100** shown in FIG. 2 is merely an example, and the electronic device **100** may include more or fewer components than those shown in FIG. 2, two or more components may be combined, or there may be different component configurations. Components shown in the figure may be implemented by hardware including one or more signal processing and/or application-specific integrated circuits, software, or a combination of hardware and software.

(65) The electronic device **100** may include a processor **110**, an external memory interface **120**, an internal memory **121**, a universal serial bus (universal serial bus, USB) interface **130**, a charging management module **140**, a power management module **141**, a battery **142**, an antenna 1, an antenna 2, a mobile communications module **150**, a wireless communications module **160**, an audio module **170**, a speaker **170A**, a receiver **170B**, a microphone **170C**, a headset jack **170D**, a sensor module **180**, a button **190**, a motor **191**, an indicator **192**, a camera **193**, a display **194**, a

subscriber identification module (subscriber identification module, SIM) card interface **195**, and the like. The sensor module **180** may include a pressure sensor **180A**, a gyroscope sensor **180B**, a barometric pressure sensor **180C**, a magnetic sensor **180D**, an acceleration sensor **180E**, a distance sensor **180F**, an optical proximity sensor **180G**, a fingerprint sensor **180H**, a temperature sensor **180J**, a touch sensor **180K**, an ambient light sensor **180L**, a bone conduction sensor **180M**, and the like.

(66) It may be understood that the structure shown in this embodiment of the present invention does not constitute a specific limitation on the electronic device **100**. In some other embodiments of this application, the electronic device **100** may include more or fewer components than those shown in the figure, some components may be combined, some components may be split, or different component arrangements may be used. The components shown in the figure may be implemented by hardware, software, or a combination of software and hardware.

(67) The processor **110** may include one or more processing units. For example, the processor **110** may include an application processor (application processor, AP), a modem processor, a graphics processing unit (graphics processing unit, GPU), an image signal processor (image signal processor, ISP), a controller, a memory, a video codec, a digital signal processor (digital signal processor, DSP), a baseband processor, or a neural-network processing unit (neural-network processing unit, NPU). Different processing units may be independent devices, or may be integrated into one or more processors.

(68) The controller may be a nerve center and a command center of the electronic device **100**. The controller may generate an operation control signal based on instruction operation code and a time sequence signal, to complete control of instruction reading and instruction execution.

(69) A memory may be further disposed in the processor **110**, and is configured to store instructions and data. In some embodiments, the memory in the processor **110** is a cache. The memory may store instructions or data just used or cyclically used by the processor **110**. If the processor **110** needs to use the instructions or the data again, the processor may directly invoke the instructions or the data from the memory. Therefore, repeated access is avoided, and a waiting time of the processor **110** is reduced, and therefore system efficiency is improved.

(70) In some embodiments, the processor **110** may include one or more interfaces. The interface may include an inter-integrated circuit (inter-integrated circuit, I2C) interface, an inter-integrated circuit sound (inter-integrated circuit sound, I2S) interface, a pulse code modulation (pulse code modulation, PCM) interface, a universal asynchronous receiver/transmitter (universal asynchronous receiver/transmitter, UART) interface, a mobile industry processor interface (mobile industry processor interface, MIPI), a general-purpose input/output (general-purpose input/output, GPIO) interface, a subscriber identity module (subscriber identity module, SIM) interface, a universal serial bus (universal serial bus, USB) interface, or the like.

(71) The charging management module **140** is configured to receive a charging input from a charger. The charger may be a wireless charger or a wired charger. In some embodiments of wired charging, the charging management module **140** may receive a charging input from a wired charger through the USB interface **130**. In some embodiments of wireless charging, the charging management module **140** may receive a wireless charging input through a wireless charging coil of the electronic device **100**. The charging management module **140** may further supply power to the electronic device by using the power management module **141** while charging the battery **142**.

(72) The power management module **141** is configured to be connected to the battery **142**, the charging management module **140**, and the processor **110**. The power management module **141** receives an input from the battery **142** and/or the charging management module **140**, and supplies power to the processor **110**, the internal memory **121**, an external memory, the display **194**, the camera **193**, the wireless communications module **160**, and the like. The power management module **141** may be further configured to monitor parameters such as a battery capacity, a battery cycle count, and a battery state of health (electric leakage and impedance). In some other

embodiments, the power management module **141** may alternatively be disposed in the processor **110**. In some other embodiments, the power management module **141** and the charging management module **140** may alternatively be disposed in a same component.

(73) A wireless communication function of the electronic device **100** may be implemented by using the antenna 1, the antenna 2, the mobile communications module **150**, the wireless communications module **160**, the modem processor, the baseband processor, and the like.

(74) The antenna 1 and the antenna 2 are configured to transmit and receive an electromagnetic wave signal. Each antenna in the electronic device **100** may be configured to cover one or more communication frequency bands. Different antennas may be multiplexed, to improve antenna utilization.

(75) The mobile communications module **150** may provide a wireless communication solution that includes 2G/3G/4G/5G or the like and that is applied to the electronic device **100**. The mobile communications module **150** may include at least one filter, a switch, a power amplifier, a low noise amplifier (low noise amplifier, LNA), and the like. The mobile communications module **150** may receive an electromagnetic wave through the antenna 1, perform processing such as filtering or amplification on the received electromagnetic wave, and transmit the electromagnetic wave to the modem processor for demodulation. The mobile communications module **150** may further amplify a signal obtained after modulation by the modem processor, and convert the signal into an electromagnetic wave for radiation through the antenna 1.

(76) The modem processor may include a modulator and a demodulator. The modulator is configured to modulate a to-be-sent low-frequency baseband signal into a medium or high-frequency signal. The demodulator is configured to demodulate a received electromagnetic wave signal into a low-frequency baseband signal.

(77) The wireless communications module **160** may provide a wireless communication solution that includes a wireless local area network (wireless local area networks, WLAN) (for example, a wireless fidelity (wireless fidelity, Wi-Fi) network), Bluetooth (Bluetooth, BT), a global navigation satellite system (global navigation satellite system, GNSS), frequency modulation (frequency modulation, FM), a near field communication (near field communication, NFC) technology, an infrared (infrared, IR) technology, or the like and that is applied to the electronic device **100**. The wireless communications module **160** may be one or more devices into which at least one communication processing module is integrated. The wireless communications module **160** receives an electromagnetic wave through the antenna 2, performs frequency modulation and filtering processing on an electromagnetic wave signal, and sends a processed signal to the processor **110**. The wireless communications module **160** may further receive a to-be-sent signal from the processor **110**, perform frequency modulation and amplification on the signal, and convert the signal into an electromagnetic wave for radiation through the antenna 2.

(78) The electronic device **100** implements a display function by using the GPU, the display **194**, the application processor, and the like. The display **194** is configured to display an image, a video, and the like. The display **194** includes a display panel.

(79) The electronic device **100** may implement a photographing function by using the ISP, the camera **193**, the video codec, the GPU, the display **194**, the application processor and the like.

(80) In some embodiments, the wireless communication solution provided by the mobile communications module **150** may enable the electronic device to communicate with a device (for example, an advertisement server) in a network, and the WLAN wireless communication solution provided by the wireless communications module **160** may also enable the electronic device to communicate with a device (for example, the advertisement server) in the network.

(81) In some embodiments, the electronic device **100** may send, by using the wireless communications module **160**, an advertisement recommendation request to establish a communication connection to the advertisement server, the electronic device **100** may further receive, by using the wireless communications module **160**, a pre-ranked advertisement sent by the

advertisement server, the electronic device **100** may further screen the pre-ranked advertisement by using the processor **110**, to obtain a to-be-placed advertisement, and the electronic device **100** may be further configured to display the to-be-placed advertisement to the user by using the display **194** for viewing.

(82) The ISP is configured to process data fed back by the camera **193**. For example, during photographing, a shutter is pressed, and light is transmitted to a photosensitive element of the camera through a lens. An optical signal is converted into an electrical signal, and the photosensitive element of the camera transmits the electrical signal to the ISP for processing, to convert the electrical signal into a visible image.

(83) The camera **193** is configured to capture a static image or a video. An optical image of an object is generated through the lens, and is projected onto the photosensitive element.

(84) The digital signal processor is configured to process a digital signal, and may process another digital signal in addition to the digital image signal.

(85) The NPU is a neural-network (neural-network, NN) computing processor, quickly processes input information by referring to a structure of a biological neural network, for example, by referring to a mode of transmission between human brain neurons, and may further continuously perform self-learning.

(86) The external memory interface **120** may be configured to be connected to an external storage card, for example, a micro SD card, to extend a storage capability of the electronic device **100**.

(87) The internal memory **121** may be configured to store computer-executable program code. The executable program code includes instructions. The processor **110** performs various functional applications and data processing of the electronic device **100** by running the instructions stored in the internal memory **121**.

(88) The electronic device **100** may implement an audio function, for example, music play and recording, by using the audio module **170**, the speaker **170A**, the receiver **170B**, the microphone **170C**, the headset jack **170D**, the application processor, and the like.

(89) The audio module **170** is configured to convert digital audio information into an analog audio signal for output, and is further configured to convert an analog audio input into a digital audio signal. The audio module **170** may be further configured to encode and decode an audio signal.

(90) The speaker **170A**, also referred to as a “loudspeaker”, is configured to convert an audio electrical signal into a sound signal. The electronic device **100** may be used to listen to music or answer a hands-free call through the speaker **170A**.

(91) The receiver **170B**, also referred to as an “earpiece”, is configured to convert an electrical audio signal into a sound signal. When a call is answered or audio information is listened to by using the electronic device **100**, the receiver **170B** may be put close to a human ear to listen to a voice.

(92) The microphone **170C**, also referred to as a “mike” or a “mic”, is configured to convert a sound signal into an electrical signal. When making a call or sending speech information, a user may place the mouth of the user near the microphone **170C** to make a sound, to input a sound signal to the microphone **170C**. At least one microphone **170C** may be disposed in the electronic device **100**. In some other embodiments, two microphones **170C** may be disposed in the electronic device **100**, to collect a sound signal and implement a noise reduction function. In some other embodiments, three, four, or more microphones **170C** may alternatively be disposed in the electronic device **100**, to collect a sound signal, implement noise reduction, and identify a sound source, to implement a directional recording function and the like.

(93) In this embodiment, the electronic device **100** collects a sound signal by using the microphone **170C**, and transmits the sound signal to an application in the electronic device **100**.

(94) The headset jack **170D** is configured to be connected to a wired headset. The headset jack **170D** may be a USB interface **130**, or may be a 3.5 mm open mobile terminal platform (open mobile terminal platform, OMTP) standard interface or cellular telecommunications industry

association of the USA (cellular telecommunications industry association of the USA, CTIA) standard interface.

(95) The pressure sensor **180A** is configured to sense a pressure signal, and may convert the pressure signal into an electrical signal. In some embodiments, the pressure sensor **180A** may be disposed on the display **194**. There are many types of pressure sensors **180A**, for example, a resistive pressure sensor, an inductive pressure sensor, and a capacitive pressure sensor. The capacitive pressure sensor may include at least two parallel plates made of conductive materials. When force is applied to the pressure sensor **180A**, capacitance between electrodes changes. The electronic device **100** determines pressure intensity based on a capacitance change. When a touch operation is performed on the display **194**, the electronic device **100** detects intensity of the touch operation by using the pressure sensor **180A**. The electronic device **100** may further calculate a touch location based on a detection signal of the pressure sensor **180A**. In some embodiments, touch operations that are performed at a same touch location but have different touch operation intensity may correspond to different operation instructions. For example, when a touch operation whose touch operation intensity is less than a first pressure threshold is performed on a messaging icon, an instruction for viewing a short message service message is executed. When a touch operation whose touch operation intensity is greater than or equal to the first pressure threshold is performed on the messaging icon, an instruction for creating a new short message service message is executed.

(96) The gyroscope sensor **180B** may be configured to determine a motion posture of the electronic device **100**. In some embodiments, angular velocities of the electronic device **100** around three axes (namely, an x axis, a y axis, and a z axis) may be determined by using the gyroscope sensor **180B**. The gyroscope sensor **180B** may be configured to implement image stabilization during photographing. For example, when the shutter is pressed, the gyroscope sensor **180B** detects an angle at which the electronic device **100** jitters, calculates, based on the angle, a distance for which a lens module needs to compensate, and allows the lens to cancel the jitter of the electronic device **100** through reverse movement, to implement image stabilization. The gyroscope sensor **180B** may be further used in a navigation scenario and a motion-sensing game scenario.

(97) The barometric pressure sensor **180C** is configured to measure barometric pressure. In some embodiments, the electronic device **100** calculates an altitude by using a value of the barometric pressure measured by the barometric pressure sensor **180C**, to assist in positioning and navigation.

(98) The magnetic sensor **180D** includes a Hall sensor. The electronic device **100** may detect opening and closing of a flip holster by using the magnetic sensor **180D**. In some embodiments, when the electronic device **100** is a flip phone, the electronic device **100** may detect opening and closing of a flip cover based on the magnetic sensor **180D**. Further, a feature such as automatic unlocking upon opening of the flip cover is set based on a detected opening or closing state of the holster or the flip cover.

(99) The acceleration sensor **180E** may detect magnitudes of acceleration of the electronic device **100** in various directions (usually on three axes), may detect a magnitude and a direction of gravity when the electronic device **100** is still, and may be further configured to identify a posture of the electronic device, and is used in an application such as switching between a landscape mode and a portrait mode or a pedometer.

(100) The distance sensor **180F** is configured to measure a distance. The electronic device **100** may measure a distance in an infrared manner or a laser manner. In some embodiments, in a photographing scenario, the electronic device **100** may measure a distance by using the distance sensor **180F**, to implement quick focusing.

(101) The optical proximity sensor **180G** may include a light-emitting diode (LED) and an optical detector, for example, a photodiode. The light-emitting diode may be an infrared light-emitting diode. The electronic device **100** emits infrared light by using the light-emitting diode. The electronic device **100** detects infrared reflected light from a nearby object by using the photodiode.

When sufficient reflected light is detected, it may be determined that there is an object near the electronic device **100**. When insufficient reflected light is detected, the electronic device **100** may determine that there is no object near the electronic device **100**. The electronic device **100** may detect, by using the optical proximity sensor **180G**, that the user holds the electronic device **100** close to an ear for making a call, to automatically turn off a screen for power saving. The optical proximity sensor **180G** may also be used in a holster mode and a pocket mode to automatically unlock or lock the screen.

(102) The ambient light sensor **180L** is configured to sense ambient light brightness. The electronic device **100** may adaptively adjust brightness of the display **194** based on the sensed ambient light brightness. The ambient light sensor **180L** may be further configured to automatically adjust white balance during photographing. The ambient light sensor **180L** may further cooperate with the optical proximity sensor **180G** to detect whether the electronic device **100** is in a pocket, to avoid an accidental touch.

(103) The fingerprint sensor **180H** is configured to collect a fingerprint. The electronic device **100** may use a feature of the collected fingerprint to implement fingerprint-based unlocking, application lock access, fingerprint-based photographing, fingerprint-based call answering, and the like.

(104) The temperature sensor **180J** is configured to detect a temperature. In some embodiments, the electronic device **100** executes a temperature processing policy based on the temperature detected by the temperature sensor **180J**. For example, when the temperature reported by the temperature sensor **180J** exceeds a threshold, the electronic device **100** lowers performance of a processor located near the temperature sensor **180J**, to reduce power consumption and implement thermal protection. In some other embodiments, when the temperature is less than another threshold, the electronic device **100** heats the battery **142** to prevent the electronic device **100** from being shut down abnormally due to a low temperature. In some other embodiments, when the temperature is less than still another threshold, the electronic device **100** boosts an output voltage of the battery **142** to avoid abnormal shutdown caused due to a low temperature.

(105) The touch sensor **180K** may also be referred to as a touch panel or a touch-sensitive surface. The touch sensor **180K** may be disposed on the display **194**, and the touch sensor **180K** and the display **194** form a touchscreen, which is also referred to as a “touchscreen”. The touch sensor **180K** is configured to detect a touch operation performed on or near the touch sensor. The touch sensor may transfer the detected touch operation to the application processor to determine a type of a touch event. A visual output related to the touch operation may be provided through the display **194**. In some other embodiments, the touch sensor **180K** may alternatively be disposed on a surface of the electronic device **100**, and is located at a position different from that of the display **194**.

(106) The bone conduction sensor **180M** may obtain a vibration signal. In some embodiments, the bone conduction sensor **180M** may obtain a vibration signal of a vibration bone of a human vocal-cord part. The bone conduction sensor **180M** may be in contact with a human pulse, to receive a blood pressure beating signal. In some embodiments, the bone conduction sensor **180M** may alternatively be disposed in a headset to be combined into a bone conduction headset. The audio module **170** may obtain a voice signal through parsing based on the vibration signal that is of the vibration bone of the vocal-cord part and that is obtained by the bone conduction sensor **180M**, to implement a voice function. The application processor may parse heart rate information based on the blood pressure beating signal obtained by the bone conduction sensor **180M**, to implement a heart rate detection function.

(107) The button **190** includes a power button, a volume button, and the like. The button **190** may be a mechanical button, or may be a touch button. The electronic device **100** may receive a key input, and generate a key signal input related to user settings and function control of the electronic device **100**.

(108) The motor **191** may generate a vibration prompt. The motor **191** may be configured to provide an incoming call vibration prompt and touch vibration feedback. For example, touch

operations performed on different applications (for example, photographing and audio play) may correspond to different vibration feedback effects. The motor **191** may correspond to different vibration feedback effects for touch operations performed on different areas of the display **194**. Different application scenarios (for example, a time reminder, message receiving, an alarm clock, and a game) may also correspond to different vibration feedback effects. A touch vibration feedback effect may be further customized.

(109) The indicator **192** may be an indicator light, and may be configured to indicate a charging status and a power change, or may be configured to indicate a message, a missed call, a notification, and the like.

(110) The SIM card interface **195** is configured to be connected to a SIM card. The SIM card may be inserted into the SIM card interface **195** or removed from the SIM card interface **195**, to come into contact with and be separated from the electronic device **100**. The electronic device **100** may support one or N SIM card interfaces, where N is a positive integer greater than 1. The SIM card interface **195** may support a nano-SIM card, a micro-SIM card, a SIM card, and the like. A plurality of cards may be simultaneously inserted into a same SIM card interface **195**. The plurality of cards may be of a same type or of different types. The SIM card interface **195** may be compatible with different types of SIM cards. The SIM card interface **195** may also be compatible with an external storage card. The electronic device **100** interacts with a network through the SIM card, to implement functions such as conversation and data communication. In some embodiments, the electronic device **100** uses an eSIM, namely, an embedded SIM card. The eSIM card may be embedded into the electronic device **100**, and cannot be separated from the electronic device **100**.

(111) A software system of the electronic device **100** may use a layered architecture, an event-driven architecture, a microkernel architecture, a micro service architecture, or a cloud architecture. In this embodiment of this application, a software structure of the electronic device **100** is described by using the layered architecture.

(112) FIG. 3 is a block diagram of a software structure of an electronic device **100** according to an embodiment of this application.

(113) In a layered architecture, a software system is divided into several layers, and each layer has a clear role and task. The layers communicate with each other through a software interface. In some embodiments, in the layered architecture, the system is divided into four layers: an application layer, an application framework layer, an Android runtime (Android runtime) and system library, and a kernel layer from top to bottom.

(114) The application layer may include a series of application packages.

(115) As shown in FIG. 3, the application package may include applications such as Camera, Gallery, Calendar, Phone, Map, Memo, Contacts, Weather, Music, Video, and Messages.

(116) The application framework layer provides an application programming interface (application programming interface, API) and a programming framework for an application at the application layer. The application framework layer includes some predefined functions.

(117) As shown in FIG. 3, the application framework layer may include a personal knowledge graph manager, a model manager, and the like.

(118) The personal knowledge graph manager is configured to construct a personal knowledge graph of a user. The personal knowledge graph manager includes a knowledge obtaining module, a knowledge fusion module, and a calculation storage module.

(119) The knowledge obtaining module is configured to obtain personal data. The knowledge obtaining module may obtain the personal data of the user from two aspects.

(120) Data generated in a running process of each application in the electronic device is stored in a data service and/or a file system, and the knowledge obtaining module may obtain the personal data of the user from the data service and/or the file system.

(121) In addition, the application in the electronic device may obtain authorization from the user, and after obtaining authorization from the user, the electronic device may obtain the personal data

of the user from each application.

(122) Then, the knowledge obtaining module sends the personal data to the knowledge fusion module.

(123) The knowledge fusion module is configured to: receive the personal data sent by the knowledge obtaining module, preprocess the personal data, and classify preprocessed personal data by relationship, event, and entity based on a machine learning algorithm, to obtain three types of knowledge, namely, relationship knowledge, event knowledge, and entity knowledge, of the user.

(124) User knowledge includes the relationship knowledge, the event knowledge, and the entity knowledge.

(125) The relationship knowledge is user knowledge that is obtained based on the personal data and that is about an interpersonal relationship such as a friend relationship, a colleague relationship, or a family relationship.

(126) The event knowledge is user knowledge that is obtained based on the personal data and that is about a thing that occurs, a thing that is being done, or a thing that does not occur, for example, traveling, going on a business trip, or doing exercise.

(127) The entity knowledge is user knowledge that is obtained based on the personal data and that is about an entity such as a movie or music that the user likes.

(128) It may be learned from the foregoing embodiment that the personal data obtained by the knowledge obtaining module may be classified into structured personal data and unstructured personal data.

(129) The knowledge fusion module may preprocess the unstructured personal data (for example, audio, a video, and a picture). The preprocessing includes converting information included in the unstructured personal data (for example, audio, a video, and a picture) into text information, and then cleansing the text information. The cleansing the text information includes performing word segmentation and part-of-speech tagging on the text information through natural language processing, and deleting a word that does not belong to a preset part of speech from the text information based on the preset part of speech, for example, deleting an article, a preposition, an adverb, a conjunction, a verb, or a modal particle. The preset part of speech may be customized by the user, and the preset part of speech may be set based on an actual requirement.

(130) Then, the knowledge fusion module deduplicates cleansed text information. Deduplication is performed because the personal data of the user obtained by the electronic device **100** from the data service and/or the file system and the personal data of the user directly obtained from each application include repeated data, and when the electronic device **100** directly obtains the personal data of the user from each application, the personal data in each application may also include repeated data. Therefore, the knowledge fusion module deduplicates the cleansed text information to delete repeated data, to reduce data redundancy.

(131) For part-of-speech tagging, refer to Table 1.

(132) TABLE-US-00001

Part of speech	Marker
a Adjective	Distinguish-
b Distinguishing word	Conjunction
c Conjunction	Adverb
d Adverb	Interjection
e Interjection	Noun of locality
f Noun of locality	Morpheme
g Morpheme	Prefix
h Prefix	Idiom
i Idiom	Abbreviation
j Abbreviation	Suffix
k Suffix	Habitual expression
l Habitual expression	Numeral
m Numeral	Noun
n Noun	Onomatopoeic word
o Onomatopoeic word	Preposition
p Preposition	Quantifier
q Quantifier	Pronoun
r Pronoun	Location
s Location	Time word
t Time word	Auxiliary word
u Auxiliary word	Verb
v Verb	Punctuation
w Punctuation	Non-mark morpheme
x Non-mark morpheme	Modal
y Modal	Descriptive
z Descriptive	Personal name particle
nr Personal name particle	Place name
ns Place name	Organization
nt Organization	Other proper name nouns
nz Other proper name nouns	

(133) Part-of-speech tagging may be performed, based on Table 1, on words obtained after word segmentation is performed on the text information. Specifically, “/a” is added after an adjective, “/b” is added after a distinguishing word, “/c” is added after a conjunction, “/d” is added after an adverb, “/e” is added after an interjection, “/f” is added after a noun of locality, “/g” is added after a morpheme, “/h” is added after a prefix, “/i” is added after an idiom, “/j” is added after an abbreviation, “/k” is added after a suffix, “/l” is added after a habitual expression, “/m” is added after a numeral, “/n” is added after a noun, “/o” is added after an onomatopoeic word, “/p” is added

after a preposition, “/q” is added after a quantifier, “/r” is added after a pronoun, “/s” is added after a location word, “/t” is added after a time word, “/u” is added after an auxiliary word, “/v” is added after a verb, “/w” is added after a punctuation mark, “/x” is added after a non-morpheme word, “/y” is added after a modal particle, “/z” is added after a descriptive word, “/nr” is added after a personal name, “/ns” is added after a place name, “/nt” is added after an organization name, and “nz” is added after other proper nouns.

(134) For example, for text information “the television series 1 is starred by an actor 1, and premiered in Apple Video on May 4, 2020”, a result obtained after word segmentation and part-of-speech tagging are performed on the text data is “the television series 1/n is/v starred/v by/p an actor 1/nr, and/c premiered/v in/p Apple/n Video/n on/p May/m 4/m, 2020/m./w”.

(135) Only some example rules for part-of-speech tagging are listed in Table 1. There may further be more rules for part-of-speech tagging, and part-of-speech tagging may be performed with reference to another rule. This is not limited herein in this application.

(136) The knowledge fusion module may preprocess the structured personal data. The preprocessing includes two steps: data cleansing and deduplication. Manners of cleansing and deduplicating the structured personal data are the same as the manners of cleansing and deduplicating the unstructured personal data. Details are not described herein.

(137) The cleansed and deduplicated personal data is input to a machine learning algorithm, and the machine learning algorithm is used to classify preprocessed personal data by relationship knowledge, event knowledge, and entity knowledge.

(138) The machine learning algorithm may be an association rule-based clustering algorithm. An association rule may be preset based on an actual requirement, and then cluster analysis processing is performed on the preprocessed personal data based on the preset association rule, to extract core information (the relationship knowledge, the event knowledge, and the entity knowledge) from the preprocessed personal data. In this method, the core information (the relationship knowledge, the event knowledge, and the entity knowledge) related to the constructed knowledge graph can be more accurately extracted from the preprocessed personal data.

(139) In addition, core information that is not related to the constructed knowledge graph in the preprocessed personal data (second person data) is collectively referred to as basic characteristic data of the user. The basic characteristic data of the user may include a gender and an age of the user, information (for example, a device identifier and a device model) about a device used by the user, and the like.

(140) In addition to the association rule-based clustering algorithm, the machine learning algorithm may be a decision tree classification method, a naive Bayes classification algorithm, a support vector machine-based classification method, or the like. This is not limited herein in this application.

(141) The knowledge fusion module is further configured to send the relationship knowledge, the entity knowledge, and the event knowledge to the calculation storage module.

(142) The calculation storage module is configured to: receive the user knowledge sent by the knowledge fusion module, and store the user knowledge based on a predetermined structure. For example, the user knowledge may be stored based on a 5-tuple structure.

(143) Specifically, the calculation storage module may store the relationship knowledge based on the predetermined structure. The relationship knowledge is stored based on the predetermined structure, so that the relationship knowledge and time are correspondingly stored, to reflect an association between the relationship knowledge and the time. For example, the relationship knowledge and the time may be stored based on a 5-tuple structure (a first 5-tuple structure), and the 5-tuple structure is “entity 1-relationship-entity 2-time point-time interval”.

(144) For example, the relationship knowledge is “I-customer-Mr. Wang-2019.6.8-14”. The relationship knowledge means that I and the customer Mr. Wang met on Jun. 8, 2019 and have known each other for 16 months up to now (for example, Aug. 10, 20202).

(145) The calculation storage module may store the event knowledge based on the predetermined structure. The event knowledge is stored based on the predetermined structure, so that the event knowledge and time are correspondingly stored, to reflect an association between the event knowledge and the time. For example, the event knowledge and the time may be stored based on a 5-tuple structure (a second 5-tuple structure), and the 5-tuple structure is “event-argument-logical relationship-time point-time interval”. Herein, the argument is an action that supports the event, and the logical relationship may be a causal relationship, a sequential relationship, or the like.

(146) For example, the event knowledge is “go on a business trip-buy an air ticket-sequential-2020.9.1-3 days”. The event knowledge expresses the event of going on a business trip, there is a sequential relationship between going on a business trip and buying an air ticket, a departure date is Sep. 1, 2020, and a schedule is 3 days.

(147) The calculation storage module may store the entity knowledge based on the predetermined structure. The entity knowledge is stored based on the predetermined structure, so that the entity knowledge and time are correspondingly stored, to reflect an association between the entity knowledge and the time. For example, the entity knowledge and the time may be stored based on a 5-tuple structure (a third 5-tuple structure), and the 5-tuple structure is “entity 1: time-association weight-entity 2-relationship weight-entity 3”.

(148) For example, the entity knowledge is “television series 1: 2020.4.6-1.0-actor 1-0.8-actor 3”. The entity knowledge indicates that the television series 1 is released on Apr. 6, 2020, a degree of association between the television series 1 and the actor 1 is 1.0, and a degree of association between the actor 1 and the actor 3 is 0.8. This indicates that there is a higher degree of association between the television series 1 and the actor 1.

(149) The calculation storage module is further configured to construct the personal knowledge graph based on the user knowledge of the predetermined structure. The personal knowledge graph graphically displays the user knowledge of the predetermined structure. Refer to a constructed personal knowledge graph that is graphically represented and that is shown in FIG. 8.

(150) The calculation storage module is further configured to send the personal knowledge graph of the user to a personal knowledge graph library for storage.

(151) The model manager includes a characteristic pool and a model pool. The characteristic pool is used to store the personal knowledge graph of the user and the basic characteristic data of the user. A re-ranking model is preset in the model pool. The re-ranking model may be an algorithm such as logistic regression, a decision tree, a factorization machine (Factorization Machine, FM), a field-aware factorization machine (Field-aware Factorization Machine, FFM), or deep learning. The model pool trains the re-ranking model based on the personal knowledge graph of the user and the basic characteristic data of the user. A trained re-ranking model (a first model) may further screen a pre-ranked advertisement, to obtain a to-be-placed advertisement.

(152) How the model pool trains the re-ranking model is described below.

(153) An input of training data of the re-ranking model is historical advertisement information, the basic characteristic data of the user, and the personal knowledge graph, and an output of the training data is a historical behavior of the user.

(154) The re-ranking model may be but is not limited to an algorithm such as logistic regression, a decision tree, an FFM, or deep learning.

(155) Historical advertisement information of a plurality of previously displayed advertisements is stored in the model pool, and the historical advertisement information may be information such as an advertisement ID, advertisement description, and an advertisement size.

(156) The basic characteristic data of the user may include a gender and an age of the user, information (for example, a device identifier and a device model) about a device used by the user, and the like.

(157) The historical behavior of the user may be an advertisement viewed by the user in a past week, duration of viewing an advertisement by the user, an advertisement closed by the user, and

the like.

(158) The input of the training data is input to the re-ranking model, and the re-ranking model outputs a result. The result may be that the user taps and browses an advertisement or that the user does not browse and closes an advertisement. The result is compared with the output of the training data. If the result does not match the output of the training data, a parameter of the re-ranking model is modified, and the re-ranking model continues to be trained. When the result that is output by the re-ranking model matches the historical behavior of the user, model training ends. After training of the re-ranking model is completed, the re-ranking model may predict a probability of tapping each advertisement in the pre-ranked advertisement, in other words, obtain a probability value of tapping each advertisement by the user, and the re-ranking model ranks advertisements in descending order of probability values of tapping the advertisements by the user, to obtain the to-be-placed advertisement.

(159) For example, an interpersonal relationship network of the user may be obtained based on the relationship knowledge recorded in the personal knowledge graph of the user, and whether the user is a social person or an introvert person may be learned based on the interpersonal relationship network. A thing that the user frequently does may be obtained based on the event knowledge recorded in the personal knowledge graph of the user, for example, events such as traveling and going on a business trip. A television series that the user likes to view and the like may be obtained based on the entity knowledge recorded in the personal knowledge graph of the user.

(160) For example, the re-ranking model learns, based on the personal knowledge graph of the user, that the user is a user who likes to view a movie and television series and occasionally goes on a business trip. The pre-ranked advertisement includes a ticket buying advertisement, a movie and television series advertisement, and a friend making advertisement. The re-ranking model predicts a probability for the pre-ranked advertisement, and obtains that a probability of tapping the ticket buying advertisement by the user is 0.5, a probability of tapping the movie and television series advertisement by the user is 0.9, and a probability of tapping the friend making advertisement by the user is 0.4. The re-ranking model re-ranks the pre-ranked advertisement based on the probability of tapping the advertisement by the user, to obtain the to-be-placed advertisement. An arrangement order of the to-be-placed advertisement is the movie and television series advertisement, the ticket buying advertisement, and the friend making advertisement.

(161) The application obtains the re-ranking model, and the application may screen the pre-ranked advertisement based on the trained re-ranking model (the first model), to obtain the to-be-placed advertisement. The to-be-placed advertisement is obtained by screening the advertisements in the pre-ranked advertisement again based on the personal behavioral characteristics of the user, and the to-be-placed advertisement is obtained through ranking performed in descending order of the probabilities that the user may tap and view the advertisements.

(162) How the application screens the pre-ranked advertisement to obtain the to-be-placed advertisement is described below.

(163) In some embodiments, after the application obtains the pre-ranked advertisement, the application obtains the re-ranking model, and ranks, based on the re-ranking model, the pre-ranked advertisement in descending order of the probabilities that the user may tap and view the advertisements, to obtain the to-be-placed advertisement.

(164) In some embodiments, after the application obtains the pre-ranked advertisement, the application obtains the re-ranking model, and the application may retain only an advertisement that corresponds to a highest probability of being tapped and viewed by the user.

(165) In some other embodiments, after the application obtains the pre-ranked advertisement, the application obtains the re-ranking model, and the application may filter out an advertisement that corresponds to a probability that is of being tapped and viewed by the user and that is less than a threshold.

(166) In some other embodiments, after the application obtains the pre-ranked advertisement, the

application obtains the re-ranking model, and ranks, based on the re-ranking model, the pre-ranked advertisement in descending order of the probabilities that the user may tap and view the advertisements, and the application further determines whether each advertisement has been pushed within a specific time (for example, 3 days). If the application determines that some of the advertisements have been pushed within the specific time (for example, 3 days), the application filters out the advertisements that have been pushed within the specific time (for example, 3 days). (167) It should be noted that another manner may be used by the application to screen the pre-ranked advertisement to obtain the to-be-placed advertisement. This is not limited herein in this application.

(168) The model manager at the application layer may provide an interface. An application server sends an advertisement recommendation request to an advertisement server. Then, the application receives a pre-ranked advertisement sent by the advertisement server. The application may obtain authorization from the user, and obtain the re-ranking model through the interface provided by the model manager. The application screens the pre-ranked advertisement by using the re-ranking model, to obtain a to-be-placed advertisement. The application recommends the obtained to-be-placed advertisement to the user for viewing.

(169) In some embodiments, the personal knowledge graph library in the system library may provide an interface. After the application obtains authorization from the user, the application may obtain the personal knowledge graph of the user from the interface. The application may recommend content that the user is interested in to the user by using the personal knowledge graph of the user.

(170) For example, a newly downloaded application has not recorded a behavior of the user, and the newly downloaded application may obtain authorization from the user to obtain the personal knowledge graph of the user. The newly downloaded application may recommend content that the user is interested in to the user by using the personal knowledge graph of the user. The user does not need to select the content that the user is interested in, and the newly downloaded application may perform personalized recommendation based on the personal knowledge graph. In addition, the newly downloaded application may perform personalized recommendation based on the personal knowledge graph, and the recommended content matches the behavioral characteristic of the user, and therefore a content recommendation effect is optimized.

(171) The Android runtime includes a kernel library and a virtual machine. The Android runtime is responsible for scheduling and management of the system.

(172) The kernel library includes two parts: a function that needs to be invoked in a Java language and a kernel library of the system.

(173) The application layer and the application framework layer run on the virtual machine. The virtual machine executes Java files at the application layer and the application framework layer as binary files. The virtual machine is configured to perform functions such as object lifecycle management, stack management, thread management, security and exception management, and garbage collection.

(174) The system library may include a plurality of functional modules, for example, the data service, the file system, the personal knowledge graph library, a surface manager (surface manager), and a three-dimensional graphics processing library (for example, OpenGL ES).

(175) The data service is used to store structured data that is related to user privacy and that is generated in a process in which the electronic device runs an application, for example, data such as a database and a table.

(176) The file system is used to store unstructured data that is related to user privacy and that is generated in the process in which the electronic device runs an application, for example, data such as a document, a picture, and a video.

(177) The personal knowledge graph library is used to store the personal knowledge graph.

(178) The surface manager is configured to: manage a display subsystem and provide fusion of 2D

and 3D layers for a plurality of applications.

(179) The three-dimensional graphics processing library is configured to implement three-dimensional graphics drawing, image rendering, composition, layer processing, and the like.

(180) The kernel layer is a layer between hardware and software. The kernel layer includes at least a display driver, a camera driver, an audio driver, and a sensor driver.

(181) FIG. 4 is a schematic diagram of a hardware structure of an advertisement server **200** according to an embodiment of this application.

(182) The advertisement server **200** may include one or more processors **301**, a memory **302**, a communications interface **303**, a transmitter **305**, a receiver **306**, a coupler **307**, and an antenna **308**. These components may be connected by using a bus **304** or in another manner. In FIG. 3, an example in which the components are connected by using the bus is used.

(183) The communications interface **303** may be used between the advertisement server **200** and another communications device, and the another communications device may be, for example, the foregoing electronic device or another network device. For example, an application server sends an advertisement recommendation request to the advertisement server **200**, the advertisement server **200** receives and responds to the advertisement recommendation request sent by the application server, and the advertisement server **200** sends a pre-ranked advertisement to an application in an electronic device **100**. Specifically, the communications interface **303** may be a long term evolution (LTE) (4G) communications interface. The communications interface is not limited to a wireless communications interface. A wired communications interface **303** may alternatively be disposed in the advertisement server **200** to support wired communication. For example, a backhaul link between the advertisement server **200** and another communications device may be a wired communication connection.

(184) In some embodiments of this application, the transmitter **305** and the receiver **306** may be considered as a wireless modem. The transmitter **305** may be configured to perform transmission processing on a signal output by the processor **301**. The receiver **306** may be configured to receive a signal. In the advertisement server **200**, there may be one or more transmitters **305** and receivers **306**. The antenna **308** may be configured to: convert electromagnetic energy in a transmission line into an electromagnetic wave in free space, or convert an electromagnetic wave in free space into electromagnetic energy in a transmission line. The coupler **307** may be configured to: divide a mobile communication signal into a plurality of signals, and allocate the plurality of signals to a plurality of receivers **306**.

(185) The memory **302** is coupled to the processor **301**, and is configured to store various software programs and/or a plurality of groups of instructions. Specifically, the memory **302** may include a high-speed random access memory, and may further include a nonvolatile memory, for example, one or more magnetic disk storage devices, a flash storage device, or another nonvolatile solid-state storage device.

(186) The memory **302** may store an operating system (which is briefly referred to as a system below), for example, an embedded operating system such as UCOS, VxWorks, or RTLinux. The memory **302** may further store a network communication program. The network communication program may be used to communicate with one or more additional devices, one or more terminal devices, and one or more network devices.

(187) In this embodiment of this application, the processor **301** may be configured to read and execute computer-readable instructions. Specifically, the processor **301** may be configured to: invoke the program stored in the memory **302**, for example, a program for implementing, on a side of the advertisement server **200**, the method provided in one or more embodiments of this application, and execute instructions included in the program.

(188) It should be noted that the hardware structure of the advertisement server **200** shown in FIG. 4 is merely an implementation in this embodiment of this application. In actual application, the advertisement server **200** may further include more or fewer components. This is not limited

herein.

(189) FIG. 5 is a schematic architectural diagram of another advertisement recommendation system according to an embodiment of this application.

(190) As shown in FIG. 5, an electronic device **100** may include a knowledge obtaining module **5101**, a knowledge fusion module **5102**, a calculation storage module **5103**, and a re-ranking module **5104**.

(191) For description of functions of the knowledge obtaining module **5101**, the knowledge fusion module **5102**, the calculation storage module **5103**, and the re-ranking module **5104**, refer to the embodiment shown in FIG. 3. Details are not described herein in this application.

(192) An advertisement server **200** may include an advertisement tapping module **5201**, a dynamic advertisement pool module **5202**, an advertisement pre-ranking module **5203**, and a group profile module **5204**.

(193) The advertisement tapping module **5201** may be configured to receive an advertisement recommendation request sent by an application server, and in response to the advertisement recommendation request sent by the application server, the advertisement tapping module **5201** sends an advertisement bidding request to the dynamic advertisement pool module **5202**.

(194) The dynamic advertisement pool module **5202** may be configured to receive and respond to the advertisement bidding request sent by the advertisement tapping module **5201**.

(195) The dynamic advertisement pool module **5202** may send an advertisement obtaining request to a plurality of advertiser servers, the plurality of advertiser servers receive and respond to the advertisement obtaining request, and the plurality of advertiser servers send advertisements to the dynamic advertisement pool module **5202**. In addition, the dynamic advertisement pool module **5202** screens the advertisements sent by the plurality of advertiser servers (for example, screens the advertisements in descending order of prices of the advertisements), to obtain an advertisement set, and the dynamic advertisement pool module **5202** sends the advertisement set to the advertisement pre-ranking module **5203**.

(196) The advertisement pre-ranking module **5203** may be configured to receive the advertisement set sent by the dynamic advertisement pool module **5202**. The advertisement pre-ranking module **5203** is further configured to receive a group profile sent by the group profile module **5204**. The advertisement pre-ranking module **5203** screens advertisements in the advertisement set based on the group profile, to obtain a pre-ranked advertisement. The pre-ranked advertisement may include one or more advertisements. The advertisement pre-ranking module **5203** sends the pre-ranked advertisement to an application.

(197) The application in the electronic device **100** receives the pre-ranked advertisement sent by the advertisement pre-ranking module **5203**, and obtains a re-ranking model. The application screens the pre-ranked advertisement based on the re-ranking model, to obtain a to-be-placed advertisement. The application recommends the to-be-placed advertisement to a user for viewing.

(198) The group profile module **5204** may be configured to obtain group data of a user group sent by the application server. The group data may be an advertisement tapped by the user group, an advertisement browsed by the user group, an advertisement closed by the user group, duration of browsing an advertisement by the user group, and the like. The group profile module **5204** performs group profiling for the user group based on the group data of the user group. The group profiling is to label the user group based on the group data of the user group, for example, a type of an advertisement that the user group likes to view or a type of an advertisement that the user group does not like to view.

(199) With reference to a user interface on an electronic device, that the electronic device directly obtains personal data of a user from an application is described below.

(200) For example, as shown in FIG. 6A, FIG. 6A shows an example of a user interface **60** of a contacts application in an electronic device.

(201) The user interface **40** may include a status bar **400** and a contacts list **410**.

(202) User contacts may be classified by attributes such as friends, colleagues, and relatives. As shown in FIG. 6A, there may be a friend contact Wang Ke, and a phone number of Wang Ke is 12345; and there may further be a friend contact Li Ke, and a phone number of Li Ke is 23456. There may be a colleague contact Zhang San, and a phone number of Zhang San is 12346; there may further be a colleague contact Lao Wang, and a phone number of Lao Wang is 12045; there may be a colleague contact Zhang San, and a phone number of Zhang San is 12365; there may further be a colleague contact Xiao Li, and a phone number of Xiao Li is 23045; and there may further be a colleague contact Huahua, and a phone number of Huahua is 92345. There may be a relative contact Mom, and a phone number of Mom is 65430.

(203) With reference to a user interface on an electronic device, personal data generated in a process in which the electronic device runs a messaging application is described below by using an example.

(204) The messaging application records short message service message information related to a user, and the electronic device may obtain behavior information related to the user from the short message service message information. For example, if the user buys an air ticket from Beijing to Shanghai by using a ticket buying application, the ticket buying application sends a ticket buying short message service message of the user to the messaging application, and the electronic device may obtain, from the messaging application, a place that the user frequently goes to. For another example, if the user buys a movie ticket by using an application, the application sends a ticket buying short message service message of the user to the messaging application, and the electronic device may obtain, from the messaging application, a type of a movie that the user likes to view.

(205) It may be understood that the electronic device may directly obtain the ticket buying short message service message of the user from the ticket buying application. This is not limited herein in this application.

(206) For example, FIG. 6B shows an example of a user interface **50** of a messaging application in an electronic device.

(207) The user interface **50** may include a status bar **400** and a short message service message content display box **420**.

(208) The short message service message content display box **420** may include short message service message content, and the short message service message content is “The order is EK123456, the seat is a lower berth numbered **24** in the coach **10** of the Z234 train on Aug. 24, 2020, and the train leaves from Shenzhen Station at 12:45, and arrives at Beijing West Station. Please enter the station with your ticket buying certificate. You have bought an electronic ticket. Please check your ticket directly with your ticket buying certificate.”.

(209) The electronic device may learn, based on the short message service message content, that the user is to take a train from Shenzhen Station to Beijing West Station on Aug. 24, 2020, and therefore the electronic device recommends a hotel accommodation advertisement to the user for viewing.

(210) With reference to a user interface on an electronic device, personal data generated in a process in which the electronic device runs a communication application is described below by using an example.

(211) FIG. 6C shows an example of a user interface of a communication application in an electronic device.

(212) The communication application may be a phone application preset in the electronic device. Alternatively, the communication application may be a communication application downloaded by a user from an application store, and the user may make a voice call or a video call with a friend by using the communication application. This is not limited herein in this application.

(213) Description is provided below by using an example in which the communication application is a phone application preset in the electronic device.

(214) When running the phone application, the electronic device may obtain a call frequency

between a user contact and the user based on a call record of the user, and therefore the electronic device may infer intimacy between the user contact and the user based on the call frequency between the user contact and the user.

(215) For example, FIG. 6C shows an example of a user interface **40** of a phone application in an electronic device.

(216) The user interface **40** may include a status bar **400** and a call record list **410**.

(217) The status bar **400** may include a time indicator **4001**, a battery status indicator **4002**, one or more signal strength indicators **4003** of a wireless fidelity (wireless fidelity, Wi-Fi) signal, and one or more signal strength indicators **4004** of a mobile communication signal (which may also be referred to as a cellular signal).

(218) The call record list **410** may include one or more call records. For example, the user made a call to Zhang San at 10:22 this morning, the user made a call to Lao Wang at 11:30 this morning, the user made a call to Huahua at 1:15 this afternoon, the user made a call to Mom at 1:21 this afternoon, the user made a call to Mr. Wang at 2:11 this afternoon, the user made a call to Wang Ke at 6:10 this afternoon, the user made a call to Li Ke at 6:10 this afternoon, the user made a call to Mom at 8:15 this evening, and the user made a call to Mom yesterday. The call record list **410** may further include more or fewer call records. No example is provided herein.

(219) With reference to a user interface on an electronic device, personal data generated in a process in which the electronic device runs a memo application is described below by using an example.

(220) An important thing and time are recorded in the memo application. The electronic device may obtain an important thing and person related to a user from the important thing and time recorded in the memo application, for example, a birthday of a friend and time, a location, and content of a conference. For example, FIG. 6D shows an example of a user interface **70** of a memo application in an electronic device.

(221) The user interface **40** may include a status bar **400** and a “My memo” list **440**.

(222) The “My memo” list **440** may include an important thing, an important person, and time recorded by the user, for example, “Perform work presentation at 2:00 p.m. on August 7, and prepare PPT”, “Wang Ke's birthday is on August 16. Remember to buy a birthday gift”, and “Fly to Beijing on a business trip at 3:00 p.m. on August 20”. The “My memo” list **440** may further record more or fewer important things, important persons, and times. Details are not described herein.

(223) With reference to a user interface on an electronic device, personal data generated in a process in which the electronic device runs a memo application is described below by using an example.

(224) A weather condition of a city preset by a user is recorded in a weather application. The electronic device may obtain a city in which the user is located, a weather condition of the city, and the like from a weather module **2106**.

(225) For example, FIG. 6E shows an example of a user interface **80** of Weather in an electronic device.

(226) The user interface **80** may include a status bar **400** and a weather condition list **450** within a week.

(227) The weather condition list **450** within a week may include a daily weather condition of a location within a week. For example, a location of the electronic device is Nanshan District, Shenzhen, it is currently a cloudy day with a temperature of 29° today (Tuesday), it is a cloudy day with a temperature of 28° at 9:00 p.m. today (Tuesday), it is a cloudy day with a temperature of 28° at 10 p.m. today (Tuesday), it is a cloudy day with a temperature of 27° at 11:00 p.m. today (Tuesday), it is a cloudy day with a temperature of 27° at 00:00 a.m. tomorrow (Wednesday), and it is a cloudy day with a temperature of 27° at 1:00 a.m. tomorrow (Wednesday). It is a shower with a highest temperature of 29° and a lowest temperature of 27° on Wednesday; it is a shower with a highest temperature of 29° and a lowest temperature of 27° on Thursday; it is a shower with a

highest temperature of 29° and a lowest temperature of 27° on Friday; it is a shower with a highest temperature of 29° and a lowest temperature of 27° on Saturday; it is a shower with a highest temperature of 29° and a lowest temperature of 27° on Sunday; and it is a shower with a highest temperature of 29° and a lowest temperature of 27° on next Monday.

(228) In the foregoing UI embodiments, that the electronic device **100** may obtain personal data of a user from the foregoing applications is merely described by using examples. The personal data may alternatively come from another application. Details are not described herein in this application.

(229) FIG. 7 is a schematic flowchart of an advertisement display method according to an embodiment of this application.

(230) The method includes the following steps.

(231) **S701**. An electronic device **100** obtains personal data, and preprocesses the personal data.

(232) Data generated in a running process of each application in the electronic device is stored in a data service and/or a file system, and the electronic device **100** may obtain the personal data of a user from the data service and/or the file system.

(233) In addition, the application in the electronic device may obtain authorization from the user, and after obtaining authorization from the user, the electronic device may directly obtain the personal data of the user from each application.

(234) For example, the electronic device **100** may directly obtain interpersonal relationship knowledge of the user from a contacts application, a communication application, and the like, for example, user knowledge such as a friend relationship of the user, a colleague relationship of the user, a relative of the user, and a customer relationship of the user.

(235) The electronic device **100** may directly obtain user knowledge such as a friend birthday, conference information, a travel city, an academic paper, and a departure date of the user from a messaging application, a memo application, and the like.

(236) The electronic device **100** may obtain user knowledge such as a thing, a city, a singer, and a song name that the user likes, and an actor that the user is interested in from a gallery application.

(237) The electronic device **100** may obtain user knowledge such as a city area in which the user is located, a weather condition, and a motion status from a wearable device (for example, a Bluetooth watch).

(238) For example, the electronic device **100** obtains description information and data of a television series 1 from a video application. The description information and the data of the television series 1 are shown in Table 2.

(239) TABLE-US-00002 TABLE 2 Television series Introduction to the television name series
Release time Television The television series 1 is a hot- The drama premiered in series 1 blooded youth drama directed by Apple Video on May 4, a director 1 and a director 2 and 2020. starred by an actor 1 and an actor 2. The drama tells that Wang Yi is ordered in face of danger to execute one top-secret mission, and during this period, Wang Er and Wang San make a deep friend relationship with Wang Si, Wang Wu, and others in constant misunderstanding and suspicion.

(240) The electronic device **100** is further configured to preprocess the personal data. The reprocessing includes cleansing and deduplicating the personal data. The cleansing the personal data includes performing word segmentation and part-of-speech tagging on text information through natural language processing, and deleting a word that does not belong to a preset part of speech from the text information based on the preset part of speech, for example, deleting an article, a preposition, an adverb, a conjunction, a verb, or a modal particle. The preset part of speech may be customized by the user, and the preset part of speech may be set based on an actual requirement.

(241) The personal data of the user obtained by the electronic device **100** from the data service and/or the file system and the personal data of the user directly obtained from each application include repeated data, and when the electronic device **100** directly obtains the personal data of the

user from each application, the personal data in each application may also include repeated data. Therefore, a knowledge fusion module deduplicates the cleansed text information to delete repeated data, to reduce data redundancy.

(242) For example, that the electronic device **100** preprocesses the obtained description information and data of the television series 1 specifically includes performing word segmentation and part-of-speech tagging on the description information and the data of the television series 1. For a rule for part-of-speech tagging, refer to the embodiment in FIG. 3. Details are not described herein in this application.

(243) A result of preprocessing the description information and the data of the television series 1 by the electronic device **100** is shown in Table 3.

(244) TABLE-US-00003 TABLE 3 Television series Introduction to the television name series
Release time Television The television series 1/n is/v a The drama/r premiered/v in/p series 1/n hot-blooded/a youth drama/n Apple/n Video/n on/p May/m directed/v by/p a director 1/nr 4/m, 2020/m./w and/c a director 2/nr and/c starred/v by/p an actor 1/nr and/c an actor 2/nr./w The drama/r tells/v that/u Wang Yi/nr is/v ordered/v in face of danger/i to/u execute/v one/m top-secret/a mission/n, and/c during this period/l, Wang Er/nr and/c Wang San/nr make/v a deep/a friend relationship/n with/p Wang Si/nr, Wang Wu/nr, and/c others/r in/p constant/a misunderstanding/n and/c suspicion/n./w

(245) For example, the electronic device **100** cleanses, based on the preset part of speech, the description information and the data of the television series 1 obtained after word segmentation and part-of-speech tagging, to obtain words such as a personal name, a place name, a song name, a movie and television series name, time, and an actor. The description information and the data of the television series 1 obtained after word segmentation and part-of-speech tagging are shown in Table 4.

(246) TABLE-US-00004 TABLE 4 Television series name Personal name Time Actor Television series 1/nr Director 1/nr May/m 4/m, 2020/m Actor 1/nr Director 2/nr Actor 2/nr Wang Yi/nr Wang Er/nr Wang San/nr Wang Si/nr Wang Wu/nr

(247) S702. The electronic device **100** classifies preprocessed personal data by relationship, event, and entity based on a machine learning algorithm, to obtain three types of knowledge, namely, relationship knowledge, event knowledge, and entity knowledge, of the user.

(248) For details, refer to the embodiment in FIG. 3. Details are not described herein.

(249) S703. The electronic device **100** stores the user knowledge based on a predetermined structure, and constructs a personal knowledge graph based on the user knowledge of the predetermined structure.

(250) Specifically, the electronic device **100** stores the relationship knowledge based on the predetermined structure. The relationship knowledge is stored based on the predetermined structure, so that the relationship knowledge and time are correspondingly stored, to reflect an association between the relationship knowledge and the time. For example, the relationship knowledge and the time may be stored based on a 5-tuple structure, and the 5-tuple structure is “entity 1-relationship-entity 2-time point-time interval”.

(251) For example, the relationship knowledge is “I-customer-Mr. Wang-2019.6.8-14”. The relationship knowledge means that I and the customer Mr. Wang met on Jun. 8, 2019 and have known each other for 16 months up to now (for example, Aug. 10, 20202).

(252) Herein, a time interval, namely, 203 days, is expressed in a quantity of months, or may be expressed in a quantity of years or a quantity of days. This is not limited in this application.

(253) In some embodiments, the electronic device **100** may alternatively represent only a relationship between entities by using only a time point. A basic format is “entity 1-relationship-entity 2-time point”.

(254) For example, the relationship knowledge is “I-colleague-Zhang San-2019.4.5”. The relationship knowledge means that I met the colleague Zhang San on Apr. 15, 2019.

(255) The electronic device **100** stores the event knowledge based on the predetermined structure. The event knowledge is stored based on the predetermined structure, so that the event knowledge and time are correspondingly stored, to reflect an association between the event knowledge and the time. For example, the event knowledge and the time may be stored based on a 5-tuple structure, and the 5-tuple structure is “event-argument-logical relationship-time point-time interval”.

(256) Herein, the argument is an action that supports the event, and the logical relationship may be a causal relationship, a sequential relationship, or the like.

(257) For example, the event knowledge is “go on a business trip-buy an air ticket-sequential-2020.9.1-3 days”. The event knowledge expresses the event of going on a business trip, there is a sequential relationship between going on a business trip and buying an air ticket, a departure date is Sep. 1, 2020, and a schedule is 3 days.

(258) For example, the event knowledge is “go to the duty-free shop-buy cosmetics-causal-2020.8.20-2 days”. The event knowledge expresses the buying event, there is a causal relationship between going to the duty-free shop and buying cosmetics, a departure date is Aug. 20, 2020, and a schedule is 2 days.

(259) In some embodiments, the electronic device **100** may alternatively represent only an event of the user that occurs by using a time point. A basic format is “entity 1: event-argument-logical relationship-time point”.

(260) For example, the event knowledge is “go on a business trip-buy an air ticket-sequential-2020.9.1”. The event knowledge expresses the event of going on a business trip, there is a sequential relationship between going on a business trip and buying an air ticket, and a departure date is Sep. 1, 2020.

(261) The electronic device **100** stores the entity knowledge based on the predetermined structure. The entity knowledge is stored based on the predetermined structure, so that the entity knowledge and time are correspondingly stored, to reflect an association between the entity knowledge and the time. For example, the entity knowledge and the time may be stored based on a 5-tuple structure, and the 5-tuple structure is “entity 1: time-association weight-entity 2-relationship weight-entity 3”.

(262) For example, the entity knowledge is “television series 1: 2020.4.6-1.0-actor 1-0.8-actor 3”. The entity knowledge indicates that the television series 1 is released on Apr. 6, 2020, a degree of association between the television series 1 and the actor 1 is 1.0, and a degree of association between the actor 1 and the actor 3 is 0.8. This indicates that there is a higher degree of association between the television series 1 and the actor 1.

(263) For example, the entity knowledge is “television series 2: 2020.2.1-0.6-actor 2-0.8-actor 1”. The entity knowledge indicates that the television series 2 is released on Feb. 1, 2020, a degree of association between the television series 2 and the actor 2 is 0.6, and a degree of association between the actor 2 and the actor 1 is 0.8. This indicates that there is a higher degree of association between the television series 2 and the actor 1.

(264) For example, the electronic device **100** performs entity mining on the description information and the data of the television series 1 that are obtained after cleansing and deduplication, and establishes time-based entity knowledge, namely, television series 1: 2020-1.0-actor 1-0.8-actor 2.

(265) The electronic device **100** constructs the personal knowledge graph based on the event knowledge of the predetermined structure, the relationship knowledge of the predetermined structure, and the entity knowledge of the predetermined structure.

(266) The personal knowledge graph graphically represents the user knowledge of the predetermined structure.

(267) FIG. **8** is a schematic diagram of graphically representing a constructed personal knowledge graph according to an embodiment of this application. It may be understood that the personal knowledge graph in FIG. **8** shows a personal knowledge graph only of a part of the user knowledge of the user, and the personal knowledge graph may further include more or less user knowledge.

(268) As shown in FIG. **8**, the personal knowledge graph of the user may include the relationship

knowledge, the event knowledge, and the entity knowledge.

(269) For specific description of the relationship knowledge, the event knowledge, and the entity knowledge of the user in the personal knowledge graph shown in FIG. 8, refer to the description in the foregoing embodiment. Details are not described in this application.

(270) It should be noted that user knowledge obtained by the electronic device **100** from each application module changes in real time, and therefore the personal knowledge graph constructed by the electronic device **100** based on the user knowledge obtained from each application module also needs to be updated in real time. In this way, the personal knowledge graph can more accurately express a characteristic of the user.

(271) After the electronic device **100** constructs the time-based personal knowledge graph of the user, the electronic device **100** may further update the user knowledge in the personal knowledge graph. Specifically, the personal knowledge graph may retain only user knowledge of the user in a recent time period, and the electronic device **100** may filter out user knowledge that does not belong to the recent time period from the personal knowledge graph. In this way, a characteristic of the user depicted by an updated personal knowledge graph is more accurate. In addition, storage resources of the electronic device **100** can be saved.

(272) How the electronic device **100** updates the personal knowledge graph is described below.

(273) The electronic device **100** may update the personal knowledge graph from two aspects: The electronic device **100** adds new knowledge of the user to the personal knowledge graph, and the electronic device **100** filters out existing knowledge of the user from the personal knowledge graph.

(274) How the electronic device **100** filters out the existing knowledge of the user from the personal knowledge graph is described below.

(275) Specifically, in some embodiments, the electronic device **100** may retain only user knowledge in a recent time period (for example, two years) in the personal knowledge graph, and filter out user knowledge in a time period other than the recent time period (for example, two years) from the personal knowledge graph.

(276) In some other embodiments, the electronic device **100** may alternatively filter out the existing knowledge of the user from the personal knowledge graph based on a memory size of the personal knowledge graph.

(277) Specifically, if the electronic device **100** detects that the memory size of the personal knowledge graph of the user is close to a preset memory size, the electronic device **100** may retain knowledge in a recent time period in the personal knowledge graph based on the preset memory size.

(278) In this embodiment of this application, the personal knowledge graph of the user may alternatively be updated in another manner. The foregoing embodiment is merely used to explain this application, and should not be construed as a limitation.

(279) The electronic device **100** may update the personal knowledge graph in a specific time interval.

(280) In some embodiments, the electronic device **100** may update the personal knowledge graph based on a fixed time (for example, 1 day).

(281) In some other embodiments, the electronic device **100** may update the personal knowledge graph based on a behavior habit of the user.

(282) For example, in a time period “22:00-8:00”, the user rests at home, and the electronic device **100** is in a standby state. In this case, the electronic device **100** may update the personal knowledge graph in the time period “22:00-8:00”. When the electronic device **100** updates the personal knowledge graph, specific memory space of the electronic device **100** is occupied. Therefore, the electronic device **100** updates the personal knowledge graph during the rest time of the user, so that more memory space is reserved for a user operation, to ensure smoothness of the user operation.

(283) S704. The electronic device **100** trains a re-ranking model based on historical advertisement information, basic characteristic data of the user, the personal knowledge graph, and a historical

behavior of the user.

(284) For how the electronic device **100** trains the re-ranking model, refer to the embodiment in FIG. 3. Details are not described herein.

(285) It should be noted that the electronic device **100** trains the re-ranking model based on data such as the personal knowledge graph. It may be learned from the foregoing embodiment that the personal knowledge graph is updated as time goes by. In this case, the electronic device **100** should also update the re-ranking model as time goes by. In this way, an advertisement ranking list obtained by re-ranking a plurality of input advertisements by the re-ranking model is more accurate.

(286) How the electronic device **100** updates the re-ranking model is described below.

(287) In some embodiments, the electronic device **100** may update the re-ranking model based on a fixed time (for example, 1 day).

(288) In some embodiments, the electronic device **100** may update the personal knowledge graph based on a behavior habit of the user.

(289) For example, in a time period “22:00-8:00”, the user rests at home, and the electronic device **100** is in a standby state. In this case, the electronic device **100** may update the re-ranking model in the time period “22:00-8:00”. When the electronic device **100** updates the re-ranking model, specific memory space of the electronic device **100** is occupied. Therefore, the electronic device **100** does not update the re-ranking model when the user uses the electronic device **100**, so that more memory space is reserved for a user operation, to ensure smoothness of the user operation.

(290) S705. An application in the electronic device **100** receives a pre-ranked advertisement sent by an advertisement server **200**.

(291) The electronic device **100** detects a user operation, and in response to the user operation, the electronic device **100** sends a user request to an application server **300**, and the application server **300** sends an advertisement recommendation request to the advertisement server **200**.

(292) For example, the user operation may be that the electronic device **100** detects that the user starts the application or the electronic device **100** detects that the user slides to a current browsing interface of a next video in the application (for example, the electronic device **100** detects that the user slides down to the current browsing interface of the next video with a single finger). In this case, the electronic device **100** sends the user request to the application server **300**.

(293) For example, FIG. 9A shows an example of a user interface **90** of a current browsing interface of an application.

(294) The user interface **90** may include a status bar **400**, a current video browsing interface **460**, and an advertisement display area **470**.

(295) The current video browsing interface **460** includes a “Recommendation” control **4601**, a “Hot” control **4602**, a “Small video” control **4603**, a “Next video” control **4604**, a video display window **4605**, a “Like” control **4606**, a “Comment” control **4607**, and a “Forward” control **4608**.

(296) The advertisement display area **470** includes an advertisement icon **4609**, a close control **4610**, and an advertisement link control **4611**.

(297) Video content **4600** of a currently played video (for example, the television series 1) is displayed in the video display window **4605**.

(298) The “Next video” control **4604** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the current video browsing interface **460** displays video content of another video.

(299) In response to an operation of tapping the “Next video” control **4604** by the user, the electronic device **100** sends the user request to the application server **300**, the application server **300** sends the advertisement recommendation request to the advertisement server **200**, the advertisement server **200** sends a new advertisement to the application in the electronic device **100** in response to the advertisement recommendation request, and the advertisement display area **470** displays new advertisement content.

(300) The current browsing interface of the application may further receive an operation of sliding down to the current browsing interface of the next video by the user with a single finger. In response to the operation that is of sliding down by the user with a single finger and that is performed on the current browsing interface, the electronic device **100** sends the user request to the application server **300**, the application server **300** sends the advertisement recommendation request to the advertisement server **200**, the advertisement server **200** sends a new advertisement to the application in the electronic device **100** in response to the advertisement recommendation request, and the advertisement display area **470** displays new advertisement content.

(301) How the advertisement server **200** sends the pre-ranked advertisement to the application in the electronic device **100** is described below.

(302) The advertisement server **200** first performs group profiling for a user group based on group data.

(303) The advertisement server **200** obtains the group data. The group data may be an advertisement tapped by the user, an advertisement browsed by the user, an advertisement closed by the user, and the like.

(304) FIG. **9B** and FIG. **9C** are diagrams of an example user interface UI for obtaining the group data by the advertisement server **200**.

(305) For example, FIG. **9B** shows an example of a user interface **900** of a current browsing interface of an application.

(306) The user interface **900** may include a status bar **400**, a current video browsing interface **460**, and an advertisement display area **470**.

(307) The current video browsing interface **460** includes a “Recommendation” control **4601**, a “Hot” control **4602**, a “Small video” control **4603**, a “Next video” control **4604**, a video display window **4605**, a “Like” control **4606**, a “Comment” control **4607**, and a “Forward” control **4608**.

(308) The advertisement display area **470** includes an advertisement icon **4609**, a close control **4610**, and an advertisement link control **4611**.

(309) Video content **4600** of a currently played video (for example, the television series 1) is displayed in the video display window **4605**.

(310) The “Next video” control **4604** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the current video browsing interface **460** displays video content of another video.

(311) The advertisement display area **470** displays advertisement content. The advertisement content is “The coupon obtaining manner is below. Please tap to obtain ABCDEFGHI”.

(312) The advertisement link control **4611** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the user interface **910** displays a user interface of the advertisement. In addition, in response to the operation of tapping the advertisement link control **4611** by the user, the application server **300** reports a behavior that the user taps and views the advertisement to the advertisement server **200**. The behavior that the user taps and views the advertisement may be used as a piece of service data of the advertisement.

(313) The close control **4610** may also receive a tap operation performed by the user, and in response to the tap operation performed by the user, the advertisement display area **470** displays a selection prompt box **4612** shown in FIG. **9C**. The selection prompt box **4612** includes an “Uninterested” control **4613**, a “Repeated recommendation” control **4614**, and a “Block this type of advertisement” control **4615**.

(314) The “Uninterested” control **4613** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the advertisement display area **470** does not display the advertisement. The “Repeated recommendation” control **4614** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the advertisement display area **470** does not recommend the advertisement to the user for viewing within a specific time (for example, 48 hours). The “Block this type of advertisement” control

46154614 may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the advertisement display area **470** does not recommend this type of advertisement (for example, a makeup advertisement) to the user for viewing.

(315) In addition, in response to the operation of tapping the close control **4610** by the user, the application server **300** reports a behavior that the user closes the advertisement and does not view the advertisement to the advertisement server **200**. The behavior that the user closes the advertisement and does not view the advertisement may be used as a piece of group data of the advertisement.

(316) The group data of the advertisement may alternatively come from another manner. The foregoing embodiment is merely used to explain this application. This is not limited in this embodiment of this application.

(317) The application server **300** collects the group data, and reports the group data to the advertisement server **200**. The advertisement server **200** performs group profiling for the user group based on groups of all users. The group profiling is to label the user group based on group data of all the users, for example, a type of an advertisement that the user group likes to view or a type of an advertisement that the user group does not like to view.

(318) It may be understood that the group data of all the users collected by the application server **300** changes in real time. Therefore, the group data of all the users that is sent by the application server **300** and that is received by the advertisement server **200** also changes in real time.

(319) The advertisement server **200** may perform group profiling for the user group based on a fixed time (for example, 1 day) based on the group data of all the users. In this case, the group profile of the user group is also periodically updated.

(320) The advertisement server **200** then screens advertisements based on the group profile of the user group, to obtain the pre-ranked advertisement.

(321) The pre-ranked advertisement may be one or more advertisements.

(322) The pre-ranked advertisement is obtained by screening a plurality of advertisements in an advertisement set based on the group profile of the user group. The advertisement server **200** sends the pre-ranked advertisement to the application in the electronic device **100**.

(323) The application in the electronic device **100** receives the pre-ranked advertisement sent by the advertisement server **200**.

(324) It may be learned from the foregoing embodiments that in some embodiments, the advertisement server **200** may classify user groups. For example, the user groups may be classified into a female user group and a male user group, or the user groups may be classified into user groups of various age groups.

(325) For example, when the advertisement server **200** classifies the user groups into a female user group and a male user group, the advertisement server **200** performs profiling for each of the male user group and the female user group.

(326) Specifically, the advertisement server **200** screens a plurality of advertisements based on a group profile of male users, to obtain a pre-ranked advertisement of the male users. The advertisement server **200** pushes the pre-ranked advertisement of the male users to an electronic device of the male users.

(327) The advertisement server **200** screens a plurality of advertisements based on a group profile of female users, to obtain a pre-ranked advertisement of the female users. The advertisement server **200** pushes the pre-ranked advertisement of the female users to an application in an electronic device of the female users.

(328) For example, when classifying the user groups into user groups of various age groups, the advertisement server **200** may perform profiling for the user groups of various age groups based on the user groups.

(329) Specifically, the advertisement server **200** performs profiling for a user group of users aged between 21 and 35, and screens a plurality of advertisements based on a group profile of the users

aged between 21 and 35, to obtain a pre-ranked advertisement of the users aged between 21 and 35. The advertisement server **200** pushes the pre-ranked advertisement of the users aged between 21 and 35 to an application in an electronic device of the users aged between 21 and 35.

(330) The advertisement server **200** performs profiling for a user group of users aged between 36 and 50, and screens a plurality of advertisements based on a group profile of the users aged between 36 and 50, to obtain a pre-ranked advertisement of the users aged between 36 and 50. The advertisement server **200** pushes the pre-ranked advertisement of the users aged between 36 and 50 to an application in an electronic device of the users aged between 36 and 50.

(331) The advertisement server **200** performs profiling for a user group of users aged between 51 and 70, and screens a plurality of advertisements based on a group profile of the users aged between 51 and 70, to obtain a pre-ranked advertisement of the users aged between 51 and 70. The advertisement server **200** pushes the pre-ranked advertisement of the users aged between 51 and 70 to an application in an electronic device of the users aged between 51 and 70.

(332) **S706**. The application in the electronic device **100** obtains the re-ranking model, and the application screens the pre-ranked advertisement based on the re-ranking model, to obtain a to-be-placed advertisement.

(333) There may be one or more to-be-placed advertisements.

(334) For how the application obtains the to-be-placed advertisement based on the pre-ranked advertisement, refer to the embodiment in FIG. 3. Details are not described herein.

(335) How the application displays the to-be-placed advertisement is described below.

(336) The electronic device **100** starts the application, there is one advertisement slot in the current browsing interface of the application, and one or more advertisements may be displayed in the advertisement slot.

(337) For example, if advertisement duration of the advertisement slot is 60 seconds, only one advertisement may be displayed in the advertisement slot, and a time of the advertisement is 60 seconds.

(338) For example, if advertisement duration of the advertisement slot is 60 seconds, six advertisements may be displayed in the advertisement slot, and a display time of each advertisement is 10 seconds.

(339) It should be noted that the foregoing embodiment is merely used to explain this application. A quantity of advertisements displayed in each advertisement slot and an advertisement time are not limited in this application.

(340) This application is not limited to advertisement recommendation, and may be further applied to content recommendation. The content recommendation may include song recommendation, electronic book recommendation, movie and television series recommendation, food recommendation, shopping recommendation, and the like. This is not limited in this application.

(341) FIG. 1 is a schematic flowchart of another advertisement display method according to an embodiment of this application.

(342) The method includes the following steps.

(343) **S1001**. An electronic device **100** obtains first personal data.

(344) The electronic device **100** obtains the first personal data. The first personal data is personal information of a user. The personal information may be one or more of the following: a gender, an age, a personality, a hobby, an interpersonal relationship, income, contacts information, a call record, a short message service message, memo information, a residence address, and a weather condition at the residence address.

(345) In some embodiments, the electronic device **100** may obtain the first personal data of the user at regular intervals (for example, one week).

(346) Specifically, for obtaining the first person data by the electronic device **100**, refer to the embodiments in FIG. 6A to FIG. 6D and the embodiment in **S701**. Details are not described herein in this application.

(347) S1002. The electronic device **100** constructs a personal knowledge graph based on the first personal data.

(348) Before constructing the personal knowledge graph based on the first personal data, the electronic device **100** needs to preprocess the first personal data. That the electronic device **100** preprocesses the first personal data includes the following two steps:

(349) Step 1: The electronic device converts the first personal data into text information, and performs sentence segmentation, word segmentation, and part-of-speech tagging on the text information; and the electronic device obtains a word that belongs to a preset part of speech from the text information.

(350) Step 2: After the electronic device obtains the word that belongs to the preset part of speech from the text information, the electronic device **100** deduplicates words in the text information, to remove data redundancy.

(351) Specifically, the electronic device **100** needs to obtain a word that appears once in the text information; and when two or more same words appear in the text information, the electronic device **100** retains one of the two or more same words in the text information.

(352) That is, the electronic device **100** obtains second personal data from the first personal data. The second person data includes relationship knowledge, event knowledge, and entity knowledge.

(353) Specifically, for preprocessing the first person data by the electronic device **100**, refer to the embodiment in S701. This is not limited herein in this application.

(354) That the electronic device **100** constructs a personal knowledge graph based on the first personal data specifically includes the following steps:

(355) The electronic device **100** stores the relationship knowledge, the event knowledge, and the entity knowledge based on a predetermined structure. The predetermined structure may be a 5-tuple structure.

(356) Specifically, the electronic device **100** stores the relationship knowledge based on a first 5-tuple structure. The first 5-tuple structure is “first entity-relationship-second entity-first time point-first time interval”. The relationship represents a relationship between the first entity and the second entity, the first time point is a time at which the relationship is established between the first entity and the second entity, and the first time interval is a time interval between the first time point and a current time point.

(357) The electronic device **100** stores the event knowledge based on a second 5-tuple structure. The second 5-tuple structure is “event-argument-logical relationship-second time point-second time interval”. The argument is an occurrence action of the event, the logical relationship represents a relationship between the event and the argument, the second time point is a time at which the event occurs, and the second time interval is a time interval between the second time point and a current time point.

(358) The electronic device **100** stores the entity knowledge based on a third 5-tuple structure. The third 5-tuple structure is “third entity: third time point-first association weight-fourth entity-second association weight-fifth entity”. The third time point is a time at which the third entity occurs, the first association weight is a degree of association between the third entity and the fourth entity, and the second association weight is a degree of association between the fourth entity and the fifth entity.

(359) The electronic device constructs the personal knowledge graph of the user based on the relationship knowledge of the predetermined structure, the event knowledge of the predetermined structure, and the entity knowledge of the predetermined structure.

(360) Specifically, for constructing the personal knowledge graph by the electronic device **100**, refer to the embodiment in S703. Details are not described herein in this application.

(361) The electronic device **100** may further update the personal knowledge graph.

(362) The electronic device **100** may delete personal data from the personal knowledge graph, to update the personal knowledge graph.

(363) Specifically, the electronic device deletes the relationship knowledge whose first time interval is greater than a first threshold from the personal knowledge graph; and/or the electronic device deletes the event knowledge whose second time interval is greater than the first threshold from the personal knowledge graph; and/or the electronic device determines a third time interval between the third time point and the current time point based on the third time point; and the electronic device deletes the entity knowledge whose third time interval is greater than the first threshold from the personal knowledge graph.

(364) In addition, the electronic device **100** may add new personal data to the personal knowledge graph.

(365) Specifically, the electronic device **100** obtains the first personal data at regular intervals, and adds the first personal data to the personal knowledge graph.

(366) **S1003.** The electronic device **100** obtains parameter information of first advertisement content from an advertisement server **200**.

(367) The electronic device may receive the parameter information of the first advertisement content from the advertisement server. The parameter information may be information such as a type, a link address, and a size of the first advertisement content. The first advertisement content may include one or more advertisements.

(368) The first advertisement content is any one or more of the following: a picture, a video, text, audio, and the like. The first advertisement content may include one or more advertisements.

(369) **S1004.** The electronic device **100** obtains parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph.

(370) The electronic device may obtain the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph in one or more of the following manners: Manner 1: The electronic device retains parameter information of all advertisements in the parameter information of the first advertisement content, and the electronic device only ranks the first advertisement content in descending order of predicted preference values of the user for types of the advertisements, to obtain the parameter information of the second advertisement content. Manner 2: The electronic device selects parameter information of some advertisements from the parameter information of the first advertisement content, to obtain the parameter information of the second advertisement content. Specifically, the electronic device ranks the first advertisement content in descending order of predicted preference values of the user for types of advertisements, and retains only parameter information of an advertisement whose predicted preference value of the user is greater than a first threshold, to obtain the parameter information of the second advertisement content.

(371) The second advertisement content is any one or more of the following: a picture, a video, text, audio, and the like. The second advertisement content may include one or more advertisements.

(372) Specifically, the electronic device **100** trains a re-ranking model based on the personal knowledge graph, to obtain a first model, and the electronic device obtains the parameter information of the second advertisement content from the parameter information of the first advertisement content by using the first model.

(373) Specifically, that the electronic device **100** trains a re-ranking model based on the personal knowledge graph may include the following content:

(374) The electronic device obtains a historical behavior of the user and historical advertisement information displayed by the electronic device; the electronic device uses the historical advertisement information and the personal knowledge graph as an input to the re-ranking model, where the re-ranking model outputs a first result; and the electronic device compares the first result with the historical behavior of the user, and modifies a parameter of the re-ranking model until the first result that is output by the re-ranking model falls within a preset range, to obtain the first

model.

(375) **S1005**. The electronic device **100** obtains the second advertisement content based on the parameter information of the second advertisement content.

(376) The electronic device **100** obtains the second advertisement content based on the parameter information (for example, a link address) of the second advertisement content.

(377) **S1006**. The electronic device **100** displays the second advertisement content on a display.

(378) For displaying the second advertisement content on the display by the electronic device **100**, refer to the following manners:

(379) Manner 1: The electronic device plays the one or more advertisements in the second advertisement content in descending order of predicted preference values of the user in the second advertisement content.

(380) Manner 2: The electronic device displays an advertisement that corresponds to a largest predicted preference value of the user in the second advertisement content.

(381) Manner 3: The electronic device plays the one or more advertisements in the second advertisement content in descending order of predicted preference values of the user in the second advertisement content, and blocks one or more advertisements played by the electronic device in a first time period in the second advertisement content.

(382) After the electronic device **100** completely displays the second advertisement content, the electronic device **100** may obtain viewing data of the user for the second advertisement content, where the viewing data includes advertisement types of one or more advertisements viewed by the user in the second advertisement content and advertisement types of one or more advertisements closed by the user in the second advertisement content; and the electronic device updates the first model based on the viewing data. In this way, the electronic device updates the first model based on the data of viewing an advertisement by the user, so that the first model recommends an advertisement of a type viewed by the user for a largest quantity of times to the user when recommending an advertisement to the user next time, to better meet a requirement of the user.

(383) In the following embodiments of this application, after the electronic device **100** constructs the personal knowledge graph based on the personal data of the user, an application in the electronic device **100** may ask for consent of the user to obtain the personal knowledge graph, and the application may perform personalized recommendation for the user based on the personal knowledge graph. In this way, the application can obtain the personal knowledge graph only after obtaining consent of the user, which fully respects personal privacy of the user. In addition, the application performs personalized recommendation for the user based on the personal knowledge graph. In this way, content recommended by the application to the user better matches a behavioral characteristic of the user.

(384) An existing content display method is first described.

(385) After the user uses the electronic device **100** for a time period, the user downloads a new application (for example, a first application) from an application store. The first application prompts the user to register personal information and log in. In addition, the first application may prompt the user to select content that the user is interested in, and the first application recommends related content that the user is interested in to the user for viewing.

(386) For example, the foregoing application scenario is described below with reference to the accompanying drawings.

(387) FIG. **11A** shows an example of a user interface **700** used for an application menu on an electronic device **100**.

(388) The user interface **700** may include a status bar **400**, a tray **710** that includes a frequently used application icon, a navigation bar **720**, and other application icons.

(389) The tray **710** that includes a frequently used application icon may display a phone icon **7012**, a contacts icon **7013**, a messaging icon **7014**, and a camera icon **7015**.

(390) The navigation bar **720** may include system navigation buttons such as a back button **7016**, a

home screen (Home screen) button **7017**, and an outgoing task history button **7018**. When detecting that the user taps the back button **7016**, the electronic device **100** may display a previous page of a current page. When detecting that the user taps the home screen button **7017**, the electronic device **100** may display a home screen. When detecting that the user taps the outgoing call task history button **7018**, the electronic device **100** may display a task recently opened by the user.

Alternatively, there may be other names for the navigation buttons. This is not limited in this application. Each navigation button in the navigation bar **720** is not limited to a virtual button, and may be implemented as a physical button.

(391) The other application icons may be, for example, a clock icon **7001**, a calendar icon **7002**, a gallery icon **7003**, a memo icon **7004**, a file management icon **7005**, an email icon **7006**, a music icon **7007**, a calculator icon **7008**, a Huawei video icon **7009**, a sports and health icon **7010**, and a first application icon **7011**.

(392) The first application is an application that has not been used after being downloaded by the user from the application store. The first application may be a shopping application, an electronic book application, a video application, or the like. The application scenario is described by using an example in which the first application is a shopping application.

(393) As shown in FIG. **11A**, the first application icon **7011** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the electronic device **100** displays an example user interface **730** shown in FIG. **11B**.

(394) The user interface **730** includes a status bar **400** and a gender selection interface **740**.

(395) The gender selection interface **740** includes a control **7101** and a control **7102**.

(396) The control **7101** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the first application recommends an item that a male is interested in to the user for viewing.

(397) The control **7102** may receive a tap operation performed by the user, and in response to the tap operation performed by the user, the first application recommends an item that a female is interested in to the user for viewing.

(398) For example, as shown in FIG. **11B**, the control **7102** receives a tap operation performed by the user, and in response to the tap operation performed by the user, the electronic device **100** displays an example user interface **750** shown in FIG. **11C**.

(399) The user interface **750** includes a status bar **400** and a personalized recommendation selection interface **760**.

(400) The personalized recommendation selection interface **760** includes a plurality of recommendation theme controls and a “Next” control **770**.

(401) The plurality of recommendation theme controls may include a “Dressing” control **7501**, a “Sports” control **7502**, a “Makeup” control **7503**, a “Travel” control **7504**, a “Food” control **7505**, and a “Games” control **7506**. The plurality of recommendation theme controls may further include another recommendation control. This is not limited herein.

(402) Any one of the plurality of recommendation theme controls may receive a tap and selection operation performed by the user, and in response to the tap operation performed by the user, the first application recommends a theme that the user is interested in to the user for viewing.

(403) For example, if the user is interested in makeup, dressing, and food, the “Dressing” control **7501**, the “Makeup” control **7503**, and the “Food” control **7505** receive a tap and selection operation performed by the user, the “Next” control **770** receives and responds to the tap operation performed by the user, the electronic device **100** displays an example user interface of the first application, and content displayed in the user interface of the first application is makeup content, dressing content, and food content selected by the user. In this way, the first application may recommend related content to the user based on a preference of the user.

(404) However, it may be learned from the foregoing embodiment that when the user opens an application that has not been used, the user needs to first select a gender, and then select theme

content that the user is interested in. After the user completes selection, the user needs to tap “next” to enter the application. It may be learned from the foregoing operation that in this recommendation manner of an application, there is a complex operation and user experience is poor.

(405) The first application may recommend, based on the personal knowledge graph provided in this embodiment of this application, content that the user is interested in. In this way, the user does not need to perform a series of operations to select content that the user is interested in. In addition, the content that the user is interested in and that is recommended by the first application based on the personal knowledge graph is more accurate.

(406) When the user opens the first application, the first application asks for a request of the user to obtain information such as the personal knowledge graph. In this case, the first application obtains data such as the personal knowledge graph only when the user authorizes the first application. In this way, personal privacy of the user is fully respected.

(407) FIG. 12 is a schematic architectural diagram of another system according to an embodiment of this application. The system includes an electronic device **100** and an application server **300**.

(408) The application server **300** sends a first content list to a first application in the electronic device **100**, where the first content list may include a plurality of pieces of content, and the first application receives the first content list sent by the application server **300**.

(409) After the first application obtains a request of a user, the electronic device **100** sends a personal knowledge graph to the first application. The first application receives the personal knowledge graph sent by the electronic device **100**. After the first application obtains the first content list, the first application screens the plurality of pieces of content in the first content list based on the personal knowledge graph, to obtain a second content list, and the first application recommends content in the second content list to the user for viewing.

(410) For example, FIG. 12A is an example user interface **780** for obtaining a request of a user by a first application.

(411) The user interface **780** includes a status bar **400** and a prompt box **790**.

(412) The prompt box **790** displays prompt information, a “Disagree” control **7801**, and an “Agree” control **7802**. The prompt information is used to prompt the user whether to agree with the first application to obtain information such as the personal knowledge graph. The prompt information includes “To better provide services such as providing a browsing recommendation, publishing information, and buying a product, necessary user information (which may include information such as a device and the personal knowledge graph) is to be collected based on your specific functional requirement of using the service”.

(413) The “Disagree” control **7801** may accept a tap operation performed by the user. In response to the tap operation performed by the user, the user does not agree with the first application to obtain data such as the personal knowledge graph. In this case, the first application does not recommend personalized content to the user.

(414) The “Agree” control **7802** may accept a tap operation performed by the user. In response to the tap operation performed by the user, the user agrees with the first application to obtain data such as the personal knowledge graph. In this case, the first application recommends content similar to a personal behavioral characteristic of the user to the user based on data such as the personal knowledge graph, for example, recommends similar content to the user for viewing based on a preference and a consumption level of the user.

(415) In this way, the first application recommends content similar to the personal behavioral characteristic of the user to the user based on data such as the personal knowledge graph, and the user does not need to manually select content that the user is interested in. In this way, there is a simple user operation, and a requirement of the user is better met because the content that the user is interested in and that is recommended by the first application based on the personal knowledge graph is more accurate.

(416) According to the context, the term “when” used in the foregoing embodiments may be

interpreted as a meaning of “if”, “after”, “in response to determining”, or “in response to detecting”. Similarly, according to the context, the phrase “when it is determined that” or “if (a stated condition or event) is detected” may be interpreted as a meaning of “if it is determined that”, “in response to determining”, “when (a stated condition or event) is detected”, or “in response to detecting (a stated condition or event)”.

(417) All or some of the foregoing embodiments may be implemented by software, hardware, firmware, or any combination thereof. When software is used to implement embodiments, all or some of embodiments may be implemented in a form of a computer program product. The computer program product includes one or more computer instructions. When the computer program instructions are loaded and executed on a computer, all or some of the procedures or functions according to embodiments of this application are generated. The computer may be a general-purpose computer, a dedicated computer, a computer network, or another programmable apparatus. The computer instructions may be stored in a computer-readable storage medium, or may be transmitted from a computer-readable storage medium to another computer-readable storage medium. For example, the computer instructions may be transmitted from a website, computer, server, or data center to another website, computer, server, or data center in a wired (for example, a coaxial cable, an optical fiber, or a digital subscriber line) or wireless (for example, infrared, radio, or microwave) manner. The computer-readable storage medium may be any available medium that can be accessed by a computer, or a data storage device such as a server or a data center into which one or more available media are integrated. The available medium may be a magnetic medium (for example, a floppy disk, a hard disk, or a magnetic tape), an optical medium (for example, a DVD), a semiconductor medium (for example, a solid-state drive), or the like.

(418) Persons of ordinary skill in the art may understand that all or some of the procedures of the methods in the foregoing embodiments may be implemented by a computer program by instructing related hardware. The program may be stored in a computer-readable storage medium. When the program is executed, the procedures in the foregoing method embodiments may be performed. The foregoing storage medium includes any medium that can store program code, for example, a ROM, a random access memory RAM, a magnetic disk, or an optical disc.

Claims

1. A method comprising: obtaining, by a terminal side electronic device, and storing, by the terminal side electronic device and onboard the terminal side electronic device, first personal data of a user, wherein the first personal data is personal information of the user; constructing, by the terminal side electronic device and onboard the terminal side electronic device, and storing, by the terminal side electronic device and onboard the terminal side electronic device, a personal knowledge graph based on the first personal data stored on the terminal side electronic device, wherein the personal knowledge graph comprises the first personal data and a time at which the first personal data is generated; obtaining, by the terminal side electronic device, parameter information of first advertisement content from an advertisement server of a server side, wherein the parameter information of the first advertisement content comprises one or more types of one or more advertisements in the first advertisement content and a link address of the first advertisement content, the first advertisement content is obtained based on screening a plurality of advertisements using group data; obtaining, by the terminal side electronic device, parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph; obtaining, by the terminal side electronic device, the second advertisement content based on the parameter information of the second advertisement content, wherein the second advertisement content comprises at least one of the one or more advertisements; and displaying, by the terminal side electronic device, the second advertisement content on a display.

2. The method according to claim 1, wherein constructing and storing, by the terminal side electronic device, the personal knowledge graph based on the first personal data comprises: obtaining, by the terminal side electronic device, second personal data from the first personal data, wherein the second personal data comprises relationship knowledge, event knowledge, and entity knowledge; storing, by the terminal side electronic device, the relationship knowledge, the event knowledge, and the entity knowledge based on a predetermined structure; and constructing, by the terminal side electronic device, the personal knowledge graph of the user based on the relationship knowledge of the predetermined structure, the event knowledge of the predetermined structure, and the entity knowledge of the predetermined structure.

3. The method according to claim 2, wherein before obtaining, by the terminal side electronic device, the second personal data from the first personal data, the method further comprises: converting, by the terminal side electronic device, the first personal data into text information; and performing, by the terminal side electronic device, sentence segmentation, word segmentation, and part-of-speech tagging on the text information, wherein the sentence segmentation, the word segmentation, and the part-of-speech tagging marks the text information with a plurality of tags; and wherein obtaining, by the terminal side electronic device, the second personal data from the first personal data comprises: obtaining, by the terminal side electronic device from the text information, a plurality of words based on a subset of the plurality of tags, wherein the plurality of words represents core information in the second personal data.

4. The method according to claim 2, wherein the predetermined structure is a 5-tuple structure; and storing, by the terminal side electronic device, the relationship knowledge based on the predetermined structure comprises: storing, by the terminal side electronic device, the relationship knowledge based on a first 5-tuple structure, wherein the first 5-tuple structure is “first entity-relationship-second entity-first time point-first time interval”, a relationship in the first 5-tuple structure is between a first entity and a second entity in the first 5-tuple structure, a first time point in the first 5-tuple structure is a time at which the relationship in the first 5-tuple structure is established between the first entity and the second entity, and a first time interval in the first 5-tuple structure is a time interval between the first time point in the first 5-tuple structure and a current time point.

5. The method according to claim 2, wherein the predetermined structure is a 5-tuple structure; and storing, by the terminal side electronic device, the event knowledge based on the predetermined structure comprises: storing, by the terminal side electronic device, the event knowledge based on a second 5-tuple structure, wherein the second 5-tuple structure is “event-argument-logical relationship-second time point-second time interval”, an argument in the second 5-tuple structure is an occurrence action of an event in the second 5-tuple structure, a logical relationship in the second 5-tuple structure is between the event and the argument in the second 5-tuple structure, a second time point in the second 5-tuple structure is a time at which the event occurs, and a second time interval in the second 5-tuple structure is between the second time point and a current time point.

6. The method according to claim 2, wherein the predetermined structure is a 5-tuple structure; and storing, by the terminal side electronic device, the entity knowledge based on the predetermined structure comprises: storing, by the terminal side electronic device, the entity knowledge based on a third 5-tuple structure, wherein the third 5-tuple structure is “third entity: third time point-first association weight-fourth entity-second association weight-fifth entity”, a third time point in the third 5-tuple structure is a time at which a third entity in the third 5-tuple structure occurs, a first association weight in the third 5-tuple structure is a degree of association between the third entity and a fourth entity in the third 5-tuple structure, and a second association weight in the third 5-tuple structure is a degree of association between the fourth entity and a fifth entity in the third 5-tuple structure.

7. The method according to claim 6, wherein the method further comprises: deleting, by the terminal side electronic device from the personal knowledge graph, at least a portion of the

relationship knowledge having a first time interval greater than a first threshold; or deleting, by the terminal side electronic device from the personal knowledge graph, at least a portion of the event knowledge having a second time interval greater than the first threshold; or determining, by the terminal side electronic device, a third time interval between the third time point and a current time point based on the third time point for the entity knowledge; and deleting, by the terminal side electronic device from the personal knowledge graph, at least a portion of the entity knowledge having the third time interval greater than the first threshold.

8. The method according to claim 2, wherein before obtaining, by the terminal side electronic device, the second personal data from the first personal data, the method further comprises: converting, by the terminal side electronic device, the first personal data into text information; and performing, by the terminal side electronic device, sentence segmentation, word segmentation, and part-of-speech tagging on the text information; and wherein obtaining, by the terminal side electronic device, the second personal data from the first personal data comprises: obtaining, by the terminal side electronic device from the text information, a word that belongs to a preset part of speech.

9. The method according to claim 8, wherein after obtaining, by the terminal side electronic device, the word that belongs to the preset part of speech, the method further comprises: obtaining, by the terminal side electronic device, a first word that appears once in the text information; and when a second word appears more than once in the text information, obtaining, by the terminal side electronic device, the second word once from the text information; and obtaining, by the terminal side electronic device, the second personal data based on the obtained first word and second word.

10. The method according to claim 1, wherein the terminal side electronic device obtains the first personal data of the user at regular intervals.

11. The method according to claim 1, wherein the first advertisement content is one or more of following: a picture, a video, text, or audio.

12. The method according to claim 1, wherein after constructing and storing, by the terminal side electronic device, the personal knowledge graph based on the first personal data, the method further comprises: obtaining, by the terminal side electronic device, a historical behavior of the user and historical advertisement information displayed by the terminal side electronic device; training, by the terminal side electronic device, a re-ranking model with the historical behavior, the historical advertisement information and the personal knowledge graph, to obtain a first model, the training comprises: generating, by the terminal side electronic device, a first result output by the re-ranking model with the historical advertisement information and the personal knowledge graph as an input to the re-ranking model; comparing, by the terminal side electronic device, the first result with the historical behavior of the user, and based thereon, modifying, by the terminal side electronic device, a parameter of the re-ranking model; and repeating, by the terminal side electronic device, steps of the generating and the comparing until the first result that is output by the re-ranking model falls within a preset range; and wherein obtaining, by the terminal side electronic device, the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph comprises: obtaining, by the terminal side electronic device, the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the first model.

13. The method according to claim 12, wherein obtaining, by the terminal side electronic device, the parameter information of the second advertisement content from the parameter information of the first advertisement content based on the first model comprises: ranking, by the terminal side electronic device based on the first model, the one or more types of the one or more advertisements in the first advertisement content in a descending order of one or more predicted preference values of the one or more advertisements given by the user, to obtain the parameter information of the second advertisement content; or ranking, by the terminal side electronic device based on the first model, the one or more types of the one or more advertisements in the first advertisement content

in the descending order of one or more predicted preference values of the one or more advertisements given by the user, and obtaining, by the terminal side electronic device, a type of an advertisement having a predicted preference value greater than a first threshold, to obtain the parameter information of the second advertisement content.

14. The method according to claim 12, wherein after displaying, by the terminal side electronic device, the second advertisement content on the display, the method further comprises: obtaining, by the terminal side electronic device, viewing data of the user for the second advertisement content, wherein the viewing data comprises one or more advertisement types of one or more advertisements viewed by the user in the second advertisement content and one or more advertisement types of one or more advertisements closed by the user in the second advertisement content; and updating, by the terminal side electronic device, the first model based on the viewing data.

15. The method according to claim 1, wherein the personal information of the user comprises one or more of following: a gender, an age, a personality, a hobby, an interpersonal relationship, income, contact information, a call record, a short message service message, memo information, a residence address, or a weather condition at the residence address.

16. The method according to claim 1, wherein displaying, by the terminal side electronic device, the second advertisement content on the display comprises: playing, by the terminal side electronic device, the one or more advertisements in the second advertisement content in a descending order of one or more predicted preference values of the one or more advertisements given by the user; displaying, by the terminal side electronic device, an advertisement that corresponds to a largest predicted preference value in the one or more advertisements; or playing, by the terminal side electronic device, the one or more advertisements in the second advertisement content in the descending order of one or more predicted preference values of the one or more advertisements given by the user, and blocking the one or more advertisements played by the terminal side electronic device in a first time period in the second advertisement content.

17. A terminal side electronic device, wherein the terminal side electronic device comprises one or more processors, one or more memories that are non-transitory, and a display, the one or more memories and the display are coupled to the one or more processors, the one or more memories are configured to store computer program code, the computer program code comprises computer instructions, and the one or more processors invoke the computer instructions to cause the terminal side electronic device to perform: obtaining, at the terminal side electronic device, and storing, onboard the terminal side electronic device, first personal data of a user, wherein the first personal data is personal information of the user; constructing, at the terminal side electronic device and onboard the terminal side electronic device, and storing, onboard the terminal side electronic device, a personal knowledge graph based on the first personal data, wherein the personal knowledge graph comprises the first personal data and a time at which the first personal data is generated; obtaining parameter information of first advertisement content from an advertisement server of a server side, wherein the parameter information of the first advertisement content comprises one or more types of one or more advertisements in the first advertisement content and a link address of the first advertisement content, the first advertisement content is obtained based on screening a plurality of advertisements using group data; obtaining parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph; obtaining the second advertisement content based on the parameter information of the second advertisement content, wherein the second advertisement content comprises at least one of the one or more advertisements; and displaying the second advertisement content on the display.

18. A non-transitory computer-readable storage medium comprising instructions, wherein when the instructions are run on a terminal side electronic device, the terminal side electronic device is caused to perform: obtaining, by the terminal side electronic device and onboard the terminal side

electronic device, and storing, by the terminal side electronic device and onboard the terminal side electronic device, first personal data of a user, wherein the first personal data is personal information of the user; constructing, by the terminal side electronic device and onboard the terminal side electronic device, and storing, by the terminal side electronic device and onboard the terminal side electronic device, a personal knowledge graph based on the first personal data, wherein the personal knowledge graph comprises the first personal data and a time at which the first personal data is generated; obtaining parameter information of first advertisement content from an advertisement server of a server side, wherein the parameter information of the first advertisement content comprises one or more types of one or more advertisements in the first advertisement content and a link address of the first advertisement content, the first advertisement content is obtained based on screening a plurality of advertisements using group data; obtaining, by the terminal side electronic device, parameter information of second advertisement content from the parameter information of the first advertisement content based on the personal knowledge graph; obtaining, by the terminal side electronic device, the second advertisement content based on the parameter information of the second advertisement content, wherein the second advertisement content comprises at least one of the one or more advertisements; and displaying, by the terminal side electronic device, the second advertisement content on a display.
