

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412314
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Walters; Austin Grant et al.

Color conversion between color spaces using reduced dimension embeddings

Abstract

Exemplary embodiments may provide an approach to converting multidimensional color data for an image encoded in a first color space into an intermediate form that is a single dimensional value. The exemplary embodiments may then decode the intermediate form value to produce an encoding of the color data that is encoded in a second color space that differs from the first color space. In this manner, the data for the image may be efficiently converted from an encoding in the first color space into an encoding in the second color space.

Inventors: Walters; Austin Grant (Savoy, IL), Goodsitt; Jeremy Edward (Champaign, IL), Pham; Vincent (Champaign, IL)

Applicant: Capital One Services, LLC (McLean, VA)

Family ID: 80269683

Assignee: Capital One Services, LLC (McLean, VA)

Appl. No.: 18/609524

Filed: March 19, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240221232 A1	Jul. 04, 2024

Related U.S. Application Data

continuation parent-doc US 18144766 20230508 US 11961267 child-doc US 18609524
continuation parent-doc US 17690404 20220309 US 11645787 20230509 child-doc US 18144766
continuation parent-doc US 16997383 20200819 US 11302036 20220412 child-doc US 17690404

Publication Classification

Int. Cl.: **G06T9/00** (20060101); **G06F18/24** (20230101); **G06T7/10** (20170101); **G06T7/90** (20170101)

U.S. Cl.:

CPC **G06T9/002** (20130101); **G06F18/24** (20230101); **G06T7/10** (20170101); **G06T7/90** (20170101); G06T2207/10024 (20130101); G06T2207/20081 (20130101); G06T2207/20084 (20130101)

Field of Classification Search

CPC: G06T (9/002); G06T (7/10); G06T (7/90); G06T (2207/10024); G06T (2207/20081); G06T (2207/20084)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5638496	12/1996	Sato	358/1.9	H04N 1/00875
6985252	12/2005	Kubo	358/1.9	H04N 1/6022
7180629	12/2006	Nishio	358/1.9	H04N 23/88
10944914	12/2020	Le	N/A	H04N 25/58
11302036	12/2021	Walters	N/A	G06T 9/002
11645787	12/2022	Walters	382/157	G06V 10/44
11961267	12/2023	Walters	N/A	G06T 5/90
2003/0235923	12/2002	Jurik	435/14	G01N 21/78
2005/0128491	12/2004	Kubo	358/1.1	H04N 1/6022
2017/0339430	12/2016	Kalevo	N/A	H04N 1/60
2019/0108618	12/2018	Hwang	N/A	G06T 3/4046
2019/0205668	12/2018	Noda	N/A	G06T 7/73
2019/0371433	12/2018	Wang	N/A	G16H 30/40
2021/0035331	12/2020	Xie	N/A	H04N 19/625
2021/0133522	12/2020	Chang	N/A	G06F 16/2282
2021/0158096	12/2020	Sinha	N/A	G06N 3/08
2021/0200501	12/2020	Stankoulov	N/A	G06F 3/0488
2021/0241522	12/2020	Guler	N/A	G06V 40/103
2021/0304389	12/2020	Li	N/A	G06F 18/2413
2022/0058835	12/2021	Walters	N/A	G06V 10/56
2022/0198718	12/2021	Walters	N/A	H04N 19/40

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017016635	12/2016	JP	N/A
20120013405	12/2011	KR	N/A

OTHER PUBLICATIONS

Primary Examiner: Motsinger; Sean T

Attorney, Agent or Firm: KDW Firm PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 18/144,766, filed May 8, 2023, which is a continuation of U.S. patent application Ser. No. 17/690,404 filed Mar. 9, 2022, which is a continuation of U.S. patent application Ser. No. 16/997,383, entitled "COLOR CONVERSION BETWEEN COLOR SPACES USING REDUCED DIMENSION EMBEDDINGS" filed on Aug. 19, 2020. The contents of the aforementioned applications are incorporated herein by reference in their entirety.

BACKGROUND

(1) Color data for two dimensional images is typically encoded on a pixel by pixel basis. Thus, color data is encoded for the pixels that make up the images. For three dimensional images, the color data is encoded for the voxels that make up the image. How the color data is represented is dependent on the color space used for the encoding. The color space is a model that describes the colors of the elements of an image (e.g., pixels or voxels) as tuples of numbers. For example, in the RGB color space, the color is represented as a combination of red, green and blue color components. Each color for an element of an image is represented by a tuple of red, green and blue color component values, with each value being in the range between 0 and 255.

(2) Color spaces differ in their representation of that color data. For instance, the CIELAB or LAB color space represents color as three values: L for the Luminance/Lightness and Alpha (A) and Beta (B) for the green-red and blue-yellow color components, respectively. The LAB color space is typically used when converting from RGB color space model into Cyan-Magenta-Yellow-Black (CMYK) color space. For some images, representing its color data in the LAB color space model provides better edge detection results than other color spaces, including the RGB model.

(3) It may be useful sometimes to convert an image from a source color space to a target color space. For instance, it may be easier to perform object recognition or edge detection in the target space rather than in the source color space. Unfortunately, since image data can be quite large, the computational cost and the memory requirements for performing such color space conversion may be onerous.

SUMMARY

(4) In accordance with an exemplary embodiment, a method is performed wherein a computing device converts multi-dimensional color data encoded in a first color space for a set of pixels in an image into a single dimensional value for each pixel in the set of pixels. The single dimensional values for the pixels in the set of pixels are provided as input into at least a portion of a neural network. With the at least a portion of the neural network, the single dimensional color values of the pixels in the set of pixels are converted into multi-dimensional color values in a second color space that is different than the first color space to produce a representation of the set of pixels in the second color space.

(5) The converting of the multi-dimensional color data may be performed by a neural network. The method may further include training the neural network to perform the converting of the multi-dimensional color data. The neural network used in the converting of the multi-dimensional color

data may be part of the neural network that converts the single dimensional color values. The neural network may be a convolutional variational autoencoder. The first color space may be the RGB color space and the second color space is the LAB color space. The first color space or the second color space may be one of an RGB color space, a LAB color space, an HSV color space, a CMYK color space, a YUV color space, a HSL color space, an ICtCp color space or a CIE color space. The multi-dimensional color values in the second color space may be compressed relative to the multidimensional color values in the first color space. The set of pixels may constitute all or substantially all of the pixels of the image.

(6) In accordance with an exemplary embodiment, a method is performed. Per the method, a neural network executes on one or more computing devices and converts multi-dimensional color data encoded in a first color space for a set of pixels in an image into a single dimensional value for each pixel in the set of pixels. An image processing operation is performed on the single dimensional values for the set of pixels.

(7) The image processing operation may be one of image segmentation, image classification, object classification, image filtering or image enhancement. The image processing operation may produce a modified version of the single dimensional values. The method may further comprise converting the modified version of the single dimensional values into multidimensional values in a second color space. The image processing operation may be segmentation and wherein the method further comprises outputting a likely segmentation of the image. The image processing operation may be image classification or object classification and a likely classification of the image or a likely classification of an object in the image may be output. The method may be performed by the neural network.

(8) In accordance with an exemplary embodiment, a non-transitory computer-readable storage medium stores computer-executable instructions for execution by a processor. The instructions cause the processor to receive a set of image color data for an image encoded in a first color space and create an embedded representation of the set of image color data in a latent space with a neural network. A first decoder is trained to convert a representation of the set of image color data in a second color space from the embedded representation. A second decoder is trained to convert a representation of the set of image color data in a third color space from the embedded representation.

(9) Instructions for using the first decoder to convert the representation of the set of image color data in the second color space from the embedded representation may be stored on the storage medium. Instructions for using the second decoder to convert the representation of the set of image color data in the third color space from the embedded representation may be stored on the storage medium. The embedded representation may be a representation of less data dimensionality than the received set of image color data. The embedded representation may have color data of a single dimension.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A depicts a block diagram of an illustrative color conversion system for an exemplary embodiment.

(2) FIG. 1B depicts a flowchart of illustrative steps that may be performed to convert between color spaces using a neural network in an exemplary embodiment.

(3) FIG. 2A depicts an illustrative neural network for use in an exemplary embodiment.

(4) FIG. 2B depicts a flowchart of illustrative steps for performing color conversion in an exemplary embodiment.

(5) FIG. 3 depicts a block diagram of illustrative encoders.

(6) FIG. 4 depicts a block diagram of illustrative decoders.

(7) FIG. 5 depicts a block diagram where in an image processing operation is performed on values in a latent space.

(8) FIG. 6 depicts a diagram of possible image processing operations.

(9) FIG. 7 depicts a block diagram of a computing environment suitable for an exemplary embodiment.

DETAILED DESCRIPTION

(10) Exemplary embodiments may provide an approach to converting multidimensional color data for an image encoded in a first color space into an intermediate form that is a single dimensional value. The exemplary embodiments may then decode the intermediate form value to produce an encoding of the color data that is encoded in a second color space that differs from the first color space. In this manner, the data for the image may be efficiently converted from an encoding in the first color space into an encoding in the second color space. The reduction of the dimensionality of the data in the intermediate form reduces the memory requirements and computational resources needed for the conversion. The conversion may be performed more quickly than conventional conversion approaches that do not reduce the dimensionality of the intermediate form. This model may be used to create embeddings. Other models may be built quickly off the embeddings (similar to text embeddings, see word2vec, glove, etc.). This can improve model accuracy and make models more transferable between domains.

(11) In the exemplary embodiments, the conversion approach may be performed by a neural network. The neural network may receive an encoding of the image data in the first color space as input. The neural network may process the input to produce an embedding in a latent space. The embedding may be a single dimensional value, whereas the input may be a multidimensional value. The portion of the neural network that performs the encoding may be viewed as an encoder. The neural network also may include a decoder that decodes the single dimensional embedding into a multidimensional representation of the color data for the image in the second color space. The neural network may be, for example, a convolutional variational autoencoder or in particular, a multi-modal convolutional variational autoencoder.

(12) The neural network may be trained to realize different encodings. For example, the neural network may be trained to generate an embedding in the latent space from color data for an image encoded in the RGB space, encoded in the LAB space, encoded in the CMYK space, etc. Thus, a number of different encoders may be realized and used as needed, depending on the input. Similarly, the decoding may decode the embedding into color values in the RGB space, in the LAB space, in the CMYK space, etc. Thus, a number of different decoders may be realized and used as needed, depending on the desired output.

(13) The embedding need not be converted directly into an output encoded in a different color space. Image processing operations may be performed on the embeddings for an image and then the resulting processed representation may be used to generate the output in the desired color space. The image processing operations may include, for example, image segmentation, image filtering, image enhancement, image or object classification or other operations.

(14) The neural network is trained on color data for images to learn how to encode the embeddings in the latent space. The neural network also is trained to produce the color data outputs in different color spaces from the embeddings. The training may entail having the neural network process a large amount of training data, such as from a library of image data.

(15) FIG. 1A depicts an illustrative color space conversion system **100** that is suitable for an exemplary embodiment. In the color space conversion system **100**. Image data encoded in a first color space **102** is input into a neural network **104** for processing. The neural network **104** processes the image data encoded in the first color space **102** to convert the data into image data encoded in a second color space **106**, which is output from the neural network **104**. The first color space and the second color space differ. Examples of color spaces include but are not limited to a

RGB color space, a LAB color space, a CMYK color space, a XYZ color space, a HSV color space, a YUV color space, a HSL color space, an ICtCp color space or a CIE color space.

(16) FIG. 1B provides a flowchart **130** of illustrative steps in the color space conversion process using a neural network in an exemplary embodiment. First, a training set of data is obtained (**132**). The training set may include image data in input color spaces and the proper conversion of the image data into converted color spaces. The training set preferably is large and diverse so as to ensure that the neural network **104** is properly and fully trained. The neural network is trained on the training set (**134**). During training, the neural network **104** processes the input image data in the training set and converts the image data into image data encoded in a target color space. The resulting conversion is compared to the correct conversion, and the settings of the nodes in the neural network **104** are adjusted to reduce the error and improve the result based on the comparison. Once the neural network **104** is trained, the neural network **104** is used to perform color conversion to the target color space (**136**).

(17) FIG. 2A depicts a block diagram of an illustrative neural network **200** for an exemplary embodiment. The neural network **200** may be a variational auto-encoder. The neural network **200** is trained on images that start in a source color space and has multiple target color spaces for the output. The operation of the neural network **200** will be described with reference to the flowchart **238** of FIG. 2B. The neural network **200** may include an input layer **202** for receiving input. In the exemplary embodiments, the input may be color data for an image encoded in a first color space (**240**). The input is then processed by intermediate layers **204**, which may include convolutional layers, sparse convolutional layers, pooling layers and the like. These intermediate layers **204** perform the encoding operation on the input. The intermediate layers **204** reduce the dimensionality of the input (**242**). This reduction in dimensionality may be performed by sparse convolutional or pooling layers. The intermediate layers **204** produce a single value per input element (e.g., pixel, voxel, etc.) (**244**). Thus, the input layer **202** and the intermediate layers act as an encoder **212** for encoding values **207** in a latent space **206**. The values are the embeddings, and the latent space is a representation of compressed data in which similar data points are closer together in space.

(18) The intermediate layers **208** may process the values **207** to produce the color data values encoded in the second color space, which differs from the first color space. In particular, each of the values **207** in the latent space is decoded to produce color values for elements of an image in the second color space (**246**). The dimensionality of the resulting color data values in the second color space may be expanded relative the values **207** in the latent space **206**. The intermediate layers **208** may include deconvolutional layers that increase dimensionality. The resulting converted color data is then output by the output layer **210** (**248**). The intermediate layers **208** and the output layer **210** form a decoder **214** hence form a decoder that decode the values **207** in the latent space to produce a reconstructed image encoded in the second color space.

(19) The neural network **200** need not be limited to input encoded in a particular color space; rather the neural network **200** may be able to encode input color data for an image encoded in different color spaces. For example, as shown in FIG. 3, encoders may be trained and used for encoding from different color spaces into values **207** the latent space **206**. For example, an encoder **304** may receive input color data for an image encoded in the RGB color space (i.e., an RGB value **302**) and produce a latent value **306** (i.e., an embedding). Similarly, an encoder **310** may receive a LAB value **308** input (i.e., color data for an image encoded in the LAB color space) and convert it into a latent value **312**. Likewise, an encoder **316** receives a CMYK value **314** and produces an output latent value **318**. These examples are illustrative and not intending to be limiting or exhaustive. Once the neural network **200** has the various encoders **304**, **310** and **316**, the neural network may choose which encoder to use based on the input.

(20) The neural network may train and use a number of different decoders as well. FIG. 4 shows an example where there are four decoders **404**, **406**, **408** and **410** that may be used to decode a latent value **402** into different respective color space values. For instance, decoder **404** outputs an RGB

value **412**, decoder **406** outputs a LAB value, decoder **408** outputs a CMYK value and decoder **410** outputs a YUV value. Decoders may also be trained and used that produce outputs encoded in other color spaces. Depending on the desired color space output, the neural network may choose the appropriate decoder.

(21) The neural network **200** thus may mix and match the encoders and decoders based on the input and desired output. For example, encoder **304** may be paired with decoder **406** to convert an RGB input into a LAB output, or encoder **310** may be paired with decoder **410** to convert a LAB input into an YUV output. The neural network may be multimodal to accommodate these numerous options.

(22) The above discussion has focused on instances where the values **207** in the latent space **206** are directly converted into values encoded in the second color space without any intervening processing. FIG. 5 depicts an arrangement **500** in which intervening processing occurs. In FIG. 5, input color data for an image encoded in a first color space is input to encoder **502**. The encoder is part of a neural network **200**. The encoder **502** encodes the input **501** into latent values **504**. At least one image processing operation **506** is performed on the latent values **504**. The processed latent values are passed to decoder **508**, which produces output color data **510** for an image encoded in a second color space. The image processing operations may be performed more quickly and/or consuming less computational or memory resources due to the compressed nature of the latent values relative to the input **501**.

(23) FIG. 6 depicts a diagram **600** of different image processing operations **602** that may be performed in **506**. Image segmentation **604** may be performed. Image segmentation **604** partitions a digital image into segments (e.g., sets of pixels) that are useful in locating objects and boundaries in the image. Image enhancement **606** may be performed. Image enhancement may remove noise, sharpen the image and/or brighten the image, for example. Image or object classification **608** may be performed. For example, the identity of objects in an image (e.g., a hat) may be determined or the identity of what is depicted may be determined (e.g., the image is of a horse). Image filtering **610** may be performed and other operations **612** may be performed.

(24) It should be appreciated that the image processing operation **506** need not be performed before decoding. In some exemplary embodiments, the image processing operation **506** is better performed in the second color space. As such, the image processing operation **506** is performed on the output in the second color space. For example, it may be easier to detect objects in the LAB color space rather than the RGB color space.

(25) FIG. 7 depicts a computing environment **700** suitable for practicing the exemplary embodiments. The computing environment **700** may include a neural network model **702** for implementing the neural network used in the color conversion. The neural network model **702** may be implemented in software executed by processing logic **704**. The processing logic **704** may include one or more processors **706**, such as central processing units (CPUs), graphics processing units (GPUs), application specific integrated circuits (ASICs) or field programmable gate arrays (FPGAs). The processors **706** may each include multiple cores or multiple interconnected processing units. The processing logic may include one or more accelerators **708**. The accelerators may include circuitry and custom hardware for speeding the execution of the neural network model **702**. The custom hardware may include a processor optimized for handling neural network operations. The processing logic may be contained in a single computer, like a personal computer (PC) or a server, or may be spread across multiple computers, such as in a server cluster, in a cloud computing environment or across peer computing systems.

(26) The computing environment **700** may include a storage **710** for storing the neural network model **702**. The storage **710** may include a magnetic storage device, an optical storage device or a combination thereof. The storage **710** may include solid state storage, hard drives, removable storage elements such as magnetic disks, optical disks, thumb drives, or the like. The storage **1104** may include RAM, ROM, and other varieties of integrated circuit storage devices. The storage may

be a singular storage device or may include multiple devices located together or remotely from each other. The storage **710** may include non-transitory computer-readable storage media, such as the types of memory and storage described above. The non-transitory computer-readable storage media may include computer program instructions for realizing the functionality of the exemplary embodiments described above. These instructions may include those of the neural network model **702**.

(27) While the present application has been described with reference to exemplary embodiments herein, it will be appreciated that various changes in form and detail may be made without departing from the intended scope as defined in the appended claims.

Claims

1. A method, comprising: determining, by a neural network, a first color space of an image received as input, the image encoded in the first color space; selecting, by the neural network based on the determined first color space of the image, a first encoder of a plurality of encoders to convert respective pixels of a first plurality of pixels of the image into a respective single-dimensional color value; converting, by the first encoder, the respective pixels of the first plurality of pixels of the image into the respective single-dimensional color value; selecting, by the neural network based on an output color space that is different than the first color space, a first decoder of a plurality of decoders to decode each respective single dimensional color value into a respective pixel of a second plurality of pixels in the output color space; and decoding, by the first decoder, each respective single dimensional color value into the respective pixel of the second plurality of pixels in the output color space.
2. The method of claim 1, wherein respective ones of the plurality of encoders and the plurality of decoders are trained using distinct color spaces.
3. The method of claim 1, further comprising: performing an image processing operation on the single-dimensional color values.
4. The method of claim 1, wherein the second plurality of pixels in the output color space are compressed relative to the first plurality of pixels in the first color space.
5. The method of claim 1, wherein a plurality of embedding values include the single-dimensional color values.
6. The method of claim 1, wherein the image is a three-dimensional image, wherein a plurality of voxels of the three-dimensional image include the first plurality of pixels, wherein the first encoder encodes the plurality of voxels into the respective single-dimensional color values.
7. The method of claim 1, wherein the first color space or the output color space is one of a RGB color space, an LAB color space, an HSV color space, a CMYK color space, a YUV color space, a HSL color space, an ICtCp color space, or a CIE color space.
8. A non-transitory computer-readable storage medium, the computer-readable storage medium including instructions that when executed by a processor, cause the processor to: determine, by a neural network, a first color space of an image received as input, the image encoded in the first color space; select, by the neural network based on the determined first color space of the image, a first encoder of a plurality of encoders to convert respective pixels of a first plurality of pixels of the image into a respective single-dimensional color value; convert, by the first encoder, the respective pixels of the first plurality of pixels of the image into the respective single-dimensional color value; select, by the neural network based on an output color space that is different than the first color space, a first decoder of a plurality of decoders to decode each respective single dimensional color value into a respective pixel of a second plurality of pixels in the output color space; and decode, by the first decoder, each respective single dimensional color value into the respective pixel of the second plurality of pixels in the output color space.
9. The computer-readable storage medium of claim 8, wherein the instructions further cause the

processor to: perform an image processing operation on the single-dimensional color values.

10. The computer-readable storage medium of claim 8, wherein respective ones of the plurality of encoders and the plurality of decoders are trained using distinct color spaces.

11. The computer-readable storage medium of claim 8, wherein the second plurality of pixels in the output color space are compressed relative to the first plurality of pixels in the first color space.

12. The computer-readable storage medium of claim 8, wherein a plurality of embedding values include the single-dimensional color values.

13. The computer-readable storage medium of claim 8, wherein the image is a three-dimensional image, wherein a plurality of voxels of the three-dimensional image include the first plurality of pixels, wherein the first encoder encodes the plurality of voxels into the respective single-dimensional color values.

14. The computer-readable storage medium of claim 8, wherein the first color space or the output color space is one of a RGB color space, an LAB color space, an HSV color space, a CMYK color space, a YUV color space, a HSL color space, an ICtCp color space, or a CIE color space.

15. A computing apparatus comprising: a processor; and a memory storing instructions that, when executed by the processor, cause the processor to: determine, by a neural network, a first color space of an image received as input, the image encoded in the first color space; select, by the neural network based on the determined first color space of the image, a first encoder of a plurality of encoders to convert respective pixels of a first plurality of pixels of the image into a respective single-dimensional color value; convert, by the first encoder, the respective pixels of the first plurality of pixels of the image into the respective single-dimensional color value; select, by the neural network based on an output color space that is different than the first color space, a first decoder of a plurality of decoders to decode each respective single dimensional color value into a respective pixel of a second plurality of pixels in the output color space; and decode, by the first decoder, each respective single dimensional color value into the respective pixel of the second plurality of pixels in the output color space.

16. The computing apparatus of claim 15, wherein respective ones of the plurality of encoders and the plurality of decoders are trained using distinct color spaces.

17. The computing apparatus of claim 15, wherein the instructions further cause the processor to: perform an image processing operation on the single-dimensional color values.

18. The computing apparatus of claim 15, wherein the second plurality of pixels in the output color space are compressed relative to the first plurality of pixels in the first color space.

19. The computing apparatus of claim 15, wherein a plurality of embedding values include the single-dimensional color values.

20. The computing apparatus of claim 15, wherein the first color space or the output color space is one of a RGB color space, an LAB color space, an HSV color space, a CMYK color space, a YUV color space, a HSL color space, an ICtCp color space, or a CIE color space.
