

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412684
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ma; Bin et al.

Wall bushing

Abstract

A wall bushing, comprising a head assembly, a conductive rod, and a connecting terminal sealing and covering the head assembly and the conductive rod. The connecting terminal and the conductive rod are electrically connected. The head assembly includes a transition tank and a transition plate that are connected to each other. An upper end of the transition tank is provided with a first through hole, and a lower end of the transition tank is hole-through. The transition plate is provided with a second through hole. The conductive rod extends through the first through hole and the second through hole. The transition tank and the transition plate are fixedly connected such that an accommodation cavity is formed around the conductive rod and in the transition tank.

Inventors:	Ma; Bin (Nantong, CN), Liu; Chao (Nantong, CN)
Applicant:	JIANGSU SHEMAR ELECTRIC CO., LTD. (Jiangsu, CN)
Family ID:	80844909
Assignee:	JIANGSU SHEMAR ELECTRIC CO., LTD. (Jiangsu, CN)
Appl. No.:	18/245304
Filed (or PCT Filed):	September 07, 2021
PCT No.:	PCT/CN2021/116947
PCT Pub. No.:	WO2022/062894
PCT Pub. Date:	March 31, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230368947 A1	Nov. 16, 2023

Foreign Application Priority Data

CN	202011015775.8	Sep. 24, 2020
----	----------------	---------------

Publication Classification

Int. Cl.: **H01B17/58** (20060101); **H01B17/30** (20060101); **H01B17/36** (20060101)

U.S. Cl.:

CPC **H01B17/583** (20130101); **H01B17/301** (20130101); **H01B17/36** (20130101);

Field of Classification Search

CPC: H01B (17/583); H01B (17/301); H01B (17/36); H01B (17/12); H01B (17/30); H01B (17/00); H01B (17/56); H02G (3/0468); H02G (3/0462); H02G (3/04); H02G (3/00); H02G (3/02)

USPC: 174/152R; 174/153R; 174/137R; 174/138R; 174/174; 174/11BH; 174/14BH; 174/12BH; 174/30; 174/31R; 174/142; 16/2.1; 16/2.2

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2896008	12/1958	Putz	174/152R	H01B 17/301
4767351	12/1987	Patel	174/152R	H01B 17/265
7812266	12/2009	Rocks	16/2.2	H01B 17/265
8003891	12/2010	Rocks	16/2.2	H01B 17/28

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101318699	12/2007	CN	N/A
202487340	12/2011	CN	N/A
104505784	12/2014	CN	N/A
105977887	12/2015	CN	N/A
107634495	12/2017	CN	N/A
107654738	12/2017	CN	N/A
107706854	12/2017	CN	N/A
108492945	12/2017	CN	N/A
208738735	12/2018	CN	N/A
110676779	12/2019	CN	N/A
110729684	12/2019	CN	N/A
111180165	12/2019	CN	N/A
112186679	12/2020	CN	N/A
112310912	12/2020	CN	N/A
112310913	12/2020	CN	N/A
214204810	12/2020	CN	N/A
214204811	12/2020	CN	N/A
102008000494	12/2008	DE	N/A
3413319	12/2017	EP	N/A

OTHER PUBLICATIONS

European Patent Office, Extended Search Report issued in corresponding Application No. 21871266.9, dated Jul. 26, 2024, 9 pp. cited by applicant

Chinese Patent Office, Office Action issued in corresponding Application No. 202011018229.X, dated Aug. 30, 2024, 6 pp. cited by applicant

Chinese Patent Office, Office Action issued in corresponding Application No. 202011015775.8, dated Aug. 30, 2024, 6 pp. cited by applicant

International Search Report for corresponding Application No. PCT/CN2021/116947 dated Dec. 1, 2021, 7 pages. cited by applicant

Written Opinion for corresponding Application No. PCT/CN2021/116947 dated Dec. 1, 2021, 4 pages. cited by applicant

Chinese Patent Office, Second Office Action issued in corresponding Application No. 202011015775.8, dated Mar. 27, 2025, 12 pp. cited by applicant

Primary Examiner: Estrada; Angel R

Attorney, Agent or Firm: Taft Stettinius & Hollister LLP

Background/Summary**CROSS REFERENCE TO RELATED APPLICATION**

(1) This application is a national stage for International Application PCT/CN2021/116947, filed on Sep. 7, 2021, which claims the priority benefit of Chinese Patent Application No. 202011015783.2, filed on Sep. 24, 2020, Chinese Patent Application No. 202011018229.X, filed on Sep. 24, 2020, and Chinese Patent Application No. 202011015775.8, filed on Sep. 24, 2020. The entireties of these applications are incorporated by reference herein for all purposes.

TECHNICAL FIELD

(2) The present disclosure relates to the technical field of power transmission insulation equipment, in particular to a wall bushing.

BACKGROUND

(3) In a direct current (DC) power transmission and transformation project, a wall bushing, as the only electrical component connecting the inside and outside of a valve hall, carries the full voltage and current of all lines, and thus the performance reliability of the wall bushing is related to the operational safety and stability of the all lines.

(4) At present, most of head assemblies of the existing wall bushings are corrugated tubes. A conductive rod is connected to the corrugated tube in an axial sealing manner, and the conductive rod passes through the corrugated tube to be directly electrically connected to external components. Specifically, an end of the conductive rod is fixed to an end of the wall bushing, the other end of the conductive rod is fixed to the corrugated tube and extends out of the corrugated tube for electrical connection with external components. The corrugated tube, which has elasticity, provides tensioning force to the conductive rod to maintain the tension of the conductive rod. When the conductive rod is heated and elongated, the corrugated tube can be elastically deformed, so that the conductive rod remains straight without stress bending. However, there are the following problems: when a head assembly of the wall bushing adopts the corrugated tube, if the axial seal is used, due to the long-term friction of thermal expansion and contraction, the long-term reliability of the dynamic seal cannot be guaranteed, and thus the wall bushing is prone to gas leakage; if the axial

seal is not used, an external transition tank is required, and a soft connection is required to be used between a connecting terminal and the conductive rod, and the through-current capability is limited. In addition, the expensive corrugated tube increases the manufacturing cost of the wall bushing, and metal chips are easily generated due to friction between the conductive rod and the head assembly, resulting in internal discharge.

SUMMARY

(5) Based on the deficiencies of the prior art, an object of the present disclosure is to provide a wall bushing, which has a simple structure, saves the corrugated tube structure, avoids the use of an axial dynamic sealing device, greatly improves the sealing reliability of the wall bushing, and reduces production costs.

(6) For realizing the above-mentioned object of the present disclosure, the technical means adopted in the present disclosure are as follows. A wall bushing includes a head assembly, a conductive rod, and a connecting terminal sealing and covering the head assembly and the conductive rod. The connecting terminal is electrically connected to the conductive rod. The head assembly includes a transition tank and a transition plate that are connected to each other. An upper end of the transition tank is provided with a first through hole, and a lower end of the transition tank is hole-through. The transition plate is provided with a second through hole. The conductive rod extends through the first through hole and the second through hole. The transition tank and the transition plate are fixedly connected so that an accommodating cavity is formed around the conductive rod and in the transition tank. The wall bushing has a simple structure, saves the corrugated tube structure, avoids the use of an axial dynamic sealing device, greatly improves the sealing reliability of the wall bushing, and reduces production costs.

(7) Preferably, the wall bushing further includes a protective cover. The protective cover is a ring-shaped casing that is hole-through in an up-down direction. The protective cover surrounds the second through hole, and is mounted at a lower end of the head assembly. The conductive rod extends through the first through hole, the second through hole, and the protective cover. The arrangement of the protective cover further prevents possible metal chips or other debris from entering the main insulating cavity of the wall bushing, improving the operation reliability of the wall bushing.

(8) Preferably, the protective cover is made of metal. A gap is formed between the protective cover and the conductive rod. The generation of metal chips due to the secondary friction between the protective cover and the conductive rod can be prevented, and the protective cover made of metal plays a shielding role to a certain extent, which improves the operation reliability of the wall bushing.

(9) Preferably, the wall bushing further includes a protective corrugated tube. The protective corrugated tube is a ring-shaped casing that is hole-through in an up-down direction. The protective corrugated tube is provided with an upper through hole and a lower through hole. The conductive rod extends through the first through hole, the second through hole, the upper through hole, and the lower through hole. The protective corrugated tube is provided with an upper connecting end around the upper through hole. The upper connecting end surrounds the second through hole and is fixedly connected to a lower end of the head assembly. The lower through hole is fixedly connected to the conductive rod. The arrangement of the protective corrugated tube further prevents possible metal chips or other debris from entering the main insulating cavity of the wall bushing, thereby improving the operation reliability of the wall bushing.

(10) Preferably, the upper connecting end is a flange plate extending along a radial direction of the upper through hole. The flange plate is attached to and fixedly connected to the lower end of the head assembly. The flange plate and the head assembly are connected in a planar contact with each other, which is convenient for mounting and reliable in structure.

(11) Preferably, a mounting hole is arranged on the flange plate. A passage is arranged between the mounting hole and the upper through hole for providing a communication of the mounting hole

with the upper through hole. A filter element is mounted in the mounting hole. The filter element is configured for only gas exchange between an inside of the protective corrugated tube and an outside of the protective corrugated tube. During the process of inflating and deflating of the wall bushing, only gas is allowed to pass through, and internal impurities, metal chips and the like cannot enter the main insulating cavity through the filter element.

(12) Preferably, a diameter of the lower through hole is less than a minimum inner diameter of the protective corrugated tube. A lower connecting end is arranged around the lower through hole. A first round nut and a second round nut are arranged on two sides of the lower connecting end, respectively. The first round nut and the second round nut are respectively threadedly connected with the conductive rod to clamp the lower connecting end so that the protective corrugated tube is fixedly connected to the conductive rod. The protective corrugated tube is fixedly connected to the conductive rod, so that on the one hand, no gap is formed between the protective corrugated tube and the conductive rod, which ensures that impurities and metal chips in the protective corrugated tube cannot enter the main insulating cavity; on the other hand, the conductive rod is deformed due to thermal expansion and cold contraction, and the protective corrugated tube has a certain space for elastic deformation, and a size of the protective corrugated tube is capable of changing accordingly with the deformation of the conductive rod, which ensures stable connections of the various components of the wall bushing.

(13) Preferably, a plurality of circular grooves is arranged on a sidewall of the transition tank and surrounds the conductive rod. The circular groove functions as a particle trap to absorb metal particles in the transition tank, and ensures the stability of the electrical property of the head portion of the wall bushing.

(14) Preferably, the lower end of the transition tank extends to form a first connecting part along an outer periphery of the transition tank. The first connecting part is in a sealed connection with the transition plate. The arrangement of the first connecting part facilitates the fixed connection between the transition tank and the transition plate. The sealed connection ensures that the interior of the transition tank is not intruded by moisture, and avoids affecting electrical properties.

(15) Preferably, a non-metallic lining is arranged on an inner wall of the first through hole and/or an inner wall of the second through hole, which prevents the metal chips from being generated due to friction between the conductive rod and the transition plate, and between the conductive rod and the transition tank, thereby improving the operation reliability of the wall bushing.

(16) Preferably, the connecting terminal includes a connecting part, an accommodating part, and a second connecting part that are sequentially arranged. The accommodating part is configured for accommodating an end of the conductive rod, and is electrically connected to the conductive rod. The second connecting part is in a sealed connection with the upper end of the transition tank. The connecting terminal is an electrical connection component of the wall bushing and is used for electrical connection with other devices. The arrangement of the second connecting part facilitates the fixed connection of the connecting terminal to the transition tank.

(17) Preferably, contact springs are arranged at the end of the conductive rod. The contact springs abut against an inner wall of the accommodating part; and a gap is formed between the accommodating part and the end of the conductive rod in an axial direction of the conductive rod. The contact springs are in close contact with the connecting terminal and the end of the conductive rod at the same time, so that the electrical connection between the connecting terminal and the end of the conductive rod is stable, and thus the equipotential of the head assembly is maintained, and the heating problem of the head portion is solved. The gap is formed between the accommodating part and the end of the conductive rod in the axial direction of the conductive rod, which is capable of absorbing the deformation due to thermal expansion and contraction, of the conductive rod, and prevent the conductive rod from being bent due to the fixed connection.

(18) Preferably, an upper surface and/or a lower surface of the transition plate is provided with a protruding ring around the second through hole. The arrangement of the protruding ring increases

the area supporting the conductive rod, which improves the bending resistance of the conductive rod.

(19) Preferably, the wall bushing further includes a hollow insulator. The hollow insulator is in a sealed connection with the transition plate. For example, A flange of the hollow insulator is in a sealed connection with a lower surface of the transition plate. The conductive rod extends through the hollow insulator. The hollow insulator provides insulation protection for the conductors inside the wall bushing.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a partial cross-sectional view of a wall busing **100** according to an embodiment of the present disclosure.
- (2) FIG. 2 is a partial cross-sectional view of a wall busing **100** according to another embodiment of the present disclosure.
- (3) FIG. 3 is a partial cross-sectional view of a wall busing **200** according to an embodiment of the present disclosure.
- (4) FIG. 4 is a partial cross-sectional view of a wall busing **200** according to another embodiment of the present disclosure.
- (5) FIG. 5 is a partial cross-sectional view of a wall busing **200** according to yet another embodiment of the present disclosure.
- (6) FIG. 6 is a perspective schematic view of a protective corrugated tube **250** according to an embodiment of the present disclosure.
- (7) FIG. 7 is an overall cross-sectional view of a filter element **260** according to an embodiment of the present disclosure.
- (8) FIG. 8 is a partial cross-sectional view of a wall bushing **300** according to an embodiment of the present disclosure.
- (9) FIG. 9 is a partial cross-sectional view of a wall bushing **300** according to another embodiment of the present disclosure.
- (10) FIG. 10 is a partial cross-sectional view of a wall bushing **300** according to yet another embodiment of the present disclosure.
- (11) FIG. 11 is a partial cross-sectional view of a wall bushing **400** according to an embodiment of the present disclosure.
- (12) FIG. 12 is a cross-sectional view of a connecting terminal **440** according to an embodiment of the present disclosure.
- (13) FIG. 13 is a partial cross-sectional view of a wall bushing **400** according to another embodiment of the present disclosure.
- (14) FIG. 14 is a partial cross-sectional view of a wall bushing **400** according to yet another embodiment of the present disclosure.
- (15) FIG. 15 is a partial cross-sectional view of a wall bushing **500** according to an embodiment of the present disclosure.
- (16) FIG. 16 is an overall cross-sectional view of the wall bushing **500** shown in FIG. 15.
- (17) FIG. 17 is a partial cross-sectional view of a wall bushing **500** according to another embodiment of the present disclosure.
- (18) FIG. 18 is an overall cross-sectional view of the wall bushing **500** shown in FIG. 17.
- (19) FIG. 19 is a partial cross-sectional view of a wall bushing **500** according to yet another embodiment of the present disclosure.
- (20) FIG. 20 is an overall cross-sectional view of the wall bushing **500** shown in FIG. 19.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(21) As required, specific embodiments of the present disclosure will be disclosed herein. However, it should be understood that the embodiments disclosed herein are merely typical examples of present disclosure, which can be embodied in various forms. Therefore, specific details disclosed herein are not to be considered to be limited, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ present disclosure in any appropriate way in practice, which includes adopting various features disclosed herein and combining features that may not be expressly disclosed herein.

(22) In an embodiment, as shown in FIG. 1, a wall bushing **100** includes a head assembly **110**, a conductive rod **120**, and a connecting terminal **140** that seals and covers the head assembly **110** and the conductive rod **120** (only schematically illustrated in the figure). The connecting terminal **140** is electrically connected to the conductive rod **120**. The head assembly **110** includes a transition tank **111** and a transition plate **112** that are connected to each other. An upper end of the transition tank **111** is provided with a first through hole **1111**, and a lower end of the transition tank **111** is hole-through. The transition plate **112** is provided with a second through hole **1121**. The conductive rod **120** extends through the first through hole **1111** and the second through hole **1121**. The transition tank **111** and the transition plate **112** are fixedly connected, so that an accommodating cavity **113** is formed around the conductive rod **120** and in the transition tank **111**. The wall bushing **100** has a simple structure, and has core components that are the transition tank **111** and the transition plate **112**. The arrangement of the transition tank **111** saves the structure of a corrugated tube. As long as the transition tank **111** is arranged in a sealing manner, that is, sealing measures are applied at the outside of the transition tank **111**, the use of an axial dynamic sealing device can be avoided between the transition tank **111** and the conductive rod **120**, which greatly improves the sealing reliability of the wall bushing **100** and reduces the production cost at the same time. It is particularly worth noting that, it is sufficient that the connecting terminal **140** that seals and covers the head assembly **110** and the conductive rod **120**, the conductive rod **120** are connected with an electrical connection. The electrical connection may be implemented to be a direct contact, or a connection of internal conductors. A shape and a configuration of the connecting terminal **140** is not specifically limited herein.

(23) It should be noted that, in this embodiment, the upper end and the lower end of the head assembly **110** are provided in the concept of relative positions. Along an axial direction of the overall structure of the wall bushing **100**, an end close to the head assembly **110** is the upper end, and an end in a direction away from the head assembly **110** is the lower end. In other embodiments, the definitions of “upper” and “lower” are also provided according to this standard.

(24) In other embodiments, the head assembly may have an integrated cavity structure, as long as it meets the requirements of the rigid assembly, that is, under the interference of external heat conditions, the head assembly will not be deformed and displaced. In this way, it can be ensured that the head assembly will not be deformed and displaced due to the length change of the conductive rod, thereby maintaining the stability of the overall structure of the wall bushing.

(25) In this embodiment, the transition plate **112** is a planar plate. In other embodiments, the shape of the transition plate is not specifically limited.

(26) In this embodiment, the transition tank **111** is a cylindrical tank, and has the upper end that is provided with the first through hole **1111**, and the lower end is hole-through and forms a cylindrical cavity. The first through hole **1111** is in communication with the cylindrical cavity. After the transition tank **111** is fixedly connected to the transition plate **112** and the conductive rod **120** extends through the first through hole **1111** and the second through hole **1121**, the circular cavity surrounding the outside the conductive rod **120** forms the accommodating cavity **113**.

(27) In other embodiments, the shape of the transition tank may also be non-cylindrical, as long as it can be adapted to the connected components.

(28) In this embodiment, a plurality of circular grooves **1112** is arranged on a sidewall of the transition tank **111** and surrounds the conductive rod **120**. The circular groove **1112** functions as a

particle trap to absorb metal particles in the transition tank **111**, so that the stability of the electrical properties of the head portion of the wall bushing **100** is ensured.

(29) In this embodiment, four circular grooves **1112** are provided. In other embodiments, the number of circular grooves is not limited and is reasonably designed according to a size of the inner wall of the transition tank. However, it can be understood that the more the number of circular grooves and the denser the circular grooves, the better the effect of adsorbing metal particles.

(30) In this embodiment, the circular groove **1112** is in the shape of a rectangular groove. In other embodiments, the circular groove may also be an arc groove or an irregularly shaped groove, and the shape of the circular groove is not specifically limited herein.

(31) In this embodiment, the lower end of the transition tank **111** extends along an outer periphery of the transition tank **111**, so as to form a first connecting part **1114**, and the first connecting part **1114** is in a sealed connection with the transition plate **112**. The arrangement of the first connecting part **1114** facilitates the fixed connection between the transition tank **111** and the transition plate **112**. The sealed connection can ensure that the interior of the transition tank **111** is not intruded by moisture, so as to avoid affecting electrical properties.

(32) In this embodiment, a first sealing groove **1122** is arranged on the transition plate **112**. A first sealing ring (not shown in figures) is arranged in the first sealing groove **1122**. In other embodiments, the first sealing groove may also be arranged on the first connecting part, or both the first connecting part and the transition plate are provided with a sealing groove to mount a sealing ring.

(33) In this embodiment, the through holes corresponding to each other are arranged on the first connecting part **1114** and the transition plate **112**, and the first connecting part **1114** and the transition plate **112** are fixedly connected by means of bolt connection (not shown in figures). In other embodiments, the first connecting part and the transition plate may be connected by gluing, welding, or a combination of the above fixed connections.

(34) In this embodiment, a portion of the conductive rod **120** located at and above the transition tank **111** is a solid structure, and a portion of the conductive rod **120** located below the transition tank **111** is a hollow structure. The solid structural portion of the conductive rod **120** has good electrical conductivity, and the hollow structural portion of the conductive rod **120** reduces the weight of the conductive rod **120**, thereby reducing the overall weight of the wall bushing **100** and reducing the cost.

(35) In other embodiments, the conductive rod can be a fully solid structure, or a completely hollow structure. In the case that the conductive rod is the completely hollow structure, the portion of the hollow conductive rod that is located at and above the transition tank is arranged to have a larger wall thickness.

(36) The wall bushing **100** according to the present embodiment is simple in structure, and has the core components that are the transition tank **111** and the transition plate **112**. The arrangement of the transition tank **111** saves the structure of the corrugated tube. As long as the transition tank **111** can be arranged in a sealing manner, that is, sealing measures are applied at the outside of the transition tank **111**, the use of an axial dynamic sealing device can be avoided between the transition tank **111** and the conductive rod **120**, which greatly improves the sealing reliability of the wall bushing **100** and reduces the production cost at the same time.

(37) In an application scenario, as shown in FIG. 2, the wall bushing **100** further includes a protective cover **150**. The protective cover **150** is a ring-shaped casing **152** that is hole-through in an up-down direction. The protective cover **150** surrounds the second through hole **1121**, and is mounted at the lower end of the head assembly **110**. The conductive rod **120** extends through the first through hole **1111**, the second through hole **1121**, and the protective cover **150**. The connecting terminal **140** is electrically connected to the conductive rod **120**, and seals and covers the head assembly **110** and the conductive rod **120**. The arrangement of the protective cover **150** further

prevents possible metal chips or other debris from entering the main insulating cavity of the wall bushing **100**, improving the operation reliability of the wall bushing **100**.

(38) In this embodiment, the protective cover **150** is made of metal, and a gap is formed between the protective cover **150** and the conductive rod **120**. The arrangement of the gap can prevent the generation of metal chips due to the secondary friction between the protective cover **150** and the conductive rod **120**. The protective cover **150** made of metal can also play a shielding role to a certain extent, improving the operation reliability of the wall bushing **100**.

(39) In other embodiments, the protective cover may also be made of non-metallic material, as long as the generation of metal chips due to the secondary friction between the protective cover and the conductive rod can be prevented.

(40) In this embodiment, an edge curl **151** is formed on a side of a lower end of the protective cover **150** close to the conductive rod **120**, and there is a gap between the edge curl **151** and the conductive rod **120**. Due to the arrangement of the edge curl **151**, the metal chips can remain in the edge curl **151**. Further, there is no sharp friction between the edge curl **151** and the conductive rod **120**, which can prevent more unwanted metal chips from being generated due to accidental contact.

(41) In this embodiment, the upper end of the protective cover **150** surrounds the outer periphery of the ring-shaped casing **152** of the protective cover **150**, and extends outward to form a circular cover connecting part **153**. The cover connecting part **153** is attached to the lower end of the head assembly **110**. The lower end of the head assembly **110** is provided with a threaded hole, and a through hole corresponding to the above threaded hole is arranged on the cover connecting part **153**, so that the cover connecting part **153** and the lower end of the head assembly **110** are fixed by means of bolt connection.

(42) In other embodiments, a threaded hole may be arranged at the cover connecting part, and a through hole corresponding to the above threaded hole is arranged at the lower end of the head assembly. In this way, the cover connecting part and the lower end of the head assembly can be also fixed by means of bolt connection. It should be noted that since there is no fixed connection between the conductive rod and the head assembly, the arrangement of the through hole and the threaded hole for the bolt connection does not affect the assembly sequence of the wall bushing.

(43) In this embodiment, the protective cover **150** is a circular casing. In other embodiments, the shape of the ring-shaped casing may also be configured to other shapes, such as square ring, oval ring, and which is not limited to the circular ring.

(44) In other embodiments, the cover connecting part and the lower end of the head assembly may be connected by gluing, welding, etc., as long as the effective connection between the cover connecting part and the lower end of the head assembly can be ensured.

(45) In another embodiment, as shown in FIG. 3, a wall bushing **200** is provided. A lower surface **2122** of a transition plate **212** is provided with a protruding ring **2123** around a second through hole **2121**. The arrangement of the protruding ring **2123** increases the area supporting the conductive rod **220**, which improves the bending resistance of the conductive rod **220**.

(46) In yet another embodiment, the protruding ring **2123** may be arranged on an upper surface of the transition plate **212**. As shown in FIG. 4, an upper surface **2124** of the transition plate **212** is provided with the protruding ring **2123** around the second through hole **2121**. The arrangement of the protruding ring **2123** increases the area supporting the conductive rod **220**, which improves the bending resistance of the conductive rod **220**.

(47) In this embodiment, the protruding ring **2123** is arranged in an accommodating cavity **213** of the head assembly **210**. The height of the protruding ring **2123** does not exceed the height of the transition tank **211**, that is, a gap is formed between an upper end surface of the protruding ring **2123** and an inner wall of the transition tank **211**, and the upper end surface of the protruding ring **2123** is not in direct contact with the inner wall of the transition tank **211**. In this way, it can be ensured that under the action of heat, even if the protruding ring **2123** undergoes expansion deformation, the protruding ring **2123** will not contact the inner wall of the transition tank **211**, and

will not deform the transition tank **211**, ensuring the reliability of the overall structure of the wall bushing **200**.

(48) The wall bushing **200** further includes a protective cover **250**. The material and structure of the protective cover **250** are the same as those of the aforementioned protective cover **150**, and which is not repeated herein.

(49) Alternatively, in other embodiments, both the upper surface and the lower surface of the transition plate may be provided with protruding rings. Essentially, the arrangement of protruding rings is intended to expand the contact area of the conductive rod and the transition plate, and then increase the area supporting the conductive rod, thereby improving the bending resistance of the conductive rod.

(50) Since the wall bushing **200** according to this embodiment is provided with the protruding ring **2123**, the bending resistance of the conductive rod **220** is improved, thereby improving the overall reliability of the wall bushing **200**.

(51) Further, in another application scenario, as shown in FIGS. 5 to 7, the wall bushing **200** includes a protective corrugated tube **250** instead of the aforementioned protective cover **250**. Specifically, the protective corrugated tube **250** is a ring-shaped casing that is hole-through in an up-down direction. The protective corrugated tube **250** is provided with an upper through hole **251** and a lower through hole **252**. The conductive rod **220** extends through the first through hole **2111**, the second through hole **2121**, the upper through hole **251** and the lower through hole **252**. The protective corrugated tube **250** is provided with an upper connecting end **253** around the upper through hole **251**. The upper connecting end **253** surrounds the second through hole **2121** and is fixedly connected to the lower end of the head assembly **210**. The lower through hole **252** is fixedly connected to the conductive rod **220**. A connecting terminal **240** is electrically connected to the conductive rod **220**, and seals and covers the head assembly **210** and the conductive rod **220**. The wall bushing **200** has a simple structure. The conventional corrugated tube structure is replaced by the head assembly **210**, which avoids the use of an axial dynamic sealing device, greatly improves the sealing reliability of the wall bushing **200**, and reduces production costs. The arrangement of the protective corrugated tube **250** further prevents possible metal chips or other debris from entering the main insulating cavity of the wall bushing **200**, thereby improving the operation reliability of the wall bushing **200**.

(52) In this embodiment, the protective corrugated tube **250** is a circular casing. In other embodiments, the shape of the ring-shaped casing of the protective corrugated tube may also be configured to other shapes, such as square ring, oval ring, and which is not limited to the circular ring.

(53) In this embodiment, the upper connecting end **253** is a flange plate **253** extending outward along a radial direction of the upper through hole **251**. The flange plate **253** is attached to and fixedly connected to the lower end of the head assembly **210**. The flange plate **253** and the head assembly **210** are in a planar contact with each other, which is convenient for mounting and reliable in structure.

(54) In other embodiments, the structure of the upper connecting end is not limited thereto. For example, the structure of the upper connecting end may be a circular ring structure or a sawtooth structure extending along the upper through hole, and the lower end of the head assembly is provided with a groove matching the circular ring structure or the sawtooth structure for insertion. An adhesive is used to aid in fixation.

(55) In this embodiment, a mounting hole **2531** is arranged on the flange plate **253**, and a passage **2532** is arranged between the mounting hole **2531** and the upper through hole **251** for providing a communication of the mounting hole **2531** with the upper through hole **251**. A filter element **260** is mounted in the mounting hole **2531**. The filter element **260** is used for only gas exchange between the inside of the protective corrugated tube **250** and the outside of the protective corrugated tube **250**. During the process of inflating and deflating of the wall bushing **200**, the filter element **260**

only allows gas to pass through, and internal impurities, metal chips and the like cannot enter the main insulating cavity through the filter element **260**.

(56) In this embodiment, three mounting holes **2531** are provided, and three corresponding filter elements **260** are provided. In other embodiments, as long as the number of mounting holes is equal to the number of filter elements, the specific number and the distance between different mounting holes are not specifically limited.

(57) In this embodiment, the mounting hole **2531** is a through hole, and the passage **2532** is arranged on a surface of the flange plate **253**, and is a linear groove communicating the mounting hole **2531** with the upper through hole **251**. The passage **2532** is a passage for gas exchange between the inside of the protective corrugated tube **250** and the outside of the protective corrugated tube **250**.

(58) In other embodiments, the mounting hole may not be a through hole, a passage is arranged between the bottom of the mounting hole and the upper through hole. The passage is arranged in the inside of the flange plate, and cannot be observed from the surface of the flange plate. That is, the shape and location of the passage are not limited, as long as the purpose of gas exchange between the inside of the protective corrugated tube and the outside of the protective corrugated tube can be achieved.

(59) In this embodiment, the filter element **260** includes a filter part **261** and a filter element connecting part **262**. The filter part **261** is a columnar metal sintered mesh. A side surface **2611** and a top surface **2612** of the filter part **261** are designed in one piece, and seamlessly connected. A bottom surface **2613** of the filter part **261** is provided with a through hole **2614**. The filter element connecting part **262** is arranged around the through hole **2614**. The filter element connecting part **262** is a cylindrical structure that is hole-through in an up-down direction, and has an end connected to the through hole **2614**, and the other end that is an outlet. A thread **2621** is arranged on the filter element connecting part **262**. The mounting hole **2531** is provided with a thread matched with the thread **2621**. When the filter element connecting part **262** is mounted in the mounting hole **2531**, the part of the filter element **260** exposed outside the mounting hole **2531** is designed in one piece and seamlessly connected.

(60) In this embodiment, the filter element **260** is a titanium rod filter element **260** with metal mesh structure. The titanium rod filter element **260** is a kind of porous filter element, which is made of industrial high-purity titanium through the following steps. That is, the industrial high-purity titanium is processed by sieving, cooling, etc., and then isostatic pressing, and then sintered at high temperature and high vacuum, so as to obtain the porous filter element. The titanium rod filter element **260** has excellent properties such as high corrosion resistance, high temperature resistance, high strength, easy assurance of filtration accuracy, and easy regeneration.

(61) In this embodiment, the titanium rod filter element **260** has the following characteristics: uniform structure, narrow pore size distribution, high separation efficiency; high porosity, low filtration resistance, high penetration efficiency; high temperature resistance (generally, normal use below 280° C.); good chemical stability, acid and alkali corrosion resistance, oxidation resistance; no particle shedding; good mechanical properties, easy to operate.

(62) In other embodiments, the filter element can also be other sintered mesh materials such as PTFE (polytetrafluoroethylene), stainless steel, and the like, which has corrosion resistance, high temperature resistance, high strength, easy assurance of filtration accuracy.

(63) In this embodiment, a diameter of the lower through hole **252** is less than the minimum inner diameter of the protective corrugated tube **250**. A lower connecting end **254** is arranged around the lower through hole **252**. A first round nut **256** and a second round nut **257** are arranged on two sides of the lower connecting end **254**, respectively. The first round nut **256** and the second round nut **257** are respectively threadedly connected with the conductive rod **220** to clamp the lower connecting end **254** so that the protective corrugated tube **250** is fixedly connected to the conductive rod **220**. The protective corrugated tube **250** is fixedly connected to the conductive rod

220, on the one hand, there is no gap between the protective corrugated tube **250** and the conductive rod **220**, so that impurities and metal chips in the protective corrugated tube **250** cannot enter the main insulating cavity; on the other hand, when the conductive rod **220** is deformed due to thermal expansion and cold contraction, and the protective corrugated tube **250** has a certain space for elastic deformation, and a size of the protective corrugated tube **250** is capable of changing accordingly with the deformation of the conductive rod **220**, ensuring stable connections of the various components of the wall bushing **200**.

(64) In other embodiments, the protective corrugated tube and the conductive rod may be fixedly connected by welding, gluing, and other fixed connection, and the fixed connection between the protective corrugated tube and the conductive rod does not require tightness.

(65) In this embodiment, the protective corrugated tube **250** is made of metal. The protective corrugated tube **250** made of metal can play a shielding role to a certain extent, improving the operation reliability of the wall bushing **200**.

(66) In other embodiments, the protective corrugated tube may be made of non-metallic material, as long as the generation of metal chips due to the secondary friction between the protective cover and the conductive rod can be prevented.

(67) It can be understood that, in this embodiment, due to the arrangement of the protective corrugated tube **250**, a cavity that only allows gas exchange and consists of the protective corrugated tube **250**, the conductive rod **220**, the transition plate **212** and the filter element **260**, is formed. There is no gap between the protective corrugated tube **250** and the conductive rod **220**, and even under the condition of not being sealed, only gas can be allowed to pass through. The passage **2532** and the filter element **260** are arranged between the protective corrugated tube **250** and the transition plate **212**. The metal particles inside the protective corrugated tube **250** are blocked by the filter element **260** and cannot migrate to the outside of the protective corrugated tube **250**. In such structure, there are no other outlets and inlets, which can ensure that the metal particles inside the protective corrugated tube **250** cannot enter the main insulating cavity of the wall bushing **200** during the process of inflating and deflating, thereby ensuring the operation reliability of the wall bushing **200**. Moreover, due to the fixed connection between the protective corrugated tube **250** and the conductive rod **220**, there is no displacement therebetween. When the conductive rod **220** is deformed due to thermal expansion and contraction, the size of the protective corrugated tube **250** is change accordingly, which ensures that the conductive rod **220** cannot be bent or the transition plate **212** cannot be deformed. The protective corrugated tube **250** is mainly used to provide a deformation space for the conductive rod **220** by the elastic deformation of the protective corrugated tube **250** itself.

(68) In this embodiment, the threaded hole is arranged on the surface of the flange plate **253** attached to the transition plate **212**, and the through hole corresponding to the threaded hole is arranged on the transition plate **212**. The flange plate **253** and the transition plate **212** are threadedly connected by bolts. The threaded hole is arranged on the surface of the flange plate **253** attached to the transition plate **212** instead of the transition plate **212**, which is for the sake of assembly, and such structure is more convenient for assembly. In this embodiment, an area of the conductive rod **220** located below the transition plate **212** is provided with threads, and the assembly sequence of the wall bushing **200** is as follows. After the other components are assembled, the second round nut **257** is sleeved downward from the head portion of the conductive rod **220**, and is screwed onto the lower edge of the threaded area of the conductive rod **220** to prevent the second round nut **257** from loosening due to vibration and other reasons. And then, the protective corrugated tube **250** assembled with the filter element **260** is sleeved downward from the head portion of the conductive rod **220**. The upper through hole **251** is located above, the lower through hole **252** is located below, and the lower connecting end **254** abuts against the second round nut **257**. And then, the first round nut **256** is sleeved downward from the head portion of the conductive rod **220**, and is screwed onto the conductive rod **220**. The first round nut **256** abut

against the lower connecting end **254**. That is, the first round nut **256** and the second round nut **257** clamp two sides of the lower connecting end **254**, so as to fix the protective corrugated tube **250** on the conductive rod **220**. And then, the transition plate **212** is sleeved downward from the head portion of the conductive rod **220**, the through hole on the transition plate **212** is matched with the threaded hole on the flange plate **253**, and the transition plate **212** is fixedly connected to the flange plate **253** by passing the bolt through the through hole and screwing the bolt into the threaded hole. And then, the transition tank **211** is sleeved downward from the head portion of the conductive rod **220**, and is fixedly connected to the transition plate **212**. Finally, the connecting terminal **240** is connected to the transition tank **211**, and the subsequent assembly is completed. During this process, the main body and the end part of the conductive rod **220** are enclosed in the main insulating cavity, if the bolt passes through the flange plate **253** first, and then through the transition plate **212**, there is practical obstacles to the bolt connection. Therefore, the connection structure in this embodiment is more convenient for assembly.

(69) Further, in an embodiment, as shown in FIGS. **8** to **10**, a non-metallic lining **330** is added to the wall bushing **300**.

(70) In an application scenario, as shown in FIG. **8**, the non-metallic lining **330** is arranged on an inner wall of a first through hole **3111** and an inner wall of a second through hole **3121**, which avoids metal particles from being generated by the friction between a conductive rod **320** and a transition plate **312**, and between a conductive rod **320** and a transition tank **311**, thereby improving the operation reliability of the wall bushing **300**.

(71) In other embodiments, the non-metallic lining may be arranged only on the inner wall of the first through hole or the inner wall of the second through hole.

(72) In this embodiment, an inner wall of a protruding ring **3123** is provided with a non-metallic lining **330**. The protruding ring **3123** is arranged on a lower surface of the transition plate **312**. In other embodiments, the non-metallic lining may be arranged continuously in an area where the conductive rod contacts other metal conductors, or may be arranged in sections so that there is a gap between the conductive rod and other metal conductors, and the generation of metal particles can be reduced or even avoided in non-contact situations.

(73) In another application scenario, as shown in FIG. **9**, the inner wall of the first through hole **3111**, the inner wall of the second through hole **3121**, and the inner wall of the protruding ring **3123** are provided with a non-metallic lining **330**, and the specific arrangements are the same as those described above, and which is not repeated herein. In this embodiment, the protruding ring **3123** is arranged on the upper surface of the transition plate **312**.

(74) In yet another application scenario, as shown in FIG. **10**, the inner wall of the protruding ring **3123** is provided with a non-metallic lining **330**. The non-metallic lining **330** prevents metal chips from being generated due to friction between the conductive rod **320** and the transition plate **312**, and between the conductive rod **320** and the transition tank **311**, thereby improving the operation reliability of the wall bushing **300**. The inner wall of the protruding ring **3123** is provided with a plurality of grooves, and the non-metallic lining **330** is embedded in the grooves. Such structure can embed the non-metallic lining **330** in the grooves by adopting a broken ring form, that is, the non-metallic lining **330** is a strip structure, not a complete circle structure. A length of the non-metallic lining **330** can be adjusted according to sizes of the grooves, so that the non-metallic lining **330** is adapted to be embedded in the grooves, which is convenient for mounting and construction. In addition, arranging grooves reduces the amount of non-metallic lining **330** and reduces production costs. Compared to the non-metallic lining with larger area integrally arranged on the inner wall of the protruding ring **3123**, the non-metallic lining **330** which is in the broken ring form and embedded in the inner wall of the grooves is easier to mount and fix, and the non-metallic lining **330** does not displace on the inner wall of the protruding ring **3123** during use. Alternatively, for the convenience of mounting, the non-metallic lining may have the structure as shown in FIGS. **8** and **9**, that is, the non-metallic lining is integrally arranged on the inner wall of the protruding

ring, and which is not limited herein.

(75) In other embodiments, the non-metallic lining may be fixedly arranged on the conductive rod, that is, as long as the non-metallic lining is connected with the conductive rod, or any one of the inner wall of the first through hole, the inner wall of the second through hole, and the inner wall of the protruding ring. Alternatively, the non-metallic lining may be continuously arranged in the area of the conductive rod contacting other metal conductors, so that there is a gap between the conductive rod and other metal conductors, and the generation of metal particles can be reduced or even avoided in non-contact situations.

(76) In this embodiment, the non-metallic lining **330** is a PTFE lining. The PTFE lining has good insulation and wear resistance, and good chemical corrosion resistance. During the operation of the wall bushing **300**, if corrosive gas is generated due to the electric arc, the performance of the PTFE lining remains unaffected, ensuring that the non-metallic lining **330** is not worn and continues to be effective during the operation of the wall bushing **300** to the greatest extent.

(77) In other embodiments, if the gas generated when the insulating gas filled in the wall bushing is subjected to the electric arc is non-corrosive gas or less corrosive gas, the non-metallic lining may be any one of a polyester lining, a glass fiber lining or the like, which has insulation and wear resistance.

(78) The non-metallic lining **330** is arranged in the wall bushing **300** according to this embodiment, the contact between the conductive rod **320** and other metal conductors is reduced or avoided, the generation of metal particles is reduced, and the operation reliability of the wall bushing **300** is improved.

(79) Further, in an embodiment, as shown in FIGS. **11** and **12**, a connecting terminal **440** and a wall bushing **400** including the connecting terminal **440** are provided. Specifically, the connecting terminal **440** of the wall bushing **400** includes a connecting part **441**, an accommodating part **442** and a second connecting part **443** that are sequentially arranged. The accommodating part **442** is used for accommodating an end of a conductive rod **420** and is electrically connected to the conductive rod **420**. The second connecting part **443** is in a sealed connection with an upper end of a transition tank **411**. The connecting terminal **440** is an electrical connection component of the wall bushing **400** and is used for electrical connection with other devices. The arrangement of the second connecting part **443** facilitates the fixed connection of connecting terminal **440** to the transition tank **411**.

(80) In this embodiment, a second sealing groove **414** is arranged between the second connecting part **443** of the connecting terminal **440** and the upper end of the transition tank **411**. A second sealing ring (not shown in figures) is arranged in the second sealing groove **414**. Specifically, the second sealing groove **414** is arranged on the upper end of the transition tank **411**. In other embodiments, the second sealing groove may also be arranged on the second connecting part, or, both the second connecting part and the upper end of the transition tank are provided with a sealing groove, and a sealing ring is mounted in the sealing groove.

(81) In this embodiment, the second connecting part **443** is provided with through holes **4431**, and the upper end of the transition tank **411** is correspondingly provided with threaded holes. The second connecting part **443** and the transition tank **411** are connected by passing screws (not shown in figures) through the through holes **4431** and screwing the screws into the threaded holes. In other embodiments, the second connecting part and the transition tank may be connected by gluing, welding, or a combination of the above fixed connections.

(82) In this embodiment, contact springs **444** are arranged at an end of the conductive rod **420**. The contact springs **444** abut against an inner wall of the accommodating part **442**. There is a gap between the accommodating part **442** and the end of the conductive rod **420** in an axial direction of the conductive rod **420**. The contact springs **444** are in close contact with the inner wall of the accommodating part **442** and the end of the conductive rod **420** at the same time, so that the electrical connection between the connecting terminal **440** and the end of the conductive rod **420** is

stable, and thus the equipotential of the head assembly is maintained, and the heating problem of the head portion is solved. The gap **446** is formed between the accommodating part **442** and the end of the conductive rod **420** in the axial direction of the conductive rod **420**, which can provide sufficient space for the conductive rod **420** to expand and contract when the conductive rod **420** undergoes axial deformation due to thermal expansion and contraction. That is, the deformation due to thermal expansion and contraction, of the conductive rod **420** can be absorbed, and the conductive rod **420** can be avoided from being bent due to fixed connection or contact with the inner wall of the accommodating part **442**.

(83) In this embodiment, a circular groove **445** is arranged on the inner wall of the accommodating part **442**, and the contact springs **444** are accommodated in the circular groove **445**. The contact springs **444** abut against an inner wall of the circular groove **445** and the end of the conductive rod **420**, so that the accommodating part **442** is electrically connected to the end of the conductive rod **420**, the equipotential of the head assembly is maintained, and the heating problem of the head is solved. In other embodiments, no circular groove may be arranged in the accommodating part, and there is a certain gap between the inner wall of the accommodating part and the end of the conductive rod, so that the contact springs can be pressed between the inner wall of the accommodating part and the end of the conductive rod. In this way, the contact springs can also be kept in a relatively fixed state.

(84) Due to the ingenious structure arrangement of the connecting terminal **440**, the wall bushing **400** according to this embodiment meets the electrical connection and equipotential requirements of the head of the wall bushing **400**, while it is ensured the sufficient space for the conductive rod **420** to expand and contract when the conductive rod **420** is deformed in the axial direction due to thermal expansion and contraction. That is, the deformation due to thermal expansion and contraction of the conductive rod **420** can be absorbed, and the conductive rod **420** can be avoided from being bent due to fixed connection or contact with the inner wall of the accommodating part **442**.

(85) In an application scenario, as shown in FIG. **13**, this embodiment adopts the aforementioned connecting terminal **440**. Contact springs **444** are arranged between the connecting terminal **440** and the conductive rod **420**, and the specific structure and the connection mode of the contact springs **444** are the same as those described above, which are not repeated herein. In this embodiment, a protruding ring **4123** is arranged on an upper surface of a transition plate **412**, and a protective cover **450** is arranged at a lower end of a head assembly around a second through hole **4121**.

(86) In yet another application scenario, as shown in FIG. **14**, this embodiment also adopts the aforementioned connecting terminal **440**, and contact springs **444** are arranged between the connecting terminal **440** and the conductive rod **420**, and the specific structure and the connection mode of the contact springs **444** are the same as those described above, which are not repeated herein. In this embodiment, the protruding ring **4123** is arranged on the upper surface of the transition plate **412**, and a protective corrugated tube **450** is arranged at the lower end of the head assembly around the second through hole **4121**.

(87) Further, the present disclosure provides an embodiment shown in FIGS. **15** and **16**, a wall bushing **500** includes a hollow insulator **570**. A flange **571** of the hollow insulator **570** is in a sealed connection with a lower surface of a transition plate **512**. The conductive rod **520** extends through the hollow insulator **570**. The hollow insulator **570** provides insulation protection for conductors inside the wall bushing **500**.

(88) In this embodiment, a third sealing groove **5711** is arranged between the flange **571** of the hollow insulator **570** and the transition plate **512**. A third sealing ring (not shown in figures) is arranged in the third sealing groove **5711**. Specifically, the third sealing groove **5711** is arranged on the flange **571**. In other embodiments, the third sealing groove may be arranged on the lower surface of the transition plate, or, both the flange and the lower surface of the transition plate are

provided with a sealing groove, and a sealing ring is mounted in the sealing groove.

(89) In this embodiment, a voltage equalizing ball **580** is arranged on an outer periphery of a head assembly **510**. The voltage equalizing ball **580** is fixedly connected to the head assembly **510**. The voltage equalizing ball **580** is used to equalize the voltage, so as to ensure that no abnormal corona discharge occurs when the head assembly **510** is charged. The terminal end of the wall bushing **500** is also provided with a voltage equalizing ball.

(90) In this embodiment, the conductive rod **520** extends inside the hollow insulator **570** and is fixedly connected to the end of the wall bushing **500**, which ensures that the conductive rod **520** extending through the head assembly **510** does not displace when the conductive rod **520** undergoes thermal expansion and contraction.

(91) In this embodiment, specifically, the overall structure of the wall bushing **500** includes that the conductive rod **520** extends inside the hollow insulator **570** and is fixedly connected to the end of the wall bushing **500**. Since the connecting terminal **540** and the transition tank **511** are in the sealed connection, the conductive rod **520** is only required to extend through the head assembly **510**, and a fixed and sealed connection is not required between the conductive rod **520** and the transition tank **511** and between the conductive rod **520** and the transition plate **512**. That is, the arrangement of an axial dynamic sealing device between the transition tank **511** and the conductive rod **520** is avoided, which greatly improves the sealing reliability of the wall bushing **500**. In addition, the production cost is reduced due to the omission of a corrugated tube. When the length of the conductive rod **520** changes due to thermal expansion and contraction, since the end of the conductive rod **520** is fixed, the head portion of the conductive rod **520** and the transition tank **511** move relative to each other in the axial direction. In this case, a gap **546** between the connecting terminal **540** and the end of the conductive rod **520** provides a space for the axial movement of the head portion of the conductive rod **520**, so that the conductive rod **520** does not bent due to the increase in length. From this aspect, the reliability of the wall bushing **500** is improved.

(92) In this embodiment, the hollow insulator **570** is a composite insulator made of composite material. The composite insulator is light in weight, low in cost, and has excellent insulation and mechanical properties. In other embodiments, the hollow insulator may also be an insulator made of other materials, such as a porcelain insulator.

(93) In this embodiment, the hollow insulator **570** includes two insulator sections. A mounting structure **572** is arranged between the two insulator sections. The mounting structure **572** is used to mounted the wall bushing **500** on the wall. That is, the wall bushing **500** includes the connecting terminal **540**, the transition tank **511**, the transition plate **512**, and the hollow insulator **570** that are connected in sequence. The conductive rod **520** extends inside the hollow insulator **570**. An end of the conductive rod **520** is connected to the connecting terminal **540**, and the other end of the conductive rod **520** is fixed on the end of the hollow insulator **570**.

(94) When mounting the wall bushing **500**, the wall bushing **500** may be mounted in a certain inclination angle, or horizontally in its axial direction. In this embodiment, the wall bushing **500** is mounted obliquely, and the head portion of the wall bushing **500** is higher than the end of the wall bushing **500**. In this case, the metal particles existing in the transition tank **511** can fall into a circular groove **5112** due to gravity. The circular groove **5112** functions as a particle trap for absorbing the metal particles in the transition tank **511**, which prevents the metal particles from floating and migrating in the transition tank **511**, and ensures the stability of the electrical properties of the head portion of the wall bushing **500**.

(95) In an application scenario, as shown in FIGS. **17** and **18**, the wall bushing **500** also includes a hollow insulator **570**. The flange **571** of the hollow insulator **570** is in a sealed connection with the lower surface of the transition plate **512**. The conductive rod **520** extends through the hollow insulator **570**. The hollow insulator **570** includes two insulator sections, and the mounting structure **572** is arranged between the two insulator sections. The specific connection mode of the mounting structure **572** is the same as those as described above, and which is not repeated herein. The outer

periphery of the head assembly **510** is also provided with a voltage equalizing ball **580**, and the specific connection mode is not repeated herein.

(96) In this embodiment, due to the arrangement of the protective cover **550**, a space is formed at the lower end of the transition plate **512** to prevent possible metal chips or other debris from entering the main insulating cavity of the wall bushing **500**. The arrangement of the gap between the protective cover **550** and the conductive rod **520** prevents the generation of metal chips due to the secondary friction between the protective cover **550** and the conductive rod **520**. The protective cover **550** made of metal plays a shielding role to a certain extent, which further improves the operation reliability of the wall bushing **500**.

(97) In another application scenario, as shown in FIGS. **19** and **20**, the wall bushing **500** also includes the hollow insulator **570**. The flange **571** of the hollow insulator **570** is in a sealed connection with the lower surface of the transition plate **512**. The conductive rod **520** extends through the hollow insulator **570**. The hollow insulator **570** includes two insulator sections, and a mounting structure **572** is arranged between the two insulator sections. The specific connection mode of the mounting structure **572** are the same as those described above, and which is not repeated herein. The outer periphery of the head assembly **510** is also provided with a voltage equalizing ball **580**, and the specific connection mode is not repeated herein.

(98) In this embodiment, due to the arrangement of the protective corrugated tube **550**, a cavity that only allows gas exchange and consists of the protective corrugated tube **550**, the conductive rod **520**, the transition plate **512** and the filter element **560**, is formed. There is no gap between the protective corrugated tube **550** and the conductive rod **520**, and even under the condition of not being sealed, only gas is allowed to pass through. The passage and the filter element **560** are arranged between the protective corrugated tube **550** and the transition plate **512**. The metal particles inside the protective corrugated tube **550** are blocked by the filter element **560** and cannot migrate to the outside of the protective corrugated tube **550**. In such structure, no other outlets and inlets are provided, which ensures that the metal particles inside the protective corrugated tube **550** cannot enter the hollow insulator **570** of the wall bushing **500** during the process of inflating and deflating, thereby ensuring the operation reliability of the wall bushing **500**. Moreover, the protective corrugated tube **550** and the conductive rod **520** are fixedly connected, so that the protective corrugated tube **550** and the conductive rod **520** cannot be displaced relative to each other. When the conductive rod **520** is deformed due to thermal expansion and contraction, the size of the protective corrugated tube **550** changes accordingly, so as to ensure that the conductive rod **520** does not bent or the transition plate **512** is not deformed. The protective corrugated tube **550** is mainly used to provide a deformation space for the conductive rod **520** by the elastic deformation of the protective corrugated tube **550** itself.

(99) The wall bushing according to the present disclosure has a simple structure, and the structure of the conventional corrugated tube is replaced by the head assembly, which avoids the use of an axial dynamic sealing device, greatly improves the sealing reliability of the wall bushing, and reduces production costs. The arrangement of the protective cover or the protective corrugated tube further prevents possible metal chips or other debris from entering the main insulating cavity of the wall bushing, thereby improving the operation reliability of the wall bushing.

(100) Technical content of the present disclosure and technical characteristics have been disclosed as above, but it can be understood that, under the creative thought of the present disclosure, various modifications and improvements can be made to above-mentioned structures and materials by those skilled in the art, including a combination of technical features disclosed herein separately or claimed to be protected, and obviously including other combinations of these features. These variants and/or combinations all fall within the technical field involved in the present disclosure, and fall within the protection scope of the claims of the present disclosure.

Claims

1. A wall bushing, comprising: a head assembly; a conductive rod; and a connecting terminal sealing and covering the head assembly and the conductive rod, wherein the connecting terminal is electrically connected to the conductive rod, the head assembly includes a transition tank and a transition plate that are connected to each other, wherein an upper end of the transition tank is provided with a first through hole, and a lower end of the transition tank is hole-through, and wherein the transition plate is provided with a second through hole, the conductive rod extends through the first through hole and the second through hole, the transition tank and the transition plate are fixedly connected so that an accommodating cavity is formed around the conductive rod and in the transition tank, the wall bushing further includes a protective corrugated tube, wherein the protective corrugated tube is a ring-shaped casing that is hole-through in an up-down direction, the protective corrugated tube is provided with an upper through hole and a lower through hole, the conductive rod extends through the first through hole, the second through hole, the upper through hole, and the lower through hole, the protective corrugated tube is provided with an upper connecting end around the upper through hole, the upper connecting end surrounds the second through hole and is fixedly connected to a lower end of the head assembly; and the lower through hole is fixedly connected to the conductive rod.
2. The wall bushing of claim 1, wherein the upper connecting end is a flange plate extending along a radial direction of the upper through hole, and the flange plate is attached to and fixedly connected to the lower end of the head assembly.
3. The wall bushing of claim 2, wherein a mounting hole is arranged on the flange plate, a passage is arranged between the mounting hole and the upper through hole for providing a communication of the mounting hole with the upper through hole, a filter element is mounted in the mounting hole, and the filter element is configured for only gas exchange between an inside of the protective corrugated tube and an outside of the protective corrugated tube.
4. The wall bushing of claim 1, wherein a diameter of the lower through hole is less than a minimum inner diameter of the protective corrugated tube, a lower connecting end is arranged around the lower through hole, a first round nut and a second round nut are arranged on two sides of the lower connecting end, and the first round nut and the second round nut are respectively threadedly connected with the conductive rod to clamp the lower connecting end, so that the protective corrugated tube is fixedly connected to the conductive rod.
5. The wall bushing of claim 1, wherein a plurality of circular grooves is arranged on a sidewall of the transition tank and surrounds the conductive rod.
6. The wall bushing of claim 1, wherein the lower end of the transition tank extends to form a first connecting part along an outer periphery of the transition tank, and the first connecting part is in a sealed connection with the transition plate.
7. The wall bushing of claim 1, wherein a non-metallic lining is arranged on an inner wall of the first through hole and/or an inner wall of the second through hole.
8. The wall bushing of claim 1, wherein the connecting terminal includes a connecting part, an accommodating part, and a second connecting part that are sequentially arranged, the accommodating part is configured for accommodating an end of the conductive rod, and is electrically connected to the conductive rod, and the second connecting part is in a sealed connection with the upper end of the transition tank.
9. The wall bushing of claim 8, wherein contact springs are arranged at the end of the conductive rod, the contact springs abut against an inner wall of the accommodating part, and a gap is formed between the accommodating part and the end of the conductive rod in an axial direction of the conductive rod.
10. The wall bushing of claim 1, wherein an upper surface and/or a lower surface of the transition

plate is provided with a protruding ring around the second through hole.

11. The wall bushing of claim 1, further comprising a hollow insulator, wherein the hollow insulator is in a sealed connection with the transition plate, and the conductive rod extends through the hollow insulator.
