

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                    |
|----------------------|--------------------|
| United States Patent | 12408729           |
| Kind Code            | B2                 |
| Date of Patent       | September 09, 2025 |
| Inventor(s)          | Kodad; Jay A.      |

---

### Fluid-filled chamber with stitched tensile member

---

#### Abstract

A chamber for receiving a pressurized fluid may include a tensile member extending between a first chamber barrier layer and a second chamber barrier layer and including a plurality of tethers extending between the first tensile member layer and the second tensile member layer. The chamber may include stitching through the tensile member in a stitched region. When the chamber is pressurized with the pressurized fluid, a substantial majority of the first tensile member layer is separated from the second tensile member layer by a distance that corresponds to a length of the plurality of tethers. In addition, the first tensile member layer is held in contact with the second tensile member layer by the stitching in the stitched region, thereby forming an area of the chamber having a reduced thickness relative to adjacent portions of the chamber.

---

---

|                   |                                    |
|-------------------|------------------------------------|
| <b>Inventors:</b> | <b>Kodad; Jay A. (Newberg, OR)</b> |
| <b>Applicant:</b> | <b>NIKE, Inc. (Beaverton, OR)</b>  |
| <b>Family ID:</b> | <b>51628446</b>                    |
| <b>Assignee:</b>  | <b>NIKE, Inc. (Beaverton, OR)</b>  |
| <b>Appl. No.:</b> | <b>18/051269</b>                   |
| <b>Filed:</b>     | <b>October 31, 2022</b>            |

#### Prior Publication Data

|                            |                         |
|----------------------------|-------------------------|
| <b>Document Identifier</b> | <b>Publication Date</b> |
| US 20230081288 A1          | Mar. 16, 2023           |

#### Related U.S. Application Data

continuation parent-doc US 16671314 20191101 US 11490687 child-doc US 18051269  
continuation parent-doc US 15214981 20160720 US 10485297 20191126 child-doc US 16671314  
division parent-doc US 14068391 20131031 US 9427043 20160830 child-doc US 15214981

---

## Publication Classification

**Int. Cl.:** **A43B13/20** (20060101); **A43B5/00** (20220101); **A43B13/14** (20060101); **B32B3/02** (20060101); **B32B3/18** (20060101); **B32B3/26** (20060101)

**U.S. Cl.:**

**CPC** **A43B13/20** (20130101); **A43B5/00** (20130101); **A43B13/141** (20130101); **B32B3/02** (20130101); **B32B3/18** (20130101); **B32B3/263** (20130101);

## Field of Classification Search

**CPC:** A43B (13/20); A43B (5/00); A43B (13/141); B32B (3/02); B32B (3/18); B32B (3/263)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No. | Issued Date | Patentee Name    | U.S. Cl. | CPC        |
|------------|-------------|------------------|----------|------------|
| 500385     | 12/1892     | Hall             | N/A      | N/A        |
| 2155166    | 12/1938     | Kraft            | N/A      | N/A        |
| 2224590    | 12/1939     | Odilon           | N/A      | N/A        |
| 2743510    | 12/1955     | Mauney           | N/A      | N/A        |
| 3087261    | 12/1962     | Russell          | N/A      | N/A        |
| 3526199    | 12/1969     | Keats            | N/A      | N/A        |
| 3608215    | 12/1970     | Fukuoka          | N/A      | N/A        |
| 3861529    | 12/1974     | Coleman          | N/A      | N/A        |
| 4012854    | 12/1976     | Berend et al.    | N/A      | N/A        |
| 4129951    | 12/1977     | Petrosky         | N/A      | N/A        |
| 4183156    | 12/1979     | Rudy             | N/A      | N/A        |
| 4219945    | 12/1979     | Rudy             | N/A      | N/A        |
| 4229889    | 12/1979     | Petrosky         | N/A      | N/A        |
| 4262046    | 12/1980     | Eitel            | N/A      | N/A        |
| 4309832    | 12/1981     | Hunt             | N/A      | N/A        |
| 4391048    | 12/1982     | Lutz             | N/A      | N/A        |
| 4409271    | 12/1982     | Pehr             | N/A      | N/A        |
| 4414760    | 12/1982     | Faiella          | N/A      | N/A        |
| 4462171    | 12/1983     | Whispell         | N/A      | N/A        |
| 4561124    | 12/1984     | Thompson         | 2/23     | A41D 1/067 |
| 4603493    | 12/1985     | Eston            | N/A      | N/A        |
| 4610099    | 12/1985     | Signori          | N/A      | N/A        |
| 4738119    | 12/1987     | Zafred           | N/A      | N/A        |
| 4747575    | 12/1987     | Putt et al.      | N/A      | N/A        |
| 4827631    | 12/1988     | Thornton         | N/A      | N/A        |
| 4833795    | 12/1988     | Diaz             | N/A      | N/A        |
| 4845861    | 12/1988     | Moumdijan        | N/A      | N/A        |
| 4852275    | 12/1988     | Bianchini et al. | N/A      | N/A        |
| 4906502    | 12/1989     | Rudy             | N/A      | N/A        |
| 4936029    | 12/1989     | Rudy             | N/A      | N/A        |
| 4970807    | 12/1989     | Anderie et al.   | N/A      | N/A        |

|          |         |                   |      |                 |
|----------|---------|-------------------|------|-----------------|
| 4991317  | 12/1990 | Lakic             | N/A  | N/A             |
| 5042176  | 12/1990 | Rudy              | N/A  | N/A             |
| 5083361  | 12/1991 | Rudy              | N/A  | N/A             |
| 5084988  | 12/1991 | Berger            | N/A  | N/A             |
| 5113599  | 12/1991 | Cohen et al.      | N/A  | N/A             |
| 5379533  | 12/1994 | Swartz            | N/A  | N/A             |
| 5497511  | 12/1995 | Zade              | 2/22 | A41D<br>13/0506 |
| 5543194  | 12/1995 | Rudy              | N/A  | N/A             |
| 5561920  | 12/1995 | Graham et al.     | N/A  | N/A             |
| 5575088  | 12/1995 | Allen et al.      | N/A  | N/A             |
| 5588227  | 12/1995 | Goldston et al.   | N/A  | N/A             |
| 5595004  | 12/1996 | Lyden             | N/A  | N/A             |
| 5709954  | 12/1997 | Lyden et al.      | N/A  | N/A             |
| 5713141  | 12/1997 | Mitchell et al.   | N/A  | N/A             |
| 5733647  | 12/1997 | Moore, III et al. | N/A  | N/A             |
| 5767412  | 12/1997 | Goldston et al.   | N/A  | N/A             |
| D396342  | 12/1997 | Foxen et al.      | N/A  | N/A             |
| 5784808  | 12/1997 | Hockerson         | N/A  | N/A             |
| 5952065  | 12/1998 | Mitchell et al.   | N/A  | N/A             |
| 5979078  | 12/1998 | McLaughlin        | N/A  | N/A             |
| 5987781  | 12/1998 | Pavesi et al.     | N/A  | N/A             |
| 6013340  | 12/1999 | Bonk et al.       | N/A  | N/A             |
| 6065230  | 12/1999 | James             | N/A  | N/A             |
| 6082025  | 12/1999 | Bonk et al.       | N/A  | N/A             |
| 6115945  | 12/1999 | Ellis, III        | N/A  | N/A             |
| 6119371  | 12/1999 | Goodwin et al.    | N/A  | N/A             |
| 6127026  | 12/1999 | Bonk et al.       | N/A  | N/A             |
| 6203868  | 12/2000 | Bonk et al.       | N/A  | N/A             |
| 6266897  | 12/2000 | Seydel            | N/A  | N/A             |
| 6321465  | 12/2000 | Bonk et al.       | N/A  | N/A             |
| 6557274  | 12/2002 | Litchfield et al. | N/A  | N/A             |
| 6630220  | 12/2002 | Veiga             | N/A  | N/A             |
| 7047667  | 12/2005 | Klavano           | N/A  | N/A             |
| 7070845  | 12/2005 | Thomas            | N/A  | N/A             |
| 7168190  | 12/2006 | Gillespie         | N/A  | N/A             |
| 7210249  | 12/2006 | Passke et al.     | N/A  | N/A             |
| 7278445  | 12/2006 | Marvin et al.     | N/A  | N/A             |
| 7752772  | 12/2009 | Hatfield et al.   | N/A  | N/A             |
| 7943225  | 12/2010 | McCormick         | N/A  | N/A             |
| 8151486  | 12/2011 | Dua               | N/A  | N/A             |
| 8220071  | 12/2011 | Rhoades et al.    | N/A  | N/A             |
| 8241450  | 12/2011 | Hensley et al.    | N/A  | N/A             |
| 8272149  | 12/2011 | Cooper et al.     | N/A  | N/A             |
| 8381418  | 12/2012 | Peyton            | N/A  | N/A             |
| 8479412  | 12/2012 | Peyton et al.     | N/A  | N/A             |
| 8919015  | 12/2013 | Holt              | N/A  | N/A             |
| 9375049  | 12/2015 | Hazenber          | N/A  | N/A             |
| 9427043  | 12/2015 | Kodad             | N/A  | B32B 3/18       |
| 10568382 | 12/2019 | Hatfield          | N/A  | N/A             |

|              |         |                  |     |     |
|--------------|---------|------------------|-----|-----|
| 2003/0097767 | 12/2002 | Perkinson        | N/A | N/A |
| 2003/0183324 | 12/2002 | Tawney et al.    | N/A | N/A |
| 2004/0211085 | 12/2003 | Passke           | N/A | N/A |
| 2005/0076536 | 12/2004 | Hatfield et al.  | N/A | N/A |
| 2005/0097777 | 12/2004 | Goodwin          | N/A | N/A |
| 2005/0132608 | 12/2004 | Dojan et al.     | N/A | N/A |
| 2005/0132610 | 12/2004 | Foxen            | N/A | N/A |
| 2005/0167029 | 12/2004 | Rapaport et al.  | N/A | N/A |
| 2007/0006487 | 12/2006 | Gallegos         | N/A | N/A |
| 2007/0022627 | 12/2006 | Sokolowski       | N/A | N/A |
| 2007/0051018 | 12/2006 | Issler           | N/A | N/A |
| 2007/0063368 | 12/2006 | Schindler        | N/A | N/A |
| 2007/0074430 | 12/2006 | Coomer           | N/A | N/A |
| 2007/0084083 | 12/2006 | Hazenberg        | N/A | N/A |
| 2007/0094896 | 12/2006 | Hatfield et al.  | N/A | N/A |
| 2007/0113425 | 12/2006 | Wakley           | N/A | N/A |
| 2007/0169376 | 12/2006 | Hatfield et al.  | N/A | N/A |
| 2007/0169379 | 12/2006 | Hazenberg et al. | N/A | N/A |
| 2007/0199211 | 12/2006 | Campbell         | N/A | N/A |
| 2008/0229617 | 12/2007 | Johnson et al.   | N/A | N/A |
| 2008/0276490 | 12/2007 | Holt             | N/A | N/A |
| 2009/0151196 | 12/2008 | Schindler et al. | N/A | N/A |
| 2009/0288312 | 12/2008 | Dua              | N/A | N/A |
| 2009/0288313 | 12/2008 | Rapaport et al.  | N/A | N/A |
| 2010/0024251 | 12/2009 | Delgatty         | N/A | N/A |
| 2010/0199406 | 12/2009 | Dua et al.       | N/A | N/A |
| 2010/0299965 | 12/2009 | Avar             | N/A | N/A |
| 2011/0131831 | 12/2010 | Peyton et al.    | N/A | N/A |
| 2011/0247744 | 12/2010 | Turner           | N/A | N/A |
| 2012/0052249 | 12/2011 | Turner           | N/A | N/A |
| 2012/0102782 | 12/2011 | Swigart et al.   | N/A | N/A |
| 2012/0102783 | 12/2011 | Swigart          | N/A | N/A |
| 2012/0211147 | 12/2011 | Rapaport et al.  | N/A | N/A |
| 2012/0255201 | 12/2011 | Little           | N/A | N/A |
| 2013/0074370 | 12/2012 | Park             | N/A | N/A |
| 2013/0232821 | 12/2012 | Schindler        | N/A | N/A |
| 2013/0247422 | 12/2012 | Holt             | N/A | N/A |
| 2013/0263391 | 12/2012 | Chao et al.      | N/A | N/A |
| 2013/0266773 | 12/2012 | Hazenberg et al. | N/A | N/A |
| 2014/0033570 | 12/2013 | Peyton           | N/A | N/A |
| 2014/0041261 | 12/2013 | Walker           | N/A | N/A |
| 2014/0053427 | 12/2013 | Patton           | N/A | N/A |
| 2014/0182167 | 12/2013 | James et al.     | N/A | N/A |
| 2014/0230276 | 12/2013 | Campos, II       | N/A | N/A |
| 2014/0250729 | 12/2013 | James et al.     | N/A | N/A |
| 2014/0259462 | 12/2013 | Taylor et al.    | N/A | N/A |
| 2014/0360046 | 12/2013 | Dojan et al.     | N/A | N/A |
| 2015/0013190 | 12/2014 | Davison          | N/A | N/A |
| 2015/0208759 | 12/2014 | Hazenberg et al. | N/A | N/A |
| 2015/0257481 | 12/2014 | Campos, II       | N/A | N/A |

|              |         |         |     |     |
|--------------|---------|---------|-----|-----|
| 2016/0081428 | 12/2015 | Swigart | N/A | N/A |
| 2017/0265564 | 12/2016 | Peyton  | N/A | N/A |
| 2017/0265565 | 12/2016 | Connell | N/A | N/A |
| 2017/0265566 | 12/2016 | Case    | N/A | N/A |
| 2018/0064207 | 12/2017 | Hurd    | N/A | N/A |
| 2018/0064208 | 12/2017 | Hurd    | N/A | N/A |

## **FOREIGN PATENT DOCUMENTS**

| <b>Patent No.</b> | <b>Application Date</b> | <b>Country</b> | <b>CPC</b> |
|-------------------|-------------------------|----------------|------------|
| 1037828           | 12/1988                 | CN             | N/A        |
| 101370405         | 12/2009                 | CN             | N/A        |
| 103025188         | 12/2012                 | CN             | N/A        |
| 2009524451        | 12/2008                 | JP             | N/A        |
| 20110100190       | 12/2010                 | KR             | N/A        |
| WO-2007087495     | 12/2006                 | WO             | N/A        |
| WO-2013155086     | 12/2012                 | WO             | N/A        |

## **OTHER PUBLICATIONS**

International Searching Authority, International Search Report and Written Opinion mailed Dec. 4, 2014 in PCT/US2014/053358. cited by applicant

State Intellectual Property Office, Chinese Office Action and Search Report for Application No. 201480059498.7, mailed Dec. 21, 2016. cited by applicant

Korean Intellectual Property Office, Office Action for KR Application No. 10-2016-7014425, mailed Aug. 11, 2017. cited by applicant

European Patent Office, Extended European Search Report for EP Application No. 18162456.0, mailed Jun. 18, 2018. cited by applicant

Korean Intellectual Property Office, Office Action for KR Application No. 10-2016-7014425, mailed Mar. 30, 2018. cited by applicant

Korean Intellectual Property Office, Office Action for KR Application No. 10-2019-7003163, mailed Apr. 27, 2019. cited by applicant

China National Intellectual Property Administration, The First Office Action for CN Application No. 201710585346.6, mailed Jun. 21, 2019. cited by applicant

Uspto, Non-Final Office Action for U.S. Appl. No. 15/214,981, mailed Dec. 14, 2018. cited by applicant

Japan Patent Office, Office Action for Application No. 2020-018026 dated Mar. 2, 2021. cited by applicant

*Primary Examiner:* Simone; Catherine A.

*Attorney, Agent or Firm:* Honigman LLP

## **Background/Summary**

**CROSS REFERENCE TO RELATED APPLICATIONS** (1) This application is a Continuation of U.S. patent Ser. No. 16/671,314, filed Nov. 1, 2019, which is a Continuation of U.S. patent Ser. No. 15/214,981, filed Jul. 20, 2016, which is a Divisional of U.S. patent application Ser. No. 14/068,391, filed Oct. 31, 2013, the entire contents of which are hereby incorporated by reference.

## **BACKGROUND**

(1) The present invention relates generally to fluid-filled chambers for use in the sole structure of

an article of footwear.

(2) Conventional articles of athletic footwear include two primary elements, an upper and a sole structure. The upper provides a covering for the foot that comfortably receives and securely positions the foot with respect to the sole structure. The sole structure is secured to a lower portion of the upper and is generally positioned between the foot and the ground. In addition to attenuating ground reaction forces (that is, providing cushioning) during walking, running, and other ambulatory activities, the sole structure may influence foot motions (for example, by resisting pronation), impart stability, and provide traction, for example. Accordingly, the upper and the sole structure operate cooperatively to provide a comfortable structure that is suited for a wide variety of athletic activities.

(3) The upper is often formed from a plurality of material elements (for example, textiles, polymer sheets, foam layers, leather, synthetic leather) that are stitched or adhesively bonded together to define a void on the interior of the footwear for comfortably and securely receiving a foot. More particularly, the upper forms a structure that extends over instep and toe areas of the foot, along medial and lateral sides of the foot, and around a heel area of the foot. The upper may also incorporate a lacing system to adjust fit of the footwear, as well as permit entry and removal of the foot from the void within the upper. In addition, the upper may include a tongue that extends under the lacing system to enhance adjustability and comfort of the footwear, and the upper may incorporate a heel counter.

(4) The sole structure generally incorporates multiple layers: a sockliner, a midsole, and a ground-engaging outer member. The sockliner is a thin, compressible member located within the upper and adjacent to a plantar (that is, lower) surface of the foot to enhance footwear comfort. The midsole is secured to a lower surface of the upper and forms a middle layer of the sole structure. Many midsole configurations are primarily formed from a resilient polymer foam material, such as polyurethane (PU) or ethyl vinyl acetate (EVA), that extends throughout the length and width of the footwear. The midsole may also incorporate plates, moderators, and/or other elements that further attenuate forces, influence the motions of the foot, and/or impart stability, for example. The ground-engaging outer member may be fashioned from a durable and wear-resistant material (for example, rubber) that includes texturing to improve traction.

(5) Further, the sole structure may include fluid-filled chambers to provide cushioning and stability. Upon inflation, such chambers experience pressure that is evenly distributed to all portions of the inner surface of the bladder material from which the chamber is formed. Accordingly, the tendency is for chambers, when inflated, to take on an outwardly rounded shape. For use as cushioning members in footwear, however, it is desirable to provide the chambers with a relatively flat form, to serve as a platform for receiving the sole of a foot of a wearer. Thus, to limit the expansion of the top and bottom portions of the chamber upon inflation, sole structures have been developed with chambers having one or more tensile structures that link the top portion of the chamber to the bottom portion of the chamber in order to maintain the chambers in a substantially planar configuration. However, such tensile members may provide increased stiffness to the chambers. Accordingly, there is a need for chamber configurations that provide tensile member-equipped fluid-filled chambers with increased flexibility.

## SUMMARY

(6) The present disclosure is generally directed to fluid-filled chamber configurations having tensile members including a top sheet bonded to a top barrier layer of the chamber, a bottom sheet bonded to a bottom barrier layer of the chamber, and a plurality of tethers extending between the top sheet and the bottom sheet. The outer barrier layers of the chamber, which retain the pressurized fluid, are bonded to the top sheet and the bottom sheet of the tensile member. The length of the tethers restricts the amount by which the outer barrier layers of the chamber may expand when the chamber is pressurized.

(7) In order to provide the chamber with greater flexibility, portions of the tensile member may be

stitched, thereby restricting the amount by which the top sheet and the bottom sheet in select portions of the tensile member separate upon pressurization of the chamber. Because the barrier layers are bonded to the tensile member, this configuration may form the chamber with a reduced thickness in the area in which the tensile member is stitched. Due to the reduced thickness, the area of the chamber having the reduced thickness may be more flexible than other portions of the chamber. For example, the reduced thickness may form a flex groove. Such flex grooves may be selectively located at various portions of the chamber corresponding with portions of the article of footwear sole structure that are desired to have greater flexibility, such as the ball of the foot.

(8) In one aspect, the present disclosure is directed to a chamber for receiving a pressurized fluid. The chamber may include a first chamber barrier layer and a second chamber barrier layer bonded to the first chamber barrier layer about peripheral portions of the first chamber barrier layer and the second chamber barrier layer to define an interior void between the first chamber barrier layer and the second chamber barrier layer. In addition, the chamber may include a tensile member extending between the first chamber barrier layer and the second chamber barrier layer, the tensile member including a first tensile member layer bonded to the first chamber barrier layer, a second tensile member layer bonded to the second chamber barrier layer, and a plurality of tethers extending between the first tensile member layer and the second tensile member layer. Further, the chamber may include stitching through the tensile member in a stitched region. When the chamber is pressurized with the pressurized fluid, a substantial majority of the first tensile member layer is separated from the second tensile member layer by a distance that corresponds to a length of the plurality of tethers. In addition, the first tensile member layer is held in contact with the second tensile member layer by the stitching in the stitched region, thereby forming an area of the chamber having a reduced thickness relative to adjacent portions of the chamber.

(9) In another aspect, the present disclosure is directed to a chamber for receiving a pressurized fluid. The chamber may include a first chamber barrier layer and a second chamber barrier layer bonded to the first chamber barrier layer about peripheral portions of the first chamber barrier layer and the second chamber barrier layer to define an interior void between the first chamber barrier layer and the second chamber barrier layer. In addition, the chamber may include a tensile member extending between the first chamber barrier layer and the second chamber barrier layer, the tensile member including a first tensile member layer bonded to the first chamber barrier layer, a second tensile member layer bonded to the second chamber barrier layer, and a plurality of tethers extending between the first tensile member layer and the second tensile member layer. Further, the chamber may include stitching through the tensile member in a stitched region. When the chamber is pressurized with the pressurized fluid, a substantial majority of the first tensile member layer is separated from the second tensile member layer by a distance that corresponds to a length of the plurality of tethers. In addition, the first tensile member layer is held at a second distance from the second tensile member layer by the stitching in the stitched region, thereby forming an area of the chamber having a reduced thickness relative to adjacent portions of the chamber. Further, the stitched region includes at least two elongate lines of stitching, including a first line of stitching and a second line of stitching arranged parallel and adjacent to the first line of stitching.

(10) In another aspect, the present disclosure is directed to a chamber for receiving a pressurized fluid. The chamber may include a first chamber barrier layer and a second chamber barrier layer bonded to the first chamber barrier layer about peripheral portions of the first chamber barrier layer and the second chamber barrier layer to define an interior void between the first chamber barrier layer and the second chamber barrier layer. The chamber may also include a tensile member extending between the first chamber barrier layer and the second chamber barrier layer, the tensile member including a first tensile member layer bonded to the first chamber barrier layer, a second tensile member layer bonded to the second chamber barrier layer, and a plurality of tethers extending between the first tensile member layer and the second tensile member layer. Also, the chamber may include first stitching through the tensile member in a first stitched region and second

stitching through the tensile member in a second stitched region. When the chamber is pressurized with the pressurized fluid, a substantial majority of the first tensile member layer is separated from the second tensile member layer by a distance that corresponds to a length of the plurality of tethers. In addition, the first tensile member layer is held a first distance from the second tensile member layer by the first stitching in the first stitched region, thereby forming a first area of the chamber having a first reduced thickness relative to adjacent portions of the chamber. Also, the first tensile member layer is held a second distance from the second tensile member layer by the second stitching in the second stitched region, thereby forming a second area of the chamber having a second reduced thickness relative to adjacent portions of the chamber, and the second distance is greater than the first distance.

(11) In another aspect, the present disclosure is directed to a method of forming a chamber for receiving a pressurized fluid. The method may include providing a plurality of chamber components, including a first chamber barrier layer, a second chamber barrier layer, and a tensile member, the tensile member having a first tensile member layer, a second tensile member layer, and a plurality of tethers extending between the first tensile member and the second tensile member layer. The method may also include stitching through a portion of the tensile member, thereby drawing the first tensile member layer into contact with the second tensile member layer in a stitched area, and arranging the plurality of chamber components in a stacked arrangement. Further, the method may include arranging the chamber components in a stacked arrangement involves locating the tensile member between the first chamber barrier layer and the second chamber barrier layer and joining the chamber components to one another by applying pressure to the stacked arrangement of chamber components. The method may also include inflating the chamber with a pressurized fluid, the pressurized fluid expanding unstitched areas of the tensile member, applying tension to the plurality of tethers, wherein, in stitched areas of the tensile member, contact is maintained between the first tensile member layer and the second tensile member layer.

(12) Other systems, methods, features and advantages of the current embodiments will be, or will become, apparent to one of ordinary skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description and this summary, be within the scope of the current embodiments, and be protected by the following claims.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

(1) The invention can be better understood with reference to the following drawings and description. The figures are schematic representations of components of the disclosed invention. Accordingly, the components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the invention. Moreover, in the figures, like reference numerals designate corresponding parts throughout the different views.

(2) FIG. 1 shows a bottom perspective view of an article of footwear according to an exemplary embodiment.

(3) FIG. 2 shows a bottom view of the article of footwear shown in FIG. 1.

(4) FIG. 3 shows an exploded perspective view of a sole structure of an article of footwear according to an exemplary embodiment.

(5) FIG. 4 is a cross-sectional view of a chamber barrier layer according to an exemplary embodiment.

(6) FIG. 5 is a cross-sectional view of a chamber barrier layer according to another exemplary embodiment.

(7) FIG. 6 is a cross-sectional view illustrating stitching of a tensile member according to an



exemplary embodiment.

(8) FIG. 7 is another cross-sectional view illustrating stitching of a tensile member according to an exemplary embodiment.

(9) FIG. 8 is a cross-sectional view illustrating bonding of thermoplastic layers to a tensile member according to an exemplary embodiment.

(10) FIG. 9 is a cross-sectional view illustrating bonding of chamber barrier layers to a tensile member according to an exemplary embodiment.

(11) FIG. 10 is a cross-sectional view illustrating inflation of a chamber according to an exemplary embodiment.

(12) FIG. 11 is a cross-sectional view illustrating bonding of thermoplastic layers to a tensile member according to an exemplary embodiment.

(13) FIG. 12 is a cross-sectional view illustrating stitching of a tensile member according to an exemplary embodiment.

(14) FIG. 13 is another cross-sectional view illustrating stitching of a tensile member according to an exemplary embodiment.

(15) FIG. 14 is a cross-sectional view illustrating bonding of chamber barrier layers to a tensile member according to an exemplary embodiment.

(16) FIG. 15 is a cross-sectional view illustrating inflation of a chamber according to an exemplary embodiment.

(17) FIG. 16 is a perspective view of an assembled sole structure of an article of footwear according to an exemplary embodiment.

(18) FIG. 17 is a cross sectional view taken at section line 17-17 in FIG. 16.

(19) FIG. 18 is a cross sectional view taken at section line 18-18 in FIG. 16.

(20) FIG. 19 is a cross sectional view illustrating the sole structure shown in FIG. 17 in an articulated configuration.

(21) FIG. 20 illustrates a stitching pattern for a chamber for an article of footwear according to an exemplary embodiment.

(22) FIG. 21 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(23) FIG. 22 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(24) FIG. 23 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(25) FIG. 24 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(26) FIG. 25 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(27) FIG. 26 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(28) FIG. 27 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(29) FIG. 28 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(30) FIG. 29 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(31) FIG. 30 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(32) FIG. 31 illustrates a stitching pattern for a chamber for an article of footwear according to another exemplary embodiment.

(33) FIG. 32 is a cross sectional view illustrating an exemplary sole structure in an articulated

configuration.

(34) FIG. 33 is a perspective view of a heel region of a chamber according to an exemplary embodiment.

(35) FIG. 34 is a cross-sectional view taken at section line 34-34 in FIG. 33.

(36) FIG. 35 is a bottom perspective view of an article of footwear according to an exemplary embodiment.

(37) FIG. 36 illustrates a garment having an incorporated chamber according to an exemplary embodiment.

(38) FIG. 37 illustrates a bag having an incorporated chamber according to an exemplary embodiment.

(39) FIG. 38 illustrates a glove having an incorporated chamber according to an exemplary embodiment.

(40) FIG. 39 illustrates a protective chest pad having an incorporated chamber according to an exemplary embodiment.

#### DETAILED DESCRIPTION

(41) The following discussion and accompanying figures disclose a sole structure for an article of footwear. Concepts associated with the footwear disclosed herein may be applied to a variety of athletic footwear types, including running shoes, basketball shoes, cross-training shoes, cricket shoes, golf shoes, soccer shoes, baseball shoes, cycling shoes, football shoes, golf shoes, tennis shoes, and walking shoes, for example. Accordingly, the concepts disclosed herein apply to a wide variety of footwear types.

(42) For consistency and convenience, directional adjectives are employed throughout this detailed description corresponding to the illustrated embodiments. The term “longitudinal,” as used throughout this detailed description and in the claims, refers to a direction extending a length of a sole structure, i.e., extending from a forefoot portion to a heel portion of the sole. The term “forward” is used to refer to the general direction in which the toes of a foot point, and the term “rearward” is used to refer to the opposite direction, i.e., the direction in which the heel of the foot is facing.

(43) The term “lateral direction,” as used throughout this detailed description and in the claims, refers to a side-to-side direction extending a width of a sole. In other words, the lateral direction may extend between a medial side and a lateral side of an article of footwear, with the lateral side of the article of footwear being the surface that faces away from the other foot, and the medial side being the surface that faces toward the other foot.

(44) The term “lateral axis,” as used throughout this detailed description and in the claims, refers to an axis oriented in a lateral direction.

(45) The term “horizontal,” as used throughout this detailed description and in the claims, refers to any direction substantially parallel with the ground, including the longitudinal direction, the lateral direction, and all directions in between. Similarly, the term “side,” as used in this specification and in the claims, refers to any portion of a component facing generally in a lateral, medial, forward, and/or rearward direction, as opposed to an upward or downward direction.

(46) The term “vertical,” as used throughout this detailed description and in the claims, refers to a direction generally perpendicular to both the lateral and longitudinal directions. For example, in cases where a sole is planted flat on a ground surface, the vertical direction may extend from the ground surface upward. It will be understood that each of these directional adjectives may be applied to individual components of a sole. The term “upward” refers to the vertical direction heading away from a ground surface, while the term “downward” refers to the vertical direction heading towards the ground surface. Similarly, the terms “top,” “upper,” and other similar terms refer to the portion of an object substantially furthest from the ground in a vertical direction, and the terms “bottom,” “lower,” and other similar terms refer to the portion of an object substantially closest to the ground in a vertical direction.

(47) For purposes of this disclosure, the foregoing directional terms, when used in reference to an article of footwear, shall refer to the article of footwear in an upright position, with the sole facing groundward as it would be positioned when worn by a wearer standing on a substantially level surface.

(48) In addition, for purposes of this disclosure, the term “fixedly attached” shall refer to two components joined in a manner such that the components may not be readily separated (for example, without destroying one or both of the components). Exemplary modalities of fixed attachment may include joining with permanent adhesive, rivets, stitches, nails, staples, welding or other thermal bonding, chemical or molecular bonding, and/or other joining techniques. In addition, two components may be “fixedly attached” by virtue of being integrally formed, for example, in a molding process.

(49) FIG. 1 depicts an embodiment of an article of footwear **100**, which may include a sole structure **105** and an upper **110** secured to sole structure **105**. As shown in FIG. 1 for reference purposes, footwear **100** may be divided into three general regions, including a forefoot region **130**, a midfoot region **135**, and a heel region **140**. Forefoot region **130** generally includes portions of footwear **100** corresponding with the toes and the joints connecting the metatarsals with the phalanges. Midfoot region **135** generally includes portions of footwear **100** corresponding with an arch area of the foot. Heel region **140** generally corresponds with rear portions of the foot, including the calcaneus bone. Forefoot region **130**, midfoot region **135**, and heel region **140** are not intended to demarcate precise areas of footwear **100**. Rather, forefoot region **130**, midfoot region **135**, and heel region **140** are intended to represent general relative areas of footwear **100** to aid in the following discussion.

(50) Since sole structure **105** and upper **110** both span substantially the entire length of footwear **100**, the terms forefoot region **130**, midfoot region **135**, and heel region **140** apply not only to footwear **100** in general, but also to sole structure **105** and upper **110**, as well as the individual elements of sole structure **105** and upper **110**. Footwear **100** may be formed of any suitable materials. In some configurations, the disclosed footwear **100** may employ one or more materials disclosed in Lyden et al., U.S. Pat. No. 5,709,954, issued Jan. 20, 1998, the entire disclosure of which is incorporated herein by reference.

(51) Upper **110** may include one or more material elements (for example, textiles, foam, leather, and synthetic leather), which may be stitched, adhesively bonded, molded, or otherwise formed to define an interior void configured to receive a foot. The material elements may be selected and arranged to selectively impart properties such as durability, air-permeability, wear-resistance, flexibility, and comfort. Upper **110** may alternatively implement any of a variety of other configurations, materials, and/or closure mechanisms.

(52) Sole structure **105** may have a configuration that extends between upper **110** and the ground and may be secured to upper **110** in any suitable manner. For example, sole structure **105** may be secured to upper **110** by adhesive attachment, stitching, welding, or any other suitable method. Sole structure **105** may include provisions for attenuating ground reaction forces (that is, cushioning and stabilizing the foot during vertical and horizontal loading). In addition, sole structure **105** may be configured to provide traction, impart stability, and/or limit various foot motions, such as pronation, supination, and/or other motions.

(53) The configuration of sole structure **105** may vary significantly according to one or more types of ground surfaces on which sole structure **105** may be used. For example, the disclosed concepts may be applicable to footwear configured for use on indoor surfaces and/or outdoor surfaces. The configuration of sole structure **105** may vary based on the properties and conditions of the surfaces on which footwear **100** is anticipated to be used. For example, sole structure **105** may vary depending on whether the surface is harder or softer. In addition, sole structure **105** may be tailored for use in wet or dry conditions, for example by varying the tread pattern and traction elements.

(54) Sole structure **105** may include multiple components, which may individually and/or

collectively provide footwear **100** with a number of attributes, such as support, rigidity, flexibility, stability, cushioning, comfort, reduced weight, traction, and/or other attributes. As shown in FIG. 1, sole structure **105** may include a ground-contacting outer member **120**. In addition, in some embodiments, sole structure **105** may also include a midsole **115** disposed between outer member **120** and upper **110**.

(55) Outer member **120** may include an outer surface **125** exposed to the ground. Outer member **120** may be formed of suitable materials for achieving the desired performance attributes. For example, outer member **120** may be formed of any suitable polymer, composite, and/or metal alloy materials. Exemplary such materials may include thermoplastic and thermoset polyurethane, polyester, nylon, polyether block amide, alloys of polyurethane and acrylonitrile butadiene styrene, carbon fiber, poly-paraphenylene terephthalamide (para-aramid fibers, e.g., Kevlar®), titanium alloys, and/or aluminum alloys. In some embodiments, outer member **120** may be fashioned from a durable and wear-resistant material (for example, rubber). In some embodiments, outer member **120** may be formed of a compressible polymer foam material. Other suitable materials, including future-developed materials, will be recognized by those having skill in the art. Materials and configurations for outer member **120** may be selected according to the type of activity for which footwear **100** is configured.

(56) In some embodiments, outer member may have a plurality of sipes extending upward and defining a plurality of sole elements. The plurality of sipes may provide the sole structure with increased flexibility. In some embodiments, the positions and orientations of the sipes may be selected to complement the natural motion of the foot during the running cycle. During the running cycle, as the heel leaves the ground, the foot rolls forward, loading the forefoot and the toes. In some embodiments, lateral sipes may be provided to increase longitudinal flexibility of the outer member of the sole structure. In some embodiments, longitudinal sipes may provide increased flexibility in a lateral direction. The increased flexibility in both the longitudinal direction and the lateral direction may allow the foot to flex in a more natural manner during contact with the ground. In addition, the siping may be configured to control, prevent, or limit certain foot motions. For example, in some embodiments, the siping may be configured to control pronation and/or supination.

(57) Upper **110** and sole structure **105** may have structures that cooperatively flex, stretch, or otherwise move to provide an individual with a sensation of natural, barefoot running. That is, upper **110** and sole structure **105** may be configured to complement the natural motion of the foot during running or other activities. In contrast with barefoot running, however, sole structure **105** may attenuate ground reaction forces to decrease the overall stress upon the foot.

(58) FIG. 2 shows a bottom view of footwear **100**. As shown in FIG. 2, outer member **120** may include a plurality of sipes **200**. For example, outer member **120** may include a laterally-located longitudinal sipe **205** and a medially-located longitudinal sipe **210**. In some embodiments, laterally-located longitudinal sipe **205** may extend a full length of outer member **120**, as shown in FIG. 2. In some embodiments, medially-located longitudinal sipe **210** may extend a partial length of outer member **120**. For example, as shown in FIG. 2, medially-located longitudinal sipe **210** may extend longitudinally in forefoot region **130** of outer member **120**. In some embodiments, laterally-located longitudinal sipe **205** and medially-located longitudinal sipe **210** may be substantially parallel to one another, as shown in FIG. 2.

(59) Outer member **120** may include a plurality of laterally oriented sipes extending in substantially lateral directions. For example, as shown in FIG. 2, outer member **120** may include a first forefoot lateral sipe **215**, a second forefoot lateral sipe **220**, a third forefoot lateral sipe **225**, a fourth forefoot lateral sipe **230**, and a fifth forefoot lateral sipe **235**. In addition, outer member **120** may include a first midfoot lateral sipe **240** and a second midfoot lateral sipe **245**. Further, outer member **120** may include a heel region lateral sipe **250**.

(60) As shown in FIG. 2, the plurality of sipes may define a plurality of discreet sole elements.

Outer member **120** may include various features configured to provide traction. For example, outer surface **125** may include a patterned tread, as shown in FIG. 2. In some embodiments, outer member **120** may include one or more tread members associated corresponding with the discrete sole elements defined by the plurality of sipes. In some embodiments, the tread members may be selectively located to provide traction at select portions of outer member **120**. For example, as shown in FIG. 2, outer member **120** may include a first lateral tread member **255**, a second lateral tread member **260**, and a third lateral tread member **265**. These tread members may provide traction during movements in which the lateral portion of the forefoot region of footwear **100** is substantially loaded.

(61) As also shown in FIG. 2, outer member **120** may include a first medial tread member **270**, a second medial tread member **275**, and a third medial tread member **280**. These tread members may provide traction during movements in which the medial portion of the forefoot region of footwear **100** is substantially loaded. In addition, outer member **120** may further include a toe region tread member **285**, and a heel region tread member **290**. On or more of first lateral tread member **255**, second lateral tread member **260**, third lateral tread member **265**, first medial tread member **270**, second medial tread member **275**, third medial tread member **280**, toe region tread member **285**, and heel region tread member **290** may be formed of a material that provides more grip than other portions of outer member **120**. For example, while a substantial majority of outer member **120** may be formed of a compressible foam material, the tread members may be formed of a rubber compound. Additionally, the tread members may have ground engaging features, such as projections or recesses, as shown in FIG. 2.

(62) FIG. 3 is an exploded view of sole structure **105**. In some embodiments, sole structure **105** may include one or more additional components that control ground reaction forces. For example, in some embodiments, sole structure **105** may include a chamber **150** for receiving a pressurized fluid, such as one or more gases. Chamber **150** may be compressible, and thus, may provide cushioning by attenuating ground reaction forces. As shown in FIG. 3, in some embodiments, midsole **115** may include a recess **145** configured to receive and contain chamber **150**.

(63) In some embodiments, sole structure **105** may include an additional component on top of chamber **150**. For example, sole structure **105** may include a footbed member (not shown). The footbed member may form a covering over top of chamber **150**, to conceal chamber **150** from an inner portion of the article of footwear. In addition, the footbed member may provide a surface or footbed configured to support the foot of a wearer directly. In some embodiments, the footbed member may be removable. For example, in some embodiments, the footbed member may be a removable insole/sockliner. In other embodiments, the footbed member may be fixedly attached to one or more portions of the article of footwear. In some embodiments, the footbed member may be fixedly attached to midsole **115** about the periphery of recess **145**, thereby enclosing chamber **150**. In some embodiments, the footbed member may be a strobil. For example, the footbed member may be fixedly attached to an upper of the article of footwear. In such a strobil embodiment, the footbed member, when combined with the upper, may substantially completely enclose the foot of a wearer and isolate the wearer's foot from chamber **150**. The footbed member may have any suitable configuration and any suitable material. For example, in some embodiments, the footbed member may be substantially incompressible. In such embodiments, the footbed member may be formed of rigid or semi-rigid materials such as hard plastics, carbon fiber, or other composite materials. In other embodiments, a substantially incompressible footbed member may be formed of a relatively flexible material, such as a textile, leather, or synthetic leather.

(64) Midsole **115** may have any suitable configuration and may provide cushioning and stability. For example, in some embodiments, midsole **115** may be formed of a compressible material, such as a resilient polymer foam material, examples of which may include polyurethane (PU) or ethyl vinyl acetate (EVA). In some embodiments, midsole **115** may extend throughout the length and width of footwear **100**. In some embodiments, midsole **115** may also incorporate incompressible

plates, moderators, and/or other elements that further attenuate forces, influence the motions of the foot, and/or impart stability, for example.

(65) As shown in the enlarged cross-sectional view in FIG. 3, chamber **150** may include a first chamber barrier layer **155** and a second chamber barrier layer **160**. As shown in FIG. 3, in some embodiments, first chamber barrier layer **155** may be a top barrier layer and second chamber barrier layer **160** may be a bottom barrier layer. Second chamber barrier layer **160** may be bonded to first chamber barrier layer **155** about peripheral portions of first chamber barrier layer **155** and second chamber barrier layer **160** to define an interior void between first chamber barrier layer **155** and second chamber barrier layer **160**.

(66) The fluid within chamber **150** may range in pressure from zero to three-hundred-fifty kilopascals (i.e., approximately fifty-one pounds per square inch) or more. In some configurations of sole structure **105**, a suitable pressure for the fluid may be a substantially ambient pressure. That is, the pressure of the fluid may be within five kilopascals of the ambient pressure of the atmospheric air surrounding footwear **100**. The pressure of fluid within chamber **150** may be selected to provide desirable performance attributes. For example, higher pressures may provide a more responsive cushioning element, whereas lower pressures may provide more ground force attenuation (a softer cushion). The pressure of fluid within chamber **150** may be selected to work in concert with other cushioning elements of footwear **100**, such as midsole **115** and footbed member **185**.

(67) In some configurations, chamber **150** may be inflated with substantially pure nitrogen. Such an inflation gas promotes maintenance of the pressure within chamber **150** through diffusion pumping, whereby the deficiency of other gases (besides nitrogen), such as oxygen, within chamber **150** biases the system for inward diffusion of such gasses into chamber **150**. Further, bladder materials, such as those discussed above, may be substantially impermeable to nitrogen, thus preventing the escape of the nitrogen from chamber **150**.

(68) In some configurations, relatively small amounts of other gases, such as oxygen or a mixture of gasses, such as air, may be added to the nitrogen occupying most of the volume within chamber **150**. In some configurations, chamber **150** may incorporate a valve that permits the individual to adjust the pressure of the fluid. In other configurations, chamber **150** may be incorporated into a fluid system, as disclosed in U.S. Pat. No. 7,210,249 to Passke, et al., as a pump chamber or a pressure chamber. In order to pressurize chamber **150** or portions of chamber **150**, the general inflation methods disclosed in Hensley et al., U.S. Pat. No. 8,241,450, issued Aug. 14, 2012, and entitled "Method For Inflating A Fluid-Filled Chamber," and Schindler et al., U.S. Pat. No. 8,860,408, issued Oct. 21, 2014, and entitled "Article Of Footwear Having A Sole Structure With A Fluid-Filled Chamber," may be utilized. The patents and published patent applications listed in this paragraph are incorporated herein by reference in their entirety.

(69) In some embodiments, the chamber may include one or more features that limit the expansion of the top and bottom portions of the chamber upon inflation. For example, in some embodiments, the chamber may include one or more tensile structures that link the top portion of the chamber to the bottom portion of the chamber. Such tensile structures may be substantially inelastic (or may have a limited elasticity) such that, when the chamber is inflated causing the top and bottom portions of the chamber to be biased apart from one another, the tensile structures limit the distance by which the top and bottom portions may be separated during inflation. Accordingly, the tensile structures may enable the bladder to retain its intended, substantially planar shape.

(70) As shown in FIG. 3, a tensile structure, such as a tensile member **165** may extend between first chamber barrier layer **155** and second chamber barrier layer **160**. Tensile member **165** may be bonded to first chamber barrier layer **155** and second chamber barrier layer **160**. For example, in some embodiments, a thermoplastic (hot melt) adhesive may be used to bond tensile member **165** to first chamber barrier layer **155** and second chamber barrier layer **160**. Tensile member **165** may have a limited elasticity and, therefore, may limit the extent to which first chamber barrier layer

**155** and second chamber barrier layer **160** may be expanded away from one another upon inflation of chamber **150**.

(71) As shown in FIG. 3, tensile member **165** may include a first tensile member layer **170** and a second tensile member layer **175**. Further, tensile member **165** may also include a plurality of tethers **180** extending between first tensile member layer **170** and second tensile member layer **175**.

(72) Tensile member **165** may have any configuration suitable for limiting the distance between first chamber barrier layer **155** and second chamber barrier layer **160** of chamber **150** when inflated. For example, tensile member **165** may have any of the configurations disclosed in Dua, U.S. Pat. No. 8,151,486, issued Apr. 10, 2012, and entitled "Fluid-Filled Chamber with a Textile Tensile Member;" Peyton et al., U.S. Pat. No. 8,479,412, issued Jul. 9, 2013, and entitled "Tethered Fluid-Filled Chambers;" and Hazenberg et al., U.S. Patent Application Publication No. 2013/0266773, published Oct. 10, 2013, and entitled "Spacer Textile Materials and Methods for Manufacturing the Spacer Textile Materials," (U.S. patent application Ser. No. 13/443,421, filed Apr. 10, 2012) the entire disclosures of which are incorporated herein by reference.

(73) In some configurations, tethers **180** may include a plurality of substantially planar slats. In some configurations, such slats may be arranged in a substantially vertical orientation. In other embodiments, such slats may be angled with respect to first chamber barrier layer **155** and second chamber barrier layer **160**. Further, such slats may be oriented in any suitable direction. For example, in some embodiments, the slats may be oriented in a substantially lateral direction. In other embodiments, the slats may be oriented in a substantially longitudinal direction. Other orientations are also possible. Tethers **180** may have any of the planar configurations disclosed in Dua, U.S. Pat. No. 8,151,486, issued Apr. 10, 2012, and entitled "Fluid-Filled Chamber with a Textile Tensile Member."

(74) In some configurations, tethers **180** may include a plurality of strand-like members having a substantially one-dimensional configuration. For example, tethers **180** may each have a length between first tensile member layer **170** and second tensile member **175**. This length may be substantially greater than the width or thickness of the one-dimensional tethers. Tethers **180** may have any of the one-dimensional configurations disclosed in Peyton et al., U.S. Pat. No. 8,479,412, issued Jul. 9, 2013, and entitled "Tethered Fluid-Filled Chambers."

(75) Tethers **180** may be formed of any suitable material. For example in some embodiments, tethers **180** may be formed of a polymer material. In some embodiments, tensile member **165** may be formed of a three-dimensional fabric (3-D fabric). Tensile member **165** may be formed as a unitary (i.e., one-piece) textile element having the configuration of a spacer-knit textile. A variety of knitting techniques may be utilized to form tensile member **165** and impart a specific configuration (e.g., taper, contour, length, width, thickness) to tensile member **165**. In general, knitting involves forming courses and wales of intermeshed loops of a yarn or multiple yarns. In production, knitting machines may be programmed to mechanically-manipulate yarns into the configuration of tensile member **165**. That is, tensile member **165** may be formed by mechanically-manipulating yarns to form a one-piece textile element that has a particular configuration. The two major categories of knitting techniques are weft-knitting and warp-knitting. Whereas a weft-knit fabric utilizes a single yarn within each course, a warp-knit fabric utilizes a different yarn for every stitch in a course. In some embodiments, tensile member **165** may be formed using double needle bar Raschel knitting. In some embodiments, tensile member **165** may be formed using configurations disclosed in Hazenberg et al., U.S. Patent Publication No. 2013/0266773, published Oct. 10, 2013, and entitled "Spacer Textile Materials and Methods for Manufacturing the Spacer Textile Materials," (U.S. patent application Ser. No. 13/443,421, filed Apr. 10, 2012).

(76) In some embodiments, all of tethers **180** may have substantially the same length, thus providing tensile member **165** with a substantially constant thickness. In other embodiments, tethers **180** may have different lengths. In some embodiments, first tensile member layer **170** and second tensile member layer **175** may each have a generally continuous and planar configuration.

In some embodiments, first tensile member layer **170** and second tensile member layer **175** may be substantially parallel to one another. In other embodiments, tensile member **165** may have a tapered configuration. For example, in some embodiments, tensile member **165** may have a tapered configuration between heel region **140** and forefoot region **130**. In order to impart the tapered configuration, the lengths of tethers **180** may decrease between the heel region and forefoot region of chamber **150**. Exemplary tapered chamber configurations are disclosed in Dua, U.S. Pat. No. 8,151,486, issued Apr. 10, 2012, and entitled “Fluid-Filled Chamber with a Textile Tensile Member.”

(77) In some embodiments, one or both of first tensile member layer **170** and second tensile member layer **175** may have a contoured configuration. For example, in some embodiments, first tensile member layer **170** may have a concave configuration to conform to the anatomical shapes of the foot. A depression in heel region **140** may cradle the heel of a wearer and more evenly distribute contact forces between chamber **150** and the foot of the wearer. Exemplary contoured chamber configurations are disclosed in Dua, U.S. Pat. No. 8,151,486, issued Apr. 10, 2012, and entitled “Fluid-Filled Chamber with a Textile Tensile Member;” and Peyton et al., U.S. Pat. No. 8,479,412, issued Jul. 9, 2013, and entitled “Tethered Fluid-Filled Chambers.”

(78) In some embodiments, the chamber may include stitching through select portions of the tensile member in order to maintain the select portions of the tensile member in a collapsed configuration. This may provide the chamber with a reduced thickness, which may provide hinge-like flexibility in the stitched region. As shown in FIG. 3, stitching **185** may be stitched through tensile member **165**. As shown in FIG. 3, first tensile member layer **155** remains continuous across multiple sections of chamber **150**. Thus, tensile member **165** may be a fully pre-formed structure prior to assembly into chamber **150**. Tensile member **165** being a fully pre-formed structure may facilitate positioning of tensile member **165** during assembly, because there are no separate pieces that may become out of place with respect to one another when pressed between first chamber barrier layer **155** and second chamber barrier layer **160**.

(79) Stitching **185** may be incorporated in chamber **150** in one or more stitched lines. For example, chamber **190** may include one or more laterally-oriented stitch lines **190**. Additionally, or alternatively, chamber **190** may include one or more longitudinally-oriented stitch lines **195**.

(80) FIG. 3 illustrates sipes **200** with hidden lines **198** in recess **145**. As shown in FIG. 3, in some embodiments, the stitch lines of chamber **150** may correspond to, and align with, sipes **200** in outer member **120**. Exemplary configurations of stitching **185** are discussed in greater detail below.

(81) FIG. 4 is a cross-sectional view of chamber barrier layer **155** according to an exemplary embodiment. Chamber barrier layers may be formed from a polymer or other bladder material that provides a sealed barrier for enclosing a fluid. As noted above, the bladder material may be transparent. A wide range of polymer materials may be utilized for chamber **150**. In selecting materials for chamber **150**, engineering properties of the material (e.g., tensile strength, stretch properties, fatigue characteristics, dynamic modulus, and loss tangent) as well as the ability of the material to prevent the diffusion of the fluid contained by chamber **150** may be considered. When formed of thermoplastic urethane, for example, the outer barrier of chamber **150** may have a thickness of approximately 1.0 millimeter, but the thickness may range from 0.25 to 2.0 millimeters or more, for example.

(82) In addition to thermoplastic urethane, examples of polymer materials that may be suitable for chamber barrier layers include polyurethane, polyester, polyester polyurethane, and polyether polyurethane. Chamber barrier layers may also be formed from a material that includes alternating layers of thermoplastic polyurethane and ethylene-vinyl alcohol copolymer, as disclosed in U.S. Pat. Nos. 5,713,141 and 5,952,065 to Mitchell, et al. A variation upon this material may also be utilized, wherein a center layer is formed of ethylene-vinyl alcohol copolymer, layers adjacent to the center layer are formed of thermoplastic polyurethane, and outer layers are formed of a regrind material of thermoplastic polyurethane and ethylene-vinyl alcohol copolymer. Another suitable



material for chamber barrier layers is a flexible microlayer membrane that includes alternating layers of a gas barrier material and an elastomeric material, as disclosed in U.S. Pat. Nos. 6,082,025 and 6,127,026 to Bonk, et al. Additional suitable materials are disclosed in U.S. Pat. Nos. 4,183,156 and 4,219,945 to Rudy. Further suitable materials include thermoplastic films containing a crystalline material, as disclosed in U.S. Pat. Nos. 4,936,029 and 5,042,176 to Rudy, and polyurethane including a polyester polyol, as disclosed in U.S. Pat. Nos. 6,013,340; 6,203,868; and 6,321,465 to Bonk, et al. The patents listed in this paragraph are incorporated herein by reference in their entirety.

(83) In some embodiments, the chamber barrier layers may be formed from a material that includes multiple layers. For example, in some embodiments, one or more of the chamber barrier layers may include alternating layers of thermoplastic polyurethane and ethylene-vinyl alcohol copolymer, as disclosed in U.S. Pat. Nos. 5,713,141 and 5,952,065 to Mitchell, et al., the entire disclosures of which are incorporated herein by reference. In some embodiments, each chamber barrier layer may have the alternating layered configuration. As depicted in FIG. 4, in some embodiments, chamber barrier layer **155** may include a first center layer **405**, a second layer **410**, and a third layer **415**. First layer **405** may be disposed between second layer **410** and third layer **415**. Further, first layer **405** may be joined to both second layer **405** and third layer **415**.

(84) In some embodiments, first layer **405** may be formed of a first material and second layer **410** may be formed of a second material. In some embodiments, third layer **415** may also be formed of the second material. Further, the second material may be different from the first material. In some embodiments, the first material may include an ethylene-vinyl copolymer. The second material may include a thermoplastic polymer. For example, in some embodiments, the thermoplastic polymer may be thermoplastic polyurethane.

(85) FIG. 5 is a cross-sectional view of a chamber barrier layer according to another exemplary embodiment. In FIG. 5, a chamber barrier layer **500** may include 5 layers of material. For example, chamber barrier layer **500** may include a first center layer **505**, a second layer **510**, and a third layer **515**. In some embodiments, first center layer **505**, second layer **510**, and third layer **515** may have configurations similar to corresponding layers discussed above with respect to FIG. 4. In addition, chamber barrier layer **500** may include a fourth layer **520** and a fifth layer **525**. Second layer **510** may be disposed between fourth layer **520** and first layer **505**. Further, second layer **505** may be joined to fourth layer **520**. In addition, third layer **515** may be disposed between fifth layer **525** and first layer **505**. Further, third layer **415** may be joined to fifth layer **425**.

(86) In some embodiments, fourth layer **520** may be formed of a third material and fifth layer **525** may also be formed of the third material. In some embodiments, the third material may be different than the second material. Further, the third material may also be different than the first material. In some embodiments, fourth layer **520** may be formed of a material that includes a regrind of thermoplastic polyurethane and ethylene-vinyl copolymer. Similarly, fifth layer **525** may also be formed of a material that includes a regrind of thermoplastic polyurethane and ethylene-vinyl copolymer.

(87) Another suitable material for chamber barrier layers is a flexible microlayer membrane that includes alternating layers of a gas barrier material and an elastomeric material, as disclosed in U.S. Pat. Nos. 6,082,025 and 6,127,026 to Bonk, et al. Additional suitable materials are disclosed in U.S. Pat. Nos. 4,183,156 and 4,219,945 to Rudy. Further suitable materials include thermoplastic films containing a crystalline material, as disclosed in U.S. Pat. Nos. 4,936,029 and 5,042,176 to Rudy, and polyurethane including a polyester polyol, as disclosed in U.S. Pat. Nos. 6,013,340; 6,203,868; and 6,321,465 to Bonk, et al.

(88) FIG. 6 is a cross-sectional view illustrating stitching of a tensile member according to an exemplary embodiment. As shown in FIG. 6, stitching **185** may be stitched through tensile member **165**. In some embodiments, the stitching may be performed with a needle **185**.

(89) The stitching may include any suitable thread or other strand-like material. The stitching

should have a tensile strength configured to prevent or limit the separation of the first tensile member layer from the second tensile member layer by the expansive forces applied by the pressurized fluid within the chamber. Any suitable material may be used for stitching the tensile member. In some embodiments, the stitching may be substantially inelastic. In other embodiments, the stitching may have a limited elasticity, allowing a predetermined amount of separation between the first tensile member layer and the second tensile member layer upon pressurization of the chamber.

(90) In some embodiments, the stitching may include a monofilament strand. In some embodiments, the stitching may include a braided strand. In some embodiments, the stitching may include synthetic strand materials. For example, the stitching may include nylon, polyvinylidene fluoride (PVDF, aka fluorocarbon), polyethylene, Dacron, Dyneema (ultra high molecular weight poly ethylene (UHMWPE)), polyvinyl chloride (PVC), polyester, rayon (processed cellulose), or combinations thereof. In some embodiments, the stitching may include natural materials, such as cotton, silk, wool, or combinations thereof. In some embodiments, the stitching may include combinations of synthetic material and natural material.

(91) The needle and thread shown in FIG. 6 are shown to schematically illustrate the stitching of the tensile member. In some embodiments, the tensile member may be stitched manually. In other embodiments, a machine may be used to stitch the tensile member. In some embodiments, the machine may be operated by a technician. In other embodiments, the machine may be semi-automated, or fully automated. For example, as discussed in greater detail below, the tensile member may be stitched in various patterns. Such patterned stitching may be performed with an automated machine. In some embodiments, the pattern may include one or more substantially straight lines. In some embodiments, the pattern may include one or more substantially curved lines. In some embodiments, the pattern may include both curved and straight lines of stitching. Further, in some embodiments, the pattern may include two or more lines of the stitching substantially adjacent one another. In some embodiments, the stitching may be embroidered.

(92) FIG. 7 is another cross-sectional view illustrating stitching of tensile member **165**. As shown in FIG. 7, stitching **185** may be pulled tight, as illustrated by a first arrow **605** showing the pulling of stitching **185** by needle **600**. As further shown in FIG. 7, the stitching through a portion of tensile member **165** may draw first tensile member layer **170** and second tensile member layer **175** toward one another in a stitched area. This may produce an area of reduced thickness **610** in tensile member **165**. In some embodiments, the stitching may draw the tensile member layers into contact with one another.

(93) It will be noted that FIG. 7 is a schematic illustration of the stitching process. The tightening of stitching **185** may be performed as part of the machine stitching process. Therefore, in some embodiments, the tightening may not necessarily be performed by pulling needle **600** in the direction of first arrow **605**.

(94) In some embodiments, adhesive layers may be utilized to bond tensile member **165** to the chamber barrier layers. In some cases, such adhesive layers may be bonded to tensile member **165** after the stitching of tensile member **165** is performed. For example, FIG. 8 is a cross-sectional view illustrating bonding of thermoplastic layers to tensile member **165**. As shown in FIG. 8, a first thermoplastic layer **615** may be placed adjacent to first tensile member layer **170** of tensile member **165**. In addition, second thermoplastic layer **620** may be placed adjacent to second tensile member layer **170**. This placement of these components may form a stacked arrangement. The stacked arrangement may be compressed in the direction of a second arrow **625** and a third arrow **630**. In addition, heat may be applied to at least partially activate first thermoplastic layer **615** and second thermoplastic layer **620** to bond with tensile member **165**.

(95) FIG. 9 is a cross-sectional view illustrating bonding of chamber barrier layers to tensile member **165**. As illustrated in FIG. 9, first chamber barrier layer **155**, tensile member **165** and second chamber barrier layer **160** may be arranged in a stacked arrangement. That is, arranging the

chamber components in a stacked arrangement involves locating tensile member **165** between first chamber barrier layer **155** and second chamber barrier layer **160**. Once stacked, the components may be joined together by compression illustrated by a fourth arrow **635** and a fifth arrow **640**. In addition to compression, heat may be applied to activate first thermoplastic layer **615** and second thermoplastic layer **620**, to thereby thermally bond thermoplastic layer **615** to first tensile member layer **170** and second thermoplastic layer **620** to second tensile member layer **175**.

(96) Once peripheral portions of first chamber barrier layer **155** and second chamber barrier layer **160** are joined together to define a chamber, the chamber may be inflated. FIG. **10** is a cross-sectional view illustrating inflation of chamber **150** formed by the steps shown in FIGS. **6-9**. As shown in FIG. **10**, inflation gases may be injected into chamber **150** to pressurize chamber **150**, as illustrated by a sixth arrow **645** and a billow of gas **650**. Pressurizing chamber **150** may be performed to expand unstitched areas of tensile member **165**. Accordingly, this will apply tension to tethers **180**, as illustrated by tethers **180** shown in a straight configuration, as opposed to the curved configuration illustrated in FIGS. **6-9**. In a stitched area **655**, first tensile member layer **170** and second tensile member layer **175** may be held closer to one another than in unstitched areas of tensile member **165**. In some embodiments, a gap may remain between first tensile member layer **170** and second tensile member layer **175** in stitched area **655**, as shown in FIG. **10**. In other embodiments, in stitched areas of the tensile member, contact may be maintained between the first tensile member layer and the second tensile member layer.

(97) In some embodiments, the adhesive layers may be bonded to the tensile member prior to stitching of the tensile member. Once the adhesive layers are bonded to the tensile member, the stitching may be passed through the tensile member and the adhesive layers. FIGS. **11-15** illustrate a similar process of forming chamber **150** as shown in FIGS. **6-10**, except that, as shown in FIG. **11**, first thermoplastic layer **615** and second thermoplastic layer **620** may be bonded to tensile member **165** prior to stitching. As shown in FIG. **12**, needle **600** may pass stitching **185** through not only tensile member **165** but also through first thermoplastic layer **615** and second thermoplastic layer **620**.

(98) As shown in FIG. **13**, upon tightening stitching **185**, an area of reduced thickness **670** in tensile member **165** may be formed. FIG. **14** illustrates the bonding of first chamber barrier layer **155** and second chamber barrier layer **160** by applying pressure indicated by a seventh arrow **675** and an eighth arrow **680**. Heat may also be applied to activate first thermoplastic layer **615** and second thermoplastic layer **620**. Finally, as indicated by ninth arrow **685** and a billow **690** in FIG. **15**, chamber **150** may be inflated with pressurized gasses. As shown in FIG. **15**, stitching **185** may provide chamber **150** with a reduced thickness in a stitched area **695**.

(99) A method of forming an article of footwear may include incorporating a chamber formed in the manner discussed above into the sole structure of the article of footwear. In some embodiments, stitching may include forming an elongate stitched region. In some cases, the sole structure of the article of footwear may include at least one flex groove, and incorporating the chamber into the sole structure includes aligning the elongate stitched region with the at least one flex groove.

(100) In some embodiments, stitching through a portion of the tensile member includes forming a stitched region by stitching a first line of stitching and a second line of stitching parallel and adjacent to the first line of stitching. This may provide a wider hinge in the chamber, which may provide varying performance in terms of flexibility.

(101) In some embodiments, pressurizing the chamber with the pressurized fluid expands the first tensile member such that a substantial majority of the first tensile member layer is separated from the second tensile member layer by a distance that corresponds to a length of the plurality of tethers. In some embodiments, a first area of the chamber corresponding with the first stitched region has a first reduced thickness relative to adjacent portions of the chamber. Further, upon inflation of the chamber, the first tensile member layer is held a distance from the second tensile member layer by stitching in the second stitched region, thereby forming a second area of the

chamber having a second reduced thickness relative to adjacent portions of the chamber.

(102) FIG. **16** is an assembled view of sole structure **105**. As shown in FIG. **16**, chamber **150** may be incorporated into sole structure **105** of the article of footwear. As further shown in FIG. **16**, the stitch lines of chamber **150** may be aligned with sipes **200** of outer member **120** of sole structure **105**. For example, chamber **150** may include a stitch line **1605** that is aligned with sipe **225**, as shown in FIG. **16**.

(103) FIGS. **17** and **18** illustrate cross-sectional views taken through sole structure **105** shown in FIG. **16**. In particular, FIG. **17** is a cross sectional view taken at section line **17-17** in FIG. **16**. FIG. **17** illustrates chamber **150** disposed in recess **145**. FIG. **17** also shows outer member **120**, including a tread member **1705**. FIG. **17** further shows area of reduced thickness **610** in chamber **150** in an enlarged view.

(104) As shown in FIG. **17**, the sipes in outer member **120** form a plurality of flex grooves in outer member **120**. In some embodiments, the flex grooves may be aligned with stitched regions of chamber **150**. For example, as shown in FIG. **17**, stitch line **1605** may be aligned with sipe **225**. By aligning the stitch lines and the flex grooves, the flexible portions of each component may be aligned, thus allowing for more overall flexibility of sole structure **105** than if the stitch lines and sipes were non-aligned.

(105) FIG. **18** is a cross sectional view taken at section line **18-18** in FIG. **16**. As shown in FIG. **18**, a longitudinal stitch line **1615** may be aligned with sipe **205**. This arrangement may provide increased lateral flexibility in sole structure **105** than if the stitch line and sipe were non-aligned. In some embodiments, the flex groove and the stitched region may be disposed in a forefoot region of the article of footwear, in a location that corresponds with a ball of a foot of a wearer of the article of footwear.

(106) FIG. **19** is a cross sectional view illustrating the sole structure shown in FIG. **17** in an articulated configuration. FIG. **19** illustrates the forefoot region of sole structure **105** being curved upward as it may be when the wearer's heel is raised off the ground. As shown in FIG. **19**, sipe **205** may open wider to form a more open flex groove upon articulation of sole structure **105**. Stitch line **1605** of chamber **150** may form a hinge region **1620**, which may articulate along with outer member **120**. That is, as shown in FIG. **19**, when chamber **1340** is articulated, adjacent sections of chamber **150** may hingedly rotate with respect to one another about the hinged region **1620**.

(107) In some embodiments, stitching in the chamber may be incorporated in patterns that provide the chamber with varying properties throughout its structure. For example, in some embodiments, stitch lines may be located at select distances or arrangements with respect to one another in order to provide the chamber with different flexibilities in different portions of the chamber. Providing the chamber with varying levels of flexibility may increase the correlation between the flexibility of the sole structure of the footwear and the wearer's foot.

(108) FIG. **20** illustrates a stitching pattern for a chamber for an article of footwear according to an exemplary embodiment. As shown in FIG. **20**, a chamber **2000** may include a stitched region. In some embodiments, the stitched region may include a longitudinal line of stitching **2005**. In some embodiments, the stitched region may include a first line of stitching **2010**, a second line of stitching **2015** substantially parallel to first line of stitching **2010**, and a third line of stitching **2020** substantially parallel to first line of stitching **2010** and second line of stitching **2015**. As shown in FIG. **20**, second line of stitching **2015** may be spaced from first line of stitching **2010** by a first distance **2025**. Further, third line of stitching **2020** may be spaced from second line of stitching **2015** by a second distance **2030**. In some cases, first distance **2025** may be different than second distance **2030**.

(109) In some embodiments, a first region of chamber **2000** including first line of stitching **2010** and second line of stitching **2015** may have a first degree of flexibility. In addition, a second region of chamber **2000** including second line of stitching **2015** and third line of stitching **2020** may have a second degree of flexibility that is different than the first degree of flexibility of the first region of

chamber **2000**.

(110) In addition, in some embodiments, chamber **2000** may include a fourth line of stitching **2035** and a fifth line of stitching **2040**. Fourth line of stitching **2035** and fifth line of stitching **2040** may be disposed at a third distance **2045** from one another. In some embodiments, third distance **2045** may be different than first distance **2025** and second distance **2030**.

(111) FIG. **21** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **21**, a chamber **2100** may include a first plurality of stitch lines **2105**. In addition, chamber **2100** may include a second plurality of stitch lines **2110**. In some embodiments, first plurality of stitch lines **2105** may be substantially perpendicular to second plurality of stitch lines **2110**. Further, in some embodiments, first plurality of stitch lines **2105** may overlap second plurality of stitch lines **2110**, thus forming a grid of stitching. It will be noted that in some embodiments, the stitch lines may be substantially linear, as shown, for example, in FIG. **21**. Linear stitch lines may be faster and less costly to produce. Further, a grid of linear stitch lines may provide the chamber with flexibility in multiple directions. In addition, it will be noted that, in some embodiments, the stitch lines may be disposed off-axis. That is, as shown in FIG. **21**, neither first plurality of stitch lines **2105** and second plurality of stitch lines **2110** may be oriented at an angle to both the longitudinal direction and the lateral direction.

(112) In some embodiments, overlapping stitch lines, or stitch lines that otherwise extend at angles to one another may reduce flexibility compared to stitch lines that do not have additional stitch lines proximate to and/or overlapping. Accordingly, in some embodiments, the chamber may include stitch lines that are discontinuous.

(113) FIG. **22** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **22**, a chamber **2200** may include an elongate stitched region, in the form of a first stitch line **2205** and a second stitch line **2210**. First stitch line **2205** and second stitch line **2210** may be oriented along axes that intersect with one another. Further, in some embodiments, first stitch line **2205** and second stitch line **2210** may intersect one another. However, as shown in FIG. **22**, both first stitch line **2205** and second stitch line **2210** may be discontinuous, and thus may not overlap one another. As shown in FIG. **22**, first stitch line **2205** may include a first gap **2215**. Similarly, second stitch line **2210** may include a second gap **2220**. First gap **2215** and second gap **2220** may prevent first stitch line **2205** and second stitch line **2210** from overlapping, and thus may avoid any reduction in flexibility that may be provided by such overlapping.

(114) In some embodiments, stitching patterns may be arranged to provide differing flexibility in different portions of the chamber. For example, in some embodiments, multi-axial flexibility may be desired in some areas of the foot, such as the forefoot region, whereas single-axis flexibility may be desired in other areas of the foot, such as a midfoot region. Accordingly, different stitching patterns may be used in different portions of the chamber.

(115) FIG. **23** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **23**, a chamber **2300** may include a first set of stitch lines **2305** in the forefoot region of chamber **2300**. First set of stitch lines **2305** may be formed in a grid-like arrangement, which may provide multi-axial flexibility. In addition, chamber **2300** may include a second set of stitch lines **2310** in the midfoot region of chamber **2300**. Second set of stitch lines **2310** may be arranged substantially parallel to one another, and may be oriented in a substantially longitudinal direction. Such longitudinally arranged stitch lines may provide increased flexibility in the lateral direction.

(116) In some embodiments, stitch lines may be arranged in an asymmetric manner to permit and/or control asymmetric aspects of foot motion. FIG. **24** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **24**, a chamber **2400** may include a plurality of elongate portions, such as stitch lines, radiating in different directions from a central point. For example, as shown in FIG. **24**, chamber **2400** may include a first stitch line **2405**, a second stitch line **2410**, a third stitch line **2415**, a fourth stitch line **2420**, a fifth stitch line **2425**, and a sixth stitch line **2430**. As further shown in FIG. **24**, first stitch line **2405**, second stitch line **2410**, third stitch

line **2415**, fourth stitch line **2420**, fifth stitch line **2425**, and sixth stitch line **2430** may all converge at a common center point **2435**. As shown in FIG. **24**, center point **2435** may be disposed on a medial side of the forefoot region of chamber **2400**. Thus, the radiating portions of the stitch lines may extend toward the lateral side of chamber **2400**. Since converging stitch lines may decrease flexibility, the additional space between the stitch lines on the lateral side of chamber **2400** may provide chamber **2400** with a greater amount of flexibility on the lateral side. In some embodiments, the center point may be located elsewhere, such as on the lateral side of the chamber, and the stitch lines may radiate in generally medial directions. In some embodiments, both configurations may be included in the same chamber, as shown in FIG. **24**.

(117) While the embodiment shown in FIG. **24** utilizes substantially linear stitch lines, in other embodiments, converging stitch lines may be curved. FIG. **25** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **25**, a chamber **2500** may include a stitched region including a plurality of curved portions intersecting at a common intersection point. For example, chamber **2500** may include a first stitch line **2505**, a second stitch line **2510**, and a third stitch line **2515**. As shown in FIG. **25**, first stitch line **2505**, second stitch line **2510**, and third stitch line **2515** may intersect at an intersection point **2517**.

(118) As further shown in FIG. **25**, in some embodiments, the plurality of curved portions may be curved about center points disposed on a common line, wherein the plurality of curved portions each have a different radius of curvature. For example, as shown in FIG. **25**, first stitch line **2505** may be curved about a first center point **2520**. Second stitch line **2510** may be curved about a second center point **2525**. Third stitch line **2515** may be curved about a third center point **2530**. As shown in FIG. **25**, first center point **2520**, second center point **2525**, and third center point **2530** may be disposed on a common line **2535**. Further, first stitch line **2505** may have a first radius of curvature **2540**, second stitch line **2510** may have a second radius of curvature **2545**, and third stitch line **2515** may have a third radius of curvature **2550**. As shown in FIG. **25**, first radius of curvature **2540**, second radius of curvature **2545**, and third radius of curvature **2550** may be different from one another. This may result in two sets of radiating stitch lines. As shown in FIG. **25**, one set of radiating stitch lines may extend toward a forefoot region of chamber **2500**, and a second set of radiating stitch lines may extend toward a heel region of chamber **2500**, the intersection **2517** being disposed in a midfoot region of chamber **2500**.

(119) In some embodiments, both curved and linear stitch lines may be utilized in a stitch pattern for a chamber. In some embodiments, such curved stitch lines may intersect with linear stitch lines. In order to avoid undesired reduction in flexibility due to overlapping, the curved stitch lines may intersect with the linear stitch lines in a non-overlapping manner.

(120) FIG. **26** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **26**, a chamber **2600** may include a first curved stitch line **2605**, a second curved stitch line **2610**, a third curved stitch line **2615**. In some embodiments, these curved stitch lines may be concentric about a common center point **2650**. In addition, as further shown in FIG. **26**, chamber **2600** may include a first linear stitch line **2620**, a second linear stitch line **2625**, and a third linear stitch line **2630**. These linear stitch lines may also each extend along axes that intersect with center point **2650**.

(121) In some embodiments, first curved stitch line **2605** may intersect with first linear stitch line **2620** at a first intersection point **2635**. Second curved stitch line **2610** may intersect with second linear stitch line **2625** at a second intersection point **2640**. Third curved stitch line **2615** may intersect with third linear stitch line **2630** at a third intersection point **2645**. As shown in FIG. **26**, the curved stitch lines and linear stitch lines may not overlap at these intersection points. As shown in FIG. **26**, in some embodiments, the curved stitch lines may be disposed on a medial side of chamber **2600**, and the linear stitch lines may be disposed on a lateral side of chamber **2600**. This arrangement may provide differing flexibility to support or control different foot motions on the medial and lateral sides of the foot. In other embodiments, the location of curved and linear stitch

lines maybe reversed. In some embodiments center point **2650** may be located in a forefoot region of chamber **2600**. In other embodiments, the center point may be located elsewhere, such as in a heel region of chamber **2600**. As shown in FIG. **26**, in some embodiments, both arrangements may be used, for example, a laterally radiating arrangement in the forefoot region, and a medially radiating arrangement in the heel region.

(122) In some embodiments, it may be desirable to provide flexibility around the peripheral edge of the chamber. FIG. **27** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **27**, a chamber **2700** may include an elongate stitched region, for example, including a stitch line **2705**. In some embodiments, as shown in FIG. **27**, the stitched region including stitch line **2705** may extend around a periphery of chamber **2700**. Further, in some embodiments, stitch line **2700** may be substantially evenly spaced from an edge of chamber **2700** in a heel region **2710** of chamber **2700**. Such a configuration may cradle the foot of the wearer, but enabling peripheral portions of chamber **2700** to flex upward to wrap around the outside of the foot.

(123) In some embodiments, stitching may be used in chambers to provide flexibility in certain regions and to provide contours in other regions. FIG. **28** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **28**, a chamber **2800** may include a first stitch line **2805** in a forefoot region of chamber **2800**. In addition, chamber **2800** may include a second stitch line **2810** in the forefoot region. First stitch line **2805** and second stitch line **2810** may extend in substantially lateral directions across the forefoot region of chamber **2800**. Accordingly, first stitch line **2805** and second stitch line **2810** may provide flexibility to the forefoot region of chamber **2800**.

(124) In addition, as shown in FIG. **28**, chamber **2800** may include a curved stitch line **2815**. Curved stitch line **2815** may extend about a peripheral portion of a heel region of chamber **2800**. Curved stitch line **2815** may provide flexibility to the peripheral portions of the heel region in order to cradle the heel of a wearer in a central area **2820** of the heel region.

(125) In some embodiments, stitching may provide flexibility at lateral and medial edges of the chamber, in select areas. FIG. **29** illustrates a stitching pattern for a chamber for an article of footwear. FIG. **29** shows a chamber **2900**, including a stitched region including a plurality of curved stitch lines. For example, chamber **2900** may include a first stitch line **2905**, a second stitch line **2910**, and a third stitch line **2915**. These three stitch lines may be curved in the same direction and may be substantially parallel to one another. In addition, these lines may extend in a substantially lateral direction across chamber **2900**, in order to provide longitudinal flexibility to chamber **2900**.

(126) Chamber **2900** may also include a toe stitch line **2920**, which may be curved in an opposite direction as first stitch line **2905**, second stitch line **2910**, and third stitch line **2915**. Further, chamber **2900** may include a medial curved stitch line **2925** disposed proximate a medial edge of chamber **2900**. In addition, chamber **2900** may include a lateral curved stitch line **2930** disposed proximate a lateral edge of chamber **2900**. Medial curved stitch line **2925** and lateral curved stitch line **2930** may provide flexibility at the medial and lateral edges of a forefoot region of chamber **2900**.

(127) In some embodiments, substantially uni-directional flexibility may be provided by arranging the stitched regions in substantially parallel lines. FIG. **30** illustrates another stitching pattern for a chamber for an article of footwear. As shown in FIG. **30**, a chamber **3000** may include a plurality of substantially parallel stitch lines. As shown in FIG. **30**, in some embodiments, the stitch lines may extend in a substantially lateral direction, in order to provide longitudinal flexibility to chamber **3000**. In some embodiments, the stitch lines may be equidistant from one another (i.e., evenly spaced), in order to provide a substantially consistent flexibility over the length of the chamber. For example, chamber **3000** may include a first stitch line **3005**, a second stitch line **3010** substantially parallel to first stitch line **3005**, and a third stitch line **3015** substantially parallel to second stitch

line **3010**. First stitch line **3005** may be disposed a first distance **3020** from second stitch line **3010**. In addition, second stitch line **3010** may be disposed a second distance **3025** from third stitch line **3015**. In some embodiments, first distance **3020** may be substantially the same as second distance **3025**, as shown in FIG. **30**. In other embodiments, first distance **3020** and second distance **3025** may be substantially different. Substantially different distances between parallel stitch lines may be implemented to provide differing flexibility to different portions of the chamber.

(128) In some embodiments, multiple stitch lines may be disposed adjacent to one another to provide different flexibility characteristics than single stitch lines. Multiple stitch lines may provide wider areas of reduced thickness in the chamber, which may increase flexibility.

(129) FIG. **31** illustrates another stitching pattern for a chamber for an article of footwear. FIG. **31** shows a chamber **3100** having a stitched region including a plurality of stitch lines **3105**. In addition, chamber **3100** may also include a first flex groove **3110** and a second flex groove **3115**. As shown in the enlarged view in FIG. **31**, first flex groove **3110** may be formed using multiple stitches adjacent to one another. For example, the stitched region may include at least two elongate lines of stitching, including a first line of stitching **3120** and a second line of stitching **3125** arranged parallel and adjacent to first line of stitching **3120**.

(130) In some embodiments, differing flexibility may be provided with stitching by holding opposing layers of the tensile member at varying distances from one another, thus varying the amount to which the thickness of the chamber is reduced in the stitched regions. A greater reduction in thickness of the chamber will provide more flexibility. In some embodiments, different flexibility may be provided in different portions of the same chamber, by utilizing stitch lines that draw opposing layers of the tensile member toward each other by differing amounts.

(131) As shown in FIG. **32**, a chamber **3200** may include multiple stitch lines. Similar to other embodiments discussed above, chamber **3200** may include a first chamber barrier layer **3205** and a second chamber barrier layer **3210**. In addition, chamber **3200** may also include a tensile member **3215**, which may include a first tensile member layer **3220**, a second tensile member layer **3225**, and a plurality of tethers **3230**.

(132) Chamber **3200** may include a first stitched region **3235**, a second stitched region **3240**, and a third stitched region **3245**. In unstitched regions of tensile member **3215**, when chamber **3200** is pressurized with a pressurized fluid, a substantial majority of first tensile member layer **3220** is separated from second tensile member layer **3225** by a distance that corresponds to a length of tethers **3230**. As shown in FIG. **32**, first stitched region **3235** features stitching having a first length **3250**. Under pressurization, first tensile member layer **3220** is held against second tensile member layer **3225** by the stitching in first stitched region **3235**.

(133) As shown in FIG. **32**, second stitched region **3240** may feature stitching having a second length **3255**, which is longer than first length **3250**. Accordingly, upon pressurization of chamber **3200**, first tensile member layer **3220** may be held a first distance **3265** away from second tensile member layer **3225**. Further, third stitched region may feature stitching having a third length **3260**, which is longer than second length **3255**. Accordingly, upon pressurization of chamber **3200**, first tensile member layer **3220** may be held a second distance **3270** away from second tensile member layer **3225**. In some embodiments, second distance **3270** may be greater than first distance **3265**.

(134) As illustrated in FIG. **32**, these different length stitches provide different amounts of reduction in the thickness of chamber **3200**, which provides different amounts of flexibility. First stitched region **3235** provides the largest reduction in chamber thickness, and thus, provides the greatest flexibility, as indicated by an angle **3290**. Second stitched region **3240** provides the next largest reduction in chamber thickness, and thus, provides a slightly less amount of flexibility, as indicated by an angle **3291**, which is less acute than angle **3290**. Similarly, third stitched region **3245** provides the least reduction in chamber thickness, and thus, provides the least flexibility, which is indicated by an angle **3292**, which is less acute than angle **3291**.

(135) As further shown in FIG. **32**, varying chamber flexibility may be disposed at locations of the



sole structure that correspond with predetermined portions of a wearer's foot **3205**. In some cases, stitched lines may provide hinges in chambers that correspond generally with portions of the wearer's foot that bend, such as the forefoot. In some embodiments, stitched lines may provide hinges that are configured to be substantially aligned with articulating joints of the wearer's foot. For example, as shown in FIG. **32**, first stitched region **3235** may be configured to be aligned with a joint between a first bone **3275** (e.g., a first metatarsal) and a second bone **3280** (e.g., a first phalanx) of the wearer's foot. In contrast, a joint between second bone **3280** and a third bone **3285** (e.g., hallux) may be located proximate to, but generally between second stitched region **3240** and third stitched region **3245**.

(136) FIG. **32** illustrates the correlation between the amount of articulation of the joints of foot **3205** and the amount of flexibility provided in corresponding portions of chamber **3200**. For example, first bone **3275** may have a first longitudinal axis **3276**, second bone **3280** may have a second longitudinal axis **3281**, and third bone **3285** may have a third longitudinal axis **3286**. As shown in FIG. **32**, a fourth angle **3293** between first longitudinal axis **3276** and second longitudinal axis **3281** may be greater than a fifth angle **3294** between second longitudinal axis **3281** and third longitudinal axis **3286**.

(137) Varying the distance at which opposing layers of the tensile member are held with respect to one another may also be implemented to provide the chamber with contours. For example, anatomical contours may provide improvements in fit, comfort, support, performance, and other characteristics of a sole structure.

(138) FIG. **33** is a perspective view of a chamber including a contoured heel region. As shown in FIG. **33**, a chamber **3300** may include a depression **3305** in a central portion of the heel region. Depression **3305** may be an anatomical contour configured to receive a portion of the foot of a wearer, such as the heel. In some embodiments, the central depression may be formed by utilizing stitching of shorter lengths near a central portion **3310** of depression **3305**, and using longer stitching further from central portion **3310**. In some embodiments, substantially concentric or spiral stitching **3315** may be utilized to form depression **3305**.

(139) FIG. **34** is a cross-sectional view of chamber **3300** taken at section line **34-34** in FIG. **33**, through a heel region of chamber **3300**. In addition, chamber **3300** is shown, in FIG. **34**, as being disposed within a recess **3330** in a midsole **3320**, above an outer member **3325**. As shown in FIG. **34**, chamber **3300** may include a first chamber barrier layer **3335**, a second chamber barrier layer **3340**, and a tensile member **3345** extending between, and bonded to, first chamber barrier layer **3335** and second chamber barrier layer **3340**.

(140) As shown in FIG. **34**, chamber **3300** may include a stitched region including stitching **3315**. In central portion **3310** of depression **3310**, stitching **3315** may include relatively short stitches **3360**. In a peripheral portion of depression **3310**, stitching **3315** may include relatively longer stitches **3355**. As illustrated in FIG. **34**, longer stitches **3355** allow first chamber barrier layer **3335** to expand further away from second chamber barrier layer **3340**, than short stitches **3360**. Stitching **3315** may be tapered and/or curved to form an anatomical depression configured to receive the heel of a wearer. Other anatomical contours may be provided in a similar manner. For example, arch supports, or other contoured features may be provided in chamber **3300**.

(141) In some embodiments, transparent windows may be utilized in the sole structure, in order to allow viewing of stitching designs in a chamber disposed in the midsole. FIG. **35** is a bottom perspective view of an article of footwear including a transparent window. As shown in FIG. **35**, an article of footwear **3500** may include a sole structure **3505** and an upper **3510** secured to the sole structure. As further shown in FIG. **35**, sole structure **3505** may include a midsole **3515** and an outer member **3520**. In some embodiments, sole structure **3505** may include an opening **3521** through which stitching **3530** of a stitched region of a chamber may be visible. In some embodiments, a substantially transparent window **3525** may be disposed in opening **3521**.

(142) In order to facilitate viewing of the stitching, the exposed chamber barrier layer may be

formed of a substantially transparent material through which the stitching may be viewed within opening **3521** and, in some embodiments, through substantially transparent window **3525**.

(143) Stitching **3530** may have any suitable configuration. In addition to the structural characteristics of the various stitching embodiments discussed above, stitching **3530** may also have various aesthetic properties. For example, in some embodiments stitching **3530** may include alphanumeric characters **3535**. Alternatively, or additionally, stitching **3530** may include graphic designs **3540**. Exemplary stitching designs may include logos, branding, customized graphics and lettering, or any other suitable designs.

(144) In some embodiments, chambers having configurations discussed above may be implemented in other products (i.e., besides footwear). For example, such chambers may be utilized as padding in garments. For example, FIG. **36** illustrates a garment **3600** including padding **3610**. As shown in FIG. **36**, garment **3600** may be a pair of pants or shorts. As also shown in FIG. **36**, padding **3610** may be disposed on a lateral portion of garment **3600**, for example, to provide protection during sporting activities.

(145) As further shown in FIG. **36**, padding **3610** may include an inner layer of fabric **3615** and an outer layer of fabric **3620** forming a pouch configured to receive a padding element. In some embodiments, such as shown in FIG. **36**, a chamber **3625** may be provided within the pouch. Chamber **3625** may have a stitched region forming a hinged portion **3630** according to any of the embodiments discussed above. With the stitched region **3630**, chamber **3625** may be configured to articulate about hinged portion **3630** to thereby form an anatomical shape configured to conform to an anatomical contour of the body of a wearer of the garment.

(146) The disclosed chambers may also be applicable for use in other types of equipment. In one example, a shoulder strap of a bag, such as a backpack, may include a fluid-filled chamber according to disclosed embodiments. FIG. **37** illustrates a bag **3700** having a shoulder strap **3705**. As illustrated in FIG. **37**, shoulder strap **3705** may include a first layer of material **3710** and a second layer of material **3715** defining an inner pocket configured to receive a cushioning element. As shown in FIG. **37**, shoulder strap **3705** may include a chamber **3720** having a stitched region providing a reduced thickness in chamber **3720**, thus forming a hinged portion **3725**. Chamber **3720** may be configured to articulate about hinged portion **3725** forming an anatomical shape configured to conform to an anatomical contour of the body of a carrier of bag **3700**.

(147) The disclosed chambers may also be applicable for use in other types of athletic equipment. For example, as shown in FIG. **38**, a glove **3800**, such as a baseball glove or softball glove, may include a finger region **3805** and a palm region **3810**. In some embodiments, glove **3800** may include a chamber **3815**, including one or more stitched regions **3820**, which may provide a reduced thickness in chamber **3815**. The pressurized chamber may provide padding for the glove. In addition, the stitched, hinge-like regions may provide an anatomical curvature and flexion, for example, while closing the hand while catching a ball.

(148) In another embodiment, protective chest pad **3900**, such as may be worn by a catcher in baseball or softball, or a goalie in other sports, may include a chamber **3905**. Chamber **3905** may include stitching **3910** according to embodiments disclosed above. Stitching **3910** may provide flexibility to chest pad **3900** to allow the pad to be fitted to the contours of the wearer's body, and to flex as the body moves, for example, when a catcher squats down and stands up.

(149) While various embodiments of the invention have been described, the description is intended to be exemplary, rather than limiting, and it will be apparent to those of ordinary skill in the art that many more embodiments and implementations are possible that are within the scope of the invention. Although many possible combinations of features are shown in the accompanying figures and discussed in this detailed description, many other combinations of the disclosed features are possible. Therefore, it will be understood that any of the features shown and/or discussed in the present disclosure may be implemented together in any suitable combination and that features of one embodiment may be implemented in other disclosed embodiments.

Accordingly, the invention is not to be restricted except in light of the attached claims and their equivalents. Also, various modifications and changes may be made within the scope of the attached claims.

## Claims

1. An article comprising: a first chamber barrier layer and a second chamber barrier layer bonded to the first chamber barrier layer to form a chamber having an interior void between the first chamber barrier layer and the second chamber barrier layer; a tensile member extending between the first chamber barrier layer and the second chamber barrier layer within the interior void and including a first tensile member layer attached to the first chamber barrier layer, a second tensile member layer attached to the second chamber barrier layer, and a plurality of tethers extending between the first tensile member layer and the second tensile member layer; a plurality of stitchings attached to the first tensile member layer and to the second tensile member layer to form a first stitched region disposed between the first chamber barrier layer and the second chamber barrier layer and providing a portion of the tensile member with a first reduced thickness relative to adjacent portions of the tensile member; and a pouch receiving the chamber therein.
2. The article of claim 1, wherein the chamber includes an area of reduced thickness at the first stitched region relative to adjacent portions of the chamber.
3. The article of claim 1, wherein the first tensile member layer and the second tensile member layer are in contact with one another at the first stitched region.
4. The article of claim 1, wherein the first tensile member layer and the second tensile member layer are spaced apart from one another at the first stitched region.
5. The article of claim 1, further comprising a second stitched region disposed between the first chamber barrier layer and the second chamber barrier layer and providing a portion of the tensile member with a second reduced thickness relative to adjacent portions of the tensile member.
6. The article of claim 5, wherein the second stitched region is spaced apart from the first stitched region.
7. The article of claim 5, wherein the first tensile member layer and the second tensile member layer are in contact with one another at the second stitched region.
8. The article of claim 5, wherein the first tensile member layer and the second tensile member layer are spaced apart from one another at the second stitched region.
9. The article of claim 1, wherein the pouch includes at least one sheet extending over an outer surface of at least one of the first chamber barrier layer and the second chamber barrier layer.
10. The article of claim 9, wherein the at least one sheet is formed from fabric.
11. An article comprising: a first chamber barrier layer and a second chamber barrier layer bonded to the first chamber barrier layer to form a chamber having an interior void between the first chamber barrier layer and the second chamber barrier layer; a tensile member extending between the first chamber barrier layer and the second chamber barrier layer within the interior void and including a first tensile member layer attached to the first chamber barrier layer, a second tensile member layer attached to the second chamber barrier layer, and a plurality of tethers extending between the first tensile member layer and the second tensile member layer; a plurality of stitchings attached to the first tensile member layer and to the second tensile member layer, stitching of the plurality of stitchings drawing the first tensile member layer and the second tensile member layer toward one another at a first stitched region disposed between the first chamber barrier layer and the second chamber barrier layer; and a pouch receiving the chamber therein.
12. The article of claim 11, wherein the chamber includes an area of reduced thickness at the first stitched region relative to adjacent portions of the chamber.
13. The article of claim 11, wherein the first tensile member layer and the second tensile member layer are in contact with one another at the first stitched region.

14. The article of claim 11, wherein the first tensile member layer and the second tensile member layer are spaced apart from one another at the first stitched region.
  15. The article of claim 11, further comprising a second stitched region disposed between the first chamber barrier layer and the second chamber barrier layer, stitching of the plurality of stitchings drawing the first tensile member layer and the second tensile member layer toward one another at the second stitched region.
  16. The article of claim 15, wherein the second stitched region is spaced apart from the first stitched region.
  17. The article of claim 15, wherein the first tensile member layer and the second tensile member layer are in contact with one another at the second stitched region.
  18. The article of claim 15, wherein the first tensile member layer and the second tensile member layer are spaced apart from one another at the second stitched region.
  19. The article of claim 11, wherein the pouch includes at least one sheet extending over an outer surface of at least one of the first chamber barrier layer and the second chamber barrier layer.
  20. The article of claim 19, wherein the at least one sheet is formed from fabric.
-