

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408939
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ingram; Shannon C. et al.

Disruptive dressing for use with negative pressure and fluid instillation

Abstract

A method and apparatus for disrupting material at a tissue site is described. A contact layer may be selected for use on the tissue site and positioned adjacent to the tissue site. The contact layer may include walls defining a plurality of through-holes. A sealing member may be positioned over the contact layer and sealed to tissue surrounding the tissue site to form a sealed space enclosing the contact layer. A negative-pressure source may be fluidly coupled to the sealed space. The negative-pressure source may supply negative pressure to the sealed space and the contact layer to draw tissue into the through-holes to form nodules. The negative pressure may be vented from the sealed space to release the nodules.

Inventors: Ingram; Shannon C. (Bulverde, TX), Locke; Christopher Brian (Bournemouth, GB), Arnold; Peter (Northumberland, GB), Robinson; Timothy Mark (Shillingstone, GB), Carroll; Christopher Allen (San Antonio, TX), Manwaring; Michael E. (San Antonio, TX)

Applicant: Solventum Intellectual Properties Company (Maplewood, MN)

Family ID: 53267628

Assignee: Solventum Intellectual Properties Company (Maplewood, MN)

Appl. No.: 16/923651

Filed: July 08, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20200337719 A1	Oct. 29, 2020

Related U.S. Application Data

division parent-doc US 15884149 20180130 US 10743900 child-doc US 16923651
division parent-doc US 14708109 20150508 US 9918733 20180320 child-doc US 15884149

Publication Classification

Int. Cl.: **A61B17/32** (20060101); **A61B17/22** (20060101); **A61F13/05** (20240101); **A61M1/00** (20060101); **A61M27/00** (20060101)

U.S. Cl.:

CPC **A61B17/32** (20130101); **A61B17/22004** (20130101); **A61F13/05** (20240101);
 A61M1/915 (20210501); **A61M1/92** (20210501); **A61M27/00** (20130101);
 A61B2017/22008 (20130101); A61B2017/22089 (20130101); A61B2017/320008
 (20130101); A61B2017/32006 (20130101); A61B2017/320064 (20130101); A61M1/96
 (20210501)

Field of Classification Search

CPC: A61B (17/32); A61B (2017/320008); A61B (2017/32006); A61B (2017/320064); A61B
 (17/22004); A61B (2017/22008); A61B (2017/22089); A61F (13/00068); A61F
 (13/00042); A61F (13/00029); A61F (13/0216); A61F (2013/00255); A61F (13/05);
 A61M (27/00); A61M (1/90); A61M (1/92); A61M (1/015); A61M (1/96)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1355846	12/1919	Rannells	N/A	N/A
2547758	12/1950	Keeling	N/A	N/A
2632443	12/1952	Lesher	N/A	N/A
2682873	12/1953	Evans et al.	N/A	N/A
2910763	12/1958	Lauterbach	N/A	N/A
2969057	12/1960	Simmons	N/A	N/A
3066672	12/1961	Crosby, Jr. et al.	N/A	N/A
3367332	12/1967	Groves	N/A	N/A
3520300	12/1969	Flower, Jr.	N/A	N/A
3568675	12/1970	Harvey	N/A	N/A
3648692	12/1971	Wheeler	N/A	N/A
3682180	12/1971	McFarlane	N/A	N/A
3683921	12/1971	Brooks et al.	N/A	N/A
3826254	12/1973	Mellor	N/A	N/A
4080970	12/1977	Miller	N/A	N/A
4096853	12/1977	Weigand	N/A	N/A
4139004	12/1978	Gonzalez, Jr.	N/A	N/A
4165748	12/1978	Johnson	N/A	N/A
4184510	12/1979	Murry et al.	N/A	N/A
4233969	12/1979	Lock et al.	N/A	N/A
4245630	12/1980	Lloyd et al.	N/A	N/A

4256109	12/1980	Nichols	N/A	N/A
4261363	12/1980	Russo	N/A	N/A
4275721	12/1980	Olson	N/A	N/A
4284079	12/1980	Adair	N/A	N/A
4297995	12/1980	Golub	N/A	N/A
4333468	12/1981	Geist	N/A	N/A
4373519	12/1982	Errede et al.	N/A	N/A
4382441	12/1982	Svedman	N/A	N/A
4392853	12/1982	Muto	N/A	N/A
4392858	12/1982	George et al.	N/A	N/A
4419097	12/1982	Rowland	N/A	N/A
4465485	12/1983	Kashmer et al.	N/A	N/A
4475909	12/1983	Eisenberg	N/A	N/A
4480638	12/1983	Schmid	N/A	N/A
4525166	12/1984	Leclerc	N/A	N/A
4525374	12/1984	Vaillancourt	N/A	N/A
4540412	12/1984	Van Overloop	N/A	N/A
4543100	12/1984	Brodsky	N/A	N/A
4548202	12/1984	Duncan	N/A	N/A
4551139	12/1984	Plaas et al.	N/A	N/A
4569348	12/1985	Hasslinger	N/A	N/A
4605399	12/1985	Weston et al.	N/A	N/A
4608041	12/1985	Nielsen	N/A	N/A
4640688	12/1986	Hauser	N/A	N/A
4655754	12/1986	Richmond et al.	N/A	N/A
4664662	12/1986	Webster	N/A	N/A
4710165	12/1986	McNeil et al.	N/A	N/A
4733659	12/1987	Edenbaum et al.	N/A	N/A
4743232	12/1987	Kruger	N/A	N/A
4758220	12/1987	Sundblom et al.	N/A	N/A
4787888	12/1987	Fox	N/A	N/A
4826494	12/1988	Richmond et al.	N/A	N/A
4838883	12/1988	Matsuura	N/A	N/A
4840187	12/1988	Brazier	N/A	N/A
4863449	12/1988	Therriault et al.	N/A	N/A
4872450	12/1988	Austad	N/A	N/A
4878901	12/1988	Sachse	N/A	N/A
4897081	12/1989	Poirier et al.	N/A	N/A
4902565	12/1989	Brook	N/A	N/A
4906233	12/1989	Moriuchi et al.	N/A	N/A
4906240	12/1989	Reed et al.	N/A	N/A
4919654	12/1989	Kalt	N/A	N/A
4941882	12/1989	Ward et al.	N/A	N/A
4953565	12/1989	Tachibana et al.	N/A	N/A
4969880	12/1989	Zamierowski	N/A	N/A
4985019	12/1990	Michelson	N/A	N/A
5037397	12/1990	Kalt et al.	N/A	N/A
5086170	12/1991	Luheshi et al.	N/A	N/A
5092858	12/1991	Benson et al.	N/A	N/A
5100396	12/1991	Zamierowski	N/A	N/A

5134994	12/1991	Say	N/A	N/A
5149331	12/1991	Ferdman et al.	N/A	N/A
5167613	12/1991	Karami et al.	N/A	N/A
5176663	12/1992	Svedman et al.	N/A	N/A
5215522	12/1992	Page et al.	N/A	N/A
5232453	12/1992	Plass et al.	N/A	N/A
5261893	12/1992	Zamierowski	N/A	N/A
5278100	12/1993	Doan et al.	N/A	N/A
5279550	12/1993	Habib et al.	N/A	N/A
5298015	12/1993	Komatsuzaki et al.	N/A	N/A
5342376	12/1993	Ruff	N/A	N/A
5344415	12/1993	DeBusk et al.	N/A	N/A
5358494	12/1993	Svedman	N/A	N/A
5437622	12/1994	Carion	N/A	N/A
5437651	12/1994	Todd et al.	N/A	N/A
5527293	12/1995	Zamierowski	N/A	N/A
5549584	12/1995	Gross	N/A	N/A
5556375	12/1995	Ewall	N/A	N/A
5607388	12/1996	Ewall	N/A	N/A
5636643	12/1996	Argenta et al.	N/A	N/A
5645081	12/1996	Argenta et al.	N/A	N/A
6071267	12/1999	Zamierowski	N/A	N/A
6135116	12/1999	Vogel et al.	N/A	N/A
6241747	12/2000	Ruff	N/A	N/A
6287316	12/2000	Agarwal et al.	N/A	N/A
6345623	12/2001	Heaton et al.	N/A	N/A
6488643	12/2001	Tumey et al.	N/A	N/A
6493568	12/2001	Bell et al.	N/A	N/A
6553998	12/2002	Heaton et al.	N/A	N/A
6765123	12/2003	de Jong et al.	N/A	N/A
6814079	12/2003	Heaton et al.	N/A	N/A
7381859	12/2007	Hunt et al.	N/A	N/A
7846141	12/2009	Weston	N/A	N/A
7951124	12/2010	Boehringer et al.	N/A	N/A
8062273	12/2010	Weston	N/A	N/A
8216198	12/2011	Heagle et al.	N/A	N/A
8251979	12/2011	Malhi	N/A	N/A
8257327	12/2011	Blott et al.	N/A	N/A
8398614	12/2012	Blott et al.	N/A	N/A
8449509	12/2012	Weston	N/A	N/A
8529548	12/2012	Blott et al.	N/A	N/A
8535296	12/2012	Blott et al.	N/A	N/A
8551060	12/2012	Schuessler et al.	N/A	N/A
8568386	12/2012	Malhi	N/A	N/A
8679081	12/2013	Heagle et al.	N/A	N/A
8834451	12/2013	Blott et al.	N/A	N/A
8926592	12/2014	Blott et al.	N/A	N/A
9017302	12/2014	Vitaris et al.	N/A	N/A
9168180	12/2014	Ha et al.	N/A	N/A

9198801	12/2014	Weston	N/A	N/A
9211365	12/2014	Weston	N/A	N/A
9289542	12/2015	Blott et al.	N/A	N/A
9421309	12/2015	Robinson et al.	N/A	N/A
9918733	12/2017	Ingram et al.	N/A	N/A
9974694	12/2017	Locke et al.	N/A	N/A
10369058	12/2018	Ha et al.	N/A	N/A
10610414	12/2019	Hartwell et al.	N/A	N/A
10736788	12/2019	Locke et al.	N/A	N/A
10743900	12/2019	Ingram et al.	N/A	N/A
11224542	12/2021	Robinson et al.	N/A	N/A
2001/0037118	12/2000	Shadduck	N/A	N/A
2002/0065494	12/2001	Lockwood et al.	N/A	N/A
2002/0077661	12/2001	Saadat	N/A	N/A
2002/0115951	12/2001	Norstrem et al.	N/A	N/A
2002/0120185	12/2001	Johnson	N/A	N/A
2002/0143286	12/2001	Tumey	N/A	N/A
2002/0161346	12/2001	Lockwood et al.	N/A	N/A
2004/0030304	12/2003	Hunt et al.	N/A	N/A
2005/0282895	12/2004	Dosch et al.	N/A	N/A
2007/0185426	12/2006	Ambrosio et al.	N/A	N/A
2008/0132819	12/2007	Radl et al.	N/A	N/A
2008/0177253	12/2007	Boehringer	602/47	A61F 13/00021
2008/0275409	12/2007	Kane et al.	N/A	N/A
2008/0300555	12/2007	Olson et al.	N/A	N/A
2009/0012482	12/2008	Pinto et al.	N/A	N/A
2009/0093779	12/2008	Riesinger	604/290	A61F 13/0243
2009/0227969	12/2008	Jaeb et al.	N/A	N/A
2009/0299303	12/2008	Seegert	N/A	N/A
2010/0063484	12/2009	Heagle	N/A	N/A
2010/0160871	12/2009	Seegert	604/290	C12Y 304/22003
2010/0160874	12/2009	Robinson et al.	N/A	N/A
2010/0160876	12/2009	Robinson et al.	N/A	N/A
2010/0185163	12/2009	Heagle	N/A	N/A
2010/0312159	12/2009	Aali et al.	N/A	N/A
2011/0054422	12/2010	Locke et al.	N/A	N/A
2011/0087176	12/2010	Blott et al.	N/A	N/A
2011/0118683	12/2010	Weston	N/A	N/A
2011/0178451	12/2010	Robinson et al.	N/A	N/A
2011/0213287	12/2010	Lattimore et al.	N/A	N/A
2011/0213319	12/2010	Blott et al.	N/A	N/A
2011/0230809	12/2010	Manwaring et al.	N/A	N/A
2011/0282309	12/2010	Adie et al.	N/A	N/A
2011/0301556	12/2010	Lichtenstein	N/A	N/A
2012/0016334	12/2011	Nakajima et al.	N/A	N/A
2012/0143113	12/2011	Robinson	604/319	A61M 1/964
2012/0143114	12/2011	Locke et al.	N/A	N/A
2012/0157945	12/2011	Robinson et al.	N/A	N/A
2013/0144230	12/2012	Wu et al.	N/A	N/A

2013/0165821	12/2012	Freedman	604/20	A61M 1/77
2013/0211349	12/2012	Stokes et al.	N/A	N/A
2013/0274717	12/2012	Dunn	N/A	N/A
2014/0066868	12/2013	Freedman et al.	N/A	N/A
2014/0155791	12/2013	Robinson et al.	N/A	N/A
2014/0163491	12/2013	Schuessler et al.	N/A	N/A
2014/0228787	12/2013	Croizat et al.	N/A	N/A
2014/0236112	12/2013	Von Wolff et al.	N/A	N/A
2015/0080788	12/2014	Blott et al.	N/A	N/A
2015/0119832	12/2014	Locke	N/A	N/A
2015/0174284	12/2014	Payne et al.	N/A	N/A
2015/0190288	12/2014	Dunn	604/319	A61F 13/00068
2015/0201954	12/2014	Pratt et al.	N/A	N/A
2015/0320434	12/2014	Ingram et al.	N/A	N/A
2015/0320602	12/2014	Locke et al.	N/A	N/A
2015/0320603	12/2014	Locke et al.	N/A	N/A
2016/0022885	12/2015	Dunn et al.	N/A	N/A
2016/0038345	12/2015	Ha et al.	N/A	N/A
2016/0095754	12/2015	Andrews et al.	N/A	N/A
2016/0158066	12/2015	Chao	N/A	N/A
2016/0354086	12/2015	Dunn	N/A	A61M 1/915
2017/0007462	12/2016	Hartwell	N/A	A61F 13/00034
2017/0135862	12/2016	Tuck et al.	N/A	N/A
2017/0189237	12/2016	Locke et al.	N/A	N/A
2017/0197006	12/2016	Johnson et al.	N/A	N/A
2017/0231822	12/2016	Hoggarth et al.	N/A	N/A
2017/0239095	12/2016	Hoggarth et al.	N/A	N/A
2018/0235646	12/2017	Locke et al.	N/A	N/A
2018/0353337	12/2017	Locke	N/A	N/A
2018/0353338	12/2017	Locke et al.	N/A	N/A
2018/0353662	12/2017	Locke et al.	N/A	N/A
2019/0117465	12/2018	Osborne et al.	N/A	N/A
2019/0192350	12/2018	Gowans et al.	N/A	N/A
2019/0231944	12/2018	Dunn et al.	N/A	N/A
2019/0274889	12/2018	Steward et al.	N/A	N/A
2019/0314209	12/2018	Ha et al.	N/A	N/A
2020/0046567	12/2019	Carroll et al.	N/A	N/A
2020/0107965	12/2019	Greener	N/A	N/A
2020/0146896	12/2019	Rice et al.	N/A	N/A
2020/0155359	12/2019	Carroll et al.	N/A	N/A
2020/0383837	12/2019	Gowans et al.	N/A	N/A
2021/0077302	12/2020	Carroll et al.	N/A	N/A
2021/0228417	12/2020	Ha et al.	N/A	N/A
2023/0000687	12/2022	Rice et al.	N/A	N/A
2023/0000688	12/2022	Rice et al.	N/A	N/A
2024/0099898	12/2023	Rice et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	---------------------	---------	-----

550575	12/1985	AU	N/A
745271	12/2001	AU	N/A
755496	12/2001	AU	N/A
2005436	12/1989	CA	N/A
26 40 413	12/1977	DE	N/A
43 06 478	12/1993	DE	N/A
29 504 378	12/1994	DE	N/A
102006017194	12/2006	DE	N/A
0100148	12/1983	EP	N/A
0117632	12/1983	EP	N/A
0161865	12/1984	EP	N/A
0358302	12/1989	EP	N/A
1018967	12/1999	EP	N/A
2098257	12/2008	EP	N/A
3263079	12/2017	EP	N/A
3378450	12/2017	EP	N/A
692578	12/1952	GB	N/A
2195255	12/1987	GB	N/A
2 197 789	12/1987	GB	N/A
2 220 357	12/1989	GB	N/A
2 235 877	12/1990	GB	N/A
2 329 127	12/1998	GB	N/A
2 333 965	12/1998	GB	N/A
2365350	12/2001	GB	N/A
2377939	12/2002	GB	N/A
S57-013040	12/1981	JP	N/A
4129536	12/2007	JP	N/A
90/010424	12/1989	NO	N/A
71559	12/2001	SG	N/A
80/02182	12/1979	WO	N/A
87/04626	12/1986	WO	N/A
93/009727	12/1992	WO	N/A
94/20041	12/1993	WO	N/A
96/05873	12/1995	WO	N/A
97/18007	12/1996	WO	N/A
99/13793	12/1998	WO	N/A
0185248	12/2000	WO	N/A
2005102234	12/2004	WO	N/A
2006114638	12/2005	WO	N/A
2008005532	12/2007	WO	N/A
2008136998	12/2007	WO	N/A
2009021523	12/2008	WO	N/A
2009/146441	12/2008	WO	N/A
2010051071	12/2009	WO	N/A
2010051073	12/2009	WO	N/A
2010075178	12/2009	WO	N/A
2011008497	12/2010	WO	N/A
2011089098	12/2010	WO	N/A
2013032745	12/2012	WO	N/A
2013066426	12/2012	WO	N/A

2013071243	12/2012	WO	N/A
2013116552	12/2012	WO	N/A
2013129343	12/2012	WO	N/A
2013149078	12/2012	WO	N/A
2014/014922	12/2013	WO	N/A
2014014871	12/2013	WO	N/A
2014024048	12/2013	WO	N/A
2014143487	12/2013	WO	N/A
2015172104	12/2014	WO	N/A
2015172111	12/2014	WO	N/A
2015173547	12/2014	WO	N/A
2017195038	12/2016	WO	N/A
2018/077872	12/2017	WO	N/A
2018/094061	12/2017	WO	N/A
2018/226328	12/2017	WO	N/A
2019136164	12/2018	WO	N/A
2019152422	12/2018	WO	N/A
2020097529	12/2019	WO	N/A

OTHER PUBLICATIONS

Louis C. Argenta, MD and Michael J. Morykwas, PHD; Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Clinical Experience; Annals of Plastic Surgery; vol. 38, No. 6, Jun. 1997; pp. 563-576. cited by applicant

Susan Mendez-Eatmen, RN; "When wounds Won't Heal" RN Jan. 1998, vol. 61 (1); Medical Economics Company, Inc., Montvale, NJ, USA; pp. 20-24. cited by applicant

James H. Blackburn II, MD et al.: Negative-Pressure Dressings as a Bolster for Skin Grafts; Annals of Plastic Surgery, vol. 40, No. 5, May 1998, pp. 453-457; Lippincott Williams & Wilkins, Inc., Philadelphia, PA, USA. cited by applicant

John Masters; "Reliable, Inexpensive and Simple Suction Dressings"; Letter to the Editor, British Journal of Plastic Surgery, 1998, vol. 51 (3), p. 267; Elsevier Science/The British Association of Plastic Surgeons, UK. cited by applicant

S.E. Greer, et al. "The Use of Subatmospheric Pressure Dressing Therapy to Close Lymphocutaneous Fistulas of the Groin" British Journal of Plastic Surgery (2000), 53, pp. 484-487. cited by applicant

George V. Letsou, MD., et al; "Stimulation of Adenylate Cyclase Activity in Cultured Endothelial Cells Subjected to Cyclic Stretch"; Journal of Cardiovascular Surgery, 31, 1990, pp. 634-639. cited by applicant

Orringer, Jay, et al; "Management of Wounds in Patients with Complex Enterocutaneous Fistulas"; Surgery, Gynecology & Obstetrics, Jul. 1987, vol. 165, pp. 79-80. cited by applicant

International Search Report for PCT International Application PCT/GB95/01983; Nov. 23, 1995. cited by applicant

PCT International Search Report for PCT International Application PCT/GB98/02713; Jan. 8, 1999. cited by applicant

PCT Written Opinion; PCT International Application PCT/GB98/02713; Jun. 8, 1999. cited by applicant

PCT International Examination and Search Report, PCT International Application PCT/GB96/02802; Jan. 15, 1998 & Apr. 29, 1997. cited by applicant

PCT Written Opinion, PCT International Application PCT/GB96/02802; Sep. 3, 1997. cited by applicant

Dattilo, Philip P., Jr., et al; "Medical Textiles: Application of an Absorbable Barbed Bi-directional

Surgical Suture”; Journal of Textile and Apparel, Technology and Management, vol. 2, Issue 2, Spring 2002, pp. 1-5. cited by applicant

Kostyuchenok, B.M., et al; “Vacuum Treatment in the Surgical Management of Purulent Wounds”; Vestnik Khirurgi, Sep. 1986, pp. 18-21 and 6 page English translation thereof. cited by applicant

Davydov, Yu. A., et al; “Vacuum Therapy in the Treatment of Purulent Lactation Mastitis”; Vestnik Khirurgi, May 14, 1986, pp. 66-70, and 9 page English translation thereof. cited by applicant

Yusupov, Yu.N., et al; “Active Wound Drainage”, Vestnik Khirurgi, vol. 138, Issue 4, 1987, and 7 page English translation thereof. cited by applicant

Davydov, Yu.A., et al; “Bacteriological and Cytological Assessment of Vacuum Therapy for Purulent Wounds”; Vestnik Khirurgi, Oct. 1988, pp. 48-52, and 8 page English translation thereof. cited by applicant

Davydov, Yu.A., et al; “Concepts for the Clinical-Biological Management of the Wound Process in the Treatment of Purulent Wounds by Means of Vacuum Therapy”; Vestnik Khirurgi, Jul. 7, 1980, pp. 132-136, and 8 page English translation thereof. cited by applicant

Chariker, Mark E., M.D., et al; “Effective Management of incisional and cutaneous fistulae with closed suction wound drainage”; Contemporary Surgery, vol. 34, Jun. 1989, pp. 59-63. cited by applicant

Egnell Minor, Instruction Book, First Edition, 300 7502, Feb. 1975, pp. 24. cited by applicant

Egnell Minor: Addition to the Users Manual Concerning Overflow Protection—Concerns all Egnell Pumps, Feb. 3, 1983, pp. 2. cited by applicant

Svedman, P.: “Irrigation Treatment of Leg Ulcers”, The Lancet, Sep. 3, 1983, pp. 532-534. cited by applicant

Chinn, Steven D. et al.: “Closed Wound Suction Drainage”, The Journal of Foot Surgery, vol. 24, No. 1, 1985, pp. 76-81. cited by applicant

Arnljots, Björn et al.: “Irrigation Treatment in Split-Thickness Skin Grafting of Intractable Leg Ulcers”, Scand J. Plast Reconstr. Surg., No. 19, 1985, pp. 211-213. cited by applicant

Svedman, P.: “A Dressing Allowing Continuous Treatment of a Biosurface”, IRCS Medical Science: Biomedical Technology, Clinical Medicine, Surgery and Transplantation, vol. 7, 1979, p. 221. cited by applicant

Svedman, P. et al: “A Dressing System Providing Fluid Supply and Suction Drainage Used for Continuous or Intermittent Irrigation”, Annals of Plastic Surgery, vol. 17, No. 2, Aug. 1986, pp. 125-133. cited by applicant

N.A. Bagautdinov, “Variant of External Vacuum Aspiration in the Treatment of Purulent Diseases of Soft Tissues,” Current Problems in Modern Clinical Surgery: Interdepartmental Collection, edited by V. Ye Volkov et al. (Chuvashia State University, Cheboksary, U.S.S.R. 1986); pp. 94-96 (copy and certified translation). cited by applicant

K.F. Jeter, T.E. Tintle, and M. Chariker, “Managing Draining Wounds and Fistulae: New and Established Methods,” Chronic Wound Care, edited by D. Krasner (Health Management Publications, Inc., King of Prussia, PA 1990), pp. 240-246. cited by applicant

G. Živadinovi?, V. ?uki?, Ž. Maksimovi?, ?. Radak, and P. Peška, “Vacuum Therapy in the Treatment of Peripheral Blood Vessels,” Timok Medical Journal 11 (1986), pp. 161-164 (copy and certified translation). cited by applicant

F.E. Johnson, “An Improved Technique for Skin Graft Placement Using a Suction Drain,” Surgery, Gynecology, and Obstetrics 159 (1984), pp. 584-585. cited by applicant

A.A. Safronov, Dissertation Abstract, Vacuum Therapy of Trophic Ulcers of the Lower Leg with Simultaneous Autoplasty of the Skin (Central Scientific Research Institute of Traumatology and Orthopedics, Moscow, U.S.S.R. 1967) (copy and certified translation). cited by applicant

M. Schein, R. Saadia, J.R. Jamieson, and G.A.G. Decker, “The ‘Sandwich Technique’ in the Management of the Open Abdomen,” British Journal of Surgery 73 (1986), pp. 369-370. cited by applicant

D.E. Tribble, An Improved Sump Drain-Irrigation Device of Simple Construction, Archives of Surgery 105 (1972) pp. 511-513. cited by applicant

M.J. Morykwas, L.C. Argenta, E.I. Shelton-Brown, and W. McGuirt, "Vacuum-Assisted Closure: A New Method for Wound Control and Treatment: Animal Studies and Basic Foundation," Annals of Plastic Surgery 38 (1997), pp. 553-562 (Morykwas I). cited by applicant

C.E. Tennants, The Use of Hypermia in the Postoperative Treatment of Lesions of the Extremities and Thorax, Journal of the American Medical Association 64 (1915), pp. 1548-1549. cited by applicant

Selections from W. Meyer and V. Schmieden, Bier's Hyperemic Treatment in Surgery, Medicine, and the Specialties: A Manual of Its Practical Application, (W.B. Saunders Co., Philadelphia, PA 1909), pp. 17-25, 44-64, 90-96, 167-170, and 210-211. cited by applicant

V.A. Solovev et al., Guidelines, The Method of Treatment of Immature External Fistulas in the Upper Gastrointestinal Tract, editor-in-chief Prov. V.I. Parahonyak (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1987) ("Solovev Guidelines"). cited by applicant

V.A. Kuznetsov & N.a. Bagautdinov, "Vacuum and Vacuum-Sorption Treatment of Open Septic Wounds," in II All-Union Conference on Wounds and Wound Infections: Presentation Abstracts, edited by B.M. Kostyuchenok et al. (Moscow, U.S.S.R. Oct. 28-29, 1986) pp. 91-92 ("Bagautdinov II"). cited by applicant

V.A. Solovev, Dissertation Abstract, Treatment and Prevention of Suture Failures after Gastric Resection (S.M. Kirov Gorky State Medical Institute, Gorky, U.S.S.R. 1988) ("Solovev Abstract"). cited by applicant

V.A.C. ® Therapy Clinical Guidelines: A Reference Source for Clinicians; Jul. 2007. cited by applicant

International Search Report and Written Opinion for PCT/US2015/030027 mailed Jul. 15, 2015. cited by applicant

Partial International Search Report from PCT/US2015/030030 mailed Jul. 22, 2015. cited by applicant

International Search Report and Written Opinion for PCT/US2015/030023 mailed Aug. 24, 2015. cited by applicant

Extended European Search Report for corresponding Application No. 171862527, mailed Nov. 14, 2017. cited by applicant

"Introduction to Polyurethanes: Thermoplastic Polyurethane", American Chemistry Council, <https://polyurethane.americanchemistry.com/polyurethanes/Introduction-to-Polyurethanes/Applications/Thermoplastic-Polyurethane/>. cited by applicant

International Search Report and Written Opinion for corresponding Application No. PCT/US2019/027463, mailed Jul. 4, 2019. cited by applicant

Japanese Notice of Rejection for corresponding Application No. 2016-566815, mailed Feb. 5, 2019. cited by applicant

Extended European Search Report for corresponding Application No. 18162504.7, mailed May 24, 2018. cited by applicant

Japanese Notice of Rejection for corresponding Application No. 2016-566785, mailed Jun. 25, 2019. cited by applicant

Japanese Notice of Rejection for corresponding Application No. 2016-566785, mailed Jan. 29, 2019. cited by applicant

Non-Final Office Action for Corresponding U.S. Appl. No. 15/960,310, mailed Apr. 29, 2020. cited by applicant

Japanese Notice of Rejection for Corresponding Application No. 2019-233695, mailed Oct. 13, 2020. cited by applicant

International Search Report and Written Opinion for Corresponding Application No. PCT/US2019/060567, mailed Feb. 14, 2020. cited by applicant

International Search Report and Written Opinion for Corresponding Application No. PCT/US2019/045505, mailed Nov. 7, 2019. cited by applicant
International Search Report and Written Opinion for Corresponding Application No. PCT/US2019/060479, mailed Apr. 7, 2020. cited by applicant
International Search Report and Written Opinion for Corresponding Application No. PCT/US2020/013922, mailed May 4, 2020. cited by applicant
Chinese Notice of Rejection Corresponding to Application No. 2020800099951, mailed Mar. 28, 2022. cited by applicant
International Search Report and Written Opinion for Corresponding Application No. PCT/IB2020/056911, mailed Oct. 21, 2020. cited by applicant
International Search Report and Written Opinion Corresponding to Application No. PCT/IB2020/061435, mailed Mar. 16, 2021. cited by applicant
International Search Report and Written Opinion Corresponding to Application No. PCT/IB2020/061465, mailed Mar. 16, 2021. cited by applicant
International Search Report and Written Opinion Corresponding to Application No. PCT/IB2020/061540, mailed Feb. 24, 2021. cited by applicant
Canadian Examination Report for related application 2,947,302, dated Jun. 11, 2021. cited by applicant
Japanese Notice of Rejection for related application 2020-557257, dated Feb. 28, 2023. cited by applicant
Office Action for related U.S. Appl. No. 16/678,450, dated Jul. 31, 2023. cited by applicant
Office action for related U.S. Appl. No. 16/918,682, dated Sep. 21, 2023. cited by applicant
Japanese Notice of Rejection for Application No. 2021-542412, dated Dec. 5, 2023. cited by applicant
European Examination Report for Application No. 20747133.5, dated Dec. 21, 2023. cited by applicant
Japanese Notice of Rejection for Application No. 2019-233695 dated Mar. 5, 2024. cited by applicant
Office action for related U.S. Appl. No. 17/629,174, dated Mar. 26, 2024. cited by applicant
Office action for U.S. Appl. No. 16/678,450, dated Sep. 9, 2024. cited by applicant
Japanese Notice of Rejection for Application No. 2021-524440 dated Apr. 16, 2024. cited by applicant
Office action for U.S. Appl. No. 16/745,075, dated Jul. 24, 2024. cited by applicant
Japanese Decision of Rejection and Decision for Dismissal of Amendment for Application No. 2021-524440, dated Oct. 15, 2024. cited by applicant
Office action for U.S. Appl. No. 16/918,682, dated Jan. 2, 2025. cited by applicant
Copper Development Association Inc., Introduction to Antimicrobial Copper, Feb. 15, 2024. cited by applicant
Office action for U.S. Appl. No. 17/629,174, dated Feb. 26, 2025. cited by applicant
Office action for U.S. Appl. No. 17/779,755, dated Apr. 9, 2025. cited by applicant
Office action for U.S. Appl. No. 17/779,792, dated Jun. 3, 2025. cited by applicant

Primary Examiner: Byrd; Brigid K

Background/Summary

RELATED APPLICATIONS (1) This application is a divisional of U.S. patent application Ser. No. 15/884,149, filed Jan. 30, 2018, which is a divisional of U.S. patent application Ser. No.

14/708,109, filed May 8, 2015, now U.S. Pat. No. 9,918,733, which claims the benefit, under 35 USC § 119(e), of the filing of U.S. Provisional Patent Application Ser. No. 61/991,150, entitled “Subcutaneous Anchor for Surgical Closure,” by Locke et al., filed May 9, 2014; U.S. Provisional Patent Application Ser. No. 61/991,174, entitled “Dressing with Contracting Layer for Linear Tissue Sites,” by Locke et al., filed May 9, 2014; and U.S. Provisional Patent Application Ser. No. 61/991,134, entitled “Debriding Dressing for use with Negative Pressure and Fluid Instillation,” by Locke et al., filed May 9, 2014, all of which are incorporated herein by reference for all purposes.

TECHNICAL FIELD

(1) The invention set forth in the appended claims relates generally to tissue treatment systems and more particularly, but without limitation, to a dressing for disrupting non-viable tissue at a tissue site.

BACKGROUND

(2) Clinical studies and practice have shown that reducing pressure in proximity to a tissue site can augment and accelerate growth of new tissue at the tissue site. The applications of this phenomenon are numerous, but it has proven particularly advantageous for treating wounds. Regardless of the etiology of a wound, whether trauma, surgery, or another cause, proper care of the wound is important to the outcome. Treatment of wounds or other tissue with reduced pressure may be commonly referred to as “negative-pressure therapy,” but is also known by other names, including “negative-pressure wound therapy,” “reduced-pressure therapy,” “vacuum therapy,” and “vacuum-assisted closure,” for example. Negative-pressure therapy may provide a number of benefits, including migration of epithelial and subcutaneous tissues, improved blood flow, and micro-deformation of tissue at a wound site. Together, these benefits can increase development of granulation tissue and reduce healing times.

(3) While the clinical benefits of negative-pressure therapy are widely known, the cost and complexity of negative-pressure therapy can be a limiting factor in its application, and the development and operation of negative-pressure systems, components, and processes continue to present significant challenges to manufacturers, healthcare providers, and patients.

(4) Often debris located in or on a tissue site may hinder the application of beneficial therapy, increasing healing times and the risk of further tissue damage. Debris can include necrotic tissue, foreign bodies, biofilms, slough, eschar, and other debris that can negatively impact tissue healing. Removal of the tissue debris can be accomplished through debridement processes; however, debridement processes can be painful to a patient and may result in further damage to the tissue site. Debriding a tissue site can also be a time-consuming process that may significantly delay the application of other beneficial therapies, such as negative-pressure therapy or instillation therapy. The development of systems, components, and processes to aid in the removal of debris to decrease healing times and increase positive patient outcomes continue to present significant challenges to manufacturers, healthcare providers, and patients.

SUMMARY

(5) New and useful systems, apparatuses, and methods for disrupting non-viable tissue at a tissue site in a negative-pressure therapy and instillation environment are set forth in the appended claims. Illustrative embodiments are also provided to enable a person skilled in the art to make and use the claimed subject matter. For example, a method for disrupting material at a tissue site is described. A contact layer may be selected for use on the tissue site and positioned adjacent to the tissue site. The contact layer may include walls defining a plurality of through-holes. A sealing member may be positioned over the contact layer and sealed to tissue surrounding the tissue site to form a sealed space enclosing the contact layer. A negative-pressure source may be fluidly coupled to the sealed space. The negative-pressure source may supply negative pressure to the sealed space and the contact layer to draw tissue into the through-holes to form nodules. The negative pressure may be vented from the sealed space to release the nodules.

(6) Alternatively, another example embodiment includes a system for softening materials at a tissue site. The system may include a contact layer formed from a compressible material and configured to be positioned adjacent the tissue site. The contact layer may include a plurality of through-holes. The system may also include a cover adapted to form a sealed space over the contact layer and the tissue site for receiving a negative pressure from a negative-pressure source. The through-holes may be configured to receive tissue in the through-holes in response to negative pressure in the sealed space to form nodules in the tissue site.

(7) Other embodiments also include an apparatus for disrupting debris in a tissue site. The apparatus may include a contact layer formed from a felted foam and having a plurality of through-holes separated from each other by walls. The through-holes may be configured to form nodules in the tissue site in response to negative pressure.

(8) A method for selecting a tissue interface for tissue disruption is also described. A status of debris in the tissue site can be determined along with other parameters influencing treatment of the tissue site. In response to determining a status of debris and other parameters influencing treatment, desired targets of treatment can be determined. In response to the desired targets of treatment, a contact layer can be selected.

(9) A system for debriding a tissue site is also described. The system can include a manifold adapted to deliver negative pressure to the tissue site. The system can also include a cover adapted to form a sealed space over the manifold and the tissue site for receiving a negative pressure from a negative-pressure source. The system can further include a debridement tool adapted to be positioned between the manifold and the tissue site. The debridement tool can have a tissue-facing surface and an opposite surface including a plurality of holes extending therebetween. The holes can be separated from each other by walls, and the walls can have transverse surfaces extending between the tissue-facing surface and the opposite surface that form cutting edges with the tissue-facing surface. The holes can have a perforation shape factor that allows the holes to collapse from a relaxed position to a contracted position in response to an application and removal of negative pressure from the sealed space. The cutting edges can be adapted to debride the tissue site in response to movement of the debridement tool between the relaxed position and the contracted position.

(10) Objectives, advantages, and a preferred mode of making and using the claimed subject matter may be understood best by reference to the accompanying drawings in conjunction with the following detailed description of illustrative embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The patent or application file contains at least one drawing executed in color. Copies of this patent or patent application publication with color drawing(s) will be provided by the Office upon request and payment of the necessary fee.

(2) FIG. 1 is a sectional section view with a portion shown in elevation, illustrating details that may be associated with some embodiments of a therapy system;

(3) FIG. 1A is a detail view of a portion of the therapy system of FIG. 1;

(4) FIG. 2 is a plan view, illustrating details that may be associated with some embodiments of a contact layer of the therapy system of FIG. 1 in a first position;

(5) FIG. 3 is a schematic view, illustrating details that may be associated with some embodiments of a through-hole of the contact layer of FIG. 2;

(6) FIG. 4 is a plan view, illustrating details that may be associated with some embodiments of the through-holes of the contact layer of FIG. 2;

(7) FIG. 5 is a plan view, illustrating details that may be associated with some embodiments of the

contact layer of FIG. 2 in a second position;

(8) FIG. 6 is a sectional view, illustrating details that may be associated with some embodiments of the contact layer of FIG. 2 at ambient pressure;

(9) FIG. 7 is a sectional view, illustrating details that may be associated with some embodiments of the contact layer of FIG. 2 during negative-pressure therapy;

(10) FIG. 8 is a sectional detail view of FIG. 7, illustrating details that may be associated with some embodiments of the contact layer of FIG. 2 during negative-pressure therapy;

(11) FIG. 9 is a plan view, illustrating details that may be associated with treatment using the contact layer of FIG. 2;

(12) FIG. 10 is a color photograph, illustrating details that may be associated with an experimental embodiment of the contact layer;

(13) FIG. 11 is a color photograph, illustrating disruption of debris associated with use of the contact layer of FIG. 2;

(14) FIG. 12 is a color photograph, illustrating additional details associated with disruption of debris caused by use of the contact layer of FIG. 2;

(15) FIG. 13 is a plan view, illustrating details that may be associated with some embodiments of another contact layer of the therapy system of FIG. 1;

(16) FIG. 14 is a plan view, illustrating details that may be associated with some embodiments of another contact layer of the therapy system of FIG. 1;

(17) FIG. 15 is a plan view, illustrating details that may be associated with some embodiments of another contact layer of the therapy system of FIG. 1;

(18) FIG. 16 is a flow chart 1600 illustrating exemplary operations that can be associated with some embodiments of the therapy system 100 of FIG. 1; and

(19) FIG. 17 is a flow chart 1700 illustrating exemplary operations that can be associated with some embodiments of the therapy system 100 of FIG. 1.

DESCRIPTION OF EXAMPLE EMBODIMENTS

(20) The following description of example embodiments provides information that enables a person skilled in the art to make and use the subject matter set forth in the appended claims, but may omit certain details already well-known in the art. The following detailed description is, therefore, to be taken as illustrative and not limiting.

(21) The example embodiments may also be described herein with reference to spatial relationships between various elements or to the spatial orientation of various elements depicted in the attached drawings. In general, such relationships or orientation assume a frame of reference consistent with or relative to a patient in a position to receive treatment. However, as should be recognized by those skilled in the art, this frame of reference is merely a descriptive expedient rather than a strict prescription.

(22) FIG. 1 is a sectional view, with a portion shown in elevation, of an example embodiment of a therapy system 100 that can provide negative pressure therapy, instillation of topical treatment solutions, and disruption of debris on tissue in accordance with this specification. The therapy system 100 may include a dressing and a negative-pressure source. For example, a dressing 102 may be fluidly coupled to a negative-pressure source 104, as illustrated in FIG. 1. FIG. 1A is a detail view of a portion of the therapy system 100 of FIG. 1. As shown in FIG. 1 and FIG. 1A, the dressing 102, for example, includes a cover, such as a drape 106, and a tissue interface 107 for positioning adjacent to or proximate to a tissue site such as, for example, a tissue site 103. In some embodiments, the tissue interface 107 may be a cover layer, such as a retainer layer 108. The tissue interface 107 can also be a contact layer 110 having a tissue-facing surface 111 adapted to face the tissue site 103 and an opposite surface 113 adapted to face, for example, the retainer layer 108. In some embodiments, the tissue interface 107 can be both the retainer layer 108 and the contact layer 110, and the retainer layer 108 and the contact layer 110 may be integral components. In other embodiments, the tissue interface 107 can include the retainer layer 108 and the contact layer 110,

and the retainer layer and the contact layer **110** may be separate components as shown in FIG. **1**. The therapy system **100** may also include an exudate container, such as a container **112**, coupled to the dressing **102** and to the negative-pressure source **104**. In some embodiments, the container **112** may be fluidly coupled to the dressing **102** by a connector **114** and a tube **116**, and the container **112** may be fluidly coupled to the negative-pressure source **104** by a tube **118**.

(23) In some embodiments, the therapy system **100** may also include an instillation solution source. For example, a fluid source **120** may be fluidly coupled to the dressing **102** by a tube **122** and a connector **124**, as illustrated in the example embodiment of FIG. **1**.

(24) In general, components of the therapy system **100** may be coupled directly or indirectly. For example, the negative-pressure source **104** may be directly coupled to the container **112** and indirectly coupled to the dressing **102** through the container **112**. Components may be fluidly coupled to each other to provide a path for transferring fluids (i.e., liquid and/or gas) between the components.

(25) In some embodiments, components may be fluidly coupled through a tube, such as the tube **116**, the tube **118**, and the tube **122**. A “tube,” as used herein, broadly refers to a tube, pipe, hose, conduit, or other structure with one or more lumina adapted to convey a fluid between two ends. Typically, a tube is an elongated, cylindrical structure with some flexibility, but the geometry and rigidity may vary. Components may also be fluidly coupled without the use of a tube, for example, by having surfaces in contact with or proximate to each other. In some embodiments, components may additionally or alternatively be coupled by virtue of physical proximity, being integral to a single structure, or being formed from the same piece of material. In some embodiments, components may be coupled by being positioned adjacent to each other or by being operable with each other. Coupling may also include mechanical, thermal, electrical, or chemical coupling (such as a chemical bond) in some contexts.

(26) In operation, the tissue interface **107** may be placed within, over, on, or otherwise proximate to the tissue site **103**. The drape **106** may be placed over the tissue interface **107** and sealed to tissue near the tissue site. For example, the drape **106** may be sealed to undamaged epidermis peripheral to a tissue site, also known as peritissue. Thus, the dressing **102** can provide a sealed therapeutic environment **128** proximate to a tissue site, substantially isolated from the external environment, and the negative-pressure source **104** can reduce the pressure in the sealed therapeutic environment **128**. Negative pressure applied across the tissue site **103** through the tissue interface **107** in the sealed therapeutic environment **128** can induce macrostrain and microstrain in the tissue site **103**, as well as remove exudates and other fluids from the tissue site **103**, which can be collected in container **112** and disposed of properly.

(27) The fluid mechanics of using a negative-pressure source to reduce pressure in another component or location, such as within a sealed therapeutic environment, can be mathematically complex. However, the basic principles of fluid mechanics applicable to negative-pressure therapy and instillation are generally well-known to those skilled in the art.

(28) In general, fluids flow toward lower pressure along a fluid path. Thus, the term “downstream” typically refers to a position in a fluid path that is closer to a source of negative pressure or alternatively further away from a source of positive pressure. Conversely, the term “upstream” refers to a position in a fluid path further away from a source of negative pressure or closer to a source of positive pressure. Similarly, it may be convenient to describe certain features in terms of fluid “inlet” or “outlet” in such a frame of reference, and the process of reducing pressure may be described illustratively herein as “delivering,” “distributing,” or “generating” reduced pressure, for example. This orientation is generally presumed for purposes of describing various features and components of systems herein.

(29) The term “tissue site,” such as the tissue site **103**, in this context broadly refers to a wound or defect located on or within tissue, including but not limited to, bone tissue, adipose tissue, muscle tissue, neural tissue, dermal tissue, vascular tissue, connective tissue, cartilage, tendons, or

ligaments. A wound may include chronic, acute, traumatic, subacute, and dehiscent wounds, partial-thickness burns, ulcers (such as diabetic, pressure, or venous insufficiency ulcers), flaps, and grafts, for example. The term “tissue site” may also refer to areas of tissue that are not necessarily wounded or defective, but are instead areas in which it may be desirable to add or promote the growth of additional tissue. For example, negative pressure may be used in certain tissue areas to grow additional tissue that may be harvested and transplanted to another tissue location. As shown in FIG. 1, the tissue site **103** may extend through an epidermis **105**, a dermis **109**, and into subcutaneous tissue **115**.

(30) “Negative pressure” generally refers to a pressure less than a local ambient pressure, such as the ambient pressure in a local environment external to the sealed therapeutic environment **128** provided by the dressing **102**. In many cases, the local ambient pressure may also be the atmospheric pressure at which a tissue site is located. Alternatively, the pressure may be less than a hydrostatic pressure associated with tissue at the tissue site. Unless otherwise indicated, values of pressure stated herein are gauge pressures. Similarly, references to increases in negative pressure typically refer to a decrease in absolute pressure, while decreases in negative pressure typically refer to an increase in absolute pressure.

(31) A negative-pressure source, such as the negative-pressure source **104**, may be a reservoir of air at a negative pressure, or may be a manual or electrically-powered device that can reduce the pressure in a sealed volume, such as a vacuum pump, a suction pump, a wall suction port available at many healthcare facilities, or a micro-pump, for example. A negative-pressure source can also include a tablet, solution, spray, or other delivery mechanism that can initiate a chemical reaction to generate negative pressure. A negative-pressure source can also include a pressurized gas cylinder, such as a CO₂ cylinder used to drive a pump to produce negative pressure. A negative-pressure source may be housed within or used in conjunction with other components, such as sensors, processing units, alarm indicators, memory, databases, software, display devices, or user interfaces that further facilitate negative-pressure therapy. While the amount and nature of negative pressure applied to a tissue site may vary according to therapeutic requirements, the pressure is generally a low vacuum, also commonly referred to as a rough vacuum, between -5 mmHg (-667 Pa) and -500 mmHg (-66.7 kPa). Common therapeutic ranges are between -25 mmHg (-3.3 kPa) and about -350 mmHg (-46.6 kPa) and more commonly between -75 mmHg (-9.9 kPa) and -300 mmHg (-39.9 kPa).

(32) A “connector,” such as the connector **114** and the connector **124**, may be used to fluidly couple a tube to the sealed therapeutic environment **128**. The negative pressure developed by a negative-pressure source may be delivered through a tube to a connector. In one illustrative embodiment, a connector may be a T.R.A.C.® Pad or Sensa T.R.A.C.® Pad available from KCI of San Antonio, Texas. In one exemplary embodiment, the connector **114** may allow the negative pressure generated by the negative-pressure source **104** to be delivered to the sealed therapeutic environment **128**. In other exemplary embodiments, a connector may also be a tube inserted through a drape. In one exemplary embodiment, the connector **124** may allow fluid provided by the fluid source **120** to be delivered to the sealed therapeutic environment **128**. In one illustrative embodiment, the connector **114** and the connector **124** may be combined in a single device, such as a Vera T.R.A.C.® Pad available from KCI of San Antonio, Texas. In some embodiments, the connector **114** and the connector **124** may include one or more filters to trap particles entering and leaving the sealed therapeutic environment **128**.

(33) The tissue interface **107** can be generally adapted to contact a tissue site. The tissue interface **107** may be partially or fully in contact with the tissue site. If the tissue site is a wound, for example, the tissue interface **107** may partially or completely fill the wound, or may be placed over the wound. The tissue interface **107** may take many forms, and may have many sizes, shapes, or thicknesses depending on a variety of factors, such as the type of treatment being implemented or the nature and size of a tissue site. For example, the size and shape of the tissue interface **107** may

be adapted to the contours of deep and irregular shaped tissue sites. In some embodiments, the tissue interface **107** may be provided in a spiral cut sheet. Moreover, any or all of the surfaces of the tissue interface **107** may have an uneven, coarse, or jagged profile that can induce microstrains and stresses at a tissue site.

(34) In some embodiments, the tissue interface **107** may include the retainer layer **108**, the contact layer **110**, or both and may also be a manifold. A “manifold” in this context generally includes any substance or structure providing a plurality of pathways adapted to collect or distribute fluid across a tissue site under negative pressure. For example, a manifold may be adapted to receive negative pressure from a source and distribute the negative pressure through multiple apertures across a tissue site, which may have the effect of collecting fluid from across a tissue site and drawing the fluid toward the source. In some embodiments, the fluid path may be reversed or a secondary fluid path may be provided to facilitate delivering fluid across a tissue site.

(35) In some illustrative embodiments, the pathways of a manifold may be channels interconnected to improve distribution or collection of fluids across a tissue site. For example, cellular foam, open-cell foam, reticulated foam, porous tissue collections, and other porous material such as gauze or felted material generally include pores, edges, and/or walls adapted to form interconnected fluid pathways. Liquids, gels, and other foams may also include or be cured to include apertures and flow channels. In some illustrative embodiments, a manifold may be a porous foam material having interconnected cells or pores adapted to uniformly (or quasi-uniformly) distribute negative pressure to a tissue site. The foam material may be either hydrophobic or hydrophilic. The pore size of a foam material may vary according to needs of a prescribed therapy. For example, in some embodiments, the retainer layer **108** may be a foam having pore sizes in a range of about 60 microns to about 2000 microns. In other embodiments, the retainer layer **108** may be a foam having pore sizes in a range of about 400 microns to about 600 microns. The tensile strength of the retainer layer **108** may also vary according to needs of a prescribed therapy. For example, the tensile strength of a foam may be increased for instillation of topical treatment solutions. In one non-limiting example, the retainer layer **108** may be an open-cell, reticulated polyurethane foam such as GranuFoam® dressing available from Kinetic Concepts, Inc. of San Antonio, Texas; in other embodiments the retainer layer **108** may be an open-cell, reticulated polyurethane foam such as a V.A.C. VeraFlo® foam, also available from Kinetic Concepts, Inc., of San Antonio, Texas. In other embodiments, the retainer layer **108** may be formed of an un-reticulated open-cell foam.

(36) In an example in which the tissue interface **107** may be made from a hydrophilic material, the tissue interface **107** may also wick fluid away from a tissue site, while continuing to distribute negative pressure to the tissue site. The wicking properties of the tissue interface **107** may draw fluid away from a tissue site by capillary flow or other wicking mechanisms. An example of a hydrophilic foam is a polyvinyl alcohol, open-cell foam such as V.A.C. WhiteFoam® dressing available from Kinetic Concepts, Inc. of San Antonio, Texas. Other hydrophilic foams may include those made from polyether. Other foams that may exhibit hydrophilic characteristics include hydrophobic foams that have been treated or coated to provide hydrophilicity.

(37) In some embodiments, the tissue interface **107** may be constructed from bioresorbable materials. Suitable bioresorbable materials may include, without limitation, a polymeric blend of polylactic acid (PLA) and polyglycolic acid (PGA). The polymeric blend may also include without limitation polycarbonates, polyfumarates, and caprolactones. The tissue interface **107** may further serve as a scaffold for new cell-growth, or a scaffold material may be used in conjunction with the tissue interface **107** to promote cell-growth. A scaffold is generally a substance or structure used to enhance or promote the growth of cells or formation of tissue, such as a three-dimensional porous structure that provides a template for cell growth. Illustrative examples of scaffold materials include calcium phosphate, collagen, PLA/PGA, coral hydroxy apatites, carbonates, or processed allograft materials.

(38) In some embodiments, the drape **106** may provide a bacterial barrier and protection from

physical trauma. The drape **106** may also be sealing member constructed from a material that can reduce evaporative losses and provide a fluid seal between two components or two environments, such as between a therapeutic environment and a local external environment. The drape **106** may be, for example, an elastomeric film or membrane that can provide a seal adequate to maintain a negative pressure at a tissue site for a given negative-pressure source. In some example embodiments, the drape **106** may be a polymer drape, such as a polyurethane film, that is permeable to water vapor but impermeable to liquid. Such drapes typically have a thickness in the range of about 25 microns to about 50 microns. For permeable materials, the permeability generally should be low enough that a desired negative pressure may be maintained.

(39) An attachment device may be used to attach the drape **106** to an attachment surface, such as undamaged epidermis, a gasket, or another cover. The attachment device may take many forms. For example, an attachment device may be a medically-acceptable, pressure-sensitive adhesive that extends about a periphery, a portion, or an entire sealing member. In some embodiments, for example, some or all of the drape **106** may be coated with an acrylic adhesive having a coating weight between about 25 grams per square meter (gsm) to about 65 gsm. Thicker adhesives, or combinations of adhesives, may be applied in some embodiments to improve the seal and reduce leaks. Other example embodiments of an attachment device may include a double-sided tape, paste, hydrocolloid, hydrogel, silicone gel, or organogel.

(40) The container **112** is representative of a container, canister, pouch, or other storage component that can be used to manage exudates and other fluids withdrawn from a tissue site. In many environments, a rigid container may be preferred or required for collecting, storing, and disposing of fluids. In other environments, fluids may be properly disposed of without rigid container storage, and a re-usable container could reduce waste and costs associated with negative-pressure therapy.

(41) The fluid source **120** may be representative of a container, canister, pouch, bag, or other storage component that can provide a solution for instillation therapy. Compositions of solutions may vary according to prescribed therapy, but examples of solutions that are suitable for some prescriptions include hypochlorite-based solutions, silver nitrate (0.5%), sulfur-based solutions, biguanides, cationic solutions, and isotonic solutions. In some embodiments, a fluid source, such as the fluid source **120**, may be a reservoir of fluid at an atmospheric or greater pressure, or may be a manual or electrically-powered device, such as a pump, that can convey fluid to a sealed volume, such as the sealed therapeutic environment **128**, for example. In some embodiments, a fluid source may include a peristaltic pump.

(42) During treatment of a tissue site, a biofilm may develop on or in the tissue site. Biofilms can comprise a microbial infection that can cover a tissue site and impair healing of the tissue site, such as the tissue site **103**. Biofilms can also lower the effectiveness of topical antibacterial treatments by preventing the topical treatments from reaching the tissue site. The presence of biofilms can increase healing times, reduce the efficacy and efficiency of various treatments, and increase the risk of a more serious infection.

(43) Even in the absence of biofilms, some tissue sites may not heal according to the normal medical protocol and may develop areas of necrotic tissue. Necrotic tissue may be dead tissue resulting from infection, toxins, or trauma that caused the tissue to die faster than the tissue can be removed by the normal body processes that regulate the removal of dead tissue. Sometimes, necrotic tissue may be in the form of slough, which may include a viscous liquid mass of tissue. Generally, slough is produced by bacterial and fungal infections that stimulate an inflammatory response in the tissue. Slough may be a creamy yellow color and may also be referred to as pus. Necrotic tissue may also include eschar. Eschar may be a portion of necrotic tissue that has become dehydrated and hardened. Eschar may be the result of a burn injury, gangrene, ulcers, fungal infections, spider bites, or anthrax. Eschar may be difficult to move without the use of surgical cutting instruments.

(44) The tissue site **103** may include biofilms, necrotic tissue, lacerated tissue, devitalized tissue,

contaminated tissue, damaged tissue, infected tissue, exudate, highly viscous exudate, fibrinous slough and/or other material that can generally be referred to as debris **130**. The debris **130** may inhibit the efficacy of tissue treatment and slow the healing of the tissue site **103**. As shown in FIG. **1**, the debris **130** may cover all or a portion of the tissue site **103**. If the debris is in the tissue site **103**, the tissue site **103** site may be treated with different processes to disrupt the debris **130**. Examples of disruption can include softening of the debris **130**, separation of the debris **130** from desired tissue, such as the subcutaneous tissue **115**, preparation of the debris **130** for removal from the tissue site **103**, and removal of the debris **130** from the tissue site **103**.

(45) The debris **130** can require debridement performed in an operating room. In some cases, tissue sites requiring debridement may not be life-threatening, and debridement may be considered low-priority. Low-priority cases can experience delays prior to treatment as other, more life-threatening, cases may be given priority for an operating room. As a result, low priority cases may need temporization. Temporization can include stasis of a tissue site, such as the tissue site **103**, that limits deterioration of the tissue site prior to other treatments, such as debridement, negative-pressure therapy or instillation.

(46) When debriding, clinicians may find it difficult to define separation between healthy, vital tissue and necrotic tissue. As a result, normal debridement techniques may remove too much healthy tissue or not enough necrotic tissue. If non-viable tissue demarcation does not extend deeper than the deep dermal layer, such as the dermis **109**, or if the tissue site **103** is covered by the debris **130**, such as slough or fibrin, gentle methods to remove the debris **130** should be considered to avoid excess damage to the tissue site **103**.

(47) Debridement may include the removal of the debris **130**. In some debridement processes, a mechanical process is used to remove the debris **130**. Mechanical processes may include using scalpels or other cutting tools having a sharp edge to cut away the debris **130** from the tissue site. Other mechanical processes may use devices that can provide a stream of particles to impact the debris **130** to remove the debris **130** in an abrasion process, or jets of high pressure fluid to impact the debris **130** to remove the debris **130** using water-jet cutting or lavage. Typically, mechanical processes of debriding a tissue site may be painful and may require the application of local anesthetics. Mechanical processes also risk over removal of healthy tissue that can cause further damage to the tissue site **103** and delay the healing process.

(48) Debridement may also be performed with an autolytic process. For example, an autolytic process may involve using enzymes and moisture produced by a tissue site to soften and liquefy the necrotic tissue and debris. Typically, a dressing may be placed over a tissue site having debris so that fluid produced by the tissue site may remain in place, hydrating the debris. Autolytic processes can be pain-free, but autolytic processes are a slow and can take many days. Because autolytic processes are slow, autolytic processes may also involve many dressing changes. Some autolytic processes may be paired with negative-pressure therapy so that, as debris hydrates, negative pressure supplied to a tissue site may draw off the debris. In some cases, a manifold positioned at a tissue site to distribute negative-pressure across the tissue site may become blocked or clogged with debris broken down by an autolytic process. If a manifold becomes clogged, negative-pressure may not be able to remove debris, which can slow or stop the autolytic process.

(49) Debridement may also be performed by adding enzymes or other agents to the tissue site that digest tissue. Often, strict control of the placement of the enzymes and the length of time the enzymes are in contact with a tissue site must be maintained. If enzymes are left on a tissue site for longer than needed, the enzymes may remove too much healthy tissue, contaminate the tissue site, or be carried to other areas of a patient. Once carried to other areas of a patient, the enzymes may break down undamaged tissue and cause other complications.

(50) These limitations and others may be addressed by the therapy system **100**, which can provide negative-pressure therapy, instillation therapy, and disruption of debris. In some embodiments, the therapy system **100** can provide mechanical movement at a surface of the tissue site in combination

with cyclic delivery and dwell of topical solutions to help solubilize debris. For example, a negative-pressure source may be fluidly coupled to a tissue site to provide negative pressure to the tissue site for negative-pressure therapy. In some embodiments, a fluid source may be fluidly coupled to a tissue site to provide therapeutic fluid to the tissue site for instillation therapy. In some embodiments, the therapy system **100** may include a contact layer positioned adjacent to a tissue site that may be used with negative-pressure therapy to disrupt areas of a tissue site having debris. In some embodiments, the therapy system **100** may include a contact layer positioned adjacent to a tissue site that may be used with instillation therapy to disrupt areas of a tissue site having debris. In some embodiments, the therapy system **100** may include a contact layer positioned adjacent to a tissue site that may be used with both negative-pressure therapy and instillation therapy to disrupt areas of a tissue site having debris. Following the disruption of the debris, negative-pressure therapy, instillation therapy, and other processes may be used to remove the debris from a tissue site. In some embodiments, the therapy system **100** may be used in conjunction with other tissue removal and debridement techniques. For example, the therapy system **100** may be used prior to enzymatic debridement to soften the debris. In another example, mechanical debridement may be used to remove a portion of the debris at the tissue site, and the therapy system **100** may then be used to remove the remaining debris while reducing the risk of trauma to the tissue site.

(51) The therapy system **100** may be used on the tissue site **103** having the debris **130**. In some embodiments, the contact layer **110** may be positioned adjacent to the tissue site **103** so that the contact layer **110** is in contact with the debris **130**. In some embodiments, the retainer layer **108** may be positioned over the contact layer **110**. In other embodiments, if the tissue site **103** has a depth that is about the same as a thickness **134** of the contact layer **110**, the retainer layer **108** may not be used. In still other embodiments, the retainer layer **108** may be positioned over the contact layer **110**, and if the depth of the tissue site **103** is greater than a thickness of the retainer layer **108** and the thickness **134** of the contact layer **110** combined, another retainer layer **108** may be placed over the contact layer **110** and the retainer layer **108**.

(52) In some embodiments, the contact layer **110** may have a substantially uniform thickness. The contact layer **110** may have the thickness **134**. In some embodiments, the thickness **134** may be between about 7 mm and about 15 mm. In other embodiments, the thickness **134** may be thinner or thicker than the stated range as needed for the tissue site **103**. In a preferred embodiment, the thickness **134** may be about 8 mm. In some embodiments, individual portions of the contact layer **110** may have a minimal tolerance from the thickness **134**. In some embodiments, the thickness **134** may have a tolerance of about 2 mm. In some embodiments, the thickness **134** may be between about 6 mm and about 10 mm. The contact layer **110** may be flexible so that the contact layer **110** can be contoured to a surface of the tissue site **103**.

(53) In some embodiments, the contact layer **110** may be formed from thermoplastic elastomers (TPE), such as styrene ethylene butylene styrene (SEBS) copolymers, or thermoplastic polyurethane (TPU). The contact layer **110** may be formed by combining sheets of TPE or TPU. In some embodiments, the sheets of TPE or TPU may be bonded, welded, adhered, or otherwise coupled to one another. For example, in some embodiments, the sheets of TPE or TPU may be welded using radiant heat, radio-frequency welding, or laser welding. Supracor, Inc., Hexacor, Ltd., Hexcel Corp., and Econocorp, Inc. may produce suitable TPE or TPU sheets for the formation of the contact layer **110**. In some embodiments, sheets of TPE or TPU having a thickness between about 0.2 mm and about 2.0 mm may be used to form a structure having the thickness **134**. In some embodiments, the contact layer **110** may be formed from a 3D textile, also referred to as a spacer fabric. Suitable 3D textiles may be produced by Heathcoat Fabrics, Ltd., Baltex, and Mueller Textil Group. The contact layer **110** can also be formed from polyurethane, silicone, polyvinyl alcohol, and metals, such as copper, tin, silver or other beneficial metals.

(54) In some embodiments, the contact layer **110** may be formed from a foam. For example, cellular foam, open-cell foam, reticulated foam, or porous tissue collections, may be used to form

the contact layer **110**. In some embodiments, the contact layer **110** may be formed of GranuFoam®, grey foam, or Zotefoam. Grey foam may be a polyester polyurethane foam having about 60 pores per inch (ppi). Zotefoam may be a closed-cell crosslinked polyolefin foam. In one non-limiting example, the contact layer **110** may be an open-cell, reticulated polyurethane foam such as GranuFoam® dressing available from Kinetic Concepts, Inc. of San Antonio, Texas; in other embodiments, the contact layer **110** may be an open-cell, reticulated polyurethane foam such as a V.A.C. VeraFlo® foam, also available from Kinetic Concepts, Inc., of San Antonio, Texas.

(55) In some embodiments, the contact layer **110** may be formed from a foam that is mechanically or chemically compressed to increase the density of the foam at ambient pressure. A foam that is mechanically or chemically compressed may be referred to as a compressed foam. A compressed foam may be characterized by a firmness factor (FF) that is defined as a ratio of the density of a foam in a compressed state to the density of the same foam in an uncompressed state. For example, a firmness factor (FF) of 5 may refer to a compressed foam having a density that is five times greater than a density of the same foam in an uncompressed state. Mechanically or chemically compressing a foam may reduce a thickness of the foam at ambient pressure when compared to the same foam that has not been compressed. Reducing a thickness of a foam by mechanical or chemical compression may increase a density of the foam, which may increase the firmness factor (FF) of the foam. Increasing the firmness factor (FF) of a foam may increase a stiffness of the foam in a direction that is parallel to a thickness of the foam. For example, increasing a firmness factor (FF) of the contact layer **110** may increase a stiffness of the contact layer **110** in a direction that is parallel to the thickness **134** of the contact layer **110**. In some embodiments, a compressed foam may be a compressed GranuFoam®. GranuFoam® may have a density of about 0.03 grams per centimeter.sup.3 (g/cm.sup.3) in its uncompressed state. If the GranuFoam® is compressed to have a firmness factor (FF) of 5, the GranuFoam® may be compressed until the density of the GranuFoam® is about 0.15 g/cm.sup.3. V.A.C. VeraFlo® foam may also be compressed to form a compressed foam having a firmness factor (FF) up to 5. In some embodiments, the contact layer **110** may have a thickness between about 4 mm to about 15 mm, and more specifically, about 8 mm at ambient pressure. In an exemplary embodiment, if the thickness **134** of the contact layer is about 8 mm, and the contact layer **110** is positioned within the sealed therapeutic environment **128** and subjected to negative pressure of about -115 mmHg to about -135 mm Hg, the thickness **134** of the contact layer **110** may be between about 1 mm and about 5 mm and, generally, greater than about 3 mm.

(56) A compressed foam may also be referred to as a felted foam. As with a compressed foam, a felted foam undergoes a thermoforming process to permanently compress the foam to increase the density of the foam. A felted foam may also be compared to other felted foams or compressed foams by comparing the firmness factor of the felted foam to the firmness factor of other compressed or uncompressed foams. Generally a compressed or felted foam may have a firmness factor greater than 1.

(57) The firmness factor (FF) may also be used to compare compressed foam materials with non-foam materials. For example, a Supracor® material may have a firmness factor (FF) that allows Supracor® to be compared to compressed foams. In some embodiments, the firmness factor (FF) for a non-foam material may represent that the non-foam material has a stiffness that is equivalent to a stiffness of a compressed foam having the same firmness factor. For example, if a contact layer is formed from Supracor®, as illustrated in Table 1 below, the contact layer may have a stiffness that is about the same as the stiffness of a compressed GranuFoam® material having a firmness factor (FF) of 3.

(58) Generally, if a compressed foam is subjected to negative pressure, the compressed foam exhibits less deformation than a similar uncompressed foam. If the contact layer **110** is formed of a compressed foam, the thickness **134** of the contact layer **110** may deform less than if the contact layer **110** is formed of a comparable uncompressed foam. The decrease in deformation may be

caused by the increased stiffness as reflected by the firmness factor (FF). If subjected to the stress of negative pressure, the contact layer **110** that is formed of compressed foam may flatten less than the contact layer **110** that is formed from uncompressed foam. Consequently, if negative pressure is applied to the contact layer **110**, the stiffness of the contact layer **110** in the direction parallel to the thickness **134** of the contact layer **110** allows the contact layer **110** to be more compliant or compressible in other directions, e.g., a direction perpendicular to the thickness **134**. The foam material used to form a compressed foam may be either hydrophobic or hydrophilic. The foam material used to form a compressed foam may also be either reticulated or un-reticulated. The pore size of a foam material may vary according to needs of the contact layer **110** and the amount of compression of the foam. For example, in some embodiments, an uncompressed foam may have pore sizes in a range of about 400 microns to about 600 microns. If the same foam is compressed, the pore sizes may be smaller than when the foam is in its uncompressed state.

(59) FIG. 2 is a plan view, illustrating additional details that may be associated with some embodiments of the contact layer **110**. The contact layer **110** may include a plurality of through-holes **140** or other perforations extending through the contact layer **110** to form walls **148**. In some embodiments, an exterior surface of the walls **148** may be parallel to sides of the contact layer **110**. In other embodiments, an interior surface of the walls **148** may be generally perpendicular to the tissue-facing surface **111** and the opposite surface **113** of the contact layer **110**. Generally, the exterior surface or surfaces of the walls **148** may be coincident with the tissue-facing surface **111** and the opposite surface **113**. The interior surface or surfaces of the walls **148** may form a perimeter **152** of each through-hole **140** and may connect the tissue facing surface **111** to the opposite surface **113**. In some embodiments, the through-holes **140** may have a circular shape as shown. In some embodiments, the through-holes **140** may have diameters between about 5 mm and about 20 mm, and in some embodiments, the diameters of the through-holes **140** may be about 10 mm. The through-holes **140** may have a depth that is about equal to the thickness **134** of the contact layer **110**. For example, the through-holes **140** may have a depth between about 6 mm to about 10 mm, and more specifically, about 8 mm at ambient pressure.

(60) In some embodiments, the contact layer **110** may have a first orientation line **136** and a second orientation line **138** that is perpendicular to the first orientation line **136**. The first orientation line **136** and the second orientation line **138** may be lines of symmetry of the contact layer **110**. A line of symmetry may be, for example, an imaginary line across the tissue-facing surface **111** or the opposite surface **113** of the contact layer **110** defining a fold line such that if the contact layer **110** is folded on the line of symmetry, the through-holes **140** and walls **148** would be coincidentally aligned. Generally, the first orientation line **136** and the second orientation line **138** aid in the description of the contact layer **110**. In some embodiments, the first orientation line **136** and the second orientation line **138** may be used to refer to the desired directions of contraction of the contact layer **110**. For example, the desired direction of contraction may be parallel to the second orientation line **138** and perpendicular to the first orientation line **136**. In other embodiments, the desired direction of contraction may be parallel to the first orientation line **136** and perpendicular to the second orientation line **138**. In still other embodiments, the desired direction of contraction may be at a non-perpendicular angle to both the first orientation line **136** and the second orientation line **138**. In other embodiments, the contact layer **110** may not have a desired direction of contraction. Generally, the contact layer **110** may be placed at the tissue site **103** so that the second orientation line **138** extends across the debris **130** of FIG. 1. Although the contact layer **110** is shown as having a generally rectangular shape including longitudinal edges **144** and latitudinal edges **146**, the contact layer **110** may have other shapes. For example, the contact layer **110** may have a diamond, square, or circular shape. In some embodiments, the shape of the contact layer **110** may be selected to accommodate the type of tissue site being treated. For example, the contact layer **110** may have an oval or circular shape to accommodate an oval or circular tissue site. In some embodiments, the first orientation line **136** may be parallel to the longitudinal edges **144**.

(61) Referring more specifically to FIG. 3, a single through-hole **140** having a circular shape is shown. The through-hole **140** may include a center **150** and a perimeter **152**. The through-hole **140** may have a perforation shape factor (PSF). The perforation shape factor (PSF) may represent an orientation of the through-hole **140** relative to the first orientation line **136** and the second orientation line **138**. Generally, the perforation shape factor (PSF) is a ratio of $\frac{1}{2}$ a maximum length of the through-hole **140** that is parallel to the desired direction of contraction to $\frac{1}{2}$ a maximum length of the through-hole **140** that is perpendicular to the desired direction of contraction. For descriptive purposes, the desired direction of contraction is parallel to the second orientation line **138**. The desired direction of contraction may be indicated by a lateral force **142**. For reference, the through-hole **140** may have an X-axis **156** extending through the center **150** between opposing vertices of the hexagon and parallel to the first orientation line **136**, and a Y-axis **154** extending through the center **150** between opposing sides of the hexagon and parallel to the second orientation line **138**. The perforation shape factor (PSF) of the through-hole **140** may be defined as a ratio of a line segment **158** on the Y-axis **154** extending from the center **150** to the perimeter **152** of the through-hole **140**, to a line segment **160** on the X-axis **156** extending from the center **150** to the perimeter **152** of the through-hole **140**. If a length of the line segment **158** is 2.5 mm and the length of the line segment **160** is 2.5 mm, the perforation shape factor (PSF) would be 1. In other embodiments, the through-holes **140** may have other shapes and orientations, for example, oval, hexagonal, square, triangular, or amorphous or irregular and be oriented relative to the first orientation line **136** and the second orientation line **138** so that the perforation shape factor (PSF) may range from about 0.5 to about 1.10.

(62) Referring to FIG. 4, a portion of the contact layer **110** of FIG. 1 is shown. The contact layer **110** may include the plurality of through-holes **140** aligned in parallel rows to form an array. The array of through-holes **140** may include a first row **162** of the through-holes **140**, a second row **164** of the through-holes **140**, and a third row **166** of the through-holes **140**. In some embodiments, a width of the wall **148** between the perimeters **152** of adjacent the through-holes **140** in a row, such as the first row **162**, may be about 5 mm. The centers **150** of the through-holes **140** in adjacent rows, for example, the first row **162** and the second row **164**, may be characterized by being offset from the second orientation line **138** along the first orientation line **136**. In some embodiments, a line connecting the centers of adjacent rows may form a strut angle (SA) with the first orientation line **136**. For example, a first through-hole **140A** in the first row **162** may have a center **150A**, and a second through-hole **140B** in the second row **164** may have a center **150B**. A strut line **168** may connect the center **150A** with the center **150B**. The strut line **168** may form an angle **170** with the first orientation line **136**. The angle **170** may be the strut angle (SA) of the contact layer **110**. In some embodiments, the strut angle (SA) may be less than about 90°. In other embodiments, the strut angle (SA) may be between about 30° and about 70° relative to the first orientation line **136**. In other embodiments, the strut angle (SA) may be about 66° from the first orientation line **136**. Generally, as the strut angle (SA) decreases, a stiffness of the contact layer **110** in a direction parallel to the first orientation line **136** may increase. Increasing the stiffness of the contact layer **110** parallel to the first orientation line **136** may increase the compressibility of the contact layer **110** perpendicular to the first orientation line **136**. Consequently, if negative pressure is applied to the contact layer **110**, the contact layer **110** may be more compliant or compressible in a direction perpendicular to the first orientation line **136**. By increasing the compressibility of the contact layer **110** in a direction perpendicular to the first orientation line **136**, the contact layer **110** may collapse to apply the lateral force **142** to the tissue site **103** described in more detail below.

(63) In some embodiments, the centers **150** of the through-holes **140** in alternating rows, for example, the center **150A** of the first through-hole **140A** in the first row **162** and a center **150C** of a through-hole **140C** in the third row **166**, may be spaced from each other parallel to the second orientation line **138** by a length **172**. In some embodiments, the length **172** may be greater than an effective diameter of the through-hole **140**. If the centers **150** of through-holes **140** in alternating

rows are separated by the length **172**, the exterior surface of the walls **148** parallel to the first orientation line **136** may be considered continuous. Generally, exterior surface of the walls **148** may be continuous if the exterior surface of the walls **148** do not have any discontinuities or breaks between through-holes **140**. In some embodiments, the length **172** may be between about 7 mm and about 25 mm.

(64) Regardless of the shape of the through-holes **140**, the through-holes **140** in the contact layer **110** may leave void spaces in the contact layer **110** and on the tissue-facing surface **111** and the opposite surface **113** of the contact layer **110** so that only the exterior surface of the walls **148** of the contact layer **110** remain with a surface available to contact the tissue site **103**. It may be desirable to minimize the exterior surface of the walls **148** so that the through-holes **140** may collapse, causing the contact layer **110** to collapse and generate the lateral force **142** in a direction perpendicular to the first orientation line **136**. However, it may also be desirable not to minimize the exterior surface of the walls **148** so much that the contact layer **110** becomes too fragile for sustaining the application of a negative pressure. The void space percentage (VS) of the through-holes **140** may be equal to the percentage of the volume or surface area of the void spaces of the tissue-facing surface **111** created by the through-holes **140** to the total volume or surface area of the tissue-facing surface **111** of the contact layer **110**. In some embodiments, the void space percentage (VS) may be between about 40% and about 75%. In other embodiments, the void space percentage (VS) may be about 55%. The organization of the through-holes **140** can also impact the void space percentage (VS), influencing the total surface area of the contact layer **110** that may contact the tissue site **103**. In some embodiments, the longitudinal edge **144** and the latitudinal edge **146** of the contact layer **110** may be discontinuous. An edge may be discontinuous where the through-holes **140** overlap an edge causing the edge to have a non-linear profile. A discontinuous edge may reduce the disruption of keratinocyte migration and enhance re-epithelialization while negative pressure is applied to the dressing **102**.

(65) In other embodiments, the through-holes **140** of the contact layer **110** may have a depth that is less than the thickness **134** of the contact layer **110**. For example, the holes **140** may be blind holes formed in the tissue-facing surface **111** of the contact layer **110**. The holes **140** may leave void spaces in the contact layer **110** on the tissue-facing surface **111** so that only the exterior surface of the walls **148** of the contact layer **110** on the tissue-facing surface **111** remain with a surface available to contact the tissue site **103** at ambient pressure. If a depth of the holes **140** extending from the tissue-facing surface **111** toward the opposite surface **113** is less than the thickness **134**, the void space percentage (VS) of the opposite surface **113** may be zero, while the void space percentage (VS) of the tissue-facing surface **111** is greater than zero, for example 55%. As used herein, the holes **140** may be similar to and operate as described with respect to the through-holes **140**, having similar structural, positional, and operational properties.

(66) In some embodiments, the through-holes **140** may be formed during molding of the contact layer **110**. In other embodiments, the through-holes **140** may be formed by cutting, melting, drilling, or vaporizing the contact layer **110** after the contact layer **110** is formed. For example, the through-holes **140** may be formed in the contact layer **110** by laser cutting the compressed foam of the contact layer **110**. In some embodiments, the through-holes **140** may be formed so that the interior surfaces of the walls **148** of the through-holes **140** are parallel to the thickness **134**. In other embodiments, the through-holes **140** may be formed so that the interior surfaces of the walls **148** of the through-holes **140** form a non-perpendicular angle with the tissue-facing surface **111**. In still other embodiments, the interior surfaces of the walls **148** of the through-holes **140** may taper toward the center **150** of the through-holes **140** to form conical, pyramidal, or other irregular through-hole shapes. If the interior surfaces of the walls **148** of the through-holes **140** taper, the through-holes **140** may have a height less than the thickness **134** of the contact layer **110**.

(67) In some embodiments, formation of the through-holes **140** may thermoform the material of the contact layer **110**, for example a compressed foam or a felted foam, causing the interior surface of

the walls **148** extending between the tissue-facing surface **111** and the opposite surface **113** to be smooth. As used herein, smoothness may refer to the formation of the through-holes **140** that causes the interior surface of the walls **148** that extends between the tissue-facing surface **111** and the opposite surface **113** to be substantially free of pores if compared to an uncut portion of the contact layer **110**. For example, laser-cutting the through-holes **140** into the contact layer **110**, may plastically deform the material of the contact layer **110**, closing any pores on the interior surfaces of the walls **148** that extend between the tissue-facing surface **111** and the opposite surface **113**. In some embodiments, a smooth interior surface of the walls **148** may limit or otherwise inhibit ingrowth of tissue into the contact layer **110** through the through-holes **140**. In other embodiments, the smooth interior surfaces of the walls **148** may be formed by a smooth material or a smooth coating.

(68) In some embodiments, an effective diameter of the through-holes **140** may be selected to permit flow of particulates through the through-holes **140**. In some embodiments, the diameter of the through-holes **140** may be selected based on the size of the solubilized debris to be lifted from the tissue site **103**. Larger through-holes **140** may allow larger debris to pass through the contact layer **110**, and smaller through-holes **140** may allow smaller debris to pass through the contact layer **110** while blocking debris larger than the through-holes. In some embodiments, successive applications of the dressing **102** can use contact layers **110** having successively smaller diameters of the through-holes **140** as the size of the solubilized debris in the tissue site **103** decreases. Sequentially decreasing diameters of the through-holes **140** may also aid in fine tuning a level of tissue disruption to the debris **130** during the treatment of the tissue site **103**. The diameter of the through-holes **140** can also influence fluid movement in the contact layer **110** and the dressing **102**. For example, the contact layer **110** can channel fluid in the dressing **102** toward the through-holes **140** to aid in the disruption of the debris **130** on the tissue site **103**. Variation of the diameters of the through-holes **140** can vary how fluid is moved through the dressing **102** with respect to both the removal of fluid and the application of negative pressure. In some embodiments, the diameter of the through-holes **140** is between about 5 mm and about 20 mm and, more specifically, about 10 mm.

(69) An effective diameter of a non-circular area is defined as a diameter of a circular area having the same surface area as the non-circular area. In some embodiments, each through-hole **140** may have an effective diameter of about 3.5 mm. In other embodiments, each through-hole **140** may have an effective diameter between about 5 mm and about 20 mm. The effective diameter of the through-holes **140** should be distinguished from the porosity of the material forming the walls **148** of the contact layer **110**. Generally, an effective diameter of the through-holes **140** is an order of magnitude larger than the effective diameter of the pores of a material forming the contact layer **110**. For example, the effective diameter of the through-holes **140** may be larger than about 1 mm, while the walls **148** may be formed from GranuFoam® material having a pore size less than about 600 microns. In some embodiments, the pores of the walls **148** may not create openings that extend all the way through the material. Generally, the through-holes **140** do not include pores formed by the foam formation process, and the through-holes **140** may have an average effective diameter that is greater than ten times an average effective diameter of pores of a material.

(70) Referring now to both FIGS. 2 and 4, the through-holes **140** may form a pattern depending on the geometry of the through-holes **140** and the alignment of the through-holes **140** between adjacent and alternating rows in the contact layer **110** with respect to the first orientation line **136**. If the contact layer **110** is subjected to negative pressure, the through-holes **140** of the contact layer **110** may contract. As used herein, contraction can refer to both vertical compression of a body parallel to a thickness of the body, such as the contact layer **110**, and lateral compression of a body perpendicular to a thickness of the body, such as the contact layer **110**. In some embodiments the void space percentage (VS), the perforation shape factor (PSF), and the strut angle (SA) may cause the contact layer **110** to contract along the second orientation line **138** perpendicular to the first

orientation line **136** as shown in more detail in FIG. 5. If the contact layer **110** is positioned on the tissue site **103**, the contact layer **110** may generate the lateral force **142** along the second orientation line **138**, contracting the contact layer **110**, as shown in more detail in FIG. 5. The lateral force **142** may be optimized by adjusting the factors described above as set forth in Table 1 below. In some embodiments, the through-holes **140** may be circular, have a strut angle (SA) of approximately 37°, a void space percentage (VS) of about 54%, a firmness factor (FF) of about 5, a perforation shape factor (PSF) of about 1, and a diameter of about 5 mm. If the contact layer **110** is subjected to a negative pressure of about -125 mmHg, the contact layer **110** asserts the lateral force **142** of approximately 11.9 N. If the diameter of the through-holes **140** of the contact layer **110** is increased to about 20 mm, the void space percentage (VS) changed to about 52%, the strut angle (SA) changed to about 52°, and the perforation shape factor (PSF) and the firmness factor (FF) remain the same, the lateral force **142** is decreased to about 6.5 N. In other embodiments, the through-holes **140** may be hexagonal, have a strut angle (SA) of approximately 66°, a void space percentage (VS) of about 55%, a firmness factor (FF) of about 5, a perforation shape factor (PSF) of about 1.07, and an effective diameter of about 5 mm. If the contact layer **110** is subjected to a negative pressure of about -125 mmHg, the lateral force **142** asserted by the contact layer **110** is about 13.3 N. If the effective diameter of the through-holes **140** of the contact layer **110** is increased to 10 mm, the lateral force **142** is decreased to about 7.5 N.

(71) Referring to FIG. 5, the contact layer **110** is in the second position, or contracted position, as indicated by the lateral force **142**. In operation, negative pressure is supplied to the sealed therapeutic environment **128** with the negative-pressure source **104**. In response to the supply of negative pressure, the contact layer **110** contracts from the relaxed position illustrated in FIG. 2 to the contracted position illustrated in FIG. 5. In one embodiment, the thickness **134** of the contact layer **110** remains substantially the same. When the negative pressure is removed, for example, by venting the negative pressure, the contact layer **110** expands back to the relaxed position. If the contact layer **110** is cycled between the contracted and relaxed positions of FIG. 5 and FIG. 2, respectively, the tissue-facing surface **111** of the contact layer **110** may disrupt the debris **130** on the tissue site **103** by rubbing the debris **130** from the tissue site **103**. The edges of the through-holes **140** formed by the tissue-facing surface **111** and the interior surfaces or transverse surfaces of the walls **148** can form cutting edges that can disrupt the debris **130** in the tissue site **103**, allowing the debris **130** to exit through the through-holes **140**. In some embodiments, the cutting edges are defined by the perimeter **152** where each through-hole **140** intersects the tissue-facing surface **111**.

(72) In some embodiments, the material, the void space percentage (VS), the firmness factor, the strut angle, the hole shape, the perforation shape factor (PSF), and the hole diameter may be selected to increase compression or collapse of the contact layer **110** in a lateral direction, as shown by the lateral force **142**, by forming weaker walls **148**. Conversely, the factors may be selected to decrease compression or collapse of the contact layer **110** in a lateral direction, as shown by the lateral force **142**, by forming stronger walls **148**. Similarly, the factors described herein can be selected to decrease or increase the compression or collapse of the contact layer **110** perpendicular to the lateral force **142**.

(73) In some embodiments, the therapy system **100** may provide cyclic therapy. Cyclic therapy may alternately apply negative pressure to and vent negative pressure from the sealed therapeutic environment **128**. In some embodiments, negative pressure may be supplied to the sealed therapeutic environment **128** until the pressure in the sealed therapeutic environment **128** reaches a predetermined therapy pressure. If negative pressure is supplied to the sealed therapeutic environment **128**, the debris **130** and the subcutaneous tissue **115** may be drawn into the through-holes **140**. In some embodiments, the sealed therapeutic environment **128** may remain at the therapy pressure for a predetermined therapy period such as, for example, about 10 minutes. In other embodiments, the therapy period may be longer or shorter as needed to supply appropriate negative-pressure therapy to the tissue site **103**.

(74) Following the therapy period, the sealed therapeutic environment **128** may be vented. For example, the negative-pressure source **104** may fluidly couple the sealed therapeutic environment **128** to the atmosphere (not shown), allowing the sealed therapeutic environment **128** to return to ambient pressure. In some embodiments, the negative-pressure source **104** may vent the sealed therapeutic environment **128** for about 1 minute. In other embodiments, the negative-pressure source **104** may vent the sealed therapeutic environment **128** for longer or shorter periods. After venting of the sealed therapeutic environment **128**, the negative-pressure source **104** may be operated to begin another negative-pressure therapy cycle.

(75) In some embodiments, instillation therapy may be combined with negative-pressure therapy. For example, following the therapy period of negative-pressure therapy, the fluid source **120** may operate to provide fluid to the sealed therapeutic environment **128**. In some embodiments, the fluid source **120** may provide fluid while the negative-pressure source **104** vents the sealed therapeutic environment **128**. For example, the fluid source **120** may include a pump configured to move instillation fluid from the fluid source **120** to the sealed therapeutic environment **128**. In some embodiments, the fluid source **120** may not have a pump and may operate using a gravity feed system. In other embodiments, the negative-pressure source **104** may not vent the sealed therapeutic environment **128**. Instead, the negative pressure in the sealed therapeutic environment **128** is used to draw instillation fluid from the fluid source **120** into the sealed therapeutic environment **128**.

(76) In some embodiments, the fluid source **120** may provide a volume of fluid to the sealed therapeutic environment **128**. In some embodiments, the volume of fluid may be the same as a volume of the sealed therapeutic environment **128**. In other embodiments, the volume of fluid may be smaller or larger than the sealed therapeutic environment **128** as needed to appropriately apply instillation therapy. Instilling of the tissue site **103** may raise a pressure in the sealed therapeutic environment **128** to a pressure greater than the ambient pressure, for example to between about 0 mmHg and about 15 mmHg and, more specifically, about 5 mmHg. In some embodiments, the fluid provided by the fluid source **120** may remain in the sealed therapeutic environment **128** for a dwell time. In some embodiments, the dwell time is about 5 minutes. In other embodiments, the dwell time may be longer or shorter as needed to appropriately administer instillation therapy to the tissue site **103**. For example, the dwell time may be zero.

(77) At the conclusion of the dwell time, the negative-pressure source **104** may be operated to draw the instillation fluid into the container **112**, completing a cycle of therapy. As the instillation fluid is removed from the sealed therapeutic environment **128** with negative pressure, negative pressure may also be supplied to the sealed therapeutic environment **128**, starting another cycle of therapy.

(78) FIG. 6 is a sectional view of a portion of the contact layer **110**, illustrating additional details that may be associated with some embodiments. The contact layer **110** and the retainer layer **108** may be placed at the tissue site **103** having the debris **130** covering the subcutaneous tissue **115**. The drape **106** may be placed over the retainer layer **108** to provide the sealed therapeutic environment **128** for the application of negative pressure therapy or instillation therapy. As shown in FIG. 6, the retainer layer **108** may have a thickness **131** if the pressure in the sealed therapeutic environment **128** is about an ambient pressure. In some embodiments, the thickness **131** may be about 8 mm. In other embodiments, the thickness **131** may be about 16 mm.

(79) FIG. 7 is a sectional view of a portion of the dressing **102** during negative-pressure therapy, illustrating additional details that may be associated with some embodiments. For example, FIG. 7 may illustrate a moment in time where a pressure in the sealed therapeutic environment **128** may be about 125 mmHg of negative pressure. In some embodiments, the retainer layer **108** may be a non-precompressed foam, and the contact layer **110** may be a precompressed foam. In response to the application of negative pressure, the contact layer **110** may not compress, and the retainer layer **108** may compress so that the manifold has a thickness **133**. In some embodiments, the thickness **133** of the retainer layer **108** during negative-pressure therapy may be less than the thickness **131** of

the retainer layer **108** if the pressure in the sealed therapeutic environment **128** is about the ambient pressure.

(80) In some embodiments, negative pressure in the sealed therapeutic environment **128** can generate concentrated stresses in the retainer layer **108** adjacent to the through-holes **140** in the contact layer **110**. The concentrated stresses can cause macro-deformation of the retainer layer **108** that draws portions of the retainer layer **108** into the through-holes **140** of the contact layer **110**. Similarly, negative pressure in the sealed therapeutic environment **128** can generate concentrated stresses in the debris **130** adjacent to the through-holes **140** in the contact layer **110**. The concentrated stresses can cause macro-deformations of the debris **130** and the subcutaneous tissue **115** that draws portions of the debris **130** and the subcutaneous tissue **115** into the through-holes **140**.

(81) FIG. **8** is a detail view of the contact layer **110**, illustrating additional details of the operation of the contact layer **110** during negative-pressure therapy. Portions of the retainer layer **108** in contact with the opposite surface **113** of the contact layer **110** may be drawn into the through-holes **140** to form bosses **137**. The bosses **137** may have a shape that corresponds to the through-holes **140**. A height of the bosses **137** from the retainer layer **108** may be dependent on the pressure of the negative pressure in the sealed therapeutic environment **128**, the area of the through-holes **140**, and the firmness factor of the retainer layer **108**.

(82) Similarly, the through-holes **140** of the contact layer **110** may create macro-pressure points in portions of the debris **130** and the subcutaneous tissue **115** that are in contact with the tissue-facing surface **111** of the contact layer **110**, causing tissue puckering and nodules **139** in the debris **130** and the subcutaneous tissue **115**.

(83) A height of the nodules **139** over the surrounding tissue may be selected to maximize disruption of debris **130** and minimize damage to subcutaneous tissue **115** or other desired tissue. Generally, the pressure in the sealed therapeutic environment **128** can exert a force that is proportional to the area over which the pressure is applied. At the through-holes **140** of the contact layer **110**, the force may be concentrated as the resistance to the application of the pressure is less than in the walls **148** of the contact layer **110**. In response to the force generated by the pressure at the through-holes **140**, the debris **130** and the subcutaneous tissue **115** that forms the nodules **139** may be drawn into and through the through-holes **140** until the force applied by the pressure is equalized by the reactive force of the debris **130** and the subcutaneous tissue **115**. In some embodiments where the negative pressure in the sealed therapeutic environment **128** may cause tearing, the thickness **134** of the contact layer **110** may be selected to limit the height of the nodules **139** over the surrounding tissue. In some embodiments, the retainer layer **108** may limit the height of the nodules **139** to the thickness **134** of the contact layer **110** under negative pressure if the contact layer is compressible. In other embodiments, the bosses **137** of the retainer layer **108** may limit the height of the nodules **139** to a height that is less than the thickness **134** of the contact layer **110**. By controlling the firmness factor of the retainer layer **108**, the height of the bosses **137** over the surrounding material of the retainer layer **108** can be controlled. The height of the nodules **139** can be limited to the difference of the thickness **134** of the contact layer **110** and the height of the bosses **137**. In some embodiments, the height of the bosses **137** can vary from zero to several millimeters as the firmness factor of the retainer layer **108** decreases. In an exemplary embodiment, the thickness **134** of the contact layer **110** may be about 7 mm. During the application of negative pressure, the bosses **137** may have a height between about 4 mm to about 5 mm, limiting the height of the nodules to about 2 mm to about 3 mm. By controlling the height of the nodules **139** by controlling the thickness **134** of the contact layer **110**, the firmness factor of the retainer layer **108**, or both, the aggressiveness of disruption to the debris **130** and tearing can be controlled.

(84) In some embodiments, the height of the nodules **139** can also be controlled by controlling an expected compression of the contact layer **110** during negative-pressure therapy. For example, the contact layer **110** may have a thickness **134** of about 8 mm. If the contact layer **110** is formed from

a compressed foam, the firmness factor of the contact layer **110** may be higher; however, the contact layer **110** may still reduce in thickness in response to negative pressure in the sealed therapeutic environment **128**. In one embodiment, application of negative pressure of between about -50 mmHg and about -350 mmHg, between about -100 mm Hg and about -250 mmHg and, more specifically, about -125 mmHg in the sealed therapeutic environment **128** may reduce the thickness **134** of the contact layer **110** from about 8 mm to about 3 mm. If the retainer layer **108** is placed over the contact layer **110**, the height of the nodules **139** may be limited to be no greater than the thickness **134** of the contact layer **110** during negative-pressure therapy, for example, about 3 mm. By controlling the height of the nodules **139**, the forces applied to the debris **130** by the contact layer **110** can be adjusted and the degree that the debris **130** is stretched can be varied.

(85) In some embodiments, the formation of the bosses **137** and the nodules **139** can cause the debris **130** to remain in contact with a tissue interface **107** during negative pressure therapy. For example, the nodules **139** may contact the sidewalls of the through-holes **140** of the contact layer **110** and the bosses **137** of the retainer layer **108**, while the surrounding tissue may contact the tissue-facing surface **111** of the contact layer **110**. In some embodiments, formation of the nodules **139** may lift debris and particulates off of the surrounding tissue, operating in a piston-like manner to move debris toward the retainer layer **108** and out of the sealed therapeutic environment **128**.

(86) In response to the return of the sealed therapeutic environment **128** to ambient pressure by venting the sealed therapeutic environment **128**, the debris **130** and the subcutaneous tissue **115** may leave the through-holes **140**, returning to the position shown in FIG. 6.

(87) The application and removal of negative pressure to the sealed therapeutic environment **128** can disrupt the debris **130**. For example, FIG. 9 is a top view of the debris **130**, illustrating additional details that may be associated with some embodiments. As shown in FIG. 9, the nodules **139** may rupture. For example, the debris **130** in a nodule **139A** may rupture, aiding in the removal of the debris **130**. In some embodiments, repeated application of negative-pressure therapy and instillation therapy while the contact layer **110** is disposed over the debris **130** may disrupt the debris **130**, allowing the debris **130** to be removed during dressing changes. In other embodiments, the contact layer **110** may disrupt the debris **130** so that the debris **130** can be removed by negative pressure. In still other embodiments, the contact layer **110** may disrupt the debris **130**, aiding removal of the debris **130** during debridement processes.

(88) With each cycle of therapy, the contact layer **110** may form nodules **139** in the debris **130**. The formation of the nodules **139** and release of the nodules **139** by the contact layer **110** during therapy may disrupt the debris **130**. With each subsequent cycle of therapy, disruption of the debris **130** can be increased.

(89) Disruption of the debris **130** can be caused, at least in part, by the concentrated forces applied to the debris **130** by the through-holes **140** and the walls **148** of the contact layer **110**. The forces applied to the debris **130** can be a function of the negative pressure supplied to the sealed therapeutic environment **128** and the area of each through-hole **140**. For example, if the negative pressure supplied to the sealed therapeutic environment **128** is about 125 mmHg and the diameter of each through-hole **140** is about 5 mm, the force applied at each through-hole **140** is about 0.07 lbs. If the diameter of each through-hole **140** is increased to about 8 mm, the force applied at each through-hole **140** can increase up to 6 times. Generally, the relationship between the diameter of each through-hole **140** and the applied force at each through-hole **140** is not linear and can increase exponentially with an increase in diameter.

(90) In some embodiments, the negative pressure applied by the negative-pressure source **104** may be cycled rapidly. For example, negative pressure may be supplied for a few seconds, then vented for a few seconds, causing a pulsation of negative pressure in the sealed therapeutic environment **128**. The pulsation of the negative pressure can pulsate the nodules **139**, causing further disruption of the debris **130**.

(91) In some embodiments, the cyclical application of instillation therapy and negative pressure

therapy may cause micro-floating. For example, negative pressure may be applied to the sealed therapeutic environment **128** during a negative-pressure therapy cycle. Following the conclusion of the negative-pressure therapy cycle, instillation fluid may be supplied during the instillation therapy cycle. The instillation fluid may cause the contact layer **110** to float relative to the debris **130**. As the contact layer **110** floats, it may change position relative to the position the contact layer **110** occupied during the negative-pressure therapy cycle. The position change may cause the contact layer **110** to engage a slightly different portion of the debris **130** during the next negative-pressure therapy cycle, aiding disruption of the debris **130**.

(92) In some embodiments, the contact layer **110** may be bonded to the retainer layer **108**. In other embodiments, the retainer layer **108** may have a portion subjected to the compression or felting processes to form the contact layer **110**. The plurality of through-holes **140** may then be formed or cut into the compressed foam portion of the retainer layer **108** to a depth for the desired height of the nodules **139**. In other embodiments, the retainer layer **108** may be a compressed or felted foam having the through-holes **140** formed in a portion of the retainer layer **108**. The portions of the retainer layer **108** having the through-holes **140** may comprise the contact layer **110**.

(93) In some embodiments, the contact layer **110** may be provided as a component of a dressing kit. The kit may include a punch, and the contact layer **110** may be provided without any through-holes **140**. When using the contact layer **110**, the user may use the punch to place the through-holes **140** through portions of the contact layer **110** that may be placed over the debris **130**. The kit provides a user, such as a clinician, the ability to customize the contact layer **110** to the particular tissue site **103**, so that the through-holes **140** are only disrupting the debris **130** and not healthy tissue that may be near or surround the debris **130**.

(94) The contact layer **110** can also be used with other foams without the through-holes **140**. The contact layer **110** can be cut to fit the debris **130** at the tissue site **103**, and dressing material without the through-holes **140** may be placed over remaining areas of the tissue site **103**. Similarly, other dressing materials may be placed between the contact layer **110** and the tissue site **103** where no disruption is desired. In some embodiments, the kit may include a first retainer layer **108** having a thickness of between about 5 mm and about 15 mm and, more specifically, about 8 mm. The kit can also include a second retainer layer **108** having a thickness between about 10 mm and about 20 mm and, more specifically, about 16 mm. During application of the dressing **102**, the user may select an appropriate one of the first retainer layer **108** and the second retainer layer **108** as needed to fill the tissue site **103**.

(95) In an experimental model, the contact layer **110** was evaluated on various matrices using a Dermosol wound model to simulate human tissue that allows contraction of the tissue during negative-pressure therapy. The matrices included a soluble Pectin matrix to simulate thick exudate or biofilm, a combination soluble and insoluble matrix to simulate slough and eschar, and an insoluble matrix, such as Prisma™, to simulate robust devitalized tissue. The experimental results indicated that the contact layer **110** provided granulation and particle loss comparable to negative-pressure therapy with a foam manifold, such as Granufoam®, with decrease in peel force and bleeding. In addition, the experimental results provided consistent visual evidence of surface changes related to the pattern of the through-holes **140** that results in loosening and detachment of exudate and infectious material.

(96) In the experimental model, each matrix was 5 cm in diameter and had a 1 cm depth. Each matrix was maintained at a controlled temperature using heated circulated water. The Pectin matrices were subjected to a single cycle, each having a 10 minute instillation soak period and 30 minute negative pressure therapy period lasting for an experimental time period of about 1 hour. The simulated eschar matrices were subjected to 10 cycles, each having a 20 minute instillation soak period and 45 minute negative pressure therapy period for an experimental time period of about 10 hours. The collagen matrices were subjected to 48 cycles, each having a 20 minute instillation soak period and a 45 minute negative pressure therapy period for an experimental time

period of about 48 hours. As illustrated in FIG. 10, in each experimental case, softening and other disruption of debris occurred.

(97) In another experimental model, the effect on granulation tissue formation and tissue healing progression using negative-pressure therapy and instillation with the contact layer in a porcine model was studied. The model used full thickness dorsal excisional wounds having a rectangular shape. The wounds were 3 cm×7 cm in size on female domestic swine. The dressings used in the experimental model were changed every two to three days during a seven day study duration. Each animal included a control site dressed with a foam manifold, such as a Granufoam®, and saline instillation. Each animal had twelve tissue sites. 180 degree peel testing was conducted at each dressing change to determine the peel force required to remove the dressing and the amount of foam retention in the site. Histology was conducted at the termination of seven days to determine the granulation tissue thickness and to make a scored assessment of inflammation, abscess, and edema. The scored assessment used the following scale: 0 for the condition not being present, 1 for the condition being minimal, 2 for the condition being mild, 3 for the condition being moderate, 4 for the condition being marked, and 5 for the condition being severe. In addition, images were made of each tissue site at each dressing change to determine healing progression and the amount of retained foam. Treatment included a 10 minute instillation soak period, a 3.5 hour negative pressure therapy period at -125 mmHg, and 6.5 therapy cycles were conducted per day. Six experimental dressing types were tested. The through-holes in the contact layer in two dressings were circular. In the first, the through-holes had 4 mm diameters and 3 mm spacing between the perimeters of adjacent through-holes; in the second, the through-holes had 10 mm diameters and 5 mm spacing between the perimeters of adjacent through-holes. The through-holes in the contact layer in two dressings were hexagonal. In the first, the through-holes had 4 mm sides and 3 mm spacing between the perimeters of adjacent through-holes. In the second, the through-holes had 10 mm sides and 5 mm spacing between the perimeters of adjacent through-holes. The through-holes in the contact layer in two dressings were ellipsoid. In the first, the through-holes had a 10 mm×5 mm ellipse and small spacing, and in the second, the through-holes had a 5 mm×10 mm ellipse and large spacing.

(98) The control group experienced an average of 5.1 Newtons (N) peel force on day 7 and maximum bleeding. Granulation tissue thickness was nominal, edema measured at 1.8, abscess at 0.5, and inflammation at 1.2. For the various contact layers described herein, the average peel force was less than 5.1 N at day 3, day 5, and day 7. In addition, the total amount of blood loss for the experimental dressings was 50% of the blood loss for the control dressings at day 7. The histological scores for the experimental contact layers were less than 3. In addition, granulation tissue thickness for the experimental dressings was measured at between 3 mm and 5 mm, where the granulation tissue thickness in the control dressings was about 4 mm.

(99) Disruption of debris associated with other experimental results is illustrated in FIG. 11 and FIG. 12. As shown in FIG. 11, a cellulose test matrix was treated with a contact layer having circular holes and a foam material. The portion treated with the contact layer having circular holes demonstrated disruption of debris on the tissue following treatment. In contrast, the portion of the cellulose test matrix treated with a foam material experienced little to no disruption. FIG. 12 illustrates a magnified view of the cellulose test matrix of FIG. 11 showing the fibrous matrix having a thickened gel-like pulp. Following treatment with the contact layer, the fibrous matrix showed evidence of disruption including rupture of the matrix.

(100) FIG. 13 is a plan view, illustrating additional details that may be associated with some embodiments of a contact layer 210. The contact layer 210 may be similar to the contact layer 110 and operate as described above with respect to FIGS. 1-9. Similar elements may have similar numbers indexed to 200. For example, the contact layer 210 is shown as having a generally rectangular shape including longitudinal edges 244 and latitudinal edges 246. The contact layer 210 may have a first orientation line 236 and a second orientation line 238 that is perpendicular to the

first orientation line **236**. The contact layer **210** may include a plurality of through-holes **240** or perforations extending through the contact layer **210** to form walls **248** that extend through the contact layer **210**. The walls **248** may have interior or transverse surfaces that intersect with the tissue-facing surface **211** to form cutting edges. In some embodiments, the through-holes **240** may have a hexagonal shape as shown.

(101) FIG. **14** is a plan view, illustrating additional details that may be associated with some embodiments of a contact layer **310**. The contact layer **310** may be similar to the contact layer **110** and operate as described above with respect to FIGS. **1-9**. Similar elements may have similar reference numbers indexed to 300. In some embodiments, the contact layer **310** may have a first orientation line **336** and a second orientation line **338** that is perpendicular to the first orientation line **336**. The contact layer **310** may include a plurality of through-holes **340** or perforations extending through the contact layer **310** to form walls **348** that extend through the contact layer **310**. The walls **348** may have interior surfaces or transverse surfaces that intersect with the tissue-facing surface **311** to form cutting edges. In some embodiments, the through-holes **340** may have an ovoid shape as shown.

(102) FIG. **15** is a plan view, illustrating additional details that may be associated with some embodiments of a contact layer **410**. The contact layer **410** may be similar to the contact layer **110** and operate as described with respect to FIGS. **1-9**. Similar elements may have similar reference numbers indexed to 400. For example, the contact layer **410** is shown as having a generally rectangular shape including longitudinal edges **444** and latitudinal edges **446**. In some embodiments, the contact layer **410** may have a first orientation line **436** and a second orientation line **438** that is perpendicular to the first orientation line **436**. The contact layer **410** may include a plurality of through-holes **440** or perforations extending through the contact layer **410** to form walls **448** that extend through the contact layer **410**. The walls **448** may have interior surfaces or transverse surfaces that intersect with the tissue-facing surface **411** to form cutting edges. In some embodiments, the through-holes **440** may have a triangular shape as shown.

(103) The through-holes **240**, the through-holes **340**, and the through-holes **440** of each of the contact layer **210**, the contact layer **310**, and the contact layer **410** may generate concentrated stresses that influence disruption of the debris **130** in different ways. For example, the triangular shaped through-holes **440** of the contact layer **410** may focus the stresses of the contact layer **410** at vertices of the through-holes **440** so that disruption of the debris **130** may be focused at the vertices of the through-holes **440**. Similarly, the different shapes of the through-holes **240** and the through-holes **340** may also focus the stresses generated by the contact layer **210** and the contact layer **310** in other advantageous areas.

(104) A lateral force, such as the lateral force **142**, generated by a contact layer, such as the contact layer **110**, may be related to a compressive force generated by applying negative pressure at a therapy pressure to a sealed therapeutic environment. For example, the lateral force **142** may be proportional to a product of a therapy pressure (TP) in the sealed therapeutic environment **128**, the compressibility factor (CF) of the contact layer **110**, and a surface area (A) the tissue-facing surface **111** of the contact layer **110**. The relationship is expressed as follows:

Lateral force $\propto (TP * CF * A)$

(105) In some embodiments, the therapy pressure TP is measured in N/m.sup.2, the compressibility factor (CF) is dimensionless, the area (A) is measured in m.sup.2, and the lateral force is measured in Newtons (N). The compressibility factor (CF) resulting from the application of negative pressure to a contact layer may be, for example, a dimensionless number that is proportional to the product of the void space percentage (VS) of a contact layer, the firmness factor (FF) of the contact layer, the strut angle (SA) of the through-holes in the contact layer, and the perforation shape factor (PSF) of the through-holes in the contact layer. The relationship is expressed as follows:

Compressibility Factor (CF) $\propto (VS * FF * \sin(SA) * PSF)$

(106) Based on the above formulas, contact layers formed from different materials with through-

holes of different shapes were manufactured and tested to determine the lateral force of the contact layers. For each contact layer, the therapy pressure TP was about -125 mmHg and the dimensions of the contact layer were about 200 mm by about 53 mm so that the surface area (A) of the tissue-facing surface of the contact layer was about 106 cm.sup.2 or 0.0106 m.sup.2. Based on the two equations described above, the lateral force for a Supracor® contact layer **210** having a firmness factor (FF) of 3 was about 13.3 where the Supracor® contact layer **210** had hexagonal through-holes **240** with a distance between opposite vertices of 5 mm, a perforation shape factor (PSF) of 1.07, a strut angle (SA) of approximately 66°, and a void space percentage (VS) of about 55%. A similarly dimensioned GranuFoam® contact layer **110** generated the lateral force **142** of about 9.1 Newtons (N).

(107) TABLE-US-00001 TABLE 1 Major Lateral Material VS FF SA Hole Shape PSF diam. (mm)
 force GranuFoam ® 56 5 47 Ovular 1 10 13.5 Supracor ® 55 3 66 Hexagon 1.1 5 13.3
 GranuFoam ® 40 5 63 Triangle 1.1 10 12.2 GranuFoam ® 54 5 37 Circular 1 5 11.9
 GranuFoam ® 52 5 37 Circular 1 20 10.3 Grey Foam N/A 5 N/A Horizontal N/A N/A 9.2 stripes
 GranuFoam ® 55 5 66 Hexagon 1.1 5 9.1 GranuFoam ® N/A 5 N/A Horizontal N/A N/A 8.8
 stripes Zotefoam 52 3 37 Circular 1 10 8.4 GranuFoam ® 52 5 37 Circular 1 10 8.0 GranuFoam ®
 52 5 64 Circular 1 10 7.7 GranuFoam ® 56 5 66 Hexagon 1.1 10 7.5 Grey Foam N/A 3 N/A
 Horizontal N/A N/A 7.2 stripes Zotefoam 52 3 52 Circular 1 20 6.8 GranuFoam ® N/A 3 N/A
 Horizontal N/A N/A 6.6 Striping GranuFoam ® 52 5 52 Circular 1 20 6.5 GranuFoam ® N/A 5 N/A
 Vertical N/A N/A 6.1 Stripes GranuFoam ® N/A 1 N/A None N/A N/A 5.9 GranuFoam ® N/A 3
 N/A Vertical N/A N/A 5.6 stripes GranuFoam ® 52 1 37 None 1 10 5.5

(108) In some embodiments, the formulas described above may not precisely describe the lateral forces due to losses in force due to the transfer of the force from the contact layer to the wound. For example, the modulus and stretching of the drape **106**, the modulus of the tissue site **103**, slippage of the drape **106** over the tissue site **103**, and friction between the contact layer **110** and the tissue site **103** may cause the actual value of the lateral force **142** to be less than the calculated value of the lateral force **142**.

(109) FIG. **16** is a flow chart **1600** illustrating exemplary operations that can be associated with some embodiments of the therapy system **100** of FIG. **1**. At block **1601**, the contact layer **110** may be selected for use on the tissue site **103**.

(110) At block **1603**, the selected contact layer can be positioned at a tissue site. For example, the contact layer **110** can be positioned over the debris **130** of the tissue site **103**. At block **1605**, a retainer layer may be selected for use on the tissue site. For example, the retainer layer **108** can be selected for use on the tissue site **103**. At block **1607**, the selected retainer layer can be positioned over the contact layer. For example, the retainer layer **108** can be positioned over the contact layer **110**. At block **1609**, a sealing member may be positioned over the retainer layer, the contact layer, and the tissue site, and at block **1611**, the sealing member can be sealed to tissue surrounding the tissue site. For example, the drape **106** can be positioned over the tissue site **103** and sealed to tissue surrounding the tissue site **103**.

(111) At block **1613**, a negative pressure source can be fluidly coupled to a sealed space formed by the sealing member. For example, the negative-pressure source **104** can be fluidly coupled to the sealed therapeutic environment **128** formed by the drape **106**. At block **1615**, the negative-pressure source can supply negative pressure to the sealed space. For example, a controller of the negative-pressure source **104** can actuate the negative-pressure source **104** to draw fluid from the sealed therapeutic environment **128**, thereby supplying negative-pressure to the sealed therapeutic environment **128** for a negative-pressure therapy period.

(112) At block **1617**, the controller can determine if the negative-pressure therapy period has concluded. For example, a controller of the negative-pressure source **104** can determine if a timer, started when the negative-pressure source was actuated to supply negative pressure, has reached a predetermined time. The predetermined time may be based on an expected timer interval for

negative-pressure therapy of the predetermined time may be a time period selected by a user. At block **1617**, if the timer has not expired, the method can continue on the NO path to block **1615**, where the controller of the negative-pressure source can continue supplying negative pressure to the sealed space.

(113) At block **1617**, if the timer has expired, the method can continue on the YES path to block **1619**, where the controller of the negative-pressure source can vent the negative pressure in the sealed space to the ambient environment. For example, the controller of the negative-pressure source **104** can vent the sealed therapeutic environment **128** to the ambient environment.

(114) At block **1621**, the method determines if therapy has concluded. For example, the controller of the negative-pressure source **104** can determine if a predetermined number of supply and vent cycles has been completed. The predetermined number of supply and vent cycles can be a standard number of cycles for therapy or can be a number of cycles entered in by a user. If therapy has not concluded, the method can continue on the NO path to block **1615**, where the negative-pressure source can be operated to supply negative pressure to the sealed space. If therapy has concluded, the method can continue on the YES path, where the method ends.

(115) FIG. **17** is a flow chart **1700** illustrating exemplary operations that can be associated with some embodiments of the therapy system **100** of FIG. **1**. For example, operations may be implemented by a controller in a negative-pressure source, such as the negative-pressure source **104**, configured to execute the operations. Operations may also be performed by a user, such as a clinician. At block **1701**, a user may examine a tissue site. For example, a clinician may examine the tissue site **103**.

(116) At block **1703**, the user may determine, based on the user's examination, a status of the debris of the tissue site. For example, a clinician may determine that the debris **130** covers the tissue site **103**. The status determination can also include: a thickness of the debris **130**, a consistency of the debris **130**, a color of the debris **130**, and a moisture level of the debris **130**. For example, the clinician may determine that the debris **130** at the tissue site **103** may have a thin, thick, runny, solid, rough, firm, smooth, heavy, or light consistency. The clinician may determine that the debris **130** at the tissue site **103** has a black, red, brown, green, yellow, gray, or other color that is indicative of a state of infection of the debris **130**. The clinician can also determine how moist the debris **130** at the tissue site **103** is on a scale ranging from no presence of liquid to saturated. In some embodiments, the determination of a moisture level aids a clinician in understanding how much exudate is present in the tissue site **103**.

(117) At block **1705**, the user may determine other parameters influencing treatment. For example, the clinician can determine a patient's pain tolerance, environment, preference, age, co-morbidities, quality of life, caregiver resources, and caregiver skills.

(118) At block **1707**, based on the information determined at block **1703** and block **1705**, the user can determine the desired targets for treatment of the debris at the tissue site. For example, the clinician can determine if the debris **130** comprises necrotic tissue, eschar, impaired tissue, other sources of infection, exudate, slough including hyperkeratosis, pus, foreign bodies, biofilm, or other types of bioburden. The clinician can also determine if treatment will reduce unpleasant odors, excess moisture, and the risk of infection of the debris **130** and the tissue site **103**.

(119) At block **1709**, in response to the determination of the desired targets for treatment of the debris at the tissue site, the user can select a contact layer having a firmness factor, a thickness, a through-hole shape, a through-hole size, and an array pattern to achieve the desired targets for treatment. For example, the clinician may select the contact layer **110** to have the thickness **134** greater than the thickness determined at block **1703**. The clinician can also select the contact layer **110** having circular through-holes **140** to permit the flow of the debris **130** having a yellowish color, a thick consistency, and a high moisture level. The clinician can further select a contact layer **110** having the through-holes **140** having a diameter greater than a size of the largest solubilized debris **130** in the tissue site **103**. In other embodiments, the clinician may select a contact layer **110**

having triangular through-holes **140**, for example, if the debris **130** is rough, black, and has a low moisture content.

(120) At block **1711**, in response to the determination of the desired targets for treatment of the debris at the tissue site, the user can select a retainer layer. For example, the clinician can select the retainer layer **108** having a firmness factor and a thickness. Generally, the thickness of the retainer layer **108** may be selected to fill the tissue site **103**. The clinician may select the firmness factor of the retainer layer **108** to limit the height of the nodules **139**. For example, if the debris **130** is thinner than the contact layer **110**, has a runny consistency, and has a smooth surface, the clinician may select a retainer layer **108** having a low firmness factor. A lower firmness factor of the retainer layer **108** may permit the bosses **137** to have a larger height than a retainer layer **108** having a high firmness factor, thereby decreasing the height of the nodules **139**. At block **1713**, the user may conduct treatment with contact layer. For example, the clinician may conduct treatment with the contact layer **110** and the therapy system **100**, after which the method concludes.

(121) The systems, apparatuses, and methods described herein may provide significant advantages. For example, combining the mechanical rubbing action of a contact layer with the hydrating and flushing action of instillation and negative-pressure therapy may enable low or no pain debridement of a tissue site. A contact layer as described herein may also require less monitoring from a clinician or other attendant as compared to other mechanical debridement processes and enzymatic debridement processes. In addition, contact layers as described herein may not become blocked by removed necrotic tissue as may occur during autolytic debridement of a tissue site. Furthermore, the contact layers described herein can aid in removal of necrosis, eschar, impaired tissue, sources of infection, exudate, slough including hyperkeratosis, pus, foreign bodies, debris, and other types of bioburden or barriers to healing. The contact layers can also decrease odor, excess wound moisture, and the risk of infection while stimulating edges of a tissue site and epithelialization. The contact layers described herein can also provide improved removal of thick exudate, allow for earlier placement of instillation and negative-pressure therapy devices, may limit or prevent the use of other debridement processes, and can be used on tissue sites that are difficult to debride.

(122) In some embodiments, the therapy system may be used in conjunction with other tissue removal and debridement techniques. For example, the therapy system may be used prior to enzymatic debridement to soften the debris. In another example, mechanical debridement may be used to remove a portion of the debris at the tissue site, and the therapy system may then be used to remove the remaining debris while reducing the risk of trauma to the tissue site.

(123) While shown in a few illustrative embodiments, a person having ordinary skill in the art will recognize that the systems, apparatuses, and methods described herein are susceptible to various changes and modifications. Moreover, descriptions of various alternatives using terms such as “or” do not require mutual exclusivity unless clearly required by the context, and the indefinite articles “a” or “an” do not limit the subject to a single instance unless clearly required by the context.

(124) The appended claims set forth novel and inventive aspects of the subject matter described above, but the claims may also encompass additional subject matter not specifically recited in detail. For example, certain features, elements, or aspects may be omitted from the claims if not necessary to distinguish the novel and inventive features from what is already known to a person having ordinary skill in the art. Features, elements, and aspects described herein may also be combined or replaced by alternative features serving the same, equivalent, or similar purpose without departing from the scope of the invention defined by the appended claims.

Claims

1. A system for debriding a tissue site, comprising: a cover adapted to form a sealed space over the tissue site for receiving a negative pressure from a negative-pressure source; and a tissue interface

having a manifold and a debridement tool, the manifold and the debridement tool being integral components of the tissue interface; the manifold adapted to deliver negative pressure to the tissue site; the debridement tool adapted to be positioned between the manifold and the tissue site, the debridement tool comprising a felted foam; a plurality of holes extending through the debridement tool, the plurality of holes being separated from each other by walls, the walls having transverse surfaces extending perpendicular to a surface of the debridement tool that form cutting edges with the surface of the debridement tool, and wherein the plurality of holes have a perforation shape factor that allows the plurality of holes to collapse from a relaxed position to a contracted position in response to an application of negative pressure to the sealed space and to return from the contracted position to the relaxed position in response to a removal of negative pressure from the sealed space; and the plurality of holes being adapted to generate macro-pressure points in the tissue site in the contracted position and the cutting edges being adapted to disrupt the macro-pressure points in the tissue site in response to movement of the debridement tool between the relaxed position and the contracted position.

2. The system of claim 1, wherein the plurality of holes are adapted to collapse from the relaxed position to the contracted position generally perpendicular to a line of symmetry of the debridement tool.
 3. The system of claim 1, wherein the plurality of holes have the perforation shape factor and a strut angle adapted to collapse the plurality of holes from the relaxed position to the contracted position.
 4. The system of claim 3, wherein the strut angle is about 90 degrees.
 5. The system of claim 3, wherein the strut angle is less than about 90 degrees.
 6. The system of claim 1, wherein: the plurality of holes are adapted to have the perforation shape factor and a strut angle that allows the plurality of holes to collapse from the relaxed position to the contracted position; and the plurality of holes are adapted to collapse from the relaxed position to the contracted position generally perpendicular to a line of symmetry of the debridement tool.
 7. The system of claim 1, further comprising a fluid source adapted to be fluidly coupled to the sealed space to provide fluid to the sealed space.
 8. The system of claim 1, wherein the plurality of holes have an average effective diameter of about 5 mm.
 9. The system of claim 1, wherein the plurality of holes are formed in two or more parallel rows.
 10. The system of claim 1, wherein the perforation shape factor of each hole of the plurality of holes is less than about 1.
 11. The system of claim 1, wherein a thickness of the debridement tool is about 15 mm.
 12. The system of claim 1, wherein a firmness factor of the debridement tool is about 5.
 13. The system of claim 1, wherein a firmness factor of the debridement tool is about 3.
 14. The system of claim 1, wherein a shape of each hole of the plurality of holes is hexagonal.
 15. The system of claim 1, wherein a shape of each hole of the plurality of holes is elliptical.
 16. The system of claim 1, wherein a shape of each hole of the plurality of holes is circular.
 17. The system of claim 1, wherein a shape of each hole of the plurality of holes is triangular.
-