

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409056
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Moss; Samuel et al.

Methods and devices for deploying and releasing a temporary implant within the body

Abstract

Methods, devices and systems for delivering a device assembly into a gastric or other space within the body, allowing the device to expand to occupy volume within the gastric space and, after an effective period of time, delivering a substance or stimulus to begin breakdown of the expanded device so that it may release from the body.

Inventors: Moss; Samuel (Natick, MA), Lake; Matthew S. (Natick, MA), Wecker; Jonathan (Natick, MA), Gaur; Shantanu K. (Natick, MA), Levy; Samuel G. (Natick, MA), Horwitz; Bruce A. (Natick, MA), Gwak; Jinyoung Daniel (Natick, MA)

Applicant: Allurion Technologies, LLC (Natick, MA)

Family ID: 53520357

Assignee: Allurion Technologies, LLC (Natick, MA)

Appl. No.: 18/452141

Filed: August 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240041628 A1	Feb. 08, 2024

Related U.S. Application Data

continuation parent-doc US 16909465 20200623 US 11766346 20230923 child-doc US 18452141
continuation parent-doc US 16102483 20180813 US 10729572 20200804 child-doc US 16909465
continuation parent-doc US 14642590 20150309 US 10182932 20190122 child-doc US 16102483
continuation-in-part parent-doc US 14069776 20131101 US 8974483 20150310 child-doc US 14642590

continuation-in-part parent-doc US 13773516 20130221 US 8870907 20141028 child-doc US 14069776
us-provisional-application US 61762196 20130207
us-provisional-application US 61699942 20120912
us-provisional-application US 61674126 20120720
us-provisional-application US 61663682 20120625
us-provisional-application US 61663683 20120625
us-provisional-application US 61663433 20120622
us-provisional-application US 61647730 20120516
us-provisional-application US 61645601 20120510
us-provisional-application US 61601384 20120221

Publication Classification

Int. Cl.: **A61F5/00** (20060101); **A61M39/22** (20060101)

U.S. Cl.:

CPC **A61F5/003** (20130101); **A61F5/0036** (20130101); **A61F5/0046** (20130101);
A61F5/0089 (20130101); **A61M39/227** (20130101);

Field of Classification Search

CPC: A61F (5/0003); A61F (5/0013); A61F (5/003); A61F (5/0033); A61F (5/0036); A61F (5/0043); A61F (5/0073)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2911988	12/1958	Ravn	N/A	N/A
3586018	12/1970	Bogardh et al.	N/A	N/A
3592207	12/1970	Borello	N/A	N/A
3638733	12/1971	De Rouville et al.	N/A	N/A
3853116	12/1973	Bucalo	N/A	N/A
4133315	12/1978	Berman et al.	N/A	N/A
4141771	12/1978	Barker et al.	N/A	N/A
4253201	12/1980	Ross	623/8	A61F 2/12
4370374	12/1982	Raabe et al.	N/A	N/A
4614188	12/1985	Bazell et al.	N/A	N/A
4636213	12/1986	Pakiam	623/8	A61B 90/94
4723547	12/1987	Kullas et al.	N/A	N/A
4732188	12/1987	Gabrlík et al.	N/A	N/A
4739758	12/1987	Lai et al.	N/A	N/A
4842007	12/1988	Kurtz	N/A	N/A
4899747	12/1989	Garren et al.	N/A	N/A
4949756	12/1989	Melinyshyn et al.	N/A	N/A

5018665	12/1990	Sulmone	N/A	N/A
5092847	12/1991	Pozzo	N/A	N/A
5181921	12/1992	Makita et al.	N/A	N/A
5222970	12/1992	Reeves	N/A	N/A
5336123	12/1993	Laske et al.	N/A	N/A
5348537	12/1993	Wiesner et al.	N/A	N/A
5496203	12/1995	Murray	N/A	N/A
5507808	12/1995	Becker	N/A	N/A
5595521	12/1996	Becker	N/A	N/A
5632297	12/1996	Sciullo et al.	N/A	N/A
5950624	12/1998	Hart	N/A	N/A
6162251	12/1999	Kredovski	N/A	N/A
6197005	12/2000	Gerlach et al.	N/A	N/A
6259953	12/2000	Lucchesi et al.	N/A	N/A
6367499	12/2001	Taku	N/A	N/A
6375972	12/2001	Guo et al.	N/A	N/A
6460541	12/2001	Shah et al.	N/A	N/A
6644336	12/2002	Dolan	N/A	N/A
6712832	12/2003	Shah	N/A	N/A
6814097	12/2003	Girouard	N/A	N/A
6939292	12/2004	Mizuno et al.	N/A	N/A
7169134	12/2006	Bills	N/A	N/A
7172613	12/2006	Wazne	N/A	N/A
7485093	12/2008	Glukhovsky	N/A	N/A
7854745	12/2009	Brister et al.	N/A	N/A
8183227	12/2011	Perrin et al.	N/A	N/A
8202291	12/2011	Brister et al.	N/A	N/A
8282666	12/2011	Birk	N/A	N/A
8287562	12/2011	Kasic, II	N/A	N/A
8292911	12/2011	Brister et al.	N/A	N/A
8585676	12/2012	Shah	N/A	N/A
8628571	12/2013	Hacohen et al.	N/A	N/A
8740845	12/2013	Shah et al.	N/A	N/A
8784486	12/2013	Schuessler	N/A	N/A
8814898	12/2013	Gaur et al.	N/A	N/A
8870907	12/2013	Gaur et al.	N/A	N/A
8974483	12/2014	Gaur et al.	N/A	N/A
9387107	12/2015	Gaur et al.	N/A	N/A
9463106	12/2015	Khieu et al.	N/A	N/A
9662239	12/2016	Brister et al.	N/A	N/A
9827128	12/2016	Brister et al.	N/A	N/A
9827129	12/2016	Gaur et al.	N/A	N/A
9849018	12/2016	Wecker et al.	N/A	N/A
10182932	12/2018	Moss et al.	N/A	N/A
10238516	12/2018	Singh et al.	N/A	N/A
10307279	12/2018	Wecker et al.	N/A	N/A
10470908	12/2018	Nelson et al.	N/A	N/A
10583024	12/2019	Nelson et al.	N/A	N/A
10588768	12/2019	Nelson et al.	N/A	N/A
10729572	12/2019	Moss et al.	N/A	N/A

10786379	12/2019	Gaur et al.	N/A	N/A
11098813	12/2020	Nelson	N/A	N/A
11497900	12/2021	Chadwick et al.	N/A	N/A
11559418	12/2022	Nelson et al.	N/A	N/A
11766346	12/2022	Moss et al.	N/A	N/A
11828377	12/2022	Nelson	N/A	N/A
12109138	12/2023	Nelson et al.	N/A	N/A
2001/0018929	12/2000	Taku	N/A	N/A
2002/0183777	12/2001	Shannon	N/A	N/A
2002/0198470	12/2001	Imran et al.	N/A	N/A
2003/0106583	12/2002	Weng	N/A	N/A
2003/0171768	12/2002	McGhan	N/A	N/A
2003/0229263	12/2002	Connors et al.	N/A	N/A
2003/0229384	12/2002	Mon	N/A	N/A
2004/0044353	12/2003	Gannoe	N/A	N/A
2004/0073249	12/2003	Trotta	N/A	N/A
2004/0101540	12/2003	Cooker	N/A	N/A
2004/0146559	12/2003	Sowden et al.	N/A	N/A
2004/0186502	12/2003	Sampson et al.	N/A	N/A
2005/0027261	12/2004	Weaver et al.	N/A	N/A
2005/0033331	12/2004	Burnett et al.	N/A	N/A
2005/0055039	12/2004	Burnett	606/151	A61B 17/12022
2005/0096750	12/2004	Kagan et al.	N/A	N/A
2005/0150548	12/2004	Kita et al.	N/A	N/A
2006/0004323	12/2005	Chang et al.	N/A	N/A
2006/0058829	12/2005	Sampson et al.	N/A	N/A
2006/0222705	12/2005	Flanner et al.	N/A	N/A
2007/0010791	12/2006	Drechsler et al.	N/A	N/A
2007/0078476	12/2006	Hull, Sr. et al.	N/A	N/A
2007/0207199	12/2006	Sogin	424/451	A61K 9/0065
2007/0250094	12/2006	Makower et al.	N/A	N/A
2008/0195226	12/2007	Williams et al.	N/A	N/A
2008/0241094	12/2007	Burnett et al.	N/A	N/A
2008/0243071	12/2007	Quijano et al.	N/A	N/A
2008/0249635	12/2007	Weitzner et al.	N/A	N/A
2008/0269555	12/2007	Paganon et al.	N/A	N/A
2008/0276992	12/2007	Nomichi et al.	N/A	N/A
2008/0306441	12/2007	Brown et al.	N/A	N/A
2009/0024227	12/2008	Lesh	N/A	N/A
2009/0048684	12/2008	Lesh	623/23.72	A61M 29/02
2009/0118756	12/2008	Valencon	N/A	N/A
2009/0192535	12/2008	Kasic	N/A	N/A
2009/0259246	12/2008	Eskaros	606/192	A61F 5/003
2009/0275919	12/2008	Todd et al.	N/A	N/A
2009/0277515	12/2008	Pechtold	N/A	N/A
2009/0299327	12/2008	Tilson et al.	N/A	N/A
2010/0062057	12/2009	Berge et al.	N/A	N/A
2010/0100116	12/2009	Brister et al.	N/A	N/A
2010/0110311	12/2009	Sade et al.	N/A	N/A

2010/0114311	12/2009	Becker	N/A	N/A
2010/0121224	12/2009	Toyota et al.	N/A	N/A
2010/0137897	12/2009	Brister	156/227	A61L 31/088
2010/0168511	12/2009	Muni et al.	N/A	N/A
2010/0174307	12/2009	Birk	N/A	N/A
2010/0193050	12/2009	Job	N/A	N/A
2010/0243065	12/2009	Zweber	N/A	N/A
2010/0246165	12/2009	Diaz et al.	N/A	N/A
2010/0274194	12/2009	Sobelman et al.	N/A	N/A
2011/0004236	12/2010	Priplata et al.	N/A	N/A
2011/0112383	12/2010	Voss et al.	N/A	N/A
2011/0275882	12/2010	Hutzenlaub et al.	N/A	N/A
2012/0141544	12/2011	Fuisz et al.	N/A	N/A
2012/0141545	12/2011	Fuisz et al.	N/A	N/A
2012/0232576	12/2011	Brister et al.	N/A	N/A
2012/0273050	12/2011	Metzger et al.	N/A	N/A
2013/0012980	12/2012	Brister et al.	N/A	N/A
2013/0035711	12/2012	Schwab et al.	N/A	N/A
2013/0165873	12/2012	Morriss et al.	N/A	N/A
2013/0190796	12/2012	Tilson et al.	N/A	N/A
2013/0218190	12/2012	Gaur et al.	N/A	N/A
2013/0267984	12/2012	Gaur et al.	N/A	N/A
2013/0289604	12/2012	Brister et al.	N/A	N/A
2013/0296751	12/2012	Martin et al.	N/A	N/A
2014/0012363	12/2013	Franano et al.	N/A	N/A
2014/0066967	12/2013	Levy et al.	N/A	N/A
2014/0074142	12/2013	Khieu et al.	N/A	N/A
2014/0180252	12/2013	Gabriel	N/A	N/A
2014/0188151	12/2013	Gaur et al.	N/A	N/A
2014/0296903	12/2013	Gaur et al.	N/A	N/A
2015/0196408	12/2014	Moss et al.	N/A	N/A
2015/0305746	12/2014	Johnson et al.	N/A	N/A
2016/0010758	12/2015	Nomichi et al.	N/A	N/A
2016/0045719	12/2015	Ha et al.	N/A	N/A
2016/0109029	12/2015	Dulin	N/A	N/A
2016/0278957	12/2015	Gaur et al.	N/A	N/A
2017/0211715	12/2016	Balmaceda et al.	N/A	N/A
2017/0312111	12/2016	Sharma et al.	N/A	N/A
2018/0042747	12/2017	Gaur et al.	N/A	N/A
2018/0071127	12/2017	Wecker et al.	N/A	N/A
2018/0236203	12/2017	Franklin et al.	N/A	N/A
2018/0311484	12/2017	Lake et al.	N/A	N/A
2018/0344498	12/2017	Moss et al.	N/A	N/A
2019/0076152	12/2018	Franklin et al.	N/A	N/A
2019/0262157	12/2018	Nelson et al.	N/A	N/A
2019/0388258	12/2018	Nelson et al.	N/A	N/A
2019/0388259	12/2018	Nelson et al.	N/A	N/A
2020/0011442	12/2019	Nelson	N/A	N/A
2020/0155335	12/2019	Nelson et al.	N/A	N/A

2020/0188644	12/2019	Chadwick et al.	N/A	N/A
2020/0323672	12/2019	Moss et al.	N/A	N/A
2021/0341069	12/2020	Nelson	N/A	N/A
2023/0120118	12/2022	Nelson et al.	N/A	N/A
2024/0084908	12/2023	Nelson	N/A	N/A
2024/0342366	12/2023	Nelson et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2925648	12/2006	CA	N/A
2865056	12/2012	CA	N/A
1387418	12/2001	CN	N/A
101384231	12/2008	CN	N/A
201977967	12/2010	CN	N/A
102883684	12/2012	CN	N/A
106029013	12/2015	CN	N/A
2139439	12/2009	EP	N/A
2817062	12/2013	EP	N/A
3117865	12/2016	EP	N/A
3720395	12/2019	EP	N/A
201514322	12/2014	GB	N/A
2008-513132	12/2007	JP	N/A
2008-515464	12/2007	JP	N/A
2010-523280	12/2009	JP	N/A
2011-517611	12/2010	JP	N/A
2016-030000	12/2015	JP	N/A
WO 2000/012167	12/1999	WO	N/A
WO 2004/075795	12/2003	WO	N/A
WO 2006/020929	12/2005	WO	N/A
WO 2009/059802	12/2008	WO	N/A
WO 2009/059803	12/2008	WO	N/A
WO 2011/106157	12/2010	WO	N/A
WO 2013/126593	12/2012	WO	N/A
WO 2014/074625	12/2013	WO	N/A
WO 2015/066545	12/2014	WO	N/A
WO 2016/145076	12/2015	WO	N/A
WO 2017/136840	12/2016	WO	N/A
WO 2018/142761	12/2017	WO	N/A
WO 2019/112768	12/2018	WO	N/A
WO 2019/165449	12/2018	WO	N/A
WO 2020/010359	12/2019	WO	N/A
WO 2020/123916	12/2019	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 16/909,465, filed Jun. 23, 2020. cited by applicant
U.S. Appl. No. 14/069,776 filed Nov. 1, 2013. cited by applicant
U.S. Appl. No. 14/642,590 filed Mar. 9, 2015. cited by applicant
U.S. Appl. No. 16/102,483 filed Aug. 13, 2018. cited by applicant
U.S. Appl. No. 13/773,516 filed Feb. 21, 2013. cited by applicant

Primary Examiner: Ton; Martin T

Attorney, Agent or Firm: Levine Bagade Han LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. Patent Application No. continuation of U.S. patent application Ser. No. 16/909,465 filed Jun. 23, 2020, which is a continuation of U.S. patent application Ser. No. 16/102,483 filed Aug. 13, 2018 (now U.S. Pat. No. 10,729,572), which is a continuation of U.S. patent application Ser. No. 14/642,590 filed Mar. 9, 2015 (now U.S. Pat. No. 10,182,932), which is a continuation-in-part of U.S. patent application Ser. No. 14/069,776 filed Nov. 1, 2013 (now U.S. Pat. No. 8,974,483) entitled Methods and Devices for Deploying and Releasing a Temporary Implant Within the Body, which is a continuation-in-part of U.S. patent application Ser. No. 13/773,516 filed Feb. 21, 2013 (now U.S. Pat. No. 8,870,907), which is a non-provisional of U.S. Provisional Applications Nos.: No. 61/762,196 filed Feb. 7, 2023 entitled Thermally Degradable Biocompatible Constructs and Methods of Degrading filed; 61/601,384 filed Feb. 21, 2012 entitled Swallowed Intra-gastric Balloon Filled via Narrow Extracorporeal Tube; 61/645,601 filed May 10, 2012 entitled Delivery String for Gastrointestinal Applications; 61/647,730 filed May 16, 2012 entitled Hydrogel Driven Valve; 61/663,433 filed Jun. 22, 2012 entitled Fluid Transfer Device for Hydrogel Constructs; 61/663,682 filed Jun. 25, 2012 entitled Hydrogel Driven Valve; 61/663,683 filed Jun. 25, 2012 entitled Fluid Transfer Device for Hydrogel Constructs; No. 61/674,126 filed Jul. 20, 2012 entitled Payload Delivery System and Method; and 61/699,942 filed Sep. 12, 2012 entitled System for Rapid Hydrogel Construct Degradation; the entirety of each of which is incorporated by reference.

BACKGROUND OF THE INVENTION

(1) The present invention generally relates to the field of devices that temporarily occlude spaces within the body to provide a therapeutic effect.

(2) According to 2010 World Health Organization data, 198 million Americans over the age of 15 are above target weight. Of these individuals, 89 million are considered overweight ($25 < \text{Body Mass Index} < 30$) and 109 million are considered obese ($\text{Body Mass Index} > 30$). Worldwide, more than 1.4 billion adults age 20 and over are overweight, and 500 million are obese. Obesity places patients at increased risk of numerous, potentially disabling conditions including type 2 diabetes, heart disease, stroke, gallbladder disease, and musculoskeletal disorders 1,2,3. Compared with healthy weight adults, obese adults are more than three times as likely to have been diagnosed with diabetes or high blood pressure 4. In the United States it is estimated that one in five cancer-related deaths may be attributable to obesity in female non-smokers and one in seven among male non-smokers (≥ 50 years of age). On average, men and women who were obese at age 40 live 5.8 and 7.1 fewer years, respectively, than their healthy weight peers.

(3) Gastric bypass surgery is the current gold standard treatment for patients with a body mass index (“BMI”) of greater than 40. Gastric bypass surgery is also an option for those with a BMI between 35-39 with obesity-related co-morbidities. While gastric bypass surgery results in decreased food consumption and weight loss for a majority of recipients, it requires life-altering, permanent anatomic modifications to the gastrointestinal tract and can result in severe complications. Gastric bypass and related surgical procedures are also expensive, costing about

\$22,500 (by laparoscopy). For these reasons, only about 250,000 surgical obesity procedures are performed per year in the US.

(4) For the vast majority of the overweight and obese population for whom surgical obesity procedures are not appropriate, few efficacious and affordable interventions are currently available. Diet and exercise remain the front line approaches to obesity, however this approach has at best slowed the growth of the epidemic. To date, drug therapies have dose limiting side effects or have lacked meaningful long term efficacy.

(5) One less-invasive intervention that has begun to gain popularity is an intragastric balloon. Intragastric balloons can be placed endoscopically or positioned using other methods and generally must be removed endoscopically or rely on the body's natural digestive processes for removal.

(6) The devices, methods, and systems discussed herein are intended to provide an effective treatment for obesity. Moreover, the devices, methods, and systems described herein are not limited to any particular patient population and can even be applied to clinical areas outside of obesity.

SUMMARY OF THE INVENTION

(7) The present invention relates to devices and methods for occupying a space within a patient's body. In particular, the devices and methods can be used within a gastric space. However, the devices and methods can be used in any part of the body.

(8) The devices described herein can also be used for delivery of drugs, pharmaceuticals, or other agents where such items can be delivered on a skin of the device, within a reservoir, in a filler of the device, or anywhere on the device. Such agents can be released over time.

(9) The present disclosure includes medical devices for use with a liquid filler material and for occupying a space within the patient's body. In one example, the medical device is a device for occupying a space within a patient's body and for use with a fluid delivery conduit that allows transport of a fluid into the medical device. For example, such a device can include a device body defining an reservoir; a tunnel member having an elongate flattened shape, the tunnel member comprising a first open end located within the reservoir and a second open end located exterior to the reservoir, the tunnel member having at least two interior opposing surfaces that define a tunnel lumen extending longitudinally between the first open end and the second open end; and where the tunnel lumen is sized to slidably receive the fluid delivery conduit within the second open end such that the fluid delivery conduit separates the interior opposing surfaces deforming the elongate flattened shape to an elongated expanded shape; wherein removal of the fluid delivery member causes the tunnel member to revert to the elongate flattened shape such that the interior opposing surfaces move together to narrow the tunnel lumen and increase a resistance to fluid flow through the tunnel lumen.

(10) In one example, the tunnel member comprises a flexible thin wall material such that the lumen can self-close to prevent fluid flowing therethrough when the fluid delivery conduit is removed therefrom. In additional variations, the increasing pressure within the reservoir caused by addition of a liquid or gas increases the resistance to fluid flow through the tunnel lumen.

(11) In an additional variation, the medical device further comprises a substance within the tunnel member that increases the resistance to fluid flow through the tunnel lumen upon removal of the fluid delivery conduit. Such a substance can be a hygroscopic material, a material swells upon contact with the patients bodily fluids or a liquid within the reservoir, a low-solubility material, a bio-compatible lubricant, and/or a viscous material where after removal of the fluid delivery member a cohesion of the viscous material increases a force required to separate the interior opposing surfaces.

(12) The tunnel member can include a first layer and a second layer sealed along at least a first longitudinal edge, the tunnel lumen being adjacent to the longitudinal edge. In an additional variation, the tunnel includes a second longitudinal edge adjacent to the tunnel lumen and opposite to the first longitudinal edge, where the first layer and second layer are sealed along the second longitudinal edge.

(13) Variations of the device include a mechanical attachment coupling the fluid delivery member to a portion of the tunnel member. The mechanical attachment can comprise a suture, and/or a mechanical or chemical bond.

(14) In some variations, a diameter of the tunnel lumen is constant. In alternate variations, the diameter of the tunnel lumen varies within the tunnel member. Additional variations include a tunnel member having at least one pocket in fluid communication with the tunnel lumen where the at least one pocket is configured to retain a substance therein.

(15) The second open end of the tunnel member can be at least even with an outer perimeter of the device body. Alternatively, or in combination, the tunnel member comprises a detachable section having a reduced tensile strength region, such that application of a tensile force causes detachment of the detachable section.

(16) The present disclosure also includes variations of medical devices for occupying a space within a patient's body. In one such example, such a medical device includes a device body defining an reservoir; a fluid delivery conduit that allows transport of a fluid into the reservoir; a tunnel member having an elongate flattened shape, the tunnel member comprising a first open end located within the reservoir and a second open end located exterior to the reservoir, the tunnel member having at least two interior opposing surfaces that define a tunnel lumen extending longitudinally between the first open end and the second open end; and where the tunnel lumen is sized to slidably receive the fluid delivery conduit within the second open end such that the fluid delivery conduit separates the interior opposing surfaces deforming the elongate flattened shape to an elongated expanded shape; wherein removal of the fluid delivery member causes the tunnel member to revert to the elongate flattened shape such that the interior opposing surfaces move together to narrow the tunnel lumen and increase a resistance to fluid flow through the tunnel lumen.

(17) In another variation, a device can include a medical device for occupying a space within a patient's body and for use with a fluid delivery conduit that allows transport of a fluid into the medical device, the medical device comprising: a device body defining an reservoir; a fluid valve having an elongate flattened shape, the fluid valve comprising an internal open end located within the reservoir and an external open end located exterior to the reservoir, the fluid valve having an elongate flattened passage extending longitudinally between the external open end and the internal open end, where the flattened passage is defined by at least two opposing segments of a fluid impermeable interior surface, where the elongate flattened passage includes a lumen extending therethrough such that the lumen remains occluded until separation of the at least two opposing segments; and where the passage is sized to slidably receive the fluid delivery conduit within the external open end such that the fluid delivery conduit separates the interior opposing segments deforming the elongate flattened shape into the elongated lumen; wherein removal of the fluid delivery conduit causes the fluid valve to revert to the elongate flattened shape such that the interior opposing segments move together to narrow the lumen and increase a resistance to fluid flow through the lumen.

(18) A variation of the fluid valve can include a flexible thin wall material such that increasing a pressure within the reservoir increases the resistance to fluid flow through the tunnel lumen. The fluid valve can include a substance within the fluid valve wherein the substance increases the resistance to fluid flow through the tunnel lumen upon removal of the fluid delivery conduit.

(19) The substance can comprise a viscous material such that after removal of the fluid delivery conduit a cohesion of the viscous material increases a force required to separate the interior opposing segments.

(20) The fluid valve can include a detachable section having a reduced tensile strength region, such that application of a tensile force causes detachment of the detachable section. The fluid valve can also be attached to an interior surface of the device body.

(21) The present disclosure also includes a fluid fill valve for use with a medical device for

occupying a space within a patient's body and for use with a fluid delivery conduit. In one example such a valve includes a first layer of fluid impermeable membrane and a second layer of fluid impermeable membrane, wherein a portion of the layers are sealingly joined to form a valve body, the valve body having an internal end disposed inside the device and an external end external to or at the surface of the device; and wherein the first layer and second layer include an unsealed region that forms a lumen region longitudinally extending in the valve body from the internal end to the external end; where the first layer and second layer are configured to join together in the lumen region reducing a diameter of the lumen region to resist passage fluids therethrough, where the lumen region is configured to permit advancement of the fluid delivery conduit therethrough.

(22) In one variation of the valve the first fluid impermeable membrane has a length and a width and two lengthwise edges and where the second fluid impermeable membrane has a length and a width and two lengthwise edges, the length and width being substantially the same as the first fluid impermeable membrane.

(23) The above and other features of the invention including various novel details of construction and combinations of parts, and other advantages, will now be more particularly described with reference to the accompanying drawings and pointed out in the claims. It will be understood that the particular method and device embodying the invention are shown by way of illustration and not as a limitation of the invention. The principles and features of this invention may be employed in various and numerous embodiments without departing from the scope of the invention. In addition, aspects of the variations, as well as the variations themselves can be combined such that the combination is within the scope of this disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The foregoing and other objects, features and advantages of the methods, devices, and systems described herein will become apparent from the following description in conjunction with the accompanying drawings, in which reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale; emphasis has instead been placed upon illustrating the principles of the invention. Of the drawings:

(2) FIG. 1A, illustrates an example of a gastric device assembly prior to assuming an active profile.

(3) FIGS. 1B and 1C show partial cutaway views of examples of device assemblies for use in occupying space within a body.

(4) FIG. 1D illustrates the variation of the device shown in FIG. 1A as the device assembly assumes an active profile.

(5) FIG. 1E shows a device assembly after it is inflated, expanded, or otherwise transitioned to achieve a desired active profile.

(6) FIG. 1F illustrates a state of a device assembly after a physician, patient, or other caregiver desires to initiate release the device assembly from the body.

(7) FIG. 2 shows a device assembly or construct in a hydrated or active profile whose outer "skin" defines a material reservoir or pocket.

(8) FIG. 3 illustrates a variation of a fluid transfer member also having a sealable fluid path for use with the device assemblies described herein.

(9) FIG. 4 shows a schematic perspective view of a variation of a tunnel member being installed during fabrication of the device assembly.

(10) FIG. 5 illustrates a partial view of a variation of an inverted section of a skin of a device assembly closed by a release material.

(11) FIG. 6 illustrates a cutaway view of the interior of a device assembly comprising an inverted section of the skin further that opens the device to release the contents of the device.

(12) FIG. 7 provides a schematic illustration of another example of a device assembly having a release material located on a surface of the skin.

(13) FIG. 8 shows an additional variation of a portion of a device assembly that provides a control over the fluid permeable path through otherwise impermeable material surface.

(14) FIGS. 9A and 9B an example of a valve driven by expansion of filler material within a reservoir of the device assembly.

(15) FIGS. 9C and 9D show another variation of the valve of FIG. 9A comprising catheter passage holes.

(16) FIG. 9E shows a variation of a valve comprising demilunar hybrid flow control layers in which the impermeable region and permeable region are semicircular.

(17) FIG. 10A illustrates a variation of a tunnel member as discussed above that forms a sealable fluid path preventing material from escaping from the interior of the device.

(18) FIG. 10B shows a schematic cross sectional view of tunnel taken along line 10B-10B of FIG. 10A.

(19) FIGS. 10C and 10D show schematic cross sectional views of two variations of the tunnel member of FIG. 10A

(20) FIG. 10E shows the tunnel in its closed configuration after the conduit is removed.

(21) FIGS. 10F to 10I show a conduit that is mechanically coupled to a tunnel member.

(22) FIG. 10J to 10L show a schematic cross-sectional view of a tunnel member including a tunnel substance between layers of the tunnel member and a conduit taken along line 10H-10H of FIG. 10B

(23) FIGS. 10M and 10N shows the use of a spring loaded closure device that aids in sealing of a tunnel member.

(24) FIG. 11A is a plan view of a variation of the device in mid-fabrication in which the two layers of the tunnel member are fabricated as part of the upper and lower skins of the device.

(25) FIG. 11B is an exploded cross-sectional view of the device of FIG. 14A taken along line 14B-14B.

(26) FIG. 12 shows a device assembly compressed to fit within an oral dosage form such as a pill, capsule, sleeve, or other form that enhances the ability of positioning the device via ingestion or swallowing without the aid of another medical device.

DETAILED DESCRIPTION OF THE INVENTION

(27) The following illustrations are examples of the invention described herein. It is contemplated that combinations of aspects of specific embodiments or combinations of the specific embodiments themselves are within the scope of this disclosure. While the methods, devices, and systems described herein are discussed as being used in the stomach or gastric space, the devices, methods, and systems of the present disclosure can be used in other parts of the body where temporary occlusion of a space might be required or beneficial. The present disclosure is related to commonly assigned to US Publication No. 2011/0295299 filed Mar. 2, 2011, the entirety of which is incorporated by reference.

(28) FIG. 1A, illustrates an example of a gastric device assembly **100**. In this example, the gastric device assembly or construct **100** can reside in a stomach (typically of a mammal) for an extended period of time. One benefit of such a device is that, when partially or fully deployed, the construct **100** occupies volume within the stomach to produce a therapeutic effect, e.g., to stimulate the sensation of satiety, and resists passage from the body by normal body function. As illustrated below the construct generally comprises three states: a pre-deployment configuration (FIG. 1A); a deployed or active configuration (FIG. 1D, 1E); and a release configuration (FIG. 1F). As noted above, the device can also be used for therapeutic benefits that do not involve occupying volume (e.g., drug delivery, creation of a cavity by separating adjacent tissue, etc.).

(29) FIG. 1A illustrates a variation of the device **100** after placement within a stomach **2**. As described herein, the initial configuration of the device **100** includes a compact state that allows

placement within the body. The device can be in a pill-type configuration or any other shape that permits swallowing. Alternatively, the device **100** can be positioned by the use of a scope type device, catheter, or other medical positioning device.

(30) For a device used in the digestive tract/gastric space, the device assembly **100** can be positioned within the body either by natural ingestion or the use of a delivery system (such as a catheter, endoscope, or other medical device). The delivery system can optionally comprise an oral dosage form, not illustrated, which facilitates the ingestion of a relatively large object. In other embodiments the system comprises a tether that allows manipulation or control of the placed construct from outside of the body. The assembly **100** can also be placed in the stomach by more invasive surgical or endoscopic procedures.

(31) In FIG. **1A**, the device **100** is shown immediately after being deployed within the stomach **2** and is ready to be activated. As noted herein, the device **100** can be deployed in the configuration shown. Alternatively, the device can be contained within a capsule or pill-type casing that allows for swallowing by a patient. Once swallowed, the casing will readily dissolve or break down resulting in the configuration shown. Once in place in the stomach, the assembly **100** begins to expand in order to occupy volume/space within the body. Expansion can occur via manual inflation, including hydration or other activation of a filler material (as shown optionally using a catheter, inflation tube or other delivery system), via absorption of body fluids, via remote actuation of a substance already located within the device assembly, and/or delivering of a fluid into the assembly, where the fluid itself causes expansion. Variations of the device also include a combination of such expansion means.

(32) The variation shown in FIG. **1A** includes a member **110** that extends from the device **100** to outside of the patient. In this variation shown, the member **110** comprises a fluid transport member that is fluidly coupled to an interior of the device **100** allowing for the delivery of substances and/or fluids within the device **100**. FIG. **1A** shows an exemplary fluid source **90** coupleable to a variation of a fluid transport member **110** such that the delivery of fluid causes a filler material **108** within the device to expand. In the illustrated example, the fluid transport member comprises a conduit. However, alternate variations of the devices described herein include fluid transport members that reside within the patient's body. Alternate variations of the device **100** also include members **110** that function as delivery or positioning systems to ensure proper placement of the device **100** within the body. Such delivery systems may or may not be fluidly coupled with an interior of the device. In variations discussed below, the device can include one or more fluid transport members that remain within the body but still convey fluid into the device **100** to allow the device to assume an active profile.

(33) FIG. **1B** shows one a partial cutaway view of an example of a device assembly **100** for use in occupying space within a body. In this variation, the device assembly **100** includes a material surface or skin **102** that forms a reservoir or pocket **104** capable of retaining a variety of substances, including but not limited to fluids, solid substances, semi-solid substances, etc. In the illustrated variation, the reservoir **104** holds a filler material **108** such as dehydrated hydrogel granules that can swell in size upon the addition of a fluid. However, any number of substances can be contained within the reservoir **104**. Alternate variations of the device and/or method include assemblies that do not include a filler material; rather a filler material can be deposited within the reservoir **104** once the assembly is deployed. Alternatively, or in combination, the reservoir can be filled with a gas, liquid or other gel type substance.

(34) In other variations, the device assembly **100** can include an empty reservoir that can be deployed into the body and subsequently filled with a filler material or other substance. For example, such variations can include a liquid filler material that is delivered to the reservoir through a conduit. The volume of liquid required to expand the device into a desired active profile can pre-determined. In some variations, the volume can be determined by measuring the back pressure in the conduit or pressure within the reservoir using any number of pressure detecting

elements.

(35) FIG. 1B also illustrates a variation of a sealable fluid path **112** coupled to and/or forming part of the fluid transfer member. In this example, the sealable fluid path **112** extends outside of the perimeter of the skin **102** of the device **100**. Additional variations of the device **100** can include significantly shortened sealable fluid paths **112**. In yet additional variations, the device assembly **100** can omit the sealable fluid path **112**.

(36) As noted herein, the skin **102** includes a release material **106** coupled thereto, where the release material **106** allows for initiating release of the assembly **100** from the body shortly after degradation, activation, or breakdown of the release material. Once the device assembly **100** is in the active profile, it can remain in the active profile for a pre-determined amount of time or until the patient experiences a desired therapeutic effect. To initiate release of the device assembly **100** from the body, an exogenous material, substance or stimulus is administered to the patient. The substance can comprise a fluid or other activating agent having properties that either directly or indirectly act on the release material to disrupt the barrier and allow the contents of the reservoir to be exposed to the body. For example, the exogenous substance can comprise a heated fluid that melts the release material. Alternatively, the exogenous material can change a temperature and/or an acidity of fluids in the stomach such that the enhanced properties of the fluids begin to act, either directly or indirectly, upon the release materials. In additional variations, the release material can comprise a material or materials that effectively form a barrier as discussed herein and are separated or disengaged by the use of an exogenous stimuli (e.g., a magnetic field, ultrasound, IR heating, coherent light, electromagnetic signals, microwave field, etc.).

(37) FIG. 1B also illustrates a variation where the release material **106** is in the form that approximates shape and/or size of the casing used to deliver the device **100** (in this example the release material **106** is in a pill shape). One benefit of such a configuration is that the release material **106** can be positioned within the casing without excessive folding or bending.

(38) FIG. 1C illustrates a sectional view of another variation of a device assembly **100**. In this variation, the release material **106** binds or otherwise joins edges of the skin from within the reservoir **104**. Such a configuration protects the release material **106** from the local environment of the body (e.g., fluids within the stomach or digestive tract). The release material can still be activated and/or degraded by the addition of the exogenous material to the body as described herein. However, positioning of the release material within the reservoir permits the skin **102** to serve as an additional layer of protection to prevent inadvertent release of the device assembly **100**. The release material **106** can comprise a layer that binds edges of the skin together.

(39) FIG. 1C also illustrates a variation of a sealable fluid path **112**. In this example, the sealable fluid path **112** does not extend outside of the perimeter of the skin **102**. Additional variations of the device **100** can include significantly shortened sealable fluid paths **112**. In yet additional variations, the device assembly **100** can omit the sealable fluid path **112**.

(40) FIG. 1D illustrates the variation of the device **100** shown in FIG. 1A as the device assembly **100** assumes an active profile. In this example, the device **100** does not include a filler material **108** as depicted in FIGS. 1C, instead, the filler material can comprise a liquid, gas, gel, or other substance that is delivered through the conduit **114** and/or sealable fluid path **112**. An active profile includes any profile apart from a deployment state and where the profile allows the device to perform the intended effect of occupying volume or space within the body to produce a therapeutic effect. In the illustrated example, a physician or other medical practitioner delivers fluid via the fluid transport member **110**, comprising a conduit **114** in this variation, and into the reservoir **104**. As noted herein, other variations include device assemblies with a filler material where the conduit **114** simply delivers fluid, causing the filler material **108** to swell to achieve an active profile.

(41) When using a conduit **114** that extends outside of the body, a physician can deliver a hydrating liquid, such as water or distilled water through the conduit **114**. Generally, a pre-determined volume of liquid can be manually or mechanically pumped into the exterior end of the conduit

wherein the volume of liquid is pre-determined based on a particular size of the device assembly or based on a desired active state. In some variations, the volume of liquid can also depend on the length of conduit.

(42) The conduit **114** can be used to transfer a substance or into the reservoir **104** of the device. In the illustrated variation, the conduit **114** transfers fluid from outside of the patient's body into the reservoir **104** after deployment of device assembly **100** within the body. Alternatively, or in combination, a fluid transfer member can comprise a wick type device that transfers liquids or other fluids from within the body to the reservoir.

(43) FIG. 1E shows the device assembly **100** after it is inflated, expanded, or otherwise transitioned to achieve a desired active profile. A physician can monitor the profile of the device assembly **100** either using a scope positioned within the stomach (not shown) or non-invasive imaging such as ultrasound or a radiographic imaging. Alternatively, or in combination, the active profile can be achieved after a pre-determined volume of fluid, liquid and/or gas is delivered to the reservoir **104**. Furthermore, variations of the device can include one or more markers (such as radiopaque markers) **116** allowing a physician to determine orientation and/or size of the device assembly **100**.

(44) As noted above, this particular variation of the assembly **100** includes a conduit **114** that is coupled to the skin **102** through the fluid path **112** and extends into the reservoir **104**. Alternatively, a conduit **114** can be directly coupled to the skin. When the device assembly **100** achieves the active state the conduit **114** can be pulled from the device assembly **100**. For those variations that employ a sealable fluid path **112**, withdrawal of the conduit **114** causes the sealable fluid path **112** to collapse or be compressed thereby preventing the contents of the reservoir **104** from escaping from the device assembly **100**. Alternatively, or in combination, the sealable fluid path **112** located within the reservoir **104** can be sealed due to the increased pressure within the reservoir. In other words, the same pressure within the reservoir **104** that causes expansion of the device **100** also causes the sealable fluid path **112** to close, compress or otherwise reduce in diameter to a sufficient degree that material is unable to escape from the reservoir through the sealable fluid path **112**.

(45) In certain variations, the conduit **114** is held in place in the sealable fluid path **112** by friction alone. Withdrawal of conduit occurs by pulling on the conduit in a direction away from the device **100**. During the initial stages of this withdrawal activity the expanded device **100** generally moves upwardly with the conduit in the stomach, until the expanded device **100** reaches the esophageal sphincter. With the device assembly restrained from further upward movement by the sphincter, the conduit **114** may then be withdrawn from the fluid path and from the patient by additional pulling force.

(46) Upon withdrawal of conduit **114** the fluid path effectively seals, as described herein, and prevents migration of fluids or other substances into and out of the reservoir. In certain variations the fluid path seals on its own after removal of a conduit or other member located therein. In additional variations, hydrostatic pressure and/or pressure caused by the expanded filler acting along the length of the fluid path can aid in sealing of the fluid path.

(47) FIG. 1F illustrates a state of the device assembly **100** (where this variation, unlike the variation of FIGS. 1D and 1E, includes a filler material **108** that swells within the device) after a physician or the patient desires to initiate release the device assembly **100** from the body. As discussed above, an exogenous material **120** is delivered into the stomach (or other portion of the body as applicable). As the exogenous material **120** (or exogenously activated body fluids) engage the release material **106**, the release material reacts to the conditions created by the exogenous material and begins to degrade, melt, break down, or otherwise become unstable such that the physical barrier of the skin **102** becomes compromised. As noted above, additional variations of the devices can be used with an exogenous stimulus in place of or in addition to an exogenous material. For example, the exogenous substance can directly act upon the release material such as providing a substance at an elevated temperature and/or PH level that causes disruption of the release material to allow the filler material to interact with the fluids in the stomach and/or to pass from reservoir

into the stomach. Alternatively, the exogenous material can interact with fluids within the body to directly or indirectly activate and/or degrade the release material.

(48) In alternate variations, the release material, or additional areas on the skin degrade or become unstable due to the passage of time in the normal gastric environment. In such cases, the additional areas can serve as a safety mechanism to ensure release of the device after a pre-determined period of time. For example, in the variation shown in FIG. 1F, one of the areas of release material **106** can be responsive to exogenous stimulus or exogenous materials while the other release material **106** can break down over time. Alternatively, or in combination, as shown in FIG. 1F an exogenous stimuli can be used in combination with the exogenous material **120** to cause disruption of the release material. In another variation, the exogenous stimuli **130** can be used to act directly on the release material **106** (without any exogenous material) to cause disruption of the release material **106** and to begin the process of releasing the device assembly **100** from the patient.

(49) FIG. 1F illustrates the filler material **108** escaping from the reservoir **104** as the device assembly **100** decreases from its active profile to allow for passage of the skin **102** and filler material **108** from the body. In certain variations, the consistency of the escaping filler material **108** is similar to or closely approximates the consistency of a food bolus. The matching of the consistency of the filler material to naturally occurring particles that travels within the body ease the passage of the filler material **108** through the remainder of the digestive tract. In certain situations, the instability or degradation of the release material **106** allows bodily fluids to mix with the content of the reservoir **104**, which liquefies the filler material and expedites reduction of the device assembly **100** from an active profile or state. Although not illustrated, as the device assembly reduces in profile, the peristaltic movement of the muscles in the digestive tract works to extrude materials out of the device **100**, allowing for the passage of the skin **102** of the device **100** through the digestive tract until it is ultimately excreted from the body. Certain variations of the device assembly can be made to have a soft, lubricious and/or malleable configuration to aid in passing through the gastrointestinal tract.

(50) FIGS. 1A to 1F are intended to illustrate variations of devices and methods for occupying space within a patient's body, especially those devices for use within a gastric space. However, the principles described above can be used with any number of variations of the device as described below. As noted herein, combinations of different variations of devices, as well as the combinations of aspects of such variations are considered to be within the scope of this disclosure where such combinations do not contradict one another.

(51) In the embodiment shown in FIG. 2 the construct **1000** is in a hydrated or active profile and comprises a generally oblate spherical shaped structure whose outer "skin" defines a material reservoir or pocket **1010**. The reservoir **1010** is bounded by a thin, flexible material surface or skin **1013** that encloses an interior volume **1015** for retaining substances that maintain the construct in the active profile. In one such variation, the reservoir **1010** contains a filler material **1200**, which may be a liquid or a semi-solid or gel-like material. In general, the volume of filler material **1200** is initially low, that is, when construct **1000** is in its initial, pre-deployment condition. The volume of filler material **1200** increases after the construct's deployment. Construct **1000** in FIG. 2 illustrates the fully expanded or active state but for clarity only a representative portion of filler material **1200** is shown.

(52) The transition from initial, unexpanded state construct **1000** to the active state can be effected by increasing the volume of filler material **1200** enclosed in reservoir **1010**. Additionally, the volume can be expanded through expansion and/or swelling of the filler material already inside the reservoir **1010**. For example, as was described in commonly assigned U.S. patent application publication number US2011/0295299, one exemplary embodiment filler material **1200** in the initial state is a pre-determined volume of dry hydrogel granules. The dry hydrogel granules can swell, for example, between 10 and 400 times their dry volume when exposed to an appropriate liquid, generally an aqueous solution.

(53) In the variation shown in FIG. 2, once a medical practitioner or user deploys of the construct **1000** into the stomach, the aqueous liquid in the stomach migrates into the reservoir **1010** and creates a slurry of liquid and substantially fully hydrated hydrogel. As is well known, hydrogels absorb water from their surroundings causing swelling of the hydrogel. In the embodiment of FIG. 2, the volume of dry hydrogel is pre-selected to have a fully swollen, unconstrained volume that slightly exceeds the volume of the reservoir **1010**. Under constraint, hydrogels cannot swell to a greater volume than the limits of the constraining volume; however, constrained hydrogels can and do exert pressure against the constraint. Thus, reservoir **1010** becomes a structurally self-supporting structure, when filled with an excess of swollen hydrogel (that is, when the unconstrained volume of the swollen hydrogel is greater than enclosed interior volume **1015**). In other embodiments, reservoir **1010** is filled and pressurized with other filler. In its expanded state, reservoir **1010** can be sufficiently elastic to deform under external pressure and returns to its pre-deformation shape when the pressure is removed. In yet additional variations, the filler material can be selected such that it hardens after a period of time to become its own skeletal structure or to support the skin. Such a filler can be selected to eventually degrade based on the environment in the stomach or digestive tract.

(54) Assemblies **1000** under the present disclosure can comprise a material surface or skin **1013** that is substantially impermeable to liquids and/or gases. In these embodiments, filler material **1200** can be, respectively, a liquid or a gas. Additionally, filler material **1200** can be a fluid-swallowable material such as hydrogel, which, when hydrated, becomes a solid, semisolid or fluid-like gel or slurry. As illustrated in FIG. 2, embodiments comprising a substantially impermeable skin **1010** further comprise a fluid transport member **1100** that allows for the migration of fluid through the skin. In some examples, as noted above, the fluid transport member includes a sealable fluid path that may or may not be coupled to an additional fluid conduit. In additional variations, the fluid transport member can include a localized liquid transfer member **1100** that is disposed in an orifice **1020** through the skin **1013** and facilitates the migration of fluid between the interior and exterior of reservoir **1010**. One such example can be found in U.S. Provisional application entitled "Resorbable Degradation System" Ser. No. 61/723,794 filed on Nov. 8, 2012, the entirety of which is incorporated by reference herein

(55) As noted above, in certain variations, where the device assembly **1000** comprises a substantially liquid impermeable material surface, a construct **1000** in the expanded active profile can remain in stomach or other portion of the body indefinitely until released. Therefore, as noted above, devices of the present disclosure can include a release material **1400**, which allow the construct **1000** to reduce in size from the active profile and ultimately pass through the body. Such an active release material **1400** configuration allows for on-demand release of the construct. As noted above, once activated, degraded, or otherwise made unstable, the release material allows migration of filler material from the reservoir and device assembly. In some variations, activation of the release material opens a passage in the skin **1013** of the device **1000**. Alternatively, or in combination, activation of the release material can result in reduction of the integrity of the skin forming the barrier about the reservoir. Once the barrier is compromised, the filler material can safely pass into the body. Regardless of the means, the activation of the release material and release of the filler material collapses the device **1000** leading to egress or removal of the device **1000** through the body (in this variation through the lower gastro-intestinal track). As noted above, variations of the devices described herein include a release material that is activated by exposure to an exogenous substance.

(56) In certain variations, the device assembly **1000**, in the active profile, comprises a highly oblate spheroid wherein the skin **1013** can be a thin, film-like material that is soft, tear-resistant, flexible, substantially inelastic, and non-self-adhesive. Such features can be beneficial for a device that is to be compressed into a small oral dosage form for administration. In certain examples, the skin **1013** comprised a 0.0015 inch thick polyether polyurethane film. In a simple variation, an oblate

spheroid can be created from skins forming an upper material surface and a lower material surface, wherein upper material surface and lower material surface are sealed to each other as shown by seam **1004** in FIG. 2. One such means for sealing the device **1000** comprises an ultrasonic or radio-frequency (RF) weld around the periphery of the surface materials. As will be described in more detail below, in a possible assembly method, the upper and lower material surfaces are formed as nominally identical, substantially disk-like shapes of material, welded in a band around most of their circumferences, the assembly is then inverted (turned inside out) through an unwelded section. Once the assembly is inverted, the welded material forms the seam **1004** that projects inwardly.

(57) In some variations, as illustrated in FIG. 1C, the release material can comprise a filament, clip, band, cap, or other structure that mechanically closes the edges of the skin. Further, as described below, a source of stored energy, such as a loaded spring or compressed sponge or other material, may be included in the release assembly, where such kinetic energy is also released upon activation of the release material and which may improve the performance of such assembly.

(58) FIG. 3 illustrates a variation of a fluid transfer member **1100** also having a sealable fluid path **1110** for use with the device assemblies described herein. In this example the fluid transfer member **1100** also includes an elongate fluid conduit, or tube, that passes through a tunnel member that functions as a sealable fluid path **1110**. The tunnel member **1110** can be positioned in an orifice in the upper **1014** or lower **1016** material surfaces or, as illustrated in FIG. 4, in an opening in a seam **1004** of the device assembly. This variation of the tunnel member **1110** comprises an elongate portion **1022** that extends within the reservoir of the device assembly. In some variations, the tunnel member can extend beyond the seam **1004** or beyond the exterior surface of the device assembly as discussed above.

(59) As illustrated in FIG. 3, a portion of the fluid transport member includes a tunnel member **1110** that can comprise two layers sealed along their edges, forming an extended orifice **1020** or lumen. In additional variations, the tunnel member **1110** can comprise a tube structure having a single continuous wall that defines a passage therethrough. In yet additional variations, a tunnel member can include more than two walls. Regardless of the configuration, the wall or walls of the tunnel member are predisposed to occluding or blocking flow through the tunnel member by obstructing the orifice or passage **1020**.

(60) The orifice or lumen **1020** forms a fluid path that allows a remainder of the fluid transport member **1100** to deliver fluids into the reservoir. In this variation the fluid transport member **1100** further comprises a conduit. However, as noted herein, the fluid transport member can comprise a wick type device or any fluid source that allows delivery of fluids into the reservoir of the device. As also noted herein, a variation of the device comprises an attachment of conduit **1100** to a portion of tunnel member **1110**, wherein the attachment may be direct or indirect and wherein, in some variations the attachment is releasable to permit conduit **1100** to be detached, withdrawn, or removed from the tunnel member **1110**.

(61) Withdrawal or removal of conduit **1110** from orifice **1020** permits the tunnel member **1110** to prevent egress of fluids or other substances from within the reservoir. Sealing of the tunnel member **1110** can occur via a rise in pressure within the reservoir. Alternatively, or in combination, a number of other mechanisms can result in sealing or closure of the orifice **1020** in the tunnel member **1110**. For example, in additional variations the surfaces forming the lumen **1020** can seal upon contact or the length of the tunnel member **1110** combined with its flexible nature can simply make it difficult for substances, such as an expanded hydrogel, to travel through the elongated portion **1022** of the tunnel member.

(62) FIG. 3 also shows the conduit **1100** extending through the tunnel member **1110** such that it extends into the reservoir. However, in alternate variations, the device end of conduit **1100** can remain within an interior of the orifice **1020** of the tunnel member **1110**. In such a variation a distal end of the distal portion of the fluid conduit remains within the elongated passage of the fluid

tunnel and can rely on flow pressure to propel the liquid through a portion of the tunnel member such that the fluid ultimately ends up in the reservoir.

(63) In one variation of the tunnel member **1110**, as illustrated in FIG. 4, the tunnel member **1110** shaped roughly as the capital letter T, wherein the vertical stem of the T comprises the elongate passage **1022** and wherein the crossbar of the T, in part, forms an increased attachment surface that can be attached to the skin as noted above. As may be seen in FIG. 4, tunnel member **1110** can be disposed through an opening in the seam **1004**. In other variations tunnel member **1110** can be formed as part of the upper **1014** or lower **1016** material surfaces. That is, the templates that are used to cut the upper and lower material surface layers can include elongated tabs that correspond to the upper and lower layers of elongate passage **1022**. The seams of said tabs may be sealed during the process of sealing the upper and lower material surface layers, leaving an unsealed, axially extended orifice in the center of the elongate tabs.

(64) Some examples of materials used to form a tunnel member include thin, film-like materials. For example, variations include tunnel member materials that have properties similar to the material used in material surface or skin of the device. Additional materials include but are not limited to polyurethane, nylon-12, and polyethylene. In certain variations, Suitable materials typically have a durometer hardness of 80 Shore A or softer and are extruded with a glossy finish to enhance cohesion and tackiness. Layers of material in exemplary tunnel members can typically be between 0.001 inch or less and 0.1 inch thick. In one example a tunnel member includes a single layer thickness of 0.001 inch. One suitable layer material, which is a 0.001" thick, high tack urethane film, is available as part number MT1001 NL from American Polyfilms. Inc, 7 Business Park Dr., Branford, CT 06405.

(65) The length of the elongate portion **1022** that extends within the reservoir of the device assembly may be short, for example, 0.1 inch or as long as the diametric width of the device assembly. In one exemplary valve the length within the reservoir is approximately 1.25 inches and the width of that portion is approximately 0.75 inches wide.

(66) As discussed above, variations of a device assembly include a release material that is coupled to a portion of the skin to form a barrier to retain substances within a reservoir of the device. FIG. 5 illustrates a partial view of a variation of an invaginated section **126** of a skin **102** of a device assembly **100**. As discussed herein, the skin **102** can include a first surface **122** and second surface **124** joined at a seam **118**. The seam **118** can include any number of unjoined sections that are intended to function as release areas **128**. In the illustrated example, the release area **128** is bounded by an inwardly directed, or inverted section **126**, of the skin **102**. The particular illustrated embodiment of inverted section **126** is also known as the invaginated section **126**, so named as it may comprise a tuck, fold, pucker, bulge, extension, etc. in the skin **102**. Alternatively or in addition, the inverted section **126** can be formed within a first **122** or second **124** surface of the skin **102** rather than within a seam **118**.

(67) The release area **128** of the invaginated section **126** ordinarily forms a passage that is fluidly sealed by a release material **106**. The release material can comprise a mechanical closure (such as a staple-type structure or a filament that ties together the invaginated structure). Alternatively, or in combination, the release material **106** can comprise a temporary seal or other joining of the edges of the invaginated section **126**. In additional variations, the release material can extend outwardly from an exterior surface of the skin. In some variations, the release material **106** is disposed on the invaginated portion **126** sufficiently close to the skin to be affected by a temperature increase caused by delivery of the exogenous substance.

(68) In certain variations, the inverted section **126** forms a release area **128** that provides a passage to provide fluid communication between the reservoir and the exterior of the device assembly. This feature allows release of any fluids or material retained within the reservoir to allow the device to reduce in size and pass from the body. The opening can be located at the end of the passage, i.e., at the open edge of the material that is closed together. Alternatively, the wall forming the passage can

be porous in an area beyond the point at which the inverted section **126** is bound (e.g., the area disposed inwardly relative to release material **106**).

(69) In additional variations, the inverted section **126** includes an energy storage element that encourages a rapid and more complete opening of the release area **128**. Variations of the internal energy storage element can include a solid structure, or a structure that allows passage of fluids. The energy storage element can include a compressible elastic material, for example, a latex foam. In some variations internal energy storage element is generally cylindrical with a diameter at least fractionally smaller than the diameter of the passage in the inverted section **126**. When device **100** is deployed in the body, release material **106** is tied firmly around the inverted section **126** at the position of the internal energy storage element, thereby simultaneously sealing the invagination and compressing the internal energy storage element. The resilience of the elastic material in the internal energy storage element creates a tensile force in release material **106** that is greater than the tension in the release material tie used to seal an invagination alone.

(70) FIG. **6** illustrates an example of an inverted section **126** that is pleated or folded and restrained by a release material **106**. The optional energy storage element, if used, is not shown in FIG. **6** for sake of clarity. However, variations of the devices can include energy storage elements that are located between folds or folded into the inverted section **126**.

(71) In another variation, not illustrated, the energy storage element is disposed outside of inverted section **126**. An external energy storage element, for example a retaining ring, is used to increase the tension in the cinched and tied filamentary release material **106**. The increased tension encourages the release material to break apart sooner, more rapidly, and more completely than it otherwise would. A suitable external energy storage element may be made using, for example, a special order, 5 millimeter diameter, Hoopster® retaining ring, available from Smalley Steel Ring Company, 555 Oakwood Road, Lake Zurich, IL 60047.

(72) The release area **128** in each of the variations of the inverted section **126** is initially sealed or closed off by a release material that is coupled, directly or indirectly, to a portion of the skin to form a barrier to retain substances within a reservoir of the device. In many variations the release material is filamentary. Examples of release materials that are available in filamentary form can include Polyglycolide (PGA), Polydioxanone (PDS), Poly(lactic-co-glycolic acid) (PLGA), Polylactide (PLA), Poly (4-hydroxybutyric acid) (P4HB), Polyglactin 910, and Polycaprolactone (PCL).

(73) In such variations, the release material in the expanded device assembly degrades over time by hydrolysis where the rate of hydrolysis varies with material selection and liquid filler pH. In variations wherein the release material is PCL the release material can also degrade by elevating the temperature of the release material since PCL softens, melts, and weakens above a pre-determined temperature. In some cases the pre-determined temperature is greater than normal body temperature. Accordingly, in such variations, the exogenous substance can comprise a heated fluid that can raise the temperature of the PCL without causing injury to the adjacent areas of the body. As the PCL release material degrades, the structural integrity of the joined region of the release section (such as the inverted section **126**) decreases. In one example, the release material is a modified PCL, wherein the modification comprises lowering the melting point of unmodified PCL from its normal melting temperature to a human-tolerable temperature.

(74) Examples of the release material can include poly(caprolactone) or PCL. In such variations, PCL softens, melts, and weakens above a pre-determined temperature. In some cases the pre-determined temperature is greater than normal body temperature. Accordingly, in such variations, the exogenous substance can comprise a heated fluid that can raise the temperature of the PCL without causing injury to the adjacent areas of the body. As the PCL release material degrades, the structural integrity of the joined region of the release section (such as the invaginated section **126**) decreases. In one example, the release material is a modified PCL, wherein the modification comprises lowering the melting point of unmodified PCL from its normal melting temperature to a

human-tolerable temperature.

(75) For example, an on-demand degrading construct composed of nylon-12 can be constructed by first fabricating a 1" circular annulus of 1.5 mil Pollethane, also known as 55DE Lubrizol 2363 polyether polyurethane (available from Specialty Extrusions Inc. of Royersford, PA, USA). A circular degradable patch of poly(caprolactone) (PCL) (with a modified melting point, T_{sub.m}, equal to -47° C.; available from Zeus Industrial Products of Charleston, SC, USA) can be RF-welded to the Pellethane annulus, covering the hole, creating a T_{sub.m}-modified PCL patch surrounded by a rim of Pollethane. The Pollethane rim can then be RF-welded to a sheet of nylon-12, which can then be used for further construction.

(76) Examples of release materials can include biocompatible manufactured polymers. Table 1 is a compilation of the degradation properties of several biocompatible materials that can be extruded or otherwise manufactured in filamentary form and which also can be predictably degraded. Some of these materials, poly(vinyl alcohol) are stable in dry environments but dissolve very quickly in moist environments. Some biocompatible polymers, for example co-polymers of methacrylic acid and methyl-methacrylate, dissolve in liquids having physiologically relevant pHs. For example, they remain stable at pH<7.0 but dissolve at pH>7.0. Other polymers, for example Poly(caprolactone), remain stable at typical gastric temperatures but melt in seconds at temperatures above a pre-determined melting point.

(77) In some variations, polymers that degrade by gradual hydrolysis may be used for the release material. The degradation times of various polymers, under various degradation conditions, can range from about 2 weeks to about 6 months, where the degradation time depends on parameters such as degradation liquid pH, suture construction (e.g., stranded or monofilament), and filament diameter. In general, polymers last longest when exposed to distilled, neutral pH water and degrade more quickly when immersed in acidic or basic pH liquid.

(78) The degradation times for several exemplary materials are tabulated in Table 1. The experimentally determined degradation times in the table were determined in simulated use conditions; that is, as illustrated in FIG. 6, the release material **106** was coupled to an example or simulation of an inverted section **126** that is pleated or folded.

(79) TABLE-US-00001 TABLE 1 Exemplary Release Material Properties Degra- Degra- Degra-
dation dation dation Polymer Mode Condition Time Poly(glycolic Gradual Exposure to ~2 weeks
acid) hydrolysis water or acid Poly Gradual Exposure to ~1 to 2 months (dioxanone) hydrolysis
water or acid 1 PDO 0.9% benzyl 54 days alcohol 3-0 PDO distilled water 56 days 4-0 PDO
distilled water 60 days 4-0 PDO 0.9% benzyl 62 days alcohol 3-0 PDO 0.9% benzyl 65 days
alcohol Poly(lactic-co- Gradual Exposure to ~1 month glycolic acid) hydrolysis water or acid 3-0
PLGA distilled water 25 days Poly(vinyl Rapid Exposure to any Seconds alcohol) dissolution
aqueous solution 4-0 Monocryl distilled water 27 days 2-0 Vicryl 0.9% benzyl 43 days alcohol 2-0
Vicryl distilled water 43 days 0 Vicryl distilled water 46 days 0 Vicryl 0.9% benzyl 48 days alcohol
1 Vicryl 0.9% benzyl 53 days alcohol 1 Vicryl distilled water 53 days Methacrylic Hydrolysis;
Exposure to Days at near acid methyl- on-demand alkaline pH neutral pH and methacrylate pH-
dependent minutes to hours co-polymers dissolution at alkaline pH Poly Hydrolysis; Exposure to 6
months at (caprolactone) on-demand at heat temperatures less temperatures than melting greater
than point, seconds 60° C. at or above melting point

(80) As the release section opens the reservoir to the surrounding environment the opening provides an open path out of the device assembly. The open path allows the contents of the device assembly, such as the filler material, to become exposed to the gastric contents and freely to exit reservoir. When positioned within the stomach, normal gastric churning assists in emptying the contents of the device assembly allowing for the entire device along with its contents to pass from the body. In some variations, the membrane that forms the skin will provide little or no structural support. This configuration allows the body's natural squeezing strength to be sufficient to extrude any reasonably viscous substance out of the device assembly.

(81) FIG. 7 provides a schematic illustration of another example of a device assembly **100** having a release material **106** located on a surface of the skin **102**. One example of such a release material comprises a degradable patch **106** that, when degraded, opens the physical barrier surrounding the reservoir **104** to allow filler material **108** (swollen or unswollen) to exit the device assembly **100**. The device assembly **100** comprises a skin material to which release material **106** can be joined (e.g. by heat sealing, RF-welding, impulse heating, or any other means). In certain variations, the release material/degradable patch **106** comprises a material or combination of materials that remains impermeable to water and hydrogel after deployment and can be degraded “on-demand” in response to an exogenous substance or in response to a condition created within the body being the result of the administration of the exogenous substance.

(82) In one example, the release material can range from 25 microns thick; up to 2.5 millimeters thick. In another example, release material is a modified poly(caprolactone) with melting point $T_{sub.M}=47^{\circ}$ C. (available from Zeus Industrial Products of Orangeburg, SC USA). In additional embodiments, degradable patch **106** may be poly(glycolic acid) or poly(L-lactide acid) (available from Poly-Med, Inc of Anderson, South Carolina).

(83) Material Surface or Skin

(84) The type of material or skin will depend upon the intended application. In some variations, a skin will be chosen as a balance of selecting a sufficiently thick film-like material that has adequate strength. For example in some variations, tear resistance can be preferred to enable the finished construct to be compression into as low a volume capsule as possible. The inventors have determined that thin films with a thickness ranging from 0.5 mils to 4 mils are generally suitable. However, the devices described herein can comprise a greater range of thicknesses depending upon the particular application, including a range of thicknesses in different parts of the same construct. In some embodiments, the film-like material must be weldable or adherable to other materials such as might be used in valves **1110**, filler material release mechanisms **1400**, and/or attachment interfaces as described herein.

(85) In additional embodiments, the film-like material exhibits low transmission rate of filler material, both before and after device expansion. In some embodiment the film-like material exhibits a low moisture vapor transmission rate. Additionally, some film-like material also exhibits high chemical resistance to the variable conditions encountered in the stomach. These conditions include low pH, high salt, high detergent concentrations (often in the form of bile salt reflux), enzymatic activities (such as pepsin), and the variable chemistries of chyme that depend upon the nature and content of consumed food. For those devices used in the gastric space, the material must also be comprised of biocompatible materials that can safely be in contact with the gastric mucosa for the duration of the treatment course.

(86) The devices described herein can use numerous thermoplastic elastomers, thermoplastic olefins and thermoplastic urethanes that can be extruded or cast into single-layer or multi-layer films which are suitable for embodiments of the gastric device. Example base resins that may be employed include polypropylene, high-density polyethylene, low density polyethylene, linear low density polyethylene, polyester, polyamide, polyether polyurethane, polyester polyurethane, polycarbonate polyurethane, bi-axially oriented polypropylene, Polyvinylidene chloride, ethylene vinyl alcohol copolymer, and Ethyl Vinyl acetate. Some embodiments comprise single layer films whilst other embodiments comprise multiple layer films. Other embodiments consist of multilayer films including one or more tie layers to prevent layer separation.

(87) In some embodiments, the film-like material may be coated with other materials. For example, in some embodiments hyaluronic acid coatings can be employed to improve softness and lubriciousness. In other embodiments, coatings such as Parylene® can be applied to improve the chemical resistance of the gastric mucosa-exposed film surface. In some embodiments, wax coatings, PVDC coatings, vacuum-metallization, or Parylene® coatings may be applied to the surface of the film to reduce its moisture vapor transmission rate.

(88) In one example, the film-like material used comprised a 1.5 mil polyether polyurethane film. In other embodiments the film-like material is a 1 mil nylon 12 film or a 1.5 mil LLDPE film. In another example, the film-like material consisted of a multi-layered structure comprising an outer layer of polyurethane, a middle layer of PVDC or EVOH, and an inner layer of polyurethane.

(89) Filler Material

(90) The devices described herein can be filled to temporarily occupy a space within a patient in any different number of ways. In one variation, the devices can use a fluid filler material that is delivered to the device upon positioning within the body. In another example, the devices can be filled with a swellable material that is in an unswollen state during ingestion and swells when hydrated by gastric liquids or an exogenous liquid. Generally, a swellable filler material that has a high swelling capacity and achieves a semi-solid consistency is useful to enable the finished construct to be compressed into as low a volume initial state as possible but still maintain rigidity once expanded. However, unless specifically noted, variations of the device can employ a number of different types or combinations of filler materials. During various experiments, it was determined that superabsorbent hydrogel polymers with a mass:mass swelling capacity of between 100 and 1000 are generally suitable, where a mass:mass swelling capacity of 100 is defined herein to mean that 1.0 g of dry hydrogel will absorb water and swell to become a semi-solid mass of 100.0 g.

(91) Typically, suitable hydrogels swell maximally in the presence of distilled water and a number of these hydrogels also de-swell (releases bound water) in the presence of the variable environmental parameters encountered in the stomach. For instance, parameters such as pH, salt concentration, concentrations of emulsifying agents (often in the form of bile salt reflux), enzymatic activities (such as pepsin), and the variable chime chemistries, which depend upon the nature and content of consumed food can affect the swelling/deswelling behavior of certain hydrogels. Typical hydrogel swelling times range from between 5 minutes and 1 hour. In one variation, the hydrogel fully swells in under 15 minutes and fully de-swells in less than 10 minutes after exposure in certain environments. Many hydrogels are supplied with particle sizes distributed between 1 and 850 microns. In certain variations, gastric applications benefit from the use of hydrogel particle sizes distributed between 1 and 100 microns. In addition, the hydrogel must also be comprised of biocompatible materials that can be safely in contact with and excreted by the gastrointestinal tract. Examples of such biocompatible superabsorbent hydrogel polymers that possess swelling capacities, swelling times, and de-swelling times suitable for embodiments of gastric construct include poly(acrylic acid), poly(acrylamide), or co-polymers of poly(acrylic acid) and poly(acrylamide). Another such material that can be used as a filler material is a crosslinked poly(acrylic acid) with particle size distribution ranging from 1-850 microns and swelling capacity of 400.

(92) Shapes

(93) As discussed above, certain variations of the device approximate a highly-oblate spheroid comprising a diameter in the X-Y plane and a thickness along the Z-axis as illustrated in FIG. 2. In certain variations, the expanded dimensions of the device assembly can range from having a diameter between 2 inches and 10 inches. In another embodiment, the diameter of the construct is approximately 4.6 inches. The Z-axis thickness can range between 2 inches and 5 inches. However, the device assembly, unless otherwise claimed, is not limited to any particular dimension. The data below of construct parameters provides the experimentally determined dimensions of two constructs having the oblate spheroidal shape.

TABLE-US-00002	Parameter	Construct 1	Construct 2
Unexpanded diameter (inches)	4.7	5.8'	
Maximum swollen volume	300 ml	500 ml	
Expanded diameter (inches)	3.64	4.63	
Expanded thickness (inches)	2.40	2.46	

Liquid Transfer Valves

(95) FIG. 8 shows an additional variation of a portion of a device assembly, in other embodiments

liquid transfer member comprises a valve **150**, where valve **150** is disposed in orifice **148** and provides a control over the fluid permeable path through otherwise impermeable material surface **102**. In some embodiments valve **150** comprises a multilayer material structure composed of regions of permeability **152** juxtaposed against regions of impermeability **154**, whereby fluid may transmigrate between the exterior and the interior of reservoir when the regions of permeability **152** and impermeability **154** are not pressed together in tight juxtaposition and whereby fluid is inhibited from transmigrating when the regions **152**, **154** are pressed together tightly. In some embodiments valve **150** is self-closing. That is, valve **150** changes from allowing fluid transmigration to inhibiting fluid transmigration without external activation. In one embodiment valve **150** self-closes in response to the increasing pressure of the expanding filler material or increasing pressure within the reservoir, for example, swelling hydrogel pressing the regions **152**, **154** sufficiently close together to form a barrier.

(96) As noted above, the device assemblies described herein can include a fluid transport member **110** that serves to deliver fluids into the reservoir. One example of such a fluid transport member is a wick that includes a filamentary material capable of conducting a liquid from one end to the other by capillary action. The wick can extend from the interior of the device reservoir to outside the device skin, typically just several millimeters beyond the skin although longer wicks may be used. In another example, the liquid transfer mechanism **1100** comprises a fluid conduit **114**, tube, or catheter that, after the device is extended from the deployed device in the patient's stomach to outside of the patient where it is connected to a source of filling fluid. In many embodiments the fluid flow through the fluid transport member is preferably shut off once the device has reached its desired deployment profile. In embodiments comprising a wick-like fluid transport mechanism the fluid flow may be shut off by pinching down on the wick while in embodiments comprising a catheter-like fluid transport mechanism the fluid flow is halted externally and the catheter-like mechanism is withdrawn from the device first and from the patient second. When the catheter-like mechanism is withdrawn from the device it is necessary to seal the orifice through which the catheter passed through the skin of the device. In many of the assemblies described herein fluid flow is inhibited by a self-sealing, two-layer valve. In other embodiments the self-sealing valve has more than two layers.

(97) In yet other embodiments liquid transfer mechanism **1100** comprises a mechanical valve. Mechanical valves of suitably small dimensions, comprising biocompatible materials, are well known in the art and are commercially available. A mechanical valve that serves as liquid transfer mechanism **1100** comprises a one-way or “check” valve design which allows fluid to enter reservoir **1010** but prevents fluid from exiting the reservoir. Alternatively, a mechanical valve that serves as liquid transfer mechanism **1100** may have a normally open state but which self-closes when internal fluid pressure is greater than external fluid pressure.

(98) FIGS. **9A** and **9B** schematically illustrate one example of a valve that self-seals by the expansion of filler material **234** within a reservoir **236** of the device assembly **230**. The valve **232** is positioned or otherwise disposed in an orifice **238** in the material surface or skin **228**. In other embodiments orifice **238** may be an unsealed section of seam **1004**, as illustrated in FIGS. **3** and **4**. In the illustrated variation valve **232** comprises two material containment layers **242**. Containment layers **242** are at least partially permeable to fluids but may be impermeable to non-fluid filler materials. This permeability may be achieved by a sieve-like structure or, as illustrated in FIG. **9A**, permeability may be achieved by puncturing an impermeable layer with at least one hole **242**. Valve **232** further comprises regions of flow control material **240**. Flow control material **240** is substantially impervious to fluids, specifically to the fluid used as filler material **234** or to hydrate a dry mass of filler material. As illustrated, the regions of flow control material are disposed directly juxtaposed to the permeable regions of containment layers **242**. During deployment there is initially no pressure within the device assembly. With no pressure the juxtaposed flow control material and fluid permeable regions of the containment layer are able to separate, creating a fluid

flow path.

(99) This flow path is indicated by the dashed arrow P in FIG. 9A. In some variations a fluid transfer member, not illustrated, is used to transfer fluid from outside the device assembly to the internal reservoir. In these variations the containment layers may be made from fluid impermeable material with a hole in each containment layer to allow the selected fluid transfer member to pass into the reservoir. The transfer member is inserted through the valve prior to deployment. In some variations the transfer member is a wick while in other variations the transfer member is a fluid conduit or catheter.

(100) FIG. 9A also illustrates a pre-determined amount of filler material 234 within the reservoir 236. In some variations, the pre-determined amount is generally measured by dry mass. The dry mass of filler material 234 is determined by the amount of filler material 234 needed to fill the known volume of the expanded device 230 when the filler material is fully hydrated. When expanded, the filler material applies a pressure within the reservoir 236, which provides a shape-restoring force that resists externally applied deforming forces. In other variations filler material 234 is not pre-loaded within reservoir 236. In these variations the filler material is a fluid or slurry material delivered through a fluid transfer member, generally embodied as conduit 114, as shown, for example, in FIG. 1D.

(101) FIG. 9A also shows valve 232 filling orifice 238. This variation of the valve 232 includes one or more flow control layers 240 that aid in closing of the valve upon action by the filler material 234. FIG. 9B illustrates expansion of the filler material 234, which increases pressure against the valve 232 and closes the fluid path by pressing the flow control layers 240 toward their respective material containment layers such that the fluid path is closed.

(102) In some variations the design may be simplified to comprise just two layers of fluid impermeable material through which passage holes have been created to allow the fluid transport member to pass. This variation is discussed further below in conjunction with FIGS. 9C and 9D.

(103) Turning back to FIG. FIG. 9A, before filler material 234 expands, valve 232 is fully open; that is, it allows fluid to pass through the valve in either an inward or outward direction. On the other hand, after filler material 234 expands, typically via hydration, the valve 232 fully closes, as shown in FIG. 9B.

(104) In some embodiments valve 232 comprises a filler material containment layer 242. Generally, containment layer 242 is at least partly fluid permeable and simultaneously able to contain filler material 234, in its dry or its hydrated state, within device 230. In some embodiments filler material containment layer 242 is also a flow control layer; that is, a single layer in valve 232 can simultaneously be a part of the flow control function of valve 232 and perform the filler containment function of containment layer 240. For example, laser micromachining may be used to create microperforations in one region of an otherwise fluid impermeable membrane. The microperforated region functions as the containment layer while the unperforated region can function as the flow control layer.

(105) Similarly, in variations in which the filler material is a fluid or slurry material that is delivered to the reservoir by a conduit or catheter, each of two fluid impermeable may be punctured by catheter passage holes 242A, as illustrated in FIG. 9C, to create permeable regions to allow the catheter, not illustrated, to be threaded from the exterior of the device to the interior of the device when the device has no filler material in the reservoir. The path of the catheter is illustrated in FIG. 9C by the dashed arrow P. FIG. 9C illustrates this variation of the valve schematically in the “open” configuration that would obtain immediately after deployment but before the filler material was hydrated and FIG. 9D shows the same valve after the filler material is fully hydrated and the conduit has been extracted. As shown in the figures the gap between the two layers in FIG. 9C is pushed closed in FIG. 9D by the pressure of the filler material in the reservoir. This closing pressure occurs with both hydrated swellable filler material, as illustrated, and when the filler material is just a fluid pumped into the reservoir under pressure.

(106) FIG. 9E show another variation of a valve **232**. In this example the valve **232** comprises more than one layer. As shown, this hybrid valve **232** comprises two demilunar hybrid flow control layers **240**, each of the layers having a hybrid construction being permeable in some generally semi-circular (viz., demilunar) regions **250** and impermeable in other regions **252**. The impermeable regions **252** of one layer are at least complementary to the permeable regions of the second layer; that is, where one layer has a permeable region the other layer has an impermeable region; generally there will be regions in which both layers are impermeable. Examples of the materials include a permeable patch comprising a polyester mesh and an impermeable semicircular patch comprising latex.

(107) As illustrated in FIG. 9E, hybrid valve **232** comprises two substantially identical demilunar hybrid flow control layers, one on top of the other, wherein the two layers are oriented so that impermeable region **252** of a first hybrid control layer is aligned with the fluid permeable region **250** of a second hybrid flow control layer. By symmetry, impermeable region **252** of second hybrid flow control layer is aligned with the fluid permeable region **250** of first hybrid flow control layer. The two layers are affixed, typically with glue, around their periphery only, thereby allowing the central areas of the two layers to move apart freely.

(108) In these exemplary embodiments of a hybrid valve, the flow control layer disposed on the internal side of the valve preferably can also function as filler material containment layer, with containment being achieved by the mesh comprising permeable patch. Alternatively, a separate innermost filler material containment layer must be added to the assembly.

(109) In other embodiments, hybrid flow control layer is fabricated by joining a patch of permeable material and a patch of impermeable edge-to-edge, wherein the joint may be a butt joint, for example, or a lap joint, for a second example, wherein further the outer periphery of the edge-joined materials is designed to fill or cover orifice. In another exemplary embodiment of a hybrid valve the skin itself can serve as one of the flow control layers.

(110) In another variation, the devices described herein can include a self-closing tunnel member. FIG. 10A is a schematic illustration of a variation of a tunnel member as discussed above. As shown, the tunnel member forms a fluid path that effectively seals and prevents material from escaping from the interior of the device. In some variations, the effective seal is caused by the nature of the layers of the tunnel member to close together and occlude any lumen extending therethrough. The interior layers that form a lumen in the tunnel member can join together and reduce the effective diameter of the lumen to increase a resistance to fluid flow through the tunnel member. Alternatively, or in combination, one or more substances can be positioned within the tunnel member lumen, where the substances increase the resistance to fluid flow. For example, the substances can expand to further reduce the effective diameter of the lumen, and/or the substance can stick together to increase a force required to open the lumen. As shown in FIG. 10A, the tunnel member can extend within the device as well as outside of the device. However, variations include valves in which one of the two ends is flush with the skin of the device or in which the valve is totally within the reservoir but is attached to an inwardly formed nipple to complete the fluid path between the exterior and interior of the device.

(111) FIG. 10A illustrates an example of a device with a tunnel member forming the sealable fluid path. As shown, the device assembly contains a tunnel body/valve **330** comprising a liquid impermeable material that can be securely joined to the skin **328** in any manner conventionally known or by those discussed herein (including, but not limited to gluing, welding, heat sealing, or other means). Examples of materials useful for the tunnel member include polyurethane, nylon-12, and polyethylene. The tunnel member **330** can include any number of fluid transport members **332**. In the illustrated variation, the valve is coupled to a conduit. However, variations include a wick type device located within the tunnel member.

(112) FIGS. 10B-10D show a cross sectional view of tunnel body or tunnel member **330** taken along line 10B-10B of FIG. 10A. As shown in FIG. 10A, the tunnel body **330** forms part of the

fluid transport member **332** allowing transport of fluids between the interior/reservoir and interior of the device assembly. In general terms tunnel member **330** comprises, for example, an upper layer **340** and a lower layer **341** that are sealed together along their longer edges but are left unsealed along an axial central region. The unsealed region forms a lumen **343** that extends along the tunnel member so that the lumen can extend from the end of the tunnel member that is exterior of the device through to the end of the tunnel member that is located within an interior reservoir of the device. The lumen permits delivery of a fluid into the device through any of the variations described herein. For example, the device can use a wick or a fluid transport member to pass fluid from the exterior of the device into the interior reservoir. In some variations the fluid transport member may be pushed through the lumen by spreading the layers apart. In certain variations, the fluid transport member **332**, can be detachable from the tunnel member **330**. Upon removal of the fluid transport member **332**, as shown in FIG. **10E**, the layers of the tunnel member **330** move toward each other to effectively close the central lumen **343** to an extent that the tunnel member effectively seals and prevents migration of the filler material from the reservoir. In certain variations, the layers of the tunnel member will not be fully closed, however, the tunnel member will still prevent fluid flow therethrough. In additional variations, the inherent flexibility of the tunnel member will prevent fluid from migrating through the lumen out of the reservoir.

Furthermore, the pressure within the reservoir pressing on the outer surface of the tunnel member acts to increase the resistance to fluid flowing within the lumen of the tunnel member.

(113) This self-closing behavior (that is, the closing behavior is initiated and completed without any external force, stimulus, energy, or action beyond the removal of the fluid transport member **332**) is effected by one or more physical mechanisms. In some variations the mechanism is the natural elasticity of the layers of the valve working to restore the layers to their initial, flat, in-contact condition. In other variations the pressure of the filler material in the reservoir presses the layers, which were held apart by the fluid transport member, together.

(114) One variation of the tunnel member, illustrated in FIG. **10B**, includes an assembly formed by two discrete membrane layers, the upper layer **341** and the lower layer **342**, that are joined by gluing, welding, heat sealing, or other means along their two edge regions **344** as indicated by bond line **345**. In another variation, illustrated schematically in FIG. **10C** the assembly may be formed by a single membrane that has been folded in half with a fold **346** that is parallel to central lumen **343**, wherein again the two regions parallel to and bordering central lumen **343** are joined together by gluing, welding, heat sealing, or other means. In some variations RF welding has been used. After the joining process is complete, the material in fold **346** may be cut away or otherwise removed or it left in place. In a third variation, shown schematically in FIG. **10D** the assembly may be formed by a sleeve of membrane material, for example, fabricated by extrusion. Flattening the sleeve creates an assembly with the two desired layers. The central lumen can be formed by again joining together the two regions parallel to the lumen by gluing, welding, heat sealing, or other means and again, after the joining process is completed, the thusly created two folds **346** may be left in place or removed. Functionally these variations of the tunnel member are equivalent and the choice of fabrication approach will be determined as an engineering decision.

(115) In exemplary tunnel members the layers can typically be between 0.001 inch or less and 0.1 inch thick. In one example a tunnel member includes a single layer thickness of 0.001 inch. One suitable layer material is a 0.001" thick, high tack urethane film.

(116) In some variations the tunnel member has a length (parallel to the central lumen) of between about 0.5 inches and 2.75 inches and a width of between 0.25 inches and 0.75 inches, although both larger and smaller tunnel members are possible. The central lumen runs the full length of the tunnel member and has a width, in one variation, of 0.095 inches, where the width is a design choice determined by the size of the particular fluid transport member **332** selected.

(117) In additional variations, tunnel members can be flexible, compressible and/or deformable. In additional variations, the lumen between the layers of the tunnel member can be reopened after

fluid transport member has been removed by the insertion and passage of a structure (e.g., a conduit or other fluid transport structure) through the closed tunnel member.

(118) As noted above, the tunnel member allows for detachment of the remainder of the fluid transport member at any time, but typically once a sufficient amount of fluid is delivered to the device. Removal can occur via applying tension to a portion of the fluid transport member.

Variations of the tunnel member can employ permeable membranes, filter, or valves placed at the end of the tunnel member to prevent dry hydrogel or other filler materials from entering the tunnel and affecting the ability of the tunnel member to seal. In some embodiments, the membrane or filter may comprise a permeable fabric such as polyester, nylon, or cellulose. In other embodiments, a valve is placed at the end of the tube comprised of a one-way duckbill or umbrella valve (available from MiniValve of Oldenzaal, Netherlands). Alternatively, or in addition, filler material **234** can be contained in an inner container which prevents the filler material from entering the tunnel member and swelling upon infusion of liquid, thereby clogging the valve.

(119) Referring to FIG. **10F**, tunnel member **1110** comprises an interior section **1110A**, which section is disposed inside the device assembly, and an exterior section **1110B** that extends outwardly from the exterior of the skin. Interior section **1110A** comprises an internal end **1110A1**, which is fabricated from flexible membrane-like materials. Once the device assembly is fully expanded, conduit **1100** is withdrawn from lumen **1020** from outside the device assembly. In some circumstances the drag between the conduit and the walls of the lumen as the conduit is withdrawn may result in interior section **1110A** “accordioning” or folding itself against the walls of the device. In some variations interior section **1110A** of the tunnel member is attached to an interior surface of the device body to prevent such folding. In some variations the attachment is achieved by fastening internal end **1110A1** to either upper material surface **1014** or lower material surface **1016**. In one variation a chemical bond or spot of glue is employed. The glue spot is disposed near to internal end **1110A1** but in such a manner to avoid accidentally obstructing orifice **1020**; for example, the glue spot may be disposed 2 or 3 millimeters away from internal end **1110A1**. Tunnel member **1110** is rotated about seam **1004** until internal end **1110A1** touches the material surface. Tunnel member **1110** and the material surface should both be smooth and flat during this gluing operation.

(120) In additional variations, as shown, for example, in FIG. **10F**, a portion of the tunnel member extends outside the device assembly to form an external section **1110B**. In some variations, as shown in FIG. **10I**, external section **1110B** terminates with two unjoined flaps, upper flap **1028** and lower flap **1026**, which may be extensions of upper layer **341** and lower layer **342** respectively. In other variations external section **1110B** may comprise a single flap or layer of material. In some examples, external section **1110B** is typically between 0.1 inch and 0.5 inch long. As will be discussed below with reference to FIG. **11**, in some variations the layers of the tunnel member are fabricated as integral parts of the upper and lower skins of the device. In these variations there is no material available to form the upper and lower flaps as extensions of the upper and lower layers, in which case a free-standing external upper flap **1028** and/or lower flap **1026** may be attached to the external surface of the device using any convenient joining method, for example, gluing or they may be attached in the seam. The free-standing flap or flaps are joined to the device in close enough proximity to the tunnel member to be able to touch a fluid transport member disposed through the central lumen of the tunnel member.

(121) In some variations the tunnel member comprises retaining elements to releasably hold the conduit in place throughout deployment of the device assembly. FIG. **10F** illustrates one embodiment for retaining the conduit in a partial cut-away view from the interior of the device assembly. tunnel member **1110**, as described above, is typically formed by sealing the edges of two layers of membrane material to form sealed seams **1024**. In some variations sealed seams **1024** extend all the way to an external end **1110B** and/or internal end **1110A1** while in other variations the edges of the two layers may be unsealed for some length inward from external end **1110B** and/or internal end **1110A1**. The relative lengths of the interior and exterior sections of tunnel

member **1110** have been distorted in the figure for clarity purposes. Typically exterior section **1110B** is just long enough to accept conduit **1100**. As has been discussed, conduit **1100** is inserted through orifice **1020** prior to deployment of the device assembly and is used to deliver fluid to the reservoir therein to expand device assembly. Conduit **1100** must remain disposed in tunnel member **1110** until enough fluid has been delivered to the device assembly to make it too large to inadvertently pass through the pylorus while at the same time conduit **1100** must be removable from the device assembly once its deployed profile has been achieved. Further, it is desirable that conduit **1100** also be useful for retrieving the device assembly from the stomach or esophagus in the case of an aborted deployment. In such an aborted deployment the conduit must be held in the tunnel member with enough resistance to withstand the drag on the unexpanded device assembly as it is retrieved upwardly through the esophagus.

(122) A suture **1032**, which may be inserted through either or both of interior section **1110A** or exterior section **1110B**, is designed to hold the conduit in the tunnel member under a wide range of extractive force. As illustrated in the figure, suture **1032** is stitched through the two layers of the tunnel member, simultaneously passing through conduit **1100**. The suture is tied to itself on the exterior of tunnel member **1110**. The small punctures in conduit **1100** and tunnel member **1110** through which the suture passes are too small to allow any significant loss of liquid filler.

(123) Once the device assembly has assumed its deployment profile conduit **1100** must be withdrawn from tunnel member **1110**. Conduit **1100** is released from tunnel member **1110** by the controlled, on-demand degradation of suture **1032**. As is discussed above certain suture materials can be dissolved or structurally weakened by exposure to specific exogenous agents not normally in the gastric environments, or not in the gastric environment in high enough concentrations to degrade the suture during the deployment time period. For example, poly(caprolactone) [PCL] softens, melts, and weakens above a pre-determined temperature, T.sub.M. In some cases the pre-determined temperature can be designed to be greater than normal body temperature but lower than human's physiologic pain threshold. In such a case, a PCL suture can be degraded by infusing heated liquid (above T.sub.M) through conduit **1100** at the end of the deployment period or by having such liquid consumed orally.

(124) In order to avoid over-filling the device assembly when the heated liquid is infused through the conduit the hot liquid infusion must start at after a pre-determined volume of un-heated liquid filler material has been infused, where the known capacity of the device assembly, the volume of fluid residual in the conduit, and the thermal capacity of the system are all incorporated into the determination. It should be noted that if the initial infusion of hot liquid fails to release the conduit by melting the suture, liquid can be withdrawn up the conduit to slightly reduce the volume of the device assembly and a second charge of hot liquid infused.

(125) In another variation, as depicted in FIG. **10G** and FIG. **10H**, conduit **1100** is detachably joined to one or both double layer sealed seams **1024** of tunnel member **1110** with a loop of suture material **1032**. Suture loop **1032** comprises a single long loop which starts and ends at the external (e.g., patient's mouth) end of conduit **1100**. The loop starts at the external end, runs down the interior of conduit **1100**, and exits the conduit at a small orifice **1036** that transverses the wall of conduit **1100** near the proximal end of exterior section **1110B**. After exiting from orifice **1036**, the suture passes through one or two eyelet holes **1034** in sealed seams **1024** before returning to orifice **1036**. The suture completes its loop by running back up the interior of conduit **1100**. The two ends of suture loop **1032** are retained at the external end of conduit **1100**.

(126) Suture loop **1032** is installed during the manufacture of the device assembly and remains disposed in conduit **1110** during infusion of the liquid filler material. Conduit **1110** cannot easily be pulled out of tunnel member **1110** while suture loop **1032** is in place. Once the device assembly has assumed its deployment profile, one end of suture loop **1032** may be released while the other end of the loop is pulled outwardly. When at least half the length of suture forming suture loop **1032** has withdrawn from conduit **1100**, the loop is known to be unthreaded from the eyelet hole(s). Freed

from the eyelets, conduit **1100** can then be withdrawn from tunnel **1100**.

(127) In some embodiments suture loop **1032** of FIGS. **10G** and **10H** may be made from PCL, in which case conduit **1110** may also be released by melting suture loop **1032** through the infusion or ingestion of hot liquid, as described above.

(128) Another variation of fluid transport member **1100** is illustrated in FIG. **10I**. In this variation sealed seams **1024** stop short of external end **1110B**, leaving two flaps of material, upper flap **1028** and lower flap **1026**, where upper and lower are arbitrary designations relating only to the figure. Upper flap **1028** or lower flap **1026** is prepared with a release region in the form of a rip-off tab **1030** which comprises the most proximal section of upper flap **1028** and which is distinguished as the region sectioned off by a tear line **1038** of diminished tear-strength material. The tear-strength of tear line **1038** may be reduced, for example, by perforations, physical thinning, or chemical application (e.g., partial de-polymerization). In some variations the tear-strength of tear line **1038** is between 1 and 1.5 lbs. while other variations may have tear-strengths between 0.5 lbs. and 2.5 lbs. (129) In some variations the length of flaps **1028**, **1026** is approximately 0.5 inches and tear line **1038** is disposed approximately 0.3125 inches from the exterior surface of the device.

(130) As illustrated in the figure, conduit **1100** is attached to rip-off tab **1030** at spot location **1040**, which is on the external side of tear line **1038**, where such attachment may be accomplished, for example, by gluing, melting, or ultrasonic welding. In some variations the attachment point, spot location **1040**, is at least 0.0625 inches away from tear line **1038**. In this variation conduit **1100** is detached from tunnel member **1110** by pulling outwardly on conduit **1100** with enough force to separate rip-off tab **1030** from upper flap **1028** along tear line **1038**. Although depicted examples show only a single rip-off tab **1030**, additional variations include two or more rip-off tabs, one such tab on each of the two flaps, wherein conduit **1100** is attached to both tabs.

(131) In some variations, as depicted in FIGS. **10J-10L**, which show a cross sectional view of tunnel member **1110** taken along line **10H-10H** of FIG. **10B**, the deposition of a tunnel substance **1046** between the layers of the tunnel member may enhance the sealing effectiveness of tunnel member **1110**. In some variations tunnel substance **1046** is a hygroscopic, fluid swellable material. In these variations the swellable material generally remains unswollen while the conduit **1100** is installed in the valve. After conduit **1100** removal, swellable material **1046** intercepts any liquid or semi-liquid filler material from the reservoir that migrates between the two layers of the nominally sealed valve. The swellable material swells in response to any liquid component in the intercepted filler material, thereby blocking further filler material migration through the valve. The substance can also serve as a packing material within the tunnel member. Additional variations include a tunnel substance that is hydrophilic.

(132) The swellable material **1046** is typically superabsorbent poly(acrylic acid) hydrogel granules or superabsorbent poly(acrylic acid) hydrogel fibers. The swelling ratio of these substances (the mass of water absorbed for every gram of substance) is typically greater than 10.

(133) In other variations the tunnel substance **1046** is a low-solubility material. Such a low-solubility tunnel substance can also function as a lubricant. In one example, the tunnel substance comprises a bio-compatible grease or grease-like material. The tunnel substance can be selected to have a high enough viscosity to remain in the central lumen for the expected duration of deployment. Typically the material is not soluble in water to any significant degree. In some variations the material is a high viscosity silicone grease. Additionally, the tunnel substance can be a hydrophobic material.

(134) In some variations, the substance **1046** is inserted into central lumen **1020** prior to the insertion of conduit **1100** while in other variations the tunnel substance is injected into the lumen and around the conduit after the conduit has been inserted through the lumen.

(135) As illustrated schematically in the cross-sectional view in FIG. **10J**, central lumen **1020** has a diameter over most of its length that closely matches the diameter of conduit **1100**. This snug fit reduces the leakage of filler material during the filling process since filling material in the reservoir

can enter the internal end **1110A1** of the lumen in the space around the exterior of the conduit. The dashed line A-A' indicates the skin of the device assembly. Generally tunnel substance **1046** is disposed toward the internal end of valve **1110** although in some variations it may be disposed towards the proximal end of the valve in the region approaching but not including the region of the unjoined flaps, as shown in the cross-sectional figure as upper flap **1028**.

(136) As depicted in the cross-sectional view schematically in FIG. **10K**, in some variations lumen **1020** is tapered in one or more regions **1042**, **1044**. The region between the two tapered regions forms a pocket into which the tunnel substance may be disposed. In embodiments with only one tapered region the region will typically be disposed near internal end **1110A1** and the tunnel substance **1046** will be disposed to the proximal side of the tapered region. Tapered regions **1042** and **1044**, may have a design diameter so that the conduit **1100** fits snugly through the tapered regions and less snugly in the untapered regions. That is, the diameter of the tapered regions is substantially equal to the diameter of the conduit. The tapered region can then prevent most of the liquid filler from reaching the tunnel substance while conduit **1100** is in place, inhibiting any swelling of a swellable tunnel substance or any migration of the tunnel substance out of the lumen during storage. This variation is particularly suitable for a swellable tunnel substance, which in many variations comprises dry, flowable granules. Once the conduit is removed any fluid that follows the conduit up the lumen is intercepted by the swellable material which then swells and blocks the flow of additional fluid.

(137) Another variation is illustrated schematically in the cross-sectional view in FIG. **10L**. In this variation lumen **1020** comprises an enlargement region or pocket **1047** into which an extra volume of tunnel substance **1046** may be inserted. This variation is similar in function to the variation illustrated in FIG. **10K**. It may be advantageous compared to that variation in that the diameter of the lumen may be snugly fit to the catheter over a longer length than is possible in the variation of FIG. **10K**, thus providing better containment of the tunnel substance in the pocket and greater resistance to filling fluid flow out of the reservoir.

(138) In some embodiments the seal of valve **1110** may be enhanced mechanically, as illustrated in FIG. **10M**. In this exemplary embodiment a spring-loaded closure device **2000** is disposed on elongate portion **1022** of valve **1110**. Closure device **2000** comprises two, U-shaped loops **2010A**, **2010B**, loops **2010** in this exemplary embodiment being connected at a hinge axle **2015**. Each loop **2010** comprises a width comparable to the width of elongate portion **1022** and a length, L, which is the length of each loop **2010** extending from hinge axle **2015**. For clarity, the loops are illustrated with exaggerated lengths.

(139) Device **2000** further comprises a spring **2020** or similar energy storage element. Loops **2010**, hinge axle **2015** and spring **2020** are configured to allow spring **2020** to drive loops **2010** into generally adjacent alignment by rotating one or both loops around hinge axle **2015**, as indicated by arrow A in FIG. **10M**.

(140) During deployment, conduit **1100** is disposed within orifice **1020**, typically extending through substantially the entire length of elongate portion **1022**. As previously noted, in some embodiments conduit **1100** extends beyond the end of orifice **1020**, as illustrated in FIG. **10M**. Closure device **2000** is disposed in its "open-flat" configuration on or around elongate portion **1022**, whereby elongate portion **1022** is threaded through closure device **2000** by passing above loops **2010** and below hinge axle **2015**.

(141) Elongate portion **1022** is, by design, stiff enough to hold closure device **2000** in its open-flat configuration during deployment. It will be noted that elongate portion **1022** is stiffened during deployment by the presence of conduit **1100** since, as described herein, elongate portion **1022** is fabricated with two thin layers of a membrane-like material designed to collapse upon themselves while conduit **1100** must be rigid enough to provide an open fluid channel from a patient's mouth to his stomach.

(142) After deployment, conduit **1100** is withdrawn from orifice **1020**. Once the end of conduit

1100 passes the crossbar of loop **2010A**, elongate portion **1022** is no longer stiff enough to retain loop **2010A** in its open-flat configuration. Loop **2010A** is rotated by torsion spring **2020** in the direction of arrow A, wrapping the distal end of elongate portion **1022** around hinge axle **2015** in the process. Loop **2010A** continues rotating until it rests against loop **2010B**, simultaneously pressing and sealing the doubled over elongate portion **1022**.

(143) In an alternative exemplary configuration, illustrated in side-view in FIG. **10N**, closure device **2000** may be used as a spring clamp only, without the doubling over functionality discussed above. As shown, during deployment closure device **2000** is disposed in its open-jaw configuration, with elongate portion **1022** inserted into an open jaw **2012** formed by loops **2010A** and **2010B**. During deployment conduit **1100** inside elongate portion **1022** is stiff enough to hold jaw **2012** open; when conduit **1100** is withdrawn, the force of torsion spring **2015** closes jaw **2012**, sealing elongate portion **1022**.

(144) In another embodiment, not illustrated, an elastic ring provides the mechanical assistance for enhancing the seal of valve **1110**. The ring is disposed around on elongate portion **1022** of valve **1110**. The ring's material properties and dimensions are selected to substantially seal the tunnel member when the valve does not contain conduit **1100**. However, when conduit **1100** is positioned within the tunnel member, the rigidity of the conduit resists the sealing force of the elastic ring. The elastic ring may be composed of any elastomeric material that is known to be biocompatible. Examples include silicone, polyurethane, and latex.

(145) As was described above, in some variations of a tunnel member the two layers of the valve, upper layer **341** and lower layer **342**, are fabricated as integral parts of the upper material surface **1014** and lower material surface **1016** of the device. A device having integral tunnel member layers shown in mid-fabrication in the plan view of FIG. **11A**. As previously described, in a simple variation, an oblate spheroid device can be created from two pre-formed skins formed by upper material surface **1014** and lower material surface **1016**, wherein upper material surface and lower material surface are sealed to each other as shown by seam **1004** as shown in FIG. **2**. In one exemplary fabrication method each of the two material surfaces are thermoformed into semi-ellipsoids by heating a sheet of membrane material **1014A** or **1016A** in a frame and forming it over a vacuum mold wherein the mold has the desired semi-ellipsoidal shape. As illustrated in exploded cross-sectional view FIG. **11B**, after cooling and upon removal from the vacuum mold, each sheet of membrane material, membrane materials **1014A** or **1016A**, retains the semi-ellipsoidal shape of upper material surface **1014** or lower material surface **1016**, albeit in a collapsed or crumpled form, the membrane material being thin and flexible. It will be noted that each formed sheet has a preferred interior surface **1014I**, **1016I** and a preferred exterior surface **1014E**, **1016E**, where the interior surfaces comprise the concave side of the molded semi-ellipse. As illustrated in FIG. **11B**, the two sheets are disposed with their interior surfaces facing each other and in close contact, with any corresponding features aligned.

(146) In another variation of a tunnel member, one layer of the tunnel member is fabricated as a separate membrane while the material surface of the device provides the second layer of the tunnel member. For example, lower layer **342** may be joined to upper material surface **1014** along its two edges, leaving a passage or lumen extending from the seam of the device to the internal end of lower layer **342**.

(147) The two sheets are then joined around the periphery of the semi-ellipses to seal them together along sealed seam **1004**. One method for sealing the device **1000** comprises an ultrasonic or radio-frequency (RF) weld. In the example shown in FIG. **11** the device includes a tunnel member in which the two layers of the valve are integral to the upper and lower material surfaces. As shown in FIGS. **11A** and **11B**, the integration of the valve upper layer **341** and lower layer **342** into the device surface material can be accomplished by configuring the joining, welding, or gluing fixture to form a pair of seams projecting in an outwardly radial direction relative to the nominally circular seam around the material surfaces. These projecting seams are formed in a flat region of the

membrane material and are disposed generally parallel to each other and spaced by a gap substantially equal to the desired diameter of central lumen.

(148) After joining the device is trimmed to remove the excess material along a trim line **1006**. Either before or after joining an access aperture **1410** is opened in one of the material surfaces. Typically this aperture is circular although it appears distorted in FIG. **11A** due to the crumpling of upper material surface **1014**. As will be understood, when the device is inverted by pulling the lower material surface **1016** through aperture **1410** to put seam **1004** on the interior, the outwardly projecting tunnel member formed by upper and lower layers **341** and **342** is converted into the desired inwardly directed valve.

(149) Delivery System

(150) As shown in FIG. **12**, in certain variations, the device assembly can be compressed to fit within an oral dosage form **352** such as a pill, capsule, sleeve, or other dosage form that enhances the ability of positioning the device via ingestion or swallowing without the aid of another medical device. In such a case, the device **350** is contained within the oral dosage form **352** and can optionally include a tether **356**. It should be noted that the conduits described above can also be used as a tether or vice versa. In any case, the tether **356** allows for controlling the deployment location of the device **350** within the gastrointestinal tract by manipulation of the tether **356**, and finally completing the administration procedure by releasing control of the device **350**, either by releasing the tether **356** for the patient to swallow or, more typically, by detaching the tether from the device **350** or oral dosage form. FIG. **12** also shows a tether **356** as having two ends to allow for greater control in positioning the device **350**.

(151) In accordance with the delivery method, a medical practitioner, typically a medically trained agent such as a physician, physician's assistant, or nurse, administers the tethered, encapsulated payload to a mammal, herein referred to as the patient. The method comprises the simultaneous steps of directing the patient to swallow oral dosage form while controlling the tether. In some embodiments controlling the tether comprises the use of a tube, conduit, or catheter to transport liquid into the device, the method also includes infusion of liquid through the tube using a syringe, pump, or other liquid delivery means. Generally, the step of controlling the tether comprises, firstly, ensuring that the tether's proximal end is retained exterior to the patient and, secondly, assisting the patient by feeding the tether into the patient's mouth and throat at a rate compatible with the ingestion of the oral dosage form **352**. That is, the agent typically adjusts the feed rate of the tether so the progress of the oral dosage form **352** down the esophagus is not impeded by tether-induced drag while at the same time the patient does not feel the tether is accumulating in his or her mouth. In additional variations, the medical practitioner can also use the tether by securing the section of the tether located outside of the patient's body (i.e., to a fixture in the room or to a part of the patient).

(152) The method further comprises an optional step of controlling the delivery distance of the device. The delivery distance is, essentially, how far into the gastrointestinal tract the device is permitted to travel. Typical devices are designed to be deployed in the stomach although some devices may be designed to reach only the esophagus whilst other devices can be intended to reach the pylorus or beyond. The step of controlling the delivery distance is best accomplished with a device attached to a marked tether, whereby the length of the ingested tether corresponds to the instantaneous delivery distance, which length being directly readable from a marked tether. Part of this optional step of controlling the delivery distance is stopping the further ingestion of the tether.

(153) In certain variations, the oral dosage form **352** dissolves upon reaching the stomach and the fluids therein. Once free from the oral dosage form, the device **350** is free to expand into a deployed state or an active profile. Alternatively, device **350** expands into its active profile upon infusion of a hydrating fluid through the fluid transfer member.

(154) One of skill in the art will note that the human GI tract is unique among the abdominal viscera as it is periodically exposed to very cold and hot substances during routine alimentation.

For instance, the temperature of the stomach is known to increase to 44° C. after ingestion of a hot meal heated to 58° C. but quickly return to core body temperature (37-39° C.) in 20 minutes. Moreover, the temperature of the stomach can reach as high as 48° C. for between 1-2 minutes if 500 milliliters of 55° C. tap water is consumed rapidly (under 2 minutes) on an empty stomach. Thus, a biocompatible material that could be eliminated by melting would ideally remain stable at core body temperature (37-39° C.) but melt in response to a planned intervention that raised the temperature in the vicinity of the biocompatible material to the material's melting point. In the GI tract, such a material would have to withstand daily fluctuations in gastric temperature (e.g. after ingestion of a hot meal) and remain stable at temperatures between 37° C. and 44° C. but melt in response to a planned intervention (e.g. consuming 500 milliliter of 55° C. tap water).

(155) In some examples it was noted that one material, polycaprolactone (PCL), has been extruded into a strong monofilament (Japanese publication JP-A05-59611 A) and has a natural melting point of 60° C., a melting point that is probably not safely usable in human stomachs. However, PCL can be modified to lower its melting point to more physiologically acceptable temperature. Moreover, the modified polymer can still be extruded into a strong monofilament suitable for suturing and stitching or a film suitable for heat welding to a membrane. PCL filamentary material with reduced melting temperatures ($T_{sub.M}$) is available from Zeus Industrial Products of Orangeburg, SC, wherein $60^{\circ} C. > T_{sub.M} > 45^{\circ} C.$ by specification.

(156) In some variations the degradable material used as release material **106** is allowed to degrade at its natural degradation rate in the mammalian gastric environment. In other variations, degradation is triggered or effected by the intentional introduction of an exogenous substance **120**. In some variations the exogenous substance is the fluid filler material delivered to the reservoir via the conduit. In these latter variations release material **106** is disposed entirely within the reservoir and is not physically contacted by the gastric environment. Further in these variations the fluid filler material both expands the device to its active profile and initiates a timed degradation of release material **106**.

(157) In additional embodiments, exogenous substance **120** is introduced orally and at least partially in a liquid format into the stomach. In the stomach, the exogenous substance **120** mixes with the resident gastric fluid to become an immersing fluid that substantially bathes the construct. Alternatively, the exogenous substance **120** may be introduced into the stomach in a solid state, as in a tablet or capsule, typically accompanied by a liquid, whereby the solid is dissolved and becomes the immersing fluid, particularly when mixed with gastric fluids. In certain embodiments extra-corporal stimulation of the exogenous substance **120** may be used.

(158) In many variations, the release material comprises modified PCL material, either as a thin film for degradable patch or as a filamentary material. In general, modified PCL melts at a specified melting temperature, $T_{sub.M}$ and the temperature of the stomach, $T_{sub.S}$, remains below $T_{sub.M}$. The exogenous agent for PCL, therefore, comprises an elevated temperature liquid—at temperature $T_{sub.L}$ —which raises $T_{sub.S}$ above $T_{sub.M}$. The exogenous agent temperature $T_{sub.L}$ needed to raise $T_{sub.S}$ above $T_{sub.M}$ is based on the design details of entire system; that is, the means of delivery of exogenous substance **120**, the design of release material (that is, for example, stitches, patch or knot), and the specified melting temperature, $T_{sub.M}$, of the modified PCL.

(159) For example, an intragastric construct comprising $T_{sub.M}=48^{\circ} C.$ modified PCL will degrade after the rapid ingestion of a large volume of water with $T_{sub.L}=55^{\circ} C.$ Clearly, the location of the PCL release material may affect the rate and/or temperature at which the PCL degrades. The extra-corporal exogenous substance **120** temperature $T_{sub.L}$ is higher than the melting temperature of the PCL to account for cooling of the formulation during transit to the stomach and due to mixing with the existent stomach fluids and for the placement of the release material. In one example, it was found that the rapid ingestion of approximately 500 milliliter of 55° C. water elevates stomach temperature $T_{sub.S}$ to at least 48° C., high enough to

dissolve/degrade the modified PCL and allow the device to open and release its hydrogel contents. (160) In another example, an intragastric construct comprising with $T_{sub.M}=50^{\circ}\text{C}$. modified PCL will degrade after rapid endoscopic infusion of 500 milliliter tap water with $T_{sub.L}=65^{\circ}\text{C}$., a temperature that is too hot for comfortable oral ingestion but which is tolerated by the stomach when the liquid is delivered directly to the stomach. Alternatively, the exogenous substance **120** may be delivered directly to the stomach via a nasogastric tube, again circumventing the comfort limitations of oral ingestion.

(161) In another variation, an exogenous substance can be used to raise the temperature or otherwise change the conditions of bodily fluids to effect release of the device. Additional variations allow for the use of an exterior energy source to raise the temperature of the area surrounding the device. For example, a patient can ingest a sufficient volume of fluid, followed by the application of an external energy source (e.g., radiofrequency or ultrasound) to the exterior of the patient's abdomen to warm the fluid within the stomach to the desired $T_{sub.M}$. In another variation, the exogenous substance, e.g. elemental magnesium, itself causes an exothermic reaction to occur in the stomach.

(162) Yet another approach providing a exogenous substance **120** to an intragastric device comprising $T_{sub.M}=50^{\circ}\text{C}$. modified PCL is the ingestion of 500 mL of alkaline solution (e.g. saturated sodium bicarbonate) pre-warmed to 55°C . Said solution initiates an exothermic reaction upon neutralization with the stomach acid, warming the stomach contents above the 50°C . PCL melting point.

Claims

1. A medical device for occupying a space within a patient's body, the medical device comprising: a device body having an interior reservoir; a fluid filler material configured to expand within the interior reservoir; a fill valve configured to deliver the fluid filler material into the interior reservoir, wherein expansion of the fluid filler material increases pressure against the fill valve, wherein the fill valve comprises a first layer and a second layer and a flow control material between the first layer and the second layer, wherein the fill valve comprises a first fluid path between the first layer and the second layer, wherein the fluid filler material closes the first fluid path by pressing the first layer and the second layer toward the flow control material such that the first fluid path is closed; a release channel providing a second fluid path between an exterior of the device body and the interior reservoir; a restraining element that closes the release channel such that the restraining element temporarily fluidly constrains the release channel closed to prevent fluid transfer between the exterior of the device body and the interior reservoir, wherein the restraining element is monolithic; and wherein the fluid filler material degrades the restraining element to unseal the release channel.

2. The medical device of claim 1, wherein the restraining element is physically separated from fluids within the patient's body, wherein the restraining element is within the interior reservoir.

3. The medical device of claim 1, further comprising an energy storage element coupled to the release channel, wherein the energy storage element is an elastically resilient member, wherein the elastically resilient member is configured to expand the release channel upon degradation of the restraining element.

4. The medical device of claim 1, wherein the first layer is positioned outside of a surface of the device and comprises a preformed first opening, wherein the second layer is positioned inside of the surface of the device and comprises a preformed second opening, wherein the flow control material is impermeable to fluid, and wherein the fill valve has a first configuration wherein the first fluid path between the first opening and the second opening is configured for access to an interior of the interior reservoir by a catheter, wherein the fill valve has a second configuration wherein the first fluid path is blocked by the flow control material.

5. The medical device of claim 4, wherein a first region of the flow control material is attached to the first layer, wherein a second region of the flow control material is attached to the second layer.
6. The medical device of claim 5, wherein in the first configuration the medical device has no internal pressure such that the first layer and the second layer are separated to form part of the first fluid path, wherein in the second configuration the medical device has an internal pressure such that the first layer and the second layer are juxtaposed to block the first fluid path.
7. The medical device of claim 4, wherein the first layer and the second layer are partially permeable.
8. The medical device of claim 7, wherein the first layer and the second layer are permeable to fluid material and impermeable to non-fluid material.
9. The medical device of claim 1, further comprising an exogenous stimuli configured to cause degradation of the restraining element when the exogenous stimuli acts on the restraining element.
10. A medical device for occupying a space within a patient's body, the medical device comprising: a device body having an interior reservoir; a fluid filler material configured to expand within the interior reservoir; a fill valve configured to deliver the fluid filler material into the interior reservoir, wherein expansion of the fluid filler material increases pressure against the fill valve, wherein the fill valve comprises a first layer and a second layer and a flow control material between the first layer and the second layer, wherein the fill valve comprises a first fluid path between the first layer and the second layer, wherein the fluid filler material closes the first fluid path by pressing the first layer and the second layer toward the flow control material such that the first fluid path is closed; a release channel configured to control flow through a second-first fluid path, where the second fluid path extends between an exterior of the device body and the interior reservoir, the release channel having a sealed configuration preventing flow of the fluid filler material through the second fluid path and an open configuration permitting flow of the fluid filler material through the second fluid path; and a restraining element that closes the release channel in the sealed configuration such that the restraining element temporarily fluidly constrains the release channel closed to prevent fluid transfer between the exterior of the device body and the interior reservoir, wherein the restraining element is monolithic; and wherein the fluid filler material degrades the restraining element to unseal the release channel and to assist in opening the release channel.
11. The medical device of claim 10, wherein the restraining element is physically separated from fluids within the patient's body, wherein the restraining element is within the interior reservoir.
12. The medical device of claim 10, further comprising an energy storage element coupled to the release channel, wherein the energy storage element is an elastically resilient member, wherein the elastically resilient member is configured to expand the release channel upon breakdown of the restraining element.
13. The medical device of claim 10, the first layer is positioned outside of a surface of the device and comprises a preformed first opening, wherein the second layer is positioned inside of the surface of the device and comprises a preformed second opening, wherein the flow control material is impermeable to fluid, and wherein the fill valve has a first configuration wherein the first fluid path between the first opening and the second opening is configured for access to an interior of the interior reservoir by a catheter, wherein the fill valve has a second configuration wherein the first fluid path is blocked by the flow control material.
14. The medical device of claim 13, wherein a first region of the flow control material is attached to the first layer, wherein a second region of the flow control material is attached to the second layer.
15. The medical device of claim 14, wherein in the first configuration the medical device has no internal pressure such that the first layer and the second layer are separated to form part of the first fluid path, wherein in the second configuration the medical device has an internal pressure such that the first layer and the second layer are juxtaposed to block the first fluid path.

16. The medical device of claim 13, wherein the first layer and the second layer are partially permeable.

17. The medical device of claim 16, wherein the first layer and the second layer are permeable to fluid material and impermeable to non-fluid material.

18. The medical device of claim 10, further comprising an exogenous stimuli configured to cause degradation of the restraining element when the exogenous stimuli acts on the restraining element.
