



US012409272B2

(12) **United States Patent**
Lannan et al.

(10) **Patent No.:** **US 12,409,272 B2**

(45) **Date of Patent:** **Sep. 9, 2025**

(54) **PREFILLED SYRINGE WITH BREAKAWAY FORCE FEATURE**

(71) Applicant: **Antares Pharma, Inc.**, Ewing, NJ (US)

(72) Inventors: **James W. Lannan**, Brooklyn Center, MN (US); **Julius C. Sund**, Plymouth, MN (US)

(73) Assignee: **Antares Pharma, Inc.**, Ewing, NJ (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 262 days.

(21) Appl. No.: **18/169,774**

(22) Filed: **Feb. 15, 2023**

(65) **Prior Publication Data**

US 2023/0191031 A1 Jun. 22, 2023

Related U.S. Application Data

(63) Continuation of application No. 16/591,169, filed on Oct. 2, 2019, now Pat. No. 11,602,597, which is a (Continued)

(51) **Int. Cl.**
A61B 5/20 (2006.01)
A61M 5/20 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **A61M 5/2033** (2013.01); **A61M 5/50** (2013.01); **A61M 2005/2013** (2013.01); **A61M 2005/2073** (2013.01); **A61M 2005/3267** (2013.01)

(58) **Field of Classification Search**
CPC .. A61M 2005/2013; A61M 2005/2073; A61M 2005/3267; A61M 5/2033; A61M 5/50
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,688,765 A 9/1972 Gasaway
3,712,301 A 1/1973 Sarnoff
(Continued)

FOREIGN PATENT DOCUMENTS

AR 00081651 10/2012
AR 082053 11/2012
(Continued)

OTHER PUBLICATIONS

Office Action for Korean Patent Application No. 10-2014-7027887 dated Mar. 8, 2016, 7 pages.

(Continued)


Primary Examiner — Deanna K Hall

(74) *Attorney, Agent, or Firm* — Morgan, Lewis & Bockius LLP

(57) **ABSTRACT**

A jet injector that includes a prefilled syringe. The syringe includes a fluid chamber that contains a medicament. The syringe also has an injection-assisting needle, and a plunger is movable within the fluid chamber. A housing is configured for allowing insertion of the needle to a penetration depth. The housing includes a retractable guard and an interference component, e.g., a lock ring, adjacent to the retractable guard that interferes with the movement of the retractable guard. An energy source is configured for biasing the plunger to produce an injecting pressure to jet inject the medicament from the fluid chamber through the needle to an injection site.

21 Claims, 11 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/702,275, filed on May 1, 2015, now Pat. No. 10,478,559, which is a continuation of application No. 13/785,582, filed on Mar. 5, 2013, now Pat. No. 9,486,583.

- (60) Provisional application No. 61/607,339, filed on Mar. 6, 2012.

(51) **Int. Cl.**

A61M 5/50 (2006.01)

A61M 5/32 (2006.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,797,489	A	3/1974	Sarnoff	6,270,479	B1	8/2001	Bergens et al.
3,882,863	A	5/1975	Sarnoff et al.	6,371,939	B2	4/2002	Bergens et al.
4,484,910	A	11/1984	Sarnoff et al.	6,391,003	B1	5/2002	Lesch, Jr.
4,558,690	A	12/1985	Joyce	6,428,528	B2	8/2002	Sadowski et al.
4,624,660	A	11/1986	Mijers et al.	6,517,517	B1	2/2003	Farrugia et al.
4,661,098	A	4/1987	Bekkering et al.	6,530,904	B1	3/2003	Edwards et al.
4,664,653	A	5/1987	Sagstetter et al.	6,544,234	B1	4/2003	Gabriel
4,678,461	A	7/1987	Mesa	6,565,553	B2	5/2003	Sadowski et al.
4,820,286	A	4/1989	van der Wal	6,569,123	B2	5/2003	Alchas et al.
4,822,340	A	4/1989	Kamstra	6,569,143	B2	5/2003	Alchas et al.
4,986,816	A	1/1991	Steiner et al.	6,607,508	B2	8/2003	Knauer
5,042,977	A	8/1991	Bechtold et al.	6,641,561	B1	11/2003	Hill et al.
5,078,680	A	1/1992	Sarnoff	6,656,150	B2	12/2003	Hill et al.
5,085,641	A	2/1992	Samoff et al.	6,673,035	B1	1/2004	Rice et al.
5,085,642	A	2/1992	Samoff et al.	6,682,504	B2	1/2004	Nelson et al.
5,092,842	A	3/1992	Bechtold et al.	6,746,429	B2	6/2004	Sadowski et al.
5,102,393	A	4/1992	Sarnoff et al.	6,767,336	B1	7/2004	Kaplan
5,114,406	A	5/1992	Gabriel et al.	6,830,560	B1	12/2004	Gross et al.
5,163,907	A	11/1992	Szuskiewicz	6,932,793	B1	8/2005	Marshall et al.
5,176,643	A	1/1993	Kramer et al.	6,932,794	B2	8/2005	Giambattista et al.
5,180,370	A	1/1993	Gillespie	6,969,370	B2	11/2005	Langley et al.
5,195,983	A	3/1993	Boese	6,969,372	B1	11/2005	Halseth
5,271,744	A	12/1993	Kramer et al.	6,979,316	B1	12/2005	Rubin et al.
5,279,543	A	1/1994	Glikfeld et al.	6,986,758	B2	1/2006	Schiffmann
5,300,030	A	4/1994	Crossman et al.	6,997,901	B2	2/2006	Popovsky
5,342,308	A	8/1994	Boschetti	7,066,907	B2	6/2006	Crossman et al.
5,354,286	A	10/1994	Mesa et al.	7,118,553	B2	10/2006	Scherer
5,358,489	A	10/1994	Wyrick	7,169,132	B2	1/2007	Bendek et al.
5,391,151	A	2/1995	Wilmot	7,195,616	B2	3/2007	Diller et al.
5,425,715	A	6/1995	Dalling et al.	7,218,962	B2	5/2007	Freyman
5,478,316	A	12/1995	Bitdinger et al.	7,247,149	B2	7/2007	Beyerlein
5,514,097	A	5/1996	Knauer	7,291,132	B2	11/2007	DeRuntz et al.
5,540,664	A	7/1996	Wyrick	7,292,885	B2	11/2007	Scott et al.
5,567,160	A	10/1996	Massino	7,297,136	B2	11/2007	Wyrick
5,569,192	A	10/1996	van der Wal	7,341,575	B2	3/2008	Rice et al.
5,593,388	A	1/1997	Phillips	7,361,160	B2	4/2008	Hommann et al.
5,599,302	A	2/1997	Lilley et al.	7,390,314	B2	6/2008	Stutz, Jr. et al.
5,658,259	A	8/1997	Pearson et al.	7,390,319	B2	6/2008	Friedman
5,665,071	A	9/1997	Wyrick	7,407,492	B2	8/2008	Gurtner
5,681,291	A	10/1997	Galli	7,416,540	B2	8/2008	Edwards et al.
5,695,472	A	12/1997	Wyrick	7,449,012	B2	11/2008	Young et al.
5,820,602	A	10/1998	Kovelman et al.	7,488,308	B2	2/2009	Lesch, Jr.
5,836,911	A	11/1998	Marzynski et al.	7,488,313	B2	2/2009	Segal et al.
5,843,036	A	12/1998	Olive et al.	7,488,314	B2	2/2009	Segal et al.
5,851,197	A	12/1998	Marano et al.	7,517,342	B2	4/2009	Scott et al.
5,891,085	A	4/1999	Lilley et al.	7,519,418	B2	4/2009	Scott et al.
5,891,086	A	4/1999	Weston	7,544,188	B2	6/2009	Edwards et al.
5,919,159	A	7/1999	Lilley et al.	7,547,293	B2	6/2009	Williamson et al.
5,935,949	A	8/1999	White	7,569,035	B1	8/2009	Wilmot et al.
6,045,534	A	4/2000	Jacobson et al.	7,611,491	B2	11/2009	Pickhard
6,077,247	A	6/2000	Marshall et al.	7,621,887	B2	11/2009	Griffiths et al.
6,090,070	A	7/2000	Hager et al.	7,621,891	B2	11/2009	Wyrick
6,099,504	A	8/2000	Gross et al.	7,635,348	B2	12/2009	Raven et al.
6,102,896	A	8/2000	Roser	7,637,891	B2	12/2009	Wall
6,203,529	B1	3/2001	Gabriel et al.	7,648,482	B2	1/2010	Edwards et al.
6,210,369	B1	4/2001	Wilmot et al.	7,648,483	B2	1/2010	Edwards et al.
6,221,046	B1	4/2001	Burroughs et al.	7,654,983	B2	2/2010	De La Sema et al.
6,241,709	B1	6/2001	Bechtold et al.	7,658,724	B2	2/2010	Rubin et al.
6,245,347	B1	6/2001	Zhang et al.	7,670,314	B2	3/2010	Wall et al.
				7,704,237	B2	4/2010	Fisher et al.
				7,717,877	B2	5/2010	Lavi et al.
				7,722,595	B2	5/2010	Pettis et al.
				7,731,686	B2	6/2010	Edwards et al.
				7,731,690	B2	6/2010	Edwards et al.
				7,736,333	B2	6/2010	Gillespie, III
				7,744,582	B2	6/2010	Sadowski et al.
				7,749,194	B2	7/2010	Edwards et al.
				7,749,195	B2	7/2010	Hommann
				7,762,996	B2	7/2010	Palasis
				7,776,015	B2	8/2010	Sadowski et al.
				7,794,432	B2	9/2010	Young et al.
				7,811,254	B2	10/2010	Wilmot et al.
				7,862,543	B2	1/2011	Potter et al.
				7,896,841	B2	3/2011	Wall et al.
				7,901,377	B1	3/2011	Harrison et al.
				7,905,352	B2	3/2011	Wyrick
				7,905,866	B2	3/2011	Haider et al.
				7,918,823	B2	4/2011	Edwards et al.
				7,927,303	B2	4/2011	Wyrick

(56)

References Cited

U.S. PATENT DOCUMENTS

7,931,618 B2	4/2011	Wyrick	2004/0267355 A1	12/2004	Scott et al.
7,947,017 B2	5/2011	Edwards et al.	2005/0027255 A1	2/2005	Lavi et al.
RE42,463 E	6/2011	Landau	2005/0101919 A1	5/2005	Brunnberg
7,955,304 B2	6/2011	Guillermo	2005/0165363 A1	7/2005	Judson et al.
7,967,772 B2	6/2011	Mckenzie et al.	2005/0209569 A1	9/2005	Ishikawa et al.
7,988,675 B2	8/2011	Gillespie, III et al.	2005/0215955 A1	9/2005	Slawson
8,016,774 B2	9/2011	Freeman et al.	2005/0240145 A1	10/2005	Scott et al.
8,016,788 B2	9/2011	Edwards et al.	2005/0256499 A1	11/2005	Pettis et al.
8,021,335 B2	9/2011	Lesch, Jr.	2005/0273054 A1	12/2005	Asch
8,048,035 B2	11/2011	Mesa et al.	2006/0106362 A1	5/2006	Pass et al.
8,048,037 B2	11/2011	Kohlbrener et al.	2006/0129122 A1	6/2006	Wyrick
8,057,427 B2	11/2011	Griffiths et al.	2006/0224124 A1	10/2006	Scherer
8,066,659 B2	11/2011	Joshi et al.	2006/0258988 A1	11/2006	Keitel et al.
8,083,711 B2	12/2011	Enggaard	2006/0258990 A1	11/2006	Weber
8,100,865 B2	1/2012	Spofforth	2007/0017533 A1	1/2007	Wyrick
8,105,272 B2	1/2012	Williamson et al.	2007/0025890 A1	2/2007	Joshi et al.
8,105,281 B2	1/2012	Edwards et al.	2007/0027430 A1	2/2007	Hommann
8,110,209 B2	2/2012	Prestrelski et al.	2007/0100288 A1	5/2007	Bozeman et al.
8,123,719 B2	2/2012	Edwards et al.	2007/0112310 A1	5/2007	Lavi et al.
8,123,724 B2	2/2012	Gillespie, III	2007/0123818 A1	5/2007	Griffiths et al.
8,162,873 B2	4/2012	Muto et al.	2007/0129687 A1	6/2007	Marshall et al.
8,162,886 B2	4/2012	Sadowski et al.	2007/0185432 A1	8/2007	Etheredge et al.
8,167,840 B2	5/2012	Matusch	2007/0191784 A1	8/2007	Jacobs et al.
8,167,866 B2	5/2012	Klein	2007/0219498 A1	9/2007	Malone et al.
8,177,758 B2	5/2012	Brooks, Jr. et al.	2008/0059133 A1	3/2008	Edwards et al.
8,187,224 B2	5/2012	Wyrick	2008/0154199 A1	6/2008	Wyrick
8,216,180 B2	7/2012	Tschirren et al.	2008/0262427 A1	10/2008	Hommann
8,216,192 B2	7/2012	Burroughs et al.	2008/0262436 A1	10/2008	Olson
8,226,618 B2	7/2012	Geertsen	2008/0262445 A1	10/2008	Hsu et al.
8,226,631 B2	7/2012	Boyd et al.	2009/0124981 A1	5/2009	Evans
8,233,135 B2	7/2012	Jansen et al.	2009/0124997 A1	5/2009	Pettis et al.
8,235,952 B2	8/2012	Wikner	2009/0204062 A1	8/2009	Muto et al.
8,246,577 B2	8/2012	Schrul et al.	2009/0254035 A1	10/2009	Kohlbrener et al.
8,251,947 B2	8/2012	Kramer et al.	2009/0299278 A1	12/2009	Lesch, Jr. et al.
8,257,318 B2	9/2012	Thogersen et al.	2009/0304812 A1	12/2009	Stainforth et al.
8,257,319 B2	9/2012	Plumptre	2009/0318361 A1	12/2009	Noera et al.
8,267,899 B2	9/2012	Moller	2010/0036318 A1	2/2010	Raday et al.
8,267,900 B2	9/2012	Harms et al.	2010/0049125 A1	2/2010	James et al.
8,273,798 B2	9/2012	Bausch et al.	2010/0069845 A1	3/2010	Marshall et al.
8,275,454 B2	9/2012	Adachi et al.	2010/0076378 A1	3/2010	Runfol
8,276,583 B2	10/2012	Farieta et al.	2010/0076400 A1	3/2010	Wall
8,277,412 B2	10/2012	Kronstedt	2010/0087847 A1	4/2010	Hong
8,277,413 B2	10/2012	Kirchhofer	2010/0094214 A1	4/2010	Abry et al.
8,298,175 B2	10/2012	Hirschel et al.	2010/0094324 A1	4/2010	Huang et al.
8,298,194 B2	10/2012	Moller	2010/0100039 A1	4/2010	Wyrick
8,300,852 B2	10/2012	Terada	2010/0152699 A1	6/2010	Ferrari et al.
RE43,834 E	11/2012	Steenfeldt-Jensen et al.	2010/0152702 A1	6/2010	Vigil et al.
8,308,232 B2	11/2012	Zamperla et al.	2010/0160894 A1	6/2010	Julian et al.
8,308,695 B2	11/2012	Laios	2010/0168677 A1	7/2010	Gabriel et al.
8,313,466 B2	11/2012	Edwards et al.	2010/0174268 A1	7/2010	Wilmot et al.
8,317,757 B2	11/2012	Plumptre	2010/0204678 A1	8/2010	Imran
8,323,237 B2	12/2012	Radmer et al.	2010/0217105 A1	8/2010	Yodfat et al.
8,333,739 B2	12/2012	Moller	2010/0228193 A1	9/2010	Wyrick
8,337,472 B2	12/2012	Edginton et al.	2010/0249746 A1	9/2010	Klein
8,343,103 B2	1/2013	Moser	2010/0256570 A1	10/2010	Maritan
8,343,109 B2	1/2013	Marshall et al.	2010/0258631 A1	10/2010	Rueblinger et al.
8,348,905 B2	1/2013	Radmer et al.	2010/0262082 A1	10/2010	Brooks et al.
8,353,878 B2	1/2013	Moller et al.	2010/0274198 A1	10/2010	Bechtold
8,357,120 B2	1/2013	Moller et al.	2010/0274273 A1	10/2010	Schraga et al.
8,357,125 B2	1/2013	Grunhut et al.	2010/0288593 A1	11/2010	Chiesa et al.
8,361,036 B2	1/2013	Moller et al.	2010/0292643 A1	11/2010	Wilmot et al.
8,366,680 B2	2/2013	Raab	2010/0298780 A1	11/2010	Laios
8,372,031 B2	2/2013	Elmen et al.	2010/0312196 A1	12/2010	Hirschel et al.
8,372,042 B2	2/2013	Wieselblad	2010/0318035 A1	12/2010	Edwards et al.
8,376,993 B2	2/2013	Cox et al.	2010/0318037 A1	12/2010	Young et al.
8,398,593 B2	3/2013	Fich et al.	2010/0324480 A1	12/2010	Chun
8,409,149 B2	4/2013	Hommann et al.	2011/0021989 A1	1/2011	Janek et al.
8,435,215 B2	5/2013	Arby et al.	2011/0054414 A1	3/2011	Shang et al.
2001/0039394 A1	11/2001	Weston	2011/0077599 A1	3/2011	Wozencroft
2002/0173752 A1	11/2002	Polzin	2011/0087192 A1	4/2011	Uhland et al.
2003/0040697 A1	2/2003	Pass et al.	2011/0098655 A1	4/2011	Jennings et al.
2003/0171717 A1	9/2003	Farrugia et al.	2011/0125076 A1	5/2011	Kraft et al.
2004/0039337 A1	2/2004	Etzing	2011/0125100 A1	5/2011	Schwartz et al.
2004/0143213 A1	7/2004	Hunter et al.	2011/0137246 A1	6/2011	Cali et al.
2004/0220524 A1	11/2004	Sadowski et al.	2011/0144594 A1*	6/2011	Sund A61M 5/31571 604/228
			2011/0190725 A1	8/2011	Pettis et al.
			2011/0196300 A1	8/2011	Edwards et al.
			2011/0196311 A1	8/2011	Bicknell et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2011/0208119	A1	8/2011	Asmussen et al.	2012/0283649	A1	11/2012	Veasey et al.
2011/0224620	A1	9/2011	Johansen et al.	2012/0283650	A1	11/2012	MacDonald et al.
2011/0238003	A1	9/2011	Bruno-Raimondi et al.	2012/0283651	A1	11/2012	Veasey et al.
2011/0269750	A1	11/2011	Kley et al.	2012/0283652	A1	11/2012	MacDonald et al.
2011/0319864	A1	12/2011	Beller et al.	2012/0283654	A1	11/2012	MacDonald et al.
2012/0004608	A1*	1/2012	Lesch, Jr. A61M 5/178 604/135	2012/0283660	A1	11/2012	Jones et al.
2012/0016296	A1	1/2012	Cleathero	2012/0283661	A1	11/2012	Jugl et al.
2012/0046609	A1	2/2012	Mesa et al.	2012/0289907	A1	11/2012	Veasey et al.
2012/0053563	A1	3/2012	Du	2012/0289908	A1	11/2012	Kouyoumjian et al.
2012/0059319	A1	3/2012	Segal	2012/0289909	A1	11/2012	Raab et al.
2012/0071829	A1	3/2012	Edwards et al.	2012/0289929	A1	11/2012	Boyd et al.
2012/0095443	A1	4/2012	Ferrari et al.	2012/0291778	A1	11/2012	Nagel et al.
2012/0101475	A1	4/2012	Wilmot et al.	2012/0296276	A1	11/2012	Nicholls et al.
2012/0116318	A1	5/2012	Edwards et al.	2012/0296287	A1	11/2012	Veasey et al.
2012/0123350	A1	5/2012	Giambattista et al.	2012/0302989	A1	11/2012	Kramer et al.
2012/0123385	A1	5/2012	Edwards et al.	2012/0302992	A1	11/2012	Brooks et al.
2012/0130318	A1	5/2012	Young	2012/0310156	A1	12/2012	Karlsson et al.
2012/0130342	A1	5/2012	Cleathero	2012/0310206	A1	12/2012	Kouyoumjian et al.
2012/0136303	A1	5/2012	Cleathero	2012/0310208	A1	12/2012	Kirchhofer
2012/0136318	A1	5/2012	Anin et al.	2012/0310289	A1	12/2012	Bottlang et al.
2012/0143144	A1	6/2012	Young	2012/0316508	A1	12/2012	Kirchhofer
2012/0157931	A1	6/2012	Nzike	2012/0323177	A1	12/2012	Adams et al.
2012/0157965	A1	6/2012	Wotton et al.	2012/0323186	A1	12/2012	Karlsen et al.
2012/0172809	A1	7/2012	Plumptre	2012/0325865	A1	12/2012	Forstreuter et al.
2012/0172811	A1	7/2012	Enggaard et al.	2012/0330228	A1	12/2012	Day et al.
2012/0172812	A1	7/2012	Plumptre et al.	2013/0006191	A1	1/2013	Jugl et al.
2012/0172813	A1	7/2012	Plumptre et al.	2013/0006192	A1	1/2013	Teucher et al.
2012/0172814	A1	7/2012	Plumptre et al.	2013/0006193	A1	1/2013	Veasey et al.
2012/0172815	A1	7/2012	Holmqvist	2013/0006310	A1	1/2013	Bottlang et al.
2012/0172816	A1	7/2012	Boyd et al.	2013/0012871	A1	1/2013	Pommereu
2012/0172818	A1	7/2012	Harms et al.	2013/0012884	A1	1/2013	Pommerau et al.
2012/0179100	A1	7/2012	Sadowski et al.	2013/0012885	A1	1/2013	Bode et al.
2012/0179137	A1	7/2012	Bartlett et al.	2013/0018310	A1	1/2013	Boyd et al.
2012/0184900	A1	7/2012	Marshall et al.	2013/0018313	A1	1/2013	Kramer et al.
2012/0184917	A1	7/2012	Bom et al.	2013/0018317	A1	1/2013	Bobroff et al.
2012/0184918	A1	7/2012	Bostrom	2013/0018323	A1	1/2013	Boyd et al.
2012/0186075	A1	7/2012	Edginton	2013/0018327	A1	1/2013	Dasbach et al.
2012/0191048	A1	7/2012	Eaton	2013/0018328	A1	1/2013	Jugl et al.
2012/0191049	A1	7/2012	Harms et al.	2013/0023830	A1	1/2013	Bode
2012/0197209	A1	8/2012	Bicknell et al.	2013/0030367	A1	1/2013	Wotton et al.
2012/0197213	A1	8/2012	Kohlbrenner et al.	2013/0030378	A1	1/2013	Jugl et al.
2012/0203184	A1	8/2012	Selz et al.	2013/0030383	A1	1/2013	Keitel
2012/0203185	A1	8/2012	Kristensen et al.	2013/0030409	A1	1/2013	Macdonald et al.
2012/0203186	A1	8/2012	Vogt et al.	2013/0035641	A1	2/2013	Moller et al.
2012/0209192	A1	8/2012	Alexandersson	2013/0035642	A1	2/2013	Daniel
2012/0209200	A1	8/2012	Jones et al.	2013/0035644	A1	2/2013	Giambattista et al.
2012/0209210	A1	8/2012	Plumptre et al.	2013/0035645	A1	2/2013	Bicknell et al.
2012/0209211	A1	8/2012	Plumptre et al.	2013/0035647	A1	2/2013	Veasey et al.
2012/0209212	A1	8/2012	Plumptre et al.	2013/0041321	A1	2/2013	Cross et al.
2012/0215162	A1	8/2012	Nielsen et al.	2013/0041324	A1	2/2013	Daniel
2012/0215176	A1	8/2012	Veasey et al.	2013/0041325	A1	2/2013	Helmer et al.
2012/0220929	A1	8/2012	Nagel et al.	2013/0041327	A1	2/2013	Daniel
2012/0220941	A1	8/2012	Jones	2013/0041328	A1	2/2013	Daniel
2012/0220953	A1	8/2012	Holmqvist	2013/0041347	A1	2/2013	Daniel
2012/0220954	A1	8/2012	Cowe	2013/0060231	A1	3/2013	Adlon et al.
2012/0226226	A1	9/2012	Edwards et al.				
2012/0230620	A1	9/2012	Holdgate et al.				
2012/0232517	A1	9/2012	Saiki				
2012/0245516	A1	9/2012	Tschirren et al.				
2012/0245532	A1	9/2012	Frantz et al.				
2012/0253274	A1	10/2012	Karlsson et al.				
2012/0253287	A1	10/2012	Giambattista et al.				
2012/0253288	A1	10/2012	Dasbach et al.				
2012/0253289	A1	10/2012	Cleathero				
2012/0253290	A1	10/2012	Geertsen				
2012/0253314	A1	10/2012	Harish et al.				
2012/0259285	A1	10/2012	Schabbach et al.				
2012/0265153	A1	10/2012	Jugl et al.				
2012/0267761	A1	10/2012	Kim et al.				
2012/0271233	A1	10/2012	Bruggemann et al.				
2012/0271243	A1	10/2012	Plumptre et al.				
2012/0277724	A1	11/2012	Larsen et al.				
2012/0283645	A1	11/2012	Veasey et al.				
2012/0283648	A1	11/2012	Veasey et al.				

FOREIGN PATENT DOCUMENTS

AU	2007253481	11/2007
AU	2007301890	4/2008
AU	2008231897	10/2008
AU	2008309660	4/2009
AU	2009217376	10/2009
AU	2009272992	1/2010
AU	2009299888	4/2010
AU	2009326132	8/2011
AU	2009326321	8/2011
AU	2009326322	8/2011
AU	2009326323	8/2011
AU	2009326324	8/2011
AU	2009326325	8/2011
AU	2009341040	9/2011
AU	2010233924	11/2011
AU	2010239762	12/2011
AU	2010242096	12/2011
AU	2010254627	1/2012
AU	2010260568	2/2012
AU	2010260569	2/2012
AU	2010287033	4/2012

(56)	References Cited		CN	102548601	7/2012
	FOREIGN PATENT DOCUMENTS		CN	102548602	7/2012
			CN	102573955	7/2012
			CN	102573958	7/2012
AU	2010303987	5/2012	CN	102573960	7/2012
AU	2010332857	7/2012	CN	102573963	7/2012
AU	2010332862	7/2012	CN	102630172	8/2012
AU	2010337136	7/2012	CN	102630173	8/2012
AU	2010338469	7/2012	CN	102630174	8/2012
AU	2010314315	8/2012	CN	102639170	8/2012
AU	2011212490	8/2012	CN	102639171	8/2012
AU	2011212556	8/2012	CN	102648014	8/2012
AU	2011212558	8/2012	CN	102655899	9/2012
AU	2011212561	8/2012	CN	102665800	9/2012
AU	2011212564	8/2012	CN	102665802	9/2012
AU	2011212566	8/2012	CN	102686255	9/2012
AU	2011212567	8/2012	CN	102686256	9/2012
AU	2011214922	8/2012	CN	102686258	9/2012
AU	2011221472	8/2012	CN	102695531	9/2012
AU	2011231688	9/2012	CN	102695532	9/2012
AU	2011231691	9/2012	CN	102711878	10/2012
AU	2011224884	10/2012	CN	102727965	10/2012
AU	2011231570	10/2012	CN	102740907	10/2012
AU	2011231697	10/2012	CN	102753222	10/2012
AU	2011233733	10/2012	CN	102753223	10/2012
AU	2011234479	10/2012	CN	102753224	10/2012
AU	2011238967	11/2012	CN	102753227	10/2012
AU	2011244232	11/2012	CN	102770170	11/2012
AU	2011244236	11/2012	CN	102770173	11/2012
AU	2011244237	11/2012	CN	102781499	11/2012
AU	2011249098	11/2012	CN	102781500	11/2012
AU	2011262408	12/2012	CN	102802699	11/2012
AU	2011270934	1/2013	CN	102802702	11/2012
AU	2011273721	1/2013	CN	102802703	11/2012
AU	2011273722	1/2013	CN	102665801	12/2012
AU	2011273723	1/2013	CN	102821801	12/2012
AU	2011273724	1/2013	CN	102821802	12/2012
AU	2011273725	1/2013	CN	102821805	12/2012
AU	2011273726	1/2013	CN	102834133	12/2012
AU	2011273727	1/2013	CN	102869399	1/2013
AU	2011273728	1/2013	CN	102895718	1/2013
BR	0208013	3/2004	CN	102905613	1/2013
BR	0308262	1/2005	CN	102905742	1/2013
BR	PI712805	10/2012	CN	102905743	1/2013
BR	PI0713802-4	11/2012	CN	102905744	1/2013
BR	0214721	12/2012	CN	102905745	1/2013
CA	2552177	7/1999	CN	102917738	2/2013
CA	2689022	11/2002	CN	102917743	2/2013
CA	2473371	7/2003	DE	102006041809	3/2008
CA	2557897	10/2005	DE	202011110155	12/2012
CA	02702412	12/2008	DK	1646844	12/2009
CN	101094700	12/2007	DK	2229201	7/2012
CN	101128231	2/2008	DK	2023982	10/2012
CN	101184520	5/2008	DK	2274032	10/2012
CN	101400394	4/2009	DK	02346552	11/2012
CN	101405582	4/2009	DK	1888148	1/2013
CN	101479000	7/2009	DK	2288400	1/2013
CN	101511410	8/2009	DK	2373361	1/2013
CN	101516421	8/2009	DK	1885414	2/2013
CN	101557849	10/2009	DK	2174682	2/2013
CN	101563123	10/2009	DK	2310073	2/2013
CN	101563124	10/2009	EG	25844	9/2012
CN	101594898	12/2009	EP	245895	11/1987
CN	101600468	12/2009	EP	255044	2/1988
CN	101605569	12/2009	EP	361668	4/1990
CN	101610804	12/2009	EP	525525	2/1993
CN	101626796	1/2010	EP	1067823	1/2001
CN	101678166	3/2010	EP	1307012	5/2003
CN	101678172	3/2010	EP	1140260	8/2005
CN	101678173	3/2010	EP	1944050	7/2008
CN	101687078	3/2010	EP	2174682	4/2010
CN	101687079	3/2010	EP	2258424	12/2010
CN	101687080	3/2010	EP	2258425	12/2010
CN	101715371	5/2010	EP	02275158	1/2011
CN	101909673	12/2010	EP	2364742	9/2011
CN	101912650	12/2010	EP	2393062	12/2011
CN	101939034	1/2011	EP	2471564	7/2012
CN	101939036	1/2011	EP	02477681	7/2012
CN	102548599	7/2012	EP	02484395	8/2012

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	2526987	11/2012	JP	2012528622	11/2012
EP	02529773	12/2012	JP	2012528623	11/2012
EP	02529774	12/2012	JP	2012528624	11/2012
EP	02529775	12/2012	JP	2012528625	11/2012
EP	2549789	1/2013	JP	2012528626	11/2012
EP	2900299 B1	7/2020	JP	2012528627	11/2012
ES	02385630	7/2012	JP	2012528628	11/2012
ES	2389866	11/2012	JP	2012528629	11/2012
ES	2392667	12/2012	JP	2012528630	11/2012
ES	02393173	12/2012	JP	2012528631	11/2012
ES	2394556	2/2013	JP	2012528632	11/2012
GB	2463034	3/2010	JP	2012528633	11/2012
IL	171247	8/2012	JP	2012528634	11/2012
IL	198750	10/2012	JP	2012528635	11/2012
JP	H 8-505543 A	6/1998	JP	2012528636	11/2012
JP	2003-512904 A	4/2003	JP	2012528637	11/2012
JP	2007-500530 A	1/2007	JP	2012528638	11/2012
JP	5016490	5/2008	JP	2012528639	11/2012
JP	2008-528126 A	7/2008	JP	2012528640	11/2012
JP	5026411	11/2008	JP	2012530576	12/2012
JP	5033792	11/2008	JP	2012532635	12/2012
JP	5074397	2/2009	JP	2012532636	12/2012
JP	2009-529395	8/2009	JP	2012532717	12/2012
JP	5066177	9/2009	JP	2012532720	12/2012
JP	5039135	11/2009	JP	2012532721	12/2012
JP	5044625	12/2009	JP	2012532722	12/2012
JP	2010-005414	1/2010	JP	5112330	1/2013
JP	2010-046507	3/2010	JP	5113847	1/2013
JP	2011-513035 A	4/2011	JP	2015-521055 A	7/2015
JP	4970282	7/2012	KR	101160735	7/2012
JP	4970286	7/2012	KR	20120091009	8/2012
JP	4972147	7/2012	KR	20120091153	8/2012
JP	4977209	7/2012	KR	20120091154	8/2012
JP	4977252	7/2012	KR	20120095919	8/2012
JP	4979686	7/2012	KR	20120099022	9/2012
JP	4982722	7/2012	KR	20120099101	9/2012
JP	2012515566	7/2012	KR	20120102597	9/2012
JP	2012515585	7/2012	KR	20120106754	9/2012
JP	2012515587	7/2012	KR	20120106756	9/2012
JP	2012516168	7/2012	KR	20120112503	10/2012
JP	2012516736	7/2012	MX	2012006694	7/2012
JP	2012516737	7/2012	NO	332622	10/2003
JP	4990151	8/2012	NZ	572765	8/2012
JP	4992147	8/2012	NZ	587235	8/2012
JP	4994370	8/2012	NZ	00590352	10/2012
JP	5001001	8/2012	PL	2023982	11/2012
JP	2012143646	8/2012	PT	2274032	10/2012
JP	2012148198	8/2012	PT	2346552	11/2012
JP	2012519508	8/2012	RU	2462275	3/2011
JP	2012519514	8/2012	RU	2459247	8/2012
JP	UP 2012519511	8/2012	RU	2011104496	8/2012
JP	2012176295	9/2012	RU	2460546	9/2012
JP	2012183322	9/2012	RU	2011109925	10/2012
JP	2012520128	9/2012	RU	2011119019	11/2012
JP	2012521821	9/2012	SG	181710	7/2012
JP	2012521825	9/2012	SG	181790	7/2012
JP	2012521826	9/2012	SG	184182	10/2012
JP	2012521827	9/2012	SG	184328	11/2012
JP	2012521828	9/2012	SG	184500	11/2012
JP	2012521829	9/2012	SG	184501	11/2012
JP	2012521830	9/2012	SG	184502	11/2012
JP	2012521831	9/2012	SI	2274032	12/2012
JP	2012521834	9/2012	SI	2346552	12/2012
JP	2012522547	9/2012	WO	88/08724	11/1988
JP	2012-525172	10/2012	WO	91/13299	9/1991
JP	2012-525180	10/2012	WO	91/13430	9/1991
JP	2012-525185	10/2012	WO	9411041 A1	5/1994
JP	2012523876	10/2012	WO	94/11041	5/1994
JP	2012525200	10/2012	WO	994011041 A1	5/1994
JP	5084825	11/2012	WO	9831369	7/1998
JP	2012232151	11/2012	WO	9832451	7/1998
JP	2012528618	11/2012	WO	9922789	5/1999
JP	2012528619	11/2012	WO	9962525	12/1999
JP	2012528620	11/2012	WO	0006228	2/2000
JP	2012528621	11/2012	WO	01/32255 A1	5/2001
			WO	02/083216	10/2002
			WO	2089805	11/2002
			WO	3047663	6/2003
			WO	3068290	8/2003
			WO	03070296	8/2003

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	03095003	A1	11/2003
WO	WO 3097133		11/2003
WO	WO 2003095003	A1	11/2003
WO	WO 2004/041331		5/2004
WO	WO 2004/047892		6/2004
WO	2004/086631	A2	10/2004
WO	WO 2005/005929		1/2005
WO	WO 2005/009515		2/2005
WO	WO 2005/053778		6/2005
WO	2006/079064	A1	7/2006
WO	WO 2006/125328		11/2006
WO	WO 2006/130098		12/2006
WO	WO 2007/063342		6/2007
WO	WO 2007/100899		9/2007
WO	WO 2006/079064		11/2007
WO	WO 2007/129106		11/2007
WO	WO 2007/131013		11/2007
WO	WO 2007/131025		11/2007
WO	WO 2007/143676		12/2007
WO	WO 2008/005315		1/2008
WO	WO 2008/009476		1/2008
WO	WO 2008/058666		5/2008
WO	WO 2008/100576		8/2008
WO	WO 2008/107378		9/2008
WO	WO 2007/104636		12/2008
WO	WO 2009049885		4/2009
WO	WO 2008/071804		8/2009
WO	2009/114542	A1	9/2009
WO	WO 2009/114542		9/2009
WO	WO 2009/132778		11/2009
WO	WO 2009/141005		11/2009
WO	WO 2010/003569		1/2010
WO	WO 2010/043533		4/2010
WO	WO 2010/046394		4/2010
WO	WO 2010/097116		9/2010
WO	WO 2010/108116		9/2010
WO	WO 2010136078	A1	12/2010
WO	WO 2011/023736		3/2011
WO	WO 2011/023882		3/2011
WO	WO 2011/035877		3/2011
WO	WO 2011/036133		3/2011
WO	WO 2011/036134		3/2011
WO	WO 2011/039163		4/2011
WO	WO 2011/039201		4/2011
WO	WO 2011/039202		4/2011
WO	WO 2011/039207		4/2011
WO	WO 2011/039208		4/2011
WO	WO 2011/039209		4/2011
WO	WO 2011/039211		4/2011
WO	WO 2011/039216		4/2011
WO	WO 2011/039217		4/2011
WO	WO 2011/039218		4/2011
WO	WO 2011/039219		4/2011
WO	WO 2011/039228		4/2011
WO	WO 2011/039231		4/2011
WO	WO 2011/039232		4/2011
WO	WO 2011/039233		4/2011
WO	WO 2011/039236		4/2011
WO	WO 2011/040861		4/2011
WO	WO 2011/045385		4/2011
WO	WO 2011/045386		4/2011
WO	WO 2011/045611		4/2011
WO	WO 2011/046756		4/2011
WO	WO 2011/048223		4/2011
WO	WO 2011/048422		4/2011
WO	WO 2011/050359		4/2011
WO	WO 2011/053225		5/2011
WO	WO 2011/054648		5/2011
WO	WO 2011/054775		5/2011
WO	WO 2011/056127		5/2011
WO	WO 2011/060087		5/2011
WO	WO 2011/067187		6/2011
WO	WO 2011/067268		6/2011
WO	WO 2011/067320		6/2011
WO	WO 2011/067615		6/2011

WO	WO 2011/068253	6/2011
WO	WO 2011/069936	6/2011
WO	WO 2011/073302	6/2011
WO	WO 2011/073307	6/2011
WO	WO 2011/076280	6/2011
WO	WO 2011/080092	7/2011
WO	WO 2011/081867	7/2011
WO	WO 2011/081885	7/2011
WO	WO 2011/089206	7/2011
WO	WO 2011/089207	7/2011
WO	WO 2011/095478	8/2011
WO	WO 2011/095480	8/2011
WO	WO 2011/095483	8/2011
WO	WO 2011/095486	8/2011
WO	WO 2011/095488	8/2011
WO	WO 2011/095489	8/2011
WO	WO 2011/095503	8/2011
WO	WO 2011/099918	8/2011
WO	WO 2011/101349	8/2011
WO	WO 2011/101351	8/2011
WO	WO 2011/101375	8/2011
WO	WO 2011/101376	8/2011
WO	WO 2011/101377	8/2011
WO	WO 2011/101378	8/2011
WO	WO 2011/101379	8/2011
WO	WO 2011/101380	8/2011
WO	WO 2011/101381	8/2011
WO	WO 2011/101382	8/2011
WO	WO 2011/101383	8/2011
WO	2011/117404	9/2011
WO	WO 2011/107805	9/2011
WO	WO 2011/109205	9/2011
WO	WO 2011/110464	9/2011
WO	WO 2011/110465	9/2011
WO	WO 2011/110466	9/2011
WO	WO 2011/111006	9/2011
WO	WO 2011/112136	9/2011
WO	WO 2011/113806	9/2011
WO	WO 2011/117212	9/2011
WO	WO 2011/117284	9/2011
WO	WO 2011/121003	10/2011
WO	WO 2011/121061	10/2011
WO	WO 2011/123024	10/2011
WO	WO 2011/124634	10/2011
WO	WO 2011/126439	10/2011
WO	WO 2012020084	2/2012
WO	WO 2012022771	2/2012
WO	WO 2012/090186	7/2012
WO	WO 2011/042537	8/2012
WO	WO 2011/042540	8/2012
WO	WO 2011/043714	8/2012
WO	WO 2011/051366	9/2012
WO	WO 2012/122643	9/2012
WO	2013/134244	A2 9/2023

OTHER PUBLICATIONS

Office Action for Japanese Patent Application No. 2014-561030 dated Jul. 7, 2016, 11 pages.

English Summary of Office Action for Japanese Patent Application No. 2014-561030 dated Jul. 7, 2016, 11 pages.

English Summary of Office Action for Korean Patent Application No. 10-2014-7027887 dated Mar. 8, 2016, 8 pages.

International Patent Application No. PCT/US14/23883, International Search Report, dated Jul. 10, 2014, 3 pages.

International Patent Application No. PCT/US14/23485, International Search Report, dated Jul. 7, 2014, 2 pages.

International Patent Application No. PCT/US14/24530, International Search Report, dated Jul. 15, 2014, 2 pages.

International Patent Application No. PCT/US14/24543, International Search Report, dated Jul. 28, 2014, 2 pages.

English Summary of the Office Action issued in corresponding Japanese Application No. 2022-135474, dated Aug. 25, 2023, 4 pages.

English Summary of Office Action for corresponding Japanese Patent Application No. 2021-017001 dated May 30, 2022, 2 pages.

(56)

References Cited

OTHER PUBLICATIONS

Japanese Office Action dated Feb. 6, 2020 for Japanese Patent Application No. 2019-060748, 4 pages.

English Summary of Office Action for Japanese Application No. 2021-017001 dated Oct. 19, 2021, 6 pages.

Office Action for EP 13 757 994.2-1122; dated Jun. 18, 2021, 5 pages.

Communication from the European Patent Office for European Patent Application No. EP 13757994.2 dated Feb. 2, 2022 (7 Pages).

Extended European Search Report issued in corresponding Application No. EP 23220455.2, dated Mar. 14, 2024, 11 pages.

European Office Action, dated May 10, 2023, for the corresponding European Patent Application No. 13757994.2, 9 pages.

European Office Action, dated Dec. 12, 2022, for the corresponding European Patent Application No. 13757994.2, 9 pages.

English Summary of Office Action for Japanese Patent Application No. 2017-121208, 6 pages.

* cited by examiner




FIG. 1





FIG. 2






FIG. 4




FIG. 5




FIG.6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11

1

PREFILLED SYRINGE WITH BREAKAWAY FORCE FEATURE

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/591,169 filed Oct. 2, 2019, which is a continuation of U.S. patent application Ser. No. 14/702,275 filed May 1, 2015, now U.S. Pat. No. 10,478,559, which is a continuation of U.S. patent application Ser. No. 13/785,582, filed Mar. 5, 2013, now U.S. Pat. No. 9,486,583 which claims the benefit of priority from U.S. Provisional Patent Application No. 61/607,339 filed Mar. 6, 2012, each of which are incorporated by reference herein for all purposes in their entirety.

BACKGROUND OF THE INVENTION

The present invention relates to a jet injector and in some embodiments a needle-assisted jet injector that uses a low jet injection pressure and has a lock ring that provides break-away force resistance.

Certain jet injection devices have needle guards that must be retracted prior to insertion of the needle and triggering of the jet injection. A certain amount of force is normally required to trigger the jet injection. To assure sufficient needle guard travel for needle insertion and triggering, it is at times desirable to require a breakaway force prior to significant needle guard retraction to assure that insertion of the needle and triggering of triggering force is overcome. The present invention addresses this problem.

SUMMARY OF THE INVENTION

In certain embodiments, the invention relates to a jet injector. In one embodiment, the jet injector includes a prefilled syringe having a container portion defining a fluid chamber containing a medicament; an injection-assisting needle disposed at the distal end of the chamber, having an injecting tip configured for piercing an insertion location, and defining a fluid pathway in fluid communication with the chamber for injecting the fluid from the chamber into an injection site; a plunger movable within the fluid chamber; a housing that houses the prefilled syringe and is configured for allowing insertion of the needle at the injection location to an insertion point that is at a penetration depth below the surface, the housing including: a retractable guard that is movable between a protecting position in which the needle is disposed within the guard and an injecting position in which the tip of the needle is exposed for insertion to the insertion point, and an interference component adjacent to the retractable guard that interferes with the movement of the retractable guard when the retractable component is moved at least partially from the protecting position toward the injecting position; a syringe support supportively mounting the prefilled syringe in the housing; an energy source configured for biasing the plunger with a force selected to produce an injecting pressure on the medicament in the fluid chamber to jet inject the medicament from the fluid chamber through the needle to the injection site.

In certain embodiments, the energy source and prefilled syringe are configured such that the injecting pressure remains between about 80 p.s.i. and about 1000 p.s.i. during injection of the medicament. In one embodiment, the energy source and prefilled syringe are configured such that the injecting pressure remains below about 500 p.s.i. and above

2

about 90 p.s.i. during the injection of the medicament. In another embodiment, the energy source and prefilled syringe are configured to produce the injecting pressure that remains at least at about 100 p.s.i. during the injection of the medicament. In one embodiment, the energy source and prefilled syringe are configured such that the injecting pressure remains up to about 350 p.s.i. during the injection of the medicament.

In certain embodiments, the prefilled syringe has a distal portion in which the injection-assisting needle is located, and a proximal portion opposite the distal portion; and the syringe support axially supports the proximal portion of the pre-filled syringe during the jet injection of the medicament, such that the distal portion of the prefilled syringe is substantially unsupported in an axial direction. In one embodiment, the container portion of the pre-filled syringe is made of blown glass. In another embodiment, the injection-assisting needle is adhered to the glass.

In certain embodiment, the interference component is a ring having at least one abutment arm extending distally from a proximal end dimensioned to fit within the housing, the abutment arm having at least one tapered portion. In one embodiment, the at least one abutment arm has an engagement portion axially adjacent to the at least one tapered portion that is configured to cause resistance to the movement of the retractable guard when the retractable guard is moved at least partially from the protecting position toward the injecting position.

In one embodiment, the energy source comprises a spring. In one embodiment, the jet injector further includes a ram that is biased by the spring against the plunger to produce the injecting pressure, wherein the ram comprises a bell portion on which the spring is seated, and the bell portion defines a hollow interior configured for receiving the prefilled syringe when the device is fired, such that the spring surrounds the prefilled syringe.

In some embodiments, the jet injector further includes a trigger mechanism operably associated with the energy source for activating the energy source to jet inject the medicament, wherein the trigger mechanism is configured for activating the energy source after the retractable guard is retracted from the protecting position. In one embodiment, the retractable guard is operably associated with the trigger mechanism to cause the trigger mechanism to activate the energy source when the guard is retracted to the injecting position.

In some embodiments, the interference component is a sleeve having an engagement portion extending outwardly from an outer surface of the sleeve that is configured to cause resistance to the movement of the retractable guard when the retractable guard is moved at least partially from the protecting position toward the injecting position. In other embodiments, the interference component is a latch coupled to the housing that is configured to cause resistance to the movement of the retractable guard when the retractable guard is moved at least partially from the protecting position toward the injecting position.

In certain embodiments, the housing is configured for allowing insertion of the needle to the penetration depth, which is between about 0.5 mm and about 5 mm below the surface at the insertion location.

In certain embodiments, the housing is configured for allowing insertion of the needle to the penetration depth, which is between about 11 mm and about 13 mm below the surface at the insertion location.

In certain embodiments, the chamber contains about between 0.02 mL and about 4 mL of the medicament.

3

In certain embodiments, the penetration depth and injecting pressure are sufficient to substantially prevent backflow of the injected medicament.

In other embodiments, the jet injector further includes a syringe cushion associated with the syringe support and prefilled syringe to compensate for shape irregularities of the pre-filled syringe.

In certain embodiments, the invention relates to a lock ring for a jet injector. In other embodiments, the lock ring includes at least one abutment arm extending distally from a proximal end of a body dimensioned to fit within in a housing of the jet injector, the abutment arm having at least one tapered portion and at least one engagement portion axially adjacent to the at least one tapered portion, the engagement portion being configured to cause resistance to the movement of a retractable guard of the jet injector; and at least one flap radially adjacent to the at least one abutment arm extending distally from the proximal end of the body.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWINGS

The foregoing summary, as well as the following detailed description of embodiments of the present invention, will be better understood when read in conjunction with the appended drawings of exemplary embodiments. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown.

In the drawings:

FIG. 1 is a side view of an embodiment of a jet injector constructed according to the present invention, showing the injector prior to injection;

FIG. 2 is a cross-sectional view of the jet injector of FIG. 1 thereof taken along plane II-II;

FIG. 3 is a perspective view of a prefilled syringe for use in the jet injector of FIG. 1;

FIG. 4 is a perspective view of a syringe cushion of the jet injector of FIG. 1;

FIG. 5 is a cross-sectional view of the jet injector of FIG. 1, showing the injector at the start of the jet injection;

FIG. 6 is a graph showing the pressure present in the polluted chamber over time that contains medicament in an embodiment during jet injection;

FIG. 7 is a side view of another embodiment of an injector that is configured for using a narrow diameter prefilled syringe;

FIG. 8 is a cross-sectional view of the jet injector of FIG. 1; taken along plane VIII-VIII;

FIG. 9 is a cross-sectional view of another embodiment of an injector using a needle for intramuscular jet-injection;

FIG. 10A is a side view of an interference component of a jet injector in accordance with an exemplary embodiment;

FIG. 10B is a perspective view of an interference component of a jet injector in accordance with an exemplary embodiment; and

FIG. 11 is a graph showing the breakaway force over time of an jet injector in accordance with an exemplary embodiment.

DETAILED DESCRIPTION OF THE INVENTION

With reference to the accompanying drawings, various embodiments of the present invention are described more fully below. Some but not all embodiments of the present invention are shown. Indeed, various embodiments of the invention may be embodied in many different forms and

4

should not be construed as limited to the embodiments expressly described. Like numbers refer to like elements throughout. The singular forms "a," "an," and "the" include the singular and plural unless the context clearly dictates otherwise.

Referring to FIGS. 1 and 2, an embodiment of an injector 10 has a housing 12 configured for allowing a user to handle the injector 10. The housing 12 includes an outer housing member 14 that substantially houses most of the components shown in FIG. 2. A syringe support member 16 is housed within and mounted with the housing 12. The syringe support member 16 is configured to hold and position a prefilled syringe 18, which is shown in FIG. 3. In one embodiment, the syringe support member 16 is substantially fixed to the housing 12, such as by snaps, an adhesive, a weld, or another known attachment. The prefilled syringe 18 has a container portion 20 that defines in its interior a fluid chamber 22, which is prefilled with medicament to be injected. At the distal end of the prefilled syringe 18 is an injection-assisting needle 24. Needle 24 has an injecting tip 26 configured as known in the art to penetrate the tissue of a patient, in certain embodiments, the skin of the patient. A needle bore extends through the needle 24, as known in the art. The bore is in fluid communication with the medicament in the fluid chamber 22 and is open at the needle tip 26 to inject the medicament.

At a proximal side of the fluid chamber 22, opposite from the needle 24, is a plunger 28 that seals the medicament in the fluid chamber 22. In certain embodiments, a syringe wall 30 comprises a tubular portion, in some embodiments closed at a distal end and open at a proximal end, to define the fluid chamber 22. Plunger 28 is slideably received in the tubular portion. The prefilled syringe 20 is configured such that when the plunger 28 is displaced in a distal direction, the volume of the fluid chamber 22 is decreased, forcing the medicament out therefrom and through the bore of the needle 24.

At the distal end of the fluid chamber 22 is a needle hub portion 32 to which the needle is mounted. In one embodiment, a syringe flange 34 extends radially from the proximal end of the syringe wall 30.

In one embodiment, the syringe 18 has a syringe body 36 that includes the flange 34, wall 30 and hub portion 32. In one embodiment, syringe body 36 that includes flange 34, wall 30, and hub portion 32 is of unitary construction. A preferred material for the syringe body 36 is glass, but other materials can be used in other embodiments. A suitable prefilled syringe is the BD Hypak™, which is available in various sizes and volumes and is sold prefilled with medicament. The glass of the syringe body 36 is adhered to the needle 24. Typical medicaments and medicament categories include epinephrine, atropine, sumatriptan, antibiotics, antidepressants, and anticoagulants. Using a prefilled syringe 18 facilitates handling of the medicament when the injector 10 is assembled, and there is an extensive body of knowledge of how the medicaments keep and behave in a prefilled syringe.

A syringe cushion 38, which is shown in detail in FIG. 4, is in certain embodiments made of an elastomeric material or other resilient material. A flange 40 of the syringe cushion 38 extends radially and is disposed and serves as an interface between the distal side of the syringe support member 16 and the syringe flange 34. Elevated portions, such as nubs 42 extend proximally from the cushion flange 40 and are configured and dimensioned to abut the syringe flange 34.

Prefilled syringes that are manufactured by a blown glass process can have significant dimensional tolerances and

5

unevenness, particularly in the glass body 36. The cushion 38 can serve to accommodate the shape irregularities and to properly position and locate the prefilled syringe 18 within the syringe support 16. Typically, the axial thickness of glass blown syringe flanges on a 1 mL prefilled syringe is within about ± 0.5 mm. For a BD Hypak™ 1 mL standard prefilled syringe, the thickness of the syringe flange 34 is 2 mm ± 0.5 mm or -0.4 mm, and in a 1 mL long configuration BD Hypak™ syringe, the flange axial thickness is about 1.65 mm ± 0.25 mm. Other dimensional variations that occur in typical glass prefilled syringes are in the internal and external diameters of the tubular wall 30. These variations can be accommodated by the resilient sleeve portion 44 of the syringe cushion 38, which extends axially around the interior of the syringe support 16. In one embodiment, the syringe cushion 38 is received in the interior of the syringe support member 16 and receives the syringe body 36, in certain embodiments fitting snugly therein.

In one embodiment, the sleeve portion 44 has radially inwardly extending protrusions 46 with a surface area and configuration selected to allow the insertion of the prefilled syringe 18 therein during assembly, but providing sufficient friction to maintain the syringe 18 in place and to provide cushioning and shock absorption during the firing of the injector 10. Outward protrusions 48 are also provided on the sleeve portion 44, which can be received in corresponding recesses of the syringe support 16 to prevent axial rotation therebetween. Recessed areas 50 can be provided on the interior and exterior of the syringe cushion 38 opposite corresponding protrusions 48 on the opposite radial side of the sleeve portion 44 if an increased wall thickness of the sleeve portion 44 is not desired. In an alternative embodiment one or both of the flange 40 and sleeve 44 of the syringe cushion 38 are substantially smooth, substantially without any protrusions. In one embodiment, the material and configuration of the syringe cushion 38 is also sufficient to entirely support the prefilled syringe 20 to withstand a firing force applied axially in a distal direction on the plunger 28. Thus, the entire support for the prefilled 20 can be provided on the syringe flange 34, while the distal end of the syringe 18 may itself be substantially unsupported in an axial direction. This can help withstand the shock on the glass body 36 of the prefilled syringe 20 produced by the elevated pressures within the fluid chamber 22.

To radially position the distal end of the prefilled syringe 18, the syringe support 16 in certain embodiments has a narrowed bore portion 51 that is in certain embodiments configured to abut the outside of the syringe wall 30. This is especially beneficial when the needle 24 is inserted into the patient's skin. The narrowed bore portion 51 can be made of a resilient material, such as an elastomer, or it can be made unitarily with the rest of the syringe support 16, in certain embodiments of a plastic material.

Referring to FIG. 2, in one embodiment, a trigger mechanism 52 is also housed within housing 12. The trigger mechanism 52 includes an inner housing 54 that can be attached to the outer housing 14, such as by snaps, an adhesive, a weld, or other known attachment. Trigger protrusions 56 extend inwardly from the proximal end of the inner housing 54 and are resiliently biased outwardly. Trigger protrusions 56 are received in a recess 58 of ram 60 in blocking association therewith to prevent distal movement of the ram 60 prior to the firing of the device. The ram 60 is urged towards the distal end of the injector 10 by an energy source, which in certain embodiments is a compression spring 52, although other suitable energy sources can

6

alternative be used such as elastomer or compressed-gas springs. In one embodiment, the compression spring is a coil spring.

A trigger member of the trigger mechanism 52, such as a latch housing 64, is provided exterior to the inner housing to retain the trigger protrusions 56 in the blocking association in the recess 58 to prevent premature firing of the injector 10. The latch housing 64 is slideable inside the outer housing 14 with respect to the inner housing 54, in certain embodiments in an axial direction, and the latch housing 64 in certain embodiments surrounds the inner housing 54.

The housing 12 has a needle guard 66 that is moveable with respect to the outer housing 14. The needle guard 66 is shown in FIGS. 1 and 2 in a protecting position, in which the needle 24 is disposed within the guard 66. The needle guard 66 is retractable, in one embodiment into the outer housing 14, in a proximal direction to an injecting position, in which the needle tip 26 and an end portion of the needle 24 is exposed as shown in FIG. 5 for insertion into a patient. In one embodiment, the proximal movement of the guard is prevented substantially at the injecting position.

In one embodiment, an interference component 134 interferes with the movement of the needle guard when the needle guard is moved at least partially from the protecting position toward the injecting position.

In one embodiment, the housing 12 has an interference component 134, e.g., a lock ring, adjacent to the needle guard 66, the interference component 134 interferes with the movement of the needle guard when the needle guard is moved at least partially from the protecting position toward the injecting position. Interference component prevents movement of the needle guard until the breakaway force 146 is exceeded. The interference component 134 is shown in FIGS. 10A and 10B. In one embodiment, the interference component 134 is included as part of a ring having at least one abutment arm 136 extending distally from a proximal end 138 dimensioned to fit within the housing 14, the abutment arm 136 having at least one tapered portion 140. The abutment arm 136 may also have an engagement portion 142 axially adjacent to the at least one tapered portion 140 that is configured to cause resistance to the movement of the needle guard 66 when the needle guard 66 is moved at least partially from the protecting position toward the injecting position. While interference component 134 may have more than one abutment arm 136 and correspondingly more than one engagement portion 142, certain embodiments include only one abutment arm 136 having an engagement portion 142. The interference component may also include at least one flap 144 radially adjacent to the at least one abutment arm 136 extending distally from the proximal end 138 of the interference component 134.

The interference component 134 may also be coupled to the housing 12, incorporated in a sleeve separate from the housing 12, or include a latch.

Referring to FIG. 11, breakaway force 146 is needed to overcome the resistance on the needle guard 66 caused by the engagement portion 142 when the needle guard 66 is moved at least partially from the protecting position toward the injecting position. Referring to FIG. 11, breakaway force 146 is the resistance to retraction that is exerted on the needle guard 66 when an initial attempt to retract the needle guard 66 occurs. Breakaway force 146 is a distinct force from the triggering force 148 that is needed to cause jet injection of the medicament and is a greater force than that provided by the spring 62 that biases the needle guard 66 in the extended position. Breakaway force 146 is sometimes also a greater force than what occurs due to the friction of

the needle guard 66 retracting motion sliding on other mating components in the device. In one embodiment the breakaway force 146 is controlled and only occurs as a single event.

Referring to FIG. 2, the needle guard 66 is associated with the latch housing 64 such that when the guard 66 is displaced distally it slides the latch housing 64 also in a distal direction to release the trigger protrusions 56 from the recess 58. In one embodiment, the latch housing 64 has a latching portion 68 that abuts the inner housing 54 in an association to bias and maintain the trigger protrusions 58 positioned in the blocking association with the ram 60 prior to the firing of the device 10. When the latch is slid proximally by the retracting of the guard 66 to the injecting position, the latching portion 68 slides beyond the portion of inner housing 54 that is contacts to flex the trigger protrusions 56 into the recess 58 of the ram 60, allowing the trigger protrusions 56 to move radially outwardly from the recess 58 and therefore from the blocking association. When this happens, spring 62 biases the ram 60 against plunger 28 to fire the jet injector 10. In certain embodiments, latch housing 64 defines trigger openings 70 adjacent to latching portions 68, which is configured to receive a portion of the inner housing 54, such as the surface disposed radially outwardly from the trigger protrusions 56.

In certain embodiments, the guard 66 is resiliently biased distally towards the protecting position by compression coil spring 72. Also, the needle guard 66 has an axial opening 74 to allow the needle 24 pass there through, and which may be sized according to the type of injector desired. The construction of the present embodiment allows a user to push the distal end of the injector 10 against the patient's skin, pushing the needle 24 into the skin at an insertion location, substantially at the same speed as the injector is pushed. Once the needle 24 is fully inserted to an insertion point at a penetration depth, the trigger mechanism 56 fires the jet injection to an injection site.

Referring to FIG. 5, in one embodiment, the prefilled syringe 18 and its needle 24 are not shuttled forward automatically into the patient's skin, such as by the firing energy source during the injection firing. The user preferably gently pushes the entire device forward to insert the needle 24, in certain embodiments retracting a guard against the skin in the process. In one embodiment, the prefilled syringe 18 is substantially stationary within the housing 12, and, in one embodiment, is substantially fixed thereto. In this manner, the present invention provides for a gentler treatment of the syringe during injection that enables the use of a sufficiently powerful spring 62 or other energy source to produce a jet injection without the risk of damaging the relatively fragile and complex shapes of the prefilled syringe, also allowing, for example, the injection of high viscosity solutions, where the risk of breaking a syringe, such as at the flange, is elevated in prior art injectors that shuttle the syringe forward in the housing and into the patient. Residual stresses are also often present in the glass bodies of prefilled syringes, and this configuration reduces the additional stresses imposed thereon during use, further protecting the syringe. Also, misalignments in the prefilled syringe are also rendered operationally less significant due to the gentle insertion of the needle that is possible with this configuration.

In one embodiment, the injecting position of the guard 66 is such that a predetermined length of the end of needle 24 is exposed from the guard 66. In some embodiments, such as where the opening 74 is of a sufficiently large diameter, the skin of the patient maybe allowed to extend into the

opening 74 when the device 10 is pressed there against, and a needle that does not protrude beyond the distal end of the guard 66 can be used while still penetrating the skin to a certain depth. In most embodiments, the distance 76 by which the needle tip 26 extends past the distal end of the guard 66 will be fairly close to the depth of the insertion of the needle.

In one embodiment, such as for subcutaneous injection, the guard 66 is configured to allow insertion of the needle 24 to a penetration depth in the skin that is up to about 5 mm below the skin surface. In another embodiment, the penetration depth is less than about 4 mm, and in one embodiment is less than about 3 mm. In one embodiment, the insertion depth is at least about 0.5 mm and, in other embodiments, at least about 1 mm. In another embodiment, the distance 76 by which the needle extends past the guard 66 or the distal surface of the guard 66 that contacts the skin is up to about 5 mm, in one embodiment, up to about 4 mm, and in another embodiment up to about 3 mm. In certain embodiments, extension distance 76 is at least about 0.5 mm, in one embodiment at least about 1 mm, and in another embodiment at least about 2 mm. In one embodiment, tip 26 extends by a distance 76 of around 2.5 mm beyond the portion of the guard 66 that contacts the skin in the injecting position.

In another embodiment, such as for intramuscular injection, the injector is configured to allow the needle 24 to be inserted into the patient to a penetration depth in the skin, or alternatively beyond the distal surface of the guard, by a distance of up to about 15 mm. In one embodiment, this distance is about between 10 mm and 14 mm. In an embodiment for jet injection of epinephrine for instance, a penetration depth or distance beyond the guard is between about 11 mm and about 17.0 mm, and, in other embodiments, between about 13 to about 15 mm. Jet injection with this length needle improves the distribution of the medicament in the patient tissue compared to non jet injection. Other exposed needle lengths can be selected for jet injection to different depths below the skin, with, in certain embodiments, an overall penetration length of between about 0.5 mm and about 20 mm. In certain embodiments, the needle guard is configured for retracting from a protecting position, in one embodiment covering the entire needle 24 (See FIG. 2), to an injecting position, in which the desired length of the end of the needle 24 is exposed (See FIG. 5).

In some embodiments, the spring 62 and the prefilled syringe 18 are configured to jet inject the medicament. Thus, the spring 62 applies a force on the plunger 28 that is sufficient to elevate the pressure within the fluid chamber 22 to a level high enough to eject the medicament from the needle 24 as a jet. Jet injection is to be understood as an injection with sufficient velocity and force to drive the medicament to locations remote from the needle tip 26. In manual and autoinjector-type injections, in which the injection pressures are very low, the medicament exits the needle tip inside the patient and is typically deposited locally around the needle in a bolus. On the other hand, with the present jet injection device 10, the medicament is jet injected distally or in other directions, such as generally radially by the elevated pressure jet, which beneficially improves the distribution of the medicament after the injection and keeps a large bolus from forming that can detrimentally force the medicament to leak back out of the patient around the needle or through the hole left behind by the needle after it is removed.

Referring to the graph shown in FIG. 6, numeral 78 represents the point in time when device 10 is fired, and numeral 80 represents the point in time of completion of the

medicament injection, in certain embodiments when the plunger **28** hits the forward wall of the container portion **20**. Numeral **82** represents the initial and peak pressure during the injection, and numeral **84** represents the final and low pressure during the injection. Since the spring **62** of one embodiment has a linear spring constant and an injection-assisting needle is used to puncture the skin before commencing the injection, the pressure drops substantially linearly from the start of the injection **78** until the injection is completed. The final pressure **84** at the end **80** of the injection is sufficiently elevated so that even at the end of the firing stroke of ram **60**, the medicament is still jet injected, and a very small amount or none of the medicament is deposited in a bolus around the needle tip **26**.

In one embodiment, the peak pressure during the injection is less than about 1,000 p.s.i., in one embodiment less than about 500 p.s.i., and in another embodiment less than about 350 p.s.i. At the end **80** of the injection, the pressure **84** applied to the medicament in the fluid chamber **22** is in one embodiment at least about 80 p.s.i., in one embodiment at least about 90 p.s.i., and in another embodiment at least about 100 p.s.i. In one embodiment of the invention, the initial pressure **82** is around 330 p.s.i., and the final pressure is about 180 p.s.i., while in another embodiment the initial pressure **82** is about 300 p.s.i., dropping to around 110 p.s.i. at the end **80** of the injection. The needles used in these embodiments are between 26 and 28 gauge, and are in certain embodiments around 27 gauge, but alternatively other needle gages can be used where the other components are cooperatively configured to produce the desired injection. In an embodiment for jet injection of epinephrine for instance, certain embodiments of the needles are between 20 and 25 gauge, and in other embodiments, 22 gauge. In one embodiment, the components of the injector **10** are configured to jet inject the medicament to a subterraneous injection site.

The amount of medicament contained and injected from fluid chamber **22** is in one embodiment between about 0.02 mL and about 4 mL, in certain embodiments less than about 3 mL, and in other embodiments is around 1 mL. Larger volumes may also be selected depending on the particular medicament and dosage required. In one embodiment, the prefilled syringe is assembled into the remaining parts of the jet injector **10** already containing the desired amount of medicament. In one embodiment, the prefilled syringe contains about 1 mL of medicament.

In one embodiment, injection rates are below about 0.75 mL/sec., in one embodiment preferably below about 0.6 mL/sec., in one embodiment at least about 0.2 mL/sec., in one embodiment at least about 0.3 mL/sec, and in other embodiments at least about 0.4 mL/sec. In one embodiment, the injection of the entire amount of medicament is completed in less than about 4 seconds, in one embodiment in less than about 3 seconds, and in other embodiments in less than about 2.5 seconds. In one embodiment, the medicament injection takes at least about 1 second, in one embodiment at least 1.5 seconds, and in other embodiments at least about 1.75 seconds. In one embodiment, the injector **10** injects the medicament at about 0.5 mL/sec., completing the injection of 1 mL in about 2 seconds.

U.S. Pat. No. 6,391,003 discloses several experimental results of pressures that can be applied to medicament in a glass cartridge, using 26 and 27 gauge needles. The following table illustrates injections with different peak pressures that can be used with glass prefilled syringes:

Pressure and Time (sec.) to Inject 1 cc

Pressure	26 Gauge needle	27 Gauge needle
150 p.s.i.	2.1	4.2
200 p.s.i.	1.9	3.9
240 p.s.i.	1.7	3.3
375 p.s.i.	1.4	3.1

It is foreseen that higher pressures and flow rates will be used with shorter needle penetration into the patient skin to achieve jet injections to a particular desired depth substantially without medicament leakback.

It has been found that using the jet injection of the present device, short needles can be used to inject medicament to different parts of the skin, in certain embodiments subcutaneously, substantially without any leakback. Using a needle **24** that extends by about 2.5 mm from the needle guard **66**, a 27 gauge needle **24**, and a pressure in the fluid chamber **22** peaking at around 300 p.s.i. and ending at around 100 p.s.i., resulting in a flow rate of about 0.5 mL/sec., 1 mL of medicament has been found to successfully be injected without leakback in close to 100% of the tested injections. Thus, the needle-assisted jet injector **10** of the present invention permits jet injection of the medicament using a very short needle reliably regardless of the thickness of the patient's skin or the patient's age, weight or other typical factors that complicate non-jet injecting with short needles.

FIGS. **7** and **8** show another embodiment of the present invention that uses a prefilled syringe that has a long, but smaller-diameter configuration than the embodiment of FIG. **2**. While in the embodiment of FIG. **2**, the firing spring **62** extends into the bore of the prefilled syringe **18** during the firing stroke, the narrower prefilled syringe **88** of injector **86** does not provide as much space to accommodate a spring. Consequently, the ram **90** of injector **86** includes a bell portion **92** defining a hollow interior **94** that is configured to receive the proximal end of the prefilled syringe **88** and the syringe support **96** when the injector **86** is fired. Similarly, a bell-receiving space **98** is defined around the exterior of the prefilled syringe **88** and syringe support **96** to receive the bell portion **92** during the firing. The bell portion **92** includes a spring seat **100** extending radially outwardly and configured and disposed to seat a compression spring **102**. When the trigger mechanism **56** is activated and the device **86** is fired, spring **102** acts against seat **100** to drive the ram **90** against plunger **104** to jet inject the medicament from the fluid chamber **106**. As a result, after firing, the spring **102** radially surrounds the prefilled syringe **88**. The outer housing portion **108** is wider than outer housing portion **14** of injector **10** to accommodate the bell portion **92** and larger diameter spring **102**.

One available long configuration syringe with a 1 mL capacity has a cylindrical syringe body portion with a diameter of 8.15 mm, which would in certain embodiments be used in the injector of FIGS. **7** and **8**, while one available shorter configuration syringe of the same capacity has a cylindrical syringe body portion with a diameter of 10.85 mm, which would in certain embodiments be used in the injector of FIGS. **1** and **2**. While the embodiment with a bell portion **92** can be used with wider/shorter syringes, in certain embodiments, the prefilled syringes have an outer diameter cylindrical wall of less than about 10 mm, and in other embodiments less than about 9 mm.

Injector **86** also includes a cap **110** fitted around the needle guard **66**, and associated with the outer housing **108** to prevent retraction of the needle guard **66** and the triggering

11

of the device **86**. Additionally, the cap **110** seals off the needle tip **26** and can be removed prior to using the device **86**. In one embodiment, the cap **110** is configured to fit over the needle guard **66** in a snap-fit association therewith, such as by including a narrower diameter portion **112** associated with an enlarged diameter portion **114** of the needle guard **66**.

Additionally, injector **86** employs a syringe cushion cap **116** that extends around the outside of the syringe flange **34** from the syringe cushion **118** to help trap and retain the prefilled syringe **88**. In one embodiment, a cushion cap **122** is connected to the cushion **118** and is, in certain embodiments, of unitary construction therewith. The cushion cap **122** abuts the distal end of the syringe body **120** to radially position and hold the proximal end of the body **120** while the needle **24** is being inserted into the patient. Similarly to the embodiment of FIG. 2, the syringe holder **96** is associated with the housing in a substantially fixed position, such as by mounting portion **124**, which traps protrusions **126** of the syringe holder.

Referring to FIG. 9, injector **128** has a needle guard **130** configured to retract further into the injector housing than the injector of FIGS. 1 and 2 or FIG. 5 before the trigger mechanism **52** fires the jet injection. The injector in this figure is shown in a position in which the trigger mechanism **52** is being released and about to fire the injection. The distance **76** by which the needle extends past the guard **130** or the distal surface of the guard **130** that contacts the skin in certain embodiments between about 12.5 and 13 mm. In one embodiment, the guard is preferably configured to reextend to a protecting position after the device is fired and removed from the patient, such as under the bias of spring **72**, and is locked in that position by locking members **132**, as known in the art to prevent reuse on the injector.

In other embodiments, the guard length, the location of the guard injecting position with respect to the needle tip (including the guard throw between the protecting and injecting positions), and the length of the needle from the syringe body can be selected to allow for shallower or deeper needle insertions before the device is fired, providing lesser or greater distances **76**, respectively. In one embodiment, the guard is kept from sliding further back than substantially at the firing position, to better control in insertion depth into the patient.

Each and every reference herein is incorporated by reference in its entirety. The entire disclosure of U.S. Patent Application 2011/0144594, U.S. Pat. Nos. 8,021,335 and 6,391,003 are hereby incorporated herein by reference thereto as if fully set forth herein.

While illustrative embodiments of the invention are disclosed herein, it will be appreciated that numerous modifications and other embodiments may be devised by those skilled in the art. For example, the features for the various embodiments can be used in other embodiments, such as the needle and guard cap of FIGS. 7 and 8, which can be applied to the embodiment of FIG. 1. Therefore, it will be understood that the appended claims are intended to cover all such modifications and embodiments that come within the spirit and scope of the present invention.

What is claimed is:

1. An injector, comprising:

a housing;

a prefilled syringe containing a volume of a medicament disposed within the housing, the prefilled syringe having a needle coupled to and extending from a distal end thereof;

12

a retractable guard disposed at least partially within the housing and axially moveable relative thereto; and an interference component disposed within the housing and configured to cause resistance to axial movement of the retractable guard when the retractable guard is moved proximally relative to the housing, wherein a breakaway force is configured to be applied to the retractable guard to overcome the resistance by the interference component,

wherein a triggering force is configured to be applied to the retractable guard to initiate delivery of the medicament, and

wherein the breakaway force is equal to or greater than the triggering force.

2. The injector of claim 1 further comprising:

a syringe support supportively mounting the prefilled syringe in the housing,

wherein the prefilled syringe has a distal portion in which the needle is located, and a proximal portion opposite the distal portion, and

wherein the syringe support axially supports the proximal portion of the prefilled syringe such that the distal portion of the prefilled syringe is substantially unsupported in an axial direction.

3. The injector of claim 2, wherein the prefilled syringe is made of glass.

4. The injector of claim 3, wherein the needle is coupled to the glass.

5. The injector of claim 1 further comprising:

a plunger moveable within a fluid chamber of the prefilled syringe; and

an energy source configured to bias the plunger with a force selected to produce an injecting pressure on a medicament in the fluid chamber to expel the medicament through the needle.

6. The injector of claim 5 further comprising:

a ram that is biased by the energy source against the plunger to produce the injecting pressure, the ram comprising a bell portion on which the energy source is seated,

wherein the prefilled syringe defines a hollow interior configured to receive at least a portion of the ram and energy source when the injector is fired.

7. The injector of claim 5 further comprising:

a trigger mechanism operably associated with the energy source for activating the energy source to expel the medicament, the trigger mechanism configured to activate the energy source after the retractable guard is moved proximally relative to the housing.

8. The injector of claim 7, wherein the retractable guard is moveable relative to the housing between a protecting position in which the needle is disposed within the retractable guard and an injecting position where the needle is at least partially exposed, and

wherein the retractable guard is operably associated with the trigger mechanism to cause the trigger mechanism to activate the energy source when the guard is retracted to the injecting position.

9. The injector of claim 1, wherein the prefilled syringe contains about between 0.02 mL and about 4 mL of the medicament.

10. The injector of claim 1, wherein delivery of the medicament is at a penetration depth and an injecting pressure sufficient to substantially prevent backflow of the medicament from a subject.

11. The injector of claim 1, wherein the interference component includes at least one abutment arm, the at least

13

one abutment arm having at least one tapered portion and an engagement portion axially adjacent to the at least one tapered portion, and

wherein the engagement portion is configured to resist the movement of the retractable guard when the retractable guard is moved proximally relative to the housing.

12. The injector of claim **11**, wherein the interference component further comprises:

a second abutment arm including a second abutment arm tapered portion and a second abutment arm face.

13. The injector of claim **12**, wherein the at least one abutment arm includes a first abutment arm face and the first abutment arm face is longer axially than the second abutment arm face.

14. The injector of claim **12**, wherein the at least one abutment arm includes a face adjacent to the engagement portion.

15. The injector of claim **12**, wherein the second abutment arm face is adjacent to the second abutment arm tapered portion.

14

16. The injector of claim **12**, wherein the second abutment arm tapered portion is longer axially than the at least one tapered portion.

17. The injector of claim **1**, wherein the breakaway force is greater than a frictional force from friction between the retractable guard and the interference component as the retractable guard is moved proximally relative to the housing.

18. The injector of claim **1**, wherein the breakaway force is applied during an initial proximal movement of the retractable guard relative to the housing.

19. The injector of claim **1**, wherein the interference component is coupled to the housing.

20. The injector of claim **1**, wherein the interference component is a latch.

21. The injector of claim **1**, wherein the medicament is epinephrine.

* * * * *