

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409280
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Saleem; Fozia

Heating smokeable material

Abstract

An apparatus configured to heat smokeable material so as to volatilize at least one of its components for inhalation comprises at least one heating element on or in a substrate material.

Inventors:	Saleem; Fozia (London, GB)
Applicant:	British American Tobacco (Investments) Limited (London, GB)
Family ID:	48226885
Assignee:	British American Tobacco (Investments) Limited (London, GB)
Appl. No.:	16/948934
Filed:	October 06, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20210170116 A1	Jun. 10, 2021

Foreign Application Priority Data

GB	1305294	Mar. 22, 2013
----	---------	---------------

Related U.S. Application Data

continuation parent-doc US 14779210 ABANDONED WO PCT/EP2014/055485 20140319 child-doc US 16948934

Publication Classification

Int. Cl.: A24F40/46 (20200101); A61M11/04 (20060101); A61M15/06 (20060101); H05B3/00 (20060101); H05B3/06 (20060101); H05B3/44 (20060101); A24F40/20 (20200101); A61M16/00 (20060101)

U.S. Cl.:

CPC A61M11/042 (20140204); A24F40/46 (20200101); A61M15/06 (20130101); H05B3/0014 (20130101); H05B3/06 (20130101); H05B3/44 (20130101); A24F40/20 (20200101); A61M2016/0015 (20130101); A61M2205/3368 (20130101); A61M2205/3633 (20130101); A61M2205/3653 (20130101); A61M2205/8206 (20130101); H05B2203/013 (20130101); H05B2203/021 (20130101); H05B2203/022 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5233166	12/1992	Maeda et al.	N/A	N/A
5264681	12/1992	Nozaki et al.	N/A	N/A
5322075	12/1993	Deevi et al.	N/A	N/A
5408574	12/1994	Deevi et al.	N/A	N/A
5468936	12/1994	Deevi et al.	N/A	N/A
5573692	12/1995	Das et al.	N/A	N/A
5878752	12/1998	Adams et al.	N/A	N/A
6084220	12/1999	Suematsu et al.	N/A	N/A
7374063	12/2007	Reid	N/A	N/A
2002/0079377	12/2001	Nichols	N/A	N/A
2003/0150451	12/2002	Shayan	128/203.12	A61M11/042
2003/0183616	12/2002	Goto	N/A	N/A
2006/0267724	12/2005	Parsons	N/A	N/A
2010/0200006	12/2009	Robinson et al.	N/A	N/A
2011/0126848	12/2010	Zuber et al.	N/A	N/A
2014/0064715	12/2013	Greim	392/394	F24H1/0018
2015/0272219	12/2014	Hatrack et al.	N/A	N/A
2016/0295922	12/2015	John et al.	N/A	N/A
2017/0055575	12/2016	Wilke et al.	N/A	N/A
2017/0055580	12/2016	Blandino et al.	N/A	N/A
2017/0055581	12/2016	Wilke et al.	N/A	N/A
2017/0055582	12/2016	Blandino et al.	N/A	N/A
2017/0055583	12/2016	Blandino et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102595943	12/2011	CN	N/A
102781266	12/2011	CN	N/A
2548019	12/1975	DE	N/A
0653898	12/1994	EP	N/A
0914021	12/1998	EP	N/A
2316286	12/2010	EP	A24B 15/167
2327318	12/2010	EP	N/A
2468117	12/2011	EP	N/A
2975951	12/2015	EP	N/A
2446440	12/2007	GB	N/A
2504075	12/2013	GB	N/A
2504076	12/2013	GB	N/A
H04324276	12/1991	JP	N/A
H07192906	12/1994	JP	N/A
3192677	12/2000	JP	N/A
2003293869	12/2002	JP	N/A
2007080892	12/2006	JP	N/A
4324276	12/2008	JP	N/A
2013509160	12/2012	JP	N/A
WO-9406314	12/1993	WO	N/A
WO-9527412	12/1994	WO	N/A
WO-2011063970	12/2010	WO	N/A
WO-2012134117	12/2011	WO	N/A
2013034460	12/2012	WO	N/A
WO-2013034459	12/2012	WO	N/A
WO-2013110211	12/2012	WO	N/A
WO-2013148810	12/2012	WO	N/A
WO-2014012905	12/2013	WO	N/A
WO-2014037794	12/2013	WO	N/A
WO-2014048745	12/2013	WO	N/A

OTHER PUBLICATIONS

Borisova A L., et al., “Reactions of Boron and Aluminum Nitrides, and Materials Based on Them, With Refractory Metals, ” 5 pages. cited by applicant
Communication pursuant to Article 94(3) EPC for European Application No. 18210216.0, mailed on Oct. 19, 2020, 6 pages. cited by applicant
Examination Report mailed Oct. 26, 2017 for European Application No. 14717683.8, 5 pages. cited by applicant
Extended European Search Report for Application No. 18210216.0, mailed on May 9, 2019, 8 pages. cited by applicant
International Preliminary Report on Patentability for Application No. PCT/EP2014/055485, mailed on Oct. 1, 2015, 11 pages. cited by applicant
International Search Report and Written Opinion for Application No. PCT/EP2014/055485, mailed on Jul. 31, 2014, 16 pages. cited by applicant
Office Action dated Sep. 30, 2019 for Chinese Application No. 201480017532.4 filed Mar. 19,

2014, 20 pages. cited by applicant
Office Action mailed Jan. 11, 2017 for Korean Application No. 10-2015-7025842, 25 pages (67 pages with translation). cited by applicant
Office Action mailed Dec. 18, 2018 for Japanese Application No. 2017-172628, 4 pages. cited by applicant
Office Action mailed Aug. 23, 2016 for Japanese Application No. 2016-503647, 3 pages. cited by applicant
Office Action mailed Aug. 25, 2020 for Japanese Application No. JP 2017-172628, 8 pages. cited by applicant
Search report dated Sep. 23, 2019 for Chinese Application No. 201480017532.4 filed Mar. 19, 2014, 2 pages. cited by applicant
Ye zonglin., “Household Electric Appliance Introduction,” Light Industry Press, Mar. 1983, First Edition, pp. 74-78. cited by applicant
Monma, et al., “Densification of Tungsten Conductors in Cofired Aluminum Nitride Multilayer Substrates by the Addition of Manganese Oxide”, Ceramic Microstructure, Control at the Atomic Level, 1998, pp. 399-406. cited by applicant
Office Action received for Brazilian Patent Application No. 122020008661-0, mailed on May 3, 2021, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 201480017532.4, mailed on Mar. 9, 2021, 16 pages (7 pages of English Translation and 9 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2017-7037837, mailed on Mar. 23, 2021, 21 pages (2 pages of English Translation and 19 pages of Official Copy). cited by applicant
Office Action received for the Brazilian Patent Application No. 112015024250-2, mailed on Feb. 10, 2021, 5 pages (2 pages of English Translation and 3 pages of Official Copy). cited by applicant
Extended European Search Report received for European Patent Application No. 20205048.0, mailed on Mar. 5, 2021, 11 pages. cited by applicant
Final Written Submissions to the opposition proceedings by HGF for European Patent Application No. 14717683.8, mailed on Apr. 23, 2021, 15 pages. cited by applicant
Reasons for Refusal received for Japanese Patent Application No. 2017-172628, mailed on Mar. 16, 2021, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant
Response to the Opposition by the 1st Opponent—JT International for European Patent Application No. 14717683.8, mailed on Apr. 23, 2021, 5 pages. cited by applicant
Response to the Opposition by the proprietor for European Patent Application No. 14717683.8, mailed on Apr. 20, 2021, 22 pages. cited by applicant
Response to the Opposition to the 2nd Opponent—Nerudia for European Patent Application No. 14717683.8, mailed on Apr. 23, 2021, 8 pages. cited by applicant
Notice of Opposition received for European Patent Application No. 20205048.0, mailed on Jul. 22, 2024, 54 pages. cited by applicant

Primary Examiner: Will; Katherine A

Attorney, Agent or Firm: MERCHANT & GOULD P.C.

Background/Summary

PRIORITY CLAIM (1) This application is a continuation application of U.S. patent application Ser. No. 14/779,210, filed Sep. 22, 2015, which is the National Stage of International Application No. PCT/EP2014/055485, filed Mar. 19, 2014, which in turn claims priority to and benefit of

FIELD

(1) The invention relates to heating smokeable material.

BACKGROUND

(2) Smoking articles such as cigarettes and cigars burn tobacco during use to create tobacco smoke. Attempts have been made to provide alternatives to these smoking articles by creating products which release compounds without creating tobacco smoke. Examples of such products are so-called heat-not-burn products which release compounds by heating, but not burning, tobacco.

SUMMARY

(3) According to the invention, there is provided a smokeable material heating apparatus comprising a substrate and at least one printed heating element arranged to heat the substrate to a smokeable material volatilizing temperature and thereby cause the substrate to volatilize at least one component of smokeable material for inhalation.

(4) The heating element may be located at least partially inside the substrate.

(5) The coefficient of thermal expansion of the heating element may be substantially equal to the coefficient of thermal expansion of the substrate.

(6) The heating element may be chemically bonded to the substrate.

(7) The heating element and the substrate may comprise a single sintered structure.

(8) The heating element may comprise an electrically resistive trace in the substrate.

(9) The substrate may comprise a ceramics material.

(10) The substrate may be proximal a smokeable material heating chamber configured to contain the body of smokeable material during heating.

(11) The apparatus may comprise a plurality of the heating elements arranged in layers inside the substrate.

(12) The layers of heating elements may be interconnected by heating element vias through the substrate.

(13) According to the invention, there is also provided an apparatus comprising a heater configured to heat smokeable material to volatilize at least one component of the smokeable material for inhalation, wherein the heater comprises a substrate and a heating element with substantially equal coefficients of thermal expansion.

(14) The heating element may be printed to the substrate.

(15) The heating element may be arranged to heat the substrate to a temperature sufficient for the substrate to volatilize at least one component of smokeable material located in an adjacent smokeable material heating chamber.

(16) The heating element may be located at least partially inside the substrate.

(17) The heating element may be chemically bonded to the substrate.

(18) The heater may comprise a sintered structure comprising the heating element and the substrate.

(19) The heating element may comprise an electrically resistive trace in the substrate and/or the substrate may comprise a ceramics material.

(20) The apparatus may comprise a plurality of the heating elements arranged in layers inside the substrate.

(21) The layers of heating elements may be interconnected by heating element vias through the substrate.

(22) According to the invention, there is also provided an apparatus comprising a heater configured to heat smokeable material to volatilize at least one component of the smokeable material for inhalation, wherein the heater comprises a multiply layered structure of ceramic material and electrically resistive heating elements.

- (23) The heating elements may comprise electrically resistive traces in the ceramic material.
- (24) The heating elements may be chemically bonded to the ceramic material in a sintered structure.
- (25) The coefficient of thermal expansion of the ceramic material may be substantially equal to the coefficient of thermal expansion of the heating elements.
- (26) The heating elements may comprise Tungsten and the ceramic material may comprise Aluminum Nitride Ceramic.
- (27) The heating elements may be printed to the substrate.
- (28) The heating elements may be arranged to heat the ceramic material to a temperature sufficient to volatilize at least one component of smokeable material located in a heating chamber adjacent the ceramic material.
- (29) The heating elements may be located inside the ceramic material.
- (30) Layers of the heating elements may be interconnected by heating element vias through the ceramic material.
- (31) According to the invention, there is also provided an apparatus comprising a heater arranged to heat smokeable material, wherein the heater comprises a substrate and at least one heating element located inside the substrate so as to heat the substrate to cause the substrate to volatilize at least one component of the smokeable material for inhalation.
- (32) The heater may comprise a thermal expansion-matching structure.
- (33) The coefficient of thermal expansion of the heating element may be substantially equal to the coefficient of thermal expansion of the substrate.
- (34) The heating element and the substrate may be sintered to form a chemically bonded structure.
- (35) The substrate may comprise a ceramics material and the heating element may comprise an electrically resistive trace material.
- (36) The substrate may be proximal a smokeable material heating chamber configured to contain the body of smokeable material during heating.
- (37) The apparatus may comprise a plurality of the heating elements arranged in layers inside the substrate.
- (38) The layers of heating elements may be interconnected by heating element vias through the substrate.
- (39) The apparatus may be configured to heat the smokeable material to a smokeable material volatilizing temperature of at least 120 degrees Celsius.
- (40) The apparatus may be configured to heat the smokeable material to a smokeable material volatilizing temperature of between 120 degrees Celsius and 250 degrees Celsius.
- (41) The apparatus may be configured to heat the smokeable material to a smokeable material volatilizing temperature of between 130 degrees Celsius and 180 degrees Celsius.
- (42) The invention may facilitate use of at least one printed heating element to heat a substrate to a smokeable material volatilizing temperature and thereby cause the substrate to volatilize at least one component of smokeable material for inhalation.
- (43) The invention may facilitate use of a heater comprising a substrate and a heating element with substantially equal coefficients of thermal expansion to heat smokeable material to volatilize at least one component of the smokeable material for inhalation.
- (44) The invention may facilitate use of a heater comprising a multiply layered structure of ceramic material and electrically resistive heating elements to heat smokeable material to volatilize at least one component of the smokeable material for inhalation.
- (45) The invention may facilitate use of a heater comprising a substrate and at least one heating element located inside the substrate to heat the substrate and cause the substrate to volatilize at least one component of smokeable material for inhalation.
- (46) According to the invention, there is provided a method of heating smokeable material, comprising heating a substrate to a smokeable material volatilizing temperature using at least one

printed heating element arranged to heat the substrate and causing the heated substrate to volatilize at least one component of smokeable material for inhalation.

(47) According to the invention, there is provided a method of heating smokeable material, comprising heating a substrate to a smokeable material volatilizing temperature using at least one heating element located inside the substrate and causing the heated substrate to volatilize at least one component of smokeable material for inhalation.

(48) For exemplary purposes only, embodiments of the invention are described below with reference to the accompanying figures in which:

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is a schematic illustration of layers of a smokeable material heater comprising a substrate and heating elements interconnected by vias between the layers;
- (2) FIG. 2 is a schematic, cross sectional illustration of an apparatus configured to heat smokeable material to release aromatic compounds and/or nicotine from the smokeable material;
- (3) FIG. 3 is a perspective, partially cut-away illustration of an apparatus configured to heat smokeable material to release aromatic compounds and/or nicotine from the smokeable material;
- (4) FIG. 4 is a perspective, partially cut-away illustration of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate heater divided into radial heating sections;
- (5) FIG. 5 is an exploded, partially cut-away view of an apparatus configured to heat smokeable material, in which the smokeable material is provided around an elongate heater divided into radial heating sections;
- (6) FIG. 6 is a flow diagram showing a method of activating heating regions and opening and closing heating chamber valves during puffing;
- (7) FIG. 7 is a schematic illustration of a gaseous flow through an apparatus configured to heat smokeable material;
- (8) FIG. 8 is a graphical illustration of a heating pattern which can be used to heat smokeable material using a heater;
- (9) FIG. 9 is a schematic illustration of a smokeable material compressor configured to compress smokeable material during heating;
- (10) FIG. 10 is a schematic illustration of a smokeable material expander configured to expand smokeable material during puffing;
- (11) FIG. 11 is a flow diagram showing a method of compressing smokeable material during heating and expanding the smokeable material for puffing;
- (12) FIG. 12 is a schematic, cross-sectional illustration of a section of vacuum insulation configured to insulate heated smokeable material from heat loss;
- (13) FIG. 13 is another schematic, cross-sectional illustration of a section of vacuum insulation configured to insulate heated smokeable material from heat loss;
- (14) FIG. 14 is a schematic, cross-sectional illustration of a heat resistive thermal bridge which follows an indirect path from a higher temperature insulation wall to a lower temperature insulation wall;
- (15) FIG. 15 is a schematic, cross-sectional illustration of a heat shield and a heat-transparent window which are moveable relative to a body of smokeable material to selectively allow thermal energy to be transmitted to different sections of the smokeable material through the window;
- (16) FIG. 16 is schematic, cross sectional illustration of part of an apparatus configured to heat smokeable material, in which a heating chamber is hermetically sealable by check valves; and
- (17) FIG. 17 is a schematic, cross sectional illustration of a partial section of deep-vacuum

insulation configured to thermally insulate an apparatus configured to heat smokeable material.

DETAILED DESCRIPTION

(18) As used herein, the term ‘smokeable material’ includes any material that provides volatilized components upon heating and includes any tobacco-containing material and may, for example, include one or more of tobacco, tobacco derivatives, expanded tobacco, reconstituted tobacco or tobacco substitutes.

(19) An apparatus **1** for heating smokeable material comprises an energy source **2**, a heater **3** and a heating chamber **4**. The energy source **2** may comprise a battery such as a Li-ion battery, Ni battery, Alkaline battery and/or the like, and is electrically coupled to the heater **3** to supply electrical energy to the heater **3** when required. It will be appreciated that, additionally or alternatively to the battery, the energy source **2** could comprise other types of source **2** such as one or more fuel cells and/or another non-battery sources of electricity. The heating chamber **4** is configured to receive smokeable material **5** so that the smokeable material **5** can be heated in the heating chamber **4**. For example, the heating chamber **4** may be located adjacent to the heater **3** so that thermal energy from the heater **3** heats the smokeable material **5** therein. Heat from the heater **3** heats the smokeable material **5** to volatilize aromatic compounds and nicotine in the smokeable material **5** without burning the smokeable material **5**. The smokeable material **5** may comprise a tobacco blend. A mouthpiece **6** is provided through which a user of the apparatus **1** can inhale the volatilized compounds during use of the apparatus **1**.

(20) A housing **7** may contain components of the apparatus **1** such as the energy source **2** and heater **3**. As shown schematically in FIG. 2, the housing **7** may comprise an approximately cylindrical tube with the energy source **2** located towards its first end **8** and the heater **3** and heating chamber **4** located towards its opposite, second end **9**. The energy source **2** and heater **3** may extend along the longitudinal axis of the housing **7**. For example, as shown in FIG. 2, the energy source **2** and heater **3** can be aligned along the central longitudinal axis of the housing **7** in a substantially end-to-end arrangement so that an end face of the energy source **2** substantially faces an end face of the heater **3**. The mouthpiece **6** may be located at the second end **9** of the housing **7**, adjacent the heating chamber **4** and smokeable material **5**.

(21) The length of the housing **7** may be approximately 130 mm. An example length of the energy source **2** is approximately 59 mm. The length of the heater **3** and heating region **4** may be approximately 50 mm. The depth, for example the diameter, of the heating chamber **4** may be between approximately 5 mm and approximately 15 mm, such as between approximately 8 mm and approximately 10 mm. The diameter of the energy source **2** may be between approximately 10.0 mm and approximately 15.0 mm, such as 14.6 mm. The diameter of the housing **7** may be between approximately 11 mm and approximately 18 mm. For example, the diameter of the housing's first end **8** may be 18 mm whilst the diameter of the mouthpiece **6** at the housing's second end **9** may be 15 mm. Dimensions other than those given above could alternatively be used.

(22) The housing **7** is suitable for being gripped by a user during use of the apparatus **1** so that the user can inhale volatilized smokeable material compounds from the mouthpiece **6** of the apparatus **1**.

(23) Heat insulation may be provided between the energy source **2** and the heater **3** to prevent direct transfer of heat from one to the other.

(24) The heater **3** may comprise a printed heater **3**. For example, the heater **3** may comprise a substrate **3a** and one or more heating elements **3b** which may be printed onto or into the substrate **3a**. As described below, the heating elements **3b** may be configured to heat the substrate **3a** at a rapid rate so that the temperature of the substrate **3a** substantially matches the temperature of the heating elements **3b** during heating of the smokeable material **5**.

(25) The substrate **3a** may comprise a ceramics material, such as Aluminum Nitride Ceramic, and the heating elements **3b** may comprise electrically resistive trace elements **3b** which are heated by electrical currents flowing in the elements **3b**. For example, the heating elements **3b** may comprise

an electrically resistive metal such as Tungsten. The currents in the heating elements **3b** may be caused by an electromotive force supplied by the energy source **2**, which is electrically coupled to the heater **3**.

(26) The heating elements **3b** are arranged in or on the substrate material **3a** so as to heat the substrate **3a**. As mentioned above, the arrangement of the heating elements **3b** in or on the substrate **3a** may be so as to heat the substrate **3a** to approximately the same temperature as the heating elements **3b**.

(27) The substrate **3a** may be heated by the heating elements **3b** to a volatilizing temperature of the smokeable material **5** so that heat from the heated substrate **3a** causes components of the smokeable material **5** to be volatilized for inhalation through the mouthpiece **6**. Therefore, smokeable material **5** in the heating region **4** may be heated by both the heating elements **3b** and the heated substrate **3a**. The rate at which the temperature of the substrate **3a** increases during heating may be substantially the same as the rate at which the temperature of the heating elements **3b** increase. Therefore, the temperature of the heating elements **3b** and the substrate **3a** may be approximately equal during heating of the smokeable material **5**.

(28) The arrangement of the heater **3** may be such that the peripheral surfaces of the heater **3** principally comprise those of the heated substrate **3a** and, as such, the smokeable material **5** may be heated principally by heat emitted from the heated substrate **3a** rather than being heated directly by the heating elements **3b**. For example, as described below and shown schematically in FIG. 1, the heating elements **3b** may be located principally or entirely inside the substrate **3a** and may comprise a plurality of distinct heating layers of heating elements **3b** separated by layers of substrate **3a**.

(29) The coefficient of thermal expansion of the heating elements **3b** may be matched to the coefficient of thermal expansion of the substrate **3a**. In particular, the value of the coefficient of thermal expansion of the heating elements **3b** may be substantially equal to the value of the coefficient of thermal expansion of the substrate **3a**. The heating elements **3b** and substrate **3a** may therefore together form an expansion-matching heater structure **3**.

(30) The matched thermal expansion coefficients of the substrate **3a** and heating elements **3b** means that thermal expansion of the heating elements **3b** is matched by a corresponding expansion in the substrate **3a**. Similarly, thermal contraction of the heating elements **3b** is matched by a corresponding contraction in the substrate **3a**. The expansion-matched nature of structure means that the heater **3** as a whole expands/contracts at substantially the same rate and by the same amount across the entire heater structure during heating/cooling. The expansion and contraction stresses on the heater structure **3** are small and the heater can be caused to undergo rapid, significant and frequent temperature transitions without placing significant material stress on the heater structure **3**.

(31) The substrate **3a** and the heating elements **3b** may be chemically bonded together in the heater structure **3**. For example, the chemical bonds between the substrate **3a** and the heating elements **3b** may be formed during a sintering process, in which the substrate **3a** and the heating elements **3b** are fused together under the application of heat to create a solid heater structure **3**.

(32) More specifically, the chemically bonded heater structure **3** may be manufactured by initially applying liquid heating element material **3b** to one or more surfaces of the substrate material **3a**, layering the substrate material **3a** with the heating element material **3b** and sintering the layered assembly to form the bonded heater structure **3**. This is illustrated schematically in FIG. 1.

(33) Application of the liquid heating element material **3b** can, for example, be carried out by printing the liquid material **3b** onto the substrate material **3a**. The application of the liquid heating element **3b** onto the substrate **3a** may be extremely precise so as to achieve very low tolerances, for example in the order of micrometres or nanometres, in the location of the heating element material **3b** on the substrate **3a** and thereby cause the heating elements **3b** to form in very specific desired regions of the substrate **3a**. A suitable printing process is to use a screen printer to print the liquid

3b, which may be in the form of an ink, onto the substrate material **3a**.

(34) The substrate material **3a** may comprise suitable binders and/or plasticizers which aid with the formation of the layered heater structure **3** before the formation of chemical bonds during sintering. Additionally or alternatively, the liquid heating element material **3b** may comprise suitable binders and/or plasticizers. These may be of the same composition as the binders and/or plasticizers comprised in the substrate material **3a**.

(35) The substrate material **3a** onto which the heating element material **3b** is applied may comprise pre-sintered layers of substrate **3a**, such as pre-sintered sections of ceramic tape, which are built up on top of one another to form a layered structure comprising both the substrate **3a** and the heating element material **3b**. One or more vias may be formed in the layers of substrate material **3a** so that the liquid heating material **3b** fills the vias and, ultimately, forms interconnections between the layers of heating elements **3b** in the heater **3**. In particular, each layer of heating elements **3b** may be interconnected to one or more other distinct layers of heating elements **3b** by sections of heating element **3b** which pass through the vias in the substrate **3a**.

(36) The vias may be formed by any suitable process. For example, the vias may be formed by punching holes in the individual layers of substrate **3a** before the layers of substrate **3a** are layered on top of one another in the heater structure **3**. The holes in the layers of substrate **3a** may be aligned in the layered structure so that interconnections between a plurality of layers of heating elements **3b** are created during sintering. The vias formed between the layers **3b** may be of any suitable shape, including three-dimensional shapes.

(37) If desired, a plurality of electrical circuits can be printed onto the substrate **3a** in order to provide control signals or measurement signals to/from a controller **12** of the apparatus **1**. For example, temperature measurement circuits, which may incorporate one or more Resistance Temperature Detectors (RTD), can be printed onto, adjacent or underneath the heater elements **3b**, or elsewhere on the substrate **3a**, so that the temperature of the heater **3** can be monitored and adjusted by the controller **12** to obtain desired volatilizing or pre-volatilizing temperatures in the smokeable material **5**.

(38) Before the assembly of substrate layers **3a** and heating element material **3b** is sintered to create the chemical bonds and cohesive nature of the heater **3** referred to above, the assembly may be de-bonded of the binders and/or plasticizers referred to previously.

(39) The chemical bonds and the matched thermal expansion coefficients create a robust heater structure **3**, which can be repeatedly re-used to heat and volatilize newly-loaded smokeable material **5** in the heating region **4**.

(40) The heater **3** can be manufactured into any suitable shape using the layering technique described above. For example, the heater **3** may comprise a substantially hollow cylinder located around the smokeable material heating region **4** so that heat is emitted by the heater **3** in a radially inward direction. An example of this is described below in relation to FIG. 2. Alternatively, the smokeable material heating region **4** may be located around the heater **3**. An example is a co-axial arrangement in which the heater **3** emits heat in a radially outward direction into the heating region **4**, although other shapes are also possible as will be evident from the discussion below.

(41) A specific example of an expansion matched, chemically bonded heater structure **3** is one in which the heating substrate **3a** comprises pre-sintered Aluminum Nitride Ceramic tape and the heating element material **3b** comprises Tungsten-containing ink which is screen printed onto the ceramics tape **3a**. Once the ceramics tape **3a** has been printed with the heating element material **3b** and holes have been created to form the vias referred to above, the ceramics tape **3a** is layered so as to form a structure containing internal layers of heating element material **3b** connected together by vias in the tape **3a**. The assembly is then sintered to form a cohesive and chemically-bonded heater **3**. During activation of the heater **3**, the Aluminum Nitride substrate **3a** and Tungsten heating elements **3b** expand and contract at a rate of approximately 4.5 parts per million per degree centigrade and thus the heater structure **3** as a whole expands and contracts without placing stress

on any particular part of the structure **3**.

(42) The thickness of the heater **3** may be small, such as less than 2 mm or less than 1 mm, which can contribute towards reducing the overall dimensions of the apparatus **1** compared to the use of other types of heaters. For example, the heater **3** may have a thickness of between approximately 0.1 mm and 2.0 mm, such as between approximately 0.3 mm and approximately 1.0 mm, although heaters **3** with larger thicknesses such as those up to 6.5 mm are equally possible.

(43) The heater **3** can be operated over a wide range of power outputs in order to heat and maintain the smokeable material **5** in a desired temperature range. For example, the power output of the heater **3** may be in the range of zero to approximately 2000 watts/in.sup.2 and may be controllable by the controller **12** of the apparatus **1** so that the temperature of the smokeable material **5** is maintained or adjusted into the desired temperature range. The controller **12** may adjust the power output of the heater **3** based on measurements of temperature inside the heater **3**, at the peripheral surfaces of the heater **3** and/or inside the smokeable material **5**, using the temperature measurement circuits referred to above.

(44) The controller **12** may cause the heater **3**, or distinct regions **10** of the heater **3**, to cycle between predetermined set temperatures for predetermined periods of time or may vary the temperature of the heater **3** and/or separate regions **10** of the heater **3** in accordance with a heating regime. The controller **12** and examples of suitable heating regimes are described in more detail below. The heater **3** has a low mass and therefore its use can help to reduce the overall mass of the apparatus **1**.

(45) As shown in FIG. 2 and referred to briefly above, the heater **3** may comprise a plurality of individual heating regions **10**. The heating regions **10** may be operable independently of one another so that different regions **10** can be activated at different times to heat the smokeable material **5**. This may be achieved by activating heating elements **3b** located in particular regions **10** of the heater **3** at different times. The heating regions **10** may be arranged in the heater **3** in any geometric arrangement. However, in the example shown in FIG. 2, the heating regions **10** are geometrically arranged in the heater **3** so that different ones of the heating regions **10** are arranged to predominately and independently heat different regions of the smokeable material **5**.

(46) For example, referring to FIG. 2, the heater **3** may comprise a plurality of axially aligned heating regions **10** in a substantially elongate arrangement. The regions **10** may each comprise an individual section of the heater **3**, such as an independently temperature-controllable section of the bonded substrate **3a** and heating elements **3b** structure **3** described above. The heating regions **10** may, for example, all be aligned with each other along a longitudinal axis of the heater **3**, thus providing a plurality of independent heating zones along the length of the heater **3**.

(47) Referring to FIG. 2, each heating region **10** may comprise a hollow heating cylinder **10**, which may be a ring **10**, having a finite length which is significantly less than the length of the heater **3** as a whole. The arrangement of axially aligned heating regions **10** define the exterior of the heating chamber **4** and are configured to heat smokeable material **5** located in the heating chamber **4**. As mentioned previously, the heat is applied inwardly, predominately towards the central longitudinal axis of the heating chamber **4**. The heating regions **10** are arranged with their radial, or otherwise transverse, surfaces facing one another along the length of the heater **3**. The transverse surfaces of each heating region **10** may optionally be separated from the transverse surfaces of their neighboring heating region(s) **10** by thermal insulation **18**, as shown in FIG. 2 and described below, or may connected and/or contiguous with their neighboring heating region(s) **10**.

(48) As shown in FIGS. 2 and 3, the heater **3** may alternatively be located in a central region of the housing **7** and the heating chamber **4** and smokeable material **5** may be located around the longitudinal surface of the heater **3**. In this arrangement, thermal energy emitted by the heater **3** travels outwards from the longitudinal surface of the heater **3** into the heating chamber **4** and the smokeable material **5**.

(49) The heating regions **10** may each comprise an individual section of the heater **3**. As shown in

FIGS. 1 to 4, each heating region **10** may comprise a heating cylinder **10** having a finite length which is significantly less than the length of the heater **3** as a whole. However, other configurations of heater **3** could alternatively be used and so the use of cylindrical sections of heater **3** is not required. The heating regions **10** may be arranged with their transverse surfaces facing one another along the length of the heater **3**. The transverse surfaces of each region **10** may touch the transverse surfaces of its neighboring regions **10**. Alternatively, a heat insulating or heat reflecting layer may be present between the transverse surfaces of the regions **10** so that thermal energy emitted from each one of the regions **10** does not substantially heat the neighboring regions **10** and instead travels predominately into the heating chamber **4** and smokeable material **5**. Each heating region **10** may have substantially the same dimensions as the other regions **10**.

(50) In this way, when a particular one of the heating regions **10** is activated, it supplies thermal energy to the smokeable material **5** located adjacent, for example radially adjacent, the heating region **10** without substantially heating the remainder of the smokeable material **5**. Referring to FIG. 3, the heated region of smokeable material **5** may comprise a ring of smokeable material **5** located around the heating region **10** which has been activated. The smokeable material **5** can therefore be heated in independent sections, for example rings or substantially solid cylinders, where each section corresponds to smokeable material **5** located directly adjacent a particular one of the heating regions **10** and has a mass and volume which is significantly less than the body of smokeable material **5** as a whole.

(51) Additionally or alternatively, the heater **3** may comprise a plurality of elongate, longitudinally extending heating regions **10** positioned at different locations around the central longitudinal axis of the heater **3**. The heating regions **10** may be of different lengths, or may be of substantially the same length so that each extends along substantially the whole length of the heater **3**.

(52) The heated sections of smokeable material **5** may comprise longitudinal sections of smokeable material **5** which lie parallel and directly adjacent to the longitudinal heating regions **10**. Therefore, as explained previously, the smokeable material **5** can be heated in independent sections.

(53) As will be described further below, the heating regions **10** can each be individually and selectively activated.

(54) The smokeable material **5** may be comprised in a cartridge **11** which can be inserted into the heating chamber **4**. For example, as shown in FIG. 2, the cartridge **11** can comprise a substantially solid body of smokeable material **5** such as a cylinder which fits into a recess of the heater **3**. In this configuration, the external surface of the smokeable material body faces the heater **3**. Alternatively, as shown in FIG. 3, the cartridge **11** can comprise a smokeable material tube **11** which can be inserted around the heater **3** so that the internal surface of the smokeable material tube **11** faces the longitudinal surface of the heater **3**. The smokeable material tube **11** may be hollow. The diameter of the hollow centre of the tube **11** may be substantially equal to, or slightly larger than, the diameter or otherwise transverse dimension of the heater **3** so that the tube **11** is a close fit around the heater **3**. The length of the cartridge **11** may be approximately equal to the length of the heater **3** so that the heater **3** can heat the cartridge **11** along its whole length.

(55) The housing **7** of the apparatus **1** may comprise an opening through which the cartridge **11** can be inserted into the heating chamber **4**. The opening may, for example, comprise an opening located at the housing's second end **9** so that the cartridge **11** can be slid into the opening and pushed directly into the heating chamber **4**. The opening is preferably closed during use of the apparatus **1** to heat the smokeable material **5**. Alternatively, a section of the housing **7** at the second end **9** is removable from the apparatus **1** so that the smokeable material **5** can be inserted into the heating chamber **4**. The apparatus **1** may optionally be equipped with a user-operable smokeable material ejection unit, such as an internal mechanism configured to slide used smokeable material **5** off and/or away from the heater **3**. The used smokeable material **5** may, for example, be pushed back through the opening in the housing **7**. A new cartridge **11** can then be inserted as required.

(56) As mentioned previously, the apparatus **1** may comprise a controller **12**, such as a

microcontroller **12**, which is configured to control operation of the apparatus **1**. The controller **12** is electronically connected to the other components of the apparatus **1** such as the energy source **2** and heater **3** so that it can control their operation by sending and receiving signals. The controller **12** is, in particular, configured to control activation of the heater **3** to heat the smokeable material **5**. For example, the controller **12** may be configured to activate the heater **3**, which may comprise selectively activating one or more heating regions **10**, in response to a user drawing on the mouthpiece **6** of the apparatus **1**. In this regard, the controller **12** may be in communication with a puff sensor **13** via a suitable communicative coupling. The puff sensor **13** is configured to detect when a puff occurs at the mouthpiece **6** and, in response, is configured to send a signal to the controller **12** indicative of the puff. An electronic signal may be used. The controller **12** may respond to the signal from the puff sensor **13** by activating the heater **3** and thereby heating the smokeable material **5**. The use of a puff sensor **13** to activate the heater **3** is not, however, essential and other means for providing a stimulus to activate the heater **3** can alternatively be used. For example, the controller **12** may activate the heater **3** in response to another type of activation stimulus such as actuation of a user-operable actuator. The volatilized compounds released during heating can then be inhaled by the user through the mouthpiece **6**. The controller **12** can be located at any suitable position within the housing **7**. An example position is between the energy source **2** and the heater **3**/heating chamber **4**, as illustrated in FIG. **5**.

(57) If the heater **3** comprises two or more heating regions **10** as described above, the controller **12** may be configured to activate the heating regions **10** in a predetermined order or pattern. For example, the controller **12** may be configured to activate the heating regions **10** sequentially along or around the heating chamber **4**. Each activation of a heating region **10** may be in response to detection of a puff by the puff sensor **13** or may be triggered in an alternative way, as described further below.

(58) Referring to FIG. **6**, an example heating method may comprise a first step **S1** in which an activation stimulus such as a first puff is detected followed by a second step **S2** in which a first section of smokeable material **5** is heated in response to the first puff or other activation stimulus. In a third step **S3**, hermetically sealable inlet and outlet valves **24** may be opened to allow air to be drawn through the heating chamber **4** and out of the apparatus **1** through the mouthpiece **6**. In a fourth step **S4**, the valves **24** are closed. These valves **24** are described in more detail below with respect to FIG. **30**. In fifth **S5**, sixth **S6**, seventh **S7** and eighth **S8** steps, a second section of smokeable material **5** may be heated in response to a second activation stimulus such as a second puff, with a corresponding opening and closing of the heating chamber inlet and outlet valves **24**. In ninth **S9**, tenth **S10**, eleventh **S11** and twelfth **S12** steps, a third section of the smokeable material **5** may be heated in response to a third activation stimulus such as a third puff with a corresponding opening and closing of the heating chamber inlet and outlet valves **24**, and so on. As referred to above, means other than a puff sensor **13** could alternatively be used. For example, a user of the apparatus **1** may actuate a control switch to indicate that he/she is taking a new puff. In this way, a fresh section of smokeable material **5** may be heated to volatilize nicotine and aromatic compounds for each new puff. The number of heating regions **10** and/or independently heatable sections of smokeable material **5** may correspond to the number of puffs for which the cartridge **11** is intended to be used. Alternatively, each independently heatable smokeable material section **5** may be heated by its corresponding heating region(s) **10** for a plurality of puffs such as two, three or four puffs, so that a fresh section of smokeable material **5** is heated only after a plurality of puffs have been taken whilst heating the previous smokeable material section.

(59) Instead of activating each heating region **10** in response to an individual puff, the heating regions **10** may alternatively be activated sequentially, one after the other, in response to a single, initial puff at the mouthpiece **6**. For example, the heating regions **10** may be activated at regular, predetermined intervals over the expected inhalation period for a particular smokeable material cartridge **11**. The inhalation period may, for example, be between approximately one and

approximately four minutes. Therefore, at least the fifth and ninth steps S5, S9 shown in FIG. 6 are optional. Each heating region **10** may be activated for a predetermined period corresponding to the duration of the single or plurality of puffs for which the corresponding independently heatable smokeable material section **5** is intended to be heated. Once all of the heating regions **10** have been activated for a particular cartridge **11**, the controller **12** may be configured to indicate to the user that the cartridge **11** should be changed. The controller **12** may, for example, activate an indicator light at the external surface of the housing **7**.

(60) It will be appreciated that activating individual heating regions **10** in order rather than activating the entire heater **3** means that the energy required to heat the smokeable material **5** is reduced over what would be required if the heater **3** were activated fully over the entire inhalation period of a cartridge **11**. Therefore, the maximum required power output of the energy source **2** is also reduced. This means that a smaller and/or lighter energy source **2** can be installed in the apparatus **1**.

(61) The controller **12** may be configured to de-activate the heater **3**, or reduce the power being supplied to the heater **3**, in between puffs. This saves energy and extends the life of the energy source **2**. For example, upon the apparatus **1** being switched on by a user or in response to some other stimulus, such as detection of a user placing their mouth against the mouthpiece **6**, the controller **12** may be configured to cause the heater **3**, or next heating region **10** to be used to heat the smokeable material **5**, to be partially activated so that it heats up in preparation to volatilize components of the smokeable material **5**. The partial activation does not heat the smokeable material **5** to a sufficient temperature to volatilize nicotine. A suitable temperature could be less than 120° C., such as approximately 100° C. In response to detection of a puff by the puff sensor **13**, the controller **12** can then cause the heater **3** or heating region **10** in question to heat the smokeable material **5** further in order to rapidly volatilize the nicotine and other aromatic compounds for inhalation by the user. If the smokeable material **5** comprises tobacco, a suitable temperature for volatilizing the nicotine and other aromatic compounds may be above 120° C., such between 150° C. and 250° C. or between 130° C. and 180° C. Therefore, examples of full activation temperatures include 180° C. and 250° C. A super-capacitor can optionally be used to provide the peak current used to heat the smokeable material **5** to the volatilization temperature. An example of a suitable heating pattern is shown in FIG. 8, in which the peaks may respectively represent the full activation of different heating regions **10**. As can be seen, the smokeable material **5** is maintained at the volatilization temperature for the approximate period of the puff which, in this example, is two seconds.

(62) Three example operational modes of the heater **3** are described below.

(63) In a first operational mode, during full activation of a particular heating region **10**, all other heating regions **10** of the heater are deactivated. Therefore, when a new heating region **10** is activated, the previous heating region is deactivated. Power is supplied only to the activated region **10**.

(64) Alternatively, in a second operational mode, during full activation of a particular heating region **10**, one or more of the other heating regions **10** may be partially activated. Partial activation of the one or more other heating regions **10** may comprise heating the other heating region(s) **10** to a temperature which is sufficient to substantially prevent condensation of components such as nicotine volatilized from the smokeable material **5** in the heating chamber **4**. The temperature of the heating regions **10** which are partially activated is less than the temperature of the heating region **10** which is fully activated. The smokeable material **10** located adjacent the partially activated regions **10** is not heated to a temperature sufficient to volatilize components of the smokeable material **5**.

(65) Alternatively, in a third operational mode, once a particular heating region **10** has been activated, it remains fully activated until the heater **3** is switched off. Therefore, the power supplied to the heater **3** incrementally increases as more of the heating regions **10** are activated during inhalation from the cartridge **11**. As with the second mode previously described, the continuing

activation of the heating regions **10** substantially prevent condensation of components such as nicotine volatilized from the smokeable material **5** in the heating chamber **4**.

(66) The apparatus **1** may comprise a heat shield **100**, which is located between the heater **3** and the heating chamber **4**/smokeable material **5**. The heat shield **100** is configured to substantially prevent thermal energy from flowing through the heat shield **100** and therefore can be used to selectively prevent the smokeable material **5** from being heated even when the heater **3** is activated and emitting thermal energy. Referring to FIG. **15**, the heat shield **100** may, for example, comprise a cylindrical layer of heat reflective material which is located co-axially around the heater **3**.

Alternatively, if the heater **3** is located around the heating chamber **4** and smokeable material **5** as previously described with reference to FIG. **2**, the heat shield **100** may comprise a cylindrical layer of heat reflective material which is located co-axially around the heating chamber **4** and co-axially inside of the heater **3**. The heat shield **100** may additionally or alternatively comprise a heat-insulating layer configured to insulate the heater **3** from the smokeable material **5**.

(67) The heat shield **100** comprises a substantially heat-transparent window **101** which allows thermal energy to propagate through the window **101** and into the heating chamber **4** and smokeable material **5**. Therefore, the section of smokeable material **5** which is aligned with the window **101** is heated whilst the remainder of the smokeable material **5** is not. The heat shield **100** and window **101** may be rotatable or otherwise moveable with respect the smokeable material **5** so that different sections of the smokeable material **5** can be selectively and individually heated by rotating or moving the heat shield **100** and window **101**. The effect is similar to the effect provided by selectively and individually activating the heating regions **10** referred to above. For example, the heat shield **100** and window **101** may be rotated or otherwise moved incrementally in response to a signal from the puff detector **13**. Additionally or alternatively, the heat shield **100** and window **101** may be rotated or otherwise moved incrementally in response to a predetermined heating period having elapsed. Movement or rotation of the heat shield **100** and window **101** may be controlled by electronic signals from the controller **12**. The relative rotation or other movement of the heat shield **100**/window **101** and smokeable material **5** may be driven by a stepper motor **3c** under the control of the controller **12**. This is illustrated in FIG. **15**. Alternatively, the heat shield **100** and window **101** may be manually rotated using a user control such as an actuator on the housing **7**. The heat shield **100** does not need to be cylindrical and may optionally comprise one or more suitably positioned longitudinally extending elements and or/plates.

(68) It will be appreciated that a similar result can be obtained by rotating or moving the smokeable material **5** relative to the heater **3**, heat shield **100** and window **101**. For example, the heating chamber **4** may be rotatable around the heater **3**. If this is the case, the above description relating to movement of the heat shield **100** can be applied instead to movement of the heating chamber **4** relative to the heat shield **100**.

(69) The heat shield **100** may comprise a coating on the longitudinal surface of the heater **3**. In this case, an area of the heater's surface is left uncoated to form the heat-transparent window **101**. The heater **3** can be rotated or otherwise moved, for example under the control of the controller **12** or user controls, to cause different sections of the smokeable material **5** to be heated. Alternatively, the heat shield **100** and window **101** may comprise a separate shield **3a** which is rotatable or otherwise moveable relative to both the heater **3** and the smokeable material **5** under the control of the controller **12** or other user controls.

(70) The apparatus **1** may comprise air inlets **14** which allow external air to be drawn into the housing **7** and through the heated smokeable material **5** during puffing. The air inlets **14** may comprise apertures **14** in the housing **7** and may be located upstream from the smokeable material **5** and heating chamber **4** towards the first end **8** of the housing **7**. This is shown in FIG. **2**. Another example is shown in FIG. **7**. Air drawn in through the inlets **14** travels through the heated smokeable material **5** and therein is enriched with smokeable material vapors, such as aroma vapors, before being inhaled by the user at the mouthpiece **6**. Optionally, as shown in FIG. **7**, the

apparatus **1** may comprise a heat exchanger **15** configured to warm the air before it enters the smokeable material **5** and/or to cool the air before it is drawn through the mouthpiece **6**. For example, the heat exchanger **15** may be configured to use heat extracted from the air entering the mouthpiece **6** to warm new air before it enters the smokeable material **5**.

(71) The apparatus **1** may comprise a smokeable material compressor **16** configured to cause the smokeable material **5** to compress upon activation of the compressor **16**. The apparatus **1** can also comprise a smokeable material expander **17** configured to cause the smokeable material **5** to expand upon activation of the expander **17**. The compressor **16** and expander **17** may, in practice, be implemented as the same unit as will be explained below. The smokeable material compressor **16** and expander **17** may optionally operate under the control of the controller **12**. In this case, the controller **12** is configured to send a signal, such as an electrical signal, to the compressor **16** or expander **17** which causes the compressor **16** or expander **17** to respectively compress or expand the smokeable material **5**. Alternatively, the compressor **16** and expander **17** may be actuated by a user of the apparatus **1** using a manual control on the housing **7** to compress or expand the smokeable material **5** as required.

(72) The compressor **16** is principally configured to compress the smokeable material **5** and thereby increase its density during heating. Compression of the smokeable material increases the thermal conductivity of the body of smokeable material **5** and therefore provides a more rapid heating and consequent rapid volatilization of nicotine and other aromatic compounds. This allows the nicotine and aromatics to be inhaled by the user without substantial delay in response to detection of a puff. Therefore, the controller **12** may activate the compressor **16** to compress the smokeable material **5** for a predetermined heating period, for example one second, in response to detection of a puff. The compressor **16** may be configured to reduce its compression of the smokeable material **5**, for example under the control of the controller **12**, after the predetermined heating period.

Alternatively, the compression may be reduced or automatically ended in response to the smokeable material **5** reaching a predetermined threshold temperature. A suitable threshold temperature may be in the range of approximately 120° C. to 250° C., or one of the other ranges discussed previously, and may be user selectable. A temperature sensor may be used to detect the temperature of the smokeable material **5**.

(73) The expander **17** is principally configured to expand the smokeable material **5** and thereby decrease its density during puffing. The arrangement of smokeable material **5** in the heating chamber **4** becomes more loose when the smokeable material **5** has been expanded and this aids the gaseous flow, for example air from the inlets **14**, through the smokeable material **5**. The air is therefore more able to carry the volatilized nicotine and aromatics to the mouthpiece **6** for inhalation. The controller **12** may activate the expander **17** to expand the smokeable material **5** immediately following the compression period referred to above so that air can be drawn more freely through the smokeable material **5**. Actuation of the expander **17** may be accompanied by a user-audible sound or other indication to indicate to the user that the smokeable material **5** has been heated and that puffing can commence.

(74) Referring to FIGS. **8** and **9**, the compressor **16** and expander **17** may comprise a spring-actuated driving rod which is configured to compress the smokeable material **5** in the heating chamber **4** when the spring is released from compression. This is schematically illustrated in FIGS. **8** and **9**, although it will be appreciated that other implementations could be used. For example, the compressor **16** may comprise a ring, having a thickness approximately equal to the tubular-shaped heating chamber **4** described above, which is driven by a spring or other means into the heating chamber **4** to compress the smokeable material **5**. Alternatively, the compressor **16** may be comprised as part of the heater **3** so that the heater **3** itself is configured to compress and expand the smokeable material **5** under the control of the controller **12**. A method of compressing and expanding the smokeable material **5** is shown in FIG. **11**. The method comprises a first step P1 of compressing the smokeable material **5** in its heating chamber **4**, a second step P2 of heating the

compressed smokeable material **5**, a third step **P3** of detecting a threshold temperature in the smokeable material **5**, a fourth step **S4** of expanding the smokeable material **5**, for example by releasing the compression force, and a fifth step **S5** of allowing external air to enter the smokeable material heating chamber **4**, for example by opening hermetically sealable inlet and outlet valves **24**.

(75) The heater **3** may be integrated with the thermal insulation **18** mentioned previously. For example, referring to FIG. **2**, the thermal insulation **18** may comprise a substantially elongate, hollow body, such as a substantially cylindrical tube of insulation **18**, which is located co-axially around the heating chamber **4** and into which the heating regions **10** are integrally located. The thermal insulation **18** may comprise a layer in which recesses are provided in the inwardly facing surface profile **21**. Heating regions **10** are located in these recesses so that the heating regions **10** face the smokeable material **5** in the heating chamber **4**. The surfaces of the heating regions **10** which face the heating chamber **4** may be flush with the inside surface **21** of the thermal insulation **18** in regions of the insulation **18** which are not recessed.

(76) The integration of the heater **3** with the thermal insulation **18** means that the heating regions **10** are substantially surrounded by the insulation **18** on all sides of the heating regions **10** other than those which face inwardly towards the smokeable material heating chamber **4**. As such, heat emitted by the heater **3** is concentrated in the smokeable material **5** and does not dissipate into other parts of the apparatus **1** or into the atmosphere outside the housing **7**.

(77) Integration of the heater **3** with the thermal insulation **18** may also reduce the thickness of the combination of heater **3** and thermal insulation **18**. This can allow the diameter of the apparatus **1**, in particular the external diameter of the housing **7**, to be further reduced. Alternatively, the reduction in thickness provided by the integration of the heater **3** with the thermal insulation **18** can allow a wider smokeable material heating chamber **4** to be accommodated in the apparatus **1**, or the introduction of further components, without any increase in the overall width of the housing **7**.

(78) Alternatively, the heater **3** may be located adjacent the insulation **18** rather than being integrated into it. For example, if the heater **3** is located externally of the heating chamber **4** as shown in FIG. **2**, the insulation **18** may be located around the outside of the heater **3** so that the inwardly-facing surface **21** of the insulation faces the heater **3**. If the heater **3** is located internally of the heating chamber **4**, the heater **3** may be located around the outwardly-facing surface **22** of the insulation **18**.

(79) Optionally, a barrier may be present between the heater **3** and the insulation **18**. For example, a layer of stainless steel may be present between the heater **3** and the insulation **18**. The barrier may comprise a stainless steel tube which fits between the heater **3** and the insulation **18**. The thickness of the barrier may be small so as not to substantially increase the dimensions of the apparatus. An example thickness is between approximately 0.1 mm and 1.0 mm.

(80) Additionally, a heat reflecting layer may be present between the transverse surfaces of the heating regions **10**. The arrangement of the heating regions **10** relative to each other may be such that thermal energy emitted from each one of the heating regions **10** does not substantially heat the neighboring heating regions **10** and instead travels predominately inwardly from the circumferential surface of the heating region **10** into the heating chamber **4** and smokeable material **5**. Each heating region **10** may have substantially the same dimensions as the other regions **10**.

(81) The heater **3** may be bonded or otherwise secured in the apparatus **1** using pressure sensitive adhesive. For example, the heater **3** may be adhered to the insulation **18** or barrier referred to above using pressure sensitive adhesive. The heater **3** may alternatively be adhered to the cartridge **11** or an exterior surface of the smokeable material heating chamber **4**.

(82) As an alternative to the use of pressure sensitive adhesive, the heater **3** may be secured in position in the apparatus **1** using self-fusing tape or by clamps which clamp the heater **3** in place. All of these methods provide a secure fixing for the heater **3** and allow effective heat transfer from the heater **3** to the smokeable material **5**. Other types of fixing are also possible.

(83) The thermal insulation **18**, which is provided between the smokeable material **5** and an external surface **19** of the housing **7**, as described above, reduces heat loss from the apparatus **1** and therefore improves the efficiency with which the smokeable material **5** is heated. For example, referring to FIG. **2**, a wall of the housing **7** may comprise a layer of insulation **18** which extends around the outside of the heating chamber **4**. The insulation layer **18** may comprise a substantially tubular length of insulation **18** located co-axially around the heating chamber **4** and smokeable material **5**. This is shown in FIG. **2**. It will be appreciated that the insulation **18** could also be comprised as part of the smokeable material cartridge **11**, in which it would be located co-axially around the outside of the smokeable material **5**.

(84) Referring to FIG. **12**, the insulation **18** may comprise vacuum insulation **18**. For example, the insulation **18** may comprise a layer which is bounded by a wall material **19** such as a metallic material. An internal region or core **20** of the insulation **18** may comprise an open-cell porous material, for example comprising polymers, aerogels or other suitable material, which is evacuated to a low pressure. The pressure in the internal region **20** may be in the range of 0.1 to 0.001 mbar. The wall **19** of the insulation **18** is sufficiently strong to withstand the force exerted against it due to the pressure differential between the core **20** and external surfaces of the wall **19**, thereby preventing the insulation **18** from collapsing. The wall **19** may, for example, comprise a stainless steel wall **19** having a thickness of approximately 100 μm . The thermal conductivity of the insulation **18** may be in the range of 0.004 to 0.005 W/mK. The heat transfer coefficient of the insulation **18** may be between approximately 1.10 W/(m²·K) and approximately 1.40 W/(m²·K) within a temperature range of between approximately 150 degrees Celsius and approximately 250 degrees Celsius. The gaseous conductivity of the insulation **18** is negligible. A reflective coating may be applied to the internal surfaces of the wall material **19** to minimize heat losses due to radiation propagating through the insulation **18**. The coating may, for example, comprise an aluminum IR reflective coating having a thickness of between approximately 0.3 μm and 1.0 μm . The evacuated state of the internal core region **20** means that the insulation **18** functions even when the thickness of the core region **20** is very small. The insulating properties are substantially unaffected by its thickness. This helps to reduce the overall size of the apparatus **1**.

(85) As shown in FIG. **12**, the wall **19** may comprise an inwardly-facing section **21** and an outwardly-facing section **22**. The inwardly-facing section **21** substantially faces the smokeable material **5** and heating chamber **4**. The outwardly-facing section **22** substantially faces the exterior of the housing **7**. During operation of the apparatus **1**, the inwardly-facing section **21** may be warmer due to the thermal energy originating from the heater **3**, whilst the outwardly-facing section **22** is cooler due to the effect of the insulation **18**. The inwardly-facing section **21** and the outwardly-facing section **22** may, for example, comprise substantially parallel longitudinally-extending walls **19** which are at least as long as the heater **3**. The internal surface of the outwardly-facing wall section **22**, i.e. the surface facing the evacuated core region **20**, may comprise a coating for absorbing gas in the core **20**. A suitable coating is a titanium oxide film.

(86) The thermal insulation **18** may comprise hyper-deep vacuum insulation such as an Insulon® Shaped-Vacuum Thermal Barrier as described in U.S. Pat. No. 7,374,063. The overall thickness of such insulation **18** may be extremely small. An example thickness is between approximately 1 mm and approximately 1 μm , such as approximately 0.1 mm, although other larger or smaller thicknesses are also possible. The thermally insulating properties of the insulation **18** are substantially unaffected by its thickness and therefore thin insulation **18** can be used without any substantial additional heat loss from the apparatus **1**. The very small thickness of the thermal insulation **18** may allow the size of the housing **7** and apparatus **1** as a whole to be reduced beyond the sizes previously discussed and may allow the thickness, for example the diameter, of the apparatus **1** to be approximately equal to smoking articles such as cigarettes, cigars and cigarillos. The weight of the apparatus **1** may also be reduced, providing similar benefits to the size reductions discussed above.

(87) Although the thermal insulation **18** described previously may comprise a gas-absorbing material to maintain or aid with creation of the vacuum in the core region **20**, a gas absorbing material is not used in the deep-vacuum insulation **18**. The absence of the gas absorbing material aids with keeping the thickness of the insulation **18** very low and thus helps to reduce the overall size of the apparatus **1**.

(88) The geometry of the hyper-deep insulation **18** allows the vacuum in the insulation to be deeper than the vacuum used to extract molecules from the core region **20** of the insulation **18** during manufacture. For example, the deep vacuum inside the insulation **18** may be deeper than that of the vacuum-furnace chamber in which it is created. The vacuum inside the insulation **18** may, for example, be of the order 10^{-7} Torr. Referring to FIG. **17**, an end of the core region **20** of the deep-vacuum insulation **18** may taper as the outwardly facing section **22** and inwardly facing section **21** converge to an outlet **25** through which gas in the core region **20** may be evacuated to create a deep vacuum during manufacture of the insulation **18**. FIG. **17** illustrates the outwardly facing section **22** converging towards the inwardly facing section **21** but a converse arrangement, in which the inwardly facing section **21** converges to the outwardly facing section **22**, could alternatively be used. The converging end of the insulating wall **19** is configured to guide gas molecules in the core region **20** out of the outlet **25** and thereby create a deep vacuum in the core **20**. The outlet **25** is sealable so as to maintain a deep vacuum in the core region **20** after the region **20** has been evacuated. The outlet **25** can be sealed, for example, by creating a brazed seal at the outlet **25** by heating brazing material at the outlet **25** after gas has been evacuated from the core **20**. Alternative sealing techniques could be used.

(89) In order to evacuate the core region **20**, the insulation **18** may be placed in a low pressure, substantially evacuated environment such as a vacuum furnace chamber so that gas molecules in the core region **20** flow into the low pressure environment outside the insulation **18**. When the pressure inside the core region **20** becomes low, the tapered geometry of the core region **20**, and in particular the converging sections **21**, **22** referred to above, becomes influential in guiding remaining gas molecules out the core **20** via the outlet **25**. Specifically, when the gas pressure in the core region **20** is low, the guiding effect of the converging inwardly and outwardly facing sections **21**, **22** is effective to channel the remaining gas molecules inside the core **20** towards the outlet **25** and make the probability of gas exiting the core **20** higher than the probability of gas entering the core **20** from the external, low pressure environment. In this way, the geometry of the core **20** allows the pressure inside the core **20** to be reduced below the pressure of the environment outside the insulation **18**.

(90) Optionally, as previously described, one or more low emissivity coatings may be present on the internal surfaces of the inwardly and outwardly facing sections **21**, **22** of the wall **19** in order to substantially prevent heat losses by radiation.

(91) Although the shape of the insulation **18** is generally described herein as substantially cylindrical or similar, the thermal insulation **18** could be another shape, for example in order to accommodate and insulate a different configuration of the apparatus **1** such as different shapes and sizes of heating chamber **4**, heater **3**, housing **7** or energy source **2**. For example, the size and shape of deep-vacuum insulation **18** such as an Insulon® Shaped-Vacuum Thermal Barrier referred to above is substantially unlimited by its manufacturing process. Suitable materials for forming the converging structure described above include ceramics, metals, metalloids and combinations of these.

(92) Referring to the schematic illustration in FIG. **13**, a thermal bridge **23** may connect the inwardly-facing wall section **21** to the outwardly-facing wall section **22** at one or more edges of the insulation **18** in order to completely encompass and contain the low pressure core **20**. The thermal bridge **23** may comprise a wall **19** formed of the same material as the inwardly and outwardly-facing sections **21**, **22**. A suitable material is stainless steel, as previously discussed. The thermal bridge **23** has a greater thermal conductivity than the insulating core **20** and therefore may

undesirably conduct heat out of the apparatus **1** and, in doing so, reduce the efficiency with which the smokeable material **5** is heated.

(93) To reduce heat losses due to the thermal bridge **23**, the thermal bridge **23** may be extended to increase its resistance to heat flow from the inwardly-facing section **21** to the outwardly-facing section **22**. This is schematically illustrated in FIG. **14**. For example, the thermal bridge **23** may follow an indirect path between the inwardly-facing section **21** of wall **19** and the outwardly-facing section **22** of wall **19**. This may be facilitated by providing the insulation **18** over a longitudinal distance which is longer than the lengths of the heater **3**, heating chamber **4** and smokeable material **5** so that the thermal bridge **23** can gradually extend from the inwardly-facing section **21** to the outwardly-facing section **22** along the indirect path, thereby reducing the thickness of the core **20** to zero, at a longitudinal location in the housing **7** where the heater **3**, heating chamber **4** and smokeable material **5** are not present.

(94) Referring to FIG. **16**, as previously discussed, the heating chamber **4** insulated by the insulation **18** may comprise inlet and outlet valves **24** which hermetically seal the heating chamber **4** when closed. The valves **24** can thereby prevent air from undesirably entering and exiting the chamber **4** and can prevent smokeable material flavors from exiting the chamber **4**. The inlet and outlet valves **24** may, for example, be provided in the insulation **18**. For example, between puffs, the valves **24** may be closed by the controller **12** so that all volatilized substances remain contained inside the chamber **4** in-between puffs. The partial pressure of the volatilized substances between puffs reaches the saturated vapour pressure and the amount of evaporated substances therefore depends only on the temperature in the heating chamber **4**. This helps to ensure that the delivery of volatilized nicotine and aromatic compounds remains constant from puff to puff. During puffing, the controller **12** is configured to open the valves **24** so that air can flow through the chamber **4** to carry volatilized smokeable material components to the mouthpiece **6**. A membrane can be located in the valves **24** to ensure that no oxygen enters the chamber **4**. The valves **24** may be breath-actuated so that the valves **24** open in response to detection of a puff at the mouthpiece **6**. The valves **24** may close in response to a detection that a puff has ended. Alternatively, the valves **24** may close following the elapse of a predetermined period after their opening. The predetermined period may be timed by the controller **12**. Optionally, a mechanical or other suitable opening/closing means may be present so that the valves **24** open and close automatically. For example, the gaseous movement caused by a user puffing on the mouthpiece **6** may be used to open and close the valves **24**. Therefore, the use of the controller **12** is not necessarily required to actuate the valves **24**.

(95) The mass of the smokeable material **5** which is heated by the heater **3**, for example by each heating region **10**, may be in the range of 0.2 to 1.0 g. The temperature to which the smokeable material **5** is heated may be user controllable, for example to any temperature within the temperature range of 120° C. to 250° C. as previously described. The mass of the apparatus **1** as a whole may be in the range of 70 to 125 g, although the mass of the apparatus **1** can be lower when incorporating the type of heater **3** described above and/or deep-vacuum insulation **18**. A battery **2** with a capacity of 1000 to 3000 mAh and voltage of 3.7V can be used. The heating regions **10** may be configured to individually and selectively heat between approximately 10 and 40 sections of smokeable material **5** for a single cartridge **11**.

(96) It will be appreciated that any of the alternatives described above can be used singly or in combination.

(97) In order to address various issues and advance the art, the entirety of this disclosure shows by way of illustration various embodiments in which the claimed invention(s) may be practiced and provide for superior apparatus. The advantages and features of the disclosure are of a representative sample of embodiments only, and are not exhaustive and/or exclusive. They are presented only to assist in understanding and teach the claimed features. It is to be understood that advantages, embodiments, examples, functions, features, structures, and/or other aspects of the disclosure are

not to be considered limitations on the disclosure as defined by the claims or limitations on equivalents to the claims, and that other embodiments may be utilized and modifications may be made without departing from the scope and/or spirit of the disclosure. Various embodiments may suitably comprise, consist of, or consist essentially of, various combinations of the disclosed elements, components, features, parts, steps, means, etc. In addition, the disclosure includes other inventions not presently claimed, but which may be claimed in future.

Claims

1. An apparatus comprising: a smokeable material heating chamber configured to contain a body of smokeable material during heating; and a heater arranged to heat smokeable material, wherein the heater comprises a substrate and at least one heating element embedded in the substrate so as to heat the substrate to cause the substrate to volatilize at least one component of the smokeable material for inhalation, wherein the smokeable material heating chamber is located around the heater such that the heater emits heat in a radially outward direction into the smokeable material heating chamber, wherein the heater has peripheral surfaces, and wherein the heater is arranged such that the peripheral surfaces of the heater principally comprise those of the substrate such that the smokeable material is heated principally by heat emitted from the heated substrate rather than being heated directly by the at least one heating element, wherein the heating element is arranged to heat the substrate to a temperature sufficient for the substrate to volatilize at least one component of the smokeable material, and wherein the rate at which the temperature of the substrate increases during heating is substantially the same as the rate at which the temperature of the at least one heating element increases.
2. An apparatus according to claim 1, wherein the coefficient of thermal expansion of the heating element is substantially equal to the coefficient of thermal expansion of the substrate.
3. An apparatus according to claim 1, wherein the heating element and the substrate are sintered to form a chemically bonded structure.
4. An apparatus according to claim 1, wherein the substrate comprises a ceramics material and the heating element comprises an electrically resistive trace material.
5. An apparatus according to claim 1, comprising a plurality of the heating elements arranged in layers inside the substrate.
6. An apparatus according to claim 5, wherein the layers of heating elements are interconnected by heating element vias through the substrate.
7. An apparatus according to claim 1, configured to heat the smokeable material to a smokeable material volatilizing temperature of at least 120 degrees Celsius.
8. An apparatus according to claim 1, configured to heat the smokeable material to a smokeable material volatilizing temperature of between 120 degrees Celsius and 250 degrees Celsius.
9. An apparatus according to claim 1, configured to heat the smokeable material to a smokeable material volatilizing temperature of between 130 degrees Celsius and 180 degrees Celsius.
10. An apparatus according to claim 1, wherein the at least one heating element is a printed heating element and wherein the at least one electrical circuit is a printed electrical circuit.
11. An apparatus according to claim 1, wherein the temperature measurement circuit comprises a resistance temperature detector.
12. An apparatus according to claim 1, wherein the heater comprises at least one electrical circuit embedded in the substrate to provide control signals or measurement signals to a controller of the apparatus, wherein the at least one electrical circuit comprises a temperature measurement circuit embedded in the substrate, and wherein the temperature measurement circuit is located on, adjacent to or underneath the at least one heating element.
13. Use of an apparatus comprising a smokeable material heating chamber configured to contain a body of smokeable material during heating and a heater comprising a substrate and at least one

heating element embedded in the substrate to heat the substrate and cause the substrate to volatilize at least one component of smokeable material for inhalation, wherein the smokeable material heating chamber is located around the heater such that the heater emits heat in a radially outward direction into the smokeable material heating chamber, wherein the heater has peripheral surfaces, and wherein the heater is arranged such that the peripheral surfaces of the heater principally comprise those of the substrate such that the smokeable material is heated principally by heat emitted from the heated substrate rather than being heated directly by the at least one heating element; wherein the heating element is arranged to heat the substrate to a temperature sufficient for the substrate to volatilize at least one component of the smokeable material; and wherein the rate at which the temperature of the substrate increases during heating is substantially the same as the rate at which the temperature of the at least one heating element increases.
