

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409294
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Donnelly; Jess Edward

Float retention arrangement for humidification chamber

Abstract

A float retention arrangement and related methods for a humidification chamber that includes at least one float that operates an inlet valve that controls a flow of water through a water inlet opening of the humidification chamber. A cover of the humidification chamber defines an interior space, at least one gas port and a float retention opening. A component forms at least a portion of a water supply conduit for supplying water from a water source to the water inlet opening. The component is insertable into the float retention opening and is positionable to contact and retain the at least one float in a non-use position. In some configurations, the component can be a water spike.

Inventors:	Donnelly; Jess Edward (Auckland, NZ)
Applicant:	Fisher & Paykel Healthcare Limited (Auckland, NZ)
Family ID:	52628715
Assignee:	Fisher & Paykel Healthcare Limited (Auckland, NZ)
Appl. No.:	18/458446
Filed:	August 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230414897 A1	Dec. 28, 2023

Related U.S. Application Data

continuation parent-doc US 17303588 20210602 US 11786692 child-doc US 18458446
continuation parent-doc US 16255175 20190123 US 11052218 20210706 child-doc US 17303588
continuation parent-doc US 14914510 US 10207074 20190219 WO PCT/NZ2014/000177
20140826 child-doc US 16255175
us-provisional-application US 61873777 20130904

Publication Classification

Int. Cl.: A61M16/16 (20060101); A61M16/08 (20060101); F16K31/26 (20060101)

U.S. Cl.:

CPC A61M16/168 (20140204); A61M16/0816 (20130101); A61M16/167 (20140204); F16K31/26 (20130101);

Field of Classification Search

CPC: A61M (16/165); A61M (16/167); A61M (16/168)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2989053	12/1960	Hamilton	N/A	N/A
3316908	12/1966	Burke	N/A	N/A
3822700	12/1973	Pennington	N/A	N/A
4045525	12/1976	Huggins	N/A	N/A
4173223	12/1978	Raines et al.	N/A	N/A
D257886	12/1980	Kersten	N/A	N/A
4262671	12/1980	Kersten	N/A	N/A
D267270	12/1981	Mittleman	N/A	N/A
4405315	12/1982	Handt	N/A	N/A
4411661	12/1982	Kersten	N/A	N/A
D272850	12/1983	Kulle	N/A	N/A
4573967	12/1985	Hargrove et al.	N/A	N/A
4665391	12/1986	Spani	N/A	N/A
4834744	12/1988	Ritson	N/A	N/A
4926856	12/1989	Cambio, Jr.	604/407	A61M 16/164
5071413	12/1990	Utterberg	N/A	N/A
5098407	12/1991	Okamura	N/A	N/A
5125911	12/1991	Grabenkort et al.	N/A	N/A
5195515	12/1992	Levine	N/A	N/A
5267412	12/1992	Bergin	N/A	N/A
5400923	12/1994	Golias et al.	N/A	N/A
5445143	12/1994	Sims	251/210	A61M 16/168
5445630	12/1994	Richmond	N/A	N/A
5618000	12/1996	Lantzy et al.	N/A	N/A
5833674	12/1997	Turnbull	604/905	A61M 39/045
5943473	12/1998	Levine	N/A	N/A
6183453	12/2000	Swisher	N/A	N/A
6261267	12/2000	Chen	N/A	N/A
10207074	12/2018	Donnelly	N/A	N/A

11052218	12/2020	Donnelly	N/A	N/A
11786692	12/2022	Donnelly	N/A	N/A
2004/0050386	12/2003	Levine	128/203.16	A61M 16/167
2004/0108393	12/2003	Thayer et al.	N/A	N/A
2005/0182383	12/2004	Wallen	N/A	N/A
2006/0081258	12/2005	Nalagatla et al.	N/A	N/A
2008/0054500	12/2007	Bradley et al.	N/A	N/A
2009/0005753	12/2008	Browne	N/A	N/A
2009/0254031	12/2008	Lee	N/A	N/A
2010/0170511	12/2009	Payne	137/423	A61M 16/167
2011/0108028	12/2010	Zollinger	128/203.12	A61M 16/168
2011/0156289	12/2010	Steg	261/DIG.65	A61M 16/168
2012/0203194	12/2011	Cederschiold et al.	N/A	N/A
2014/0150911	12/2013	Hanner et al.	N/A	N/A
2016/0228671	12/2015	Jackson et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO 2013/162386	12/2012	WO	N/A

OTHER PUBLICATIONS

PCT Application No. PCT/NZ2014/000177 International Search Report and Written Opinion Mailed Nov. 17, 2014, in 8 pages. cited by applicant

Primary Examiner: Ditmer; Kathryn E

Attorney, Agent or Firm: VIA LLP

Background/Summary

INCORPORATION BY REFERENCE (1) The present application is a continuation application of U.S. patent application Ser. No. 17/303,588, filed Jun. 2, 2021, which is a continuation application of U.S. patent application Ser. No. 16/255,175, filed Jan. 23, 2019, now U.S. Pat. No. 11,052,218, which is a continuation application of U.S. patent application Ser. No. 14/914,510, filed Feb. 25, 2016, now U.S. Pat. No. 10,207,074, which is a national stage application under 35 U.S.C. § 371 (c) of PCT Application No. PCT/NZ2014/000177, filed Aug. 26, 2014, which is related to and claims priority to U.S. Provisional Patent Application No. 61/873,777, filed Sep. 4, 2013, the entireties of which are hereby incorporated by reference herein and made a part of the present disclosure.

BACKGROUND

Field

(1) The present disclosure relates to humidifiers for respiratory support systems. More particularly, the present disclosure relates to a float retention arrangement for a humidification chamber.

Description of Related Art

(2) In a humidification chamber, one or more floats regulate the level of water flowing into the chamber by controlling a fill valve. Float retention devices are used to hold the float(s) in a desired position post-manufacture to prevent or reduce occurrence of impact damage and fatigue to the components of the float valve mechanism during transport and storage. The float valve mechanism comprises floats, lift arms, valve diaphragms, and float hinges. Damage to any component of the float valve mechanism could result in an uncontrolled water level within the chamber, which is undesirable. Typically, the float retention device holds the float in a position corresponding to an open position of the water inlet valve.

(3) Prior art float retention devices, or float retainers, are often assembled onto the gas inlet and outlet ports, typically during manufacture. The float retainer is intended to be removed and discarded by the user at the point-of-use. The float retainer can incorporate port caps, which can provide a substantially airtight seal to inhibit or prevent ingress of foreign material into the inlet or outlet ports during transport and storage.

(4) As described above, typically, the water inlet valve is held open by the float retainer. Thus, the humidification chamber could overflow if the water spike, which provides water to the water inlet valve, is inserted into a water source before the float retainer is removed. In addition, the float retainer precludes factory pre-assembly of breathing tubes and adapters to the chamber because the float retainer obstructs the inlet and outlet ports until removed by the end user at the point-of-use.

SUMMARY

(5) The systems, methods and devices described herein have innovative aspects, no single one of which is indispensable or solely responsible for their desirable attributes. Without limiting the scope of the claims, some of the advantageous features will now be summarized.

(6) In some configurations, a humidification chamber comprises a cover defining an interior space. The cover comprises at least one gas port, a water inlet opening and a float retention opening. At least one float operates an inlet valve that controls a flow of water through the water inlet opening. A water supply conduit has a first end and a second end. The first end is connected to the water inlet opening. An adapter is connected to the second end of the water supply conduit and is configured, in use, to couple the water supply conduit to a source of water. The adapter is insertable into the float retention opening and is positionable to contact and retain the at least one float in a non-use position.

(7) In some configurations, the adapter is a water spike.

(8) In some configurations, the at least one float comprises a primary float and a secondary float.

(9) In some configurations, the at least one gas port comprises a gas inlet port and a gas outlet port.

(10) In some configurations, the water spike comprises a handle.

(11) In some configurations, a tip of the water spike contacts the at least one float.

(12) In some configurations, when the adapter is positioned in the float retention opening, the adapter does not obstruct the at least one gas port such that breathing tubes, adapters or other components can be coupled to the at least one gas port with the adapter positioned in the float retention opening.

(13) In some configurations, a humidification chamber comprises a cover defining an interior space. The cover comprises at least one gas port, a water inlet opening and a float retention opening. At least one float operates an inlet valve that controls a flow of water through the water inlet opening. A component forms at least a portion of a water supply conduit for supplying water from a water source to the water inlet opening. The component is insertable into the float retention opening and is positionable to contact and retain the at least one float in a non-use position.

(14) In some configurations, the at least one float comprises a primary float and a secondary float.

(15) In some configurations, the at least one gas port comprises a gas inlet port and a gas outlet port.

(16) In some configurations, a method of retaining a float of a humidification chamber comprises

inserting an adapter that is connected to a free end of a water supply conduit through a float retention opening in a cover of the humidification chamber until the adapter moves and retains the float in a non-use position, wherein an end of the water supply conduit opposite the free end is coupled to a water inlet of the humidification chamber.

(17) In some configurations, a method of using a humidification chamber comprises removing an adapter that is connected to a free end of a water supply conduit from a float retention opening in a cover of the humidification chamber to release a float from a non-use position, wherein an end of the water supply conduit opposite the free end is coupled to a water inlet of the humidification chamber.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Throughout the drawings, reference numbers can be reused to indicate general correspondence between reference elements. The drawings are provided to illustrate example embodiments described herein and are not intended to limit the scope of the disclosure.

(2) FIG. 1 is a perspective view of a humidification chamber having a float retention arrangement, which preferably comprises a water spike inserted into the chamber to retain the float(s) in a non-use (e.g., storage and/or shipping) position.

(3) FIG. 2 is a front view of the humidification chamber of FIG. 1 with the water spike removed to illustrate an access opening through which the water spike can be inserted.

(4) FIG. 3 is a side view of the water spike separate from the humidification chamber.

(5) FIG. 4 is a sectional view of the humidification chamber of FIG. 1 illustrating a dual valve arrangement and interaction between the water spike, the cover of the chamber and the floats.

(6) FIG. 5 is a perspective view of a humidification chamber having a float retention arrangement, such as the arrangement of FIGS. 1-4, illustrating that breathing tubes can be assembled with the float retention arrangement in use.

(7) FIG. 6 is a perspective view of a humidification chamber having a float retention arrangement, such as the arrangement of FIGS. 1-4, wherein the water spike omits the finger loop.

(8) FIG. 7 is a sectional view of a humidification chamber having a float retention arrangement, such as the arrangement of FIGS. 1-4, wherein the access opening includes a cover or seal element.

DETAILED DESCRIPTION

(9) In one or more embodiments of the present humidification chamber, a component of the humidification chamber is utilized as a float retainer in at least one mode of the humidification chamber, such as a storage or shipping mode, for example and without limitation. The component preferably is a component that has utility in connection with the use of the humidification chamber other than use as a float retainer. For example, in some configurations, the component used as a float retainer is or includes an adapter for connecting the humidification chamber to a source of water (e.g., a water spike). In at least some configurations, the water spike can be inserted through an access opening in the chamber cover, wherein the access opening is separate from the gas inlet port and the gas outlet port. The access opening can be separate from the water inlet. The humidification chamber can be of any suitable arrangement that includes one or more floats (or other movable components) that are desirably held in a particular position (e.g., open or a non-use position) under certain circumstances (e.g., during non-use, such as shipping or storage). An example of a humidification chamber is described below. Components or features of the humidification chamber not discussed in detail herein can be of any suitable construction, such as the same as or similar to corresponding components or features of the humidification chambers disclosed in Applicant's PCT Publication No. WO2013/162386, entitled USABILITY FEATURES FOR RESPIRATORY HUMIDIFICATION SYSTEM, and related U.S. priority application Nos.

61/639,632 and 61/785,733, the entireties of which are hereby incorporated by reference herein. However, other suitable arrangements can also be used.

(10) With reference to FIGS. **1-4**, the humidification chamber **100** generally comprises a housing defining an internal space, an inlet port **102** and an outlet port **104**, each of which communicate with the internal space of the humidification chamber **100**. In use, gases flow into the humidification chamber **100** via the inlet port **102**. The gases are humidified within the humidification chamber **100** and flow out of the humidification chamber **100** through the outlet port **104**.

(11) The humidification chamber **100** is configured to be installed on a heater plate of an associated humidifier, such that a base **106** of the humidification chamber **100** contacts the heater plate of the humidifier. The base **106** preferably comprises a metal with good thermal conductivity, such as aluminum or copper, for example and without limitation. The humidification chamber **100** is further configured to hold a volume of a liquid, such as water. In use, the liquid contacts the base **106**. The base **106** is heated by the heater plate, which causes at least some of liquid in the humidification chamber **100** to evaporate.

(12) A water reservoir, such as a water bag (not shown), supplies liquid water to the humidification chamber **100** through a water inlet **108** in use. As discussed, the humidification chamber **100** contains water in both liquid and vapor phases as a result of heat energy supplied through the heat transfer base **106** by the heater plate of the associated humidifier. Liquid water enters the humidification chamber **100** through the water inlet **108** and rises to a level dependent on the amount of water allowed to enter the humidification chamber **100** by a suitable control arrangement, such as one or more valves.

(13) In the illustrated arrangement, a dual valve arrangement **110** controls the entry of liquid water from the water reservoir or other water supply into the humidification chamber **100**. The illustrated dual valve arrangement **110** comprises a primary valve arrangement **112** (“primary valve **112**”) and a secondary valve arrangement **114** (“secondary valve **114**”). At least one of the primary valve **112** and the secondary valve **114** is controlled by a float. In the illustrated arrangement, the primary valve **112** is controlled by a primary float **116**, which can be at least partially constructed of an air or gas-filled, sealed or unsealed element or other buoyant structure which is able to rise and fall with the water level. In the illustrated arrangement, the primary float **116** includes a vent **116a** that opens on an upper surface of the float **116** at a position above the normal water line. The vent **116a** connects the interior of the primary float **116** with the air space within the humidification chamber **100** to avoid or reduce volume changes of the primary float **116** as a result of pressure or temperature changes within the humidification chamber **100**.

(14) Preferably, the secondary valve **114** is also controlled by a float, which is referred to herein as a secondary float **117**. The secondary float **117** can be at least partially constructed of an air or gas-filled, sealed or unsealed element or other buoyant structure in a manner similar to the primary float **116**. In the illustrated arrangement, the secondary float **117** does not include a vent. The larger volume compared to the primary float **116** and the secondary, back-up functionality of the secondary float **117** reduces or eliminates the advantages of a vent in the secondary float **117**. That is, the secondary float **117** generally operates only in the event of a malfunction of the primary float **116** to shut off the supply of water to the humidification chamber **100**. Thus, fine control of the secondary valve **117** is not necessarily required and changes in buoyancy due to volume changes can be tolerated. However, in some arrangements, a vent could be provided.

(15) In some configurations, one of the valves **112**, **114** is not controlled by a float, but is operated by an alternative arrangement. For example, the secondary valve **114** can be controlled by an alternative arrangement, such as a water level sensor and actuator arrangement, so that the usual secondary float can be omitted to provide additional useful volume within the humidification chamber **100** or space for other components or arrangements. In such configurations, the float retention arrangement can be modified accordingly from that illustrated herein.

(16) The illustrated first or primary float **116** includes a coupling arrangement, such as a coupling arm **118**, which is pivotally connected to support, such as a hinge bracket **120**, for movement about an axis of rotation of the primary float **116**. The hinge bracket **120** can be supported by any suitable portion of the humidification chamber body. For example, an upper portion of the hinge bracket **120** can be coupled (e.g., fastened, snap-fit or bonded) to the water inlet **108** portion of the humidification chamber body and, if desired, a lower portion of the hinge bracket **120** can rest against a side surface of the humidification chamber body. Thus, the primary float **116** rises and falls along with the water level within the humidification chamber **100**.

(17) The primary float **116** actuates the primary valve **112**. In particular, the primary float **116** moves a push rod **124**, which includes a first portion or lower end portion **128** pivotally coupled to the coupling arm **118** of the primary float **116** and a second portion or upper end portion **126**. The upper end portion **126** includes a valve body **130** that cooperates with a first valve seat **132** of the dual valve arrangement **110**. The valve body **130** and first valve seat **132** form a portion of the first or primary valve **112**. The valve body **130** can engage the first valve seat **132**, directly or indirectly, to close the primary valve **112** and create at least a substantial seal that inhibits or substantially prevents water from entering the humidification chamber **100** through the primary valve **112**. The valve body **130** can also be disengaged from the first valve seat **132** to open the primary valve **112** and permit entry of water into the humidification chamber **100**. The primary float **116**, coupling arm **118**, push rod **124** and first valve seat **132** are sized, proportioned, arranged or otherwise configured to close the primary valve **112** once a desirable water level within the humidification chamber **100** is reached and to open the primary valve **112** when the actual water level falls below the desirable water level thereby preferably maintaining the actual water level at or near the desirable water level.

(18) The secondary valve **114** operates in conjunction with the primary valve **112** as a redundant or failsafe arrangement. Preferably, the primary valve **112** controls the entry of water into the humidification chamber **100** under normal operating conditions. However, if the primary valve **112** should malfunction or, for whatever reason, the water level should rise above the desirable water level, the secondary valve **114** preferably closes to inhibit or stop water from entering the humidification chamber **100**. The secondary valve **114** can also open when the water level falls below the desirable water level to permit refill of water and continued use of the humidifier **107**.

(19) The secondary valve **114** includes a movable valve body assembly **134** that is movable between a closed position, in which a valve body element **136** directly or indirectly engages a second valve seat **138** of the secondary valve **114** to inhibit or stop water from entering the humidification chamber **100** through the secondary valve **114**, and an open position, in which the valve body element **136** does not engage or close the second valve seat **138** of the secondary valve **114** so that water is permitted to enter the humidification chamber **100** through the secondary valve **114**.

(20) In the illustrated arrangement, the valve body assembly **134** is pivotally connected to the hinge bracket **120** for movement about an axis of rotation. The illustrated valve body assembly **134** includes a base **142** and a retainer cap **144** that support a push tube **146** therebetween. The base **142** is rotatably supported by the hinge bracket **120**. The push tube **146** defines or carries the valve body element **136**. Preferably, the base **142** defines a hemispherical portion and the push tube **146** defines a complementary hemispherical portion that cooperate to form a ball-joint arrangement, which permits rotation of the push tube **146** relative to the base **142** about two axes of rotation. Accordingly, a desirable orientation of the push tube **146** can be maintained throughout a range of pivotal movement of the base **142**. In some configurations, the hemispherical portions can be cylindrical such that the base **142** and push tube **146** are movable about a single axis relative to one another. The retainer cap **144** can be secured to the base **142** by any suitable arrangement, such as a snap-fit arrangement, mechanical fasteners, adhesives or ultrasonic welding, for example and without limitation. Preferably, a space is provided between the retainer cap **144** and the push tube

146 such that the retainer cap **144** inhibits separation of the push tube **146** from the base **142**, while allowing for relatively free movement of the push tube **146** relative to the base **142**.

(21) In the illustrated arrangement, the push rod **124** is co-axial with the push tube **146**. The push rod **124** and push tube **146** are capable of moving freely and independently of one another. The end of the push rod **124** facing the water inlet **108** is tapered to a blunt point, which forms the valve body **130**. The valve body **130** of the push rod **124** and the valve body element **136** of the push tube **146** can be covered by a valve seal element, which can be a flexible sealing membrane. Such a valve seal element can be configured to fit snugly over the rim of the push tube **146**, thus coupling the push tube **146** to the push rod **124** in a floating connection. Thus, in such a configuration, the valve seal element can directly contact the first valve seat **132** and the second valve seat **138** when the respective valve is in a closed position. In addition, the valve seal element can prevent water from entering the humidification chamber **100** through the water inlet **108** when the secondary valve **114** is closed regardless of the position of the primary valve **112**. The valve seal element can be made of material that is supple but strong, for example, a medical grade silicone rubber material.

(22) As described above, water is supplied to the humidification chamber **100** from a water source by a supply tube arrangement comprising a supply tube **150**. One end of the supply tube **150** is coupled to the water inlet **108** and the other end of the supply tube **150** is coupled to an adapter for coupling the supply tube **150** to a source of water. The adapter can be in the form of a water spike **152**, for example. Preferably, the water spike **152** can also be used as a float retention device.

(23) In at least some configurations, the water spike **152** can be inserted through an access opening **154** in the humidification chamber **100**, such as in a chamber cover **156**, for example. The access opening **154** can be in the form of a slot and, in at least some configurations, can be located within a recess **158** defined by the cover **156**. The recess **158** positions the water spike **152** in close proximity with the floats **116**, **117**, so that the water spike **152** does not need to be excessively long in order to contact the floats **116**, **117**, while preserving the desired volume of the humidification chamber **100**. Accordingly, in at least some configurations, one or more dimensions (e.g., a width) of the recess **158** are selected to accommodate the water spike **152** without substantial additional space. For example, the width (or other dimension) of the recess **158** is preferably less than twice the width (or corresponding other dimension) of the water spike **152** and, in some configurations, is less than one and one-half times the width or less than one and one-quarter of the width.

(24) In some embodiments, a cover or seal element **200** (FIG. 7) covers the access opening **154**. In some embodiments, the seal element **200** comprises a flexible silicone membrane **202**. The flexible silicone membrane **202** can additionally provide a protective sheath for the spike **152** to prevent contamination and damage to either or both of the spike **152** and float(s) **116**, **117**. The cover or seal **200** could be another type of stretchable membrane or other displaceable structure that stretches or moves to accommodate insertion of the spike **152** through the access opening **154**. In some embodiments, the cover or seal **200** maintains a physical barrier around the spike **152** and between the spike **152** and the interior of the humidification chamber **100**. The membrane **202** (or displaceable structure) could include a reinforcing portion or member **204** that inhibits or prevents the spike **152** from puncturing the membrane **202** (or displaceable structure). In some configurations, the cover or seal **200** could be a self-sealing membrane or valve (e.g., duckbill valve) that permits the spike **152** to pass through into the chamber **100** and that seals or substantially seals the access opening **154** when the spike **152** is withdrawn. A separate member (e.g., a plug) could be provided to block, cover, or seal the access opening once the spike is removed. The separate member could be coupled to the chamber cover, such as near the access opening with a leash, lanyard, receptacle or other suitable arrangement.

(25) The access opening **154** can be positioned above a certain water level of the chamber **100** (e.g., a maximum or normal level) such that blocking, covering, or sealing of the access opening **154** is not necessary. Thus, in some configurations, the access opening **154** can be open to the atmosphere. However, in any arrangement regardless of the location of the access opening **154**, a

cover, block, or seal may be provided if desired.

(26) In some configurations, one or both of the inlet port **102** and the outlet port **104** of the chamber **100** are not obstructed by the float retention arrangement. Such an arrangement permits preassembly (such as during manufacture) or semi-permanent or permanent integration of breathing tubes **210**, adapters **212** or other components to the inlet port **102** and/or outlet port **104**, as illustrated in FIG. 5.

(27) In some configurations, the present float retention arrangement intrinsically inhibits or prevents water from being introduced into the chamber **100** while the float retention arrangement is in place. One purpose of the water spike **152** is to retain the float(s) **116**, **117** in the non-use position, but preferably the spike **152** is also the only path for water to pass to the inlet valve **108** through the supply tube or conduit **150** that extends between the inlet valve **108** and the water spike **152** (FIG. 1). Thus, in the illustrated arrangement there is no way for water to enter the chamber **100** through the inlet while the floats **116**, **117** are retained in the non-use position and, thus, the valve arrangement **110** is held open. Advantageously, with such an arrangement, water cannot be accidentally introduced into the humidification chamber **100** via the normal pathway of the supply tube **150** while the valve arrangement **110** controlling the water inlet **108** is held open by a float retention arrangement. Therefore, accidental overfilling of the humidification chamber **100** can be avoided.

(28) The water spike **152** can have any suitable structure to cooperate with a suitable water supply (e.g., water bag) and function as a float retention device. For example, the water spike **152** can include a grip portion, such as a handle or finger loop **160**, as shown in FIGS. 1-4. Alternatively, the water spike **152** can omit the handle or finger loop, as shown in the arrangement of FIG. 6. Such an arrangement can include a body of the water spike **152** that is sized and shaped or otherwise configured to facilitate gripping and removal of the water spike **152**. The water spike **152** comprises a passage or conduit **174** for water to move from a tip **172** of the water spike **152** to the supply tube **150**.

(29) The water spike **152** (or other retention component) can engage the float(s) **116**, **117** in any suitable manner. In some configurations, the tip **172** of the water spike **152** contacts one of the floats (e.g., the primary float). The water spike **152** can comprise a thin web portion **170** that extends through the access opening **154** and has a lower end portion that contacts one of the floats (e.g., the secondary float). FIG. 4 illustrates one example of possible water spike **152** contact positions with the floats **116**, **117** (i.e., the retention locations). In some configurations, the water spike **152** contacts both floats **116**, **117**. In the illustrated arrangement, the water spike **152** contacts the front portion of each float **116**, **117**, preferably at a location forward of an axis of the gas inlet port **102** and/or outlet port **104**, which can be forward of an entirety of the gas inlet port **102** and/or outlet port **104**.

(30) The primary float **116** can include a tab, arm **162** or other structure that extends away from (e.g., forwardly from) a main body of the float **116** and is contacted or otherwise engaged by the water spike **152**. Similarly, the secondary float **117** can include a tab **164**, arm or other structure that extends from (e.g., forwardly from) a main body of the float **117** that is contacted or otherwise engaged by the water spike **152**. In the illustrated arrangement, the primary float **116** includes an elongate arm **162** and the secondary float **117** includes a relatively small tab **164**; however, other suitable arrangements can be used, including the water spike **152** contacting a main body or buoyant portion of the floats **116**, **117**. In the illustrated arrangement, the water spike **152** retains one or both of the floats **116**, **117** in a downward position e.g., fully downward corresponding to a fully open position of the valves **112**, **114**.

(31) The water spike **152** can define surfaces **176**, **178** that contact and rest upon the cover **156** with the water spike **152** in position to contact the floats **116**, **117**. The surfaces **176**, **178** can be defined by a main body portion of the water spike **152**. The surfaces **176**, **178** can be positioned forward and rearward of the tip **172**. The surfaces **176**, **178** can be vertically offset from one

another. One of the surfaces **176** can be angled relative to an axis of the water spike **152**. One of the surfaces **178** can surround a portion of the web portion **170**.

(32) In the illustrated arrangement, the water spike **152** is located on a side of the chamber **100** opposite the water inlet **108**. Preferably, the water inlet **108** is located on one side of a line extending through the axes of the gas inlet port **102** and outlet port **104** and the water spike **152** is located on an opposite side of the line when engaged with the chamber **100** as a float retention device. In such a position, the water spike **152** can be diametrically opposed to the water inlet **108**. A line passing through both the water inlet **108** and the water spike **152** can be generally or substantially orthogonal to the line passing through the axes of the gas inlet port **102** and outlet port **104**.

(33) In at least some configurations, the inlet and outlet ports **102**, **104** are not covered by the float retention device, thereby allowing factory pre-assembly or integration/permanent assembly of breathing tubes, adapters or other components to the humidification chamber. In at least some configurations, the float retention device intrinsically prevents the flow of water into the chamber while floats are held down. In at least some configurations, the float retention device reduces occurrence of impact damage and fatigue to the components of the float valve mechanism during transport and/or storage. In some configurations, the float retention device provides an inherent protective sheath for the water spike.

(34) Unless the context clearly requires otherwise, throughout the description and the claims, the words “comprise”, “comprising”, and the like, are to be construed in an inclusive sense as opposed to an exclusive or exhaustive sense, that is to say, in the sense of “including, but not limited to”.

(35) Reference to any prior art, in this specification is not, and should not be taken as, an acknowledgement or any form of suggestion that prior art forms part of the common general knowledge in the field of endeavour in any country in the world.

(36) The invention may also be said broadly to consist in the parts, elements and features referred to or indicated in the specification of the application, individually or collectively, in any or all combinations of two or more of said parts, elements or features.

(37) Where, in the foregoing description reference has been made to integers or components having known equivalents thereof, those integers are herein incorporated as if individually set forth.

(38) It should be noted that various changes and modifications to the presently preferred embodiments described herein will be apparent to those skilled in the art. Such changes and modifications may be made without departing from the spirit and scope of the invention and without diminishing its attendant advantages. For instance, various components may be repositioned as desired. It is therefore intended that such changes and modifications be included within the scope of the invention. Moreover, not all of the features, aspects and advantages are necessarily required to practice the present invention. Accordingly, the scope of the present invention is intended to be defined only by the claims that follow.

Claims

1. A circuit kit for a respiratory humidification system comprising: a humidifier chamber having a cover defining an interior space, a gas inlet port, a gas outlet port, a water inlet opening, a seal element and a float retention opening; and a component, wherein the seal element is configured to stretch or move to accommodate insertion of the component through the float retention opening such that the component is positionable to engage and retain at least one float in a non-use position.
2. The circuit kit of claim 1, wherein the humidifier chamber comprises the at least one float, wherein the at least one float comprises a first float and a second float.
3. The circuit kit of claim 2, wherein at least one of the first float and the second float is configured to operate an inlet valve that is configured to control a flow of water through the water inlet opening.

4. The circuit kit of claim 2, wherein the component comprises an adapter for connecting the humidifier chamber to a water source.
 5. The circuit kit of claim 4, wherein the adapter is a water spike.
 6. The circuit kit of claim 5, wherein the seal element maintains a physical barrier between the water spike and an interior of the humidifier chamber.
 7. The circuit kit of claim 6, wherein the seal element comprises a membrane or a valve.
 8. The circuit kit of claim 7, wherein the seal element is self-sealing.
 9. The circuit kit of claim 6, wherein the seal element comprises a stretchable membrane configured to stretch to accommodate insertion of the water spike into the float retention opening.
 10. The circuit kit of claim 9, wherein the stretchable membrane comprises a reinforced portion configured to prevent the water spike from puncturing the stretchable membrane.
 11. The circuit kit of claim 5, wherein the seal element permits the water spike to pass through the float retention opening when inserted and substantially seals the float retention opening when the water spike is withdrawn.
 12. The circuit kit of claim 11, wherein, when the water spike is positioned in the float retention opening, the water spike does not obstruct at least one of the gas inlet port and the gas outlet port such that breathing tubes, adapters or other components can be coupled to the at least one of the gas inlet port and the gas outlet port with the water spike positioned in the float retention opening.
 13. The circuit kit of claim 5, wherein a portion of the water spike is positionable to engage at least one of the first float or the second float.
 14. The circuit kit of claim 2, wherein at least one of the first float and the second float comprises buoyant structure configured to rise and fall with a water level within the humidifier chamber.
 15. The circuit kit of claim 2, wherein at least one of the first float and the second float is coupled to humidification chamber.
 16. The circuit kit of claim 15, wherein the first float is coupled to the humidification chamber with a coupling arm configured to support movement about an axis for rotation of the first float.
 17. The circuit kit of claim 2, wherein the first float is coupled to the water inlet opening of the humidifier chamber.
 18. The circuit kit of claim 2, wherein the first float is configured to operate an inlet valve that controls a flow of water through the water inlet opening in use.
 19. The circuit kit of claim 1, wherein the component forms at least a portion of a water supply conduit for supplying water from a water source to the water inlet opening.
 20. The circuit kit of claim 1, wherein the circuit kit comprises an inspiratory breathing tube and a gas supply tube, wherein the circuit kit is preassembled with the inspiratory breathing tube coupled to the gas outlet port and the gas supply tube to the gas inlet port.
-