

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12413493
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Stalzer; Mark Edward et al.

Network connection automation

Abstract

A computing resource service provider receives a request from a customer to establish a physical connection between a provider network device and a customer network device in a colocation center. Once the connection has been established, the customer may transmit cryptographic authentication information, through the physical connection, to the provider network device. The provider network device transmits this information to an authentication service operated by the computing resource service provider to verify the authenticity of the information. If the information is authentic, the authentication service may re-configure the provider network device to allow the customer to access one or more services provided by the computing resource service provider. The authentication service may transmit cryptographic authentication information to the customer to verify the identity of the computing resource service provider.

Inventors: Stalzer; Mark Edward (Arlington, VA), Arllen; Christian Arthur (McLean, VA)

Applicant: Amazon Technologies, Inc. (Seattle, WA)

Family ID: 52690022

Assignee: Amazon Technologies, Inc. (Seattle, WA)

Appl. No.: 18/513547

Filed: November 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240089241 A1	Mar. 14, 2024

Related U.S. Application Data

continuation parent-doc US 17404126 20210817 US 11843589 child-doc US 18513547
continuation parent-doc US 15632166 20170623 US 11122022 20210914 child-doc US 17404126

Publication Classification

Int. Cl.: **H04L9/40** (20220101); **H04L41/046** (20220101); **H04L43/0811** (20220101); **H04L45/302** (20220101); **H04L67/14** (20220101); H04L12/14 (20060101); H04L41/0896 (20220101)

U.S. Cl.:

CPC **H04L43/0811** (20130101); **H04L9/40** (20220501); **H04L41/046** (20130101); **H04L45/306** (20130101); **H04L63/0428** (20130101); **H04L63/061** (20130101); **H04L63/08** (20130101); **H04L63/0853** (20130101); **H04L63/10** (20130101); **H04L67/14** (20130101); H04L12/1435 (20130101); H04L41/0896 (20130101); H04L63/0272 (20130101)

Field of Classification Search

CPC: H04L (63/061); H04L (9/40); H04L (41/046); H04L (43/0811); H04L (45/306); H04L (63/0428); H04L (63/08); H04L (63/0853); H04L (63/10); H04L (67/14); H04L (12/1435); H04L (41/0896); H04L (63/0272)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5361062	12/1993	Weiss et al.	N/A	N/A
5748629	12/1997	Caldara et al.	N/A	N/A
6198824	12/2000	Shambroom	N/A	N/A
6311218	12/2000	Jain et al.	N/A	N/A
6639919	12/2002	Kroninger et al.	N/A	N/A
6842628	12/2004	Arnold et al.	N/A	N/A
7039713	12/2005	Van Gunter et al.	N/A	N/A
7107312	12/2005	Hackbarth et al.	N/A	N/A
7254643	12/2006	Peters, Jr. et al.	N/A	N/A
7272643	12/2006	Sarkar et al.	N/A	N/A
7292577	12/2006	Ginipalli et al.	N/A	N/A
7327682	12/2007	Gandhi et al.	N/A	N/A
7359322	12/2007	Khurana et al.	N/A	N/A
7453825	12/2007	Sivasankaran	709/239	H04L 45/026
7577154	12/2008	Yung et al.	N/A	N/A
7734516	12/2009	Barnum et al.	N/A	N/A
7743001	12/2009	Vermeulen et al.	N/A	N/A
7890581	12/2010	Rao	709/204	H04W 4/21
7933230	12/2010	Sato	N/A	N/A
7970903	12/2010	Oeda	N/A	N/A
8239684	12/2011	Shima	713/185	H04L 63/123
8340107	12/2011	Luthra	370/401	H04L 49/20
8495199	12/2012	Miller et al.	N/A	N/A

8724642	12/2013	Miller et al.	N/A	N/A
8832039	12/2013	Sorenson, III et al.	N/A	N/A
8955055	12/2014	Bogdanovic et al.	N/A	N/A
8959203	12/2014	Miller et al.	N/A	N/A
9565212	12/2016	Faltyn et al.	N/A	N/A
2001/0022837	12/2000	Vasell et al.	N/A	N/A
2002/0009092	12/2001	Seaman et al.	N/A	N/A
2003/0074443	12/2002	Melaku et al.	N/A	N/A
2003/0190024	12/2002	Ju	379/142.01	H04M 15/56
2003/0236745	12/2002	Hartsell et al.	N/A	N/A
2004/0003287	12/2003	Zissimopoulos	726/10	H04L 63/0807
2004/0066769	12/2003	Ahmavaara et al.	N/A	N/A
2005/0063400	12/2004	Lum	N/A	N/A
2006/0089124	12/2005	Frank et al.	N/A	N/A
2007/0067424	12/2006	Raciborski et al.	N/A	N/A
2007/0135109	12/2006	Walter et al.	N/A	N/A
2007/0226490	12/2006	Odawara et al.	N/A	N/A
2007/0234054	12/2006	Robert et al.	N/A	N/A
2007/0256094	12/2006	Pugel	348/E7.05	H04N 7/106
2008/0028445	12/2007	Dubuc et al.	N/A	N/A
2008/0133716	12/2007	Rao	709/227	H04L 67/306
2008/0276085	12/2007	Davidson et al.	N/A	N/A
2008/0298374	12/2007	Rhoades et al.	N/A	N/A
2009/0070235	12/2008	Mehta et al.	N/A	N/A
2009/0106551	12/2008	Boren et al.	N/A	N/A
2009/0112735	12/2008	Viehmann et al.	N/A	N/A
2009/0192945	12/2008	Perpina et al.	N/A	N/A
2009/0216889	12/2008	Hadi	N/A	N/A
2009/0276771	12/2008	Nickolov et al.	N/A	N/A
2009/0300635	12/2008	Ferris	N/A	N/A
2010/0027552	12/2009	Hill	N/A	N/A
2010/0039959	12/2009	Gilmartin	N/A	N/A
2010/0046381	12/2009	Bajpay et al.	N/A	N/A
2010/0111093	12/2009	Satterlee et al.	N/A	N/A
2010/0122094	12/2009	Shima	N/A	N/A
2010/0125664	12/2009	Hadar et al.	N/A	N/A
2010/0131649	12/2009	Ferris	N/A	N/A
2010/0131948	12/2009	Ferris	N/A	N/A
2010/0177752	12/2009	Aggarwal	370/338	H04W 8/082
2010/0195540	12/2009	Kerr et al.	N/A	N/A
2010/0226254	12/2009	Kerr et al.	N/A	N/A
2010/0226280	12/2009	Burns et al.	N/A	N/A
2010/0278177	12/2009	Chase	370/389	H04L 12/413
2010/0280934	12/2009	Kerr et al.	N/A	N/A
2010/0306547	12/2009	Fallows et al.	N/A	N/A
2010/0319004	12/2009	Hudson et al.	N/A	N/A
2010/0332262	12/2009	Horvitz et al.	N/A	N/A
2011/0016028	12/2010	Toure et al.	N/A	N/A

2011/0022492	12/2010	Karaoguz	705/26.4	G06Q 30/0611
2011/0066752	12/2010	Lippincott et al.	N/A	N/A
2011/0078311	12/2010	Nakashima	N/A	N/A
2011/0107090	12/2010	Varadarajan et al.	N/A	N/A
2011/0131335	12/2010	Spaltro et al.	N/A	N/A
2011/0131647	12/2010	Sanders et al.	N/A	N/A
2011/0154212	12/2010	Gharpure et al.	N/A	N/A
2011/0179162	12/2010	Mayo et al.	N/A	N/A
2011/0231899	12/2010	Pulier et al.	N/A	N/A
2011/0310892	12/2010	DiMambro	N/A	N/A
2012/0066351	12/2011	Choi	709/219	H04L 65/80
2012/0130873	12/2011	Morgan	N/A	N/A
2012/0226998	12/2011	Friedl	715/760	H04L 65/1069
2012/0240204	12/2011	Bhatnagar et al.	N/A	N/A
2012/0291109	12/2011	Minamizawa	N/A	N/A
2013/0046976	12/2012	Rosati et al.	N/A	N/A
2013/0136138	12/2012	Miller	370/395.53	H04L 45/306
2013/0156093	12/2012	Vonog et al.	N/A	N/A
2013/0166709	12/2012	Doane et al.	N/A	N/A
2014/0068721	12/2013	Ong et al.	N/A	N/A
2014/0157298	12/2013	Murphy	N/A	N/A
2014/0230044	12/2013	Liu et al.	N/A	N/A
2014/0269496	12/2013	Mufti	N/A	N/A
2014/0279259	12/2013	Harman et al.	N/A	N/A
2014/0282922	12/2013	Iwanski et al.	N/A	N/A
2014/0282936	12/2013	Fitzgerald	709/221	H04L 41/0806
2015/0023207	12/2014	Lan et al.	N/A	N/A
2016/0344590	12/2015	Huey	N/A	H04Q 11/0071

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002108818	12/2001	JP	N/A
2004318582	12/2003	JP	N/A
2005333350	12/2004	JP	N/A
2013134530	12/2012	JP	N/A
2005032042	12/2004	WO	N/A
2013056585	12/2012	WO	N/A
2013081962	12/2012	WO	N/A

OTHER PUBLICATIONS

“Network Virtualization—Network Admission Control Deployment Guide” Cisco Systems, Inc., 2007, pp. 1-14. cited by applicant

Canadian Notice of Allowance, dated Jul. 10, 2019, for Patent Application No. 2,923,431, 1 page. cited by applicant

Canadian Office Action for Application No. 2,923,431 dated Oct. 24, 2017, 3 pages. cited by

applicant

Canadian Office Action, dated Oct. 22, 2018, for Patent Application No. 2,923,431, 5 pages. cited by applicant

Chinese First Office Action for Patent Application No. 201480050814.4, dated Apr. 3, 2018, 36 pages. cited by applicant

Chinese Notice on Grant of Patent for Application No. 201480050814.4 dated Feb. 11, 2019, 4 pages. cited by applicant

Cullen et al., "Automated Multi-Party Cloud Connectivity Provisioning," U.S. Appl. No. 13/555,360, filed Jul. 23, 2012. cited by applicant

Doane et al., "Interfaces to Manage Inter-Region Connectivity For Direct Network Peerings," U.S. Appl. No. 13/335,465, filed Dec. 22, 2011. cited by applicant

European Communication pursuant to Article 94(3) EPC for Patent Application No. 14845785.6 dated Aug. 15, 2018, 7 pages. cited by applicant

European Communication to Article 94(3) EPC for Patent Application No. 19204080.6 dated Apr. 5, 2023, 8 pages. cited by applicant

European Communication to Article 94(3) EPC for Patent Application No. 19204080.6 dated Feb. 9, 2021, 5 pages. cited by applicant

European Communication to Article 94(3) EPC for Patent Application No. 19204080.6 dated Mar. 2, 2022, 9 pages. cited by applicant

European Extended Search Report for Patent Application No. 19204080.6 dated Apr. 17, 2020, 9 pages. cited by applicant

Furr et al., "Differential Bandwidth Metering for Networks with Direct Peerings," U.S. Appl. No. 13/330,449, filed Dec. 19, 2011. cited by applicant

India First Examination Report for Patent Application No. 201617008292 dated Nov. 22, 2019, 6 pages. cited by applicant

International Search Report and Written Opinion in International Application No. PCT/US2012/066517 mailed Feb. 5, 2013, 12 pages. cited by applicant

International Search Report and Written Opinion mailed Dec. 22, 2014, International Patent Application No. PCT/US2014/055874, filed Sep. 16, 2014. cited by applicant

Japanese Appeal Decision for Patent Application No. 2018-020880 dated Jan. 4, 2021, 52 pages. cited by applicant

Japanese Decision to Grant for Patent Application No. 2016-542872 dated Jan. 14, 2020, 3 pages. cited by applicant

Japanese Final Office Action for Application No. 2016-542872 dated Nov. 20, 2017, 5 pages. cited by applicant

Japanese Final Office Action for Patent Application No. 2020-000160 dated Mar. 18, 2022, 8 pages. cited by applicant

Japanese Final Rejection dated Jul. 23, 2018, for Patent Application No. 2016-542872, 5 pages. cited by applicant

Japanese Final Rejection for Patent Application No. 2018-020880 dated Sep. 2, 2019, 4 pages. cited by applicant

Japanese First Office Action for Patent Application No. 2018-020880 dated Feb. 4, 2019, 9 pages. cited by applicant

Japanese Office Action for Patent Application No. 2016-542872 dated Aug. 26, 2019, 3 pages. cited by applicant

Japanese Office Action for Patent Application No. 2020-000160 dated Apr. 23, 2021, 10 pages. cited by applicant

Miller et al., "Dynamic Bandwidth Management Using Routing Signals in Networks With Direct Peerings," U.S. Appl. No. 13/330,438, filed Dec. 19, 2011. cited by applicant

Miller et al., "Interfaces to Manage Direct Network Peerings," U.S. Appl. No. 13/306,775, filed

Nov. 29, 2011. cited by applicant
Miller et al., “Interfaces To Manage Service Marketplaces Accessible Via Direct Network Peerings,” U.S. Appl. No. 13/335,490, filed Dec. 22, 2011. cited by applicant
Miller, et al., “Interfaces To Manage Last-Mile Connectivity For Direct Network Peerings,” U.S. Appl. No. 13/306,801, filed Nov. 29, 2011. cited by applicant
Rekhter et al., “A Border Gateway Protocol 4 (BGP-4),” Standards Track, The Internet Engineering Task Force (IETF), Jan. 2006, The Internet Society (2006), 105 pages, retrieved from the Internet: <http://tools.ietf.org/pdf/rfc4271.pdf>. cited by applicant
Singapore Notice of Allowance for Patent Application No. 1120161797T dated Dec. 3, 2018, 4 pages. cited by applicant
Wikipedia, “Public key-cryptography,” Oct. 28, 2011, from http://en.wikipedia.org/w/index.php?title=Public-key_cryptography&oldid==457792582 retrieved on Jan. 18, 2013. cited by applicant
European Patent Office Notice of Allowance dated Jul. 26, 2024, Application No. 19204080.6, 64 pages. cited by applicant

Primary Examiner: Jamshidi; Ghodrat

Attorney, Agent or Firm: Davis Wright Tremaine LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to and is a continuation of U.S. patent application Ser. No. 17/404,126, filed Aug. 17, 2021, entitled “NETWORK CONNECTION AUTOMATION,” which is a continuation of U.S. patent application Ser. No. 15/632,166, filed Jun. 23, 2017, now U.S. Pat. No. 11,122,022, entitled “NETWORK CONNECTION AUTOMATION,” which is a continuation of U.S. patent application Ser. No. 14/029,496, filed Sep. 17, 2013, now U.S. Pat. No. 9,692,732, entitled “NETWORK CONNECTION AUTOMATION,” the disclosures of which are incorporated herein by reference in their entirety. This application also relates to and incorporates by reference in its entirety the full disclosure of U.S. patent application Ser. No. 13/306,775, filed Nov. 29, 2011, now U.S. Pat. No. 8,724,642, entitled “INTERFACES TO MANAGE DIRECT NETWORK PEERINGS.”

BACKGROUND

(1) Computing resource service providers and other service providers often grant users access to their services through the use of dedicated network connections. Many users, for example, utilize a colocation environment to connect directly with the computing resource service provider in order to access one or more services. Despite their many advantages, creating a dedicated and secure connection between the computing resource service provider and a customer may not be free of all risks. For example, despite their best efforts to avoid it, even a physical, dedicated connection may have points of susceptibility (e.g., at patch panels) where unauthorized and/or unintentional access to communications is possible. Currently, computing resource service providers may use conventional authentication methods to ensure that the connection is secure. However, conventional authentication methods often rely on manual intervention and are inherently inflexible. Additionally, the cryptographic techniques used to secure the connection may have vulnerabilities exploitable to gain unauthorized access to the connection. Adequately addressing these risks presents additional costs to the organizations that rely on the dedicated connection and to the computing resource service provider.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Various embodiments in accordance with the present disclosure will be described with reference to the drawings, in which:
- (2) FIG. 1 shows an illustrative example of an environment in which various embodiments can be practiced;
- (3) FIG. 2 shows an illustrative example of an environment in which various embodiments can be practiced;
- (4) FIG. 3 shows an illustrative example of one or more services provided by a computing resource service provider in accordance with at least one embodiment;
- (5) FIG. 4 shows an illustrative example of an environment in which various embodiments can be practiced;
- (6) FIG. 5 shows an illustrative example of an environment in which a physical connection is authenticated in accordance with at least one embodiment;
- (7) FIG. 6 shows an illustrative example of an environment in which a connection with one or more services is managed upon initial authentication in accordance with at least one embodiment;
- (8) FIG. 7 shows an illustrative example of a process for establishing a physical connection between a customer and a computing resource service provider in accordance with at least one embodiment;
- (9) FIG. 8 shows an illustrative example of a process for authenticating a connection for the first time in accordance with at least one embodiment;
- (10) FIG. 9 shows an illustrative example of a process for authenticating a connection after a connection has been previously established in accordance with at least one embodiment;
- (11) FIG. 10 shows an illustrative example of a process for authenticating a connection in accordance with at least one embodiment; and
- (12) FIG. 11 illustrates an environment in which various embodiments can be implemented.

DETAILED DESCRIPTION

- (13) In the following description, various embodiments will be described. For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the embodiments. However, it will also be apparent to one skilled in the art that the embodiments may be practiced without the specific details. Furthermore, well-known features may be omitted or simplified in order not to obscure the embodiment being described.
- (14) Techniques described and suggested herein relate to the authentication of a connection between a customer (e.g., a network operated by the customer) and a computing resource service provider. In an embodiment, a computing resource service provider may receive a request from an entity (e.g., an organization) to establish a direct connection between the entity and the computing resource service provider. The entity may be a customer of the computing resource service provider who may operate various services, such as data storage services, virtual computing system services and/or database services. For optimal usage of one or more of the services, the computing resource service provider may allow customers to communicate with the computing resource service provider's network using direct connections, i.e., physical communications connections that connect customer computing resources to computing resource service provider computing resources. Example techniques for establishing such connections are described in U.S. patent application Ser. No. 13/306,775, filed on Nov. 29, 2011, entitled "INTERFACES TO MANAGE DIRECT NETWORK PEERINGS," which is incorporated herein by reference in its entirety for all purposes.
- (15) Prior to installation of the connection between the computing resource service provider and the customer, the computing resource service provider may generate a letter of authority in order to

allow an employee of the computing resource service provider (e.g., a data technician) to connect physical routers associated with the customer and the computing resource service provider. This letter of authority may be generated in response to the received request from a customer to establish a direct connection with the computing resource service provider.

(16) In various embodiments, the computing resource service provider may transmit one or more signals to the customer router upon connection to initiate network connectivity between the customer and the computing resource service provider. These one or more signals may additionally include an authentication request in order to verify that the connection has been established correctly and that the customer is the correct entity authorized to connect to the computing resource service provider. The customer may transmit one or more signals in response to computing resource service provider in order to verify that the customer is authorized to access the computing resource service provider computer systems. These one or more signals may include a digital signature generated using one or more authentication credentials, such as a secret cryptographic key, originating from one or more customer computer systems. This signature may be generated using a symmetric cryptographic algorithm and/or an asymmetric cryptographic algorithm. The computing resource service provider may transmit the customer signals (or information based at least in part thereon) to an authentication service in order to determine whether the signature received from the customer is authentic and corresponds to this customer. If the customer signals are not authenticated, the computing resource service provider may deny access to its various services. Otherwise, the customer may be granted access to the one or more services that the customer has opted to use.

(17) In an embodiment, the computing resource service provider may transmit one or more authentication requests to the customer over time after the initial connection to ensure the connection has not been compromised. The customer may transmit a response to the request, which may comprise a digital signature generated using a hash function and a cryptographic key to the computing resource service provider to provide evidence that the customer is authorized to maintain the connection. Accordingly, if the signature is verified, such as through the authentication service, the computing resource service provider may allow the connection to continue. However, if the authentication service is unable to verify that the customer has the authority to access the services provided by the computing resource service provider, the computing resource service provider may limit the customer's access to the services until the customer is able to provide a valid digital signature to the computing resource service provider.

(18) In an embodiment, the customer transmits an authentication request to the computing resource service provider, such as through an appropriately configured API call to the service, to verify that the connection is currently between the customer and the computing resource service provider. If the signal received from the computing resource service provider is not authentic (e.g., does not include a valid digital signature on behalf of the computing resource service provider), the customer may limit or even terminate the connection with the computing resource service provider. Otherwise, the customer may continue his/her access to the various services provided by the computing resource service provider provided the customer may reciprocally provide authentication credentials to the computing resource service provider when requested.

(19) In some embodiments, the customer may transmit an authentication request to the computing resource service provider, such as through an appropriately configured API call to the service, to cause the authentication service to verify that the customer communications are truly originating from a customer computer system. This authentication request transmitted by the customer may include a digital signature which may be used by the computing resource service provider to verify the customer's identity. If the digital signature is authentic, the computing resource service provider may transmit one or more signals comprising a digital signature for the computing resource service provider to the customer. Accordingly, the customer may use this digital signature to verify the identity of the computing resource service provider.

(20) In this manner, the computing resource service provider and its customers may be connected through one or more physical routers and ensure that the connection is limited or terminated in the event of a failure to authenticate the customer or computing resource service provider signals. In addition, the techniques described herein facilitate additional technical advantages. For example, because, in some embodiments, the authentication processes are performed by computer systems managed by either the computing resource service provider or the customer, manual intervention may not be required to authenticate the connection. Accordingly, these techniques may increase the flexibility available to the computing resource service provider and its customers in ensuring a secure connection. Additionally, the use of an alternative authentication process may eliminate the use of the conventional router-to-router authentication techniques, potentially eliminating or mitigating any vulnerability that may be inherent in the conventional techniques. Additional uses are also enabled by the various techniques described herein.

(21) FIG. 1 shows an illustrative example of an environment **100** in which various embodiments may be practiced. In the environment **100**, a computing resource service provider **102** provides various computing resource services to customers of the computing resource service provider. The computing resource service provider **102** may be an organization that hosts various computing resources on behalf of one or more customers. For example, a computing resource service provider may operate one or more facilities that are used to host various computing hardware resources, such as hardware servers, data storage devices, network devices, and other equipment, such as server racks, networking cables, and the like. The computing resource hardware may utilize its computing hardware resources to operate one or more services. Such services may include services that enable customers of the computing resource service provider to remotely manage computing resources to support the customers' operations while reducing or even eliminating the need of the customers to invest in physical equipment. Example services include, but are not limited to, various data storage services (object-based data storage services, archival data storage services, database services, and the like), program execution services and other services. The services may be used by customers to support a wide variety of activities, such as operating a website, operating enterprise systems supporting an organization, distributed computation and/or other activities.

(22) Accordingly, as illustrated in FIG. 1, the environment **100** includes a customer **104**. The customer **104** may be an organization that utilizes some or all of the various services at least in part by establishing a direct connection with the computing resource service provider **102**. The customer **104** of the computing resource service provider **102** may utilize various services provided by the computing resource service provider **102**. For example, the customer **104** may utilize the services provided by the computing resource service provider **102** through automated processes, such as batch requests made to a service or customer server requests that require access to the service to support a customer operation. The customer **104** may contact the computing resource service provider **102** to request the installation of a direct connection to the computing resource service provider. The computing resource service provider may generate a letter of authority and either deploy a data technician or allow the customer **102** to use its own data technician or third party to connect a customer router and a computing resource service provider router **106**. The routers may be located in a data center or colocation which, in turn, may be located in a remote location. While routers are used extensively throughout the present disclosure for the purpose of illustration, the techniques illustrated in the present disclosure may additionally apply generally to other network devices (e.g., gateway devices, etc.).

(23) Once the connection between the customer **104** and the computing resource service provider router **106** has been established, the computing resource service provider router may initiate transmission of one or more signals to the customer router. One such signal may include an authentication request in order to verify that the customer **104** is authorized to connect to the computing resource service provider **102**. This authentication request may originate in an authentication service **108**, maintained and operated by the computing resource service provider

102. The authentication service **108** may be configured to obtain customer information from an account service (not shown) in order to obtain a cryptographic key which may be necessary to hash the received customer data to generate an expected customer digital signature. This expected customer digital signature may be compared to the received customer digital signature to verify the customer's identity. Additionally, the authentication service **108** may be configured to transmit executable commands to the computing resource service provider router **106** to transmit the authentication request to the customer **104**.

(24) In response to the authentication request, the customer **104** may provide one or more data packets comprising a digital signature along with additional data (e.g., customer identification number, port number, etc.) to the computing resource service provider **102** through one or more signals transmitted to the computing resource service provider router **106**. Accordingly, the router **106** may transmit these data packets to the authentication service **108** for validation. The authentication service **108** may be configured to hash the additional data received from the customer **104**, along with a cryptographic key to generate an expected customer digital signature. If the digital signatures match, the authentication service **108** may reconfigure the computing resource service provider router **106** to enable the customer to access one or more other services **110** provided by the computing resource service provider **102**. These other services **110** may include various data storage services (object-based data storage services, archival data storage services, database services, and the like), program execution services, and the like. However, if the digital signature received from the customer **104** does not match the expected digital signature, the authentication service **108** may deny access to the other services **110**.

(25) Alternatively, the customer **104** may initiate the authentication process, such as through an appropriately configured API call to the service, by transmitting one or more data packets to the computing resource service provider router **106**. These data packets may include a digital signature generated using a secret key which, when processed by the computing resource service provider **102**, causes the service provider to hash the received data, along with a cryptographic key, to generate an expected customer digital signature which may be used to determine whether the received digital signature is authentic. Additionally, these data packets may cause the service provider **102** to generate one or more data packets comprising its own digital signature which may be used by the customer **104** to verify the identity of the computing resource service provider. In this fashion, both the customer **104** and the computing resource service provider **102** may verify the authenticity of the signals transmitted through the direct physical connection.

(26) Once the customer **104** has attained access to the one or more other services **110**, the computing resource service provider **102** may use the authentication service **108** to transmit one or more authentication requests to the customer to ensure that the connection has not been compromised. If there is an indication that the connection may have been compromised (e.g., the authentication credentials received from the customer **104** do not match the expected values), the computing resource service provider **102**, through the authentication service **108**, may perform one or more actions with regard to the existing connection. For instance, the computing resource service provider **102** may configure the authentication service **108** to transmit one or more executable instructions to the router **106** to limit the connection. This may include throttling the available network bandwidth to the customer **104** or disabling access to the other services **110**. In another instance, the authentication service **108** may refer to the account service (not shown) to apply one or more restrictions to the connection in accordance with customer **104** specifications. For instance, the customer **104** may have specified during the initial request for a direct connection to the computing resource service provider **102** that certain actions are to be taken if the connection is compromised. The computing resource service provider **102** may restore the connection if the customer **104** at a later point provides valid authentication credentials to the computing resource service provider.

(27) As noted above, the physical connection between a customer router and a computing resource

service provider router may be made at a data center or colocation that may be located at a remote location. Accordingly, FIG. 2 is an illustrative example of an environment in which various embodiments can be practiced. In the environment **200**, direct connections may have been established between one or more customers **202** and a computing resource service provider **212**. As noted above, a customer **202** may contact the computing resource service provider **212** to request the installation of a direct connection to the computing resource service provider. Accordingly, the computing resource service provider **212** may deploy a data technician to establish a physical connection between a customer router **206** and a computing resource service provider router **210**. The routers **206**, **210** may be located in a data center or colocation **204** which, in turn, may be located in a remote location.

(28) In this illustrative example, the direct connection between one or more customers **202** and the computing resource service provider **212** may be established by installing cables between the customer routers **206** and a computing resource service provider router **210**. The routers **206**, **210** illustrated in FIG. 2 may comprise a variety of ports configured to allow users to transmit data to a recipient or receive data from a source. For instance, in embodiments where the customer and provider connect using fiber optic cables, a router **206**, **210** may comprise a number of transmission ports and a number of receiving ports. Thus, the connection between a customer router **206** and the computing resource service provider router **210** may include a plurality of cables that, when connected to the routers, enable a customer **202** and the computing resource service provider **212** to transmit and receive data.

(29) Depending on the configuration of the colocation **204**, a direct physical connection (or simply “physical connection”) between a customer router **206** and a computing resource service provider router **210** may include one or more patch panels **208** or other intervening structures (e.g., non-routing devices, couplers, etc.). For instance, the one or more patch panels **208** may enable a colocation **204** operator to use shorter lengths of cable to connect two or more devices, such as the customer routers **206** and the computing resource service provider router **210**. Additionally, the patch panels **208** may be used to simplify the identification of the ports used to establish the connection as the input/output ports may be labeled accordingly from the patch panels **208**. In other words, embodiments of the present disclosure are not limited to those in which a contiguous cable connects the customer and provider routers. Once the physical connection has been established from the customer routers **206** to the computing resource service provider router **210** in the colocation **204**, the computing resource service provider **212** may begin transmitting one or more signals through the computing resource service provider router to the customer routers. The customer router **206**, upon receiving the one or more signals from the computing resource service provider **212**, may transmit the one or more signals to the customer **202** for processing. As noted above, the one or more signals may include an authentication request which may cause the computer systems operated by a customer **202** to transmit a response comprising authentication proof. The authentication proof may include a digital signature or other account credential necessary to establish the identity of the customer **202**. While the use of digital signatures for authentication is used extensively throughout the present disclosure for the purpose of illustration, other authentication methods may be used. For instance, the authentication request sent by a computing resource service provider **212** may include executable instructions that may cause a customer graphical user interface to appear on a customer **202** computer system with a prompt for a password. Thus, a customer **202** may be required to type in a password in the prompt in order to authenticate the connection.

(30) Once the connection has been authenticated, the computing resource service provider **212**, through an authentication service, may re-configure the computing resource service provider router **210** to allow communications between a customer **202** and one or more services provided by the computing resource service provider. At a later time, the computing resource service provider **212** may transmit one or more signals through its router **210** to a customer **202** to verify that the

connection has not been compromised. If the customer **202** is unable to provide adequate authentication proof (e.g., invalid credential, invalid digital signature, incorrect Internet protocol (IP) address, checksum mismatch, etc.) to the computing resource service provider **212**, the computing resource service provider, through the authentication service, may once again re-configure the computing resource service provider router **210** to limit the customer's **202** access to the one or more services.

(31) At the same time, the customer **202** may transmit, through the customer router **206** one or more signals to the computing resource service provider **212** to verify that the connection has not been compromised. If the computing resource service provider **212** is unable to provide adequate authentication proof, the customer **202**, through one or more computer systems operated by the customer, may transmit an executable command to the customer router **206** to limit or even terminate the existing connection.

(32) As noted above, the computing resource service provider may provide a number of services which a customer may use to support its business operations. Accordingly, FIG. 3 is an illustrative example of one or more services provided by a computing resource service provider **302** in accordance with at least one embodiment. In this illustrative example, the computing resource service provider **302** provides at least five types of services. The services provided by the computing resource service provider **302**, in this example, include a virtual computer system service **304**, an object-based data storage service **306**, a database service **308**, an account service **310**, an authentication service **312** and one or more other services **314**, although not all embodiments of the present disclosure will include all such services and additional services may be provided in addition to or as an alternative to services explicitly described herein.

(33) The virtual computer system service **304** may be a collection of computing resources configured to instantiate virtual machine instances onto virtual computing systems on behalf of the customers of the computing resource service provider **302**. Customers of the computing resource service provider **302** may interact with the virtual computer systems' service to provision and operate virtual computer systems that are instantiated on physical computing devices hosted and operated by the computing resource service provider **302**. The virtual computer systems may be used for various purposes, such as to operate as servers supporting a website. Other applications for the virtual computer systems may be to support database applications, electronic commerce applications, business applications and/or other applications.

(34) The object-based data storage service **306** may comprise a collection of computing resources that collectively operate to store data for a customer. The data stored in the object-based data storage service **306** may be organized into data objects. The data objects may have arbitrary sizes except, perhaps, for certain constraints on size. Thus, the object-based data storage service **306** may store numerous data objects of varying sizes. The object-based data storage service **306** may operate as a key value store that associates data objects with identifiers of the data objects which may be used by the customer to retrieve or perform other operations in connection with the data objects stored by the data storage service **306**. Access to the data storage service may be through appropriately configured API calls.

(35) The database service **308** may be a collection of computing resources that collectively operate to run one or more databases for one or more customers. Customers of the computing resource service provider **302** may operate and manage a database from the database service **308** by utilizing appropriately configured API calls. This, in turn, may allow a customer to maintain and potentially scale the operations in the database.

(36) The account service **310** may be a collection of computing resources that collectively operate to maintain customer account information for each customer of the computing resource service provider **302**. The account service **310** may include, for example, the customer name, address, phone numbers, billing details and other personal identification information for each customer of the computing resource service provider **302**. Additionally, the account service **310** may include

cryptographic keys or other credentials that may be used to verify that a customer has the proper authorization to access the one or more services provided by the computing resource service provider **302**. Accordingly, the account service **310** may be configured to operate in conjunction with the authentication service **312** to enable customer connections and limit access to the one or more services provided by the computing resource service provider **302** should the customer fail to provide adequate authentication proof (e.g., digital signature, password, etc.). The customer may be able to interact with the account service **310** through one or more communications networks, such as the Internet, in order to provide and update the account information as necessary. Accordingly, the customer may access the account service **310** to perform a key exchange to ensure both the customer and the computing resource service provider **302** have a copy of the cryptographic keys necessary to validate a physical connection.

(37) The authentication service **312**, as noted above, may serve to authenticate and verify a connection between the computing resource service provider **302** and a customer. For instance, after a direct connection has been established between a customer and the computing resource service provider **302** (e.g., for example, through the use of routers located in a colocation, as illustrated in FIG. 2), the authentication service **312** may transmit an authentication request to the customer in order to ensure that the customer has authorization to access the one or more services provided by the computing resource service provider. Accordingly, the authentication service **312** may be configured to receive authentication proof from the customer and perform one or more operations to determine whether the authentication proof provided is authentic. For instance, the authentication service **312** may interact with the account service **310** to obtain necessary customer information for verifying the provided authentication proof (e.g., one or more cryptographic keys, passwords, customer identification numbers, etc.). If the authentication proof is not adequate, the authentication service **312** may transmit one or more executable commands to the computing resource service provider **302** router to limit customer access to the one or more services until the customer is able to provide adequate authentication proof. The authentication service **312** may be configured to perform this authentication process at different times to ensure that a connection between the customer and the computing resource service provider **302** is not compromised.

(38) The authentication service **312** may additionally be configured to respond to an authentication request transmitted by a customer to the computing resource service provider **302**. For instance, after a direct connection has been established between a customer and the computing resource service provider **302**, the customer may transmit an authentication request to the computing resource service provider in order to verify that the connection is authentic and has not been compromised. The authentication service **312** may process the request and provide authentication proof necessary to verify that the connection is authentic. For example, the authentication service **312** may be configured to access the account service **310** to locate the account information related to the customer and identify the type of authentication proof required to authenticate the connection. In this fashion, the authentication service **312** may provide added security to the connection between a customer and the computing resource service provider **302**.

(39) The computing resource service provider **302** may additionally maintain one or more other services **314** based on the needs of its customers. For instance, the computing resource service provider **302** may maintain a block-level data storage service which may comprise a collection of computing resources that collectively operate to store data for a customer by utilizing block-level data storage volumes. The storage volumes may be configured to behave like raw, unformatted block storage devices with a block level customer interface. Accordingly, a customer, through properly configured API calls to the service, may create a file system on top of the block-level data storage volumes or utilize the volume as a block-level storage device (e.g., a hard drive). Other services include, but are not limited to, object-level archival data storage services, services that manage other services and/or other services.

(40) As noted above, the computing resource service provider may utilize an authentication service

to authenticate a direct, physical connection between a customer and the computing resource service provider. However, the use of the authentication service to authenticate a connection may be used for other types of connections. Accordingly, FIG. 4 is an illustrative example of an environment **400** in which various embodiments can be practiced. In the environment **400**, a customer may utilize a customer gateway device **402** to communicate with the computing resource service provider **408** through one or more communications networks **404**, such as the Internet. While the Internet is used extensively throughout the present disclosure for the purpose of illustration, the present disclosure is not so limited. For instance, the gateway device **402** may be used to communicate with the computing resource service provider **408** through a local area network (LAN), intranet, extranet, a wireless network and any combination thereof.

(41) The customer gateway device **402** may be any device configured to act as an entrance, or “gateway,” to a network **404**. The customer gateway **402** may be configured to convert data originating in a customer computer system into data packets that may be transmitted over the network **404** to an intended recipient (e.g., in this case, the computing resource service provider **408**). Additionally, the customer gateway device **402** may be configured to receive any data packets transmitted through the network **404** and to convert these data packets into data that is readable by a customer computer system. For example, if the customer gateway device **402** is connected to the computing resource service provider **408** through the Internet, the customer gateway device **402** may be configured to use a suite of communications protocols, such as the Transmission Control Protocol/Internet Protocol (TCP/IP), to transmit data packets to the computing resource service provider **408**. The IP component may provide routing from the customer computer system to the computing resource service provider **408** through the Internet. This may be accomplished through the use of IP addresses (e.g., IPv4 or IPv6 addresses) that may correspond to the customer computer system and the computing resource service provider **408** systems. The TCP component may be responsible for verifying the correct delivery of data from the customer to the computing resource service provider **408**.

(42) The customer computer systems and the computing resource service provider **408** computing systems may additionally use an additional network protocol to identify the most efficient or expedient pathway for routing data packets. For instance, the various computer systems may utilize a border gateway protocol (BGP) in order to exchange routing information in the network **404**. The customer computer systems and computing resource service provider computer systems may use BGP to determine the available gateway devices (e.g., routers) available to transmit and receive data packets sent over the network **404** (e.g., Internet). Thus the computer systems using BGP may rely on TCP/IP in order to transmit the data packets through the various routers connected to the computer systems and that support the network **404**.

(43) The protocol used to connect the customer gateway device **402** to the computing resource service provider **408** through the network **404** may include a security protocol necessary to verify that the customer and computing resource service provider are authorized to participate in the secure connection **406**. The secure connection **406** may be a virtual private network (VPN) operated through one or more secure tunnels (e.g., Internet Protocol Security (IPsec) tunnels using one or more encryption methods). Thus, when the initial connection is made between the customer and the computing resource service provider **408** through the network **404** using this security protocol, the computing resource service provider may transmit an authentication request to the customer to determine whether the customer has the authority to participate in this secure connection **406**. Accordingly, the customer, through the customer gateway device **402**, may transmit a data packet comprising the IP address of an authentication service provided by the computing resource service provider **408** and authentication proof (e.g., password, digital signature, etc.) subject to the security protocol.

(44) Once the authentication service provided by the computing resource service provider **408** receives the data packet from the customer gateway device **402**, the authentication credential

received may utilize a hash function to hash the received data, along with a cryptographic key associated with the customer, to generate an expected customer digital signature. Accordingly, the computing resource service provider **408** may compare this expected customer digital signature to the digital signature received from the customer gateway device **402** to determine if these signatures match. If there is a match, the computing resource service provider **408** may re-configure its own gateway devices to permit the customer to access one or more other services provided by the computing resource service provider. However, if digital signatures do not match, any data packets transmitted to the one or more other services may be denied. Additionally, the customer may use the customer gateway device **402** to transmit an authentication request to the computing resource service provider **408**. Accordingly, the computing resource service provider **408** may transmit a data packet comprising the IP address of the customer computing system and an authentication credential (e.g., digital signature, password, etc.) subject to the security protocol. If the authentication credential received is inadequate, the customer may transmit one or more executable commands to the customer gateway device **402** to limit or terminate the secure connection **406** to the computing resource service provider **408**.

(45) FIG. 5 is an illustrative example of an environment **500** in which a physical connection is authenticated in accordance with at least one embodiment. In the environment **500**, a customer may submit a request to a computing resource service provider **504** to establish a direct connection with the computing resource service provider. Accordingly, the computing resource service provider **504** may generate a letter of authority to physically connect a customer router **502** to a computing resource service provider router **506**. A data technician may be deployed to establish the physical connection, as illustrated in FIG. 2.

(46) Once the physical connection has been established between the customer router **502** and the computing resource service provider router **506**, the computing resource service provider **504** may utilize an authentication service **508** to verify that the customer transmissions through the physical connection originate from the authorized customer. Accordingly, the authentication service **508** may be configured to transmit an authentication request through the computing resource service provider router **506**. The computing resource service provider router **506** may be configured to transmit this authentication request using a security protocol, as described above, to elicit a response from the customer.

(47) Accordingly, the customer router **502** may receive this authentication request and transmit the request to one or more customer computer systems for processing. The one or more customer computer systems may be configured to prepare a data packet comprising the necessary authentication proof (e.g., password, digital signature, etc.) to verify the identity of the customer, along with any other requisite information necessary to access the other services **512** available to the customer. This data packet may be transmitted to the customer router **502**, which, in turn, may utilize the security protocol to transmit the data packet comprising the authentication proof.

(48) The computing resource service provider router **506** may transmit the received customer data packet to the authentication service **508** for verification. Accordingly, the authentication service **508** may be configured to extract the authentication proof from the data packet. The authentication proof may include a digital signature which may need to be verified using a hash of the received data and a cryptographic key maintained by the computing resource service provider and specific to the customer. Thus, the authentication service **508** may be configured to interact with an account service **510** managed by the computing resource service provider **504** to obtain relevant customer information. For instance, the account service **510**, as illustrated above, may comprise customer account information for each customer of the computing resource service provider **504**. For example, the customer account may comprise one or more cryptographic keys that may be used to generate an expected customer digital signature in order to verify the received digital signature is authentic and thus verify the identity of a customer computer system connected directly to the computing resource service provider **504**. Thus, the account service **510** may be configured to

transmit these keys to the authentication service **508**.

(49) The authentication service **508** may use the cryptographic keys from the account service **510**, along with data received from the customer, to generate an expected customer digital signature and attempt to match this signature with the customer authentication proof. If there is a resulting match between the digital signatures, the authentication service **508** may transmit one or more executable commands to the computing resource service provider router **506** to allow the customer to access the other services **512** provided by the computing resource service provider **504**. However, if no match can be established, the authentication service **508** may transmit an informative message to the customer comprising the reason why access to the other services **512** has been denied.

(50) In another embodiment, once the physical connection has been established between the customer router **502** and the computing resource service provider router **506**, the customer may generate one or more data packets comprising customer information and a digital signature, such as through one or more appropriately configured API calls to the service, which may be used to verify the identity of the customer. These data packets may be transmitted over the physical connection using an authentication protocol to the computing resource service provider router **506**. This router **506** may be configured to transfer these data packets to an authentication service **508** for further processing.

(51) The authentication service **508** may be configured to interact with an account service **510** in order to obtain one or more cryptographic keys necessary to generate an expected customer digital signature. Accordingly, the authentication service **508** may be configured to hash the cryptographic keys and the received customer data to generate this expected customer digital signature. This signature may be compared with the received customer digital signature to determine if there is a match. If there is a match, the customer transmissions may be deemed authentic, causing the authentication service **508** to transmit one or more executable instructions to the provider router **506** to enable the customer to access the one or more other services **512** provided by the computing resource service provider **504**. For instance, if the customer transmissions are deemed to be authentic, the computing resource service provider **504** may allow a customer to provision one or more virtual interfaces to access these other services **512**.

(52) Additionally, the verification of the customer identity may cause the authentication service **508** to generate one or more data packets comprising a digital signature for the computing resource service provider **504** which may be transmitted to the customer router **502**. This may enable the customer to verify the identity of the computing resource service provider **504**.

(53) After the initial authentication of the customer has been made, the customer may now access a variety of services offered by the computing resource service provider. However, further authentication requests may be transmitted between the customer and the computing resource service provider to ensure that the connection has not been compromised. Accordingly, FIG. **6** is an illustrative example of an environment **600** in which a connection with one or more services is managed upon initial authentication in accordance with at least one embodiment. In the environment **600**, the customer may transmit one or more signals through the customer router **602** to access one or more other services **612** provided by the computing resource service provider **604**. Accordingly, these one or more signals may be received by the computing resource service provider router **606** and transmitted to the one or more other services **612** for disposition. For instance, the customer may utilize the customer router **602** to provision a virtual interface, which may be necessary to access the one or more services **612**. In this fashion, the customer may utilize the one or more services **612** for his/her purposes.

(54) At any point during the interactions between the customer and computing resource service provider **604** and its associated other services **612**, the authentication service **608** may transmit an authentication request to the customer, via the computing resource service provider router **606** and the customer router **602**, to ensure that the connection has not been compromised (e.g., a third party has intercepted the connection, etc.). Accordingly, the customer may use one or more computer

systems maintained and operated by the customer to transmit authentication proof necessary to satisfy the received authentication request. This authentication proof may be transmitted through the customer router **602**. As in the initial authentication process illustrated in FIG. 5, the authentication proof may include a password, digital signature or any other credential requested in the authentication request. This authentication proof may be transmitted in one or more data packets configured according to a security protocol to the computing resource service provider **604**.

(55) The computing resource service provider router **606** may receive this authentication proof and accordingly deliver the proof to the authentication service **608** for verification. As illustrated in FIG. 5, the authentication service **608** may be configured to interact with an account service **610** to obtain relevant customer information (e.g., cryptographic keys, customer account credentials, etc.) necessary to evaluate the received authentication proof. If the authentication proof provided by the customer is confirmed to be authentic, the authentication service **608** may allow continued customer access to the other services **612**. However, if the provided authentication proof does not comport with the relevant customer information obtained from the account service **610**, the authentication service **608** may transmit one or more executable instructions to the computing resource service provider router **606** to limit customer access to the other services **612** provided by the computing resource service provider **604**. For instance, the computing resource service provider router **606** may be configured to reduce the available connection bandwidth to the customer or terminate the connection or the virtual interface altogether. Alternatively, the authentication service **608** may be configured to again interact with the account service **610** to identify one or more actions that may be taken in the event of a failed authentication challenge. For example, the customer may specify that the computing resource service provider **604** is to monitor and log all activities related to a user purporting to be the customer that is accessing the other services **612**.

(56) Alternatively, at any point during the interactions between the customer and the computing resource service provider **604** and its associated other services **612**, the computer systems operated by the customer may transmit one or more authentication requests to the computing resource service provider to ensure that the connection has not been compromised. Once the request has been received by the computing resource service provider router **606**, the request may be transmitted to the authentication service **608** for processing. The authentication service **608** may be configured to interact with the account service **610** to obtain the relevant customer information, including, but not limited to, one or more cryptographic keys necessary to generate authentication proof to satisfy the customer authentication request. For instance, the authentication service **608** may be configured to use a hash function to hash data and the cryptographic key to generate a digital signature. Accordingly, the authentication service **608** may generate one or more data packets that may comprise the authentication proof (e.g., digital signature) along with other data that may be transmitted to the customer computer systems via the physical connection between the computing resource service provider router **606** and the customer router **602**.

(57) If the authentication proof provided by the computing resource service provider **604** is inadequate, the customer computing systems may be configured to transmit executable commands that may cause the customer router **602** to terminate the connection. This may include generating a request for a data technician to sever the physical connection or the complete ceasing of transmission of one or more signals through the physical connection. However, if the authentication proof is adequate, such that the connection with the computing resource service provider **604** is indeed authentic, the customer may continue to utilize the physical connection to access the one or more other services **612** necessary to support its business.

(58) In another embodiment, the customer may generate additional data packets comprising cryptographic authentication information, such as through one or more appropriately configured API calls to the service, which may be used to verify the identity of the customer. As noted above, these data packets may be transmitted over the physical connection using an authentication protocol to the computing resource service provider router **606**. This router **606** may be configured

to transfer these data packets to an authentication service **608** for further processing.

(59) As noted above, the authentication service **608** may be configured to interact with an account service **610** in order to obtain one or more cryptographic keys necessary to generate an expected customer digital signature. Accordingly, the authentication service **608** may be configured to hash the cryptographic keys and the received customer data to generate this expected customer digital signature. This signature may be compared with the received customer digital signature to determine if there is a match. If there is a match, the customer transmissions may be deemed authentic, causing the authentication service **608** to allow continued access to the one or more services **612** provided by the computing resource service provider **604**. However, if there is no match, the authentication service **608** may perform one or more actions to limit or even terminate the existing connection, as illustrated above.

(60) In addition, if the digital signatures match, the authentication service **608** may generate one or more data packets comprising a computing resource service provider **604** digital signature which may be transmitted to the customer router **602**. This may enable the customer to verify the identity of the computing resource service provider **604** in order to continue the present direct connection.

(61) As noted above, a direct connection may be established between a customer router and a computing resource service provider to enable a customer to access one or more services provided by the computing resource service provider. Accordingly, FIG. 7 is an illustrative example of a process **700** for establishing a physical connection between a customer and a computing resource service provider in accordance with at least one embodiment. The process **700** may be performed by a variety of networking and computing components operated by the computing resource service provider, as well as one or more services maintained and operated by the computing resource service provider (e.g., authentication and account services).

(62) A customer may contact a computing resource service provider to request the creation of a direct physical connection between a customer router and a computing resource service provider router. For instance, the customer may desire to establish a dedicated network connection between the customer computing systems and the computing resource service provider computing systems. This may enable the customer to access the one or more services provided by the computing resource service provider to support his/her business operations. Accordingly, the process **700** may include a computing resource service provider receiving **702** a request from the customer to establish this direct connection.

(63) Once the computing resource service provider has received the request from the customer, the computing resource service provider may generate **704** a letter of authority to connect the customer router to the computing resource service provider router. As illustrated in FIG. 2, the customer routers and the computing resource service provider routers may be located in a data center or colocation center. Thus, the letter of authority may grant a data technician (e.g., employee of the computing resource service provider, customer or contracted third party) permission to establish the connection between the customer router and the computing resource service provider router.

(64) The data technician may use one or more cables to connect **706** the physical routers. This may entail identifying the customer and computing resource service provider routers within the colocation center and the corresponding ports required to establish the connection. For instance, the data technician may insert one end of a set of cables (e.g., fiber-optic, copper, or other material) in a receiving and transmission port of the customer router and connect the other end of the cables to a receiving and transmission port of the computing resource service provider. If the colocation center includes one or more patch panels, the data technician may connect the cables from the customer router, through the patch panels, and from the final patch panel ports to the computing resource service provider router. The data technician may use a diagnostic tool to ensure proper connectivity or may contact the computing resource service provider to inform the computing resource service provider that the connection has been established.

(65) It should be noted that the authentication process may be port independent. For instance, in an

embodiment, the customer operates and maintains a cage within a colocation center that comprises the customer router and routers maintained and operated by a secondary or tertiary customer (e.g., a customer of the customer with the existing relationship with the computing resource service provider). At any point, the customer may disconnect the physical connection between the customer router and the computing resource service provider and reconnect the physical connection with a router maintained by a secondary or tertiary customer. The secondary or tertiary customer may maintain a set of credentials that may be associated with this secondary or tertiary customer and may be used to provide authentication proof to the computing resource service provider. Thus, the computing resource service provider may accordingly authenticate the physical connection with this secondary or tertiary customer through this physical connection. The secondary or tertiary customer may accordingly provide authentication proof to the computing resource service provider to authenticate the connection, as will be illustrated below.

(66) In various embodiments, the customer and/or provider may change a network device port used to establish a direct physical connection. For example, the customer may request an upgrade of an existing physical connection (e.g., transition from a one gigabyte port to a ten gigabyte port on a computing resource service provider router) resulting in a different connection between the customer router and the computing resource service provider router. In this instance, the authentication process may be repeated once the connection has been established without any systemic changes to the process. This may ensure that the authentication process is port independent.

(67) Once the physical routers in the colocation center have been connected and the data technician has provided confirmation of the connection, the computing resource service provider may use the router to transmit **708** one or more signals to the customer router. As illustrated above in connection with FIG. 5, the computing resource service provider may operate and maintain an authentication service, which may be configured to transmit authentication requests to a customer in order to verify that the customer is authorized to connect to one or more services provided by the computing resource service provider. Accordingly, the authentication service may be configured to generate one or more data packets subject to a security protocol comprising this authentication request. These data packets may be transmitted by the computing resource service provider router to the customer router via the physical connection established in the colocation center.

(68) When the customer router receives these one or more data packets from the computing resource service provider, the customer router may transmit these data packets to the customer computing systems for processing. Based on the authentication request, the customer computer systems may be configured to utilize a hash function and a cryptographic key to generate a digital signature. The digital signature may comprise the authentication proof necessary to satisfy the authentication request. Accordingly, the customer computer systems may be configured to generate one or more data packets comprising the authentication proof required to satisfy the request along with other customer data. These data packets may be created according to the security protocol established for the transmission of authentication information.

(69) The data packets comprising the customer authentication proof may be transmitted to the computing resource service provider through the physical connection using the customer router. Accordingly, the computing resource service provider may receive **710** the signals comprising the customer data packets from the customer router. The signals originating from the customer router may be received by the computing resource service provider router, which may be configured to decompose the signals from the customer and extract the one or more data packets. The data packets, which may be addressed to the authentication service, may be transmitted to the authentication service for processing.

(70) As noted above, the authentication service may be configured to extract the customer authentication proof (e.g., digital signature) from the received data packets in order to verify the identity of the customer. Thus, the authentication service may attempt to authenticate **712** the

digital signature received through the physical connection. As noted above, the authentication service may be configured to interact with an account service in order to obtain relevant customer information. For instance, the authentication service may obtain one or more customer cryptographic keys (e.g., a customer key generated using one or more cryptographic methods, such as elliptic-curve cryptography) from the account service in order to verify the authentication proof. For instance, the authentication service may be configured to hash the customer data received, along with the cryptographic key, to generate an expected customer digital signature. If this expected customer digital signature matches the received digital signature from the customer, then the signals are authentic and the customer identity is verified.

(71) If the authentication proof provided by the customer is adequate (e.g., the digital signatures produce a match), the authentication service may enable **714** the customer to access the one or more services provided by the computing resource service provider. In order to enable customer access to the one or more services, the authentication service may be configured to transmit one or more executable instructions to the computing resource service provider router to re-configure the router to allow the customer to transmit one or more signals to access the one or more services. For instance, the computing resource service provider router may be configured to allow any data packets comprising a recipient IP address of one or more services to be delivered to the one or more services. Additionally, the authentication may be configured to transmit one or more executable instructions to the computing resource service provider router to allow a customer to provision a virtual interface, which may be used to access these services. In this fashion, the customer may be able to access the one or more services provided by the computing resource service provider.

(72) As noted above, the authentication service may be configured to verify that the customer has the authority to access the one or more services provided by the computing resource service provider after the physical connection between the customer and the computing resource service provider has been established. Accordingly, FIG. **8** is an illustrative example of a process **800** for authenticating a connection for the first time in accordance with at least one embodiment. As noted above, the computing resource service provider and customer may establish a physical connection through the use of routers located in a colocation center. Once the physical connection has been established, there is a risk that an unauthorized third party may interfere with the connection (e.g., attempt to impersonate the customer and access customer information). Accordingly, the computing resource service provider may include an authentication service that may be configured to transmit **802** an authentication request to the customer to verify the customer has the authority to access the requested services.

(73) As noted above, the authentication service may be configured to generate one or more data packets comprising the authentication request which may be sent through the physical connection. These data packets may additionally be configured according to a security protocol in addition to other standard protocols (e.g., TCP/IP, IPsec, etc.) such that the data packets may be processed by the customer computer systems and the transmission is secure. Accordingly, the authentication service may be configured to transmit these data packets to the computing resource service provider router which, in turn, may transmit the data packets to the customer.

(74) The customer may receive these data packets through the customer router that may be physically connected to the computing resource service provider router in the colocation center. Accordingly, the data packets may be transmitted to one or more customer computer systems for processing, such that the one or more computer systems may generate one or more data packets in response to the request comprising the necessary authentication proof to verify that the customer has the authority to access the services provided by the computing resource service provider. As is the case with the data packets generated using the authentication service, the one or more customer computer systems may be configured to generate one or more data packets configured according to the security protocol in addition to the other standard protocols. Thus, these data packets may be

transmitted from the customer router to the computing resource service provider router for processing. The computing resource service provider may transmit the one or more data packets received from the customer to the authentication service.

(75) Accordingly, the authentication service may be configured to receive **804** the authentication proof from the customer. Based on the type of authentication proof requested, the authentication service may be configured to interact with an account service to obtain customer account information necessary to verify the authentication proof. For instance, the authentication service may obtain a cryptographic key associated with the customer account to generate an expected customer digital signature which may be used to determine whether the digital signature received from the customer is authentic.

(76) Accordingly, the authentication service may be configured to use the cryptographic key to generate an expected customer digital signature to compare to the received digital signature from the customer to determine whether there is a match. Accordingly, the authentication service may be configured to determine **806** whether the customer authentication proof is authentic. If the authentication proof received from the customer matches the expected customer digital signature generated by the authentication service, the authentication service may establish **808** a connection to the one or more services provided by the computing resource service provider. For instance, the authentication service may be configured to transmit one or more executable instructions to the computing resource service provider router that may cause the router to transmit any data packets received from the customer addressed to the one or more services provided by the computing resource service provider to these one or more services. Thus, the customer may be able to access these services to support its business.

(77) However, if the authentication proof received from the customer does not match the expected customer digital signature generated by the authentication service, the authentication service may deny **810** the customer access to the services provided by the computing resource service provider. For instance, the authentication service may be configured to transmit one or more executable commands to the computing resource service provider router which may cause the router to reject any data packets from the customer that may be addressed to these one or more services.

Alternatively, if the configuration of the computing resource service provider router during the initial physical connection includes automatically rejected any data packets addressed to the one or more services, the authentication service may not transmit any additional instructions to the router. Thus, the router may continue to reject these data packets from the customer.

(78) Once the customer has successfully connected to the one or more services, the customer may continue to utilize these services to support its business. The authentication service, however, may be configured to continue to submit authentication requests to the customer in order to ensure that the connection has not been compromised. Accordingly, FIG. 9 is an illustrative example of a process **900** for authenticating a connection after a connection has been previously established in accordance with at least one embodiment. As in the process illustrated in FIG. 8, an authentication service may be configured to transmit **902** an authentication request to a customer. This authentication requested may be transmitted in one or more data packets configured according to one or more communications protocols (e.g., TCP/IP) and a security protocol necessary for the security of the physical connection.

(79) As noted above, the customer may operate one or more computer systems configured to further operations of the customer's business. Accordingly, these one or more computer systems may be configured to process the authentication request and generate one or more data packets comprising the necessary authentication proof to satisfy the request. The authentication proof, as noted above, may include one or more customer credentials (e.g., passwords, digital signatures, etc.). As in the data packets comprising the authentication request, the data packets generated using the customer computing systems may be configured to one or more communications protocols and a security protocol. These data packets may be delivered using a customer router which may be

directly (e.g., through physical cables in a colocation center) connected to a computing resource service provider router.

(80) The computing resource service provider router may thus be configured to receive **904** the data packets comprising the authentication proof and transmit these data packets to the authentication service operated by the computing resource service provider. Accordingly, the authentication service may be configured to interact with an account service operated by the computing resource service provider to obtain necessary information to verify the authentication proof. This may enable the authentication service to determine **906** whether the customer authentication proof is authentic. For instance, the authentication service may obtain one or more cryptographic keys necessary to generate an expected customer digital signature which may be used to verify the received digital signature from the customer.

(81) If the authentication proof satisfies the authentication request (e.g., the provided customer digital signature matches the expected customer digital signature generated by the authentication service), the authentication service may further determine **908** whether the customer currently has access to the one or more services provided by the computing resource service provider. If the computing resource service provider has previously established a connection between the customer and these services, the authentication service may be configured to continue to allow the customer to access these services. Accordingly, the authentication service may be configured to transmit **902** another authentication request to the customer in order to ensure the connection has not been compromised. These subsequent requests may be made at a later time, based at least in part on the configuration of the authentication service.

(82) However, if the customer currently does not have access to the one or more services provided by the computing resource service provider, the authentication service may establish **910** a connection between the customer and these services. For instance, the authentication service may be configured to transmit one or more executable instructions to the computing resource service provider router that causes the router to permit any data packets originating from a customer computer system to be transmitted to the one or more services. Thus, a customer may now access these services to further his/her business. Again, once the connection has been established, the authentication service may continue to transmit **902** authentication requests to the customer to ensure the connection has not been compromised. These subsequent requests may be made daily, weekly, monthly or at varying time intervals, dependent upon the configuration of the authentication service.

(83) If the authentication service evaluates the received authentication proof from the customer and determines that the proof is not authentic, the authentication service may further determine **912** whether to limit the customer's access to the one or more services provided by the computing resource service provider. For instance, the computing resource service provider may allow a customer to define what actions may be taken in the event the connection has been compromised. For example, the customer may specify that the connection should be terminated upon a potential breach. In another example, a customer may prefer to allow the connection to continue uninterrupted while logging all transmissions between the purported customer (e.g., unauthorized third party, etc.) and the computing resource service provider.

(84) Accordingly, the authentication service may be configured to interact with the account service to refer to the customer's instructions in the event of a breach and perform these actions.

Alternatively, if the customer has not specified any actions to be taken, the authentication service may refer to one or more default instructions that may cause the service to perform one or more actions with regard to the connection. If the customer's instructions or default instructions include limiting access to the one or more services, the authentication service may proceed to limit **914** the customer's access to these services. For instance, the authentication service may be configured to transmit one or more executable instructions to the computing resource service provider router to throttle the available connection bandwidth available to the customer, thus slowing the ability of

the customer to access the services. Alternatively, the connection may be terminated entirely. Other methods for limiting access to the services may additionally be incorporated and are considered to be within the scope of the present disclosure.

(85) Once the connection between the customer and the computing resource service provider has been limited, the authentication service may continue to transmit **902** authentication requests to the customer. Thus, if the customer is able to provide adequate authentication proof in response to a new authentication request, the authentication service may transmit one or more executable instructions to the computing resource service provider router to restore the access to the one or more services. In this fashion, the customer and the computing resource service provider may resolve the issue with the connection, be it an unauthorized third party, expiration of a credential or some other issue, and restore the connection.

(86) If, for example, the customer has specified that the computing resource service provider should not take any actions in the event that the authentication proof is inadequate, the computing resource service provider may allow the connection to continue unfettered. Accordingly, the authentication service may be configured to continue to transmit **902** authentication requests to determine whether issues still remain with regard with the connection. For instance, the authentication service may be configured to terminate a connection after a number of authentication requests have resulted in no adequate authentication proof responses.

(87) As noted above, once the physical connection between a customer router and a computing resource service provider router has been established, the computing resource service provider may transmit one or more authentication requests to the customer in order to verify the customer's identity and ensure that the connection has not been compromised. In a similar manner, the customer may utilize one or more computing systems that the customer may use to support his/her business to transmit one or more authentication requests to the computing resource service provider to verify the identity of the provider. Accordingly, FIG. **10** is an illustrative example of a process **1000** for authenticating a connection in accordance with at least one embodiment.

(88) The customer may desire to verify the identity of the party at the other end of the connection prior to transmitting potentially sensitive customer data to the one or more services. Accordingly, the customer may configure one or more computer systems to transmit **1002** an authentication request to the computing resource service provider. As noted above, the customer computing systems may be configured to generate one or more data packets configured according to one or more communications protocols and a security protocol necessary to transmit these data packets over the secure connection. These data packets may comprise an authentication request and customer identification data. Thus, the customer computer systems may transfer these data packets to a customer router which may be configured to transmit these data packets to the computing resource service provider router on the other end of the physical connection.

(89) Accordingly, the authentication request may be delivered to an authentication service operated by the computing resource service provider for processing. The authentication service may be configured to interact with an account service to access the customer account and locate the necessary information to fulfill the request. For example, the authentication service may obtain a cryptographic key from the customer account in order to generate a digital signature which may be used as authentication proof. The authentication service may be configured to generate one or more data packets comprising the information necessary to fulfill the request and transmit these data packets, through the computing resource service provider router to the one or more customer computing systems. In this fashion, the one or more customer computer systems may receive **1004** the authentication proof from the computing resource service provider.

(90) Once the customer computing systems have obtained the authentication proof from the computing resource service provider, the customer computing systems may process the authentication proof to determine **1006** whether the proof is authentic. In order to determine whether the proof is indeed authentic, the customer computing systems may be configured to use a

cryptographic key to generate an expected authentication service digital signature and compare this digital signature to the digital signature received from the authentication service. Accordingly, the customer computer systems may locate or generate the expected computing resource service provider credentials (e.g., cryptographic key, expected digital signature, etc.) and compare these credentials to the proof provided. If the authentication proof received does not match the expected computing resource service provider credentials, the customer computer systems may transmit reconfiguration information (e.g., executable instructions) to the customer router to terminate **1008** the connection. Thus, no further transmissions may be received from the computing resource service provider, allowing the customer to address the potential issue.

(91) If the authentication proof received from the computing resource service provider is valid (e.g., the expected authentication service digital signature matches the received digital signature), the customer may allow further transmissions to be made and may continue to access the one or more services provided by the computing resource service provider. Additionally, the customer computer systems may be configured to continue to transmit **1002** one or more authentication requests to the computing resource service provider to ensure that the connection has not been compromised.

(92) FIG. **11** illustrates aspects of an example environment **1100** for implementing aspects in accordance with various embodiments. As will be appreciated, although a web-based environment is used for purposes of explanation, different environments may be used, as appropriate, to implement various embodiments. The environment includes an electronic client device **1102**, which can include any appropriate device operable to send and receive requests, messages or information over an appropriate network **1104** and convey information back to a user of the device. Examples of such client devices include personal computers, cell phones, handheld messaging devices, laptop computers, tablet computers, set-top boxes, personal data assistants, embedded computer systems, electronic book readers and the like. The network can include any appropriate network, including an intranet, the Internet, a cellular network, a local area network or any other such network or combination thereof. Components used for such a system can depend at least in part upon the type of network and/or environment selected. Protocols and components for communicating via such a network are well known and will not be discussed herein in detail. Communication over the network can be enabled by wired or wireless connections and combinations thereof. In this example, the network includes the Internet, as the environment includes a web server **1106** for receiving requests and serving content in response thereto, although for other networks an alternative device serving a similar purpose could be used as would be apparent to one of ordinary skill in the art.

(93) The illustrative environment includes at least one application server **1108** and a data store **1110**. It should be understood that there can be several application servers, layers or other elements, processes or components, which may be chained or otherwise configured, which can interact to perform tasks such as obtaining data from an appropriate data store. Servers, as used herein, may be implemented in various ways, such as hardware devices or virtual computer systems. In some contexts, servers may refer to a programming module being executed on a computer system. As used herein the term “data store” refers to any device or combination of devices capable of storing, accessing and retrieving data, which may include any combination and number of data servers, databases, data storage devices and data storage media, in any standard, distributed or clustered environment. The application server can include any appropriate hardware and software for integrating with the data store as needed to execute aspects of one or more applications for the client device, handling some (even a majority) of the data access and business logic for an application. The application server may provide access control services in cooperation with the data store and is able to generate content such as text, graphics, audio and/or video to be transferred to the user, which may be served to the user by the web server in the form of HyperText Markup Language (“HTML”), Extensible Markup Language (“XML”) or another appropriate structured

language in this example. The handling of all requests and responses, as well as the delivery of content between the client device **1102** and the application server **1108**, can be handled by the web server. It should be understood that the web and application servers are not required and are merely example components, as structured code discussed herein can be executed on any appropriate device or host machine as discussed elsewhere herein. Further, operations described herein as being performed by a single device may, unless otherwise clear from context, be performed collectively by multiple devices, which may form a distributed system.

(94) The data store **1110** can include several separate data tables, databases or other data storage mechanisms and media for storing data relating to a particular aspect of the present disclosure. For example, the data store illustrated may include mechanisms for storing production data **1112** and user information **1116**, which can be used to serve content for the production side. The data store also is shown to include a mechanism for storing log data **1114**, which can be used for reporting, analysis or other such purposes. It should be understood that there can be many other aspects that may need to be stored in the data store, such as page image information and access rights information, which can be stored in any of the above listed mechanisms as appropriate or in additional mechanisms in the data store **1110**. The data store **1110** is operable, through logic associated therewith, to receive instructions from the application server **1108** and obtain, update or otherwise process data in response thereto. In one example, a user, through a device operated by the user, might submit a search request for a certain type of item. In this case, the data store might access the user information to verify the identity of the user and can access the catalog detail information to obtain information about items of that type. The information then can be returned to the user, such as in a results listing on a web page that the user is able to view via a browser on the user device **1102**. Information for a particular item of interest can be viewed in a dedicated page or window of the browser. It should be noted, however, that embodiments of the present disclosure are not necessarily limited to the context of web pages, but may be more generally applicable to processing requests in general, where the requests are not necessarily requests for content.

(95) Each server typically will include an operating system that provides executable program instructions for the general administration and operation of that server and typically will include a computer-readable storage medium (e.g., a hard disk, random access memory, read only memory, etc.) storing instructions that, when executed by a processor of the server, allow the server to perform its intended functions. Suitable implementations for the operating system and general functionality of the servers are known or commercially available and are readily implemented by persons having ordinary skill in the art, particularly in light of the disclosure herein.

(96) The environment in one embodiment is a distributed computing environment utilizing several computer systems and components that are interconnected via communication links, using one or more computer networks or direct connections. However, it will be appreciated by those of ordinary skill in the art that such a system could operate equally well in a system having fewer or a greater number of components than are illustrated in FIG. **11**. Thus, the depiction of the system **1100** in FIG. **11** should be taken as being illustrative in nature and not limiting to the scope of the disclosure.

(97) The various embodiments further can be implemented in a wide variety of operating environments, which in some cases can include one or more user computers, computing devices or processing devices which can be used to operate any of a number of applications. User or client devices can include any of a number of general purpose personal computers, such as desktop, laptop or tablet computers running a standard operating system, as well as cellular, wireless and handheld devices running mobile software and capable of supporting a number of networking and messaging protocols. Such a system also can include a number of workstations running any of a variety of commercially-available operating systems and other known applications for purposes such as development and database management. These devices also can include other electronic devices, such as dummy terminals, thin-clients, gaming systems and other devices capable of

communicating via a network.

(98) Various embodiments of the present disclosure utilize at least one network that would be familiar to those skilled in the art for supporting communications using any of a variety of commercially-available protocols, such as Transmission Control Protocol/Internet Protocol (“TCP/IP”), protocols operating in various layers of the Open System Interconnection (“OSI”) model, File Transfer Protocol (“FTP”), Universal Plug and Play (“UpnP”), Network File System (“NFS”), Common Internet File System (“CIFS”) and AppleTalk. The network can be, for example, a local area network, a wide-area network, a virtual private network, the Internet, an intranet, an extranet, a public switched telephone network, an infrared network, a wireless network and any combination thereof.

(99) In embodiments utilizing a web server, the web server can run any of a variety of server or mid-tier applications, including Hypertext Transfer Protocol (“HTTP”) servers, FTP servers, Common Gateway Interface (“CGI”) servers, data servers, Java servers and business application servers. The server(s) also may be capable of executing programs or scripts in response to requests from user devices, such as by executing one or more web applications that may be implemented as one or more scripts or programs written in any programming language, such as Java®, C, C# or C++, or any scripting language, such as Perl, Python or TCL, as well as combinations thereof. The server(s) may also include database servers, including without limitation those commercially available from Oracle®, Microsoft®, Sybase® and IBM®.

(100) The environment can include a variety of data stores and other memory and storage media as discussed above. These can reside in a variety of locations, such as on a storage medium local to (and/or resident in) one or more of the computers or remote from any or all of the computers across the network. In a particular set of embodiments, the information may reside in a storage-area network (“SAN”) familiar to those skilled in the art. Similarly, any necessary files for performing the functions attributed to the computers, servers or other network devices may be stored locally and/or remotely, as appropriate. Where a system includes computerized devices, each such device can include hardware elements that may be electrically coupled via a bus, the elements including, for example, at least one central processing unit (“CPU” or “processor”), at least one input device (e.g., a mouse, keyboard, controller, touch screen or keypad) and at least one output device (e.g., a display device, printer or speaker). Such a system may also include one or more storage devices, such as disk drives, optical storage devices and solid-state storage devices such as random access memory (“RAM”) or read-only memory (“ROM”), as well as removable media devices, memory cards, flash cards, etc.

(101) Such devices also can include a computer-readable storage media reader, a communications device (e.g., a modem, a network card (wireless or wired), an infrared communication device, etc.) and working memory as described above. The computer-readable storage media reader can be connected with, or configured to receive, a computer-readable storage medium, representing remote, local, fixed and/or removable storage devices as well as storage media for temporarily and/or more permanently containing, storing, transmitting and retrieving computer-readable information. The system and various devices also typically will include a number of software applications, modules, services or other elements located within at least one working memory device, including an operating system and application programs, such as a client application or web browser. It should be appreciated that alternate embodiments may have numerous variations from that described above. For example, customized hardware might also be used and/or particular elements might be implemented in hardware, software (including portable software, such as applets) or both. Further, connection to other computing devices such as network input/output devices may be employed.

(102) Storage media and computer readable media for containing code, or portions of code, can include any appropriate media known or used in the art, including storage media and communication media, such as, but not limited to, volatile and non-volatile, removable and non-

removable media implemented in any method or technology for storage and/or transmission of information such as computer readable instructions, data structures, program modules or other data, including RAM, ROM, Electrically Erasable Programmable Read-Only Memory (“EEPROM”), flash memory or other memory technology, Compact Disc Read-Only Memory (“CD-ROM”), digital versatile disk (DVD) or other optical storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices or any other medium which can be used to store the desired information and which can be accessed by the system device. Based on the disclosure and teachings provided herein, a person of ordinary skill in the art will appreciate other ways and/or methods to implement the various embodiments.

(103) The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense. It will, however, be evident that various modifications and changes may be made thereunto without departing from the broader spirit and scope of the invention as set forth in the claims.

(104) Other variations are within the spirit of the present disclosure. Thus, while the disclosed techniques are susceptible to various modifications and alternative constructions, certain illustrated embodiments thereof are shown in the drawings and have been described above in detail. It should be understood, however, that there is no intention to limit the invention to the specific form or forms disclosed, but on the contrary, the intention is to cover all modifications, alternative constructions and equivalents falling within the spirit and scope of the invention, as defined in the appended claims.

(105) The use of the terms “a” and “an” and “the” and similar referents in the context of describing the disclosed embodiments (especially in the context of the following claims) are to be construed to cover both the singular and the plural, unless otherwise indicated herein or clearly contradicted by context. The terms “comprising,” “having,” “including,” and “containing” are to be construed as open-ended terms (i.e., meaning “including, but not limited to,”) unless otherwise noted. The term “connected,” when unmodified and referring to physical connections, is to be construed as partly or wholly contained within, attached to or joined together, even if there is something intervening. Recitation of ranges of values herein are merely intended to serve as a shorthand method of referring individually to each separate value falling within the range, unless otherwise indicated herein and each separate value is incorporated into the specification as if it were individually recited herein. The use of the term “set” (e.g., “a set of items”) or “subset” unless otherwise noted or contradicted by context, is to be construed as a nonempty collection comprising one or more members. Further, unless otherwise noted or contradicted by context, the term “subset” of a corresponding set does not necessarily denote a proper subset of the corresponding set, but the subset and the corresponding set may be equal.

(106) Conjunctive language, such as phrases of the form “at least one of A, B, and C,” or “at least one of A, B and C,” unless specifically stated otherwise or otherwise clearly contradicted by context, is otherwise understood with the context as used in general to present that an item, term, etc., may be either A or B or C, or any nonempty subset of the set of A and B and C. For instance, in the illustrative example of a set having three members used in the above conjunctive phrase, “at least one of A, B, and C” and “at least one of A, B and C” refers to any of the following sets: {A}, {B}, {C}, {A, B}, {A, C}, {B, C}, {A, B, C}. Thus, such conjunctive language is not generally intended to imply that certain embodiments require at least one of A, at least one of B and at least one of C to each be present.

(107) Operations of processes described herein can be performed in any suitable order unless otherwise indicated herein or otherwise clearly contradicted by context. Processes described herein (or variations and/or combinations thereof) may be performed under the control of one or more computer systems configured with executable instructions and may be implemented as code (e.g., executable instructions, one or more computer programs or one or more applications) executing collectively on one or more processors, by hardware or combinations thereof. The code may be

stored on a computer-readable storage medium, for example, in the form of a computer program comprising a plurality of instructions executable by one or more processors. The computer-readable storage medium may be non-transitory.

(108) The use of any and all examples, or exemplary language (e.g., “such as”) provided herein, is intended merely to better illuminate embodiments of the invention and does not pose a limitation on the scope of the invention unless otherwise claimed. No language in the specification should be construed as indicating any non-claimed element as essential to the practice of the invention.

(109) Preferred embodiments of this disclosure are described herein, including the best mode known to the inventors for carrying out the invention. Variations of those preferred embodiments may become apparent to those of ordinary skill in the art upon reading the foregoing description. The inventors expect skilled artisans to employ such variations as appropriate and the inventors intend for embodiments of the present disclosure to be practiced otherwise than as specifically described herein. Accordingly, the scope of the present disclosure includes all modifications and equivalents of the subject matter recited in the claims appended hereto as permitted by applicable law. Moreover, any combination of the above-described elements in all possible variations thereof is encompassed by the scope of the present disclosure unless otherwise indicated herein or otherwise clearly contradicted by context.

(110) All references, including publications, patent applications and patents, cited herein are hereby incorporated by reference to the same extent as if each reference were individually and specifically indicated to be incorporated by reference and were set forth in its entirety herein.

Claims

1. A computer-implemented method, comprising: receiving, at a service provider gateway and from a customer device of a customer connected with a service provider over a secure connection, cryptographic authentication information wherein the secure connection comprises a physical connection between a set of customer ports and a set of service provider ports, the set of customer ports colocated with the set of service provider ports; forwarding, from the service provider gateway, the cryptographic authentication information to an authentication service that is operable to authenticate the cryptographic authentication information; and as a result of the authentication service successfully authenticating the cryptographic authentication information, configuring the service provider gateway to route network traffic from the customer device to one or more services of the service provider different from the authentication service.

2. The computer-implemented method of claim 1, wherein the customer device is a customer gateway device in a colocation center with the service provider gateway, and the physical connection includes one or more cables connecting the set of customer ports to the set of computing resource service provider ports.

3. The computer-implemented method of claim 1, wherein the secure connection comprises a virtual private network (VPN).

4. The computer-implemented method of claim 1, wherein the secure connection comprises a virtual circuit.

5. The computer-implemented method of claim 1, wherein the cryptographic authentication information is obtained based at least in part on extracted authentication proof from a data packet included in a customer request to access a network of the service provider.

6. The computer-implemented method of claim 1, further comprising: receiving a request to update the secure connection to a different connection between a different customer device and the service provider; determining that a second secure connection is established between the service provider gateway and the different customer device; and updating network traffic between the service provider gateway and the customer device to be routed between the service provider gateway and the different customer device.

7. The computer-implemented method of claim 1, wherein receiving the cryptographic authentication information from the customer device is a result of determining, using border gateway protocol (BGP), gateway devices available to transmit and receive data packets between the service provider gateway and the customer device.
8. The computer-implemented method of claim 1, wherein the one or more services of the service provider include an object-based data storage service.
9. The computer-implemented method of claim 1, wherein forwarding the cryptographic authentication information to the authentication service is based at least in part on information included in a letter of authority (LOA) provided by the service provider to a customer associated with the customer device.
10. A computer-implemented method, comprising: receiving, at a virtual interface of a service provider and from a local gateway device associated with a customer connected with the service provider over a dedicated physical connection, cryptographic authentication information, wherein the dedicated physical connection is established based at least in part on a physical connection comprising one or more cables connected from a set of customer ports to a set of computing resource service provider ports colocated with the set of customer ports; forwarding, from the virtual interface, the cryptographic authentication information to an authentication service that is operable to cause the cryptographic authentication information to be authenticated; and configuring, as a result of an indication that the authentication service authenticated the cryptographic authentication information, the virtual interface to route network traffic from the local gateway device to a service of the service provider different from the authentication service.
11. The computer-implemented method of claim 10, wherein the cryptographic authentication information is obtained based at least in part on one or more data packets included with a customer request to access a network of the service provider.
12. The computer-implemented method of claim 10, wherein forwarding the cryptographic authentication information further causes the authentication service to generate a letter of authority to authorize connecting one or more physical routers associated with the customer and the service provider.
13. The computer-implemented method of claim 10, further comprising: receiving an additional request to upgrade the dedicated physical connection to a different dedicated connection between a different local gateway device and the service provider; determining that the different dedicated connection is established between a different service provider gateway and the different local gateway device; and upgrading network traffic between the service provider and the customer to be routed between the different service provider gateway and the different local gateway device.
14. The computer-implemented method of claim 13, wherein the additional request is received as a result of the local gateway device being disconnected from the service provider.
15. The computer-implemented method of claim 10, wherein the service is a database service.
16. A system, comprising non-transitory memory storing computer-executable instructions that, as a result of execution by one or more processors, cause the one or more processors to: receive, using a virtual interface and from a gateway device connected with a service provider over a dedicated connection, a request from a user of the virtual interface, wherein the dedicated connection is established based at least in part on a physical connection, the physical connection comprising one or more cables connected from a set of customer ports to a set of computing resource service provider ports colocated with the set of customer ports; forward the request to an authentication service that is operable to cause the request to be authenticated; and configure, as a result of successful authentication of the request, the virtual interface to route network traffic from the gateway device to one or more services of the service provider different from the authentication service.
17. The system of claim 16, wherein the request includes authentication information associated with the user.

18. The system of claim 16, wherein the computer-executable instructions further cause the one or more processors to: transmit one or more signals, from the virtual interface to the gateway device; and reconfigure, as a result of the gateway device being unable to provide authentication proof in response to transmission of the signals, the dedicated connection to limit access of the gateway device to the one or more services.

19. The system of claim 16, wherein the routed network traffic between the virtual interface and the gateway device is over a communication network separate from an Internet network.

20. The system of claim 16, wherein the one or more services include an object-based data storage service.
