

US Patent & Trademark Office

Patent Public Search | Text View

United States Reissue Patent

RE50582

Kind Code

E

Date of Reissued Patent

September 09, 2025

Inventor(s)

Dong; Fangxu

Color mixing optics for LED lighting

Abstract

Color mixing optics for a multi-color LED lamp comprise an outer reflector having a paraboloidal surface of revolution and a total inner reflection (TIR) lens having an outer contour with a paraboloidal surface of revolution. The outer reflector and the TIR lens are centered around a common center axis. A common focal point of the outer reflector and the TIR lens is provided for placing a LED assembly. Such LED lamps produce uniform color throughout the entire light beam while the outer dimensions are such that the optics fit into conventional lamp housings.

Inventors: Dong; Fangxu (Austin, TX)

Applicant: Lutron Technology Company LLC (Coopersburg, PA)

Family ID: 54266588

Assignee: Lutron Technology Company LLC (Coopersburg, PA)

Appl. No.: 17/459159

Filed: August 27, 2021

Related U.S. Application Data

continuation parent-doc US 16198005 20181121 US RE48712 child-doc US 17459159
reissue parent-doc US 14474408 20140902 US 9500324 20161122 child-doc US 16198005
reissue parent-doc US 14474408 20140902 GRANTED US 9500324 20161122 child-doc US
17459159

Publication Classification

Int. Cl.: F21K99/00 (20160101); F21K9/232 (20160101); F21K9/62 (20160101); F21V7/00
(20060101); F21V7/06 (20060101); F21V13/04 (20060101); F21Y113/17 (20160101);

U.S. Cl.:

CPC **F21K9/232** (20160801); **F21K9/62** (20160801); **F21V7/0025** (20130101); **F21V7/0091** (20130101); **F21V7/06** (20130101); **F21V13/04** (20130101); F21Y2113/17 (20160801); F21Y2115/10 (20160801)

Field of Classification Search

CPC: F21V (7/0025); F21V (7/0083); F21V (7/0091); F21V (7/06); F21V (13/04); F21V (5/048); F21K (9/62); F21K (9/232)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1888995	12/1931	Matter	N/A	N/A
4767172	12/1987	Nichols et al.	N/A	N/A
7349163	12/2007	Angelini	257/99	F21K 9/00
7401960	12/2007	Pond	362/516	B60Q 1/04
7431480	12/2007	Godo	N/A	N/A
8016451	12/2010	Householder	362/188	F21L 4/027
8246210	12/2011	Angelini	362/187	F21L 4/027
8469544	12/2012	Angelini	362/240	F21V 5/04
8485692	12/2012	Li	362/308	G02B 19/0066
8529102	12/2012	Pickard et al.	N/A	N/A
8733981	12/2013	Jiang et al.	N/A	N/A
9170001	12/2014	Schenkl	N/A	D06F 7/266
RE48712	12/2020	Dong	N/A	F21V 7/0025
2004/0165388	12/2003	Shoji	N/A	N/A
2008/0030986	12/2007	Ogawa et al.	N/A	N/A
2011/0044025	12/2010	Ikeda et al.	N/A	N/A
2012/0218765	12/2011	Inoue	N/A	N/A
2013/0058104	12/2012	Catalano	N/A	N/A
2013/0088142	12/2012	Allen	N/A	N/A
2013/0134456	12/2012	Lu	N/A	N/A
2013/0194808	12/2012	Guercio et al.	N/A	N/A
2013/0314925	12/2012	Jiang et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2180232	12/2009	EP	N/A
2180232	12/2009	EP	N/A
2014/043384	12/2013	WO	N/A
2014/043384	12/2013	WO	N/A

OTHER PUBLICATIONS

“International Search Report & Written Opinion”, for PCT Patent Application No. PCT/IB2015/001435, Mailed Nov. 12, 2015, 10 pages. cited by applicant

Primary Examiner: Menefee; James A

Attorney, Agent or Firm: Condo Roccia Koptiw LLP

Background/Summary

.Iadd.CROSS-REFERENCE TO RELATED APPLICATIONS .Iaddend.

(1) .Iadd.Notice: More than one reissue application has been filed for the reissue of U.S. Patent No. 9,500,324. The reissue applications are the present application and U.S. application No. 16/198,005. This application is a reissue continuation of U.S. application No. 16/198,005, filed Nov. 21, 2018, which is an application for reissue of U.S. Patent No. 9,500,324, issued Nov. 22, 2016, from U.S. application No. 14/474,408, filed Sep. 2, 2014, each of which is hereby incorporated by reference herein in their entirety as if completely and fully set forth herein.

.Iaddend.

BACKGROUND OF THE INVENTION

(2) 1. Field of the Invention

(3) The invention relates to a LED lamp and color mixing optics to produce a uniform intensity distribution and a uniform color output throughout the beam pattern of the light beam produced by a multi-color LED light source for use in LED lamps.

(4) 2. Description of Relevant Art

(5) Color LED lamps should have an even intensity and color distribution over a broad range of radiation angles. As there is no single point LED source available, the radiation of multiple LED sources must be combined to form a multi-color light source. These multiple LED sources are placed offset to each other, so there is no common focal point. To obtain an even color distribution, color mixing is required.

(6) Conventional color mixing uses light guides which typically are large and inefficient. The rule of thumb for a light guide is that it should be about 10 times longer than the dimensions of the multi-color light source. A typical 90 Watt halogen lamp produces about 1200 lumens. An array of many large LEDs is necessary to produce such output light. Such 1200 lumen output arrays may be about 5-6 mm in diameter. If such a light source comprises multi-color LEDs, a 50-60 mm light guide would be needed to properly mix the colors. Considering that the beam needs to be shaped after color mixing, the dimensions needed for a light guide become too large to fit into conventional lamp housings.

(7) U.S. Pat. No. 8,529,102 discloses a reflector system for a multi-color LED lamp providing color mixing. The system uses two reflective surfaces to redirect the light before it is emitted.

(8) A lens the system with multiple curved surfaces for a multi-color LED lamp is disclosed in the U.S. Pat. No. 8,733,981. It is based on a total inner reflection (TIR) lens system which has some similarity to a Fresnel lens.

SUMMARY OF THE INVENTION

(9) The embodiments are based on the object of making a color mixing optic for color LED lamps which produces uniform intensity and color throughout the entire light beam while the outer dimensions are such small that the optics fit into conventional lamp housings. Furthermore, the optic should be simple, robust as well as easy and cost-effective to manufacture. Another embodiment is based on the object of making a color LED lamp comprising the color mixing optic.

(10) In an embodiment, an optic system comprises an outer reflector which preferably has a

concave surface. This reflector preferably has a paraboloidal surface of revolution and is centered around a center axis. Preferably, it has a reflector focal point.

(11) A total inner reflection (TIR) lens is provided, which has an outer contour with a paraboloidal surface of revolution and with a TIR lens focal point. Preferably, the reflector focal point is in close proximity to the TIR lens focal point most preferably at the TIR lens focal point.

(12) Preferably, the color mixing optic is rotationally symmetrical about a center axis. Therefore it is preferred to align the outer reflector and the TIR lens with the center axis.

(13) Furthermore, the TIR lens preferably has a concave light entrance surface by which it receives light from the at least one LED. Preferably, the light entrance surface has a spherical shape.

(14) Preferably, the TIR lens is arranged within the outer reflector. Most preferably it is held within the outer reflector.

(15) Preferably, the TIR lens is held by a cover, which preferably covers the outer reflector, preventing dust and debris from entering into the lamp. It is preferred, if the cover and the TIR lens are made of one piece and therefore, the TIR lens is part of the cover.

(16) Preferably, the LED assembly or the center of the LED assembly is located close to and most preferably at the focal point.

(17) In an embodiment, an LED lamp comprises LEDs and an optic system as mentioned before. The optic system comprises a housing enclosing the outer reflector or being part thereof, a total inner reflection (TIR) lens, and a cover.

(18) A LED assembly holds at least one LED, preferably a plurality of LEDs. It may be based on a printed circuit board and it preferably has a heat sink. It may be part of the base. The LED assembly preferably is positioned at or close to the focal point of the paraboloidal outer reflector. Most preferably a LED surface plane is positioned at or close to the focal point of the paraboloidal outer reflector. The LED surface plane is a plane defined by the radiating surfaces of the individual LEDs of the LED assembly. The LED assembly may be covered by a protective cover, which preferably forms a LED lens. Preferably, the LED lens has a spherical shape. It is preferred to align the (optical) center of the LED assembly, the outer reflector and the TIR lens with the center axis. The LED assembly may be held by a base to the housing.

(19) The optics still works with comparatively large LED arrays, where individual LEDs are spaced apart in the range of tenths of millimeters to millimeters. Furthermore, the optics works with a plurality of colors and is therefore usable for multicolor LEDs, as the color mixing properties are largely independent of the wavelength.

(20) In this embodiment, for the first time an LED lamp can be built which provides accurate white light along the black body curve along with saturated colors. This lamp may be implemented in a PAR form factor, preferably a PAR that provides uniform color throughout the standard 10, 25, 40 degree beam angles.

(21) It is essential for these embodiments, that almost all the light radiated by the LEDs is only reflected by either the outer reflector or by the TIR lens, thus avoiding any refraction which is wavelength dependent and therefore causes deviation in the color distribution.

(22) Another embodiment relates to an LED lamp comprising a housing, a socket, a power supply, and/or driver, an LED assembly and the optics comprising an outer reflector, a TIR lens, and preferably a cover.

(23) A further embodiment relates to a method for generating a mixed beam of light. First, light of multiple wavelengths is generated by a LED assembly comprising a plurality of LEDs. After generating the light, deflecting the light in two portions take place. A first portion of the light is deflected by an outer reflector having a paraboloidal surface of revolution centered around a center axis and defining a reflector focal point. A second portion of the light is deflected by a total inner reflection (TIR) lens having an outer contour with a paraboloidal surface of revolution centered around the center axis and defining a TIR lens focal point. The reflector focal point is in close

proximity to the TIR lens focal point. This method may be combined with any of the embodiments disclosed herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In the following, the invention will be described by way of example, without limitation of the general inventive concept, on examples of embodiment and with reference to the drawings.
- (2) FIG. 1 shows a sectional view of a first embodiment;
- (3) FIG. 2 shows details of the color mixing optic;
- (4) FIG. 3 shows a detail of the LED assembly;
- (5) FIG. 4 shows a side view of the LED assembly;
- (6) FIG. 5 shows ray traces of the embodiments;
- (7) FIG. 6 shows a lamp without TIR lens;
- (8) FIG. 7 shows the distribution of light intensity of the embodiments;
- (9) FIG. 8 shows the distribution of light intensity without TIR lens; and
- (10) FIG. 9 shows further details of the color mixing optic.
- (11) While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(12) In FIG. 1, a sectional view of a first embodiment is shown. A color mixing optic **10** comprises an outer reflector **21** which preferably is held in a housing **20**, or which may be a part thereof. It further comprises a total inner reflection (TIR) lens **40** which preferably is held by a cover **30** on or within the outer reflector **21** and/or the housing **20**. The TIR lens comprises a body of an optic material which may be plastic material or glass. It has an outer contour **41** which in one embodiment is defined by a paraboloidal surface of revolution about a center axis. In other embodiments, the outer contour **41** of the TIR lens **40** may be substantially conical in shape. In addition to the outer contour **41**, the TIR lens **40** preferably has a concave shaped light entrance surface **43** and a light exit surface **42**. The concave light entrance surface **43** preferably has a substantially spherical shape, and most preferably has a radius of curvature that enables light rays emitted by an LED assembly to pass through the concave light entrance surface **43** without refraction. The light exit surface **42** is preferably a planar surface, and most preferably is connected to and/or part of the cover **30**.

(13) An LED assembly **60** is attached to the outer reflector and/or the housing, preferably by a base **22**, although it may be held independently thereof. The LED assembly comprises a plurality of LEDs **61**, **62**. It preferably has a cover **50** which may be a protective cover and/or forming a LED lens. The LED assembly **60** may be mounted to a base which may be a printed circuit board and/or a heat sink. Preferably, the LED assembly is arranged on a common center axis **11** which preferably is the center axis of the outer reflector **21** and of the TIR lens **40**. Furthermore, it is preferred that the LED assembly is arranged at a common focal point of the outer reflector **21** and the TIR lens **40**, as will be shown later.

(14) In FIG. 2, details of the color mixing optic are shown. Preferably, the outer reflector **21** has a paraboloidal surface of revolution. It is defined by a revolution of the reflector parabola **28** around the center axis **11**. This parabola defines a reflector focal point **29**. The TIR lens **40** preferably has a paraboloidal surface of revolution defined by a TIR lens parabola **48**, which is revolved about the

center axis **11**, and which defines a TIR lens focal point **49**. Most preferably, the TIR lens focal point **49** is the same point as the reflector focal point **29**. It is further preferred, that the LED assembly is arranged close to or at the common focal point **29, 49**. Further details of the color mixing optic are shown in FIG. **9** and discussed below.

(15) In FIG. **3**, the LED assembly **60** is shown in detail. A plurality of LEDs **61-64** may be arranged on the LED assembly. There may be a printed circuit board holding the LEDs, which may be covered by a LED lens **50**. In this embodiment, there is a set of four LEDs comprising LEDs for red, green, and blue, as well as a phosphor-converted white LED for providing whites and pastels. It is preferred that a plurality of such sets of four LEDs is provided. In this embodiment, four of these sets are arranged in a 4×4 matrix. Preferably, this arrangement or this matrix is centered around the center axis **11**. It is further preferred that at least one sensor which may be a LED or a photodiode **65** is provided for measuring the emitted light intensity.

(16) In FIG. **4**, a side view of the LED assembly **60** is shown. Here, the convex shape of the LED lens **50** can be seen. Preferably, the geometrical and/or optical center of the LED assembly is aligned with the center axis **11**. The LEDs **61, 62, 63, 64** may be surface-mounted on a PCB **51**. These LEDs define a surface plane **52**, which may be the top surface and which preferably is the plane on which light of the LEDs is emitted. It is preferred that the intersection **53** of this plane **52** with the center axis **11** is located at the reflector focal points **29, 49**.

(17) In FIG. **5**, ray traces of a preferred embodiment of the color mixing optic **10** are shown. In this figure, for simplicity only rays originating from a first LED **61** and second LED **62** are shown. There is a first set of rays **71** originating from the LEDs **61, 62** and reflected by the outer reflector **21**. These rays are propagating approximately parallel to the center axis **11**. A second set of rays **72** is originating from the LEDs **61, 62** and reflected by the TIR lens **40**. As it can be seen, these rays are also propagating approximately parallel to the center axis **11** and having a comparatively small deviation. This is important for color mixing.

(18) To obtain a uniform color distribution, the rays originating by the individual LEDs **61, 62** should be projected to approximately the same point. In the embodiment of FIG. **6**, the displacement of the individual rays originating from LEDs **61** or **62** is mainly given by the spatial displacement of the LEDs on the LED assembly. It is not dependent on the wavelength of the light emitted by LEDs, since the outer reflector **21** and the TIR lens **40** are specifically designed to reflect light rays **71** and **72**, so that there is no refraction in the path of light. Providing a TIR lens **40** design that avoids refraction is important, since refraction changes the propagation path of the emitted light depending on the light wavelength.

(19) As shown in FIG. **6**, the light emitted from the LEDs **61, 62** propagates at a right angle through the spherical surface of the LED lens **50**. Due to the concave shaped light entrance surface **43** of the TIR lens **40**, the light enters the TIR lens at a right angle to the concave light entrance surface **43**, therefore avoiding refraction. Finally, the light exits the optic through the cover **30** at an approximately right angle to the planar surface of the cover **30**, further preventing any refraction. Avoiding any refraction is one of the fundamental points of these embodiments. The light from the LEDs **61, 62** is only reflected either by the outer reflector **21** or by the TIR lens **40**. As refraction typically is wavelength dependent, no compensation is required, keeping the design simple and inexpensive. Furthermore, deviations in the color distribution due to wavelength dependent effects are avoided.

(20) Finally, there are third set of rays **73** which propagate from LEDs **61, 62** via LED lens **50** through light entrance surface **43** and which are not reflected by the outer reflector **21** or the TIR lens **40**. As these rays propagate through the planar light exit surface **42** and/or the cover **30** at some angle other than 90°, there is refraction, leading to a deviation of the light rays with respect to the center axis **11**. However, this part of the light is only a small part of the total radiation of the LEDs. It is further distributed over a wide angle and mixes with the other light of the rays **71** and **72**. Therefore, it has a negligible effect on color distribution.

(21) The color mixing optic **10** shown in FIGS. **1**, **2**, and **5** significantly improves the color distribution throughout the beam pattern produced by the LEDs **61**, **62** by avoiding any refraction of light through the TIR lens **40**. This is achieved by: (a) co-locating and aligning the focal points **29**, **49** of the outer reflector **21** and the TIR lens **40** with the center axis **11**, which intersects the surface plane **52** of the LED assembly at center point **53**, (b) providing the TIR lens **40** with a spherical, concave light entrance surface **43**, which is also centered on the center axis **11**, and (c) dimensioning the TIR lens **40** so that no light rays can escape between the outer contour **41** of the TIR lens **40** and the outer reflector **21** without being collimated by the outer reflector. Exemplary dimensions for the TIR lens **40** are shown in FIG. **9** and discussed below.

(22) Generally speaking, the depth (d.sub.TIR) of the TIR lens **40** and the radius (r.sub.TIR) of the upper aperture of the TIR lens **40** are dependent on the depth (d) of the outer reflector **21** and the radii (r.sub.u, r.sub.b) of the upper and lower apertures of the outer reflector **21**. According to one embodiment, the radius (r.sub.TIR) of the upper aperture of the TIR lens **40** is made to be substantially equal to the radius (r.sub.b) of the lower aperture of the outer reflector **21**. This allows the TIR lens **40** to capture and collimate as much of the emitted light as possible without interfering with the first set of rays **71** (see, FIG. **5**) collimated by the outer reflector **21**.

(23) The depth (d.sub.TIR) of the TIR lens **40** is preferably designed so that no light rays can escape between the outer contour **41** of the TIR lens **40** and the outer reflector **21** without being collimated by the outer reflector **21**. In other words, the depth (d.sub.TIR) of the TIR lens **40** should be configured to intercept all light rays, which are emitted by the LED assembly **60** above a line extending between source point (0,0) and an edge point (r.sub.u, h) of the outer reflector **21**. In the exemplary embodiment shown in FIG. **9**, the depth (d.sub.TIR) of the TIR lens **40** extends to point (x,y), which is the point where the TIR lens parabola **48** intersects the line extending between source point (0,0) and edge point (r.sub.u, h). By configuring the TIR lens **40** as shown in FIG. **9**, the color mixing optic is able to collimate a vast majority of the emitted light while producing substantially uniform intensity and color distribution throughout the entire beam pattern.

(24) In FIG. **6**, ray traces from a lamp without a TIR lens is shown. Here, a first set of rays **71** are reflected by the outer reflector **21** and are radiated approximately parallel to the center axis **11**. The remaining rays **75** are radiated in all directions starting from the center to a very wide angle, resulting in a significantly wider pattern.

(25) In FIG. **7**, the distribution of light intensity of the embodiments is shown. If the light of the lamp is projected on a plane in some distance to the lamp, there will be a first approximately circular pattern **81** generated by the first set of rays **71** shown in FIG. **5**. A second set of rays **72** are shown in FIG. **7** forming a second pattern **82** at the center of the first pattern. The remaining rays **75** have a negligible intensity and are not shown herein. At the bottom of the figure, the intensity distribution is shown in a section of the previous image. Here, the intensity of the second pattern **82** is approximately the same as of the first pattern **81**, resulting in a uniform light distribution across the entire beam pattern.

(26) In FIG. **8**, the distribution of light intensity of the lamp without a TIR lens is shown. Due to the lacking TIR lens, the light of beams **75**, which is not reflected by the outer reflector **21**, is distributed over a wide area **85**, whereas the light at the center of the pattern **81** has a comparatively low intensity. This results in a beam pattern looking like a ring.

(27) It will be appreciated to those skilled in the art having the benefit of this disclosure that this invention is believed to provide optics for LED lighting with color mixing properties. Specifically, color mixing optics are disclosed herein for producing a uniform intensity distribution and a uniform color distribution throughout the entire beam pattern produced by a multi-color LED light source. Further modifications and alternative embodiments of various aspects of the invention will be apparent to those skilled in the art in view of this description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the general manner of carrying out the invention. It is to be understood that the forms of the invention

shown and described herein are to be taken as the presently preferred embodiments. Elements and materials may be substituted for those illustrated and described herein, parts and processes may be reversed, and certain features of the invention may be utilized independently, all as would be apparent to one skilled in the art after having the benefit of this description of the invention. Changes may be made in the elements described herein without departing from the spirit and scope of the invention as described in the following claims.

Claims

- . [1. A color mixing optics for LED lighting comprising: an outer reflector having a paraboloidal surface of revolution centered around a center axis and defining a reflector focal point; a total inner reflection lens having a concave light entrance surface with a radius of curvature to enable light to enter the total inner reflection lens at a right angle, and the total inner reflection lens having an outer contour with a paraboloidal surface of revolution centered around the center axis and defining a total inner reflection lens focal point, wherein the outer contour with a paraboloidal surface of revolution of the total inner reflection lens is held a spaced distance within the outer reflector; and wherein the reflector focal point is in close proximity to the total inner reflection lens focal point..].
- . [2. The color mixing optics according to claim 1, wherein the total inner reflection lens has a concave light entrance surface oriented towards the total inner reflection lens focal point..].
- . [3. The color mixing optics according to claim 2, wherein the concave light entrance surface has a spherical shape..].
- . [4. The color mixing optics according to claim 1, wherein the total inner reflection lens is positioned within the outer reflector..].
- . [5. The color mixing optics according to claim 1, wherein the total inner reflection lens is attached to a cover located on the outer reflector..].
- . [6. The color mixing optics according to claim 1, wherein the total inner reflection lens is part of a cover located on the outer reflector..].
- . [7. The color mixing optics of claim 1, wherein a radius of an upper aperture of the total inner reflection lens is substantially equal to a radius of a lower aperture of the outer reflector..].
- . [8. The color mixing optics of claim 1, wherein a depth of the total inner reflection lens extends to a point where the total inner reflection lens parabola intersects a line extending between a source point on the center axis and an edge point of the outer reflector..].
- . [9. A multi-color LED lamp comprising: an outer reflector having a paraboloidal surface of revolution centered around a center axis and defining a reflector focal point; a total inner reflection lens having a concave light entrance surface with a radius of curvature to enable light to enter the total inner reflection lens at a right angle, and the total inner reflection lens having an outer contour with a paraboloidal surface of revolution centered around the center axis and defining a total inner reflection lens focal point; wherein the outer contour with a paraboloidal surface of revolution of the total inner reflection lens is held a spaced distance within the outer reflector; wherein the reflector focal point is in close proximity to the total inner reflection lens focal point; and an LED assembly comprising a plurality of LEDs and being mounted in close proximity to the reflector focal point and the total inner reflection lens focal point..].
- . [10. The multi-color LED lamp according to claim 9, wherein the LED assembly or parts thereof are covered by a LED lens..].
- . [11. The multi-color LED lamp according to claim 10, wherein the LED lens has a spherical shape..].
- . [12. The multi-color LED lamp according to claim 9, wherein the LED assembly has a LED surface plane which is mounted in close proximity to the total inner reflection lens focal point..].
- . [13. The multi-color LED lamp according to claim 9, wherein the center of the LED assembly is mounted in close proximity to the center axis..].

.14. The multi-color LED lamp according to claim 9, wherein the LED assembly is mounted on a base..].

.15. The multi-color LED lamp according to claim 9, wherein a housing is provided surrounding the outer reflector..].

.16. The multi-color LED lamp according to claim 9, wherein the total inner reflection lens is attached to a cover located on the housing..].

.17. The multi-color LED lamp according to claim 9, wherein the total inner reflection lens is part of a cover located on the housing..].

.18. A method for generating a mixed beam of light by generating light at multiple wavelengths by a LED assembly comprising a plurality of LEDs and: reflecting a first portion of said light by an outer reflector having a paraboloidal surface of revolution centered around a center axis and defining a reflector focal point; while reflecting a second portion of said light forwarded from the plurality of LEDs at an angle relative to the center axis that is less than the first portion of said light forwarded from the plurality of LEDs, wherein the second portion is reflected from a total inner reflection lens having a concave light entrance surface with a radius of curvature to enable light to enter the total inner reflection lens at a right angle, and the total inner reflection lens having an outer contour with a paraboloidal surface of revolution centered around the center axis and defining a total inner reflection lens focal point; and wherein the reflector focal point is in close proximity to the total inner reflection lens focal point..].

.19. The method as recited in claim 18, wherein said reflecting consists of avoiding any refraction..].

.Iadd.20. A lamp comprising: a hollow parabolic reflective surface disposed about a central axis; a transparent cover member disposed coaxially along the central axis, proximate a first end of the hollow parabolic reflective surface; and a total internal reflection (TIR) lens having an external surface, the TIR lens disposed coaxially along the central axis inside the hollow parabolic reflective surface; wherein an exit surface of the TIR lens is disposed proximate the transparent cover; wherein the transparent cover member spaces the external surface of the TIR lens apart from the hollow parabolic reflective surface to provide a gap between the TIR lens and the reflective surface; wherein the TIR lens and the hollow parabolic reflective surface have a common focal point; and wherein the lamp is configured to accommodate a light-emitting diode (LED) light source disposed at the common focal point such that light emitted by the LED light source either: enters the TIR lens at a normal angle and passes through the TIR lens; or reflects from the hollow parabolic reflective surface without passing through the TIR lens. .Iaddend.

.Iadd.21. The lamp of claim 20 wherein the TIR lens comprises a conic frustum. .Iaddend.

.Iadd.22. The lamp of claim 20 wherein the TIR lens comprises a paraboloidal frustum. .Iaddend.

.Iadd.23. The lamp of claim 22 wherein an entrance surface of the TIR lens comprises a concave entrance surface and the exit surface of the TIR lens comprises a planar exit surface. .Iaddend.

.Iadd.24. The lamp of claim 23: wherein the hollow parabolic reflective surface includes: a lower aperture; and an upper aperture: and wherein a radius of the exit surface of the TIR lens is approximately equal to a radius of the lower aperture of the hollow parabolic reflective surface. .Iaddend.

.Iadd.25. The lamp of claim 24, wherein the transparent cover member is affixed to the exit surface of the TIR lens. .Iaddend.

.Iadd.26. The lamp of claim 24 wherein the transparent cover is formed integral with the TIR lens. .Iaddend.

.Iadd.27. The lamp of claim 23 wherein the LED light source includes: a light-emitting diode (LED) assembly having a central axis disposed coaxially with the TIR lens and the hollow parabolic reflective surface, the LED assembly including: a plurality of LEDs distributed as a matrix about the central axis; and a hemispherical lens disposed about the central axis, the hemispherical lens covering the plurality of LEDs, the hemispherical lens spaced apart from the

concave entrance surface of the TIR lens by an air gap. .Iaddend.

.Iadd.28. The lamp of claim 27 wherein the LED assembly comprises a planar LED array having a center point disposed at the common focal point of the TIR lens and the hollow parabolic reflective surface. .Iaddend.

.Iadd.29. The lamp of claim 28 wherein the LED assembly further comprises a photodiode disposed proximate the plurality of LEDs, the photodiode positioned such that the hemispherical lens covers the photodiode. .Iaddend.

.Iadd.30. The lamp of claim 29 wherein the plurality of LEDs and the photodiode are mounted on a common printed circuit board. .Iaddend.

.Iadd.31. The lamp of claim 30 wherein the plurality of LEDs comprises a 2×2 matrix of LEDs consisting of: one red LED, one blue LED, one green LED, and one white LED. .Iaddend.

.Iadd.32. A lamp comprising: a light-emitting diode (LED) array; a reflector adjacent to the LED array to collimate a portion of light emitted by the LED array; and a total internal reflection (TIR) lens coaxially disposed within the reflector, wherein the remaining portion of light emitted by the LED array enters the TIR lens without refraction and passes through the TIR lens, and wherein the TIR lens and the reflector have a common focal point. .Iaddend.

.Iadd.33. The lamp of claim 32, further comprising a transparent cover engaging an upper aperture of the reflector and an upper aperture of the TIR lens. .Iaddend.

.Iadd.34. The lamp of claim 33, wherein a radius of the upper aperture of the TIR lens is substantially equal to a radius of a lower aperture of the reflector. .Iaddend.

.Iadd.35. The lamp of claim 33, wherein a depth of the TIR lens extending from the cover toward the LED array is less than a depth of the reflector extending from the cover to the lower aperture of the reflector. .Iaddend.

.Iadd.36. The lamp of claim 35, wherein the depth of the TIR lens is sufficient to ensure the portion of light emitted by the LED array which does not pass through the TIR lens is collimated by the reflector. .Iaddend.

.Iadd.37. The lamp of claim 32, wherein the LED array, the reflector, and the TIR lens are each aligned along a common central axis. .Iaddend.

.Iadd.38. The lamp of claim 32, wherein the TIR lens has a concave light entrance. .Iaddend.

.Iadd.39. The lamp of claim 32, wherein an interior surface of the reflector is parabolic reflective surface. .Iaddend.
