

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402702
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hillebrecht; Luke et al.

Handle for hair styling tool with replaceable spring

Abstract

A hair styling tool or curling iron includes a handle portion and a styling portion. The handle portion houses a torsion spring. The styling portion includes a hair engaging member adapted to be biased toward the styling portion by the torsion spring. A spring door is releasably and/or removably connected to the handle portion and is configured to cover and at least partially secure the torsion spring within the handle portion. The torsion spring is not mechanically connected to the handle portion so that releasing and/or removing of the spring door from the handle portion allows for removal and replacement of the torsion spring.

Inventors: Hillebrecht; Luke (El Paso, TX), Koenemann; Gary (El Paso, TX), Fiebel; William C. (Succasunna, NJ)

Applicant: Helen of Troy Limited (St. Michael, BB)

Family ID: 79315433

Assignee: KAZ EUROPE SÁRL (Bussigny, CH)

Appl. No.: 18/077461

Filed: December 08, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230109480 A1	Apr. 06, 2023

Related U.S. Application Data

continuation parent-doc WO PCT/US2021/038001 20210618 PENDING child-doc US 18077461
us-provisional-application US 63211159 20210616
us-provisional-application US 63046755 20200701

Publication Classification

Int. Cl.: A45D1/00 (20060101)

U.S. Cl.:

CPC A45D1/00 (20130101);

Field of Classification Search

CPC: A45D (1/00); A45D (1/04); A45D (1/06); A45D (1/08); A45D (1/10); A45D (1/14); A45D (1/16); A45D (2001/002)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9232839	12/2015	Hein	N/A	A45D 1/28
2001/0035079	12/2000	Kesinger et al.	N/A	N/A
2011/0180096	12/2010	Palermo et al.	N/A	N/A
2013/0125909	12/2012	Meeks	N/A	N/A
2016/0374445	12/2015	Cho	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1020160074948	12/2015	KR	N/A
10-1714470	12/2016	KR	N/A
1020190079779	12/2018	KR	N/A

OTHER PUBLICATIONS

CN Office action & Search Report filed in CN 202180035352.9 dated Mar. 27, 2024. cited by applicant

International Search Report filed in PCT/US2021/038001 mailed Oct. 15, 2021. cited by applicant
Tt_zone. 'Let's repair a broken spring of the yes-beauty curling iron YB-377 35mm'. Jul. 3, 2019 [retrieved on Sep. 14, 2021]. Retrieved from the Internet: <URL: https://blog.naver.com/tt_zone/221577104237>. cited by applicant

Primary Examiner: Steitz; Rachel R

Attorney, Agent or Firm: RANKIN, HILL & CLARK LLP

Background/Summary

BACKGROUND

(1) There are numerous hair styling tools for heated styling of hair, and one example of such hair styling tools are curling irons. As is well known, curling irons impart a curl or pattern to hair being styled by sufficiently heating a barrel of a styling portion of the curling iron and restraining the hair

in physical contact with the heated barrel via a clamp or plate for a period of time. When the heat styled hair is removed from the heated barrel, the hair retains the shape of the curling iron's barrel. Typically, a torsion spring is provided to pivot the clamp from an open position to a closed position where the clamp is held against the barrel. However, over time and through continued use of the curling iron the torsion spring can break, and replacement of the torsion spring may be difficult. For example, existing curling irons generally require disassembly of the styling portion and/or handle portion to access the torsion spring. This may require removal of pins, fasteners, spacers, and other components of the curling iron, any number of which may be lost or misplaced. Because of this, many users simply discard the old curling iron, opting to purchase a new one.

SUMMARY

(2) According to one embodiment of the present disclosure, a hair styling tool or curling iron comprises a handle portion and a styling portion. The handle portion houses a torsion spring. The styling portion includes a hair engaging member adapted to be biased toward the styling portion by the torsion spring. A spring door is releasably and/or removably connected to the handle portion and is configured to cover and at least partially secure the torsion spring within the handle portion. The torsion spring is not mechanically connected to the handle portion so that releasing and/or removing of the spring door from the handle portion allows for removal and replacement of the torsion spring.

(3) According to another embodiment of the present disclosure, a hair styling tool or curling iron comprises a handle portion and a styling portion. The handle portion houses a barrel adapter. The styling portion is connected to the barrel adapter and includes a flipper pivotally connected to the barrel adapter. A torsion spring for biasing the flipper from an open position toward a closed position is removably housed in the handle portion. A spring door removably connected to one of the handle portion and the barrel adapter secures the torsion spring in the handle portion. The torsion spring is not mechanically connected to the handle portion so that removal of the spring door from the handle portion allows for unobstructed removal and replacement of the torsion spring.

(4) According to another aspect, the torsion spring is secured within the handle portion by being positioned between first and second spring mounts provided respectively on the flipper and the spring door, with one leg biased against the barrel adapter and another leg biased against the flipper.

(5) According to another aspect, the spring door includes one end portion fastened to the barrel adapter and an opposite end portion pivotally connected to the barrel adapter.

(6) According to another embodiment of the present disclosure, hair styling tool or curling iron comprises a handle portion and a styling portion. The handle portion houses a torsion spring. The styling portion includes a hair engaging member adapted to be biased toward the styling portion by the torsion spring. A spring door is releasably and/or removably connected to the handle portion. The spring door is configured to cover and at least partially secure the torsion spring within the handle portion. First and second spring mounts secure the torsion spring within the handle portion. The first spring mount is provided on the spring door so that releasing and/or removing of the spring door from the handle portion allows for removal and replacement of the torsion spring.

(7) According to another embodiment of the present disclosure, a method of removing a torsion spring from a hair styling tool or curling iron is provided. The hair styling tool or curling iron includes a handle portion adapted to house the torsion spring, and a styling portion connected to the handle portion and including a hair engaging member adapted to be biased toward the styling portion by the torsion spring. The method comprises providing a spring door on the handle portion for covering and at least partially securing the torsion spring within the handle portion; releasing and/or removing the spring door from the handle portion to provide direct access to the torsion spring; and removing the torsion spring from within the handle portion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a perspective view of an exemplary curling iron according to the present disclosure.
- (2) FIG. 2 is a cross-sectional view of the curling iron of FIG. 1.
- (3) FIG. 3 is a partial exploded perspective view of the curling iron of FIG. 1, showing a flipper connected to a barrel adapter.
- (4) FIG. 4 is a partial enlarged cross-sectional view of the flipper and barrel adapter of the curling iron of FIG. 2.
- (5) FIGS. 5 and 6 are enlarged partial cross-sectional views of the curling iron of FIG. 1.
- (6) FIG. 7 is an enlarged partial cross-sectional view of the curling iron of FIG. 1 according to another aspect of the present disclosure.

DETAILED DESCRIPTION

(7) It should, of course, be understood that the description and drawings herein are merely illustrative and that various modifications and changes can be made in the structures disclosed without departing from the present disclosure. Referring now to the drawings, wherein like numerals refer to like parts throughout the several views, FIG. 1 is a perspective view of a hair styling tool **100**, for example a curling iron, having a handle portion **102** and a styling portion **104**. The handle portion **102** can be defined by a housing **110** having a first or proximal end portion **112** and second or distal end portion **114**. A user control part **120** is coupled to the proximal end portion **112**, and the styling portion **104** is coupled to the distal end portion **114**. A power cord connector **122** for powering the curling iron is coupled to the user control part **120**; however, it should be appreciated that the curling iron **100** can be powered by, for example, a battery housed in the handle portion **102**. The styling portion **104** includes a barrel **126** and a hair engaging member or flipper **130** operably associated with the barrel. The barrel **126** has a first or proximal end portion **132** axially spaced from the housing **110** by the flipper **130** and a second or distal end portion **134**. An insulated tip (i.e., a cool tip) **138** can be connected to the distal end portion **134** of the barrel **126**, allowing for ease of handling during use of the curling iron **100**. As depicted, the flipper **130** includes a lever **140** connected to a clamp or plate **144**, and is movable from an open position to a closed position for positioning hair against the barrel **126**. Although, it should be appreciated that alternative configurations of the hair engaging member are contemplated.

(8) The operational components and features of the curling iron **100** will be described with reference to FIG. 2. According to the present disclosure, the housing **110**, which can be a two-part housing consisting of an upper or first housing part **148** and a lower or second housing part **150**, houses an electronic circuit board (e.g., printed circuit board (PCB) **154**) and an encoder **156**, which is electrically connected to the PCB. The PCB **154**, which can be fastened to one of the first housing part **148** and the second housing part **150**, is elongated along a length direction of the housing **110** such that the PCB **154** at least partially extends into the user control part **120** and a barrel adapter **164** located at the distal end portion **114** of the housing **110**. A power button **168**, preferably located at the distal end portion **114**, is electrically connected to the PCB **154**. A control knob **172** and a display screen or lens **174** are provided with the user control part **120**, each being electrically connected to the PCB **154**. The control knob **172** allows a user to select and control one or more of the operable features of the curling iron **100**, including a desired output temperature for the styling portion **104**. The encoder **156** is operable to detect rotational movement of the control knob **172**. The display lens **174** provides a visual indication of the operable features and/or the output temperature. The display lens **174** can be a liquid crystal display (LCD) although other display means, such as light emitting diode (LED) devices, may also be employed and are contemplated herein. The display lens **174** may optionally be equipped with a backlight to illuminate the display lens while the curling iron is switched on. It should also be appreciated that

internal electrical connections connect the internal circuitry of the PCB **154** to the power cord connector **122**.

(9) The barrel **126** of the styling portion **104** may be made of any thermally conductive material adapted to transfer heat from a heater assembly (not shown) located in the curling iron **100**. The barrel **126** may define a smooth cylindrical surface as shown or may have one or more raised or depressed thermally conductive surfaces located thereon including, e.g., transverse ribs, a helical rib, and a raised pattern to impart a decorative crimp or wave pattern onto the hair. The heater assembly may be any conventional heater assembly which can be incorporated within the barrel **126**. The PCB **154** may include circuitry to regulate the output temperature of the heater assembly, as selected by the control knob **172**.

(10) With reference to FIGS. 3-6, the barrel adapter **164**, which secures the styling portion **104** to the handle portion **102**, includes a body **180**, a curling iron stand **182**, and a connecting member **184**. The body **180** includes a base wall **188** and first and second side walls **192**, **194** extended upward from the base wall **188**. With the arrangement of the base and the sidewalls, the body **180** defines a channel **198** elongated along a length direction of the barrel adapter **164**. The first sidewall **192** includes a first mounting portion **202** adapted for the mounting of a first bearing cap **204**, and the second sidewall **194** includes a second mounting portion **206** adapted for the mounting of a second bearing cap **208**. As shown, the first and second mounting portions **202**, **206** are located at an end of the body **180** adjacent the stand **182**. The first and second mounting portions **202**, **206** together with the respective first and second bearing caps **204**, **208** rotationally support the flipper **130** on the handle portion **102**. By way of example, the first and second mounting portions **202**, **206** together with the respective first and second bearing caps **204**, **208** can define bosses that receive hubs on first and second flanges **220**, **222** depending from the lever **140** (only hub **224** on the first flange **220** is visible). With this arrangement, the flipper **130** is rotationally or pivotally connected to the barrel adapter **164**. The stand **182** axially separates the body **180** and the connecting member **184**. As depicted in FIG. 1, the stand **182** can be configured to as an extension of the lever **140** to enhance the aesthetics of the curling iron **100**. In FIG. 2, the connecting member **184** is received within the first end portion **132** of the barrel **126** and is configured to engage an inner surface of the barrel **126**, thereby securely retaining the barrel **126** on the barrel adapter **164**. Further depicted in FIGS. 3, 5 and 6, to properly align the barrel adapter **164** within the housing **110**, the first and second side walls **192**, **194** can include respective notches **230**, **232** which receive alignments tabs **234** depending from an inner surface of the upper housing part **148**.

(11) A torsion spring **240** housed in the handle portion **102** is adapted to bias the flipper **130** toward the styling portion **104**, and more particularly bias the flipper **130** from an open clamp position toward a closed clamp position where the clamp **144** is held against an outer surface of the barrel **126**. In the depicted embodiment, the torsion spring **240** is located at least partially in the channel **198** of the barrel adapter **164** adjacent the stand **182** with a coiled body **242** of the torsion spring seated on/between first and second spring mounts **244**, **246**. The first spring mount **244** is formed on a spring door **250** that is releasably and/or removably connected or fastened to one of the housing **110** and the barrel adapter **164**. As best depicted in FIGS. 4-6, according to one aspect, one end portion **252** of the door **250** includes a mounting boss **254** adapted to receive a fastener **256**. The mounting boss **254** is aligned with a corresponding mounting boss **262** depending from the base wall **188** of the body **180** of the barrel adapter **164**. The fastener **256** extends through the mounting boss **254**, an aperture **264** in the lower housing part **150**, and threadingly engages the mounting boss **262**. To further secure the door **250** to the barrel adapter **164**, an opposite end portion **268** of the door **250** is step-shaped and is received in a cutout or notch **270** located in the stand **182**. With the door properly secured to the barrel adapter **164**, an outer surface of the door conforms to and is continuous with an outer surface of the housing **110**. Further illustrated, the second spring mount **246** for the torsion spring **240** depends the lever **140**, particularly from a lever wall **272** that spans between the first and second flanges **220**, **222**. As shown in FIGS. 4-6, with the

torsion spring **240** positioned between the first and second spring mounts **244, 246**, one leg **280** of the torsion spring is biased against an inner surface portion **282** of the stand **182**, and the other leg **286** of the torsion spring is biased against an inner surface of the lever wall **272**. According to the depicted aspect, to maintain contact of the leg **280** with the inner surface portion **282**, a notch **290** sized to receive the leg **280** can be formed in the inner surface portion **282**. Therefore, in contrast to known designs which mechanically attach a torsion spring to a handle portion (e.g., by a pin extended through the spring), the torsion spring **240** is not mechanically connected to the respective components of the handle portion **102** and the styling portion **104**, thereby allowing a user to easily remove and replace a damaged spring simply by releasing and/or removing the spring door **250** from the handle portion **102**.

(12) FIG. 7 depicts another configuration of a spring door **300** for use with the curling iron **100**. Similar to the spring door **250** described above, the spring door **300** includes a first spring mount **304** for the torsion spring **240** and a mounting boss **306** adapted to receive the fastener **256**. An end portion **310** of the spring door **300** is also step-shaped and is received in the cutout or notch **270** located in the stand **182**. The spring door **300** further includes a stop **314** located adjacent the first spring mount **304** for the hair engaging member **130**. As shown, upon opening of the hair engaging member **130**, an end wall **320** depending from the lever wall **272** abuts the stop **314** to define a fully open position of the hair engaging member **130**. With use of the stop **314**, over-pivoting of the hair engaging member **130** which may damage the torsion spring **240** can be prevented.

(13) Accordingly, the present disclosure provides a hair styling tool or curling iron **100** comprising the handle portion **102** and the styling portion **104**. The handle portion **102** houses the torsion spring **240**. The styling portion **104** includes the hair engaging member **130** adapted to be biased toward the styling portion **104** by the torsion spring **240**. The spring door **250, 300** is releasably and/or removably connected to the handle portion **102** and is configured to cover and at least partially secure the torsion spring **240** within the handle portion **102**. The torsion spring **240** is not mechanically connected to the handle portion **102** so that releasing and/or removing of the spring door **250** from the handle portion **102** allows for removal and replacement of the torsion spring **240**.

(14) As is evident from the foregoing, a method of removing the torsion spring **240** from the hair styling tool or curling iron **100** is provided. The exemplary method generally comprises providing the spring door **250, 300** on the handle portion **102** for covering and at least partially securing the torsion spring **240** within the handle portion; releasing and/or removing the spring door **250, 300** from the handle portion **102** to provide direct access to the torsion spring **240**; and removing the torsion spring **240** from within the handle portion **102**. The method includes securing the torsion spring **240** between the first spring mount **244, 304** and the second spring mount **246**, with one of the first and second spring mounts provided on the spring door. The method includes housing the barrel adapter **164** within the handle portion **102**, connecting the styling portion **104** to the barrel adapter, and releasably securing the spring door **250, 300** to the barrel adapter **164**. The method includes providing an opening in the barrel adapter **164** for passage of the torsion spring **240** upon release and/or removal of the spring door **250, 300**. With the torsion spring **240** positioned between the first and second spring mounts, the method includes biasing one leg **280** of the torsion spring **240** against an inner surface portion of the barrel adapter **164** and biasing the other leg **186** of the torsion spring **240** an inner surface of one of the housing portion **102** and the styling portion **104**.

(15) The present disclosure further provides a method of removing and replacing a damaged torsion spring from the hair styling tool or curling iron **100**. According to the exemplary method, the fastener **256** is first removed, disconnecting the spring door **250, 300** from one of the handle portion **102** and the barrel adapter **164**. Once removed, the spring door can be pivoted downward about the step-shaped end portion **268, 310** received in the cutout **270** and then, optionally, completely removed or separated from the housing **110**. The releasing and/or removal of the spring door **250, 300** (and, in turn, the first spring mount **244, 304** integral with the spring door) provides

direct access to the torsion spring **240**—now only held at least partially within the channel **198** of the barrel adapter **164** by the legs **280, 286** biased against the stand **182** and lever wall **272**. The user can then simply, for example, tap the handle portion **102** against a hard surface to displace one of the legs (assuming both legs are still intact with the coiled body of the damaged torsion spring), allowing the torsion spring **240** to fall out of the handle portion. A replacement torsion spring can then be repositioned in the channel **198**, with the respective legs **280, 286** biased against the stand **182** and the lever wall **274** of the flipper **130** in its closed position. The door **250, 300** can then be fastened to the barrel adapter **164**, which secures the coiled body of the new torsion spring **240** between the first and second spring mounts. In this manner, the damaged torsion spring **240** can be removed from the curling iron **100** and replaced without disassembling the handle portion **102** and/or the styling portion **104**.

(16) It will be appreciated that the above-disclosed embodiments and other features and functions, or alternatives or varieties thereof, may be desirably combined into many other different systems or applications. Also that various presently unforeseen or unanticipated alternatives, modifications, variations or improvements therein may be subsequently made by those skilled in the art which are also intended to be encompassed by the following claims.

Claims

1. A hair styling tool or curling iron comprises: a handle portion housing a torsion spring; and a styling portion including a hair engaging member adapted to be biased toward the styling portion by the torsion spring; and a spring door releasably and/or removably connected directly to the handle portion, the spring door configured to cover and at least partially secure the torsion spring housed within the handle portion, wherein the torsion spring is not mechanically connected to the handle portion so that releasing and/or removing of the spring door from the handle portion allows for removal and replacement of the torsion spring.
2. The hair styling tool or curling iron of claim 1, including a barrel adapter housed within the handle portion, the styling portion connected to the barrel adapter, and the spring door is releasably connected to the barrel adapter.
3. The hair styling tool or curling iron of claim 2, wherein the hair engaging member is pivotally connected to the barrel adapter.
4. The hair styling tool or curling iron of claim 3, wherein the spring door includes a stop, and the hair engaging member abuts the stop in an open position of the hair engaging member.
5. The hair styling tool or curling iron of claim 2, wherein the barrel adapter includes a body and a stand extended from the body, the spring door is engaged to both the body and the stand.
6. The hair styling tool or curling iron of claim 1, including first and second spring mounts adapted to secure the torsion spring within the handle portion.
7. The hair styling tool or curling iron of claim 6, wherein the first spring mount is provided on the spring door and the second spring mount is provided on one of the handle portion and the styling portion.
8. The hair styling tool or curling iron of claim 7, wherein the second spring mount is provided on the styling portion.
9. The hair styling tool or curling iron of claim 8, wherein the second spring mount is provided on the hair engaging member of the styling portion.
10. The hair styling tool or curling iron of claim 6, wherein the torsion spring is seated between the first and second spring mounts, and further including a barrel adapter housed within the handle portion, the barrel adapter including a body adapted to at least partially receive the torsion spring.
11. The hair styling tool or curling iron of claim 10, wherein with the torsion spring seated between the first and second spring mounts, one leg of the torsion spring is biased against an inner surface portion of the barrel adapter, and the other leg of the torsion spring is biased against an inner

surface of one of the handle portion and the styling portion.

12. The hair styling tool or curling iron of claim 11, wherein the inner surface portion includes a notch sized to receive the one leg.

13. A hair styling tool or curling iron comprises: a handle portion housing a torsion spring; and a styling portion including a hair engaging member adapted to be biased toward the styling portion by the torsion spring; and a spring door releasably and/or removably connected to the handle portion, the spring door configured to cover and at least partially secure the torsion spring within the handle portion, wherein first and second spring mounts secure the torsion spring within the handle portion, the first spring mount provided on the spring door so that releasing and/or removing of the spring door from the handle portion allows for removal and replacement of the torsion spring.

14. The hair styling tool or curling iron of claim 13, wherein the second spring mount is provided on one of the handle portion and the styling portion.

15. The hair styling tool or curling iron of claim 13, including a barrel adapter housed within the handle portion, the styling portion connected to the barrel adapter, and the spring door is releasably connected to the barrel adapter.

16. The hair styling tool or curling iron of claim 15, wherein the barrel adapter includes a body and a stand extended from the body, the spring door is engaged to both the body and the stand.

17. A method of removing a torsion spring from a hair styling tool or curling iron, the hair styling tool or curling iron including: a handle portion adapted to house the torsion spring, and a styling portion connected to the handle portion and including a hair engaging member adapted to be biased toward the styling portion by the torsion spring, the method comprises: providing a spring door directly on the handle portion for covering and at least partially securing the torsion spring within the handle portion; releasing and/or removing the spring door from the handle portion to provide direct access to the torsion spring; and removing the torsion spring from within the handle portion.

18. The method of claim 17, including securing the torsion spring between first and second spring mounts, with one of the first and second spring mounts provided on the spring door.

19. The method of claim 17, including housing a barrel adapter within the handle portion, connecting the styling portion to the barrel adapter, and releasably securing the spring door to the barrel adapter.

20. The method of claim 19, including providing an opening in the barrel adapter for passage of the torsion spring upon release and/or removal of the spring door.

21. The method of claim 19, wherein with the torsion spring positioned between the first and second spring mounts, the method includes biasing one leg of the torsion spring against an inner surface portion of the barrel adapter and biasing the other leg of the torsion spring an inner surface of one of the housing portion and the styling portion.
