

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402767
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Choi; Byoungsuk

Method for controlling robot cleaner

Abstract

The present disclosure relates to a method for controlling a robot cleaner and, more particularly, to a method for controlling a robot cleaner including a plurality of obstacle detection sensors, the method for controlling the robot cleaner to execute the operations comprising: a first step for approaching a charging device for the robot cleaner according to an IR signal transmitted from the charging device for the robot cleaner including a charging terminal for charging the robot cleaner; a second step for checking whether the shortest distance between the robot cleaner and the charging device for the robot cleaner is less than or equal to a first distance through the plurality of obstacle detection sensors; a third step for checking whether the center lines of the robot cleaner and the charging device for the robot cleaner are aligned through the plurality of obstacle detection sensors, and aligning the center lines of the robot cleaner and the charging device for the robot cleaner; and a fourth step for, when the center lines of the robot cleaner and the charging device for the robot cleaner have been aligned, moving the robot cleaner straight toward the charging device for the robot cleaner.

Inventors:	Choi; Byoungsuk (Seoul, KR)
Applicant:	LG ELECTRONICS INC. (Seoul, KR)
Family ID:	79315426
Assignee:	LG ELECTRONICS INC. (Seoul, KR)
Appl. No.:	18/013430
Filed (or PCT Filed):	October 06, 2020
PCT No.:	PCT/KR2020/013543
PCT Pub. No.:	WO2022/004949
PCT Pub. Date:	January 06, 2022

Prior Publication Data

Foreign Application Priority Data

KR 10-2020-0081415 Jul. 02, 2020

Publication Classification

Int. Cl.: A47L11/40 (20060101); G05D1/00 (20240101)

U.S. Cl.:

CPC A47L11/4011 (20130101); G05D1/0225 (20130101); G05D1/0238 (20130101); G05D1/0242 (20130101); A47L2201/02 (20130101); A47L2201/022 (20130101); A47L2201/04 (20130101); A47L2201/06 (20130101)

Field of Classification Search

CPC: A47L (11/4011); A47L (2201/02); A47L (2201/022); A47L (2201/04); A47L (2201/06); A47L (9/2852); A47L (11/4061); A47L (9/2805); A47L (9/2873); G05D (1/0225); G05D (1/0238); G05D (1/0242)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11199853	12/2020	Afrouzi	N/A	B25J 13/006
11274929	12/2021	Afrouzi	N/A	G06T 7/30
2007/0271011	12/2006	Lee	901/1	G05D 1/028
2012/0296511	12/2011	More et al.	N/A	N/A
2016/0271795	12/2015	Vicenti	N/A	G05D 1/644
2017/0344014	12/2016	Wu	N/A	G05D 1/0225
2019/0121361	12/2018	Afrouzi	N/A	G01C 21/206
2019/0196489	12/2018	Xiong	N/A	G05D 1/0225
2020/0004263	12/2019	Dalla Libera	N/A	G01S 7/4808
2020/0030982	12/2019	Xiong	N/A	G05D 1/0242
2020/0093342	12/2019	Jeong	N/A	A47L 11/4005
2020/0150676	12/2019	Huang	N/A	G05D 1/0236
2021/0146552	12/2020	Hong	N/A	A47L 9/2852
2022/0129002	12/2021	Li	N/A	G05D 1/0274
2022/0374022	12/2021	Chen	N/A	G05D 1/0225
2023/0030855	12/2022	Lundkvist	N/A	G05D 1/0265

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2008-181177	12/2007	JP	N/A
10-2004-0081629	12/2003	KR	N/A
10-2010-0136904	12/2009	KR	N/A
10-1080366	12/2010	KR	N/A

Primary Examiner: Khayer; Sohana Tanju

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is the National Phase of PCT International Application No. PCT/KR2020/013543, filed on Oct. 6, 2020, which claims priority under 35 U.S.C. 119 (a) to Patent Application No. 10-2020-0081415, filed in the Republic of Korea on Jul. 2, 2020, all of which are hereby expressly incorporated by reference into the present application.

TECHNICAL FIELD

(2) The present disclosure relates to a control method of a robot cleaner. More particularly, the present disclosure relates to a control method of a robot cleaner for performing a proximity docking operation using an obstacle detection sensor.

BACKGROUND ART

(3) In general, a robot cleaner is a cleaning device that sucks dust and a foreign substance from a floor surface while traveling a certain range of work areas without user manipulation, and a cleaning work is performed by determining the position of an obstacle or a wall through a sensor, a camera, or the like and avoiding the obstacle and the wall using the determined information while the robot cleaner travels.

(4) After the cleaning work is performed, the robot cleaner moves to a robot cleaner charging device for charging, and according to a conventional robot cleaner control method, the robot cleaner receives an IR signal transmitted from the robot cleaner charging device and moves.

(5) In this regard, Korean Patent Publication 20100136904 A (hereinafter referred to as Cited Reference 1) discloses a control method for detecting the position of a robot cleaner using three IR LEDs and inducing the robot cleaner to approach the center of a charging device for the robot cleaner, but since the robot cleaner control method using the IR signal is greatly affected by indoor lighting, sunlight, etc., it is difficult to control a detailed operation of the robot cleaner, and the intensity of the IR signal has the maximum intensity and it is impossible to distinguish a specific area of the robot cleaner charging device in a state in which the robot cleaner and the robot cleaner charging device are close to each other, and accordingly, there is a disadvantage in that docking for charging the robot cleaner and the robot cleaner charging device is not precisely performed.

(6) Korean Patent Publication 20180079054 A (hereinafter referred to as Cited Reference 2) discloses that the robot cleaner is docked to the robot cleaner charging device at a close distance through the patterns and the 3D sensor by applying black and white color patterns to a front surface of a robot cleaner charging device and applying a 3D sensor including an IR line laser and a camera to the robot cleaner. However, in the Cited Reference 2, since the 3D sensor applied to the robot cleaner requires high cost and the patterns need to be applied to all front surfaces of the robot cleaner charging device, inefficient cost expenditure is disadvantageously required.

DISCLOSURE

Technical Problem

(7) One of various objects of the present disclosure is to provide a control method of controlling a detailed operation using an obstacle detection sensor.

Technical Solution

(8) According to exemplary embodiments of the present disclosure, a control method of a robot cleaner includes a first operation in which a robot cleaner including a plurality of obstacle detection sensors approaches the robot cleaner charging device according to an IR signal transmitted from a charging terminal for charging the robot cleaner, a second operation of checking whether a shortest distance between the robot cleaner and the robot cleaner charging device is equal to or less than a first distance, a third operation of checking whether center lines of the robot cleaner and the robot cleaner charging device are aligned through the plurality of obstacle detection sensors and aligning the center lines of the robot cleaner and the robot cleaner charging device, and a fourth operation in which the robot cleaner moves straight toward the robot cleaner charging device when the center lines of the robot cleaner and the robot cleaner charging device are aligned.

(9) The control method of the robot cleaner may further include a fifth operation of checking whether the minimum distance between the robot cleaner and the robot cleaner charging device is equal to or less than a second distance smaller than the first distance in a state in which the center lines of the robot cleaner and the robot cleaner charging device are aligned, a sixth operation of checking whether a difference in direction angle occurs between the robot cleaner and the robot cleaner charging device through the plurality of obstacle detection sensors and correcting the difference in direction angle between the robot cleaner and the robot cleaner charging device, and a seventh operation in which the robot cleaner and the charging terminal come into contact when direction angles of the robot cleaner and the robot cleaner charging device are corrected.

(10) According to exemplary embodiments of the present disclosure, a control method of a robot cleaner includes a first operation in which the robot cleaner including a plurality of obstacle detection sensors approaches the robot cleaner charging device according to an IR signal transmitted from a robot cleaner charging device including a charging terminal for charging the robot cleaner, a second operation of checking whether a shortest distance between the robot cleaner and the robot cleaner charging device is equal to or less than a first distance through the plurality of obstacle detection sensors, a third operation of checking whether center lines of the robot cleaner and the robot cleaner charging device are aligned through the plurality of obstacle detection sensors and aligning the center lines of the robot cleaner and the robot cleaner charging device, and a fourth operation in which the robot cleaner moves straight toward the robot cleaner charging device when the center lines of the robot cleaner and the robot cleaner charging device are aligned.

(11) In the third operation, whether the center lines of the robot cleaner and the robot cleaner charging device are aligned may be determined through a distance measurement value of an obstacle detection sensor that detects a position of the robot cleaner charging device and a distance measurement value of an obstacle detection sensor that does not detect the position of the robot cleaner charging device.

(12) In the third operation, when a distance measurement value of an obstacle detection sensor adjacent to an obstacle detection sensor that detects a position of the robot cleaner charging device is greater than a distance measurement value of the obstacle detection sensor that detects the position of the robot cleaner charging device, one end of the robot cleaner charging device is determined to be located between the obstacle detection sensors, and a center separation distance between the center line of the robot cleaner and the center line of the robot cleaner charging device may be estimated based on a position of the one end of the robot cleaner charging device through a 2D Cartesian coordinate system using a center of the robot cleaner as an origin.

(13) In the third operation, when an absolute value of the center separation distance is smaller than a specific value, the center lines of the robot cleaner and the robot cleaner charging device may be determined to be aligned, and when the absolute value of the center separation distance is greater than the specific value, the center lines of the robot cleaner and the robot cleaner charging device may be determined not to be aligned.

(14) In the third operation, when a value of the center separation distance is a positive value, the robot cleaner may be determined to be located to a left from the center line of the robot cleaner

charging device, and when the value of the center separation distance is a negative value, the robot cleaner may be determined to be located to a right from the center line of the robot cleaner charging device.

(15) The plurality of obstacle detection sensors may include a pair of first obstacle detection sensors for detecting a side obstacle, and a second obstacle detection sensor disposed between the pair of first obstacle detection sensors and provided to detect a forward obstacle, and in the third operation, whether the center lines of the robot cleaner and the robot cleaner charging device are aligned may be determined according to whether the first obstacle detection sensor and the second obstacle detection sensor detect the robot cleaner charging device.

(16) In the third operation, a state in which only the second obstacle detection sensor among the plurality of obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the center lines of the robot cleaner and the robot cleaner charging device are aligned

(17) In the third operation, a state in which at least one first obstacle detection sensor among the pair of first obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the center lines of the robot cleaner and the robot cleaner charging device are determined not to be aligned.

(18) In the third operation, a state in which only the first obstacle detection sensor disposed on a right among the pair of first obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the center line of the robot cleaner is spaced apart from the center line of the robot cleaner charging device to a left.

(19) In the third operation, when the center line of the robot cleaner is determined to be spaced apart from the center line of the robot cleaner charging device to the left, the robot cleaner may move to a right.

(20) In the third operation, a state in which only the first obstacle detection sensor disposed on a left among the pair of first obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the center line of the robot cleaner is spaced apart from the center line of the robot cleaner charging device to a right.

(21) In the third operation, when the center line of the robot cleaner is determined to be spaced apart from the center line of the robot cleaner charging device to the right, the robot cleaner may move to a left.

(22) The method may further include a fifth operation of checking whether the shortest distance between the robot cleaner and the robot cleaner charging device is equal to or less than a second distance smaller than the first distance in a state in which the center lines of the robot cleaner and the robot cleaner charging device are aligned, a sixth operation of checking whether a difference in direction angle occurs between the robot cleaner and the robot cleaner charging device through the plurality of obstacle detection sensors and correcting the difference in the direction angle between the robot cleaner and the robot cleaner charging device, and a seventh operation in which in which the robot cleaner and the charging terminal come into contact when direction angles of the robot cleaner and the robot cleaner charging device are corrected.

(23) In the sixth operation, whether the difference in direction angle occurs between the robot cleaner and the robot cleaner charging device may be determined using a smallest distance measurement value among distance measurement values of obstacle detection sensors that detect a position of the robot cleaner charging device and a distance measurement value closest to the smallest distance measurement value.

(24) The plurality of obstacle detection sensors include a pair of first obstacle detection sensors for detecting a side obstacle, and a second obstacle detection sensor disposed between the pair of first obstacle detection sensors and provided to detect a forward obstacle, and in sixth operation, whether the difference in direction angle occurs between the robot cleaner and the robot cleaner charging device may be determined according to whether at least one of the pair of first obstacle

detection sensors detects the robot cleaner charging device.

(25) In the sixth operation, a state in which only the first obstacle detection sensor disposed on a right among the pair of first obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the difference in direction angle in a counterclockwise direction occurs between the robot cleaner and the center line of the robot cleaner charging device by a specific angle.

(26) In the sixth operation, when the difference in direction angle in the counterclockwise direction is determined to occur between the robot cleaner and the center line of the robot cleaner charging device by the specific angle, the robot cleaner may rotate in a clockwise direction to correct the difference in direction angle.

(27) In the sixth operation, only the first obstacle detection sensor disposed to a left among the pair of first obstacle detection sensors detects the robot cleaner charging device may be determined as a state in which the difference in direction angle in a clockwise direction occurs between the robot cleaner and the center line of the robot cleaner charging device by a specific angle.

(28) In the sixth operation, when the difference in direction angle in the clockwise direction is determined to occur between the robot cleaner and the center line of the robot cleaner charging device by the specific angle, the robot cleaner may rotate in a counterclockwise direction to correct the difference in direction angle.

Advantageous Effects

(29) In a control method of a robot cleaner according to exemplary embodiments of the present disclosure, remote docking of a robot cleaner including an obstacle detection sensor may be performed according to an IR signal generated from a robot cleaner charging device, and then short-distance docking of the robot cleaner may be additionally performed through the obstacle detection sensor in a state in which the robot cleaner is close to the robot cleaner charging device.

(30) Short-distance docking of the robot cleaner through the obstacle detection sensor may not be affected by external environments, such as indoor lighting and sunlight, and a disadvantage that it is difficult to distinguish a specific area of the robot cleaner charging device according to the maximum intensity of the IR signal may be overcome. Accordingly, short-distance docking for charging the robot cleaner and the robot cleaner charging device may be precisely performed.

Description

DESCRIPTION OF DRAWINGS

(1) FIGS. 1 and 2 are diagrams for explaining a robot cleaner according to an embodiment of the present disclosure.

(2) FIG. 3 is a diagram for explaining a robot cleaner charging device according to an embodiment of the present disclosure.

(3) FIGS. 4 and 5 are diagrams for explaining an obstacle detection sensor of a robot cleaner according to exemplary embodiments of the present disclosure.

(4) FIGS. 6 and 7 are diagrams for explaining a method of aligning a center line of a robot cleaner according to an embodiment of the present disclosure.

(5) FIGS. 8 and 9 are diagrams for explaining a method of correcting a direction angle of a robot cleaner according to an embodiment of the present disclosure.

(6) FIG. 10 is a flowchart for explaining a method of aligning a center line of a robot cleaner according to an embodiment of the present disclosure.

(7) FIG. 11 is a flowchart for explaining a method of correcting a direction angle of a robot cleaner according to an embodiment of the present disclosure.

BEST MODE

(8) Hereinafter, specific embodiments of the present disclosure will be described with reference to

the drawings. The following detailed description is provided to provide a comprehensive understanding of the methods, apparatus, and/or systems described herein. However, this is merely an example and the present disclosure is not limited thereto.

(9) In the following description of the present disclosure, a detailed description of known technology incorporated herein will be omitted when it may make the subject matter of the present disclosure unclear. The terms used in the specification are defined in consideration of functions used in the present disclosure, and may be changed according to the intent or conventionally used methods of clients, operators, and users. Accordingly, definitions of the terms should be understood on the basis of the entire description of the present specification. The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the present disclosure. As used herein, unless explicitly used otherwise, expressions in the singular include the meaning of the plural. In this description, expressions such as “comprising” or “including” are intended to indicate certain features, numbers, steps, operations, elements, some or a combination thereof, and but do not preclude the presence or addition of one or more other features, numbers, steps, operations, elements, some or a combination thereof.

(10) It will be understood that, although the terms first, second, A, B, (a), (b), etc. may be used herein to describe various elements of the present disclosure, these terms are only used to distinguish one element from another element and essential, order, or sequence of corresponding elements are not limited by these terms.

(11) FIGS. **1** and **2** are diagrams for explaining a robot cleaner according to an embodiment of the present disclosure. In more detail, FIG. **1** is a perspective view for explaining an overall appearance of the robot cleaner. FIG. **2** is a bottom view for explaining a lower structure of a robot cleaner.

(12) Referring to FIGS. **1** and **2**, a robot cleaner **100** may include a main body **110**. Hereinafter, in defining each part of the main body **110**, a part facing a ceiling in a traveling area is defined as an upper surface part, a part facing the floor in the traveling area is defined as a bottom surface part, and a part facing a traveling direction of parts constituting a circumference of the main body **110** between the upper surface part and the lower surface part is defined as a front part. In addition, a part facing an opposite direction from the front surface part of the main body **110** is defined as a rear surface part. The main body **110** may include a case **111** defining a space in which various parts constituting the robot cleaner **100** are accommodated.

(13) The robot cleaner **100** may include a sensing part **130** that performs detection to obtain the current state information. The sensing part **130** may detect a surrounding situation of the robot cleaner **100** while the robot cleaner **100** travels, and the sensing part **130** may also detect a state of the robot cleaner **100**.

(14) The sensing part **130** may detect information about a traveling zone. The sensing part **130** may detect obstacles such as walls, furniture, and cliffs on the driving surface. The sensing part **130** may detect a robot cleaner charging device **200** to be described later. The sensing part **130** may detect information about the ceiling. Through information detected by the sensing part **130**, the robot cleaner **100** may map a traveling zone.

(15) The sensing part **130** may include at least one of an obstacle detection sensor **131**, a cliff detection sensor **132**, an external signal detection sensor (not shown), a shock detection sensor (not shown), an image detection sensor **138**, 3D sensors **138a**, **139a**, and **139b**, or a docking detection sensor.

(16) The sensing part **130** may include the obstacle detection sensor **131** for detecting a distance to a surrounding object. The obstacle detection sensor **131** may be disposed on a front part of the body **110** or may be disposed on a side part. The obstacle detection sensor **131** may detect surrounding obstacles. The obstacle detection sensor **131** may be provided in plurality.

(17) Although FIG. **2** shows that the two obstacle detection sensors **131** are provided on the front or side part of the robot cleaner **100**, the concept of the present disclosure is not necessarily limited thereto. That is, the obstacle detection sensor **131** may be provided on the front and side parts of the

robot cleaner **100**, respectively, and the number of the obstacle detection sensors **131** may also not be limited.

(18) For example, the obstacle detection sensor **131** may be an infrared sensor having a light emitter and a light receiver, an ultrasonic sensor, an RF sensor, a geomagnetic sensor, and the like. The obstacle detection sensor **131** may be implemented using ultrasonic waves or infrared rays. The obstacle detection sensor **131** may be implemented using a camera. The obstacle detection sensor **131** may be implemented with two or more types of sensors.

(19) The obstacle detection sensor **131** may also be referred to as a distance detection sensor **131**.

(20) The sensing part **130** may include a cliff detection sensor **132** that detects obstacles on the floor within the traveling area. The cliff detection sensor **132** may detect whether a cliff exists on the floor.

(21) The cliff detection sensor **132** may be provided in plurality and may be disposed on the bottom surface part of the robot cleaner **100**.

(22) The cliff detection sensor **132** may be an infrared ray sensor, an ultrasonic sensor, an RF sensor, a Position Sensitive Detector (PSD), or the like, which includes a light emitter and a light receiver. For example, the cliff detection sensor may be a PSD sensor, but may also include a plurality of different types of sensors. The PSD sensor may include a light emitter that emits infrared rays on obstacles and a light receiver that receives infrared rays reflected from obstacles.

(23) The sensing part **130** may include the shock detection sensor for detecting an impact caused by the robot cleaner **100** coming into contact with an external object.

(24) The sensing part **130** may include the external signal detection sensor for detecting a signal emitted from the outside of the robot cleaner **100**. The external signal detection sensor may include at least one of an infrared ray sensor for detecting an infrared ray signal from the outside, an ultrasonic sensor for detecting an ultrasonic wave signal from the outside, or a Radio Frequency (RF) Sensor for detecting an RF signal from the outside.

(25) The sensing part **130** may include the image detection sensor **138** for detecting an image of the outside of the robot cleaner **100**.

(26) The image detection sensor **138** may include a digital camera. The digital camera may include an image sensor (e.g., CMOS image sensor) including at least one optical lens and a plurality of photodiodes (e.g., pixels) forming an image by light passing through the optical lens, and a digital signal processor (DSP) configuring an image based on signals output from the photodiodes. The DSP may generate not only a still image, but also a moving image including frames configured with still images.

(27) The image detection sensor **138** may include a front image sensor **138a** for detecting a forward image of the robot cleaner **100**. The front image sensor **138a** may detect an image of a nearby object, such as an obstacle or the robot cleaner charging device **200**.

(28) The image detection sensor **138** may include an upward image sensor **138b** for detecting an upward image of the robot cleaner **100**. The upper image sensor **138b** may detect an image of a ceiling or a lower surface of furniture disposed above the robot cleaner **100**.

(29) The image detection sensor **138** may include a downward image sensor **138c** for detecting a downward image of the robot cleaner **100**. The downward image sensor **138c** may detect an image of the floor.

(30) The image detection sensor **138** may include a sensor for detecting images from the side or the rear.

(31) The sensing part **130** may include the 3D sensors **138a**, **139a**, and **139b** that detect 3D information of an external environment.

(32) The 3D sensors **138a**, **139a**, and **139b** may include a 3D depth camera **138a** that calculates a near distance of the robot cleaner **100** and an object to be photographed.

(33) In the present embodiment, the 3D sensors **138a**, **139a**, and **139b** may include a pattern emitter **139** that emits a predetermined pattern of light toward the body **110**, and the front image sensor

138a that acquires an image of the front of the body **110**. The pattern emitter **139** may include a first pattern emitter **139a** for emitting light of a first pattern toward a lower side of the front of the body **110**, and a second pattern emitter **139b** for emitting light of a second pattern toward an upper side of the front of the body **110**. The front image sensor **138a** may acquire an image of an area where the light of the first pattern and the light of the second pattern are incident.

(34) The pattern emitter **139** may be provided to emit an infrared ray pattern.

(35) In this case, the front image sensor **138a** may measure a distance between the 3D sensor and the object to be photographed by capturing a shape of the infrared ray pattern projected onto the object to be photographed.

(36) The light of the first pattern and the light of the second pattern may be emitted in the form of straight lines intersecting each other. The light of the first pattern and the light of the second pattern may be emitted in the form of horizontal straight lines spaced vertically.

(37) The sensing part **130** may include a docking detection sensor (not shown) that detects whether or not docking of the robot cleaner **100** is successful with respect to the robot cleaner charging device **200**. The docking detection sensor may be implemented to be detected by contact between the corresponding terminal **190** and the charging terminal **215** or may be implemented as a detection sensor disposed separately from the corresponding terminal **190**, and may be implemented by detecting the charging state of the battery **177** during charging. A docking success state and a docking failure state may be detected by the docking detection sensor.

(38) The robot cleaner **100** may include the battery **177** for supplying driving power to each component. The battery **177** may supply power for the robot cleaner **100** to perform an action according to selected action information. The battery **177** may be mounted on the body **110**. The battery **177** may be detachably provided in the body **110**.

(39) The battery **177** may be provided to be charged as the robot cleaner **100** is docked with the robot cleaner charging device **200** and the charging terminal **215** and the corresponding terminal **190** are connected. When the charge amount of the battery **177** is equal to or less than a predetermined value, the robot cleaner **100** may start a docking mode for charging. In the docking mode, the robot cleaner **100** may return to the robot cleaner charging device **200**.

(40) The robot cleaner **100** may include a traveling part that moves the body **110** with respect to the floor. The traveling part may include at least one driving wheel **166** for moving the body **110** and a driving motor (not shown) for driving the same. The driving wheel **166** may include a left wheel **166** (L) and a right wheel **166** (R) provided on the left and right sides of the body **110**, respectively.

(41) The left wheel **166** (L) and the right wheel **166** (R) may be driven by one drive motor, but if necessary, a left wheel drive motor for driving the left wheel **166** (L) and a right wheel driving motor for the right wheel **166** (R) may be provided, respectively. A traveling direction of the body **110** may be switched to the left or right by making a difference between rotation speeds of the left wheel **166** (L) and the right wheel **166** (R).

(42) The traveling part may further include an auxiliary wheel **168** that does not provide a separate driving force but assists the main body with respect to the floor.

(43) The robot cleaner **100** may include a work part that performs a predetermined task. The robot cleaner **100** may move the traveling zone and may clean the floor by the work part. The work part may perform suction of foreign substances and may perform wiping.

(44) The work part may include a suction device for sucking foreign substances, brushes **184** and **185** for sweeping, a dust bin (not shown) for storing foreign substances collected by the suction device or the brush, and/or a mop part (not shown) for performing wiping.

(45) A suction port **180h** through which air is sucked may be formed on the bottom surface part of the body **110**. A suction device (not shown) that provides suction power for sucking air through the suction port **180h** and a dust bin (not shown) for collecting dust sucked together with air through the suction port **180h** may be provided inside the body **110**.

(46) An opening for insertion and removal of the dust bin may be formed in the case **111**, and a dust

bin cover **112** that opens and closes the opening may be rotatably provided with respect to the case **111**.

(47) The work part may include a roll-type main brush **184** having brushes exposed through the suction port **180h**, and an auxiliary brush **185** having a plurality of radially extending wings located on the front side of the bottom surface part of the body **110**. Dust may be removed from the floor in the traveling area by rotation of these brushes **184** and **185**, and dust separated from the floor may be sucked through the suction port **180h** and collected in the dust bin.

(48) The robot cleaner **100** may include the corresponding terminal **190** for charging the battery **177** when docked with the robot cleaner charging device **200**. The corresponding terminal **190** may be disposed at a position accessible to the charging terminal **215** of the robot cleaner charging device **200** in a successful docking state of the robot cleaner **100**. In one embodiment, a pair of the corresponding terminals **190** may be disposed on the bottom surface part of the body **110**.

(49) The robot cleaner **100** may include an input interface **171** for inputting information. The input interface **171** may receive On/Off or various commands. The input interface **171** may include a button, a key, a touch type display, or the like. The input interface **171** may include a microphone for voice recognition.

(50) The robot cleaner **100** may include an output interface (not shown) for outputting information, a communication interface (not shown) for transmitting and receiving information with other external devices, and a storage (not shown) for storing various information.

(51) The robot cleaner **100** may include a controller (not shown) that processes and determines various information such as mapping and/or recognizing the current location therein, and the controller may control the overall operation of the robot cleaner **100** through control of various components of the robot cleaner **100**.

(52) FIG. 3 is a diagram for explaining a robot cleaner charging device according to an embodiment of the present disclosure. In more detail, FIG. 3 is a perspective view for explaining the overall appearance of the robot cleaner charging device.

(53) Referring to FIG. 3, the robot cleaner charging device **200** may be provided to be placed on the floor, and may include the charging terminal **215** provided to be connected to the corresponding terminal **190** in a successful docking state of the robot cleaner **100**.

(54) In detail, the robot cleaner charging device **200** may include a main body **210** defining an outer appearance and provided to charge the robot cleaner **100** including the plurality of obstacle detection sensors **131**, and the array plate **220** defining a lower part of the main body **210** and having an upper surface on which the charging terminal **215** for charging the robot cleaner **100** is provided.

(55) The main body **210** of the robot cleaner charging device **200** may be made of various materials as needed. In exemplary embodiments, the main body **210** may be made of an opaque material that may be visually blocked from the outside, or may be made of a transparent or translucent material that is visually exposed from the outside.

(56) Various components for charging the robot cleaner **100**, for example, a printed circuit board, a sensor, a guide member, etc. may be provided inside the main body **210** of the robot cleaner charging device **200**, and a docking confirmation part (not shown) for checking whether the robot cleaner **100** is docked may be further provided.

(57) The array plate **220** of the robot cleaner charging device **200** may have a flat upper surface and may be inclined at a predetermined angle with respect to the ground. In exemplary embodiments, a portion of the array plate **220** adjacent to the main body **210** may have an upper surface higher than a lower surface of the main body **210**, and the upper surface of the array plate **220** may be formed to have a constant angle from an adjacent portion to the main body **210** to a portion spaced apart from the main body **210**. In one embodiment, a portion of the array plate **220** spaced apart from the main body **210** may partially have the same height as a lower surface of the main body **210**.

(58) The shape and material of the array plate **220** are not particularly limited, and the robot cleaner

charging device **200** may not include the array plate **220**. When the robot cleaner charging device **200** does not include the array plate **220**, a separate terminal part (not shown) may be provided below the main body **210** to allow the charging terminal **215** to be disposed.

(59) FIGS. **4** and **5** are diagrams for explaining an obstacle detection sensor of a robot cleaner according to exemplary embodiments of the present disclosure.

(60) Referring to FIGS. **4** and **5**, the robot cleaner **100** may include a pair of first obstacle detection sensors **131a** for detecting side obstacles and a second obstacle detection sensor **131b** disposed between the pair of first obstacle detection sensors **131a** and provided to detect forward obstacles.

(61) Although FIG. **4** shows the case in which two second obstacle detection sensors **131b** are formed, and FIG. **5** shows the case in which four second obstacle detection sensors **131b** are formed, the concept of the present disclosure is not limited thereto. That is, the number of the second obstacle detection sensors **131b** is not particularly limited, and the number of the first obstacle detection sensors **131a** is also not particularly limited.

(62) In exemplary embodiments, in a state in which the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200** are aligned, the second obstacle detection sensors **131b** may be disposed to detect the main body **210** of the robot cleaner charging device **200**, but the first obstacle detection sensors **131a** may be disposed not to detect the main body **210** of the robot cleaner charging device **200**.

(63) In one embodiment, in a state in which the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200** are aligned, the first obstacle detection sensors **131a** may be disposed to detect a wall located farther than the main body **210** of the robot cleaner charging device **200**.

(64) Hereinafter, a method of aligning the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200** using the plurality of obstacle detection sensors **131** will be described.

(65) FIG. **6** is a diagram for explaining a method of aligning a center line of a robot cleaner according to an embodiment of the present disclosure. For convenience of description, FIG. **6** illustrates the case in which the robot cleaner **100** includes a total of four obstacle detection sensors **131**, more specifically, a pair of the first obstacle detection sensors **131a** and a pair of the second obstacle detection sensors **131b**, and based thereon, a method of aligning the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200** will be described.

(66) Referring to FIG. **6**, based on the position of one end of the robot cleaner charging device **200** through a two-dimensional Cartesian coordinate system with the center of the robot cleaner **100** as the origin, a center separation distance between the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200** may be estimated.

(67) In detail, when the robot cleaner **100** approaches the robot cleaner charging device **200** through an IR signal by a first distance D_a , for example, a distance of less than 30 cm, the position of one end of the robot cleaner charging device **200** may be estimated using distance measurement values of the obstacle detection sensor **131** that detects the robot cleaner charging device **200** and the obstacle detection sensor **131** that does not detect the robot cleaner charging device **200**.

(68) For example, when the robot cleaner **100** is located on the left side from the main body **210** of the robot cleaner charging device **200**, that is, the center line of the robot cleaner **100** is located on the left side from the center line of the main body **210**, the first obstacle detection sensors **131a** and the second obstacle detection sensors **131b** disposed on the left side may each detect a wall located behind the main body **210**, and the first obstacle detection sensors **131a** and the second obstacle detection sensors **131b** disposed on the right side may each detect the main body **210**. Accordingly, the left end of the main body **210** may be estimated to be located between the second obstacle detection sensors **131b** disposed on the left side and the second obstacle detection sensors **131b** disposed on the right side.

(69) In exemplary embodiments, when a distance measurement value of the second obstacle

detection sensors **131b** disposed on the left side is a first measurement distance $D_{\text{sub.1}}$, a separation distance of the second obstacle detection sensors **131b** disposed on the left side from the center of the robot cleaner **100** in the x-axis direction is a first mounting distance $A_{\text{sub.1}}$, and a mounting angle of the second obstacle detection sensors **131b** disposed on the left side is a first angle $\theta_{\text{sub.1}}$, the minimum value of a range in which the left end of the main body **210** is to be located may be estimated as a first estimated distance $A_{\text{sub.2}}$. In this case, the first estimated distance $A_{\text{sub.2}}$ may be expressed by the following Equation.

$$A_{\text{sub.2}} = A_{\text{sub.1}} - D_{\text{sub.1}} \sin \theta_{\text{sub.1}} \quad \text{<Equation 1>}$$

(70) Similarly, when a distance measurement value of the second obstacle detection sensors **131b** disposed on the right side is a second measurement distance $D_{\text{sub.2}}$, a separation distance of the second obstacle detection sensors **131b** disposed on the right side from the center of the robot cleaner **100** in the x-axis direction is a second mounting distance $A_{\text{sub.1}}$, and a mounting angle of the second obstacle detection sensors **131b** disposed on the right side is a second angle $\theta_{\text{sub.2}}$, the maximum value of a range in which the left end of the main body **210** is to be located may be estimated as a second estimated distance $A_{\text{sub.2}}$. In this case, the second estimated distance $A_{\text{sub.2}}$ may be expressed by the following Equation.

$$A_{\text{sub.2}} = A_{\text{sub.1}} + D_{\text{sub.2}} \sin \theta_{\text{sub.2}} \quad \text{<Equation 2>}$$

(71) Accordingly, when the x-axis position of the left end of the main body **210** is a first position L , a range of the first position L may be estimated as follows.

$$A_{\text{sub.1}} - D_{\text{sub.1}} \sin \theta_{\text{sub.1}} < L < A_{\text{sub.1}} + D_{\text{sub.2}} \sin \theta_{\text{sub.2}} \quad \text{<Equation 3>}$$

(72) Then, when a vertical width of the main body **210** is a first width $W_{\text{sub.1}}$ and a horizontal width of the main body **210** is a second width $W_{\text{sub.2}}$, the center of the robot cleaner **100** is the origin, and thus the x-axis position of the center line of the main body **210** may be a center separation distance D_{an} between the robot cleaner **100** and the robot cleaner charging device **200**, and the center separation distance D_{an} may be estimated as follows.

$$D_{\text{an}} = L + W_{\text{sub.2}}/2 \quad \text{<Equation 4>}$$

(73) That is, as a result, the center separation distance between the robot cleaner **100** and the robot cleaner charging device **200** may be expressed as an x-axis position difference between the center of the robot cleaner **100** and the center of the robot cleaner charging device **200**.

(74) Although not shown, a method for estimating the center separation distance between the robot cleaner **100** and the robot cleaner charging device **200** through Equations 1 to 4 above may be applied in substantially the same or similar way when the robot cleaner **100** is located on the right side of the main body **210**, that is, when the center line of the robot cleaner **100** is located on the right side from the center line of the main body **210**.

(75) In exemplary embodiments, when an absolute value of the center separation distance D_{an} is smaller than a specific value, the center lines of the robot cleaner **100** and the robot cleaner charging device **200** may be determined to be aligned, and when an absolute value of the center separation distance D_{an} is greater than the specific value, the center lines of the robot cleaner **100** and the robot cleaner charging device **200** may not be determined to be aligned. In one embodiment, the specific value may be about 5 cm.

(76) In exemplary embodiments, when a value of the center separation distance D_{an} is positive, the robot cleaner **100** may be determined to be located on the left side from the center line of the robot cleaner charging device **200**, and when a value of the center separation distance D_{an} is negative, the robot cleaner **100** may be determined to be located on the right side from the center line of the robot cleaner charging device **200**.

(77) FIG. 7 is a diagram for explaining a state in which a center line of a robot cleaner is not aligned according to an embodiment of the present disclosure.

(78) Referring to FIGS. 7(a) to 7(b), when the robot cleaner **100** approaches the robot cleaner charging device **200** by the first distance D_a through an IR signal, whether the center line of the robot cleaner **100** and the robot cleaner charging device **200** are aligned may be determined

according to whether the plurality of obstacle detection sensors **131** detect the robot cleaner charging device **200**. In this case, the plurality of obstacle detection sensors **131** may include a pair of the first obstacle detection sensors **131a** for detecting side obstacles, and the second obstacle detection sensors **131b** disposed between the pair of first obstacle detection sensors **131a** and provided to detect side obstacles, and the second obstacle detection sensors **131b** may be provided in a total of four.

(79) In exemplary embodiments, as shown in FIG. 5, the robot cleaner **100** may determine a state in which only the second obstacle detection sensor **131b** of the plurality of obstacle detection sensors **131** detects the robot cleaner charging device as a state in which the center lines of the robot cleaner **100** and the robot cleaner charging device **200** are aligned.

(80) In contrast, as shown in FIGS. 7(a) to 7(b), the robot cleaner **100** may determine a state in which at least one of the pair of first obstacle detection sensors **131a** detects the robot cleaner charging device **200** as a state in which the center lines of the robot cleaner **100** and the robot cleaner charging device **200** are not aligned.

(81) For example, the robot cleaner **100** may determine a state in which only the first obstacle detection sensor **131a** disposed on the right among the pair of first obstacle detection sensors **131a** detects the robot cleaner charging device **200** as a state in which the center line of the robot cleaner **100** is spaced apart from the center line of the robot cleaner charging device **200** to the left side. In this case, the robot cleaner **100** may move to the right side to align the center line of the robot cleaner **100** and the center line of the robot cleaner charging device **200**.

(82) Similarly, the robot cleaner **100** may determine a state in which only the first obstacle detection sensor **131a** disposed on the left among the pair of first obstacle detection sensors **131a** detects the robot cleaner charging device **200** as a state in which the center of the robot cleaner **100** is spaced apart from the center line of the robot cleaner charging device **200** to the right side. In this case, the robot cleaner **100** may move to the left side to align the center lines of the robot cleaner **100** and the robot cleaner charging device **200**.

(83) In this case, the robot cleaner **100** may be controlled to move to the right or left side by the aforementioned center separation distance D_{an} .

(84) FIG. 7(a) shows that the center line of the robot cleaner **100** is separated from the center line of the main body **210** of the robot cleaner charging device to the left by a first center separation distance $D_{a.sub.1}$, FIG. 7(b) shows that the center line of the robot cleaner **100** is separated from the center line of the main body **210** of the robot cleaner charging device by a second center separation distance $D_{a.sub.2}$ that is greater than the first center separation distance $D_{a.sub.1}$, and FIG. 7(c) shows that the center line of the robot cleaner **100** is separated from the center of the main body **210** of the robot cleaner charging device by a third center separation distance $D_{a.sub.3}$ that is greater than the second center separation distance $D_{a.sub.2}$. In this case, the center separation distance D_{an} between the robot cleaner **100** and the robot cleaner charging device **200** may be indirectly estimated by comparing which sensor detects the robot cleaner charging device **200** among the obstacle detection sensors **131** in addition to the above-described estimation method using Equations 1 to 4 above.

(85) For example, as shown in FIG. 7(a), the robot cleaner **100** may determine a state in which the leftmost obstacle detection sensor and an obstacle detection sensor adjacent thereto among the plurality of obstacle detection sensors **131** do not detect the main body **210** and the other obstacle detection sensors detect the main body **210** as a state in which the center line of the robot cleaner **100** is spaced apart from the center line of the main body **210** of the robot cleaner charging device to the left by a first center separation distance $D_{a.sub.1}$.

(86) For example, as shown in FIG. 7(b), the robot cleaner **100** may determine a state in which obstacle detection sensors disposed on the left among the plurality of obstacle detection sensors **131** do not detect the main body **210** and obstacle detection sensors disposed on the right detect the main body **210** as a state in which the center line of the robot cleaner **100** is spaced apart from the

center line of the main body **210** of the robot cleaner charging device to the left by a second center separation distance $Da.sub.2$.

(87) For example, as shown in FIG. 7(c), the robot cleaner **100** may determine a state in which the rightmost obstacle detection sensor and an obstacle detection sensor adjacent thereto among the plurality of obstacle detection sensors **131** detect the main body **210** and the other obstacle detection sensors do not detect the main body **210** as a state in which the center line of the robot cleaner **100** is spaced apart from the center line of the main body **210** of the robot cleaner charging device to the left by a third center separation distance $Da.sub.3$.

(88) Hereinafter, a method of correcting a direction angle between the robot cleaner **100** and the robot cleaner charging device **200** using the plurality of obstacle detection sensors **131** will be described.

(89) FIGS. **8** and **9** are diagrams for explaining a method of correcting a direction angle of a robot cleaner according to an embodiment of the present disclosure.

(90) Referring to FIGS. **8(a)** and **8(b)**, the robot cleaner **100** may check whether the shortest distance between the robot cleaner **100** and the robot cleaner charging device **200** is equal to or less than a second distance Db smaller than the first distance Da in a state in which the center lines of the robot cleaner **100** and the robot cleaner charging device **200** are aligned, may then check whether a difference in direction angle occurs between the robot cleaner **100** and the robot cleaner charging device **200** through the plurality of obstacle detection sensors **131**, and may correct the difference in the direction angle. In one embodiment, the second distance Db may be about 15 cm.

(91) In this case, whether a difference in direction angle occurs between the robot cleaner **100** and the robot cleaner charging device **200** may be determined according to whether at least one of the pair of first obstacle detection sensors **131a** detects the robot cleaner charging device **200**.

(92) For example, as shown in FIG. **8(a)**, the robot cleaner **100** may determine a state in which only the first obstacle detection sensor **131a** disposed on the right among the pair of first obstacle detection sensors **131a** detects the main body **210** of the robot cleaner charging device as a state in which a difference in direction angle in a counterclockwise direction occurs between the robot cleaner **100** and the center line of the robot cleaner charging device **200** by a specific angle. In this case, the robot cleaner **100** may rotate in a clockwise direction to correct the difference in direction angle between the robot cleaner **100** and the robot cleaner charging device **200**.

(93) In contrast, as shown in FIG. **8(b)**, the robot cleaner **100** may determine a state in which only the first obstacle detection sensor **131a** disposed on the left among the pair of first obstacle detection sensors **131a** detects the main body **210** of the robot cleaner charging device as a state in which a difference in direction angle in a clockwise direction occurs between the robot cleaner **100** and the center line of the robot cleaner charging device **200** by a specific angle. In this case, the robot cleaner **100** may rotate in a counterclockwise direction to correct the difference in direction angle between the robot cleaner **100** and the robot cleaner charging device **200**.

(94) Referring to FIG. **9**, the difference in direction angle between the robot cleaner **100** and the robot cleaner charging device **200** may be determined using the smallest distance measurement value and a distance measurement value closest thereto among distance measurement values of the obstacle detection sensors **131** that detect the position of the robot cleaner charging device **200**.

(95) In detail, when the smallest distance measurement value among distance measurement values of the obstacle detection sensor **131** that detects the position of the main body **210** of the robot cleaner charging device is a third measurement distance $Db.sub.1$ and a distance measurement value adjacent thereto is a fourth measurement distance $Db.sub.2$, a first direction angle between the obstacle detection sensors **131** that detects the position of the main body **210** of the robot cleaner charging device and the main body **210** of the robot cleaner charging device may be estimated as follows.

$\alpha = \tan.sup.-1(|Db.sub.1 - Db.sub.2| / \text{distance between obstacle detection sensors})$ <Equation 5>

(96) Then, when a placement angle of the obstacle detection sensor **131** that detects the position of

the main body **210** of the robot cleaner charging device is a second direction angle β , a difference in the total direction angle between the robot cleaner **100** and the main body **210** of the robot cleaner charging device may be estimated as the sum of the first direction angle α and the second direction angle β .

(97) Accordingly, the robot cleaner **100** may rotate in a clockwise or counterclockwise direction by an angle corresponding to the sum of the total direction angles, that is, the first direction angle α and the second direction angle β to correct the difference in direction angle between the robot cleaner **100** and the robot cleaner charging device **200**.

(98) Although FIG. **9** shows that an obstacle detection sensor having the closest distance measurement value is the first obstacle detection sensors **131a** and an obstacle detection sensor having a distance measurement value closest thereto is the second obstacle detection sensors **131b**, the concept of the present disclosure is not necessarily limited thereto. That is, all obstacle detection sensors having the closest distance measurement value and the distance measurement value closest thereto may also be the second obstacle detection sensor **131b**.

(99) FIG. **10** is a flowchart for explaining a method of aligning a center line of a robot cleaner according to an embodiment of the present disclosure.

(100) Referring to FIG. **10**, a control method of a robot cleaner according to the present disclosure may include a first operation S1 in which the robot cleaner **100** approaches the robot cleaner charging device **200** through an IR signal, a second operation S2 of checking whether a distance between the robot cleaner **100** and the robot cleaner charging device **200** is less than a first distance D1, a third operation S3 of checking whether the robot cleaner **100** receives a proximity docking IR signal generated from the robot cleaner charging device **200**, a fourth operation S4 of checking whether the center lines of the robot cleaner **100** and the robot cleaner charging device **200** are aligned through the obstacle detection sensor **131** (S4a) and aligning the center lines (S4b), and a fifth operation S5 in which the robot cleaner **100** moves straight toward the robot cleaner charging device **200** when the center lines of the robot cleaner **100** and the robot cleaner charging device **200** are aligned.

(101) In this case, the fourth operation S4 may be performed through the center line alignment method of the robot cleaner **100** described with reference to FIGS. **6** and **7**.

(102) The first operation S1 may be referred to as a remote docking operation, and the second operation S2 to the fifth operation S5 may be referred to as a center line alignment operation.

(103) In exemplary embodiments, the first distance D1 may be about 30 cm.

(104) FIG. **11** is a flowchart for explaining a method of correcting a direction angle of a robot cleaner according to an embodiment of the present disclosure.

(105) Referring to FIG. **11**, a control method of a robot cleaner according to the present disclosure may further include a sixth operation S6 in which the robot cleaner **100** approaches the robot cleaner charging device **200** after the center line alignment operation, a seventh operation S7 of checking whether a distance between the robot cleaner **100** and the robot cleaner charging device **200** is less than a second distance D2 that is smaller than the first distance D1, an eighth operation S8 of measuring a distance between the robot cleaner **100** and the robot cleaner charging device **200** through the obstacle detection sensor **131**, a ninth operation S9 of checking whether a difference in direction angle occurs between the robot cleaner **100** and the robot cleaner charging device **200** through the obstacle detection sensor **131** (S9a) and correcting the direction angle difference (S9b), and a tenth operation S10 in which the robot cleaner **100** and the charging terminal **215** come into contact when the direction angles of the robot cleaner **100** and the robot cleaner charging device **200** are corrected.

(106) In this case, the eighth operation S8 and the ninth operation S9 may be performed through the center line alignment method of the robot cleaner **100** described with reference to FIGS. **6** and **7**.

(107) The sixth operation S6 to the tenth operation S10 may be referred to as a direction angle

correction operation, and the second operation S2 to the tenth operation S10 may be referred to as a short-distance docking operation together.

(108) In exemplary embodiments, the second distance D1 may be about 15 cm.

(109) As described above, the remote docking operation of the robot cleaner **100** may be performed according to the IR signal generated from the robot cleaner charging device **200**, and the short-distance docking operation of the robot cleaner **100** may be performed by estimating the position of the robot cleaner charging device **200** through the obstacle detection sensor **131**.

(110) In this case, docking in a state in which the robot cleaner **100** is in close proximity to the robot cleaner charging device **200** may not be performed according to an IR signal, and thus may not be affected by external environments, such as indoor lighting and sunlight, and a disadvantage that it is difficult to distinguish a specific area of the robot cleaner charging device **200** according to the maximum intensity of the IR signal may be overcome. Accordingly, short-distance docking for charging the robot cleaner **100** and the robot cleaner charging device **200** may be precisely performed.

(111) Although various embodiments of the present disclosure have been described in detail above, those of ordinary skill in the art to which the present disclosure pertains will understand that it is possible to make various modifications to the above-described embodiments without departing from the scope of the present disclosure. Therefore, the scope of the present disclosure should not be limited to the described embodiments, and should be defined by the claims described below as well as the claims and equivalents.

Claims

1. A control method of a robot cleaner, the method comprising: a first operation in which the robot cleaner including a plurality of obstacle detection sensors approaches a robot cleaner charging device according to an IR signal transmitted from the robot cleaner charging device including a charging terminal for charging the robot cleaner; a second operation of checking whether a shortest distance between the robot cleaner and the robot cleaner charging device is equal to or less than a first distance through the plurality of obstacle detection sensors; a third operation of checking whether center lines of the robot cleaner and the robot cleaner charging device are aligned through the plurality of obstacle detection sensors and aligning the center lines of the robot cleaner and the robot cleaner charging device; a fourth operation in which the robot cleaner moves straight toward the robot cleaner charging device when the center lines of the robot cleaner and the robot cleaner charging device are aligned; a fifth operation of checking whether the shortest distance between the robot cleaner and the robot cleaner charging device is equal to or less than a second distance smaller than the first distance in a state in which the center lines of the robot cleaner and the robot cleaner charging device are aligned; a sixth operation of checking whether a difference in direction angle occurs between the robot cleaner and the robot cleaner charging device through the plurality of obstacle detection sensors and correcting the difference in the direction angle between the robot cleaner and the robot cleaner charging device; and a seventh operation in which the robot cleaner and the charging terminal come into contact when direction angles of the robot cleaner and the robot cleaner charging device are corrected.
2. The method of claim 1, wherein, in the third operation, when a distance measurement value of a first obstacle detection sensor of the plurality of obstacle detection sensors is greater than a distance measurement value of a second obstacle detection sensor of the plurality of obstacle detection sensors that detects a position of the robot cleaner charging device, one end of the robot cleaner charging device is determined to be located between the plurality of obstacle detection sensors, and a center separation distance between the center line of the robot cleaner and the center line of the robot cleaner charging device is estimated based on a position of the one end of the robot cleaner charging device through a 2D Cartesian coordinate system using a center of the robot cleaner as an

origin.

3. The method of claim 2, wherein, in the third operation, when an absolute value of the center separation distance is smaller than a specific value, the center lines of the robot cleaner and the robot cleaner charging device are determined to be aligned, and when the absolute value of the center separation distance is greater than the specific value, the center lines of the robot cleaner and the robot cleaner charging device are determined not to be aligned.

4. The method of claim 3, wherein, in the third operation, when a value of the center separation distance is a positive value, the robot cleaner is determined to be located to a left from the center line of the robot cleaner charging device, and when the value of the center separation distance is a negative value, the robot cleaner is determined to be located to a right from the center line of the robot cleaner charging device.

5. The method of claim 1, wherein the plurality of obstacle detection sensors include a pair of first obstacle detection sensors for detecting a side obstacle, and a second obstacle detection sensor disposed between the pair of first obstacle detection sensors and provided to detect a forward obstacle, and wherein, in the third operation, whether the center lines of the robot cleaner and the robot cleaner charging device are aligned is determined according to whether the first obstacle detection sensor and the second obstacle detection sensor detect the robot cleaner charging device.

6. The method of claim 5, wherein, in the third operation, a state in which only the second obstacle detection sensor among the plurality of obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the center lines of the robot cleaner and the robot cleaner charging device are aligned.

7. The method of claim 6, wherein, in the third operation, a state in which at least one first obstacle detection sensor among the pair of first obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the center lines of the robot cleaner and the robot cleaner charging device are determined not to be aligned.

8. The method of claim 7, wherein, in the third operation, a state in which only the first obstacle detection sensor disposed on a right among the pair of first obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the center line of the robot cleaner is spaced apart from the center line of the robot cleaner charging device to a left.

9. The method of claim 8, wherein, in the third operation, when the center line of the robot cleaner is determined to be spaced apart from the center line of the robot cleaner charging device to the left, the robot cleaner moves to a right.

10. The method of claim 7, wherein, in the third operation, a state in which only the first obstacle detection sensor disposed on a left among the pair of first obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the center line of the robot cleaner is spaced apart from the center line of the robot cleaner charging device to a right.

11. The method of claim 10, wherein, in the third operation, when the center line of the robot cleaner is determined to be spaced apart from the center line of the robot cleaner charging device to the right, the robot cleaner moves to a left.

12. The method of claim 1, wherein, in the sixth operation, whether the difference in direction angle occurs between the robot cleaner and the robot cleaner charging device is determined using a smallest distance measurement value among distance measurement values measured by the plurality of obstacle detection sensors that detect a position of the robot cleaner charging device and a distance measurement value, measured by the remaining obstacle detection sensors of the plurality of obstacle detection sensors, closest to the smallest distance measurement value.

13. The method of claim 1, wherein the plurality of obstacle detection sensors include a pair of first obstacle detection sensors for detecting a side obstacle, and a second obstacle detection sensor disposed between the pair of first obstacle detection sensors and provided to detect a forward obstacle, and wherein, in the sixth operation, whether the difference in direction angle occurs between the robot cleaner and the robot cleaner charging device is determined according to whether

at least one of the pair of first obstacle detection sensors detects the robot cleaner charging device.

14. The method of claim 13, wherein, in the sixth operation, a state in which only the first obstacle detection sensor disposed on a right among the pair of first obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the difference in direction angle in a counterclockwise direction occurs between the robot cleaner and the center line of the robot cleaner charging device by a specific angle.

15. The method of claim 14, wherein, in the sixth operation, when the difference in direction angle in the counterclockwise direction is determined to occur between the robot cleaner and the center line of the robot cleaner charging device by the specific angle, the robot cleaner rotates in a clockwise direction to correct the difference in direction angle.

16. The method of claim 13, wherein, in the sixth operation, only the first obstacle detection sensor disposed to a left among the pair of first obstacle detection sensors detects the robot cleaner charging device is determined as a state in which the difference in direction angle in a clockwise direction occurs between the robot cleaner and the center line of the robot cleaner charging device by a specific angle.

17. The method of claim 16, wherein, in the sixth operation, when the difference in direction angle in the clockwise direction is determined to occur between the robot cleaner and the center line of the robot cleaner charging device by the specific angle, the robot cleaner rotates in a counterclockwise direction to correct the difference in direction angle.
