

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405285
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Sakai; Tatsuya et al.

Automatic analyzer

Abstract

An object of the present invention is to provide an automatic analyzer capable of efficiently performing stirring by a discharge operation. In the automatic analyzer according to the present invention, by lifting the probe while discharging a specimen or a reagent after the probe starts to discharge the specimen to a vessel, as a height of a liquid level of the liquid in the vessel, which is discharged from the probe, is gradually raised, a distance between the liquid level in the vessel and a tip end of the probe is gradually increased.

Inventors:	Sakai; Tatsuya (Tokyo, JP), Miyazaki; Mariko (Tokyo, JP)
Applicant:	Hitachi High-Tech Corporation (Tokyo, JP)
Family ID:	78830388
Assignee:	HITACHI HIGH-TECH CORPORATION (Tokyo, JP)
Appl. No.:	17/925462
Filed (or PCT Filed):	February 09, 2021
PCT No.:	PCT/JP2021/004769
PCT Pub. No.:	WO2021/245989
PCT Pub. Date:	December 09, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230184803 A1	Jun. 15, 2023

Foreign Application Priority Data

JP	2020-095585	Jun. 01, 2020
----	-------------	---------------

Publication Classification

Int. Cl.: G01N35/10 (20060101)

U.S. Cl.:

CPC G01N35/1011 (20130101); G01N35/1002 (20130101); G01N2035/1058 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4586546	12/1985	Mezei et al.	N/A	N/A
2017/0205321	12/2016	Sasaki et al.	N/A	N/A
2022/0381799	12/2021	Noda	N/A	G01N 35/10
2022/0397582	12/2021	Miyazaki	N/A	G01N 35/1011
2023/0417789	12/2022	Fukuda	N/A	G01N 35/1011

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2002340915	12/2001	JP	N/A
6381917	12/2017	JP	N/A
2016/136377	12/2015	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report issued on Apr. 12, 2024 for European Patent Application No. 21817738.4. cited by applicant

Primary Examiner: Wright; P. Kathryn

Attorney, Agent or Firm: Volpe Koenig

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to an automatic analyzer.

BACKGROUND ART

(2) Examples of an automatic analyzer that analyzes components of blood, urine, spinal fluid, and the like of a patient include (a) a biochemical automatic analyzer that measures an amount of transmitted light or scattered light obtained by irradiating a reaction liquid of a specimen and a reagent with light, and (b) an immune automatic analyzer in which a reagent added with a label reacts with a specimen and an amount of light emitted from the label is measured. A technique for preventing liquid scattering when a liquid is discharged from a probe to a reaction vessel is

disclosed in these automatic analyzers (see PTL 1).

CITATION LIST

Patent Literature

(3) PTL 1: Japanese Patent No. 6381917

SUMMARY OF INVENTION

Technical Problem

(4) According to PTL 1, a probe discharges a liquid while the probe is immersed in a liquid of several millimeters. A liquid level above a tip end of the probe and a liquid flow around the tip end of the probe are poor, and it is not clear whether the liquid can be stirred efficiently by a discharge operation.

(5) An object of the invention is to provide an automatic analyzer capable of efficiently stirring a liquid by a discharge operation.

Solution to Problem

(6) In the automatic analyzer according to the invention, after a probe starts to discharge a specimen to a vessel, the probe is lifted while discharging the specimen or a reagent, so that a height of a liquid level of a liquid in the vessel discharged from the probe increases, and a distance between the liquid level in the vessel and a tip end of the probe gradually increases.

Advantageous Effects of Invention

(7) According to the invention, stirring can be efficiently performed by a discharge operation.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a block diagram schematically illustrating an overall view of an automatic analyzer 10 according to a first embodiment.

(2) FIG. 2 is a plan view schematically illustrating a configuration of an analysis unit 1.

(3) FIG. 3 is a schematic view of a dispensing mechanism 11.

(4) FIG. 4 is a flowchart illustrating a measurement operation of the automatic analyzer 10.

(5) FIG. 5 is a diagram schematically illustrating a movement of a dispensing probe 30 and an effect thereof when the automatic analyzer 10 simultaneously dispenses a specimen and a first reagent in the first embodiment.

(6) FIG. 6A is a relationship diagram between a height of a tip end of the dispensing probe 30 from the bottom of a reaction vessel 14 and a height of a liquid level of a reaction liquid 36.

(7) FIG. 6B is a diagram illustrating an elapsed time change in a distance D_a between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36.

(8) FIG. 7 is a diagram schematically illustrating a movement of the dispensing probe 30 and an effect thereof when the automatic analyzer 10 simultaneously dispenses a specimen and a first reagent in a second embodiment.

(9) FIG. 8A is a relationship diagram between the height of the tip end of the dispensing probe 30 from the bottom of the reaction vessel 14 and the height of the liquid level of the reaction liquid 36.

(10) FIG. 8B is a diagram illustrating an elapsed time change in a distance D_a between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36.

(11) FIG. 9 is a diagram schematically illustrating a movement of the dispensing probe 30 and an effect thereof when the automatic analyzer 10 simultaneously dispenses a specimen and a first reagent in a third embodiment.

(12) FIG. 10A is a relationship diagram between the height of the tip end of the dispensing probe 30 from the bottom of the reaction vessel 14 and the height of the liquid level of the reaction liquid 36.

(13) FIG. 10B is a diagram illustrating an elapsed time change in a distance D_a between the tip end

of the dispensing probe **30** and the liquid level of the reaction liquid **36**.

(14) FIG. **11** is a diagram schematically illustrating a movement of the dispensing probe **30** and an effect thereof when the automatic analyzer **10** simultaneously dispenses a specimen and a first reagent in a fourth embodiment.

(15) FIG. **12A** is a relationship diagram between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**.

(16) FIG. **12B** is a diagram illustrating an elapsed time change in a distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**.

(17) FIG. **13** is a diagram schematically illustrating a movement of the dispensing probe **30** and an effect thereof when the automatic analyzer **10** simultaneously dispenses a specimen and a first reagent in a fifth embodiment.

(18) FIG. **14A** is a relationship diagram between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**.

(19) FIG. **14B** is a diagram illustrating an elapsed time change in a distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**.

(20) FIG. **15** is a diagram schematically illustrating a movement of the dispensing probe **30** and an effect thereof when the automatic analyzer **10** simultaneously dispenses a specimen and a first reagent in a sixth embodiment.

(21) FIG. **16A** is a relationship diagram between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**.

(22) FIG. **16B** is a diagram illustrating an elapsed time change in a distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**.

(23) FIG. **17** is a diagram illustrating a deviation rate (%) for each of the first embodiment and a comparative example.

(24) FIG. **18** is a diagram illustrating a light absorbance fluctuation rate fix 5 minutes for each of the first embodiment and the comparative example.

DESCRIPTION OF EMBODIMENTS

(25) Embodiments of the invention will be described in detail with reference to the drawings. In the drawings, common components or similar components are denoted by the same reference numerals, and repetitive description thereof will be omitted as appropriate. In the following embodiments, it is needless to say that components (including element steps and the like) are not necessarily essential unless otherwise particularly specified or clearly considered as essential in principle.

First Embodiment

(26) FIG. **1** is a block diagram schematically illustrating an overall configuration of an automatic analyzer **10** according to a first embodiment. The automatic analyzer **10** mainly includes an analysis unit **1** that analyzes a mixed liquid of a liquid specimen and a reagent, a computer **3** (a control unit) that controls the analysis unit **1**, and an analysis control unit **8**.

(27) The analysis control unit **8** controls an operation of each mechanism of the analysis unit **1**. Details will be described later. The computer **3** is connected to the analysis control unit **8**, an A/D converter **7**, and the like via an interface **9**. The computer **3** sends a command to the analysis control unit **8** or the like and controls an operation of each mechanism. A/D-converted data (a photometric value) acquired from the analysis unit **1** is sent to the computer **3**. The computer **3** executes calculation processing using the acquired data (the photometric value). That is, the computer **3** can control each mechanism of the analysis unit **1** via the analysis control unit **8**, and can perform data calculation processing.

(28) The interface **9** is connected to a printer **4** for printing, a memory **6** that is a recording device, a

keyboard **2** for inputting an operation command and the like, and a display device **5** implemented by a CRT display, a liquid crystal display or the like. The memory **6** includes, for example, a hard disk memory or an external memory. The memory **6** records information such as an analysis parameter, an analysis item request, a calibration result, and an analysis result.

(29) FIG. **2** is a plan view schematically illustrating a configuration of the analysis unit **1**. The analysis unit **1** mainly includes sample racks **25**, a reagent disk **21**, and a reaction disk incubator) **15**. The sample rack **25** holds a specimen vessel **24**. The reagent disk **21** holds a reagent vessel **22**. The reaction disk **15** holds a reaction vessel **14** on its circumference. The analysis unit **1** further includes a dispensing mechanism **11**, a dispensing mechanism washing unit **26**, a reaction vessel washing unit **27**, a light source **12**, and a spectroscopic detector **13**.

(30) The sample rack **25** is movable in a horizontal direction, and a plurality of the specimen vessels **24** for holding biological samples (hereinafter referred to as specimens) such as blood are placed on the sample rack **25**.

(31) The reagent disk **21** can intermittently rotate clockwise and counterclockwise, and a plurality of the reagent vessels **22** corresponding to analysis items of the automatic analyzer **10** are placed on the reagent disk **21**. In FIG. **2**, the reagent disk **21** is illustrated in a manner of being partially cut away. The reagent disk **21** has a circular shape in a plan view, in the reagent disk **21**, two reagent vessels **22** are arranged in a radial direction of the reagent disk **21** (two reference numerals **22** at two ends are illustrated). That is, two circular rows of the reagent vessels **22** arranged in a manner of surrounding the center of the reagent disk **21** are concentrically disposed in the reagent disk **21**. Reagents in the two reagent vessels **22** arranged in the radial direction may be reagents of different types.

(32) The reaction disk **15** can intermittently rotate clockwise and counterclockwise, and a plurality of the reaction vessels **14** in which a specimen and a reagent reacts with each other are placed on a circumference of the reaction disk **15**.

(33) The dispensing mechanism **11** aspirates a specimen from the specimen vessel **24** placed on the sample rack **25**, aspirates a reagent from the reagent vessel **22** in the reagent disk **21**, and discharges and dispenses an aspirated liquid into the reaction vessel **14** in the reaction disk **15**. The dispensing mechanism **11** does not only indicate a tip end portion of a vessel constituting a flow path for aspirating and discharging a liquid, but also indicates a vessel around the entire flow path from a pump (for example, a syringe) for aspirating and discharging a liquid to the tip end portion. FIG. **2** illustrates a vertical rotation operation unit (a movement unit) of the dispensing mechanism **11**. The vertical rotation operation unit is an operation unit that changes a position where a liquid is aspirated and discharged.

(34) The light source **12** is disposed in the vicinity of an outer periphery of the reaction disk **15**, and emits light to the reaction vessel **14**. The spectroscopic detector **13** is disposed at an opposite side to the light source **12** with the reaction vessel **14** interposed between the spectroscopic detector **13** and the light source **12**, and optically measures light absorbance of light emitted from the light source **12** to a specimen, a reagent, or a mixed liquid of a specimen and a reagent in a reaction vessel. At a timing when the reaction vessel **14** crosses a predetermined optical path, the light source **12** emits light to each of the plurality of reaction vessels **14** that are moved accompanying with a rotational movement of the reaction disk **15**. Through the light emission, the spectroscopic detector **13** detects light transmitted through a specimen, a reagent, or a mixed liquid of a specimen and a reagent stored in each of the reaction vessels **14** for each wavelength of a test item. An analog signal such as an intensity of light detected by the spectroscopic detector **13** is input to the A/D converter **7** (see FIG. **1**). The A/D converter **7** generates standard data or test data based on an input digital signal, and the generated data are sent to the computer **3**.

(35) The reaction vessel washing unit **27** washes an inner side of each of the plurality of reaction vessels **14** for which a measurement performed by the spectroscopic detector **13** is completed.

(36) Although not particularly illustrated, the analysis unit **1** may include a stirring mechanism that

stirs a liquid in a reaction vessel. Examples of the stirring mechanism include a method in which a spatula is immersed in a solution in the reaction vessel **14** and the spatula is rotated to physically stir the solution, and a method in which ultrasonic waves are radiated to the solution to generate a swirling flow.

(37) The analysis control unit **8** controls operations of a plurality of units constituting the analysis unit **1**. The analysis control unit **8** controls rotational movements of the reagent disk **21** and the reaction disk **15** by driving a movement mechanism such as a disk. The analysis control unit **8** controls a horizontal movement of the sample rack **25** by driving a belt pulley mechanism or a ball screw mechanism. The analysis control unit **8** controls a vertical movement and a rotational movement of the dispensing mechanism **11** by driving an arm movement mechanism. The analysis control unit **8** controls a vertical movement of the reaction vessel washing unit **27** by driving a lifting and lowering mechanism. The analysis control unit **8** controls an aspirating and discharge operation of various pumps which will be described later with reference to FIG. **3**) connected to the dispensing mechanism **11**, and controls a liquid feeding and stopping operation of a pump that supplies washing water to the reaction vessel washing unit **27**.

(38) FIG. **3** is a schematic view of the dispensing mechanism **11**. The dispensing mechanism **11** includes a dispensing probe **30**, a dispensing arm **41**, and a vertical rotation operation unit **42**. The dispensing probe **30** is attached to one end of the dispensing arm **41**, and the dispensing arm **41** is coupled to the dispensing probe **30** and the vertical rotation operation unit **42**. The vertical rotation operation unit **42** includes a biaxial movement mechanism of a vertical (vertical direction) movement mechanism and a rotation movement mechanism. The dispensing mechanism **11** can be vertically moved and rotationally moved by the vertical rotation operation unit **42**. As a result, the dispensing mechanism **11** can move to a reagent aspirating position where the reagent vessel **22** (see FIG. **2**) is installed in order to aspirate a reagent, can move to a specimen aspirating position where the specimen vessel **24** (see FIG. **2**) is installed in order to aspirate a specimen, and can move to a specimen and reagent discharging position where the reaction vessel **14** is installed in order to discharge the aspirated specimen and reagent. A tip end of the dispensing probe **30** can move to a position of the dispensing mechanism washing unit **26** (see FIG. **2**) where the tip end of the dispensing probe **30** is washed with washing water or the like. The vertical rotation operation unit **42** is controlled by the analysis control unit **8** (see FIGS. **1** and **2**).

(39) A dispensing flow path **47** is a flow path of the dispensing mechanism **11** that passes through an inner side of the dispensing arm **41** and an inner side of the vertical rotation operation unit **42**. The dispensing probe **30** is connected to a metering pump **45** via the dispensing flow path **47** in the dispensing arm **41**. The metering pump **45** includes a plunger **43** and a drive unit **44**, and is connected to a pump **46** via a valve **49**. The metering pump **45** is controlled by the analysis control unit **8** (see FIGS. **1** and **2**).

(40) An aspiration operation and a discharge operation of the dispensing mechanism **11** are performed by moving up and down the plunger **43** fixed to the metering pump **45** (a reciprocating motion of the plunger **43**). A working fluid (for example, pure water) or the like is filled from the tip end of the dispensing probe **30** to the metering pump **45** and the pump **46** through the dispensing flow path **47**. The dispensing mechanism **11** includes a liquid level detector **48** that detects a liquid level of a specimen, a reagent, and a mixed liquid of a specimen and a reagent. The liquid level detector **48** detects a liquid level according to, for example, a change in capacitance caused by the liquid level being brought into contact with the dispensing probe **30**.

(41) FIG. **4** is a flowchart illustrating a measurement operation of the automatic analyzer **10**. A series of analysis operations in the automatic analyzer **10** will be described with reference to FIG. **4**.

(42) (FIG. **4**: Step **S01**: Preliminary Operation)

(43) When the analysis unit **1** receives an analysis operation start command from the computer **3** via the interface **9**, the reaction vessel washing unit **27** starts to wash the reaction vessel **14**, and a

water blank is measured using pure water discharged from the reaction vessel washing unit **27**. A water blank measurement value serves as a reference of light absorbance to be measured in the reaction vessel **14** thereafter. When the washed reaction vessel **14** is moved to a dispensing position in a circumference of the dispensing mechanism **11** in a rotation direction by an operation of the reaction disk **15** in one cycle (that is, repetition of an intermittent operation of moving the reaction disk **15** for a certain distance and temporarily stopping the reaction disk **15**), the specimen vessel **24** is moved to a specimen dispensing position in the circumference of the dispensing mechanism **11** in the rotation direction by a horizontal operation of the sample rack **25**. At the same time, the reagent disk **21** is rotated so that the reagent vessel **22** of a corresponding analysis item is positioned at a reagent aspirating position in the circumference of the dispensing mechanism **11** in the rotation direction.

(44) (FIG. 4: Step S01)

(45) The dispensing mechanism **11** aspirates air from the air to form an air layer at the tip end of the dispensing probe **30**. The air layer is an air layer that is provided to prevent a working fluid (for example, pure water) filled in the dispensing flow path **47** from the tip end of the dispensing probe **30** and a reagent to be aspirated subsequently from the reagent vessel **22** from being mixed in the dispensing probe **30**. Thereafter, when the dispensing mechanism **11** is moved to a reagent dispensing position by the rotational movement and the vertical movement, the dispensing mechanism **11** aspirates a reagent from the reagent vessel **22** into the dispensing probe **30**.

(46) (FIG. 4: Step S02)

(47) After the reagent is aspirated, the dispensing mechanism **11** is moved to a position in the air by the vertical movement, and aspirates air to form an air layer at the tip end of the dispensing probe **30**. The air layer is an air layer that is provided to prevent a specimen to be aspirated subsequently from the specimen vessel **24** from being mixed with the reagent in the dispensing probe **30**. Then, the dispensing mechanism **11** is moved to the dispensing mechanism washing unit **26** by the rotational movement and the vertical movement, and the tip end of the dispensing probe **30** is washed with washing water. After the dispensing probe **30** is washed, when the dispensing mechanism **11** is moved to the specimen aspirating position by the rotational movement and the vertical movement, the dispensing mechanism **11** aspirates a specimen from the specimen vessel **24** into the dispensing probe **30**.

(48) (FIG. 4: Step S03)

(49) After the specimen is aspirated, the dispensing mechanism **11** is moved to the dispensing mechanism washing unit **26** by the rotational movement and the vertical movement, and the tip end of the dispensing probe **30** is washed with washing water. Next, the dispensing mechanism **11** is moved to the dispensing position by the rotational movement and the vertical movement, and simultaneously dispenses the specimen and the reagent into the reaction vessel **14** by a predetermined amount. Details of dispensing the specimen and the reagent will be described later.

(50) (FIG. 4: Step S04)

(51) After the specimen and the reagent are dispensed, in order to stir a mixed liquid of the specimen and the reagent in the reaction vessel **14**, the dispensing mechanism **11** aspirates a predetermined amount of the mixed liquid, and then discharges the mixed liquid into the reaction vessel **14** again. Accordingly, the mixed liquid is stirred. An operation of performing the aspiration and discharge operations again after the specimen and the reagent are discharged is hereinafter referred to as pipette stirring. Although not particularly illustrated, a stirring operation of a stirring mechanism other than the pipette stirring may be performed. For example, the stirring mechanism is a stirring mechanism having functions such as performing stirring by rotation of a spatula immersed in a reaction liquid or performing stirring by a swirling flow generated by radiating ultrasonic waves. In a case where stirring can be sufficiently performed simply by an operation of simultaneously discharging the specimen and the reagent by the dispensing mechanism **11**, it is not particularly necessary to use the stirring operations described above. The dispensing mechanism **11**

is moved to the dispensing mechanism washing unit by the vertical movement and the rotational movement and the tip end of the dispensing probe **30** is washed with washing water to prepare for a subsequent dispensing operation.

(52) (FIG. 4: Step S05)

(53) After the specimen and the reagent are dispensed or stirred, a measurement to be performed by the spectroscopic detector **13** is started. Photometry is performed when the reaction vessel **14** crosses a light beam during the reaction disk **15** is in rotation. The spectroscopic detector **13** performs photometry for the same reaction vessel **14** for a plurality of times at a time interval determined for each analysis item.

(54) (FIG. 4: Step S06)

(55) Depending on an analysis item, there is an item to which a second reagent is added. In this case, the reagent disk **21** is rotated so that the reagent vessel **22** of a corresponding analysis item is positioned at a reagent aspirating position in the circumference of the dispensing mechanism **11** in the rotation direction after a certain period of time is elapsed from when the specimen and a first reagent are discharged. The dispensing mechanism **11** is moved to the reagent aspirating position by the vertical movement and the rotational movement. The dispensing mechanism **11** aspirates air in the air to form an air layer at the tip end of the probe. The air layer is an air layer that is provided to prevent a working fluid (for example, pure water) filled in the dispensing flow path **47** from the tip end of the dispensing probe **30** and the second reagent to be aspirated subsequently from the reagent vessel **22** from being mixed in the dispensing probe **30**. Thereafter, when the dispensing mechanism **11** is moved to the reagent dispensing position by the rotational movement and the vertical movement, the dispensing mechanism **11** aspirates the second reagent from the reagent vessel into the dispensing probe **30**. The dispensing mechanism **11** is moved to the dispensing mechanism washing unit **26** by the rotational movement and the vertical movement, and the tip end of the dispensing probe **30** is washed with washing water. Next, the dispensing mechanism **11** is moved to the dispensing position by the rotational movement and the vertical movement, and dispenses the second reagent into the reaction vessel **14** by a predetermined amount.

(56) (FIG. 4: Step S07)

(57) Subsequently, a mixed liquid in the reaction vessel **14** is stirred by pipette stirring or a stirring mechanism using a spatula, ultrasonic waves, or the like. When stirring can be sufficiently performed simply by an operation of discharging the second reagent by the dispensing mechanism **11**, the stirring operations described above may not be used.

(58) (FIG. 4: Step S08)

(59) After the second reagent is dispensed or after the stirring is performed, a measurement performed by the spectroscopic detector **13** continues to be performed.

(60) (FIG. 4: Step S09)

(61) After a predetermined time is elapsed, the reaction vessel washing unit **27** discharges a reaction liquid in the reaction vessel **14** for which the measurement is completed, thereby washing the reaction vessel **14** to prepare for a subsequent measurement. During these operations including the washing, another reaction vessel **14** performs an analysis operation (dispensing, photometry operation, or the like) in parallel using another specimen and another reagent. The computer **3** calculates a concentration and an enzyme activity value based on an obtained measurement value (light absorbance). The calculated concentration and enzyme activity value are stored in the memory **6** using the interface **9**. In addition, a result is reported to a user using the display device **5**. Through the above operations, the analysis operation performed by the automatic analyzer **10** is ended.

(62) FIG. 5 is a diagram schematically illustrating a movement of the dispensing probe **30** and its effect when the automatic analyzer **10** simultaneously dispenses the specimen and the first reagent in the first embodiment. FIG. 5 illustrates an operation of the dispensing probe **30** in step S03. Lowercase alphabets in FIG. 5 indicate a time flow of the operation at the time of discharging in

the order of (a), (b), (c), (d), (e), and (f), and the diagrams schematically illustrate respective situations at the time of discharging at an elapsed time. Similarly, in other drawings to be described below, lowercase alphabets indicate a time flow of the discharge operation.

(63) First, the analysis control unit **8** lowers the dispensing mechanism **11** to the vicinity of the bottom of the reaction vessel **14** ((a) in FIG. 5). It is preferable that a position at which the dispensing probe **30** is lowered into the reaction vessel **14** is about several millimeters front the bottom of the reaction vessel **14**. A reason for this will be described later. In the first embodiment, a distance from the bottom of the reaction vessel to the tip end of the dispensing probe **30** is set to about 1 mm to 2 mm. At this time, a specimen **33**, a reagent **32**, and system water **31** (pure water or the like) are held in the dispensing probe **30**. Liquids in the dispensing probe **30** have a positional relationship with a positional relationship of the specimen **33**, the reagent **32**, and the system water **31** in the order from a tip end side to an upper side of the dispensing probe **30** in the vertical direction. A layer of segmented air **37** is present between the specimen **33** and the reagent **32**, and this is provided to prevent the specimen **33** and the reagent **32** from being mixed in the dispensing probe **30**. Similarly, a layer of segmented air **38** is present between the reagent **32** and the system water **31**, and this is provided to prevent the reagent **32** and the system water **31** from being mixed in the dispensing probe **30**. When an operation of simultaneously discharging the specimen **33** and the reagent **32** is started in this state, a liquid is discharged from the tip end of the dispensing probe **30** to the reaction vessel **14** in the order of the specimen **33**, the segmented air **37** (the layer between the specimen **33** and the reagent **32**), and the reagent **32**.

(64) Next, the analysis control unit **8** starts the discharge operation. First, the specimen **33** is discharged from the tip end of the dispensing probe **30**. Then, the analysis control unit **8** controls the dispensing probe **30** to start a lifting operation at the same time as the start of the discharge operation or after several milliseconds (for example, before the tip end of the dispensing probe **30** is immersed in the discharged specimen **33** in the reaction vessel **14**) ((h) FIG. 5).

(65) Subsequently, the analysis control unit **8** controls the lifting operation and the discharge operation of the dispensing probe **30** until the specimen and the reagent are discharged at a specified amount. In addition, the analysis control unit **8** controls a lifting speed of the dispensing probe **30** so that a distance D_a between the tip end of the dispensing probe **30** and a liquid level of a reaction liquid **36** in the reaction vessel **14** increases with an elapsed time ((c), (d), and (e) in FIG. 5).

(66) When discharging of the specimen and the reagent at a specified amount is completed, the analysis control unit **8** ends the discharge operation, and the lifting operation of the dispensing mechanism **11** ((f) in FIG. 5).

(67) The analysis control unit **8** records data of a correspondence relationship between a total discharge amount of the specimen **33** and the reagent **32** (a height of the liquid level of the reaction liquid **36** discharged into the reaction vessel **14**) and a drive pulse and a lifting speed that provide a lifting amount of the dispensing probe **30**. The data is set based on known data such as a dimension of the reaction vessel **14** and a time change (a discharge speed) of a discharge amount. For example, in the first embodiment, the lifting speed and the drive pulse of the dispensing probe **30** are applied so that a change rate a of the distance D_a between the tip end of the dispensing probe **30** and the height of the liquid level of the reaction liquid **36** (a slope when a horizontal axis represents an elapsed time and a vertical axis represents the distance D_a) is 8.0 m/s. The analysis control unit **8** controls the lifting speed of the dispensing probe **30** according to a total discharge amount of the dispensing probe **30** so that the change rate a is constant or changes freely.

(68) FIG. 6A is a relationship diagram between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**. FIG. 6B illustrates an elapsed time change in the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**. An operation of the dispensing probe **30** will be described in detail with reference to FIGS. 6A and 6B. P1, P2, and P3 in FIGS. 6A and 6B

indicate points of an elapsed time. Similarly, P^* (* is a numeral for calculation) displayed in the drawings to be described later indicates a point of an elapsed time, and description thereof will be omitted. In FIGS. 6A and 6B, a discharge operation is started at the point P1, a lifting operation of the dispensing probe 30 is started at the point P2, and the discharge operation and the lifting operation are ended at the point P3.

(69) At the point P1 of the elapsed time, the analysis control unit 8 controls the dispensing probe 30 to start a discharge operation. First, the specimen 33 is discharged from the tip end of the dispensing probe 30 into the reaction vessel 14. At the time point P1, the dispensing probe 30 is stopped at a height of several millimeters above the bottom of the reaction vessel 14, and the lifting operation of the dispensing probe 30 is not yet started. Up to the point P2 when the lifting operation of the dispensing probe 30 is started, that is, from P1 to P2, a liquid level of a discharged liquid rises, and thus the distance D_a between the tip end of the dispensing probe 30 and the liquid level decreases with an elapsed time.

(70) Subsequently, the analysis control unit 8 controls the dispensing probe 30 to start the lifting operation at the point P2 of the elapsed time. A discharged liquid (the specimen 33 or the reagent 32) is continuously discharged from the tip end of the dispensing probe 30. The liquid discharged from the tip end of the dispensing probe 30 at the time point P2 may be either the specimen 33 or the reagent 32. That is, the analysis control unit 8 may bring the dispensing probe 30 into standby (does not start the lifting operation) until all specimens 33 are discharged, and then control the dispensing probe 30 to start the lifting operation after starting discharging of the reagent 32 from the tip end of the dispensing probe 30. The analysis control unit 8 may control the dispensing probe 30 to start the lifting operation at the same time as the start of discharging the specimen 33 (at the point P1 of the elapsed time) or may control the dispensing probe 30 to start the lifting operation during discharging the specimen 33.

(71) After the point P2 of the elapsed time, the analysis control unit 8 controls the dispensing probe 30 to perform the discharge operation and the lifting operation until discharging of a liquid at a specified amount is completed (until P3). In addition, the analysis control unit 8 controls a lifting speed of the dispensing probe 30 so that the distance D_a between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36 in the reaction vessel 14 increases with an elapsed time until discharging of a liquid at a specified amount is completed (until P3). That is, the analysis control unit 8 controls the lifting speed of the dispensing probe 30 so that the above-described change rate α of the distance D_a between the tip end of the dispensing probe 30 and the height of the liquid level of the reaction liquid 36 (for example, $\alpha=8.0$ m/s) is achieved. The analysis control unit 8 ends the discharge operation and the lifting operation of the dispensing probe at the point P3 of the elapsed time when the specimen 33 and the reagent 32 are discharged at a specified amount.

(72) In this manner, a height position 35 (see FIG. 5) at which the discharged liquid arrives in the reaction liquid 36 also gradually changes by increasing the distance D_a between the tip end of the dispensing probe 30 and the height of the liquid level of the reaction liquid 36 with an elapsed time. As a result, a liquid flow can be given to the entire reaction liquid 36, and an effect of efficiently stirring the discharged specimen 33 and reagent 32 by the discharge operation is obtained.

(73) In the above description, a position at which the dispensing probe 30 is lowered into the reaction vessel 14 before the start of discharging is preferably in the vicinity of the bottom of the reaction vessel 14, that is, about several millimeters from the bottom of the reaction vessel 14. When the discharge operation is started, it is assumed that the segmented air 37 between the specimen 33 and the reagent 32 disappears when the segmented air is discharged from the tip end of the probe, and one or both of the specimen 33 and the reagent 32 scatter onto a wall surface of the reaction vessel 14. When the scattered liquid remains adhering to the wall surface of the reaction vessel 14, reaction of the reaction liquid does not proceed sufficiently, which may adversely affect an analysis result. In recent years, a technique for reducing an amount of a

specimen used in a measurement has been advanced due to the trend of reducing burdens on a patient. It is assumed that the number of specimens used in a measurement is as small as about 40 μ L. Therefore, discharging is started when a position of the tip end of the dispensing probe **30** at the start of discharging is in the vicinity of the bottom of the reaction vessel **14** (in the last embodiment, the position of the tip end of the dispensing probe **30** is set to 1 to 2 mm from the bottom of the reaction vessel **14**), and the segmented air **37** between the specimen **33** and the reagent **32** is discharged in the vicinity of the bottom of the reaction vessel **14**. Accordingly, even when scattering of the discharged liquid occurs due to the segmented air **37** between the specimen **33** and the reagent **32**, since the reagent continues to be discharged from a higher position thereafter, the scattered liquid adhering to the reaction vessel **14** is buried in the reaction liquid **36** as the liquid level rises. In this manner, the analysis control unit **8** controls the dispensing probe **30** to be lowered to the vicinity of the bottom of the reaction vessel **14** and controls the start of the discharge operation, so that an influence of scattering can be reduced, and an effect of improving analysis performance is obtained.

First Embodiment: Summary

(74) When the specimen **33** and the reagent **32** that are different liquids are simultaneously discharged, the automatic analyzer **10** according to the first embodiment can gradually change an arrival position of a height of the discharged liquid in the reaction liquid **36** by increasing the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** with an elapsed time. As a result, a large liquid flow can be given to the entire reaction liquid, and the specimen **33** and the reagent **32** can be efficiently stirred at the time of discharging. When stirring can be efficiently performed at the time of discharging, a time required for a subsequent additional stirring operation (pipette stirring or the like) can be shortened, and processing capacity is improved. When stirring can be sufficiently performed at the time of discharging, an additional stirring mechanism (stirring using ultrasonic waves or the like) is not necessary, which leads to space saving of a device.

(75) In the automatic analyzer **10** according to the first embodiment, the dispensing probe **30** is lowered to the vicinity of a bottom portion of the reaction vessel **14** to start discharging, so that a position to which a scattered liquid adheres due to the segmented air **38** between the specimen **33** and the reagent **32** can be restricted to the vicinity of the bottom portion of the reaction vessel **14**. The lifting operation of the probe is started at the same time as or several milliseconds after the start of discharging, so that the reagent **32** is discharged from a high position while the dispensing probe **30** is raised, and thus the scattered liquid adhering to the reaction vessel **14** is buried in the reaction liquid **36** due to the rise of the liquid level of the reaction liquid **36**. As a result, an influence of scattering on measurement data can be reduced, and analysis performance can be improved.

(76) Although not particularly illustrated, the automatic analyzer **10** according to the first embodiment may have a configuration of an automatic analyzer and a dispensing flow as will be described below. The dispensing probe **30** aspirates the specimen **33** from the specimen vessel **24** and discharges the specimen **33** to the reaction vessel **14**. Subsequently, the tip end of the dispensing probe **30** is washed by the dispensing mechanism washing unit **26**, and then the dispensing probe **30** aspirates the reagent **32** from the reagent vessel **22**. Then, after the tip end of the dispensing probe **30** is washed by the dispensing mechanism washing unit **26**, the analysis control unit **8** lowers the dispensing probe **30** to the vicinity of a height of a liquid level (for example, 1 mm above the liquid level) of the specimen **33** in the reaction vessel **14**. Thereafter, the analysis control unit **8** controls the dispensing probe **30** to start the lifting operation at the same time as the start of the discharge operation of the reagent **32** or after several milliseconds. Subsequently, the analysis control unit **8** controls the dispensing probe **30** to perform the lifting operation and the discharge operation until the reagent **32** is discharged at a specified amount. In addition, the analysis control unit **8** controls the lifting speed of the dispensing probe **30** so that the

distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** in the reaction vessel **14** increases with an elapsed time. As a result, an arrival position of a height of a discharged liquid in the reaction liquid **36** can be gradually changed. A large liquid flow can be given to the entire reaction liquid, and the specimen **33** and the reagent **32** can be efficiently stirred at the time of discharging.

(77) Although not particularly illustrated, the automatic analyzer **10** according to the first embodiment may have a configuration of an automatic analyzer and a dispensing flow as will be described below. The automatic analyzer **10** includes two dispensing probes **30**. That is, the automatic analyzer **10** includes a specimen probe that dispenses the specimen **33** and a reagent probe that dispenses the reagent **32**. The specimen probe aspirates the specimen **33** from the specimen vessel **24**. The reagent probe aspirates the reagent **32** from the reagent vessel **22**. After tip ends of the two probes are washed by the dispensing mechanism washing unit **26**, the analysis control unit **8** lowers the specimen probe and the reagent probe to the vicinity of the bottom of the reaction vessel **14**, and starts to discharge the specimen **33** from the specimen probe and discharge the reagent **32** from the reagent probe. The analysis control unit **8** controls the dispensing probe **30** to start the lifting operation at the same time as the start of discharging or after several milliseconds. Subsequently, the analysis control unit **8** controls the dispensing probe **30** to perform the lifting operation and the discharge operation until the reagent **32** is discharged at a specified amount. In addition, the analysis control unit **8** controls the lifting speed of the dispensing probe **30** so that the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** in the reaction vessel **14** increases with an elapsed time. As a result, an arrival position of a height of a discharged liquid in the reaction liquid **36** can be gradually changed. A large liquid flow can be given to the entire reaction liquid, and the specimen **33** and the reagent **32** can be efficiently stirred at the time of discharging.

(78) Further, although not particularly illustrated, the automatic analyzer **10** according to the first embodiment may have a configuration of an automatic analyzer and a dispensing flow as will be described below. The second reagent may be discharged into the reaction vessel **14** in step **S06**. The analysis control unit **8** lowers the dispensing probe **30** to the vicinity of a height of a liquid level (for example, 1 mm above the liquid level) of a reaction liquid (a mixed liquid of the specimen **33** and the reagent **32**) in the reaction vessel **14**. Thereafter, the analysis control unit **8** controls the dispensing probe **30** to start the lifting operation at the same time as the start of the discharge operation of the second reagent or after several milliseconds. Subsequently, the analysis control unit **8** controls the dispensing probe **30** to perform the lifting operation and the discharge operation until the second reagent is discharged at a specified amount. In addition, the analysis control unit **8** controls the lifting speed of the dispensing probe **30** so that the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** in the reaction vessel **14** increases with an elapsed time. As a result, an arrival position of a height of a discharged liquid in the reaction liquid **36** can be gradually changed. A large liquid flow can be given to the entire reaction liquid, and the reaction liquid (the mixed liquid of the specimen **33** and the reagent **32**) and the second reagent can be efficiently stirred at the time of discharging.

Second Embodiment

(79) In the first embodiment, the analysis control unit **8** controls the lifting speed of the dispensing probe **30** so that the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** in the reaction vessel **14** increases with an elapsed time until discharging of the reagent of a specified amount is completed in step **S03**. A procedure for lifting the dispensing probe **30** is not limited thereto.

(80) In the second embodiment, after the analysis control unit **8** performs control for a predetermined time so that the distance D_a increases with an elapsed time, the analysis control unit **8** performs control so that the distance D_a decreases with an elapsed time. In this case, the same effects as those of the first embodiment can also be obtained. Since the configuration of the

automatic analyzer **10** is the same as that in the first embodiment, differences in the dispensing operation will be mainly described below.

(81) FIG. **7** is a diagram schematically illustrating a movement of the dispensing probe **30** and its effect when the automatic analyzer **10** simultaneously dispenses the specimen and the first reagent in the second embodiment. A time change of a position of the tip end of the dispensing probe **30** in FIG. **7** will be described with reference to FIGS. **8A** and **8B**.

(82) FIG. **8A** illustrates a relationship between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**. FIG. **8B** illustrates an elapsed time change in the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**. The second embodiment will be described in detail with reference to FIGS. **8A** and **8B**. Lifting control of the dispensing probe **30** performed by the analysis control unit **8** is the same as that in the first embodiment, and thus description thereof will be omitted.

(83) The analysis control unit **8** controls the dispensing probe **30** to start the discharge operation (P4), and lifts the probe of the dispensing probe **30** so that the distance D_a increases with an elapsed time (P5 to P6). After a certain period of time is elapsed, the analysis control unit **8** stops the lifting operation of the dispensing probe **30** at the P6 of the elapsed time at a time point before discharging of the reagent of a specified amount is completed). At the time point P6, the discharge operation is continued. The analysis control unit **8** ends the discharge operation at a point P7 of the elapsed time when the reagent is discharged at a specified amount. That is, the analysis control unit **8** performs control to increase the distance D_a from the point P5 of the elapsed time to the point P6 of the elapsed time, and performs control to decrease the distance D_a from the point P6 to the point P7 of the elapsed time.

Second Embodiment: Summary

(84) The automatic analyzer **10** according to the second embodiment moves the dispensing probe **30** so as to increase the distance D_a , and then moves the dispensing probe **30** so as to decrease the distance D_a by fixing a position of the dispensing probe **30** in the vertical direction. The second embodiment can obtain the same effects as those of the first embodiment.

Third Embodiment

(85) In step S03, the analysis control unit **8** may perform control to immerse the tip end of the dispensing probe **30** into the liquid level of the reaction liquid **36** when discharging of the reagent of a specified amount is completed (when discharging of the reagent **32** is completed). In a third embodiment, a specific example will be described. In this case, the same effects as those of the first embodiment can also be obtained. Since the configuration of the automatic analyzer **10** is the same as that in the first embodiment, differences in a dispensing operation will be mainly described below.

(86) FIG. **9** is a diagram schematically illustrating a movement of the dispensing probe **30** and its effect when the automatic analyzer **10** simultaneously dispenses the specimen and the first reagent in the third embodiment. A time change of a position of the tip end of the dispensing probe **30** in FIG. **9** will be described with reference to FIGS. **10A** and **10B**.

(87) FIG. **10A** illustrates a relationship between the height of the tip end of the dispensing probe **30** from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**. FIG. **10B** illustrates an elapsed time change in the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**. The third embodiment will be described in detail with reference to FIGS. **10A** and **10B**. Lifting control of the dispensing probe **30** performed by the analysis control unit **8** is the same as that in the first embodiment, and thus description thereof will be omitted.

(88) The analysis control unit **8** controls the dispensing probe **30** to start the discharge operation (P8), and controls a probe lining operation of the dispensing probe **30** so that the distance D_a increases with an elapsed time (P9 to P10). After a certain period of time is elapsed, the analysis

control unit **8** stops the lifting operation of the dispensing probe **30** at the point PICT of the elapsed time (at a time point before discharging of the reagent of a specified amount is completed). At this time, the analysis control unit **8** stops the lifting operation of the dispensing probe **30** so that a stopping position of the dispensing probe **30** is located at a position lower than the height of the liquid level of the reaction liquid **36** after the reagent is discharged at a specified amount. Thereafter, the discharge operation is ended at a point P11 of the elapsed time. That is, at the point P11 of the elapsed time when discharging of the reagent of a specified amount is completed, the tip end of the dispensing probe **30** is in a state of being immersed in the reaction liquid **36**. It is preferable that an immersing amount of the tip end of the dispensing probe **30** is about several millimeters (for example, 4 mm) in order to reduce a contamination range of the tip end of the dispensing probe.

(89) The liquid level detector **48** may detect the liquid level at the point P11 of the elapsed time. Due to a difference in wettability of the reaction liquid **36** (due to an influence of meniscus), it is expected that the height of the liquid level of the reaction liquid **36** is slightly different from known data. Therefore, the liquid level may be detected using the liquid level detector **48** after the discharge operation of the dispensing probe **30** is completed, and it may be confirmed whether the tip end of the dispensing probe **30** is accurately immersed in the reaction liquid **36** after discharging is completed.

Third Embodiment: Summary

(90) In the automatic analyzer **10** according to the third embodiment, the analysis control unit **8** controls the tip end of the dispensing probe **30** to be immersed in the reaction liquid **36** when discharging of the reagent is completed. For example, under a condition that the liquid discharging at the tip end of the dispensing probe **30** at the end of discharging is poor and liquid droplets are formed at the tip end of the dispensing probe **30**, the liquid droplets may not be discharged into the reaction vessel **14**, and the reagent may not be accurately dispensed at a specified amount. When the tip end of the dispensing probe **30** is immersed in the liquid level at the end of discharging, the liquid droplets can be immersed in the reaction liquid, and the reagent can be accurately dispensed at a specified amount. As a result, analysis performance is improved.

(91) The automatic analyzer **10** according to the third embodiment can accurately determine whether the tip end of the dispensing probe **30** is immersed in the liquid level of the reaction liquid **36** by the liquid level detector **48** detecting the liquid level at the end of discharging. When the liquid level detector **48** does not detect the liquid level, since dispensing performance deteriorates due to the formation of the liquid droplets at the tip end of the dispensing probe **30**, the analysis control unit **8** may add a data alarm indicating that the liquid level cannot be detected on the display device **5** via the interface **9**. As a result, a user can know a cause of data failure, and can appropriately deal with the data failure, for example, by requesting a re-inspection. Appropriate measurement data can be obtained by performing a re-inspection, which leads to an improvement in reliability of a measurement result.

Fourth Embodiment

(92) In step S03, the analysis control unit **8** may perform control to stop the tip end of the dispensing probe **30** above the liquid level of the reaction liquid **36** when discharging of the reagent of a specified amount is completed (when discharging of the reagent **32** is completed). In a fourth embodiment, a specific example will be described. In this case, the same effects as those of the first embodiment can also be obtained. Since the configuration of the automatic analyzer **10** is the same as that in the first embodiment, differences in a dispensing operation will be mainly described below.

(93) FIG. **11** is a diagram schematically illustrating a movement of the dispensing probe **30** and its effect when the automatic analyzer **10** simultaneously dispenses the specimen and the first reagent in the fourth embodiment. A time change of a position of the tip end of the dispensing probe **30** in FIG. **11** will be described with reference to FIGS. **12A** and **12B**.

(94) FIG. 12A illustrates a relationship between the height of the tip end of the dispensing probe 30 from the bottom of the reaction vessel 14 and the height of the liquid level of the reaction liquid 36. FIG. 12B illustrates an elapsed time change in the distance Da between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36. The fourth embodiment will be described in detail with reference to FIGS. 12A and 12B. Lifting control of the dispensing probe 30 performed by the analysis control unit 8 is the same as that in the first embodiment, and thus description thereof will be omitted.

(95) The analysis control unit 8 controls the dispensing probe 30 to start the discharge operation (P12), and controls the probe lifting operation of the dispensing probe 30 so that the distance Da increases with an elapsed time (P13 to P14). After a certain period of time is elapsed, the analysis control unit 8 stops the lifting operation of the dispensing probe 30 at the point P14 of the elapsed time (at a time point before discharging of the reagent of a specified amount is completed). At this time, the analysis control unit 8 stops the lifting operation of the dispensing probe 30 so that the stopping position of the dispensing probe 30 is located at a position higher than the liquid level of the reaction liquid 36 after the reagent is discharged at a specified amount. Thereafter, the discharge operation is ended at a point P15 of the elapsed time. That is, at the point P15 of the elapsed time when discharging of the reagent of a specified amount is completed, the tip end of the dispensing probe 30 is located at a position higher than the liquid level of the reaction liquid 36.

Fourth Embodiment: Summary

(96) In the automatic analyzer 10 according to the fourth embodiment, the analysis control unit 8 controls the tip end of the dispensing probe 30 to be higher than the liquid level of the reaction liquid 36 at the end of discharging. For example, in step S04 in FIG. 4, when pipette stirring (stirring by aspirating and discharging the reaction liquid 36 again after discharging) is performed, a state in the dispensing probe 30 before the start of the pipette stirring is a state in which the dispensing probe 30 is filled with a liquid (system water or the like). In order to prevent the reaction liquid 36 to be aspirated again in the dispensing probe 30 and the liquid (such as the system water 31) in the tip end of the dispensing probe 30 from being mixed by the pipette stirring, it is necessary to aspirate air before aspirating the reaction liquid 36 again. That is, it is necessary to form a layer of segmented air between the reaction liquid 36 and the system water 31. When the specimen and the reagent discharge operation of the dispensing probe 30 is completed in a state in which the tip end of the dispensing probe 30 is immersed in the reaction liquid 36, it is necessary to add a lifting operation of pulling out the tip end of the dispensing probe 30 from the reaction liquid 36 in order to form the layer of segmented air. On the other hand, as in the fourth embodiment, when the tip end of the dispensing probe 30 is stopped above the liquid level of the reaction liquid 36 at the end of discharging, the tip end of the dispensing probe 30 is in the air, so that air can be aspirated without the necessary to add the lifting operation. As a result, an operation time from the start of discharging by the dispensing probe 30 to the end of stirring (pipette stirring) is reduced, and the effect of improving processing capacity of the automatic analyzer 10 is obtained.

Fifth Embodiment

(97) In step S03, the analysis control unit 8 may perform control such that the tip end of the dispensing probe 30 is immersed in the discharged specimen 33 or the liquid level of the reaction liquid 36 for a certain period of time after the start or the end of discharging of the specimen 33. In a fifth embodiment, a specific example will be described. In this case, the same effects as those of the first embodiment can also be obtained. Since the configuration of the automatic analyzer 10 is the same as that in the first embodiment, differences in a dispensing operation will be mainly described below.

(98) FIG. 13 is a diagram schematically illustrating a movement of the dispensing probe 30 and its effect when the automatic analyzer 10 simultaneously dispenses the specimen and the first reagent in the fifth embodiment. A time change of a position of the tip end of the dispensing probe 30 in FIG. 13 will be described with reference to FIGS. 14A and 14B.

(99) FIG. 14A illustrates a relationship between the height of the tip end of the dispensing probe 30 from the bottom of the reaction vessel 14 and the height of the liquid level of the reaction liquid 36. FIG. 14B illustrates an elapsed time change in the distance Da between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36. The fifth embodiment will be described in detail with reference to FIGS. 14A and 14B. Lifting control of the dispensing probe 30 performed by the analysis control unit 8 is the same as that in the first embodiment, and thus description thereof will be omitted.

(100) The analysis control unit 8 controls the dispensing probe 30 to start the discharge operation (P16). The analysis control unit 8 may perform control such that the tip end of the dispensing probe 30 is immersed in the discharged specimen 33 or the reaction liquid 36 (a mixed liquid of the specimen 33 and the reagent 32) for a certain period of time after discharging of the specimen 33 is completed. That is, the analysis control unit 8 controls a lowering amount of the dispensing probe 30 to the reaction vessel 14 before the start of the discharge so as to immerse the tip end of the dispensing probe 30 in the discharged specimen 33 and the reaction liquid 36 (the specimen 33 and the reagent 32) for a certain period of time after discharging of the specimen 33 is completed, and after the tip end of the dispensing probe 30 is immersed, the analysis control unit 8 performs control to lift the dispensing probe 30 while discharging the reagent 32. Alternatively, the analysis control unit 8 may perform control such that the tip end of the dispensing probe 30 is in standby at a discharge start position until the tip end of the dispensing probe 30 is immersed in the discharged specimen 33 or the reaction liquid 36 (the specimen 33 and the reagent 32) for a certain period of time after discharging of the specimen 33 is completed, and thereafter perform control to lift the dispensing probe 30 while discharging the reagent 32.

(101) It is preferable that the immersing amount of the tip end of the dispensing probe 30 is about several millimeters in order to reduce a contamination range of a nozzle tip end. For example, it is preferable that the analysis control unit 8 controls the dispensing probe 30 such that the immersing amount of the tip end of the dispensing probe 30 is about 4 mm or less.

Fifth Embodiment: Summary

(102) In the automatic analyzer 10 according to the fifth embodiment, the tip end of the dispensing probe 30 is immersed in the specimen 33 or the liquid level of the reaction liquid 36 (the specimen 33 and the reagent 32) in the vessel for a certain period of time after the start or after the end of discharging the specimen 33. Accordingly; for example, when the tip end of the probe is immersed in a liquid when all specimens are discharged, the segmented air 37 that is present between the specimen 33 and the reagent 32 and is subsequently discharged from the tip end of the dispensing probe 30 is discharged into the specimen 33 or into the reaction liquid 36 of the specimen 33 and the reagent 32. In this case, since the tip end of the dispensing probe 30 is in the liquid, it is possible to prevent an influence of liquid scattering caused by the segmented air 37. That is, analysis performance can be improved.

Sixth Embodiment

(103) In step S03, the analysis control unit 8 may perform control to start to discharge the specimen 33 and the reagent 32 after lowering the tip end of the probe to the vicinity of a height of a liquid level when the dispensing probe 30 discharges all the specimens 33 into the reaction vessel 14. In a sixth embodiment, a specific example will be described. In this case, the same effects as those of the first embodiment can also be obtained. Since the configuration of the automatic analyzer 10 is the same as that in the first embodiment, differences in a dispensing operation will be mainly described below.

(104) FIG. 15 is a diagram schematically illustrating a movement of the dispensing probe 30 and its effect when the automatic analyzer 10 simultaneously dispenses the specimen and the first reagent in the sixth embodiment. A time change of a position of the tip end of the dispensing probe 30 in FIG. 15 will be described with reference to FIGS. 16A and 16B.

(105) FIG. 16A illustrates a relationship between the height of the tip end of the dispensing probe

30 from the bottom of the reaction vessel **14** and the height of the liquid level of the reaction liquid **36**. FIG. **16B** illustrates an elapsed time change in the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36**. The sixth embodiment will be described in detail with reference to FIG. **15** and FIGS. **16A** and **16B**. Lifting control of the dispensing probe **30** performed by the analysis control unit **8** is the same as that in the first embodiment, and thus description thereof will be omitted.

(106) The analysis control unit **8** lowers the dispensing probe **30** into the reaction vessel **14** ((a) in FIG. **15**). At this time, the analysis control unit **8** lowers the tip end of the dispensing probe **30** to the vicinity of a height of a liquid level (for example, to the same height as the liquid level or within 1 mm above the liquid level) when the tip end of the dispensing probe **30** discharges all of the specimens **33** at a specified amount. The analysis control unit **8** starts the discharge operation of the dispensing probe **30** (a point **P20** of the elapsed time). At a point **P21** of the elapsed time, a height of the tip end of the dispensing probe **30** is the same as or several millimeters higher than a height of a liquid level of the discharged specimen **33**.

Sixth Embodiment: Summary

(107) In the automatic analyzer **10** according to the sixth embodiment, the dispensing probe **30** is lowered to the vicinity of the height of the liquid level when all of the specimens **33** of a specified amount are discharged into the reaction vessel **14**, and then discharging of the specimen **33** is started. As a result, for example, when the height of the tip end of the dispensing probe **30** is the same as the height of the specimen **33** or at a position several millimeters above the specimen **33** when all specimens are discharged, the segmented air **37** that is present between the specimen **33** and the reagent **32** and is subsequently discharged from the tip end of the dispensing probe **30** is discharged in the air. Since the segmented air **37** is discharged in the air, it is possible to prevent air bubbles derived from the segmented air **37** from being mixed into the liquid. When air bubbles are mixed into the reaction liquid and adhere to an optical path region of the light source **12** in the reaction vessel **14**, measurement data may be affected. According to the sixth embodiment, analysis performance is improved by preventing the mixing of the air bubbles.

Seventh Embodiment

(108) In step **S03**, the analysis control unit **8** may change a lifting speed of the dispensing probe **30** in accordance with liquid property information of a discharged solution. The term "liquid property" used herein refers to viscosity polarity, contact angle, and the like. Due to differences in viscosity, polarity, contact angle, and the like of a discharged liquid, intermolecular forces of the specimen **33** and the reagent **32** are also different. In this case, a liquid arrival height of the discharge liquid and a liquid flow state of the discharged liquid relative to the reaction liquid **36** that is a mixed liquid of the specimen **33** and the reagent **32** at the time of discharging are different depending on the liquid property. In a seventh embodiment, the liquid property of the solution and the change rate a of the distance D_a that is suitable to obtain a large stirring effect at the time of discharging are recorded in association with each other as data in the memory **6** in advance. Alternatively, a user may input viscosity information, contact angle information, and the like of a reagent serving as an analysis item to the analysis control unit **8** via the keyboard **2** at the time of requesting the analysis item before the start of a measurement. Other configurations are the same as those according to the first embodiment.

(109) Before the dispensing probe **30** starts discharging, the analysis control unit **8** reads the change rate a corresponding to the liquid property of the solution from the memory **6**. Then, the analysis control unit **8** controls an appropriate lifting speed of the dispensing probe **30** which will obtain a large stirring effect at the time of discharging. Regarding viscosity information, the computer **3** can acquire a pressure waveform at the time of aspirating the specimen **33** and at the time of aspirating the reagent **32**, analyze viscosity of the specimen **33** and the reagent **32** based on the pressure waveform, and input an analysis result to the analysis control unit **8**.

(110) In the automatic analyzer **10** according to the seventh embodiment, it is possible to efficiently

stir the specimen **33** and the reagent **32** that are different liquids when the specimen **33** and the reagent **32** are simultaneously discharged by changing the lifting speed of the dispensing probe **30** according to the liquid property of the solution.

Experimental Example

(111) Hereinafter, the effect of improving stirring efficiency at the time of simultaneously discharging a specimen and a reagent in the present embodiment will be described using experimental results. The following experimental results are used to describe the effect of the present embodiment, and a technical scope of the invention is not limited by the following experimental results.

(112) An experiment was performed using the automatic analyzer **10** according to the first embodiment. The following two conditions were used. According to the condition of the first embodiment, after lifting of the dispensing probe **30** was started, the lifting speed of the dispensing probe **30** was controlled such that the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** increased with an elapsed time. According to a condition in a comparative example, after lifting of the dispensing probe **30** was started, the lifting speed of the dispensing probe **30** was controlled such that the distance D_a between the tip end of the dispensing probe **30** and the liquid level of the reaction liquid **36** was constant regardless of an elapsed time, and a state in which the tip end of the dispensing probe was immersed by 2 mm from the liquid level of the reaction liquid **36** was maintained. After the specimen **33** and the reagent **32** are simultaneously discharged, stirring such as pipette stirring or stirring using ultrasonic waves is not performed.

(113) An aqueous solution to which a dye was added was used as the specimen **33**, and a colorless and transparent solution having viscosity was used as the reagent **32**. The specimen **33** and the reagent **32** were simultaneously discharged, and light absorbance (specific light absorbance of the dye used as the specimen) after a predetermined elapsed time was measured. A deviation rate (%) from light absorbance at the time of complete mixing was calculated based on the measured light absorbance and light absorbance in a state where the specimen and the dye were completely mixed. A lower deviation rate (%) indicates that a state of stirring performed by discharging only is close to a completely mixed state. That is, it can be said that stirring can be more efficiently performed by a discharge operation as the deviation rate (%) decreases.

(114) Further, the light absorbance was measured every certain period of time immediately after discharging, and a light absorbance fluctuation rate (%) for 5 minutes was calculated. The light absorbance fluctuation rate (%) for 5 minutes indicates a ratio of a range of light absorbance data acquired for a plurality of times in 5 minutes (maximum light absorbance value minimum light absorbance value) to light absorbance 5 minutes after discharging. In a state in which stirring is not efficiently performed at the time of discharging, the light absorbance fluctuates due to a diffusion phenomenon of the specimen fa dye liquid) even after the end of discharging, and thus the light absorbance fluctuation rate (%) increases. That is, it can be said stirring can be more efficiently performed as the light absorbance fluctuation rate (%) for 5 minutes decreases.

(115) FIG. **17** is a diagram illustrating a deviation rate (%) for each of the first embodiment and the comparative example. A measurement is performed for a plurality of times under a condition of each of the first embodiment and the comparative example, and the deviation rate (%) is plotted. As can be seen from FIG. **17** according to the first embodiment, the deviation rate (%) from complete mixing is low, and fluctuation among multiple measurements is small.

(116) FIG. **18** is a diagram illustrating a light absorbance fluctuation rate (%) for 5 minutes for each of the first embodiment and the comparative example. A measurement is performed for a plurality of times under the condition of each of the first embodiment and the comparative example, and the light absorbance fluctuation rate (%) is plotted. As can be seen from FIG. **18**, according to the first embodiment, the light absorbance fluctuation rate (%) is low, and fluctuation among measurements is small. Therefore, it can be understood that stirring can be performed more efficiently at the time

of discharging in the first embodiment. That is, after lifting of the dispensing probe 30 is started, when the lifting speed of the dispensing probe 30 is controlled such that the distance Da between the tip end of the dispensing probe 30 and the liquid level of the reaction liquid 36 increases with an elapsed time, it is possible to efficiently stir a specimen and a reagent at the time of simultaneously discharging the specimen and the reagent.

Modifications of Invention

(117) The invention is not limited to the embodiments described above, and includes various modifications. For example, the above-described embodiments are described in detail for easy understanding of the invention, and the invention is not necessarily limited to those including all the configurations described above. A part of a configuration of one embodiment can be replaced with a configuration of another embodiment, and the configuration of another embodiment can be added to the configuration of one embodiment. A part of a configuration of each embodiment can be added, deleted, or replaced with another configuration.

REFERENCE SIGNS LIST

(118) 1: analysis unit 2: keyboard 3: computer 4: printer 5: display device 6: memory 7: A/D converter 8: analysis control unit 11: dispensing mechanism 12: light source 13: spectroscopic detector 14: reaction vessel 15: reaction disk 21: reagent disk 22: reagent vessel 24: specimen vessel 25: sample rack 26: dispensing mechanism washing unit 30: dispensing probe 31: system water 32: reagent 33: specimen 36: reaction liquid 41: dispensing arm 42: vertical rotation operation unit 43: plunger 44: drive unit 45: metering pump 46: pump 47: dispensing flow path 48: liquid level detector 49: valve

Claims

1. A device for preparing a specimen for an automatic analyzer, the device comprising: a probe configured to aspirate and discharge the specimen and a reagent via a tip end of the probe; and a control unit that is coupled to the probe, wherein the control unit is configured to: form a first air layer within the probe by aspirating air into the probe and then aspirating the reagent into the probe, wherein the first air layer is a barrier between the reagent and working fluid in the probe, form, after forming the first air layer, a second air layer within the probe by aspirating the air into the probe and then aspirating the specimen into the probe, wherein the second air layer is a barrier between the reagent and the specimen, discharge the specimen and the reagent from the probe into a vessel, determine a time change of a discharge amount using a discharge speed of the discharge amount and a duration of discharge of the reagent and the specimen discharged into the vessel, detect a height of a liquid surface level of the reagent and the specimen discharged into the vessel, wherein the height of the liquid surface is detected using at least a dimension of a reaction vessel and the time change of the discharge amount, continuously determine a distance between the tip end of the probe and the liquid surface based on at least the height of the liquid surface and the discharge amount of the specimen and the reagent from the probe into the vessel, wherein the distance is above the liquid surface, and lift the probe while the specimen and the reagent are discharged so that, the distance between the liquid surface and the tip end of the probe is increased while the specimen and the reagent are discharged.
2. The device according to claim 1, wherein the control unit is further configured to: discharge the specimen from the probe to the vessel after the tip end of the probe is moved below an inlet of the vessel, and not move the probe in a vertical direction while the probe discharges the specimen to the vessel.
3. The device according to claim 1, wherein subsequent to the distance being increased, the control unit is further configured to: decrease the distance while the discharge of the specimen and the reagent is completed.
4. The device according to claim 3, wherein the control unit is further configured to: decrease the

distance by fixing a position of the probe in a height direction.

5. The device according to claim 3, wherein the control unit is further configured to: lift the probe so that the tip end of the probe is immersed below the liquid surface when the discharge is complete.
 6. The device according to claim 5, wherein the control unit is further configured to output an alert when the tip end of the is above the liquid surface when the discharge is completed.
 7. The device according to claim 3, wherein the control unit is further configured to: finish the discharge when the probe is at a fixed position.
 8. The device according to claim 1, wherein the control unit is further configured to before the probe starts the discharge the specimen, lower the probe to a height within 1 mm above the liquid surface when the probe finishes the discharge.
 9. The device according to claim 1, further comprising: a storage unit that stores data describing liquid characteristics of the specimen or liquid characteristics of the reagent, wherein the control unit controls a lifting rate of the probe according to the liquid characteristics described in the data.
 10. The device according to claim 9, wherein the liquid characteristics include at least one of viscosity or a contact angle.
-