

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405574
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Beugin; Stéphane et al.

Natural escapement for horological movement and horological movement comprising such an escapement

Abstract

A natural escapement for horological movement including a balance that moves from a first extreme position to a second extreme position and vice versa by passing through a middle locking position, this balance including a balance wheel on an arbor of which is adjusted a balance plate, the natural escapement also including a first escape wheel set driven by a wheel set of the train of the horological movement and driving in turn a second escape wheel set, the first and second escape wheel sets forming a kinematic chain cooperating with an anchor, the balance plate carrying a second impulse pallet-stone which receives a driving impulse from the first escape wheel set during the first alternation, and a first impulse pallet-stone which receives a driving impulse from the second escape wheel set during the second alternation.

Inventors:	Beugin; Stéphane (Les Rousses, FR), Macé; Jérôme (Le Pont, CH)
Applicant:	Montres Breguet S.A. (L'Abbaye, CH)
Family ID:	78957934
Assignee:	Montres Breguet S.A. (L'Abbaye, CH)
Appl. No.:	18/051912
Filed:	November 02, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230251604 A1	Aug. 10, 2023

Foreign Application Priority Data

EP	21215870	Dec. 20, 2021
----	----------	---------------

Publication Classification

Int. Cl.: G04B15/08 (20060101); G04B15/14 (20060101)

U.S. Cl.:

CPC G04B15/08 (20130101); G04B15/14 (20130101);

Field of Classification Search

CPC: G04B (15/00); G04B (15/06); G04B (15/08); G04B (15/14)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2690048	12/1953	Smith	N/A	N/A
7604395	12/2008	Cabezas Jurin	368/127	G04B 15/06
8308346	12/2011	Conus	368/131	G04B 15/08
11402804	12/2021	Favre	N/A	G04B 15/14
12055894	12/2023	Zaugg	N/A	G04B 17/063
2015/0177690	12/2014	Di Domenico	368/126	G04B 17/06
2016/0266546	12/2015	Di Domenico	N/A	G04C 5/00
2023/0185240	12/2022	Zaugg	N/A	G04B 15/08

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
286913	12/1951	CH	N/A
712 631	12/2016	CH	N/A
112368648	12/2020	CN	N/A
113608424	12/2020	CN	N/A
2565730	12/2012	EP	N/A
2008268209	12/2007	JP	N/A
2012168172	12/2011	JP	N/A
2017013611	12/2016	WO	N/A

OTHER PUBLICATIONS

European Search Report issued May 20, 2022 in European Application 21215870.3 filed on Dec. 20, 2021 (with English Translation of Categories of Cited Documents), 3 pages. cited by applicant
Chinese Office Action issued in Chinese Patent Application No. 202211648398.0 on Apr. 21, 2025. cited by applicant

Primary Examiner: Leon; Edwin A.

Assistant Examiner: Collins; Jason M

Attorney, Agent or Firm: Oblon, McClelland, Maier & Neustadt, L.L.P.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims priority to European Patent Application No. 21215870.3 filed on Dec. 20, 2021, the entire disclosure of which is hereby incorporated herein by reference.

TECHNICAL FIELD OF THE INVENTION

(2) The present invention relates to a natural escapement for horological movement also known under its name tangential impulse escapement. The present invention more particularly relates to a natural escapement protected against the damages that may be caused by a premature release of the escapement impulse in the absence of the balance. The present invention also relates to a horological movement comprising such an escapement.

TECHNOLOGICAL BACKGROUND

(3) The principle of the natural escapement was invented by Abraham Louis Breguet at the beginning of the 19th Century. The advantage of Breguet's natural escapement is particularly that it is a free escapement insofar as the balance is only disturbed by the operation of the escapement over a small fraction of its oscillation. The advantage of Breguet's natural escapement is also that it gives with each alternation a direct and tangential impulse to the balance. In other words, energy is transferred directly from the escape wheel to the balance, without passing through an anchor. Moreover, the transmission of energy only takes place tangentially, so that the frictions generated by the operation of this escapement are limited. Unlike a detent escapement, a natural escapement does not have a coup perdu in its function for maintaining oscillations of the balance; it delivers a similar impulse with each alternation, in a symmetrical and more uniform manner, so that the losses of mechanical energy by coup perdu are eliminated. All of these qualities thus make the natural escapement potentially one of the most efficient.

(4) Breguet nevertheless subsequently discovered that the natural escapement that he had invented had certain drawbacks foremost of which mention may be made of the fact that the last escape wheel is not under the tension of the train when the first wheel gives the impulse or when the latter is locked. The various plays of the gears and the manufacturing quality of the various components incorporated into the composition of a Breguet natural escapement may thus cause an incorrect positioning of the last escape wheel and, consequently, a malfunction of the escapement accompanied with parasitic noises. Furthermore, as the escape wheel is free, its position is unstable, so that the operational safety of such a natural escapement is poor.

(5) Of course, many improvements have been made to the original Breguet natural escapement to attempt to overcome the above-mentioned drawbacks. Nevertheless, despite the efforts of successive watch manufacturers, difficulties remain. Some watchmakers have thus proposed to superimpose the two escape wheels, a solution which, of course, increases the thickness of the movement and makes it difficult to integrate such a movement into a watch case. Other watch manufacturers have for their part proposed to position the anchor between the two escape wheels, in the plane of the latter. Here too, such a solution is bulky, this time in the plane of the movement. In addition, whether the escape wheels are superimposed or the anchor is disposed between the two escape wheels, it has been realised upon use that the watchmakers had difficulties in accessing the miscellaneous components of the escapement, in particular when this concerned adjusting the depth of penetration of the teeth of the first and of the second escape wheel with the entry and exit pallets of the anchor. In addition, when the watchmaker carries out control and regulation manipulations and when for this he removes the balance wheel, it may transpire that a release of the impulse occurs while neither of the two impulse pallet-stones carried by the balance plate is in the perimeter of rotation of one or other of the escape wheels to ensure the escapement function. In such cases, the escape wheels are not retained by the escapement function and may rotate uncontrollably. This

then causes at best a loss of the timekeeper function with an undesired advance, and at worst a sudden stop after acceleration of the train in one or other of its locking positions that may lead to a deterioration of the components of the train and of the escapement.

SUMMARY OF THE INVENTION

(6) The aim of the present invention is to remedy the above-mentioned problems as well as others also by providing a natural escapement for a horological movement that is protected against the effects of a release of the escapement function when the balance is not present.

(7) To this end, the present invention relates to a natural escapement for horological movement carrying out a succession of operating cycles each consisting of a first and of a second alternation of a balance during which the balance moves from a first extreme position to a second extreme position by passing through a middle rest position, then from its second extreme position to its first extreme position by passing again a second time through its middle rest position, this balance comprising a balance wheel on an arbor of which is adjusted a balance plate, this natural escapement comprising a first escape wheel set having at least one first toothing, this first escape wheel set, arranged to be driven by a wheel set of the train of the horological movement, driving in turn a second escape wheel set having at least one second toothing, the first and second escape wheel sets forming a kinematic chain arranged to cooperate with an anchor capable of pivoting about an anchor-staff, the balance plate causing the anchor to pivot with each of the first and second alternations, this anchor being arranged to lock respectively the first and the second escape wheel set temporarily during the second and first alternations of an operating cycle, the anchor further comprising a first, respectively a second safety lever, these first and second safety levers being arranged so that, in the absence of the balance, one or other of the second and first escape wheel sets, by driving the second or the first safety lever, causes the anchor to pivot to ensure the locking of the first or of the second escape wheel set by abutment of this first or of this second escape wheel set on the portion of the anchor that ensures the function of a stop pallet-stone of this first or of this second escape wheel set during normal operation of the escapement, the first and second safety levers being arranged so as not to be in contact with the first and second escape wheel sets during normal operation of the escapement during which it is the balance plate that causes the anchor to pivot.

(8) According to special embodiments of the invention: at least one first lever, pivoted about a pivot pin, being connected to the first arm of the anchor via at least one pivoting articulation, the anchor comprising a second lever that extends its second arm, these first and second levers being arranged to lock respectively the first and second escape wheels temporarily during the second and first alternations of an operating cycle, the pivoting displacement of the first and second levers being limited; the first and second levers are pivoted about respective pivot pins and are connected respectively to the first and second arms of the anchor via at least one pivoting articulation; the pivoting articulations are each formed of a catch that protrudes in an oblong opening; the pivoting displacement of the anchor is limited by first and second limit banking-pins; the first and second limit banking-pins are pegs; the first and second banking-pins are machined in a fixed element of the horological movement; the first and second limit banking-pins are eccentrics; the first lever is made of one part and has a geometry that ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel during the second alternation, and the second lever is made of one part and has a geometry that ensures the function of a second stop pallet-stone to temporarily lock the second escape wheel during the first alternation; the first escape wheel comprises a first drive toothing whereby it meshes with a second drive toothing of the second escape wheel, and the first and second escape wheels each comprise an impulse and locking toothing whereby they provide a direct and tangential driving impulse to the balance plate, the drive and impulse and locking toothings of each of the first and second escape wheels extending in a single plane or in two parallel planes; the anchor comprises a fork formed of a first and of a second horn, the balance plate coming to abut by its balance pin against the second horn of the fork

and causing this anchor to pivot in a first direction during the first alternation, and against the first horn during the second alternation, causing the anchor to pivot in a second direction opposite to the first; the fork carries a dart that cooperates with the balance plate to prevent the accidental movements of the fork during a period called supplementary arc; the first and second escape wheels are each one-piece; a reduction wheel set is disposed between the wheel set of the train of the horological movement and the first escape wheel.

(9) The invention also relates to a horological movement comprising a natural escapement of the type described above.

(10) Thanks to these features, the present invention provides a natural escapement protected against the damages that may be created by a premature release of the impulse. Indeed, by teaching to provide the first and second arms of the anchor with a first and second safety lever, the locking of the first escape wheel set is advantageously ensured when in the absence of the balance plate, this locking is not ensured by the cooperation between this balance plate and the anchor. Indeed, it is understood that in the absence of the balance plate, the second escape wheel set is not retained by the escapement function and may therefore rotate uncontrollably, which may cause a loss of the timekeeping function with an undesired advance, or even a sudden stop after acceleration of the train of the horological movement that may lead to a deterioration of the components of the train and of the escapement. To achieve this objective, the first and second safety levers are arranged so that, in the absence of the balance, the second escape wheel set, by action on the second safety lever, causes the second arm of the anchor, the anchor and the first arm of the anchor to pivot to ensure the locking of the first escape wheel set on the portion of this anchor that, usually, that is to say when the balance plate is present, ensures the function of a stop pallet-stone to temporarily lock the first escape wheel set during an operating cycle of the natural escapement. Of course, the first and second safety levers are designed so as not to be in contact with the first and second escape wheel sets during normal operation of the escapement during which it is the balance plate that causes the anchor to pivot. Likewise, it will be understood that the symmetrical situation is also possible, namely that by pivoting of the anchor controlled by the first escape wheel set, the locking of the second escape wheel set is ensured by abutment against the portion of this anchor that, usually, ensures the function of a stop pallet-stone to temporarily lock the second escape wheel set during an operating cycle of the natural escapement.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) Other features and advantages of the present invention will become more apparent from the following detailed description of one embodiment of a natural escapement according to the invention, this example being given for purely illustrative and non-limiting purposes only in connection with the appended drawing wherein:

(2) FIG. 1 is an overview from the top of a natural escapement in its locking position wherein the second escape wheel abuts against the second lever;

(3) FIG. 2 is a top view of the natural escapement in its position wherein the balance pin comes into contact with the second horn of the fork, which will cause the beginning of unlocking of the second escape wheel from its engagement with the second lever;

(4) FIG. 3 is a top view of the natural escapement in its position wherein the balance plate drives the anchor and the levers, which causes the beginning of the first drop by unlocking the second escape wheel from its engagement with the second lever;

(5) FIG. 4 is a top view of the natural escapement in its position wherein the first escape wheel comes to abut against the first impulse pallet-stone and starts to give an impulse to the balance plate, which marks the end of the first drop;

- (6) FIG. 5 is a top view of the natural escapement in its position wherein the first escape wheel imparts the impulse to the balance plate whereas the second lever comes to abut against the second limit banking-pin;
- (7) FIG. 6 is a top view of the natural escapement in its position wherein the first escape wheel finishes imparting an impulse to the balance plate, which marks the beginning of the second drop, whereas the second lever is pressed on the second limit banking-pin;
- (8) FIG. 7 is a top view of the natural escapement in its position wherein the first escape wheel presses on the first lever, which marks the end of the second drop, whereas the balance plate finishes its alternation freely;
- (9) FIG. 8 is a top view of a natural escapement according to an implementing mode of the invention in the case where the balance wheel has been removed, the anchor being provided with safety levers in accordance with the invention, the natural escapement being in the position wherein the second escape wheel, by action on the second safety lever, will cause the anchor to pivot to ensure the locking of the first escape wheel by pressing, via one of the teeth of its impulse and locking toothing, on the portion of this anchor that, usually, that is to say when the balance plate is present, ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel during an operating cycle of the natural escapement;
- (10) FIG. 9 is a top view similar to that of FIG. 8 wherein, in the absence of the balance wheel, the first escape wheel will, by action on the first safety lever, cause the anchor to pivot so as to make it possible for the second escape wheel to come into locking position by pressing on one of the teeth of its impulse and locking toothing on the portion of this anchor that, usually, ensures the function of a second stop pallet-stone the role of which is to temporarily lock this second escape wheel;
- (11) FIG. 10 is a top view that illustrates the position of the natural escapement after the position wherein this natural escapement is in FIG. 8 and wherein, the balance wheel being absent, the second escape wheel has, by action on the second safety lever, caused the anchor to pivot so as to make it possible for the first escape wheel to take its locking position by pressing on one of the teeth of its impulse and locking toothing on the portion of this anchor that, usually, that is to say when the balance plate is present, ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel during an operating cycle of the natural escapement.

DETAILED DESCRIPTION OF THE INVENTION

(12) The present invention proceeds from the general inventive idea that consists in providing the first and second arms of the anchor of a natural escapement, also known under its name tangential impulse escapement, with a first and with a second safety lever in the aim of guaranteeing that, if the watchmaker, for any reason, needs to remove the balance wheel, an unexpected release of the rotation of the first and second escape wheel sets is stopped immediately by bringing one of the first and second escape wheel sets into its locking position. To this end, the safety levers are arranged such that, when the balance wheel is removed, the second escape wheel set, by action on the second safety lever, pivots the anchor and the first arm of this anchor to make it possible for the first escape wheel set to immobilise in its locking position pressed against the portion of this anchor that, usually, that is to say when the balance plate is present, ensures the function of a stop pallet-stone to temporarily lock the first escape wheel set during an operating cycle of the natural escapement.

(13) Designated as a whole by the general numerical reference **1**, the natural escapement is shown in its locking position in FIG. 1. This natural escapement **1** is arranged to be driven by a wheel set of the train of the horological movement, for example a second wheel **2** that, according to a preferred but not limiting embodiment, meshes with a pinion **4** fixedly mounted on an arbor **6** of a first escape wheel set comprising a first escape wheel **10**. This first escape wheel **10** meshes for its part via a first drive toothing **12** with a second drive toothing **14** of a second escape wheel set comprising a second escape wheel **16** that pivots about an arbor **18**.

(14) The natural escapement **1** also comprises a balance **20** that includes a balance wheel **22** on an

arbor **24** of which is adjusted a balance plate **26**. This balance plate **26** carries a balance pin **28** as well as a first and a second impulse pallet-stone **30** and **32** the respective roles of which will be described below.

(15) The natural escapement **1** also comprises an anchor **34** pivoted about an anchor-staff **36**. This anchor **34** includes an anchor body **38** that carries a fork **40** formed of a first and of a second horn **42a** and **42b** as well as of a dart **44**. This dart **44** cooperates with the balance plate **26** in the aim of preventing the accidental movements of the fork **40** during the periods commonly called supplementary arcs, periods during which the balance plate **26** is distant to its middle rest position called angle of lift.

(16) As can be seen upon examining FIG. **1**, the anchor body **38** includes a first and a second arm **46a** and **46b** that are preferably but not in a limiting manner arranged symmetrically on either side of the fork **40**. According to one embodiment given purely by way of illustration only in FIGS. **8** to **10**, first and second levers **48a**, **48b**, pivoted about respective pivot pins **50** and **52**, are connected to the first and second arms **46a**, **46b** of the anchor body **38** via a pivoting articulation **53**. In this embodiment, the first lever **48a** is made of one part and has a geometry that ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel **10** during an operating cycle of the natural escapement **1**, and the second lever **48b** has a geometry that ensures the function of a second stop pallet-stone to temporarily lock the second escape wheel **16** during the same operating cycle of the natural escapement **1**.

(17) According to the embodiment shown in the drawing, the first and second levers **48a**, **48b** each carry a catch **54**, respectively **56**, that protrudes in an oblong opening **58**, respectively **60**, made in the first and second arms **46a**, **46b** of the anchor body **38**. Of course, the catches **54** and **56** could be carried by the first and second arms **46a**, **46b**, and the oblong openings **58**, **60** could be made in the first and second levers **48a**, **48b**. Thus, by engaging the catches **54**, **56** in the oblong openings **58**, **60**, the first and second levers **48a**, **48b** are capable of pivoting in relation to the first and second arms **46a**, **46b** of the anchor body **38**.

(18) In the embodiment of the natural escapement **1** illustrated in the drawing, it is assumed that the second wheel **2** that supplies the natural escapement **1** with the energy necessary for its operation rotates in the clockwise direction. Consequently, the second wheel **2** tends to rotate the pinion **4** and the first escape wheel **10** on the arbor **6** of which is fixed the pinion **4** in the anti-clockwise direction, and the second escape wheel **16** in the clockwise direction.

(19) An operating cycle of the natural escapement **1** comprises two alternations during which the balance plate **26** will go successively from a first extreme position to a second extreme position by passing through a middle rest position, then from its second extreme position to its first extreme position by passing again a second time through its middle rest position. Thus, at the beginning of a cycle (see FIG. **1**), the balance plate **26** rotates towards its middle rest position by rotating in the clockwise direction, whereas the second escape wheel **16** is pressed on the second lever **48b**.

(20) At a given moment of its movement illustrated in FIG. **2**, the balance plate **26** arrives in a position wherein it abuts by its balance pin **28** against the second horn **42b** of the fork **40** and starts to cause the anchor **34** to pivot in the anti-clockwise direction. The pivoting of the anchor **34** in the anti-clockwise direction has the effect of starting to release the second escape wheel **16** from its engagement with the second lever **48b**, which will make it possible for the second wheel **2** to drive, via the first escape wheel **10**, the second escape wheel **16** in the clockwise direction.

(21) In FIG. **3**, the natural escapement **1** is in a position wherein the balance plate **26** drives the anchor **34**, which causes the beginning of the first drop by unlocking the second escape wheel **16** from its engagement with the second lever **48b**. "Drop" means the periods of operation of the natural escapement **1** according to the invention during which the first and second escape wheels **10** and **16** are neither in contact with one or other of the first and second levers **48a**, **48b**, nor with one or other of the first and second impulse pallet-stones **30**, **32**.

(22) It will be understood that at the same time as the first escape wheel drives the second escape

wheel **16** by pivoting in the clockwise direction, the first escape wheel **10** also starts to give a driving impulse to the balance plate **26** via a tooth **66** of an impulse and locking tothing **68** that drives the first impulse pallet-stone **30** (see FIG. 4). This driving impulse is referred to as direct and tangential because it is given directly by the first escape wheel to the balance plate **26** and that the path of the tooth **66** catches that of the first impulse pallet-stone **30** of the balance plate **26** tangentially, which makes a contact almost on time and without friction possible. Moreover, it will be noted that the tooth **66** of the first escape wheel **10** coming into contact with the first impulse pallet-stone **30** of the balance plate **26** marks the end of the first drop.

(23) FIG. 5 is a top view of the natural escapement **1** in its position wherein the first escape wheel **10** imparts the impulse to the balance plate **26**, whereas the second lever **48b** pivots about its pivot pin **52** and comes to press against the second limit banking-pin **64**. This movement is controlled by the anchor **34** which, driven by the balance pin **28**, pivots about its anchor-staff **36** in the anti-clockwise direction.

(24) In FIG. 6, the first escape wheel **10** finishes by imparting an impulse to the balance plate **26**, which marks the beginning of the second drop. Indeed, it can be seen that the tooth **66** of the first escape wheel **10** will no longer be in contact with the first impulse pallet-stone **30** of the balance plate **26**. Moreover, the second lever **48b** is pressed on the second limit banking-pin **64**.

(25) Finally, FIG. 7 is a top view of the natural escapement **1** in its other locking position wherein the first escape wheel **10** presses on the first lever **48a**, which marks the end of the second drop, whereas the balance plate **26** finishes its alternation freely by rotating in the clockwise direction. The following alternation during which the balance plate **26** will rotate in the anti-clockwise direction reproduces the same functions as those illustrated in FIGS. 2 to 7 symmetrically in the reverse order.

(26) FIG. 8 is a top view of the natural escapement **1** of FIG. 1 in the case where the balance **20** has been removed, situation schematically illustrated by showing the balance **20** in a dotted line. In accordance with the invention, the first and second levers **48a**, **48b** of the anchor **34** are provided respectively with a first safety lever **84** and with a second safety lever **86**. As can be seen in this FIG. 8, the natural escapement **1** is in the position wherein the second escape wheel **16** will, by pivoting in the clockwise direction, act by one of the teeth of its impulse and locking tothing **70** on the second safety lever **86** carried by the second lever **48b** and cause the anchor **34** to pivot to ensure the locking of the first escape wheel **10** by pressing on one of the teeth **66** of its impulse and locking tothing **68** on the portion **88** of this anchor **34** that, usually, that is to say when the balance plate **26** is present, ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel **10** during an operating cycle of the natural escapement **1**.

(27) The situation described above is illustrated in FIG. 10 wherein, the balance **20** still being absent, the first escape wheel **10** is locked by pressing on one of the teeth **66** of its impulse and locking tothing **68** on the portion **88** of the anchor **34** that ensures the function of stop pallet-stone. Indeed, under the effect of the pivoting of the anchor **34** caused by the rotation of the second escape wheel **16**, the portion **88** of the anchor **34** that ensures the function of stop pallet-stone is in the perimeter of rotation of the first escape wheel **10** and the first escape wheel **10** comes by one of the teeth **66** of its impulse and locking tothing **68** to press against this portion **88** of the anchor **34**.

(28) Finally, the situation illustrated in FIG. 9 is symmetrical with that shown in FIG. 8, namely that it is the first escape wheel **16** that, by pivoting in the anti-clockwise direction, will act on the first safety lever **84** carried by the first lever **48a** and cause the anchor **34** to pivot to ensure the locking of the second escape wheel **10** by pressing on one of the teeth of its impulse and locking tothing **70** on the portion **90** of this anchor **34** that, usually, that is to say when the balance plate **26** is present, ensures the function of a second stop pallet-stone to temporarily lock the second escape wheel **16** during an operating cycle of the natural escapement **1**.

(29) It goes without saying that the present invention is not limited to the embodiment that has just been described, and that miscellaneous modifications and simple variants may be envisaged

without departing from the scope of the invention as defined by the appended claims. In particular, it will be understood that, although the natural escapement **1** has been described in connection with an anchor **34** to the arms **46a**, **46b** of which are connected the first and second levers **48a**, **48b**, it is absolutely possible, in a simplified embodiment, to only provide for a single lever pivotally connected to one of the arms of the anchor, the other lever being made integrally with the second arm of the anchor **34**. It will also be noted that the presence of the first and second levers **48a**, **48b** is not essential, the anchor **34** only being able to include the arms **46a**, **46b**, the first arm **46a** having a geometry that ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel **10** during an operating cycle of the natural escapement **1**, and the second arm **46b** a geometry that ensures the function of a second stop pallet-stone to temporarily lock the second escape wheel **16** during the same operating cycle of the natural escapement **1**. It will also be noted that a reduction wheel set may be disposed between the second wheel **2** and the first escape wheel **10**. The first escape wheel **10** comprises a first drive toothing **12** whereby it meshes with a second drive toothing **14** of the second escape wheel **16**. Likewise, the first and second escape wheels **10**, **16** each comprise an impulse and locking toothing **68**, **70** whereby they provide a direct and tangential driving impulse to the balance plate **26**. The drive **12**, **14** and impulse and locking toothings **68**, **70** of each of the first and second escape wheels **10**, **16** extending in a single plane or in two parallel planes. Preferably, the first and second escape wheels **10**, **16** are each one-piece.

NOMENCLATURE

(30) **1**. Natural escapement **2**. Second wheel **4**. Pinion **6**. Arbor **10**. First escape wheel **12**. First drive toothing **14**. Second drive toothing **16**. Second escape wheel **18**. Arbor **20**. Balance **22**. Balance wheel **24**. Arbor **26**. Balance plate **28**. Balance pin **30**. First impulse pallet-stone **32**. Second impulse pallet-stone **34**. Anchor **36**. Anchor-staff **38**. Anchor body **40**. Fork **42a**. First horn **42b**. Second horn **44**. Dart **46a**. First arm **46b**. Second arm **48a**. First lever **48b**. Second lever **50**. Pivot pin **52**. Pivot pin **53**. Pivoting articulations **54**. Catch **55**. Catch **56**. Catch **57**. Circular opening **58**. Oblong opening **60**. Oblong opening **62**. First limit banking-pin **64**. Second limit banking-pin **66**. Tooth **68**. Impulse and locking toothing **70**. Impulse and locking toothing **76**. Eccentrics **84**. First safety lever **86**. Second safety lever **88**. Portion **90**. Portion

Claims

1. A natural escapement for horological movement carrying out a succession of operating cycles each comprising a first and of a second alternation of a balance during which the balance moves from a first extreme position to a second extreme position by passing through a middle rest position, then from its second extreme position to its first extreme position by passing again a second time through its middle rest position, said balance comprising a balance wheel on an arbor of which is adjusted a balance plate, said natural escapement comprising a first escape wheel set having at least one first toothing, said first escape wheel set, arranged to be driven by a wheel set of the train of the horological movement, driving in turn a second escape wheel set having at least one second toothing, the first and second escape wheel sets forming a kinematic chain arranged to cooperate with an anchor capable of pivoting about an anchor-staff, the balance plate causing the anchor to pivot with each of the first and second alternations, said anchor being arranged to lock respectively the first and the second escape wheel set temporarily during the second and first alternations of an operating cycle, the anchor further comprising a first, respectively a second safety lever, these first and second safety levers being arranged so that, in the absence of the balance, one or other of the second and first escape wheel sets, by driving the second or the first safety lever, causes the anchor to pivot to ensure the locking of the first or of the second escape wheel set by abutment of this said first or of this said second escape wheel set on a portion of the anchor that ensures the function of a stop pallet-stone of said first or of said second escape wheel set during normal operation of the escapement, the first and second safety levers being arranged so

as not to be in contact with the first and second escape wheel sets during normal operation of the escapement during which it is the balance plate that causes the anchor to pivot.

2. The natural escapement according to claim 1, wherein the anchor comprises a first and a second arm arranged to lock respectively the first and the second escape wheel set temporarily during the second and first alternations of an operating cycle, the first safety lever being arranged on the first arm of the anchor, whereas the second safety lever is arranged on the second arm of the anchor.

3. The natural escapement according to claim 2, wherein at least one first lever, pivoted about a pivot pin and whereon is arranged the first safety lever, is connected to the first arm of the anchor via at least one pivoting articulation, the anchor comprising a second lever that extends its second arm and whereon is arranged the second safety lever, these first and second levers being arranged to lock respectively a first and second escape wheel that are included in the first and second escape wheel sets temporarily during second and first alternations of an operating cycle, the pivoting displacement of the first and second levers being limited.

4. The natural escapement according to claim 3, wherein the balance plate carries a first impulse pallet whereby said balance plate receives a direct and tangential driving impulse from the first escape wheel set during the first alternation, and a second impulse pallet-stone whereby said balance plate receives a direct and tangential driving impulse from the second escape wheel during the second alternation.

5. The natural escapement according to claim 2, wherein the balance plate carries a first impulse pallet whereby said balance plate receives a direct and tangential driving impulse from the first escape wheel set during the first alternation, and a second impulse pallet-stone whereby said balance plate receives a direct and tangential driving impulse from the second escape wheel during the second alternation.

6. The natural escapement according to claim 2, wherein the balance plate carries a balance pin whereby said balance plate causes the anchor to pivot with each of the first and second alternations.

7. The natural escapement according to claim 6, wherein the first and second levers are pivoted about the respective pivot pins and are connected respectively to the first and second arms of the anchor via at least one pivoting articulation.

8. The natural escapement according to claim 7, wherein the at least one of the pivoting articulations are each formed of a catch that protrudes in an oblong opening.

9. The natural escapement according to claim 8, wherein the pivoting displacement of the anchor is limited by first and second limit banking-pins.

10. The natural escapement according to claim 7, wherein the pivoting displacement of the anchor is limited by first and second limit banking-pins.

11. The natural escapement according to claim 6, wherein the pivoting displacement of the anchor is limited by first and second limit banking-pins.

12. The natural escapement according to claim 11, wherein the first and second limit banking-pins are pegs.

13. The natural escapement according to claim 11, wherein the first and second limit banking-pins are machined in a fixed element of the horological movement.

14. The natural escapement according to claim 11, wherein the first and second limit banking-pins are eccentrics.

15. The natural escapement according to claim 6, wherein the pivoting displacement of the anchor is limited by first and second limit banking-pins.

16. The natural escapement according to claim 6, wherein the first lever is made of one part and has a geometry that ensures the function of a first stop pallet-stone to temporarily lock the first escape wheel during the second alternation, and the second lever is made of one part and has a geometry that ensures the function of a second stop pallet-stone to temporarily lock the second escape wheel during the first alternation.

17. The natural escapement according to claim 6, wherein the first escape wheel comprises a first

drive toothing whereby it meshes with a second drive toothing of the second escape wheel, and in that wherein the first and second escape wheels each comprise an impulse and locking toothing whereby they provide a direct and tangential driving impulse to the balance plate, the drive and impulse and locking toothings of each of the first and second escape wheels extending in a single plane or in two parallel planes.

18. The natural escapement according to claim 17, wherein the first and second escape wheels are each one-piece.

19. The natural escapement according to claim 6, wherein the anchor comprises a fork formed of a first and of a second horn, the balance plate coming to abut by its balance pin against the second horn of the fork and causing this said anchor to pivot in a first direction during the first alternation, and against the first horn during the second alternation, causing the anchor to pivot in a second direction opposite to the first.

20. The natural escapement according to claim 19, wherein the fork carries a dart that cooperates with the balance plate to prevent the accidental movements of the fork during a period called supplementary arc.

21. The natural escapement according to claim 6, wherein it comprises a reduction wheel set arranged to be disposed between the train of the horological movement and the first escape wheel.

22. A horological movement comprising a natural escapement according to claim 1.

23. The horological movement according to claim 22, wherein the train of said horological movement which drives the first escape wheel is a second wheel.
