

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406902
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tanaka; Kengo

Vapor chamber and manufacturing method of vapor chamber

Abstract

A vapor chamber includes a working fluid in an internal space formed between a first metal sheet and a second metal sheet, in which the first metal sheet includes a recessed channel, at least one projecting part, and at least one flow channel groove. The recessed channel is provided at an inner surface of the first metal sheet, the projecting part projects from the inner surface of the first metal sheet toward an inner surface of the second metal sheet, and a top face of the projecting part abuts the inner surface of the second metal sheet. The flow channel groove has a bottom groove part, a side face groove part and a top face groove part. The bottom groove part is provided at a bottom face of the recessed channel, the side face groove part is provided at a side face of the projecting part, and is connected to the bottom groove part, and the top face groove part is provided at the top face of the projecting part, and is connected to the side face groove part.

Inventors:	Tanaka; Kengo (Tokyo, JP)
Applicant:	FURUKAWA ELECTRIC CO., LTD. (Tokyo, JP)
Family ID:	78830359
Assignee:	FURUKAWA ELECTRIC CO., LTD. (Tokyo, JP)
Appl. No.:	18/000473
Filed (or PCT Filed):	June 04, 2021
PCT No.:	PCT/JP2021/021371
PCT Pub. No.:	WO2021/246519
PCT Pub. Date:	December 09, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230215777 A1	Jul. 06, 2023

Foreign Application Priority Data

JP 2020-098035 Jun. 04, 2020

Publication Classification

Int. Cl.: H01L23/427 (20060101); B23P15/26 (20060101); H01L21/48 (20060101)

U.S. Cl.:

CPC H01L23/427 (20130101); B23P15/26 (20130101); H01L21/4871 (20130101); B23P2700/09 (20130101)

Field of Classification Search

CPC: H01L (23/427); H01L (21/4871); B23P (15/26); B23P (2700/09)

USPC: 165/104.26

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6269866	12/2000	Yamamoto	174/15.2	F28D 15/0233
6880626	12/2004	Lindemuth	174/15.2	F28D 15/0233
10973151	12/2020	Wakaoka	N/A	F28D 15/0233
11340022	12/2021	Wakaoka	N/A	H05K 7/20336
11421942	12/2021	Kume	N/A	F28D 15/0233
11448470	12/2021	Chan	N/A	F28F 21/084
11486651	12/2021	Wang	N/A	F28D 15/046
11497141	12/2021	Koo	N/A	F28D 15/0283
11635263	12/2022	Chen	165/104.26	F28D 15/04
11740029	12/2022	Wakaoka	165/104.26	B23K 31/00
11747092	12/2022	Chen	165/104.26	F28D 15/0233
11765861	12/2022	Yang	165/104.26	H01L 23/3736
11985796	12/2023	Yeh	N/A	F28D 15/046
11988453	12/2023	Lewis	N/A	F28F 21/085
12078423	12/2023	Inagaki	N/A	F28D 15/0266
12082381	12/2023	Yurchenko	N/A	H05K 7/20445

12104856	12/2023	Lewis	N/A	F28D 15/046
12111114	12/2023	Huang	N/A	F28D 15/0283
2002/0108333	12/2001	Clayton	52/302.1	E04B 1/70
2004/0211549	12/2003	Garner	431/325	F28D 15/046
2005/0280128	12/2004	Mok	257/E23.088	H01L 23/427
2005/0280162	12/2004	Mok	257/E23.088	H01L 24/31
2007/0056711	12/2006	Ohsawa	165/104.21	B23P 15/26
2007/0295486	12/2006	Su	165/104.26	F28D 15/046
2008/0216994	12/2007	Lee	29/890.03	F28D 15/0233
2009/0040726	12/2008	Hoffman	29/890.032	F28D 15/0233
2009/0145586	12/2008	Yoshida	165/146	H01L 23/427
2010/0071879	12/2009	Hou	29/890.032	F28D 15/046
2012/0186784	12/2011	Yang	165/104.21	F28D 15/0266
2013/0025829	12/2012	Huang	165/104.26	F28D 15/0233
2014/0166244	12/2013	Dai	29/890.032	F28D 15/0233
2014/0345832	12/2013	Lin	165/104.26	F28D 15/046
2016/0290739	12/2015	Mochizuki	N/A	F28F 3/046
2017/0023308	12/2016	Huang	N/A	F28F 3/00
2017/0229375	12/2016	Haj-Hariri	N/A	H01L 24/16
2019/0141855	12/2018	Inagaki	N/A	H01L 23/427
2021/0095930	12/2020	Inagaki	N/A	F28D 15/0233
2021/0136955	12/2020	Wakaoka	N/A	F28D 15/046
2021/0392781	12/2020	Oda	N/A	F28D 15/046
2022/0390184	12/2021	Chen	N/A	F28D 15/04
2023/0215777	12/2022	Tanaka	165/104.26	F28D 15/04
2023/0258416	12/2022	Tanaka	165/170	F28D 15/0233
2024/0011716	12/2023	Tanaka	N/A	H05K 7/20
2024/0172395	12/2023	Oda	N/A	F28D 15/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
11-183067	12/1998	JP	N/A
2001-91172	12/2000	JP	N/A
2016-188734	12/2015	JP	N/A
2017-83042	12/2016	JP	N/A
2018-128208	12/2017	JP	N/A
2019-207076	12/2018	JP	N/A
I690684	12/2019	TW	N/A

OTHER PUBLICATIONS

International Search Report mailed on Jul. 6, 2021 in PCT/JP2021/021371 filed on Jun. 4, 2021 (3 pages). cited by applicant

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to a vapor chamber and a manufacturing method of a vapor chamber.

BACKGROUND ART

(2) Electronic components such as semiconductor elements mounted in electrical/electronic devices such as notebook computers, digital cameras and mobile telephones are in a trend of increasing heat generation amount, due to the high-density mounting accompanying improved performance. In order to correctly drive an electrical/electronic device over a long period, it is necessary to efficiently cool the electronic components.

(3) For example, Patent Document 1 discloses a vapor chamber including a first metal sheet and a second metal sheet, in which the first metal sheet has a first flow passage concave part, a first bottom surface groove and first flow passage projection parts. With the vapor chamber of Patent Document 1, the first bottom surface groove has a width smaller than a gap between a first flow passage projection part adjacent to the first bottom surface groove on one side in the width direction of the first bottom surface groove, and a first flow passage projection part adjacent to the first bottom surface groove on the other side, when viewing along the longitudinal direction of the first bottom surface groove.

(4) The vapor chamber of Patent Document 1 attempts an improvement in the heat transport efficiency by the first bottom surface groove and the first flow passage projection part having predetermined arrangement relation. However, it is insufficient in addressing the demand of cooling performance of the electrical/electronic device which are increasing in recent years. Patent Document 1: Japanese Unexamined Patent Application, Publication No. 2018-128208

DISCLOSURE OF THE INVENTION

Problems to be Solved by the Invention

(5) An object of the present disclosure is to provide a vapor chamber having superior heat transport characteristics, as well as a manufacturing method of the vapor chamber.

Means for Solving the Problems

(6) According to a first aspect of the present disclosure, a vapor chamber includes a working fluid in an internal space formed between a first metal sheet and a second metal sheet, in which the first metal sheet comprises a recessed channel, at least one projecting part, and at least one flow channel groove; the recessed channel is provided at an inner surface of the first metal sheet; the projecting part projects from the inner surface of the first metal sheet toward an inner surface of the second metal sheet, and a top face of the projecting part abuts the inner surface of the second metal sheet; the flow channel groove has a bottom groove part, a side face groove part and a top face groove part; the bottom groove part is provided at a bottom face of the recessed channel; the side face groove part is provided at a side face of the projecting part, and is connected to the bottom groove part; and the top face groove part is provided at the top face of the projecting part, and is connected to the side face groove part.

(7) According to a second aspect of the present disclosure, in the vapor chamber as described in the first aspect, the flow channel groove has a groove depth d and a groove width w , and the groove depth d is longer than the groove width w .

(8) According to a third aspect of the present disclosure, in the vapor chamber as described in the

first or second aspect, a ratio (t_2/t_1) of a sheet thickness t_2 at the projecting part of the first metal sheet relative to a sheet thickness t_1 at the recessed channel of the first metal sheet is 0.1 or more and 10.0 or less.

According to a fourth aspect of the present disclosure, in the vapor chamber as described in any one of the first to third aspects, the first metal sheet includes a plurality of the flow channel grooves, and has a crossing part at which the plurality of the flow channel grooves intersect.

According to a fifth aspect of the present disclosure, a manufacturing method of the vapor chamber as described in any one of the first to fourth aspects includes: a laser processing step of forming at least the side face groove part among the flow channel groove of the first metal sheet by laser.

According to a sixth aspect of the present disclosure, in the manufacturing method of the vapor chamber as described in the fifth aspect, the flow channel groove is formed by laser in the laser processing step.

According to a seventh aspect of the present disclosure, the manufacturing method of the vapor chamber as described in the fifth or sixth aspect further includes a press processing step of forming the recessed channel and the projecting part of the first metal sheet by press molding, prior to the laser processing step.

According to an eighth aspect of the present disclosure, the manufacturing method of the vapor chamber as described in any one of the fifth to seventh aspects further includes a laser welding step of welding the first metal sheet and the second metal sheet by laser, after the laser processing step.

Effects of the Invention

(9) According to the present disclosure, it is possible to provide a vapor chamber having superior heat transport characteristics, as well as a manufacturing method of the vapor chamber.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a perspective view showing an example of a vapor chamber according to an embodiment.

(2) FIG. 2 is a cross-sectional view along the line A-A in FIG. 1.

(3) FIG. 3 is a cross-sectional view along the line B-B in FIG. 1.

(4) FIG. 4 is a cross-sectional view along the line C-C in FIG. 1.

(5) FIG. 5 is a perspective view showing another example of a vapor chamber according to an embodiment.

(6) FIG. 6 is a perspective view showing another example of a vapor chamber according to an embodiment.

(7) FIG. 7 is a cross-sectional view along the line A-A in FIG. 6.

(8) FIG. 8 is a cross-sectional view along the line B-B in FIG. 6.

PREFERRED MODE FOR CARRYING OUT THE INVENTION

(9) Hereinafter, an embodiment will be explained in detail.

(10) The present inventors, as a result of thorough examination, achieved an improvement in heat transport characteristics by suppressing the disturbance in flow of a liquid-phase working fluid to efficiently circulate the liquid-phase working fluid and the gas-phase working fluid in a vapor chamber.

(11) A vapor chamber of the embodiment includes a working fluid in an internal space formed between a first metal sheet and a second metal sheet, in which the first metal sheet comprises a recessed channel, at least one projecting part, and at least one flow channel groove; the recessed channel is provided at an inner surface of the first metal sheet; the projecting part projects from the inner surface of the first metal sheet toward an inner surface of the second metal sheet, and a top face of the projecting part abuts the inner surface of the second metal sheet; the flow channel

groove has a bottom groove part, a side face groove part and a top face groove part; the bottom groove part is provided at a bottom face of the recessed channel; the side face groove part is provided at a side face of the projecting part, and is connected to the bottom groove part; and the top face groove part is provided at the top face of the projecting part, and is connected to the side face groove part.

(12) FIG. 1 is a perspective view showing an example of a vapor chamber according to the embodiment. FIG. 2 is a cross-sectional view along the line A-A in FIG. 1. FIG. 3 is a cross-sectional view along the line B-B in FIG. 1. FIG. 4 is a cross-sectional view along the line C-C in FIG. 1. For convenience, FIG. 1 shows an aspect partially penetrating so that the internal structure of the vapor chamber is understood. In addition, FIG. 1 shows the flow direction of the liquid-phase working fluid F(L) by the black arrows, and shows the flow direction of the gas-phase working fluid F(G) by the white arrows.

(13) As shown in FIGS. 1 to 4, the vapor chamber 1 of the embodiment has a first metal sheet 10 and a second metal sheet 20. The first metal sheet 10 and the second metal sheet 20 are joined so that an inner surface 10a of the first metal sheet 10 and an inner surface 20a of the second metal sheet 20 are opposing. In other words, the first metal sheet 10 and the second metal sheet 20 have the insides closed. In addition, the vapor chamber 1 has a working fluid in an internal space S formed between the first metal sheet 10 and the second metal sheet 20. The internal space S is sealed by the first metal sheet 10 and the second metal sheet 20. The working fluid is enclosed in the internal space S provided inside of the vapor chamber 1.

(14) As the working fluid enclosed in the internal space S, pure water, ethanol, methanol, acetone, etc. can be exemplified from the viewpoint of cooling performance of the vapor chamber 1.

(15) The first metal sheet 10 constituting the vapor chamber 1 includes a recessed channel 11, at least one projecting part 12, and at least one flow channel groove 13.

(16) As shown in FIG. 1, the recessed channel 11 is provided at the inner surface 10a of the first metal sheet 10. The recessed channel 11 provided on the side of the inner surface 10a indents from an outer edge 10c of the first metal sheet 10 along the center of the inner surface 10a. For example, the recessed channel is a space from the internal space S excluding the projecting part 12 and flow channel groove 13. The gas-phase working fluid mainly flows in the recessed channel 11.

(17) The projecting part 12 projects from the inner surface 10a of the first metal sheet 10 toward the inner surface 20a of the second metal sheet 20. A top face 12a of the projecting part 12 abuts the inner surface 20a of the second metal sheet 20.

(18) The shape of the projecting part 12 is not particularly limited, so long as the top face 12a of the projecting part 12 can abut the inner surface 20a of the second metal sheet 20. In addition, in the case of the first metal sheet 10 including a plurality of the projecting parts 12, the shapes of the projecting parts 12 may be entirely the same, or may differ. Herein, an example is shown in which all of the projecting parts 12 are columnar.

(19) The flow channel groove 13 has a bottom groove part 14, a side face groove part 15 and a top face groove part 16.

(20) As shown in FIGS. 1 and 4, the bottom groove part 14 constituting the flow channel groove 13 is provided at the bottom 11a of the recessed channel 11. In addition, as shown in FIG. 1, the side face groove part 15 constituting the flow channel groove 13 is provided at a side face 12b of the projecting part 12, and is connected to the bottom groove part 14. In addition, as shown in FIGS. 1 to 3, the top face groove part 16 constituting the flow channel groove 13 is provided at the top face 12a of the projecting part 12, and is connected to the side face groove part 15. The liquid-phase working fluid flows in the flow channel groove 13.

(21) The side face groove part 15 provided at the side face 12b of the projecting part 12 extends along the entire length from the bottom side to the top face side of the side face 12b. In this way, the side face groove part 15 extending in the height direction of the projecting part 12 extends along the entire length in the thickness direction of the vapor chamber 1 in the internal space S,

from the inner surface **10a** of the first metal sheet **10** until the inner surface **20a** of the second metal sheet **20**. In addition, a bottom side end of the side face groove part **15** is connected to the bottom groove part **14**. A top face side end of the side face groove part **15** is connected to the top face groove part **16**.

(22) The groove width w of the flow channel groove **13** is very small compared to the width of the recessed channel **11**. The shortest width of the recessed channel **11** is the shortest distance between adjacent projecting parts **12**, or the shortest distance between the projecting part **12** and the outer edge **10c** of the first metal sheet **10**.

(23) The groove depth d of the flow channel groove **13** is very small compared to the depth of the recessed channel **11**. The depth of the recessed channel **11** is the distance from the inner surface **10a** of the outer edge **10c** until the bottom of the recessed channel.

(24) The liquid-phase working fluid flows along the flow channel groove **13**, as shown by the arrow $F(L)$. When the flow channel groove **13** having the side face groove part **15** extending along the thickness direction of the vapor chamber **1**, and having the bottom groove part **14** and the top face groove part **16** connected to the side face groove part **15**, is provided in the internal space S , in addition to the disturbance in flow of the liquid-phase working fluid flowing along the in-plane direction of the vapor chamber **1** being suppressed by the bottom groove part **14** and top face groove part **16**, the disturbance in flow of the liquid-phase working fluid flowing along the thickness direction of the vapor chamber **1** is suppressed by the side face groove part **15**, and the liquid-phase working fluid favorably flows also in the thickness direction of the vapor chamber **1**. When the liquid-phase working fluid favorably flows also in the thickness direction of the vapor chamber **1**, it is possible to suppress a state in which the liquid-phase working fluid is not present in the evaporation part **41**, i.e. dry-out, the flow of circulation of the liquid-phase working fluid and the gas-phase working fluid becomes favorable, and the heat transport within the internal space S improves. For this reason, the vapor chamber **1** can have superior heat transport characteristics.

(25) Furthermore, when the flow channel groove **13** is provided in the internal space S , the working fluid favorably flows along the thickness direction of the vapor chamber **1** and the in-plane direction which is a direction perpendicular to the thickness direction of the vapor chamber **1**. For example, even if the vapor chamber **1** is in any posture, such as a state in which the vapor chamber **1** shown in FIG. **1** is inclined by an angle of 90 degrees in the paper, or is in a state up-side down, the working fluid which becomes liquid phase from the gas phase in the condensation part **42** easily returns to the evaporation part **41**. In this way, the heat transport characteristics of the vapor chamber **1** is superior, due to the flow of circulation of the liquid-phase working fluid and the gas-phase working fluid being favorable, independently of the arrangement state of the vapor chamber **1**.

(26) Furthermore, when the flow channel groove **13** is provided in the internal space S , the evaporation area of the working fluid in the internal space S increases, and the evaporation amount of the working fluid increases. As a result, the heat transport characteristics of the vapor chamber **1** increases due to the heat transport amount within the internal space S improving.

(27) In addition, as shown in FIG. **1**, for the bottom groove part **14**, it is preferable for ends different from the end (also referred to as side face groove part-side end of bottom groove part) connecting with the side face groove part **15** to be connected to each other. When the ends of the bottom groove part **14** different from the side face groove part-side end are connected, the adjacent bottom groove parts **14** are connected. The flow of the liquid-phase working fluid along the inner surface **10a** of the first metal sheet **10** improves. For this reason, the heat transport characteristics of the vapor chamber **1** improves.

(28) In addition, as shown in FIG. **1**, for the top face groove part **16**, it is preferable for ends differing from the end (also referred to as side face groove part-side end of the top face groove part) connecting with the side face groove part **15** to be connected to each other. When the ends of the top face groove part **16** different from the side face groove part-side end are connected, the

adjacent top face groove parts **16** are connected. The flow of the liquid-phase working fluid along the inner surface **20a** of the second metal sheet **20** improves. For this reason, the heat transport characteristics of the vapor chamber **1** improves.

(29) In addition, the flow channel groove **13** preferably has a groove depth d longer than the groove width w . When the groove depth d of the flow channel groove **13** is longer than the groove width w of the flow channel groove **13**, the capillary phenomenon of the flow channel groove **13** relative to the liquid-phase working fluid tends to be exhibited. The liquid-phase working fluid favorably flows within the flow channel groove **13** by the capillary phenomenon of the flow channel groove **13**. For this reason, the heat transport characteristics of the vapor chamber **1** further improves.

(30) In addition, the groove width w of the flow channel groove **13** is preferably $20\ \mu\text{m}$ or more and $200\ \mu\text{m}$ or less, and more preferably $50\ \mu\text{m}$ or more and $100\ \mu\text{m}$ or less. The groove depth d and the groove width w of the flow channel groove **13** preferably has a ratio d/w of 2.0 or more and 20.0 or less. When the groove width w or the groove depth d of the flow channel groove **13** is the above-mentioned lower limit value or more, it is possible to easily form the flow channel groove **13**. When the groove width w or the groove depth d of the flow channel groove **13** is the above-mentioned upper limit value or less, the capillary phenomenon of the flow channel groove **13** tends to act on the working fluid.

(31) In addition, in the case of the first metal sheet **10** including a plurality of the flow channel grooves **13**, the plurality of flow channel grooves **13** preferably extends in parallel to each other. In the case of the plurality of flow channel grooves **13** extending in parallel, the groove interval p of adjacent flow channel grooves **13** is preferably $40\ \mu\text{m}$ or more and $400\ \mu\text{m}$ or less, and more preferably $100\ \mu\text{m}$ or more and $200\ \mu\text{m}$ or less. The groove interval p of the flow channel grooves **13** is a distance between center lines of the groove width of adjacent flow channel grooves **13**. When the groove interval p of the flow channel grooves **13** is $40\ \mu\text{m}$ or more, it is possible to easily form the flow channel grooves **13**. When the groove interval p of the flow channel grooves **13** is $400\ \mu\text{m}$ or less, since the working fluid favorably flows within the internal space S , the heat transport characteristics of the vapor chamber **1** improves. In addition, the groove interval p is preferably at least $50\ \mu\text{m}$ and no more than $100\ \mu\text{m}$ larger than the groove width w . If the groove interval p and the groove width w are in such a relationship, it is possible to easily form the flow channel groove **13**. In addition, since a large working fluid amount in the flow channel groove per unit area can be kept, dry out in which the working fluid disappears will hardly occur, and the heat transport amount performance of the vapor chamber **1** improves.

(32) In addition, the groove width w of the bottom groove part **14** constituting the flow channel groove **13** is preferably $20\ \mu\text{m}$ or more and $200\ \mu\text{m}$ or less, and is more preferably $50\ \mu\text{m}$ or more and $100\ \mu\text{m}$ or less. The groove depth d and the groove width w of the bottom groove part **14** preferably has a ratio d/w of 2.0 or more and 20.0 or less. When the groove width w or the groove depth d of the bottom groove part **14** is the above-mentioned lower limit value or more, it is possible to easily form the bottom groove part **14**. When the groove width w or the groove depth d of the bottom groove part **14** is the above-mentioned upper limit value or less, the capillary phenomenon of the bottom groove part **14** tends to further act on the working fluid.

(33) In addition, the groove width w of the side face groove part **15** is preferably $20\ \mu\text{m}$ or more and $200\ \mu\text{m}$ or less, and is more preferably $50\ \mu\text{m}$ or more and $100\ \mu\text{m}$ or less. The groove depth d and the groove width w of the side face groove part **15** preferably has a ratio d/w of 2.0 or more and 20.0 or less. When the groove width w or the groove depth d of the side face groove part **15** is the above-mentioned lower limit value or more, it is possible to easily form the side face groove part **15**. When the groove width w or the groove depth d of the side face groove part **15** is the above-mentioned upper limit value or less, the capillary phenomenon of the side face groove part **15** tends to further act on the working fluid.

(34) In addition, the groove width w of the top face groove part **16** is preferably $20\ \mu\text{m}$ or more and $200\ \mu\text{m}$ or less, and is more preferably $50\ \mu\text{m}$ or more and $100\ \mu\text{m}$ or less. The groove depth d and

the groove width w of the top face groove part **16** preferably has a ratio d/w of 2.0 or more and 20.0 μm or less. When the groove width w or the groove depth d of the top face groove part **16** is the above-mentioned lower limit value or more, it is possible to easily form the top face groove part **16**. When the groove width w or the groove depth d of the top face groove part **16** is the above-mentioned upper limit value or less, the capillary phenomenon of the top face groove part **16** tends to further act on the working fluid.

(35) In the formation of the flow channel groove **13** improving the heat transport characteristics of such a vapor chamber **1**, particularly in the formation of the side face groove part **15** and the flow channel groove **13** having the above-mentioned predetermined groove width w , groove depth and groove interval p , a process using a laser is preferable, and thereamong, a process using a fiber laser is more preferable. In a process by laser, it is possible to form the flow channel groove **13** including the side face groove part **15** into a desired shape in a short time. On the other hand, in the etching process using an etching liquid adopted in conventional vapor chambers, the processability is very low compared to laser processing, such as the control of the shape of the flow channel groove **13** being difficult, and the formation itself of the side face groove part **15** being difficult.

(36) In addition, the material constituting the first metal sheet **10** and the second metal sheet **20** is preferably copper, copper alloy, aluminum, aluminum alloy or stainless steel, from the viewpoint of high thermal conductivity, processing ease by laser, etc. Thereamong, for the purpose of achieving weight reduction, aluminum or aluminum alloy is more preferable, and for the purpose of raising the mechanical strength, stainless steel is more preferable. In addition, depending on the use environment, tin, tin alloy, titanium, titanium alloy, nickel, nickel alloy, etc. may be used in the first metal sheet **10** and the second metal sheet **20**.

(37) In addition, as shown in FIGS. **2** to **4**, the ratio (t_2/t_1) of the sheet thickness t_2 at the projecting part **12** of the first metal sheet **10** relative to the sheet thickness t_1 at the recessed channel **11** of the first metal sheet **10** is preferably 0.1 or more and 10.0 or less, more preferably 0.2 or more and 5.0 or less, even more preferably 0.5 or more and 2.0 or less, and most preferably 1.0, i.e. the sheet thickness t_1 at the recessed channel **11** and the sheet thickness t_2 at the projecting part **12** are equal. When the ratio (t_2/t_1) is within the above-mentioned range, since the variation in sheet thickness of the first metal sheet **10** is suppressed, it is possible to lighten the weight of the vapor chamber **1**. In the formation of the first metal sheet **10** having such a predetermined ratio (t_2/t_1) , processing by press molding is favorable.

(38) In addition, as shown in FIG. **1**, it is preferable that the first metal sheet **10** includes a plurality of flow channel grooves **13**, and has a crossing part **17** at which the plurality of flow channel grooves **13** intersect. As the state in which the plurality of flow channel grooves **13** intersect, the plurality of flow channel grooves **13** may intersect at a right angle as shown in FIG. **1**, or the plurality of flow channel grooves **13** may intersect at an angle other than a right angle. The crossing part **17** may be configured by a plurality of the bottom groove parts **14** intersecting, may be configured by a plurality of the side face groove parts **15** intersecting, or may be configured by a plurality of the top face groove parts **16** intersecting as shown in FIG. **1**. The crossing part **17** configured by the plurality of bottom groove parts **14** is provided to the bottom face **11a** of the recessed channel **11**. The crossing part **17** configured by the plurality of side face groove parts **15** is provided to the side face **12b** of the projecting part **12**. The crossing part **17** configured by the plurality of the top face groove parts **16** is provided to the top face **12a** of the projecting part **12**.

(39) When the first metal sheet **10** has the crossing part **17**, the capillary phenomenon of the crossing part **17** acts on the working fluid, in addition to the capillary phenomenon of the flow channel groove **13**, and heat transport within the internal space S further improves. For this reason, the heat transport characteristics of the vapor chamber **1** further improves.

(40) In addition, as shown in FIGS. **1** and **4**, when mounting a heat generating body **30** to the outer face **20b** of the second metal sheet **20**, the position on the back surface of the heat generating body **30** on the inner surface **20a** of the second metal sheet **20** becomes a condensation part **42**, and the

liquid-phase working fluid favorably flows to the top face groove part **16** from the bottom groove part **14** via the side face groove part **15**. Since circulation of the liquid-phase working fluid and the gas-phase working fluid further improves, the heat transport characteristics of the vapor chamber **1** further improves. The heat generating body **30** is a member such as an electronic component which generates heat during operation, such as a semiconductor element, for example.

(41) In addition, from the viewpoint of an improvement in heat transport characteristics of the vapor chamber **1**, the projecting part **12** including the top face groove part **16** is preferably arranged at a position excluding the evaporation part **41**.

(42) The vapor chamber **1** cools the heat generating body **30** mainly by the following cooling path.

(43) First, the heat generated by the heat generating body **30** thermally connected with the outer surface **20b** of the second metal sheet **20** is transferred to the evaporation part **41** positioned at the inner surface **20a** of the second metal sheet **20**. The evaporation part **41** causes the liquid-phase working fluid flowing in the top face groove part **16** to evaporate and phase changes to gas-phase working fluid, by the heat received from the heat generating body **30**. The gas-phase working fluid heated by evaporation flows to the condensation part **42** at a position distanced from the evaporation part **41**, as shown by the arrow F(G). In the course of the gas-phase working fluid flowing toward the condensation part **42**, the temperature of the working fluid drops. In the condensation part **42**, the gas-phase working fluid which has dropped in temperature is condensed and phase changes to the liquid-phase working fluid. The latent heat generated by phase change is transferred to the first metal sheet **10** or the second metal sheet **20**, and is radiated to outside of the vapor chamber **1**. The condensed liquid-phase working fluid favorably flows in the in-plane direction of the vapor chamber **1**, along the bottom groove part **14**, as shown by the arrow F(L). When the liquid-phase working fluid flowing in the bottom groove part **14** reaches the side face groove part **15**, the liquid-phase working fluid favorably flows in the thickness direction of the vapor chamber **1** along the side face groove part **15**. The liquid-phase working fluid flowing in the thickness direction of the vapor chamber **1** returns to the evaporation part **41** again via the top face groove part **16**. By such favorable circulation of the liquid-phase working fluid and the gas-phase working fluid, the vapor chamber **1** can cool the heat generating body **30**.

(44) Next, a manufacturing method of the above-mentioned vapor chamber **1** will be explained.

(45) The manufacturing method of the vapor chamber **1** has a laser processing step of forming at least the side face groove part **15** among the flow channel groove **13** of the first metal sheet **10** by laser. In the laser processing step, it is preferable to form the side face groove part **15** by a fiber laser. In the laser processing, the side face groove part **15** tends to be process controlled to the desired shape, and the side face groove part **15** can be formed in a short time. Furthermore, among lasers, the fiber laser is more superior in processing control and short-time processing. On the other hand, in the etching process using an etchant adopted in a conventional vapor chamber, the formation of the side face groove part **15** itself is difficult.

(46) In addition, in the laser processing step, forming the flow channel groove **13** by laser is preferable. In other words, it is preferable to form the bottom groove part **14**, the side face groove part **15** and the top face groove part **16** constituting the flow channel groove **13** by laser. When using a laser, it is possible to form the flow channel groove **13** including the side face groove part **15** into the desired shape in a short time. On the other hand, in a conventional etching process, it is difficult to conduct processing control of the flow channel groove **13** including the side face groove part **15** into the desired shape.

(47) In addition, the manufacturing method of the vapor chamber **1** preferably further includes a press processing step of forming the recessed channel **11** and the projecting part **12** of the first metal sheet **10** by press molding, prior to the laser processing step. By press molding the first metal sheet **10**, it is possible to easily form the recessed channel **11** and the projecting part **12**.

(48) In addition, the manufacturing method of the vapor chamber **1** preferably further includes a laser welding step of welding the first metal sheet **10** and the second metal sheet **20** by laser, after

the laser processing step. By welding the first metal sheet **10** and the second metal sheet **20** by laser, it is possible to easily manufacture the vapor chamber **1** including the internal space **S** inside. (49) More specifically, the inner surface **10a** of the first metal sheet **10** including the recessed channel **11**, the projecting part **12**, the flow channel groove **13**, etc. and the inner surface **20a** of the second metal sheet **20** are opposing each other, and the laser is irradiated onto the first metal sheet **10** and the second metal sheet **20** in a state in which the outer edge **10c** of the first metal sheet **10** and the inner surface **20a** of the second metal sheet **20** are contacting. For example, the laser may be irradiated onto the contacting portion of the first metal sheet **10** and the second metal sheet **20** from the side of the first metal sheet **10**, the laser may be irradiated onto the contacting portion of the first metal sheet **10** and the second metal sheet **20** from the side of the second metal sheet **20**, the laser may be irradiated onto the contacting portion of the first metal sheet **10** and the second metal sheet **20** from the in-plane direction of the vapor chamber **1**, or the irradiation of these lasers may be combined.

(50) In addition, the above-mentioned vapor chamber **1** is suitably used in electronic devices such as portable telephones, for which good heat transport characteristics are required even in various postures. The electronic device equipped with the vapor chamber **1** has high heat transport characteristics of the vapor chamber **1**, even in various usage states.

(51) According to the above explained embodiment, the liquid-phase working fluid in the internal space of the vapor chamber favorably flows also in the thickness direction of the vapor chamber along the flow channel groove. Since disturbance in the flow of the liquid-phase working fluid is suppressed, the flow of circulation of the liquid-phase working fluid and the gas-phase working fluid improves, and the heat transfer within the internal space of the vapor chamber increases. For this reason, the vapor chamber can have superior heat transfer characteristics.

(52) It should be noted that, although the above illustrates an example mounting a heat generating body **30** to the outer surface **20b** of the second metal sheet **20** as shown in FIG. 1, the heat generating body **30** may be mounted to the outer surface **10b** of the first metal sheet **10**.

(53) In addition, although the above illustrates an example in which the inner surface **20a** of the second metal sheet **20** is flat, in addition to the first metal sheet **10**, the inner surface **20a** of the second metal sheet **20** may have the bottom groove part **14**. When the second metal sheet **20** has the bottom groove part **14**, the heat transfer characteristics of the vapor chamber **1** further improve.

(54) In addition, although the above illustrates an example in which the inner surface **20a** of the second metal sheet **20** is flat, the inner surface **20a** of the second metal sheet **20** may have any of the configurations of the recessed channel, at least one projecting part and at least one flow channel groove, similarly to the inner surface **10a** of the first metal sheet **10**. When the second metal sheet **20** has the recessed channel, at least one projecting part or at least one flow channel groove, the heat transfer characteristics of the vapor chamber **1** further improve.

(55) In addition, although the above illustrates an example in which the projecting part **12** is cylindrical as shown in FIG. 1, the shape of the projecting part **12** is sufficient so long as the top face **12a** can abut the inner surface **20a** of the second metal sheet **20**. For example, the shape of the projecting part **12** may be a square column, as shown in FIG. 5.

(56) In addition, although the above illustrates an example in which the uniformity of the sheet thickness of the first metal sheet **10** is high as shown in FIGS. 1 to 4, the sheet thickness at the projecting part **12** of the first metal sheet **10** may be clearly greater than the sheet thickness at the recessed channel **11**, as shown in FIGS. 6 to 8. In this case, the bottom groove part **14** may enter part of the projecting part **12**, and preferably penetrates the projecting part **12** as illustrated. If the bottom groove part **14** enters part of the projecting part **12** or penetrates the projecting part **12**, since the liquid-phase working fluid flows more favorably, the heat transfer characteristics of the vapor chamber **1** further improve.

(57) Although an embodiment has been explained above, the present invention encompasses all aspects included in the gist of the present disclosure and the claims without being limited to the

above-mentioned embodiment, and can be modified in various ways within the scope of the present disclosure.

EXPLANATION OF REFERENCE NUMERALS

(58) **1** vapor chamber **10** first metal sheet **10a** inner surface of first metal sheet **10b** outer surface of first metal sheet **10c** outer edge of first metal sheet **11** recessed channel **11a** bottom of recessed channel **12** projecting part **12a** top face of projecting part **12b** side face of projecting part **13** flow channel groove **14** bottom groove part **15** side face groove part **16** top face groove part **17** crossing part **20** second metal sheet **20a** inner surface of second metal sheet **20b** outer surface of second metal sheet **30** heat generating body **41** evaporation part **42** condensation part **S** internal space **F(L)** flow of liquid-phase working fluid **F(G)** flow of gas-phase working fluid

Claims

1. A vapor chamber having a working fluid in an internal space formed between a first metal sheet and a second metal sheet, wherein: the first metal sheet comprises a recessed channel, at least one projecting part, and at least one flow channel groove, the recessed channel is provided at an inner surface of the first metal sheet, the projecting part projects from the inner surface of the first metal sheet toward an inner surface of the second metal sheet, and a top face of the projecting part abuts the inner surface of the second metal sheet, the flow channel groove has a bottom groove part, a side face groove part and a top face groove part, the bottom groove part is provided at a bottom face of the recessed channel, the side face groove part is provided at a side face of the projecting part, and is connected to the bottom groove part, and the top face groove part is provided at the top face of the projecting part, and is connected to the side face groove part, wherein, the bottom groove part, the side face groove part and the top face groove part form a sealed space, the top groove part is higher than the side face groove part, for the top face groove part, first ends differing from second ends connecting with the side face groove part are connected to each other, or for the bottom face groove part, third ends differing from fourth ends connecting with the side face groove part are connected to each other.
2. The vapor chamber according to claim 1, wherein each of the bottom groove part, the side face groove part and the top face groove part of the flow channel groove has a groove depth d and a groove width w with the groove depth d being longer than the groove width w .
3. The vapor chamber according to claim 1, wherein a ratio (t_2/t_1) of a sheet thickness t_2 at the projecting part of the first metal sheet relative to a sheet thickness t_1 at the recessed channel of the first metal sheet is 0.1 or more and 10.0 or less.
4. The vapor chamber according to claim 1, wherein the first metal sheet includes a plurality of the flow channel grooves, and has a crossing part at which the plurality of the flow channel grooves intersect.
5. The vapor chamber according to claim 2, wherein a ratio (t_2/t_1) of a sheet thickness t_2 at the projecting part of the first metal sheet relative to a sheet thickness t_1 at the recessed channel of the first metal sheet is 0.1 or more and 10.0 or less.
6. The vapor chamber according to claim 2, wherein the first metal sheet includes a plurality of the flow channel grooves, and has a crossing part at which the plurality of the flow channel grooves intersect.
7. The vapor chamber according to claim 3, wherein the first metal sheet includes a plurality of the flow channel grooves, and has a crossing part at which the plurality of the flow channel grooves intersect.
8. The vapor chamber according to claim 1, wherein the bottom groove part, the side face groove part and the top face groove part form a sealed space.
9. The vapor chamber according to claim 1, wherein the top groove part is higher than the side face groove part.

10. The vapor chamber according to claim 1, wherein for the top face groove part, first ends differing from second ends connecting with the side face groove part are connected to each other.
 11. The vapor chamber according to claim 1, wherein for the bottom face groove part, third ends differing from fourth ends connecting with the side face groove part are connected to each other.
-