

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403754
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Tobon; David et al.

Hidden outer belt seal

Abstract

Various examples of a window seal for a door assembly, e.g., for a vehicle, a door assembly, and a method of making a seal or door assembly are provided. A window seal may include a longitudinally extending channel having a cross section opened toward a moveable window. The belt seal structure may further comprise an insert having a base received longitudinally in the channel. An example door assembly may include an exterior door panel having a visible exterior surface and an interior surface. The door assembly may further comprise a window seal having a channel extending along the interior surface and an insert comprising a base received longitudinally in the channel. Example inserts may comprise a sealing lip extending laterally out of the channel to contact the moveable window.

Inventors: Tobon; David (Northville, MI), Mumma; Benjamin (Huntington Woods, MI)

Applicant: Rivian IP Holdings, LLC (Plymouth, MI)

Family ID: 92933370

Assignee: Rivian IP Holdings, LLC (Plymouth, MI)

Appl. No.: 18/135912

Filed: April 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240351412 A1	Oct. 24, 2024

Publication Classification

Int. Cl.: B60J10/75 (20160101); B60J10/76 (20160101)

U.S. Cl.:

Field of Classification Search**CPC:** B60J (10/75); B60J (10/20); B60J (10/76)**USPC:** 49/377

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2198290	12/1939	Place	49/492.1	B60J 10/75
2523839	12/1949	McKinney	49/492.1	B60J 10/75
2664603	12/1953	McKinney	49/377	B60J 10/75
2913783	12/1958	Bright	49/377	B60J 10/75
3203059	12/1964	Becker	24/336	B60J 10/75
3359688	12/1966	Kondolf	49/490.1	B60J 10/75
3583757	12/1970	Wilfert	296/84.1	B60R 13/07
3763596	12/1972	Anderson	49/492.1	B60J 10/75
4330959	12/1981	Nishikawa	49/377	B60J 10/75
4442634	12/1983	Kimura	49/377	B60J 10/17
4481736	12/1983	Norton	49/377	B60J 10/75
4817336	12/1988	Kisanuki	49/377	B60J 10/21
4860494	12/1988	Fujii	49/377	B60J 10/75
5054240	12/1990	Nakahara et al.	N/A	N/A
5085005	12/1991	Yasukawa	15/250.1	B60J 10/244
5275455	12/1993	Harney et al.	N/A	N/A
5339488	12/1993	Maass	15/250.19	B60J 10/248
5353549	12/1993	Henderson	49/492.1	B60J 10/75
5388371	12/1994	Nozaki	49/377	B60J 10/265
5495693	12/1995	Tiesler	296/146.3	B60J 1/17
5607198	12/1996	Wirsing	49/492.1	B60J 1/17
5815985	12/1997	Nishida	49/377	B60J 10/265
5970659	12/1998	Oord	49/377	B60J 10/75
6070364	12/1999	Berry	49/495.1	B60J 10/75
7210730	12/2006	Fujita et al.	N/A	N/A
7390050	12/2007	Nakao et al.	N/A	N/A
7407205	12/2007	Nakao et al.	N/A	N/A
8549790	12/2012	Murree	49/377	B60J 10/75
9649994	12/2016	Masuda	N/A	B60J 10/16
10035411	12/2017	Toyota	N/A	B60J 10/50
10232694	12/2018	Alhof	N/A	B60J 10/88
10442276	12/2018	Kunapareddy	N/A	B60J 10/75
11938792	12/2023	Filipczak	N/A	B60J 10/75
2005/0126077	12/2004	Cittadini	49/377	B60J 10/38
2007/0227072	12/2006	Kawase	49/377	B60J 10/75
2013/0061532	12/2012	Dishman	24/570	B60J 10/32
2019/0061503	12/2018	Filipczak	N/A	B60J 1/2097

2023/0118935	12/2022	Warmington	49/493.1	B60J 5/0415
2025/0065703	12/2024	Li	N/A	B60J 10/76
2025/0083508	12/2024	Che	N/A	B60J 10/75

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1850524	12/2010	CN	B60J 10/24
102652071	12/2011	CN	B60J 5/0413
111890902	12/2019	CN	B60J 10/76
3615078	12/1986	DE	N/A
2865969	12/2004	FR	B60J 10/75
3047930	12/2016	FR	B60J 10/16
3051731	12/2016	FR	B60J 10/273
1218687	12/1989	IT	B60J 1/001
2003252055	12/2002	JP	B60J 10/75
2004249745	12/2003	JP	B60J 10/75
19980013375	12/1997	KR	N/A
20060060862	12/2005	KR	N/A
100892492	12/2008	KR	N/A

Primary Examiner: Kelly; Catherine A

Attorney, Agent or Firm: Haley Guiliano LLP

Background/Summary

INTRODUCTION

(1) The present disclosure is directed to systems and methods for providing an outer belt seal for a vehicle door assembly that remains generally hidden and, more specifically, to systems and methods for installing an outer belt seal that remains hidden and facilitates service and replacement.

SUMMARY

(2) Belt line seals are utilized to create a seal against an actuated window within a door assembly to limit or prevent the intrusion of fluids into the body of the door assembly. A belt line seal is positioned between a door panel and a surface of the actuated window. Belt line seals are typically secured to an upper edge of a door panel with at least a portion of the seal or associated cladding being visible adjacent window glass. These elements are typically molded and cannot be painted to match exterior surfaces of the door panel assembly, and as such may create unsightly or otherwise undesirable interruptions or blemishes in vehicle styling. There is a desire to eliminate the belt line seal from view to improve vehicle aesthetics, however moving the seal to locations hidden from view inherently makes servicing or replacing the seal more difficult. As a result, a compromise generally must be struck between serviceability and vehicle styling, particularly for vehicles used in commercial applications or where an extended service life is otherwise expected.

(3) Accordingly, in at least some example approaches herein, a vehicle window seal is provided comprising a longitudinally extending channel having a cross section opened toward a moveable window. The belt seal structure may further comprise an insert having a base received longitudinally in the channel. The insert comprises a sealing lip extending laterally out of the channel to contact the moveable window.

(4) In at least some examples, the base comprises at least one protrusion configured to contact one

or more inner surfaces of the channel to retain the insert in the channel by creating friction between the at least one protrusion and the one or more inner surfaces.

(5) In at least some examples, the at least one protrusion comprises a plurality of protrusions, each extending in a different direction from the base.

(6) In at least some example illustrations, the channel defines a c-shaped cross section.

(7) In at least some examples, the channel defines opposing interior surfaces engaged by upper and lower protrusions of the base.

(8) In at least some examples, the base defines a hollow cross section, with the sealing lip defined by a protrusion extending away from the hollow cross section. The base may also comprise one or more protrusions configured to contact one or more inner surfaces of the channel.

(9) In at least some example approaches, the sealing lip comprises a layer of wear resistant material that prevents marks from appearing on a glass window.

(10) In at least some example illustrations, the base of the insert defines a locking pin structure configured to extend through a lock aperture defined by the channel.

(11) In at least some examples, the locking pin structure is integrally formed with the base.

(12) In at least some example approaches, the locking pin structure extends laterally away from the window.

(13) In at least some example illustrations, the locking pin structure is located longitudinally on the base such that the locking pin structure is received in the lock aperture when the base is fully inserted into the channel.

(14) In at least some examples, the channel comprises a locator tab configured to limit longitudinal insertion of the base of the insert into the channel.

(15) In at least some examples, the belt seal structure comprises a door panel having an interior surface defining the longitudinally extending channel.

(16) Additional examples herein are directed to a door assembly comprising an exterior door panel having a visible exterior surface extending toward a window opening for a moveable window. The exterior door panel also has an interior surface. The door assembly further comprises a window seal having a longitudinally extending channel extending along the hidden interior surface, the channel having a cross-section opened toward the moveable window. The window seal also comprises an insert having a base received longitudinally in the channel. The insert comprises a sealing lip extending laterally out of the channel to contact the moveable window.

(17) In at least some example illustrations, the door assembly defines an access hole aligned with channel for withdrawing the insert longitudinally from the channel and out of the door assembly.

(18) In at least some example approaches, the base of the insert defines a locking pin structure configured to extend through a lock aperture defined by the base of the channel. Further, in these examples the channel may have a locator tab configured to limit longitudinal insertion of the base of the insert into the channel.

(19) In at least some examples, the locking pin structure is integrally formed with the base. Additionally, the locking pin structure may be located longitudinally on the base such that the locking pin structure is received in the lock aperture when the base is fully inserted into the channel.

(20) Example illustrations are also directed to a method of manufacturing a door assembly. In an example, the method comprises positioning a longitudinally extending channel along an interior surface of a door panel. The method may further include inserting a base of an insert longitudinally into the channel. The insert may have a sealing lip extending laterally out of the channel to contact a moveable window.

(21) In at least some example methods, the method further comprises sealing an access hole defined by the door panel with a removeable plug. The access hole may be aligned with the channel such that the insert is configured to be withdrawn longitudinally from the channel and out of the door assembly through the access hole.

(22) In at least some examples, a method further includes limiting longitudinal insertion of the base of the insert into the channel with a locator tab of the channel, wherein the base of the insert defines a locking pin structure configured to extend through a lock aperture defined by the base of the channel when the insert is fully inserted longitudinally into the channel. The locking pin structure may in at least some examples be integrally formed with the base.

Description

BRIEF DESCRIPTIONS OF THE DRAWINGS

- (1) The above and other objects and advantages of the disclosure may be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 illustrates an example door assembly incorporating a belt seal assembly that remains generally hidden from view and comprises a channel and insert to facilitate service and/or replaceability, in accordance with some disclosed embodiments;
- (3) FIG. 2A is an end view of the channel of FIG. 1, in accordance with some disclosed embodiments;
- (4) FIG. 2B is a side view of the channel of FIG. 2A, in accordance with some disclosed embodiments;
- (5) FIG. 3 illustrates another example door assembly incorporating a belt seal assembly that remains generally hidden from view and comprises a channel and insert to facilitate service and/or replaceability, in accordance with some disclosed embodiments;
- (6) FIG. 4A illustrates the door assembly of FIG. 1 or FIG. 3, illustrating the insert aligned for insertion into the channel and/or the door assembly, in accordance with some disclosed embodiments;
- (7) FIG. 4B illustrates the door assembly of FIG. 4A, illustrating the insert partially inserted into the channel and the door assembly, in accordance with some disclosed embodiments;
- (8) FIG. 5A illustrates the door assembly of FIG. 1 or FIG. 3, illustrating an access hole of the door assembly and a removeable plug, in accordance with some disclosed embodiments;
- (9) FIG. 5B illustrates the removeable plug of FIG. 5A, in accordance with some disclosed embodiments;
- (10) FIG. 6A illustrates an example method for manufacturing a door assembly that incorporates a belt seal assembly, in accordance with some disclosed embodiments;
- (11) FIG. 6B illustrates an example method for servicing an insert for a belt seal assembly, in accordance with some disclosed embodiments; and
- (12) FIG. 7 illustrates an example vehicle assembly that includes one or more door assemblies, in accordance with some disclosed embodiments.

DETAILED DESCRIPTION

- (13) Methods and systems are provided herein for providing an outer belt seal that generally remains hidden from view from users/drivers of the vehicle and observers outside the vehicle. The belt seal may be generally concealed within a door assembly such that it is hidden from view during normal use. Nevertheless, the belt seal may also facilitate service and/or replacement of sealing element(s) in contact with moveable windows, e.g., as may be useful for high-mileage or high-usage vehicles. For example, as will be described further below, a belt seal structure may have a removeable insert that can be withdrawn from a door assembly without requiring disassembly of the door assembly or special tools to access the insert.
- (14) Turning now to FIG. 1, a vehicle **100** having an example door assembly **102a** is illustrated that incorporates a window seal (e.g., a belt seal structure for a vehicle, or vehicle window seal) or assembly **104a** with features that facilitate positioning of a seal such that it remains generally

hidden when installed, and also allows for relatively easy removal and/or replacement. The door assembly **102a** generally houses a moveable window **106**. The window **106** may be formed of glass, e.g., safety glass, and may translate vertically within the door assembly **102a**. Merely by way of example, the window **106** may be moved vertically up/down by a crank or electrically powered actuator. The window seal **104a** generally comprises a longitudinally extending channel **108a** having a base **110** adjacent the moveable window **106**. The channel **108a** generally faces toward the window **106**. As illustrated in FIG. 1, the window seal **104a** may be positioned adjacent a lower portion of a window opening, such that the window seal **104a** is positioned along a beltline of the vehicle.

(15) The door assembly **102a** may have any construction that is convenient. As shown in the example in FIG. 1, the inner door panel **112** may be joined at an upper edge thereof with an exterior door panel **114**, e.g., via a press such as a hemming press or the like. The inner door panel **112** and exterior door panel **114** may be joined around an entire perimeter of each in similar manner as shown along the upper edge, thereby forming an outer door assembly. The outer door assembly may be joined with an interior door assembly **116**. The interior door assembly **116** may include a trim panel **118** mounted to an interior door structure **120**. The interior door structure **120** may comprise an interior inner panel **122** and interior outer panel **124**, which may be hemmed or otherwise joined together in any manner that is convenient. The interior door structure **120** may be joined with the exterior door panel **114** and/or inner door panel **112** along front, rear, and bottom sides of the door assembly **102a**, with a window opening **126** being defined along an upper end of the door assembly **102a**. The window **106** may protrude through the window opening when raised vertically by the actuator, and may be withdrawn into an interior **128** of the door assembly **102a** when lowered.

(16) An interior seal **130** may be secured to an upper edge of the interior inner panel **122** in any manner that is convenient. In the example illustrated, the seal **130** includes a base **132** having a plurality of fingers **134** that are resiliently engaged with the interior inner panel **122**. The interior seal **130** also has a sealing arm **136** extending away from the base to engage the window **106**. The sealing arm **136** may generally remain in contact with the window **106** during raising/lowering of the window **106**, and may thereby generally “wipe” foreign objects, liquid, dust, etc. from the interior surface of the window **106**. The sealing arm **136** may also generally prevent foreign objects, liquid, or the like from falling into the door assembly **102a** from an interior side of the window **106**.

(17) In the example illustrated, the channel **108a** is formed as a separate component and secured to an inner door panel **112**. While the channel **108a** is generally formed as a separate component from the inner door panel **112**, in other examples that will be described further below a channel may be formed directly in the inner door panel. In any case, the channel **108a** is illustrated in FIG. 1 having a cross section opened toward the moveable window **106**.

(18) The window seal **104a** may have an insert **138** that is received longitudinally in the channel **108a**. More specifically, as illustrated in FIG. 1 the insert **138** has a base **140** that is received longitudinally in the channel **108a**. The insert **138** and channel **108a** may each have a generally consistent cross section longitudinally with respect to the door assembly **102a** and/or the vehicle **100** (i.e., longitudinally being oriented in a front-to-rear direction of the vehicle **100**). Accordingly, the insert **138** may be slid into the channel **108a**. Further, as will be discussed below in more detail, the insert **138** may be configured to be removed from the channel **108a**. The insert **138** may be configured to seal against the window **106**, e.g., to prevent intrusion of contaminants, water, or the like into the door assembly **102a**. Accordingly, the insert **138** may be provided with a sealing lip or other feature to engage or contact the window. In the example illustrated in FIG. 1, the insert **138** comprises a sealing lip **142** extending laterally out of the channel to contact the moveable window **106**. The base **140** generally has a hollow cross section, e.g., to facilitate compression for fitting within the channel **108a**. More specifically, the sealing lip **142** is defined by a protrusion or arm

extending away from the hollow cross section of the base **140**. More specifically, arm **144** extends away from the base **140** such that the arm **144** extends generally upwardly to the sealing lip **142**, with the sealing lip **142** positioned at an end of the arm **144** to contact the window **106**. Accordingly, in similar manner as the sealing arm **136** on the interior side of the window **106**, the sealing lip **142** generally remains in contact with the window **106** and may “wipe” liquid, dust, etc. from an exterior surface of the window **106**. The sealing lip may have a layer of wear resistant material that prevents marks from appearing on the window **106**, which as noted above may be formed of a glass material. Example wear resistant materials may generally reduce drag/friction on a contact surface of a glass window, e.g., window **106**, and also prevent marks from appearing on the glass window. Wear resistant materials may be a coating or a secured separate layer of material. Further, the sealing lip **142** may prevent foreign objects, liquid, or the like from falling into the door assembly **102a** from an exterior side of the window **106**.

(19) As seen in FIGS. **1** and **2**, the base **140** may have one or more lobes **151a**, **151b** (collectively, **151**) which may facilitate retention of the base **140** within the channel **108a**. More specifically, an upper lobe **151a** is disposed along an upper portion of the base **140** such that it contacts upper curved surface **150b** of the channel **108a**, while a lower lobe **151b** is disposed along a lower portion of the base **140** such that it contacts lower curved surface **150c** of the channel **108a**. The upper and lower curved surfaces **150b**, **150c** may generally wrap around the corresponding lobes **151**, e.g., such that the curved surfaces **150b**, **150c** each laterally restrain their respective lobes **151** on opposite sides thereof.

(20) The base **140** may include one or more additional features that generally facilitate retention of the insert **138** within the channel **108a**. For example, as illustrated in FIG. **1**, the base **140** may have protrusions **148a**, **148b**, **148c**, **148d**, and **148e** (collectively, **148**) that are configured to engage with one or more interior surfaces of the channel **108a** when the insert **138** is longitudinally inserted into the channel **108a**. Generally, the additional friction provided by the protrusions works in combination with the lobes **151** being retained within the curved surfaces **150b**, **150c** to retain the base **140** within the channel **108a**. However, in some example approaches only one of these two features, or none, are present. In the example illustrated in FIG. **1**, the base **140** includes protrusion **148a** which projects vertically upward from the base **140**, protrusions **148b**, **148c**, and **148d** which project laterally away from the base **140** and window **106**, and protrusion **148e** which projects vertically downward from the base **140**. However, any number of protrusions **148** may be employed that is convenient, and the protrusions **148** may have any configuration that is convenient. Moreover, in at least some example approaches the base **140** is without any protrusions **148** (e.g., where an elasticity or compliance of the base **140** is sufficient to allow the base **140** to be adequately retained within the channel **108a** without the protrusions **148**). One or more of the protrusions **148**, and in some cases all of the protrusions **148**, may extend longitudinally along the base **140**, and as such each of the protrusions **148** may thereby defining one or more corresponding ridges along the base **140**. The protrusions **148** may each be in contact with interior surfaces **150** of the channel **108a**. The base **140** and protrusions **148** (and, for that matter, all other components/portions of the insert **138**) may be formed of a resilient material such as rubber or other thermoplastic vulcanizates, or the like, that is configured to deflect or compress, allowing the base **140** to be radially “squeezed” into the channel **108a**. In some examples, protrusion(s) **148** are formed integrally with the base **140**, e.g., via an extrusion process. Accordingly, the protrusions **148** may each make contact with inner surfaces **150** of the channel **108a**, and may retain the insert **138** an opening defined by the channel **108a**. More particularly, the protrusions **148** each generally create or increase friction between the protrusions **148**, respectively, and inner surface(s) **150** contacted by the protrusion **148**. The protrusions **148** may deflect to allow the base **140** to be received within the channel **108a**. Accordingly, absent application of a sufficient longitudinal force applied to the insert **138** to remove from the channel **108a**, the insert **138** may remain resiliently retained within the channel **108a**. It should be noted that protrusions **148** or other gripping features

or gripping structure may have different shapes or dimensions than those depicted, and may incorporate additional features to enable the base **140** to remain resiliently retained within the depicted channel **108a**.

(21) Referring now to FIGS. **1**, **2A**, and **2B**, the channel **108a** is illustrated and described in further detail. The channel **108a**, as noted above, is generally opened toward the window **106**. The channel **108a** may define a c-shaped cross section. Interior surfaces **150** of the channel **108a** generally facilitate retention of the insert **138** within the channel **108a**, e.g., via one or more protrusions **148** as noted above. More specifically, the interior surfaces **150** include a base surface **150a**, an upper curved surface **150b**, and a lower curved surface **150c**. The upper and lower curved surfaces **150b**, **150c** are opposing surfaces. For example, the surfaces **150b** and **150c** face each other such that the protrusions **148** associated with each may deflect in opposition to each other. Accordingly, the base **140** of the insert **138** is resiliently retained within the channel **108a**. Absent a longitudinally applied force overcoming the friction between the base **140** and the interior surfaces **150**, the insert **138** may generally remain within the channel **108a**. In some examples, it may be desirable to remove the insert **138** from the channel **108a**, e.g., to allow service and/or replacement of the insert **138**.

(22) Referring now to FIG. **2B**, the base **140** of the insert **138** may define a locking pin structure **152** configured to extend through a lock aperture **154** defined by the channel **108a** when the insert **138** is fully inserted longitudinally into the channel **108a**. While the locking pin structure **152** is illustrated as being formed integrally with the base **140** of the insert **138**, any configuration of the locking pin structure **152** may be employed that is convenient. For example, a separate pin or other structure may be provided that extends laterally through the insert **138** and channel **108a**, thereby generally preventing longitudinal movement of the insert **138** within the channel **108a**. Further, at an opposite end of the channel **108a** from the lock aperture **154**, a locator tab **156** of the channel **108a** protrudes into the channel **108a**, thereby preventing over-insertion of the insert **138**.

Accordingly, the locator tab **156** may limit longitudinal insertion of the base **140** of the insert **138** into the channel **108a**. The locator tab **156** may thereby prevent over-insertion or otherwise incorrect positioning of the insert **138** within the channel **108a**. The insert **138** may be sized longitudinally so that as the insert **138** is installed by longitudinal insertion into the channel **108a**, an end of the insert **138** abuts the locator tab **156** as the locking pin structure **152** reaches the lock aperture **154**. The locking pin structure **152** and locator tab **156** may each further enhance the degree to which the insert **138** is resiliently retained within the channel **108a** after installation/insertion. Nevertheless, the insert **138** may still be removed from the channel **108a** by application of sufficient longitudinal force, e.g., in a direction opposite that for insertion/installation of the insert **138** to the channel **108a**, to thereby dislodge the locking pin structure **152** from the lock aperture **154**. (It should be noted that in examples where the locking pin is a separate part from the insert **138**/base **140**, it may be necessary or desirable to first remove the pin before sliding the insert **138** longitudinally out of the channel **108a**.) Accordingly, the insert **138** may be withdrawn from the channel **108a** for service and/or replacement of the insert **138**. Additionally, to the extent the locking pin structure **152** or other features of the insert **138** make the insert **138** asymmetrical longitudinally, an “insertion end” of the insert **138** is more clearly identified, and may facilitate insertion of the insert **138** in the designed orientation. Put another way, the locking pin structure **152** provides a visual cue as to the non-insertion end of the insert **138**, facilitating correct insertion of the opposite end of the insert **138** into the channel **108** by manufacturing or service personnel. While the locking pin structure **152** and/or the locator tab **156** may enhance retention of the insert **138** or provide other benefits such as described above, it should be noted that in some example approaches a locking pin (e.g., locking pin structure **152**) and locator tab **156** may not be needed. For example, to any extent friction between the channel **108a** and the base **140** is generally sufficient to retain the insert **138** in a desired longitudinal position in the channel **108a**, it may not be necessary to provide a locking pin (e.g., locking pin structure **152**) or locator tab **156**. For example, an elasticity/compliance and/or shape of the base **140** may, in some cases, be sufficient to

retain the base **140** securely within the channel **108a**. Moreover, other features may be provided as alternatives to the locking pin structure **152** and/or locator tab **156**. Merely as one examples, an end cap or cover in the channel **108a** may retain the insert **138** within the channel **108a**, and/or a pin formed as a separate part from the insert **138** may be passed through the insert **138** and the channel **108a** after the insert **138** is installed.

(23) As noted above, the channel **108a** in the example illustrated in FIG. **1** is configured to be secured to an interior surface of inner door panel **112**. The channel **108a** may be formed as a separate component and secured to interior surface **112'** of the inner door panel **112**. The channel **108a** may be formed in any manner of any material that is convenient. In an example, the channel **108a** is stamped or rolled, e.g., using a sheetmetal blank, and then welded or bonded to the interior surface **112'**. In another example, the channel **108a** is extruded or molded of a plastic, polypropylene, or nylon material, and secured to the interior surface **112'** via one or more clips (not shown), or via bonding, merely as examples.

(24) In another example approach, a channel may be defined by a door panel itself, rather than being formed as a separate component. For example, referring now to FIG. **3**., another example door assembly **102b** having a window seal **104b** is illustrated. The window seal **104b** comprises insert **138**, which is received in a channel **108b** defined by an interior door panel **113**. More specifically, an interior surface **113'** of the door panel **113** defines the longitudinally extending channel **108b**. The general shape and structure of the channel **108b** of the interior door panel **113** may generally be the same as described above regarding channel **108a**, e.g., with the channel **108b** extending longitudinally along the interior door panel **113** to allow insertion of the same insert **138** described above. Additionally, the insert **138** may, in at least some examples, be identical in FIG. **3** to the example seal illustrated in FIGS. **1-2** and described above.

(25) In each of the foregoing example window seals **104a** and **104b**, components may generally remain hidden from view, e.g., from outside the vehicle. For example, a visible exterior surface **114'** of the exterior door panel **114** generally extends toward the window opening **126** for window **106**, with the window seals **104a/104b** concealed within the door assembly **102a/102b**, as respectively seen in FIGS. **1** and **3**. More particularly, the door assembly **102a/102b** has an interior surface that remains hidden, and to which the channel **108a** is attached as shown in FIG. **1**. Similarly, in the example illustrated in FIG. **3**, the channel **108b** is defined by interior door panel surface **113'**, which remains hidden from view. Accordingly, the window seals **104a** and **104b** are generally not visible from outside the door assemblies **102a/102b**, enhancing aesthetic appeal of the vehicle **100**.

(26) Referring now to FIGS. **4A** and **4B**, door assembly **102** may define an access hole **158**, e.g., at an end of the door assembly **102** adjacent a free end (i.e., non-hinged or rearward end) of the door assembly **102**. The insert **138** is illustrated being inserted into the access hole **158**, e.g., in an installation or replacement procedure, in FIG. **4A**. The insert **138** may be inserted further into the channel **108**, e.g., as shown in FIG. **4B**.

(27) The access hole **158** may, in some example approaches, be aligned with channel **108** with respect to the longitudinal direction of insertion/removal of the insert **138** to the channel **108**. Accordingly, for the insert **138** may with withdrawn longitudinally from the channel **108** and out of the door assembly **102** via the access hole **158**. Additionally, a removeable plug **160** may be provided that is configured to seal the access hole **158** and/or the door assembly **102**, or otherwise prevent ingress of liquid, dirt, debris, etc. into the door assembly **102** via the access hole **158**.

(28) Referring now to FIG. **6A**, an example process **600** for manufacturing a door assembly, e.g., that incorporates a belt seal structure, is illustrated and described in further detail. Method **600** may incorporate or be used to manufacture aspects of door assembly **102a** of FIG. **1**, door assembly **102b** of FIG. **3**, and/or vehicle **100** of FIG. **1**, in accordance with some embodiments of this disclosure.

(29) Process **600** may begin at block **602**. At block **602**, process **600** may provide an exterior door

panel. For example, as discussed above, an exterior door panel **114** may be provided having a visible exterior surface **114'** extending toward a window opening **126** for a moveable window **106**. Further, the exterior door panel **114** and/or may have a hidden interior surface, of an inner door panel **112**. Process **600** may then proceed to block **604**.

(30) At block **604**, process **600** may provide a belt seal structure, e.g., window seal **104a** or **104b**. For example, as described above, a base of a longitudinally extending channel may be positioned along or upon the hidden interior surface of the door assembly **102**. In some examples, a channel **108a** may be a separate component that is secured to the interior surface **112'**. In another example described above, a channel **108b** is provided that is defined by an interior surface **113'** of the door panel. In either case, the channel **108a/108b** is generally opened toward the moveable window **106**.

(31) Proceeding to block **606**, process **600** may further include inserting a base of an insert longitudinally into the channel. For example, as described above an insert **138** may have a base **140** which may be longitudinally inserted into channel **108a** or **108b**. Additionally, the insert **138** may have a sealing lip **142** extending laterally out of the opened channel **108** to contact the moveable window **106**. In some examples, process **600** may also limit longitudinal insertion of the base **140** of the insert **138** into the channel **108**, e.g., with a locator tab **156** of the channel **108** as described above. Furthermore, in some examples as discussed above, the base **140** of the insert **138** may define a locking pin structure **152** configured to extend through a lock aperture **154** defined by the channel **108**. For example, when the insert **138** is fully inserted longitudinally into the channel **108**, the locking pin structure **152** may be positioned such that it extends through the lock aperture **154**, thereby enhancing longitudinal securement of the insert **138** within the channel **108**. Process **600** may then proceed to block **608**.

(32) At block **608**, process **600** may provide an access hole in the door assembly. For example, as described above, access hole **158** may be present in one or more of the door panels, and may be aligned and/or adjacent channel **108** to facilitate insertion/removal of an insert **138**.

(33) Proceeding to block **610**, process **600** may seal an access hole defined by the door panel with a removeable plug. For example, removeable plug **160** may be installed to access hole **158** after installation of the insert **138**. Process **600** may then terminate.

(34) Referring now to FIG. **6B**, an example process **601** for servicing an insert for a belt seal is illustrated and described in further detail. Process **601** may begin at block **612**, where an access hole is un-sealed or opened. For example, as discussed above, removable plug **160** may be removed from access hole **158**. Process **601** may then proceed to block **614**.

(35) At block **614**, process **601** may withdraw the insert from the channel. For example, as noted above, insert **138** may be longitudinally removed from the channel **108**. In examples where a locking pin structure **152** is present, the locking pin structure **152** may be dislodged from the lock aperture **154**. The insert **138** may be withdrawn from the channel **108**.

(36) Proceeding to block **616**, the removeable plug **160** may be serviced and/or replaced. To the extent an insert **138** is able to be serviced, it may be re-inserted into the channel **108**. To the extent the insert **138** is not capable of being fixed, a new insert **138** may instead be inserted into the channel **108**, and the old/damaged insert discarded. Process **601** may then proceed to block **618**.

(37) At block **618**, process **601** may seal the access hole. For example, the removeable plug **160** may be reinstalled to re-seal the door assembly **102**, thereby preventing ingress of water or other liquid, dirt, debris, etc. into an interior of the door assembly. Process **601** may then terminate.

(38) Referring now to FIG. **7**, an example vehicle **700** is schematically illustrated that includes multiple door assemblies. Vehicle **700** may incorporate door assembly **102a** of FIG. **1**, door assembly **102b** of FIG. **3**, and/or may be manufactured using process **600** of FIG. **6**, in accordance with some embodiments of the disclosure.

(39) Vehicle **700** includes a vehicle body **702**. Attached to vehicle body **702** are door assemblies **704a** and **704b** (collectively, **704**). In some embodiments, vehicle body **702** has additional door assemblies, e.g., positioned rearward of door assemblies **704a** and **704b**. Each of door assemblies

704a and **704b** may include respective exterior panels **706a** and **706b**, proximate to each of windows **710a** and **710b**, respectively. Further, the door assemblies **704a** and **704b** may have belt seals **708a** and **708b**, respectively. Each of door panel assemblies **704** may incorporate any/all of the features of the door assembly **102a** and/or door assembly **102b** described above. For example, each of the door panel assemblies **704a** and **704b** may have a belt seal structure incorporating in whole or in part window seals **104a** (e.g., as illustrated in FIG. 1) or **104b** (e.g., as illustrated in FIG. 3) as belt seals **708a** and **708b**, respectively.

(40) Example approaches herein may facilitate relatively easy installation. For example, the longitudinal installation and orientation of the channel **108** and insert **138** may facilitate reduction of parts (e.g., pins or other elements otherwise needed for positioning seals near windows). In one example, the elimination of pins from a seal facilitated an overall reduction in door width of approximately 7 millimeters. The longitudinal orientation of installation also facilitates relative reductions in cycle time in comparison to previous approaches, e.g., where disassembly of a door is required to install or replace a seal. To the extent the cross-section of the channel **108** and/or insert **138** is consistent, the channel **108** and insert **138** may be extruded or otherwise formed in relatively simple manufacturing operations. Example window seals **104** are also useful in a wide variety of different door architectures, e.g., frameless doors, framed doors, flush glazing, etc.

(41) The systems and processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the actions of the processes discussed herein may be omitted, modified, combined, and/or rearranged, and any additional actions may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be exemplary and not limiting. Only the claims that follow are meant to set bounds as to what the present disclosure includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted that the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

(42) While some portions of this disclosure may refer to “convention” or examples, any such reference is merely to provide context to the instant disclosure and does not form any admission as to what constitutes the state of the art.

Claims

1. A vehicle window seal, comprising: a channel extending along a longitudinal axis and having a cross section opened toward a moveable window, wherein the channel is fixed in a door assembly and wherein the channel is aligned with an access hole arranged at a longitudinal end of the door assembly; and an insert comprising: a base receivable through the access hole and into the channel along the longitudinal axis, wherein the insert is removable from the channel along the longitudinal axis and through the access hole; and a sealing lip extending laterally out of the channel to contact the moveable window.
2. The vehicle window seal of claim 1, wherein the base comprises at least one protrusion configured to contact one or more inner surfaces of the channel to retain the insert in the channel by creating friction between the at least one protrusion and the one or more inner surfaces.
3. The vehicle window seal of claim 2, wherein the at least one protrusion comprises a plurality of protrusions, each extending in a different direction from the base.
4. The vehicle window seal of claim 1, wherein the channel defines a c-shaped cross section.
5. The vehicle window seal of claim 1, wherein the channel defines opposing interior surfaces engaged by upper and lower protrusions of the base.

6. The vehicle window seal of claim 1, wherein the base defines a hollow cross section, the sealing lip defined by an arm extending away from the hollow cross section, wherein the base comprises one or more protrusions configured to contact one or more inner surfaces of the channel.
7. The vehicle window seal of claim 1, wherein the moveable window comprises glass, and wherein the sealing lip comprises a layer of wear resistant material that prevents marks from appearing on the glass.
8. The vehicle window seal of claim 1, wherein the base defines a locking pin structure configured to extend through a lock aperture defined by the channel.
9. The vehicle window seal of claim 8, wherein the locking pin structure extends laterally away from the moveable window.
10. The vehicle window seal of claim 8, wherein the locking pin structure is located longitudinally on the base such that the locking pin structure is received in the lock aperture when the base is fully inserted into the channel.
11. The vehicle window seal of claim 1, wherein the channel comprises a locator tab configured to limit insertion of the base into the channel along the longitudinal axis.
12. The vehicle window seal of claim 1, further comprising a door panel having an interior surface defining the channel.
13. A door assembly for a vehicle, comprising: an exterior door panel having a visible exterior surface extending toward a window opening for a moveable window, the exterior door panel having an interior surface; an access hole defined by the door assembly at a longitudinal end of the door assembly; and a window seal, comprising: a channel extending along a longitudinal axis and along the interior surface, the channel having a cross section opened toward the moveable window, wherein the channel is aligned with the access hole; and an insert comprising: a base receivable through the access hole and into the channel along the longitudinal axis, wherein the insert is removable from the channel along the longitudinal axis and through the access hole; and a sealing lip extending laterally out of the channel to contact the moveable window.
14. The door assembly of claim 13, further comprising a removeable plug configured to seal the access hole before or after the insert is received in the channel.
15. The door assembly of claim 13, wherein the base defines a locking pin structure configured to extend through a lock aperture defined by the channel; and wherein the channel comprises a locator tab configured to limit insertion of the base into the channel along the longitudinal axis.
16. The door assembly of claim 15, wherein the locking pin structure is integrally formed with the base, wherein the locking pin structure is located longitudinally on the base such that the locking pin structure is received in the lock aperture when the base is fully inserted into the channel.
17. A method of manufacturing a door assembly, the method comprising: positioning a channel, extending along a longitudinal axis, along an interior surface of a door panel such that the channel is fixed in the door assembly, wherein the channel comprises a cross section opened toward a moveable window, and wherein the channel is aligned with an access hole arranged at a longitudinal end of the door assembly; and inserting a base of an insert through the access hole and into the channel along the longitudinal axis, the insert comprising a sealing lip extending laterally out of the channel to contact the moveable window, wherein the insert is removable from the channel along the longitudinal axis through the access hole.
18. The method of claim 17, further comprising sealing the access hole with a removeable plug.
19. The method of claim 17, further comprising limiting insertion of the base of the insert into the channel along the longitudinal axis with a locator tab of the channel, wherein the base of the insert defines a locking pin structure configured to extend through a lock aperture defined by the channel when the insert is fully inserted into the channel along the longitudinal axis, wherein the locking pin structure is integrally formed with the base.
-