

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404923
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Quigley; Todd Cameron

Universal transfer case for right side or left side installation

Abstract

A universal transfer case for a vehicle having a casing with a primary drive axis and a secondary drive axis spaced apart and parallel to the primary axis. The casing includes a connector configured to permit coupling to a vehicle in a manner locating the secondary drive axis in one of a plurality of orientations in relation to the primary drive axis thereby allowing the transfer case to be used with front axle drives offset to the right or left of the primary powertrain axis. Interface connection locations may be provided in the casing which when machined allow openings in and/or connections to the casing to be optimally positioned based on the installation orientation.

Inventors:	Quigley; Todd Cameron (York, PA)
Applicant:	QUIGLEY MOTOR COMPANY, INC. (Manchester, PA)
Family ID:	92544804
Assignee:	Quigley Motor Company, Inc. (Manchester, PA)
Appl. No.:	18/591784
Filed:	February 29, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240294066 A1	Sep. 05, 2024

Related U.S. Application Data

us-provisional-application US 63488191 20230303

Publication Classification

Int. Cl.: **F16H57/037** (20120101); **B60B35/16** (20060101); **B60K17/16** (20060101); **B60K17/344** (20060101); **B62D65/10** (20060101); **F16H48/42** (20120101); **F16H57/021** (20120101); **F16H57/02** (20120101)

U.S. Cl.:

CPC **F16H57/037** (20130101); **B60B35/16** (20130101); **B60K17/165** (20130101); **B60K17/344** (20130101); **B62D65/10** (20130101); **F16H48/42** (20130101); **F16H57/021** (20130101); **B60B2320/10** (20130101); **B60B2900/116** (20130101); **B60B2900/351** (20130101); **F16H2057/02052** (20130101)

Field of Classification Search

CPC: **F16H** (57/037); **F16H** (57/021); **F16H** (48/42); **F16H** (2057/02052); **B60B** (35/16); **B60B** (2320/10); **B60B** (2900/116); **B60B** (2900/351); **B60K** (17/165); **B60K** (17/344); **B62D** (65/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3145582	12/1963	Wagner	74/606R	F16H 57/027
4020715	12/1976	Sollars	74/606R	F16H 57/031
4641547	12/1986	Stich	74/606R	F16H 57/025
4744436	12/1987	Uchiyama	464/178	B60K 17/34
5116293	12/1991	Reuter	475/222	F16D 3/223
6155126	12/1999	Vogt	74/335	F16H 61/32
10415687	12/2018	Hemry	N/A	G01M 13/021
2015/0159751	12/2014	Pritchard	29/893.1	B60K 23/0808

OTHER PUBLICATIONS

Amazon listing, NP261XHD transfer case, Date first available Feb. 28, 2019 (Year: 2019). cited by examiner

Primary Examiner: Diaz; Thomas C

Attorney, Agent or Firm: Saxton & Stump, LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application claims priority benefit to provisional patent application No. 63/488,191 filed on Mar. 3, 2023, the entirety of which is incorporated by reference herein.

FIELD OF THE INVENTION

(1) The present disclosure relates generally to vehicular drivetrains and, more particularly, to a transfer case for four-wheel drive vehicles adaptable for multiple driveline arrangements.

BACKGROUND OF THE INVENTION

(2) Four-wheel drive systems for vehicles in which power trains are longitudinally arranged

generally requires that the drive shaft for one of the axles be laterally offset from the main engine/driveline axis. Drive lines for the front axles are most commonly laterally offset allowing the rear axle driveline to be arranged on the vehicle's longitudinal centerline and in line with the powertrain centerline. Front driveline offset is typically accomplished in a transfer case which offsets the front drive shaft take-off and provides a rear drive shaft take-off aligned on the main power drive line.

(3) Drivetrain components in high-volume production runs (e.g., OEM applications) may be designed from the outset for a specific drive side configuration. Such OEM designs warrant drivetrain components specifically designed for right-side or left-side front axle drive shaft locations. Demands for continual improvements in production efficiency as well as after-market applications, make apparent the need to greater installation flexibility and adaptability, especially as more vehicle manufacturers turn to second-tier suppliers for components, including transmissions, axles, and other drivetrain components.

(4) Such adaptability in drivetrain components does not currently exist in the automotive industry. Transfer cases and axles for longitudinal driveline four-wheel drive systems are specifically designed to laterally offset front axle drive shafts on only one side. Therefore, it would be desirable to have a universal powertrain component, such as the transfer case and/or axle, that can be easily adapted for use in a vehicle regardless of the required front driveline offset. Other features and advantages will be made apparent from the present specification. The teachings disclosed extend to those embodiments that fall within the scope of the claims, regardless of whether they accomplish one or more of the aforementioned needs.

SUMMARY OF THE INVENTION

(5) The concept and physical design of a universal drive train component, whether a transfer case or axle, will lend itself to a more streamlined timeframe during the engineering and design process. It also lends to a more efficient manufacturing process as well as reducing expenses and the amount of time from concept to market.

(6) In an embodiment, a universal transfer case includes a casing, a primary driveline axis, a secondary driveline axis parallel to and spaced apart from the primary axis, and a connector for coupling the casing to a vehicle and aligning the secondary axis in one of a plurality of orientations relative to the primary axis. The plurality of orientations allows the secondary driveline to be positioned in at least to the vehicle left of the primary driveline axis and to the vehicle right of the primary drive line axis.

(7) In an embodiment, a universal transfer case includes casing with a mechanical connector, the connector having a plurality of connectors arranged symmetrically about a primary driveline axis to couple the transfer case to the vehicle. The connectors are regularly positioned in a manner allowing the casing to be rotationally clocked about the primary driveline axis. The connector arrangement allows the secondary driveline to be positioned to the vehicle left or vehicle right of the primary driveline axis as well as vertically below or above the primary drive line axis. Secondary driveline axis locations that are laterally offset to the right or left of the primary driveline axis and vertically offset below the primary driveline axis are preferred.

(8) In an embodiment, a universal transfer case includes a casing having a plurality of interface locations positioned on the casing. One or more of the interface locations may be made functional by a machining operation, the specific location being selected based upon the orientation of the transfer case in the vehicle. Interface location functionality may include a machining operation to create an opening in the casing wall or a threaded blind hole to allow connection of an externally mounted component in the location best suited for the installed transfer case orientation.

(9) In an embodiment, a method of installing a universal transfer case into a vehicle includes identifying a first drive axis in relation to the first axle, identifying a second drive axis in relation to the second axle and determining an offset of the second drive axis from the first drive axis. A universal drivetrain component having a casing, a primary drive axis, a secondary drive axis, and a

connector for coupling the casing to the vehicle to position the secondary drive axis in one of a plurality of orientations in relation to the primary drive axis is provided. The universal drivetrain component is oriented to position the secondary drive axis proximate to the second drive axis and then connected to the vehicle.

(10) In an embodiment, a method of installing a universal transfer case into a vehicle includes providing a plurality of interface locations on the casing, identifying the interface location(s) best positioned based on the planned installed orientation of the transfer case in the vehicle, and making the selected interface location(s) made functional by a machining operation. Interface location functionality may include a machining operation to create an opening in the casing wall or a threaded blind hole to allow connection of an externally mounted component in the location best suited for the installed transfer case orientation.

(11) Other features and advantages of the present invention will be apparent from the following more detailed description of the preferred embodiment, taken in conjunction with the accompanying drawings which illustrate, by way of example, the principles of the invention.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) The advantages of this invention will be apparent upon consideration of the following detailed disclosure of the invention, especially when taken in conjunction with the accompanying drawings wherein:
- (2) FIG. 1 illustrates a drivetrain layout in a four-wheel drive vehicle in which the front driveline is offset to the right;
- (3) FIG. 2 illustrates a drivetrain layout in a four-wheel drive vehicle in which the front driveline is offset to the left;
- (4) FIG. 3 is a side elevation illustration of a drivetrain layout in a four-wheel drive vehicle;
- (5) FIG. 4 is a plan view of a universal transfer case oriented for use in right-side offset front driveline;
- (6) FIG. 5 is a plan view of the universal transfer case re-oriented for use in a left-side offset front driveline;
- (7) FIG. 6 is an elevation view of the universal transfer case illustrated in FIG. 4;
- (8) FIG. 7 is a front perspective view of a universal transfer case; and
- (9) FIG. 8 is a second perspective view of the universal transfer case of FIG. 7.
- (10) Wherever possible, the same reference numbers will be used throughout the drawings to represent the same parts.

DETAILED DESCRIPTION OF THE INVENTION

(11) Transfer cases and axles are either a left-side installation or a right-side installation, based off the centerline of an Original Equipment (OE) manufacturer's powertrain centerline. Transfer cases and axles according to the present disclosure have a design that may be mounted or installed on either side of the OE's powertrain centerline. In one embodiment, both a transfer case and an axle having the universal configuration are configured to permit the installation on an OE's powertrain. To provide the universal configuration, the component should have a raw casting configured to permit multiple unique connection features to be machined while still maintaining the correct alignment of the connection features with the other drivetrain components. The casing interior must be configured to assure proper distribution of lubrication to internal rotation components regardless of the installed orientation. Once the castings are engineered to be universal in nature, the second phase is to engineer the machining of the casting to adapt it to one of a plurality of installation orientations. The machining step transforms the universal casting into one specific to a right-side or a left-side driveline installation.

(12) The transfer case and the axle, whether they are machined for a left-side or right-side installation, still have the same internal components. The final transfer case and axle products are universal in relation to how they can be installed/mounted simply based on how the raw casting is achieved. This flexibility allows the transfer case to be easily configured for a left-side or right-side installation/mounting.

(13) Referring to FIGS. **1** through **3**, diagrams of traditional drivetrain layouts illustrate laterally offset front drive mechanism. There is shown a powertrain **10** longitudinally oriented in a vehicle and defining a primary axis **100**. A transmission **20** is coupled to the powertrain **10** and a transfer case assembly **30** is coupled to the transmission via mechanical adapter connector **25**. The transfer case assembly **30** splits drive torque from the transmission **20** between a rear drive axle **22** and a front drive axle **26**. Drive torque is delivered to the rear axle **22** through rear driveshaft **24**; drive torque is delivered to the front axle **26** through front driveshaft **28**. The preferred alignment of the transmission and transfer case input is in line with the powertrain axis, primary axis **100** as illustrated. Spatial demands for locating the front driveshaft requires offsetting the front driveshaft from the primary axis to a secondary axis **110**. Normal limitations on vehicle ground clearance and space available for the drivetrain dictate that the offset be primarily lateral, though some vertical drop may also be desirable to reduce front driveshaft angle.

(14) Front axles may be solid axles in which a unitary structure laterally spans between the front wheels. The outboard ends of the axle include connections to allow the front wheels to be steered, but the axle assembly is a structural beam spanning between the wheels and the vehicle in turn is supported on the axle. Front axles may also be adapted for use with independent suspensions in which the front axle structure is separated vehicle suspension. A portion of the front drive axle **26** is attached to the vehicle and axle shafts **27**, sometimes referred to as half-shafts, extend between the axle structure to wheel hubs. The half-shafts **27** include flexible joints **29** to allow the axle shafts to deflect from the drive axis established by the differential. The flexible joints **29** also allow the front wheels to be steered. The flexible joints **29** may be universal joints, constant-velocity joints, or other functionally equivalent mechanism enabling deflection of the half shaft from the drive axis.

(15) The terms all-wheel drive and four-wheel drive describe power transmission systems for vehicles. All-wheel drive generally describes systems in which power is directed to drive wheels at all times while four-wheel drive systems normally provide power to the drive wheels on typically the rear axle(s), and power all drive wheels, including a front axle, only when selected. Four-wheel drive systems also commonly include reduction gears to provide additional low speed gearing options for the vehicle. The present invention is primarily directed toward four-wheel drive systems but offers utility in all-wheel drive systems as well. Accordingly, the terms all-wheel drive and four-wheel drive are used synonymously herein to describe a transmission system for delivering power to more than one drive axle simultaneously.

(16) Referring to FIG. **4** through **8**, an embodiment of a universal powertrain component, specifically a transfer case assembly **30**, is illustrated. Universal transfer case assembly **30** comprises a front housing **31**, a rear housing **32**, and a tail shaft housing **33**. The tail shaft housing **33** may be integral with the rear housing **32** in some transfer case designs. The housings are joined by conventional means to create an internal space in which is located necessary gears and power take-off components to direct torque to the front and rear axles. Interfaces between the mating housing portions may include sealing means to contain lubricant for the drive components and to isolate the internals from external contamination. Separating the housing parts provides easy access to the transfer case interior for assembly or maintenance.

(17) The connection **40** between the transfer case and the transmission is a mechanical adapter connector **25** structurally joining the transfer case to the transmission. The transfer case may be entirely supported by the connection to the transmission or a support connection between the vehicle and the mechanical adapter connector may be provided. The adapter connector **25** facilitates the drivetrain connection replacing the tail shaft structure typically transitioning the

transmission to a drive shaft powering a rear axle. The transfer case connection to the transmission or adapter is traditionally accomplished by a flanged connection. A flange structure **42** is configured to matingly interface with a matching flange provided on the transmission or the mechanical connector adapter **25** and may incorporate a combination of threaded fasteners **44** simultaneously engaging the respective flange structures. Threaded studs may be provided on one flange and a plurality of holes provided on the opposing flange through which the studs extend. Threaded openings may be provided and engaged by threaded capscrews to clamp the flanges together. The spacing and arrangement of the fasteners may be established by the transmission manufacturer. The connection configuration may vary between different transmission manufacturers and even among different transmission models from the same manufacturer.

(18) In an embodiment, a plurality of fasteners **44** is radially disposed about the primary axis **100**. The plurality of fasteners may be symmetrically arranged about the primary axis **100** and regularly spaced. A regular, symmetric arrangement permits the transfer case to be rotationally “clocked” to vary the location of the secondary axis in relation to the primary axis. In the illustrated embodiment, the range of clocking enables the secondary axis to be positioned laterally to the left or right of the primary axis. Additional clocking alignments may allow the position of the secondary axis to be vertically as well as laterally offset in relation to the primary axis (drive centerline).

(19) The housings may include access port locations, such as oil fill port locations **34a**, **34b** and oil drain port locations **35a**, **35b**, which may be selectively machined to provide an opening into the housing interior, such as to allow the addition or removal of lubricant from the transfer case. Access port locations may be made functional by a machining operation, such as drilling and tapping an opening through the housing, in the location best suited for the installed transfer case orientation. In the embodiment illustrated in FIG. **8**, oil fill port **34a** and oil drain port **35a** have been machined for use while port locations **34b** and **35b** remain unmachined. The alternate locations may remain unmachined (non-functional) to reduce the number of openings in the housing. A machined, functional access port may then be sealed with a threaded plug to contain lubricant within the housing. The selection of the access port location may be made dependent upon the planned installed orientation of the transfer case. In this way the access ports may be ideally positioned, and the alternative locations remain unmachined to reduce the number of openings in the housing.

(20) The housing may include interface locations **37a**, **37b** to allow installation of sensors in the transfer case and provide a vent penetration into the casing. Interface locations **37a**, **37b** may be made functional by a machining operation to the housing. The functional interface location may be adapted to receive the required interface component, such as a sensor conductor and a vent. The alternate location may remain unmachined (non-functional) to reduce the required machining of the housing.

(21) The transfer case housings **31**, **32** may incorporate additional mounting locations **38**, **39** for connecting other external components or appurtenances to the transfer case. Additional mounting locations may be provided in the casing castings and remain unmachined if a particular mounting location is not required for the planned installation. The additional mounting locations may also be arranged on the casing to provide potential mounting locations dependent upon the installed orientation of the transfer case.

(22) The transfer case may include an actuator interface **50** to enable a user to select different operational modes of the transfer case. It is common for transfer cases to include provisions to selectively connect or disconnect the front axle driveline from the primary drive (commonly referred to as selecting two-wheel drive or four-wheel drive). Many transfer cases include a planetary reduction gearset allowing for lower speed, higher torque multiplication operation. Selection means may be provided to allow a user to select whether to engage or disengage the front driveline and to select between high (normal) range operation and low range operation. The

actuator may rely on electrical servos to operate the transfer case. The actuator may be by a manually operated shift lever connected by a linkage to the transfer case. The transfer case includes an actuator interface connection 50 to connect external actuator means to the internal mechanisms effecting changes in operational modes. The location of the interface connection 50 on the transfer case exterior and the relative position to internal components defines a preferred location on the housing. Provisions for alternate may be provided, but the preferred approach is to provide a linkage between a transfer case shift lever located in the vehicle and the interface connection wherever it is positioned in the installation.

(23) While the exemplary embodiments illustrated in the figures and described herein are presently preferred, it should be understood that these embodiments are offered by way of example only. Accordingly, the present application is not limited to a particular embodiment but extends to various modifications that nevertheless fall within the scope of the appended claims. The order or sequence of any processes or method steps may be varied or re-sequenced according to alternative embodiments.

(24) It is important to note that the construction and arrangement of the various exemplary embodiments is illustrative only. Although only a few embodiments have been described in detail in this disclosure, those skilled in the art who review this disclosure will readily appreciate that many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.) without materially departing from the novel teachings and advantages of the subject matter recited in the claims. For example, elements shown as integrally formed may be constructed of multiple parts or elements, the position of elements may be reversed or otherwise varied, and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present application. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. In the claims, any means-plus-function clause is intended to cover the structures described herein as performing the recited function and not only structural equivalents but also equivalent structures. Other substitutions, modifications, changes and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present application.

Claims

1. A method of installing a universal drivetrain component into a vehicle drivetrain powering a first axle and a second axle comprising the steps of: identifying a first drive axis in relation to the first axle; identifying a second drive axis in relation to the second axle; determining an orientation of an offset of the second drive axis in relation to the first drive axis for the vehicle; providing a universal drivetrain component having a casing, a primary drive axis, a secondary drive axis, and a connector for coupling the casing to the vehicle; providing a first interface location positioned on the casing for function in the first orientation of the powertrain component; providing a second interface location being positioned on the casing for function in the second orientation of the powertrain component; performing a machining operation to make functional the first interface location or the second interface location dependent upon the determined offset of the second drive axis from the first drive axis for the vehicle; to position the secondary drive axis in one of a the first orientation or the second orientation in relation to the primary drive axis; orienting the universal drivetrain component to position the secondary drive axis proximate to the second drive axis; and connecting the universal drivetrain component to the vehicle.
2. The method of claim 1, further comprising the steps of: selecting the first or the second interface location to be made functional dependent upon the orientation of the universal drivetrain component.

3. The method of claim 2, wherein the machining operation includes creating an opening in the casing.

4. The method of claim 3, wherein a function of the first interface location is an oil fill port when in the first orientation, and a function of the second interface location is an oil fill port when in the second orientation.

5. The method of claim 3, wherein a function of the first interface location is an oil drain port when in the first orientation, and a function of the second interface location is an oil fill port when in the second orientation.
