

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404998
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Martin; Alexander et al.

Shaped part

Abstract

The invention relates to a shaped part comprising a translucent decorative layer with a front side designed as a visible side and a back side opposite the front side, a functional layer arranged on the back side of the decorative layer, and a carrier arranged on a back side of the shaped part. The invention is characterized in that a functional structure is arranged on or in the functional layer and/or on the back side of the decorative layer, wherein the functional structure is, on the one hand, electrically conductive and, on the other, light-conducting for realizing an illumination function of the shaped part.

Inventors: Martin; Alexander (Neuhaus an der Pegnitz, DE), Weih; Philipp (Haag, DE), Neuner; Tobias (Buttenheim, DE), Roetzer; Ilka (Kastl, DE)

Applicant: Novem Car Interior Design GmbH (Vorbach, DE)

Family ID: 92933732

Assignee: Novem Car Interior Design GmbH (N/A, DE)

Appl. No.: 18/635302

Filed: April 15, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240369215 A1	Nov. 07, 2024

Foreign Application Priority Data

DE	102023109746.6	Apr. 18, 2023
----	----------------	---------------

Publication Classification

Int. Cl.: F21V23/06 (20060101); B60Q3/20 (20170101); F21W106/00 (20180101); F21Y113/00 (20160101); F21Y115/10 (20160101)

U.S. Cl.:

CPC F21V23/06 (20130101); B60Q3/20 (20170201); F21W2106/00 (20180101); F21Y2113/00 (20130101); F21Y2115/10 (20160801)

Field of Classification Search

CPC: B60Q (3/20); F21V (23/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0391475	12/2019	Weih	N/A	B60Q 3/14
2024/0004120	12/2023	Keranen et al.	N/A	G02B 6/0055
2024/0148094	12/2023	Chiu	N/A	F21V 23/06
2024/0316899	12/2023	Martin	N/A	B60R 13/02
2024/0332875	12/2023	Itschner	N/A	H01R 24/005

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102022201354	12/2022	DE	N/A
3150442	12/2016	EP	B60R 13/02
3575153	12/2018	EP	N/A
3326863	12/2020	EP	N/A

Primary Examiner: Dunay; Christopher E

Attorney, Agent or Firm: Workman Nydegger

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present invention claims priority to German Application 102023109746.6, filed on Apr. 18, 2023. The entire content of each of the aforementioned patent applications is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention
- (2) The invention relates to a shaped part, in particular a decorative part (also: body trim part) and/or panel part designed as a shaped part for a vehicle interior.
2. The Relevant Technology
- (3) Numerous decorative and panel parts are installed in the vehicle interior—for example, door panels, console panels, and instrument panels. The decorative and panel parts also include control buttons and their covers.
- (4) The requirements for such shaped parts are continuously increasing; in particular, there is a

need for shaped parts with which many optical light effects can be realized on the visible side.

BRIEF SUMMARY OF THE INVENTION

(5) The object of the invention is to provide a new shaped part, in particular a shaped part that enables a light design on the visible side of the shaped part.

(6) This object is achieved by a shaped part having the features of claim 1. Advantageous embodiments and further developments are provided in the dependent claims.

(7) The shaped part according to the invention comprises a translucent decorative layer with a front side designed as a visible side and a back side opposite the front side, a functional layer arranged on the back side of the decorative layer, and a carrier arranged on a back side of the shaped part.

(8) The invention is characterized in that a functional structure is arranged on or in the functional layer and/or on the back side of the decorative layer, wherein the functional structure is designed to be, on the one hand, electrically conductive and, on the other, light-conducting for realizing an illumination function of the shaped part. Thus, the functional structure is both electrically conductive and light-conducting for realizing an illumination function of the shaped part. Thus, the functional structure realizes both functions.

(9) The advantages of the invention lie in particular in the fact that the functional structure fulfills not just a single function, but can be used both as a light guide and as an electrical contact. In this way, additional components and/or production steps can be avoided, which results in more cost-effective solutions. Another advantage is the narrow structure of the shaped part.

(10) It can be provided that the functional structure be formed by conductive tracks, in particular from light-conducting wires. Alternatively, it can be provided that the functional structure be formed by a paste, in particular an electrically conductive and light-conducting paste, and/or a lacquer, in particular an electrically conductive and light-conducting lacquer, and/or a paint, in particular an electrically conductive and light-conducting paint. The paste and/or the lacquer and/or the paint can be made electrically conductive using additives.

(11) The functional structure can also be made at least temporarily self-illuminating, e.g., by adding additives and/or luminescent, in particular fluorescent and/or phosphorescent admixtures. In this context, temporarily is understood in particular to mean that the functional structure is only self-illuminating when activated accordingly, e.g., electrically or optically, e.g., by irradiated visible or non-visible light, and/or following a corresponding activation. In the case of fluorescent admixtures, incident light leads directly to light emission by the admixtures. In the case of phosphorescent admixtures, the energy radiated by the light is at least partially stored by the admixtures and gradually released, even if the incident light has already been switched off again. Thus, the functional structure continues to light up, at least for a certain time, even after the incident light has been switched off.

(12) According to one embodiment variant of the invention, the functional structure forms an intended pattern or symbol, in particular in a top view on the visible side of the shaped part. The symbol can, for example, be one or more functional symbols and/or geometries and/or shapes and/or emblems and/or one or more letters and/or lettering and/or characters and/or logos and, in the case of decorations, for example, lines, in particular lines following a shape, and/or other design elements, which are shown on the visible side of the decorative layer of the shaped part.

(13) The functional structure can be applied to the front side or back side of the functional layer, or to the back of the decorative layer. Furthermore, it can be provided that the functional structure be incorporated into the functional layer, in particular by applying the functional structure to the respective inner front side or back side of a sub-layer of the functional layer.

(14) Furthermore, it can be provided that a layer of flexible material, e.g., of fabric or woven fabric, adjoin the layer to which the functional structure is applied, e.g., the functional layer or the decorative layer, wherein the functional structure presses through the flexible material or presses into it, so that, in particular, a 3-D look is created if the functional structure is self-illuminating.

(15) The functional structure can, for example, be applied to the functional layer or sub-layers of

the functional layer or the decorative layer by means of a printing process, such as screen printing or digital printing, and/or by means of a spraying process.

(16) According to a further development of the invention, the shaped part comprises one or more electrical components, wherein the functional structure is provided for connecting the electrical components to an energy source. The energy source can be provided on or in the shaped part. However, it is preferably an external energy source.

(17) The one or more electrical components can be or comprise illumination units, e.g., LED's, and/or heating units and/or sensor units and/or haptic units, in particular for outputting a haptic signal when touched, and/or acoustic units, in particular loudspeakers.

(18) The functional layer is preferably designed to be transparent or translucent. The functional layer can, for example, be a light pane or a diffusing pane (or light-diffusing pane) or a flat light guide or a functional film. The functional layer can be made of a plastic, for example.

(19) Furthermore, it can be provided that the functional layer have a multilayer structure, wherein the functional layer has at least two sub-layers, wherein the functional structure is arranged at an interface between the two sub-layers. Furthermore, the electrical components are preferably arranged at the interface between the two sub-layers.

(20) According to one embodiment variant of the invention, a light-shielding layer, in particular a light-shielding lacquer layer or a mask, is arranged at least in sections on the back side of the functional layer.

(21) Preferably, the shaped part comprises a light source for coupling light into the functional structure, in particular on the back side of the carrier or on the side of the shaped part.

(22) It can be provided that a reflective layer be arranged on the front side of the carrier, wherein the reflective layer preferably reflects light, emanating from the functional structure and/or the electrical components designed as illumination units, in the direction of the visible side of the shaped part.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The invention is explained in more detail below also with regard to further features and advantages on the basis of the description of exemplary embodiments and with reference to the accompanying schematic drawings. Shown are:

(2) FIG. 1 shows a section of a first shaped part according to the invention, designed as a decorative and/or panel part for the vehicle interior, in a schematic sectional view;

(3) FIG. 2 shows a section of a second shaped part according to the invention, designed as a decorative and/or panel part for the vehicle interior, in a schematic sectional view;

(4) FIG. 3 shows a section of a third shaped part according to the invention, designed as a decorative and/or panel part for the vehicle interior, in a schematic sectional view;

(5) FIG. 4 shows a section of a fourth shaped part according to the invention, designed as a decorative and/or panel part for the vehicle interior, in a schematic sectional view.

(6) FIG. 1 to FIG. 4 in each case shows a shaped part **10**, which comprises a translucent decorative layer **11** with a front side **12** designed as a visible side and a back side **13** opposite the front side **12**, a functional layer **15** arranged on the back side **13** of the decorative layer **11**, and a carrier **14** arranged on a back side **22** of the shaped part.

DETAILED DESCRIPTION

(7) According to the exemplary embodiment according to FIG. 1, a functional structure **17** is arranged on a back side **19** of the functional layer **15**, wherein the functional structure **17** is, on the one hand, electrically conductive and, on the other, light-conducting for realizing an illumination function of the shaped part **10**. The functional structure **17** can be formed by conductive tracks

made of light-conducting wires or by an electrically conductive and light-conducting paste and/or an electrically conductive and light-conducting lacquer and/or an electrically conductive and light-conducting paint. The functional structure **17** is also at least temporarily self-illuminating, e.g., by the addition of additives or luminescent, in particular fluorescent and/or phosphorescent, admixtures. The functional structure **17** is applied to the back side **19** of the functional layer **15** by means of a printing process, e.g., screen printing or digital printing, or by means of a spraying process. In a top view of the visible side of the shaped part **10**, the functional structure **17** forms a symbol **21**, as shown by way of example in FIG. 4.

(8) The functional layer **15** is designed to be transparent or translucent. A light-shielding lacquer layer **20** is arranged on the back side **19** of the functional layer **15**.

(9) The shaped part **10** further comprises a light source **23** on the side of the shaped part **10**, wherein light emanating from the light source **23** is coupled into the functional structure **17**—for example, in such a way that the functional structure **17** itself lights up.

(10) According to the exemplary embodiment according to FIG. 2, the functional structure **17** is arranged on the back side **13** of the decorative layer **11**, wherein the functional structure **17** is, on the one hand, electrically conductive and, on the other, light-conducting for realizing an illumination function of the shaped part **10**. The functional structure **17** can be formed by conductive tracks made of light-conducting wires or by an electrically conductive and light-conducting paste and/or an electrically conductive and light-conducting lacquer and/or an electrically conductive and light-conducting paint. The functional structure **17** can also be made self-illuminating, at least temporarily—for example by adding additives or fluorescent admixtures. The functional structure **17** is applied to the back side **13** of the decorative layer **11** by means of a printing process, e.g., screen printing or digital printing, or by means of a spraying process.

(11) The shaped part **10** according to the exemplary embodiment according to FIG. 2 also comprises several electrical components **16**, wherein the functional structure **17** is provided for connecting the electrical components **16** to an energy source. The energy source can be arranged on or in the shaped part **10**, but is preferably an external energy source. The electrical components **16** are also arranged on the back side **13** of the decorative layer **11** and are at least partially embedded in the functional layer **15**. The electrical components **16** according to the exemplary embodiment according to FIG. 2 are illumination units, preferably LED's. However, the electrical components **16** can also be heating units, sensor units, haptic units for emitting a haptic signal when touched, or acoustic units such as loudspeakers.

(12) The functional layer **15** is designed to be transparent or translucent. A reflective layer **25** is arranged on a front side **24** of the carrier **14**, wherein the reflective layer **25** reflects light, emanating from the functional structure **17** and/or the electrical components **16** designed as illumination units, in the direction of the visible side of the shaped part **10**.

(13) According to the exemplary embodiment according to FIG. 3, the functional structure **17** is arranged in the functional layer **15**, wherein the functional structure **17** is, on the one hand, electrically conductive and, on the other, light-conducting for realizing an illumination function of the shaped part **10**. The functional structure **17** can be formed by conductive tracks made of light-conducting wires or by an electrically conductive and light-conducting paste. The functional structure **17** can also be made at least temporarily self-illuminating, e.g., by adding additives or luminescent, in particular fluorescent and/or phosphorescent admixtures.

(14) The functional layer **15** is designed to be transparent or translucent, on the one hand, and has a multilayer structure, on the other, wherein the functional layer **15** has two sub-layers **15a**, **15b**, wherein the functional structure **17** is arranged at an interface **18** between the two sub-layers **15a**, **15b**. The functional structure **17** is incorporated into the functional layer **15** by applying the functional structure **17** to the respective inner front side or back side of a sub-layer **15a**, **15b** of the functional layer **15** before the second sub-layer **15a**, **15b** is added. The functional structure **17** can be applied to the respective sub-layer **15a**, **15b** by means of a printing process—for example,

screen printing or digital printing.

(15) The shaped part **10** according to the exemplary embodiment according to FIG. 3 further comprises several electrical components **16**, wherein the functional structure **17** is provided for connecting the electrical components **16** to an energy source. The electrical components **16** are arranged at the interface **18** between the two sub-layers **15a**, **15b** of the functional layer **15** and are thus also embedded in the functional layer **15**. The electrical components **16** according to the exemplary embodiment according to FIG. 2 are illumination units, preferably LED's.

(16) A reflective layer **25** is arranged on the front side **24** of the carrier **14**, wherein the reflective layer **25** reflects light, emanating from the functional structure **17** and the electrical components **16**, which are designed as illumination units, in the direction of the visible side of the shaped part **10**.

(17) FIG. 4 shows a top view of a section of a shaped part **10** designed as a decorative and/or panel part for the vehicle interior. In a top view of the visible side of the shaped part **10**, the functional structure **17** forms a symbol **21**. FIG. 4 shows an exemplary symbol **21**. The symbol **21** can, for example, be one or more functional symbols and/or geometries and/or shapes and/or one or more letters and/or lettering and/or characters and, in the case of decorations, e.g., lines, in particular lines following a shape, and/or other design elements, which are shown on the visible side of the decorative layer **11** of the shaped part **10**.

LIST OF REFERENCE SIGNS

(18) **10** Shaped part **11** Decorative layer **12** Front side **13** Back side **14** Carrier **15** Functional layer **15a** Sub-layer **15b** Sub-layer **16** Electrical component **17** Functional structure **18** Interface **19** Back side (functional layer) **20** Light-shielding layer **21** Symbol **22** Back side (shaped part) **23** Light source **24** Front side (carrier) **25** Reflective layer

Claims

1. Shaped part, comprising a translucent decorative layer with a front side designed as a visible side and a back side opposite the front side, a functional layer arranged on the back side of the decorative layer, wherein the functional layer comprises a transparent or translucent layer, and a carrier arranged on a back side of the shaped part, wherein: a functional structure is arranged on or in the functional layer and/or on the back side of the decorative layer, wherein the functional structure is electrically conductive and at the same time light-conducting for realizing an illumination function of the shaped part; wherein: the shaped part comprises one or more electrical components, wherein the functional structure is configured for connecting the electrical components to an energy source, the shaped part comprises a light source for coupling light into the functional structure, and the functional structure is formed by one or more of a paste, a lacquer, or a paint.

2. Shaped part according to claim 1, wherein: the functional structure is formed by conductive tracks, or that the functional structure is formed by a paste and/or a lacquer and/or a paint.

3. Shaped part according to claim 1, wherein: the functional structure is at least temporarily self-illuminating.

4. Shaped part according to claim 3, wherein: the functional structure is self-illuminating, at least temporarily, by adding additives and/or luminescent admixtures.

5. Shaped part according to claim 1, wherein: the functional structure forms an intended pattern or symbol.

6. Shaped part according to claim 1, wherein: the functional structure is applied to the back side of the decorative layer.

7. Shaped part according to claim 1, wherein: the functional structure is applied to the functional layer or the decorative layer by means of a printing process and/or by means of a spraying process.

8. Shaped part according to claim 1, wherein: the shaped part comprises one or more electrical components, wherein the functional structure is provided for connecting the electrical components

to an energy source.

9. Shaped part according to claim 8, wherein: the one or more electrical components are or comprise illumination units and/or heating units and/or sensor units and/or haptic units and/or acoustic units.

10. Shaped part according to claim 1, wherein: the functional layer is designed to be transparent or translucent.

11. Shaped part according to claim 1, wherein: a light-shielding layer is arranged at least in sections on a back side of the functional layer.

12. Shaped part according to claim 1, wherein: a reflective layer is arranged on a front side of the carrier.
