

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406163
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	DiTullio; Jeff et al.

QR remote control

Abstract

Systems and methods are disclosed for implementing a virtual remote control for a streaming content device based on a QR code associated with the streaming device. In certain embodiments, a method may comprise implementing a virtual remote control for a streaming device, including providing an interface for the virtual remote control to a user device over a network, receiving an input to the virtual remote control from the user device over the network, and adjusting a setting of the streaming device over the network based on the input.

Inventors: DiTullio; Jeff (Austin, TX), Durbuzovic; Alen (Austin, TX), Hays; Brent (Austin, TX)

Applicant: Atmosphere.tv (Austin, TX)

Family ID: 93016640

Assignee: tmosphere.tv (Austin, TX)

Appl. No.: 18/299370

Filed: April 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240346274 A1	Oct. 17, 2024

Publication Classification

Int. Cl.: G06K19/06 (20060101); G08C17/02 (20060101)

U.S. Cl.:

CPC G06K19/06037 (20130101); G08C17/02 (20130101); G08C2201/30 (20130101);

Field of Classification Search**CPC:** G06K (19/06037); G08C (17/02)**USPC:** 235/494**References Cited****U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9898175	12/2017	Fiedler	N/A	N/A
11244561	12/2021	Fuchs	N/A	H04W 12/68
11678002	12/2022	Koopmans	725/38	H04N 21/42226
2010/0153576	12/2009	Wohlert et al.	N/A	N/A
2013/0082827	12/2012	Cho et al.	N/A	N/A
2018/0176113	12/2017	Thota	N/A	N/A
2020/0186857	12/2019	Easley	N/A	H04N 21/25816
2022/0095006	12/2021	Seed	N/A	H04N 21/4788
2022/0311857	12/2021	Sweeney	N/A	H04M 1/72436
2023/0059126	12/2022	Arling	N/A	H04W 12/068
2023/0298089	12/2022	Peterson	705/27.1	G06Q 30/0641

Primary Examiner: Kim; Ahshik**Background/Summary****SUMMARY**

- (1) In certain embodiments, a method may comprise implementing a virtual remote control for a streaming device, including providing an interface for the virtual remote control to a user device over a network, receiving an input to the virtual remote control from the user device over the network, and adjusting a setting of the streaming device over the network based on the input.
- (2) In certain embodiments, a system may comprise a streaming service configured to implement a virtual remote control for a streaming device at a user device, the streaming service physically remote from the user device and the streaming device. The streaming service may provide an interface for the virtual remote control to a user device over a network, receive an input to the virtual remote control from the user device over the network, and adjust a setting of the streaming device over the network based on the input.
- (3) In certain embodiments, a memory device may store instructions that, when executed, cause a processor to perform a method comprising implementing, via a streaming service physically remote from a user device and a streaming device, a virtual remote control for the streaming device at the user device. The streaming service may be configured for generating a quick response (QR) code associated with the streaming device, receiving metadata associated with the QR code from a user device over a network, in response to receiving the metadata, providing an interface for the virtual remote control to the user device over the network, receiving an input to the virtual remote control

from the user device over the network, and adjusting a setting of the streaming device over the network based on the input.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram of a system configured to implement a QR (quick response) remote control, in accordance with certain embodiments of the present disclosure;
- (2) FIG. 2 is a diagram of a system configured to implement a QR remote control, in accordance with certain embodiments of the present disclosure;
- (3) FIG. 3 depicts a flowchart of an example method for implementing a QR remote control, in accordance with certain embodiments of the present disclosure; and
- (4) FIG. 4 is a diagram of a system configured to implement a QR remote control, in accordance with certain embodiments of the present disclosure.

DETAILED DESCRIPTION

(5) In the following detailed description of certain embodiments, reference is made to the accompanying drawings which form a part hereof, and in which are shown by way of illustration of example embodiments. It is also to be understood that features of the embodiments and examples herein can be combined, exchanged, or removed, other embodiments may be utilized or created, and structural changes may be made without departing from the scope of the present disclosure.

(6) In accordance with various embodiments, the methods and functions described herein may be implemented as one or more software programs running on a computer processor or controller. Dedicated hardware implementations including, but not limited to, application specific integrated circuits, programmable logic arrays, and other hardware devices can likewise be constructed to implement the methods and functions described herein. Methods and functions may be performed by modules or nodes, which may include one or more physical components of a computing device (e.g., logic, circuits, processors, etc.) configured to perform a particular task or job, or may include instructions that, when executed, can cause a processor to perform a particular task or job, or any combination thereof. Further, the methods described herein may be implemented as a computer readable storage medium or memory device including instructions that, when executed, cause a processor to perform the methods.

(7) FIG. 1 depicts a diagram of a system **100** configured to implement a quick response (QR) remote control, in accordance with certain embodiments of the present disclosure. The system **100** may include a streaming service **102**, a content source **104**, a streaming device **106**, a user scanning device **116**, and a network **110** over which the components of system **100** may communicate and exchange data. Each or any of streaming service **102**, content source **104**, streaming device **106**, user scanning device **116**, and network **110** may be implemented via computers, servers, hardware and software modules, or other system components. Further, the system **100** may include a QR code **112** for accessing a remote control for controlling the playback of a stream over streaming device **106**.

(8) Streaming service **102** may generate, publish, or broadcast streaming content to streaming device **106**. Some or all of the content, such as video segments or advertisements, may be obtained or transmitted from content source **104**. Content source **104** may include one or more servers or databases providing content (e.g., video segments or streams, advertising, music, etc.) that may be displayed or presented at streaming device **106**. In some embodiments, the streaming service **102** may acquire (e.g., download) content from content source **104** and generate streaming content to send to streaming device **106** over network **110**. In some other embodiments, the streaming service **102** may provide content source **104** with a list or sequence of content elements to include in a content feed, and the streaming content can be provided from content source **104** to streaming

device **106** via network **110**. The streaming service **102** may provide a plurality of content feed options, such as multiple channels or content categories. Streaming service **102** may be configured with the capability to adjust or change behavior at the streaming device **106** (e.g., through commands sent via network **110**) to change the channel or content feed displaying at the streaming device **106**, adjust the volume or display settings, or otherwise modify the content being presented at streaming device **106**. Further, streaming service **102** may include one or more data storage devices, data storage mediums, data storage servers, and related data structures, and may store information about streaming device **106** or associated client systems or accounts, streaming content data, or other information.

(9) Streaming device **106**, such as computers, smartphones, set-top boxes, or televisions, may receive streaming content such as video feeds. Streaming device **106** may include a streaming content module **108** and display device **114**. Streaming content module **108** may receive streamed content, such as from streaming service **102** or content source **104** via network **110**, and perform any data conversion necessary to display the streaming content on display device **114**. In some examples, streaming content module **108** may also generate or load content to display with a stream, such as advertisements. Display device **114** may be a television, monitor, digital billboard, computer, smartphone, or other device having a digital display element. In some examples, a business may stream content to a television or video display device **114** at the business location (e.g., at a bar or restaurant) for the entertainment of customers. Streaming content may include both video segments and advertisements, as well as supplemental overlay data, such as news tickers, sports scores, stock market updates, a listing of current or upcoming video segments, or other data.

(10) Streaming device **106** may be configured to be controlled via one or more local control options, such as a physical remote control, control elements on the streaming device itself, or other local inputs. As used herein, local controls or local inputs may include control devices physically proximate to the streaming device **106**, which may send inputs from the control device to the streaming device **106** via wired electrical connections, infrared signals, Bluetooth, local Wi-Fi, radio frequency, or other limited-range transmission options.

(11) However, physical control devices such as remote controls may be lost or stolen, and may be costly or difficult to replace. While a control device is lost, it may be difficult or impossible to control the streaming device **106**. Even when a local remote is available, it may operate by bringing up a channel guide or menus on the display device **114**, which may be intrusive or undesirable, especially when the display device **114** is displayed at a public business for customer entertainment. Further, a local control device may limit the ability to adjust the streaming device **106** remotely. For example, a business owner may have a streaming device **106** set at a business location, and may desire to adjust what is being displayed at the business location without physically traveling to the business location.

(12) As an alternative to a local remote control, the system **100** may include a QR code **112** for accessing a remote control via a web application or other remote or online interface. In an example embodiment, a printout or physical element having a QR code **112** (or other scannable indicator) associated with streaming device **106** could be provided to a customer along with streaming device **106** or when signing up for a streaming product offered by streaming service **102**. In another example, a component of system **100**, such as streaming service **102** or streaming device **106**, may dynamically generate a QR code **112** associated with streaming device **106**, which code can be accessed by the customer. For example, the code may be sent (e.g., via a text message image or link, or via an email to a customer's account) or otherwise displayed (e.g., accessible via a customer account website), where the code may be scanned or printed for use by the customer. The QR code **112** may be generated, hosted, or otherwise presented via streaming service **102**, content source **104**, or via another component of system **100**.

(13) When a user scanning device **116** scans the QR code **112**, the QR code **112** connect the user scanning device **116** with an application program interface (API) for the streaming service **102** via

the network **110**, e.g., by displaying a web link or directly initiating a network connection. The API may obtain information from the user scanning device **116**, such as metadata that was included in the QR code **112**. For example, the QR code may include a device identifier that uniquely identifies the streaming device **106**. In some examples, the metadata included in the QR code **112** and provided by the user scanning device **116** may be encrypted or otherwise include security features (such as a randomly generated secure key, or requiring account log-in credentials) to indicate that the QR code is authenticated for providing control access to streaming device **106**. The user scanning device **116** may include a smartphone, a tablet, a laptop, or another computing device capable of using an image capture element (e.g., a camera) to detect a scannable indicator and obtain data from it, such as a web address and metadata information. The user scanning device **116** may be internet- or network-capable, such as having cellular data capabilities or Wi-Fi connectivity, to access streaming service **102** via network **110**.

(14) In response to the user scanning device **116** contacting the API based on the QR code **112**, the API can determine the streaming device **106** associated with the QR code, and may generate or direct the user scanning device **116** to a web-based remote control interface. For example, a WebView remote control may be presented at the user scanning device **116**. The web-based remote control may be linked, via streaming service **102**, to a specific streaming device **106**, and may enable control of the streaming device via the streaming service and network **110**. In this manner, a user may be able to control the content channel or other settings of the streamed content presented via the streaming device without the constraints of a local control device.

(15) The web-based remote control may present a user with a control interface, e.g. via user streaming device **116** through an application or web browser, that allows for changing or selecting a content channel, volume control, adjusting settings such as closed captions, or otherwise adjusting the display elements for the streaming device **106**. In some embodiments, the web-based remote may depict a channel guide for selecting a content or stream channel without the need to display the guide on the display device **114**.

(16) Further, a customer of streaming service **102** may manage the creation or invalidation of QR codes **112** via a remote interface, such as an account webpage or app, via user scanning device **116** or another computing device. For example, a user may request to have a QR code **112** associated with the streaming device **106** be generated. In response to a QR code generation request, the streaming service **102** may generate a QR code **112** associated with (and therefor providing control for) a selected streaming device **106** by including metadata such as a device ID, and a randomly or dynamically generated key. The streaming service **102** may store a copy or pair of the key (e.g., for a symmetric key pair) at the streaming service, so that API requests due to a scanning device **116** scanning the QR code **112** can be validated and grant access to the streaming device **106**. In another example, a user may select to have an existing QR code **112** associated with a streaming device **106** invalidated or dissociated with the streaming device, for example in the event the QR code is compromised or lost. An example implementation of system **100** is discussed in more detail in regard to FIG. 2.

(17) FIG. 2 depicts a diagram of a system **200** configured to implement a QR remote control, in accordance with certain embodiments of the present disclosure. In particular, FIG. 2 presents an example embodiment of a streaming service system configured to utilize QR codes to access web-based remote controls for streaming content. System **200** may include a streaming service **202**, a streaming device **206**, a user scanning device **216**, and a scannable indicator such as a QR code **212**. In some embodiments, the system **200** of FIG. 2 may correspond to the system **100** of FIG. 1.

(18) Streaming device **206** may be a computing device configured to receive streaming content over a network, and display the stream on a display device **114**. The streaming device may include a set-top box or streaming stick, a smartphone, a gaming console, a smart TV, or any other device capable of the described operations. The streaming content may be received from a remote source, such as streaming service **202** or content source **104**.

(19) The streaming service **202** may generate a QR code **212** associated with a streaming device **206**, at step **1**. The streaming service **202** may generate the QR code **212** in response to a request from a user (e.g., through an account page on a website or app, via a request submitted through a call, email, text, or mailing, or via other means) or automatically (e.g., based upon initial account creation or to accompany a streaming device **206** delivered to a customer). The QR code **212** may be associated with the streaming device **206** by including metadata in the QR code that corresponds to a device ID or user account stored at the streaming service **202**. Accordingly, when a user scanning device **216** scans the QR code **212**, the streaming service **202** may use the metadata transmitted from the scanning device to identify and transmit commands to a particular streaming device (e.g., via network **110**). The generated QR code **212** may also include security features in the metadata such as keys or encryption, which may enable the streaming service **202** to authenticate or verify the QR code **212**. If a QR code **212** needs to be invalidated or dissociated from a user account or streaming device **206**, the associated key(s) or encryption may be removed from the streaming service **202** so that the QR code is no longer recognized as valid. New key(s) or encryption may be generated for replacement QR codes **212**. The generated QR code **212** may be provided to a customer or user via a physical printout or display (e.g., which may be included in packaging with the streaming device **206** or mailed), or as a digital web page or image which a customer or user may access through an account page, internet link, streaming service application, or other method.

(20) A user scanning device **216** may scan the QR code **212** at step **2**. For example, the user scanning device **216** may include a smartphone or tablet having a camera and software that can detect the QR code **212** and extract metadata encoded within the QR code. The QR code **212** may include an internet link directing the user scanning device **216** to access a web page or API associated with the streaming service **202**. At step **3**, the user scanning device **216** may access the link from the QR code **212**, and may provide or transmit metadata from the QR code to the API, such as encrypted data, one or more keys, a device ID associated with streaming device **206**, or other metadata elements.

(21) In response to the metadata from the QR code **212**, the streaming service **202** may verify or authenticate the QR code or the user device **216** that transmitted the data, and generate a web-based or virtual remote control, at step **4**. The virtual remote control may be presented or generated within an application running on the user scanning device **216**, such as a web browser or through an app associated with the streaming service **202** (e.g., as a WebView remote control). The virtual remote control may be connected, via the streaming service **202**, to the streaming device **206** associated with the QR code **212**, so that inputs to the virtual remote control affect the streaming device **206**.

(22) At step **5**, the user scanning device **216** may send remote control inputs to the streaming service **202**. For example, the web-based remote control may accept touchscreen or other inputs to enable a user to change a channel, turn the streaming device **206** on or off, or adjust volume or other settings. These inputs may be received at scanning device **216** and converted into network message packets, which may be sent over network **110** to streaming service **202**.

(23) Based on the received remote inputs, the streaming service **202** may change the stream content, channel, or other settings at the streaming device, at step **6**. For example, input messages received at the streaming service **202** from the user scanning device **216** may be identified as corresponding to a particular streaming device **206** based on the virtual remote interface. The received messages may either be forwarded from the streaming service **202** to the streaming device **206**, where they may be unpacked and executed, or the input messages may be received and interpreted by the streaming service API **202**, which may then generate new messages (potentially in a different format) and send them to the streaming device. Messages or commands sent from streaming service **202** to streaming device **206** may be sent over network **110**. In some examples, the streaming device **206** may return a response to the streaming service **202** indicating that a command was received or executed. The user scanning device **216** may continue sending remote

inputs via the QR remote control as necessary, including scanning the QR code **212** again if the remote is closed, times out, or otherwise is lost at the scanning device **216** or the streaming service **202**.

(24) In an example embodiment, the QR code **212** may be lost or exposed to a person who should not have access to it. Accordingly, a user scanning device **216** or other computing device may transmit an invalidation request about the QR code **212** to the streaming service **202**, at step **7**. For example, a customer may access a user account page and request to invalidate all or selected QR codes associated with streaming device **206**. In response to the invalidation request, the streaming service **202** may invalidate or dissociate the QR code **212** from streaming device **206**, at step **8**. For example, the streaming service **202** may delete one or more keys, unique identifiers, or other records of the QR code **212** stored at the streaming service, so that attempts to use the QR code to access a virtual remote for streaming device **206** will fail to be authenticated or validated.

(25) After invalidating a QR code **212**, or to obtain a first or new QR code **212** associated with streaming device **206**, a user scanning device **216** or another computing device may request a new QR code, at step **9**. The QR code generation request may initiate a new QR code generation process at step **1**. An example method for implementing a QR remote control is discussed in regard to FIG. **3**.

(26) FIG. **3** depicts a flowchart **300** of an example method for implementing a QR remote control, in accordance with certain embodiments of the present disclosure. In particular, the method of FIG. **3** may be a process for creating a QR code that can be used to pull up a virtual or web-based remote control for controlling a streaming device or streaming content. The method of FIG. **3** may be implemented by systems shown in FIG. **1**, such as streaming service **102**, streaming device **106** and streaming content module **108**, user scanning device **116**, other components, or some combination thereof, generally collectively referred to as the streaming service **102**.

(27) The method may include receiving a QR code generation request, which request may include or be associated with a device ID for a particular streaming device, at **302**. For example, a user may request generation of a remote control QR code via an application or web interface, where a corresponding device may be selected or a device ID may be entered. In another example, a streaming device may include a label, manual, or other printed element that may be scanned by a user scanning device, which may direct the scanning device to send a device ID and implement a QR code generation request.

(28) In response to receiving the QR code generation request, the method may include generating a QR code based on the device ID, at **304**. Generating the QR code may include generating one or more keys, code identifiers, or encrypting data in the QR code with a particular encryption scheme, and storing corresponding security data at the streaming service. The QR code security features and corresponding data stored at the streaming service may be used to validate or authenticate a scanning device for accessing a virtual remote control for the streaming device.

(29) At **306**, the method may include receiving QR code metadata associated with the device ID from the user scanning device. For example, scanning the QR code may direct the user scanning device to access an API for the streaming service and provide metadata included within the QR to the API. The method may then determine whether the metadata is recognized or authenticated, at **308**. For example, the API may use the metadata to look up authorization data and an associated streaming device stored at the streaming service. If the metadata is not recognized or does not correspond to stored data, it may indicate that the scanned QR code has been invalidated, and the method may include not authenticating the user scanning device for access to a virtual remote control, at **310**.

(30) When the metadata is recognized or authenticated, at **308**, the method may include directing the user device to a virtual remote control associated with the device ID, at **312**. For example, the streaming service API may generate an instance of a virtual remote tied to the streaming device at the user streaming device, or may direct the user device to a web-based implementation or

application of a virtual remote.

(31) At **314**, the method may include receiving remote control inputs via the virtual remote, and adjust a stream or content at the device associated with the device ID based on the inputs. For example, the streaming service (e.g., via the API) may either forward authorized commands received from the user scanning device to the streaming device, or may receive and interpret the commands, and generate corresponding commands to send to the streaming device.

(32) At **316**, the method may include determining whether a QR code invalidation request has been received, such as through a streaming service application or web interface. If not, the method may include continuing to receive virtual remote inputs and adjusting the stream or streaming device settings, at **314**. If an invalidation request has been received, the method may include dissociating or invalidating the current QR code from the associated device ID or streaming device, at **318**. For example, the streaming service may mark keys or identification data associated with the QR code as invalid, or may delete the identification data so that an authentication attempt will fail. The method may then return to receiving any future QR code generation request, at **302**.

(33) Turning now to FIG. 4, a diagram of a system **400** configured to implement a QR remote control is shown, in accordance with certain embodiments of the present disclosure. In particular, FIG. 4 depicts a computer system **402**, which may be an example of any computing system that may be employed to perform the operations of streaming service **102**, content source **104**, streaming device **106** or streaming content module **108**, user scanning device **116**, and related processes and methods. Computing system **402** may include a processing system **404**, a communication interface **406**, and a user interface **408**. Computing system **402** may include other components, such as a battery and enclosure, that are not shown for clarity. Computing system **402** may comprise one or more server computing systems, desktop computing systems, laptop computing systems, smartphone devices, tablet devices, set-top or streaming boxes, connected televisions, or any other computing system, including combinations thereof.

(34) Communication interface **406** may comprise components that communicate over communication links, such as network cards, ports, radio frequency (RF), processing circuitry and software, or other communication components. Communication interface **406** may be configured to communicate over metallic, wireless, or optical links. Communication interface **406** may be configured to use Time Division Multiplex (TDM), Internet Protocol (IP), Ethernet, optical networking, wireless protocols, communication signaling, other communication formats, or any combinations thereof. In particular, communication interface **406** may be configured to communicate over a network **110** with streaming service **102**, streaming device **106**, content source **104**, user scanning device **116**, or other external systems. Communication interface **406** may also enable communication with local external devices, such as external storage or interface devices.

(35) User interface **408** may comprise components that interact with a user to receive user inputs and to present media or other information. User interface **408** may include a display screen, touch screen, touch pad, keyboard, buttons, speaker, microphone, pointer device or interface, communication port, other user input/output apparatus, or any combination thereof. User interface **408** may also include camera or image capture apparatus for scanning elements such as QR codes. In some examples, user interface **408** may be a module configured to interface with a separate system for presenting information and receiving inputs. For example, computing system **402** may have limited or no direct user input components, but it connects (e.g., via communication interface **406**) to a monitor or other device that may receive inputs via touch screen, remote control, or other input method, which inputs are then provided or relayed to computing system **402**.

(36) Processing system **404** may be linked to communication interface **406** and user interface **408**. Processing system **404** can include processing circuitry **410** and memory device **412**. Memory device **412** can store executable instructions or other operating software **416**, as well as non-executable data files, such as stream device identifier (ID) data **414** or security or authorization data, and stream content **422**. Stream device ID **414** may include a unique identifier for one or

more streaming devices, keys, or other identifiers which may be incorporated into generated QR codes for generating or authorizing virtual remote controls. For example, a streaming service may maintain device IDs **414**, keys, encryption information, or other identifiers associated with multiple client streaming devices, and may generate QR codes for generating virtual remote controls associated with those devices. Stream content **422** may include video, audio, advertising, or other content of a content stream, which may be provided from streaming service **102** or content source **104** to streaming device **106**.

(37) Processing circuitry **410** may comprise a microprocessor and other circuitry that can retrieve and execute instructions **416** from memory device **412**. Memory **412** may comprise a non-volatile data storage medium, such as a disk drive or solid state drive, or volatile memory such as random access memories (RAM) and dynamic RAM (DRAM), or any other memory apparatus. In some examples, processing circuitry **410** may be mounted on a circuit board that may also hold memory device **412** and portions of communication interface **406** or user interface **408**.

(38) Executable instructions **416** may comprise computer programs, firmware, or some other form of machine-readable processing instructions. Executable instructions **416** may include QR module **418**, and remote module **420**, although related operations may be handled by multiple different modules or programs (potentially located on multiple computing devices), all operations may be performed by a single module, or additional modules may be included in executable instructions **416**. For example, elements or aspects of QR module **418** and remote module **420** may be implemented by streaming service **102**, streaming device **106** or streaming content module **108**, user scanning device **116**, other systems, or a combination thereof. Executable instructions **416** may further include an operating system, utilities, drivers, network interfaces, applications, or other types of software. When executed by processing circuitry **410**, executable instructions **416** may direct processing system **404** to operate computing system **402** as described herein.

(39) QR module **418** may be a set of instructions for generating QR codes, validating or authorizing QR code metadata received from user devices, or both. In some examples, QR module **418** may also transmit QR codes to user devices, or link user devices to web pages or applications where QR codes may be accessed. The QR module **418** may include a streaming device ID received from a user device or retrieved from stream device ID **414** into the QR code. The QR module **418** may also randomly or dynamically generate keys, QR code identifiers, encryption algorithms, or other data which may be used for authenticating a remote control QR code, and storing data (e.g., to stream device ID **414**) that may be used to verify or authenticate the generated keys, etc. in a manner that associates particular QR code metadata with a particular streaming device. When a transmission is received from a user scanning device after scanning a QR code, the QR module **418** may compare the received metadata against the stream device ID **414** to determine whether a virtual remote control may be generated for controlling a particular streaming device. If a QR code invalidation request is received, the QR module **418** may delete, invalidate, or dissociate keys or validation information, so that the associated QR code cannot be used to generate a virtual remote control.

(40) Remote module **420** may include a set of computer functions or instructions for generating a virtual remote control that may be accessed via a user streaming device. For example, when a user streaming device scans a QR code for a remote and accesses an API for the streaming service, the QR module **418** may first validate the QR code, and then direct the remote module **420** to generate or direct the user scanning device to a virtual remote that can control a particular streaming device, or the content provided to the streaming device. The remote module **420** may receive inputs to the virtual remote, and based on those inputs, may alter what stream content **422** is provided to a streaming device, or may send instructions to the streaming device to change a channel, adjust a setting, or otherwise alter its operation.

(41) The illustrations of the embodiments described herein are intended to provide a general understanding of the structure of the various embodiments. The illustrations are not intended to

serve as a complete description of all of the elements and features of apparatus and systems that utilize the structures or methods described herein. Many other embodiments may be apparent to those of skill in the art upon reviewing the disclosure. Other embodiments may be utilized and derived from the disclosure, such that structural and logical substitutions and changes may be made without departing from the scope of the disclosure. Moreover, although specific embodiments have been illustrated and described herein, it should be appreciated that any subsequent arrangement designed to achieve the same or similar purpose may be substituted for the specific embodiments shown.

(42) This disclosure is intended to cover any and all subsequent adaptations or variations of various embodiments. Combinations of the above embodiments, and other embodiments not specifically described herein, will be apparent to those of skill in the art upon reviewing the description. Steps depicted in the flowcharts may optionally be excluded, added, performed in a different order, or performed with different degrees of concurrency than shown (e.g., steps depicted as sequential may be performed concurrently). Additionally, the illustrations are merely representational and may not be drawn to scale. Certain proportions within the illustrations may be exaggerated, while other proportions may be reduced. Accordingly, the disclosure and the figures are to be regarded as illustrative and not restrictive.

Claims

1. A method comprising: implementing a virtual remote control for a streaming device, including: providing an interface for the virtual remote control to a user device over a network, including: generating a quick response (QR) code associated with the streaming device; receiving metadata associated with the QR code from the user device; and providing the interface in response to receiving the metadata; receiving an input to the virtual remote control from the user device over the network; and adjusting a setting of the streaming device over the network based on the input, including changing a channel playing at the streaming device.
2. The method of claim 1 further comprising: receiving a QR code generation request; and generating the QR code based on the QR code generation request.
3. The method of claim 1 further comprising: generating the QR code to include the metadata, the metadata including a dynamically generated key; based on receiving the metadata from the user device, authorizing the metadata; and providing the interface based on authorizing the metadata.
4. The method of claim 3 further comprising: receiving an invalidation request for the QR code; and invalidating the QR code, resulting in the metadata not being authorized for accessing the interface.
5. The method of claim 1 further comprising: implementing the virtual remote control via a streaming service physically remote from the user device and the streaming device.
6. The method of claim 1 further comprising the interface includes a channel guide displayed at the user device and not displayed via the streaming device.
7. A system comprising: a streaming service configured to implement a virtual remote control for a streaming device at a user device, the streaming service physically remote from the user device and the streaming device, including: generate a quick response (QR) code associated with the streaming device; in response to the QR code being scanned by the user device, provide an interface for the virtual remote control to the user device over a network; receive an input to the virtual remote control from the user device over the network; and adjust a setting of the streaming device over the network based on the input.
8. The system of claim 7 comprising the streaming service further configured to: receive metadata associated with the QR code from the user device when the QR code is scanned by the user device; and provide the interface in response to receiving the metadata.
9. The system of claim 8 comprising the streaming service further configured to: receive a QR code

generation request; and generate the QR code based on the QR code generation request.

10. The system of claim 8 comprising the streaming service further configured to: generate the QR code to include the metadata, the metadata including a dynamically generated key; based on receiving the metadata from the user device, authorize the metadata; and provide the interface based on authorizing the metadata.

11. The system of claim 10 comprising the streaming service further configured to: receive an invalidation request for the QR code; and invalidate the QR code, resulting in the metadata not being authorized for accessing the interface.

12. The system of claim 7 comprising the streaming service further configured to: adjust the setting by changing a channel playing at the streaming device.

13. The system of claim 12 comprising the streaming service further configured to: provide the interface to include a channel guide displayed at the user device and not displayed via the streaming device.

14. A memory device storing instructions that, when executed, cause a processor to perform a method comprising: implementing, via a streaming service physically remote from a user device and a streaming device, a virtual remote control for the streaming device at the user device, including: generating a quick response (QR) code associated with the streaming device; receiving metadata associated with the QR code from a user device over a network; in response to receiving the metadata, providing an interface for the virtual remote control to the user device over the network, wherein the interface includes a channel guide displayed at the user device and not displayed via the streaming device; receiving an input to the virtual remote control from the user device over the network; and adjusting a setting of the streaming device over the network based on the input.

15. The memory device of claim 14 storing instructions that, when executed, cause the processor to perform the method further comprising: receiving a QR code generation request; and generating the QR code based on the QR code generation request.

16. The memory device of claim 14 storing instructions that, when executed, cause the processor to perform the method further comprising: generating the QR code to include the metadata, the metadata including a dynamically generated key; based on receiving the metadata from the user device, authorizing the metadata; and providing the interface based on authorizing the metadata.

17. The memory device of claim 16 storing instructions that, when executed, cause the processor to perform the method further comprising: receiving an invalidation request for the QR code; and invalidating the QR code, resulting in the metadata not being authorized for accessing the interface.

18. The memory device of claim 14 storing instructions that, when executed, cause the processor to perform the method further comprising: adjusting the setting includes changing a channel playing at the streaming device.
