

(12) **United States Patent**
Bryan et al.

(10) **Patent No.:** **US 12,406,456 B2**
(45) **Date of Patent:** **Sep. 2, 2025**

(54) **STATISTICAL SHAPE AND APPEARANCE
MODELING FOR VOLUMETRIC
GEOMETRY AND INTENSITY DATA**

(56) **References Cited**
U.S. PATENT DOCUMENTS

(71) Applicant: **Synopsys, Inc.**, Sunnyvale, CA (US)

6,858,003 B2 * 2/2005 Evans A61B 34/71
606/1
9,019,237 B2 * 4/2015 Ludwig G06F 3/04883
345/158

(72) Inventors: **Rebecca Louise Bryan**,
Bishopsteignton (GB); **David Richard
Raymont**, Devon (GB); **Furqanullah
Furqanullah**, Exeter (GB);
Christopher John Louis Goddard,
Exeter (GB); **Mark Taylor**, Adelaide
(AU)

(Continued)

OTHER PUBLICATIONS

Agudo et al—Combining Local-Physical and Global-Statistical
Models for Sequential Deformable Shape from Motion -201611—
Sprin (Year: 2016).*

(Continued)

(73) Assignee: **Synopsys, Inc.**, Sunnyvale, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 221 days.

Primary Examiner — Yujang Tswei
(74) *Attorney, Agent, or Firm* — Patterson + Sheridan,
LLP

(57) **ABSTRACT**

An image-based approach for statistical shape and appearance modeling includes re-orienting (rotating/translating) training masks to align the training masks with a reference mask to provide corresponding re-orientation parameters, where the training masks represent 3-dimensional shapes of a population of objects and the reference mask represents a 3-dimensional shape of a reference object, deforming the re-oriented training masks based on the reference mask to provide displacement fields indicative of differences between a 3-dimensional shape of the reference mask and 3-dimensional shapes of the re-oriented training masks, re-orienting training backgrounds based on the re-orientation parameters, where the training backgrounds represent volumetric intensity data of the 3-dimensional images of the objects, deforming the re-oriented training backgrounds based on the displacement fields, combining the deformed training backgrounds and the displacement fields, and reducing a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model.

(21) Appl. No.: **18/138,672**

(22) Filed: **Apr. 24, 2023**

(65) **Prior Publication Data**
US 2024/0355078 A1 Oct. 24, 2024


(51) **Int. Cl.**
G06T 19/20 (2011.01)
G06T 7/50 (2017.01)
G06V 10/74 (2022.01)

(52) **U.S. Cl.**
CPC **G06T 19/20** (2013.01); **G06T 7/50**
(2017.01); **G06V 10/761** (2022.01); **G06T**
2219/2004 (2013.01)

(58) **Field of Classification Search**
CPC ... G06T 19/20; G06T 7/50; G06T 2219/2004;
G06V 10/761

See application file for complete search history.

19 Claims, 6 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

11,348,257	B2 *	5/2022	Lang	A61B 90/92
12,211,151	B1 *	1/2025	Chiou	G06T 19/003
2009/0297012	A1 *	12/2009	Brett	G06V 10/755
				382/128
2014/0323845	A1 *	10/2014	Forsberg	G06T 7/60
				600/407
2016/0239966	A1 *	8/2016	Parsey	A61B 6/037
2017/0354385	A1 *	12/2017	Lerch	A61B 6/4435
2018/0031719	A1 *	2/2018	Huang	G06T 17/20
2020/0284883	A1 *	9/2020	Ferreira	G01S 7/4815
2021/0134467	A1 *	5/2021	Poltaretskyi	A61B 5/1127
2022/0160430	A1 *	5/2022	Landon	A61B 90/36
2023/0237661	A1 *	7/2023	Hsiao	G06N 3/08
				382/128

OTHER PUBLICATIONS

Krebs—Robust medical image registration and motion modeling based on machine learning—2020—HAL open science (Year: 2020).*

Li et al—A diffeomorphic demons approach to statistical shape modeling—201801—ResearchGate (Year: 2018).*

Zikic Contributions to Medical Image Registration—2011—Technische Universität „At Mă” UNCHEN (Year: 2011).*

Vercauteren, et al., “Non-parametric Diffeomorphic Image Registration with the Demons Algorithm”, Non-parametric Diffeomorphic Image Registration with the Demons Algorithm. Medical Image Computing and Computer Assisted Intervention (MIC-CAI™07), Oct. 2007, Brisbane, Australia. pp. 319-326, T 10.1007/978-3-540-75759-7_39 .inria-00166123.

Heimann, et al., “Statistical shape models for 3D medical image segmentation: A review”, Medical Image Analysis 13 (2009) 543-563.

Day et al., “Using Statistical Shaper and Appearance Modelling to Characterise the 3D Shape and Material Properties of Human Lumbar Vertebrae: A Proof of Concept Study” Journal of the Mechanical Behavior of Biomedical Materials 126 (2022).

Zitpva et al., “Image Registration Methods: A Survey” Department of Image Processing, Institute of Information Theory and Automation, Academy of Sciences of the Czech Republic Pod 4, 182 08 Prague 8, Czech Republic Received Nov. 9, 2001; received in revised form Jun. 20, 2003; accepted Jun. 26, 2003.

Erdt, et al., “Smart Manual Lnadmarking of Organs” Article in Proceedings of SPIE Mar. 2010.

Grassi, et al., “Statistical Shape and Appearance Models: Development Towards Improved Osteoporosis Care” Current Osteoporosis Reports (2021) 19:676-687.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A





FIG. 5B



1

STATISTICAL SHAPE AND APPEARANCE MODELING FOR VOLUMETRIC GEOMETRY AND INTENSITY DATA

TECHNICAL FIELD

The present disclosure generally relates to a three-dimensional (3D) image segmentation and model generation system. In particular, the present disclosure relates to statistical shape and appearance modeling for volumetric geometry and intensity data.

BACKGROUND

In-silico trials are becoming of increasing interest for use in medical device research and development, and for generation of evidence of safety and efficacy for regulatory submission of a new design, design modification, or treatment. Regulatory bodies, such as the U.S. Food and Drug Administration (USFDA), encourage adoption of computational modelling and simulation (CM&S). CM&S provide a number of advantages over conventional in-vivo (animal/human) testing and in-vitro (i.e., bench) testing, such as reduced costs, reduced time-to-market, acceleration of development cycles, and reduced risks and suffering associated with in-vivo testing.

A significant barrier to wider adoption of in-silico trials is a need for large numbers of patients to construct computational models on which to perform simulation or analysis. Traditionally this would require access to large numbers of clinical imaging data sets, such as from computed tomography (CT) scans or magnetic resonance imaging (MRI) scans, which is often infeasible due to cost, acquisition time, and data privacy restrictions.

A statistical shape model (SSM) is a geometric model that describes a collection of semantically similar objects. A SSM represents an average shape, or mean, of an object (e.g., pelvises) within a population, and variations in the shapes within the population. A statistical shape and appearance model (SSAM) incorporates appearance data (e.g., color or texture represented by voxel intensity) extracted from images of the objects.

SUMMARY

Techniques for statistical shape and appearance modeling for volumetric geometry and intensity data are described.

One example is a machine-implemented method that includes re-orienting training masks to align the training masks with a reference mask to provide corresponding re-orientation parameters (where the training masks represent 3-dimensional shapes of a population of objects and the reference mask represents a 3-dimensional shape of a reference object), deforming the re-oriented training masks based on the reference mask to provide displacement fields indicative of differences between a 3-dimensional shape of the reference mask and 3-dimensional shapes of the re-oriented training masks, re-orienting training backgrounds based on the re-orientation parameters to provide re-oriented training backgrounds (where the training backgrounds represent volumetric intensity data of the 3-dimensional images of the objects), deforming the re-oriented training backgrounds based on the displacement fields of the respective training masks to provide deformed training backgrounds, combining the deformed training backgrounds and the displacement fields, and reducing a dimensionality of the

2

combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model.

Re-orienting training masks may include converting the training masks and the reference mask to triangulated meshes, and re-orienting the triangulated meshes of the training masks to the triangulated meshes of the reference mask based on an iterative closest point method to provide the re-orientation parameters to include iterative closest point transformation matrices.

Deforming the re-oriented training masks may include computing signed distance maps of the re-oriented training masks and the reference mask, and computing the displacement fields based on the signed distance maps. The displacement fields may be computed with a diffeomorphic demons deformable method. Deforming the re-oriented training masks may include representing the displacement fields as images having vector-type pixels with N elements, where N is a dimensionality of the reference mask.

Combining may include combining the deformed training backgrounds and the displacement fields in a matrix. The matrix may be scaled, such as by computing means of rows of the matrix and dividing the rows of the matrix by the means of the respective rows. The dimensionality of the matrix may be reduced based on principal component analysis to provide the statistical shape and appearance model to include a mean dataset, modes of variation, and weighting, wherein the modes of variation and the weighting reflect variations in the objects relative to a mean of the objects.

The statistical shape and appearance model may be used to generate virtual objects based on variations amongst the training masks and the training backgrounds, analyze variability in shape and material properties of the population of objects based on variations amongst the training masks and the training backgrounds, and/or predict missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

Another example is a non-transitory computer readable medium encoded with a computer program that includes instructions to cause a processor to compute signed distance maps of training masks and of a reference mask (where the training masks represent 3-dimensional shapes of a population of objects extracted from 3-dimensional images of the objects and the reference mask represents a 3-dimensional shape of a reference object), compute displacement fields indicative of geometric differences between the reference mask and the training masks based on the respective signed distance maps, deform training backgrounds based on the displacement fields to provide deformed training backgrounds (where the training backgrounds comprise volumetric intensity data extracted from the 3-dimensional images of the training objects), combine the deformed training backgrounds and the displacement fields, and reduce a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model.

The instructions may include instructions to compute the displacement fields with a diffeomorphic demons deformable method.

The instructions may include instructions to represent the displacement fields as images having vector-type pixels with N elements, where N is a dimensionality of the reference mask.

The instructions may include instructions to combine the deformed training backgrounds and the displacement fields in a matrix. The instructions may further include instructions to scale the matrix, such as by computing means of rows of the matrix and dividing the rows of the matrix by the means

3

of the respective rows. The instructions may include instructions to reduce a dimensionality of the matrix based on principal component analysis to provide the statistical shape and appearance model to include a mean dataset, modes of variation, and weighting, wherein the modes of variation and the weighting reflect variations in the objects relative to a mean of the objects.

The instructions may include instructions to use the statistical shape and appearance model to generate virtual objects based on variations amongst the training masks and the training backgrounds, analyze variability in shape and material properties of the population of objects based on variations amongst the training masks and the training backgrounds, and/or predict missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

Another example is an integrated circuit (IC) device that includes re-orientation circuitry that aligns training masks with a reference mask to provide corresponding re-orientation parameters and re-orient training backgrounds based on the re-orientation parameters to provide re-oriented training backgrounds, and deformation circuitry that deforms the re-oriented training masks based on the reference mask to provide displacement fields indicative of differences between a 3-dimensional shape of the reference mask and 3-dimensional shapes of the re-oriented training masks and deforms the re-oriented training backgrounds based on the displacement fields of the respective training masks to provide deformed training backgrounds.

The deformation circuitry may deform the re-oriented training masks and the re-oriented training backgrounds by deformably registering signed distance maps of the re-oriented training masks to provide an initial set of displacement fields, deformably registering background intensity values of the re-oriented training backgrounds based on the initial set of displacement fields to provide an initial set of deformed training backgrounds, deformably registering the initial set of displacement fields to provide a refined set of displacement fields, and refining the initial set of deformed training backgrounds based on the refined set of displacement fields to provide a refined set of deformed training backgrounds.

The IC device may further include combining circuitry that combines the deformed training backgrounds and the displacement fields, and dimensionality reduction circuitry that reduces a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model (SSAM).

The IC device may further include SSAM application that generates virtual objects based on variations amongst the training masks and the training backgrounds, analyzes variability in shape and material properties of the population of objects based on variations amongst the training masks and the training backgrounds, and/or predicts missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

BRIEF DESCRIPTION OF DRAWINGS

The disclosure will be understood more fully from the detailed description given below and from the accompanying figures of embodiments of the disclosure. The figures are used to provide knowledge and understanding of embodiments of the disclosure and do not limit the scope of the disclosure to these specific embodiments. Furthermore, the figures are not necessarily drawn to scale.

4

FIG. 1 is a block diagram of a statistical shape and appearance model (SSAM) generator that generates a statistical shape and appearance model based on training data extracted from images of objects, according to an embodiment.

FIG. 2 is a block diagram of an image processing system that extracts training masks and training backgrounds from images, according to an embodiment.

FIG. 3 is a flowchart of a method of generating a statistical shape and appearance model based on training masks and training backgrounds, according to an embodiment.

FIG. 4 is an image of synthetic or virtual samples generated from an experimental SSAM, according to an embodiment.

FIG. 5A illustrates box plot distributions for the experimental SSAM (i.e., distances between posterior superior iliac spine and pubic tubercle, and distances between posterior superior iliac spine and anterior superior iliac spine), according to an embodiment.

FIG. 5B is an image of a representative virtual pelvis generated by the experimental SSAM.

FIG. 6 depicts a diagram of an example computer system in which embodiments of the present disclosure may operate, according to an embodiment.

DETAILED DESCRIPTION

Aspects of the present disclosure relate to statistical shape and appearance modeling for volumetric (i.e., 3-dimensional) geometry and intensity data. Volumetric geometry and intensity data may be obtained from 3-dimensional images of the objects. The intensity data may correspond to material properties of the respective objects (e.g., bone mineral density). The 3-dimensional images may include, without limitation, medical images such as computed tomography (CT) scans, micro CT scans, and/or magnetic resonance imaging (MRI) scans. A SSAM essentially describes geometric variations amongst the objects and variations in the scalar or vector values of the objects.

A challenge in generating a statistical shape and appearance model (SSAM) is that 3-dimensional medical images contain significant amounts of data. As a result, capturing shape and intensity variations amongst the objects is computationally intensive.

Another challenge in generating a SSAM is that 3-dimensional images of objects may be taken from different reference points and/or distances, which make it difficult to correctly identify differences in shapes and intensities amongst the images.

Another challenge in generating a SSAM is combining the shape and intensity variations into a model.

Another challenge in generating a SSAM is reducing the complexity or dimensionality of the combined shape and intensity variations.

Embodiments herein describe techniques to overcome/accommodate the aforementioned challenges, and other challenges.

Embodiments herein describe an image-based approach in which 3-dimensional shape information, referred to herein as training masks, and 3-dimensional appearance information (i.e., intensity or grayscale volumetric data), referred to herein as training backgrounds, are extracted from training images of a population of objects. In an embodiment, the training masks are re-oriented (i.e., translated, rotated, and/or re-sized) to match an orientation of a reference mask, and the training backgrounds are re-oriented based on the reorientations of the respective training masks.

Geometric differences between the reference mask and the re-oriented training masks are computed as displacement fields (e.g., N dimensional vector fields), and the displacement fields are applied to the re-oriented training backgrounds. Resultant deformed training backgrounds are combined with the displacement fields and reduced in dimensionality (e.g., via principal component analysis) to provide a SSAM.

The SSAM may be useful in one or more of a variety of applications such as to capture or characterize variability in shape and material properties within a population, to generate synthetic virtual patients (i.e., virtual objects/body parts) having shapes and material properties within ranges of a training population, such as for computational modelling and simulation (CM&S), and/or to predict missing information from partial data sets.

Technical advantages of the present disclosure include, but are not limited to, relatively fast, efficient, and robust model training. Technical advantages further include improved performance and stability of a deformable registration process by computing displacement fields based on signed distance maps rather than mask volumes.

An image-based approach, as disclosed herein may be useful to generate new backgrounds and masks allowing for further image-based processing and/or robust image-based volumetric meshing.

Displacement fields generated as disclosed herein may be re-used, such as for mapping of measurements (e.g., points and/or distances) between a reference mask and training masks and/or between the reference mask and virtual object/samples generated from the SSAM.

Where background intensity values are used in the deformable registration process, the deformable registration process may produce more accurate mappings between a reference mask and training masks, relative to a mesh-based technique that uses approximate methods to establish correspondence for non-boundary points.

FIG. 1 is a block diagram of a statistical shape and appearance model (SSAM) generator **100** that generates a SSAM **146** based on training data extracted from images of objects, according to an embodiment. The objects may include, without limitation, anatomical objects (e.g., bone and/or tissue). The images may include medical images such as, without limitation, computed tomography (CT) scans, micro CT scans, and/or magnetic resonance imaging (MRI) scans. The images may be obtained from a population of patients. The images may be referred to as training images, and the objects may be referred to as training objects.

In the example of FIG. 1, the training data includes training masks **102**, training backgrounds **104**, and a reference mask **108**. Training masks **102** represent external surfaces or geometric shapes of the training objects. Training backgrounds **104** represent intensity information of the images (e.g., grayscale volumetric image data). Training masks **102** and training backgrounds **104** may be obtained/retrieved from a training population dataset **101**. Reference mask **108** may be selected from training masks **102** or may be derived from training masks **102** (e.g., as a mean of training masks **102**).

In the example of FIG. 1, SSAM generator **100** includes circuitry that performs various functions disclosed herein. The circuitry may be combined or distributed in one or more of a variety of combinations, without deviating from the scope of the present disclosure. Alternatively, or additionally, SSAM generator **100** may include a processor and memory configured with instructions/code to perform one or more of the functions disclosed herein.

FIG. 2 is a block diagram of an image processing system **200** that extracts training masks **102** and training backgrounds **104** from images **202**, according to an embodiment. Images **202** may include 3-dimensional images constructed from multiple 2-dimensional images obtained from, for example, CT and/or MRI scans. In the example of FIG. 2, image processing system **200** includes shape and intensity extraction circuitry **204**. Alternatively, or additionally, image processing system **200** may include a processor and memory configured with instructions/code to extract training masks **102** and training backgrounds **104**.

Shape and intensity extraction circuitry **204** may partition an image **202** into segments (e.g., sets of pixels) based on variations amongst neighboring pixels of the image (e.g., based on an edge detection method). Shape and intensity extraction circuitry **204** may assign labels to the pixels based on the segments to which the pixels belong (i.e., pixels of a segment share the same label).

Shape and intensity extraction circuitry **204** may generate a training mask **102** to include a set of points distributed across a surface of one or more segments of an image **202**. The points may be extracted from volume data, such as with a marching cubes method. Coordinates for the points may be combined as a vector that describes the shape. The points may be referred to as landmarks. Landmarks may not necessarily correspond to salient features (i.e., landmarks do not necessarily represent anatomically significant features of an object). Training masks **102** may further include connectivity information between the points, which may be useful to reconstruct the surface and calculate normal vectors. A point set with connectivity information may be referred to as a mesh. The term landmarks may be associated with or used interchangeably with point distribution models (PDMs). Segmentation and intensity extraction circuitry **204** are not, however, limited to the foregoing example segmentation techniques. Other examples include, without limitation, medial models, Fourier surfaces, and spherical harmonics (SPHARMs).

Shape and intensity extraction circuitry **204** may generate training backgrounds **104** based on intensity data of images **202**. Training backgrounds **104** may include volumetric meshes that include points within an object for describing internal structures. Coordinates of the points may be collected into a vector that describes a volumetric shape. Where images **202** include images of bones, intensity data may represent bone density, which may be expressed, without limitation, in terms of Hounsfield units, bone mass density (BMD), or bone volume over total volume (BV/TV).

FIG. 3 is a flowchart of a method **300** of generating a SSAM based on training masks and training backgrounds, according to an embodiment. Due to the volume of data contained within training masks and training backgrounds, method **300** cannot practically be performed in a human mind. Rather, method **300** is performed by a machine (e.g., circuitry and/or a suitably programmed processor and memory). Method **300** is described below with reference to SSAM generator **100**. Method **300** is not, however, limited to the example of SSAM generator **100**.

At **302**, pre-processing circuitry **114** pre-processes training backgrounds **104** to provide pre-processed training backgrounds **136**. Pre-processing circuitry **114** may filter training backgrounds **104** (e.g., de-noising and/or clamping intensity values between a defined minimum bound and a maximum bound) and/or normalize training backgrounds **104** (e.g., normalize intensity values with a defined factor). Pre-processing circuitry **114** may be useful to ensure that training

backgrounds **104** are compatible with one another and/or are compatible with other aspects of SSAM generator **100**.

In order to generate SSAM **146**, orientations and dimensions of training masks **102** and training backgrounds **104** should correspond to one another, such that any sample (e.g., a pixel or voxel) of any of training masks **102** or training backgrounds **104** represents the same relative position in other training masks **102** or training backgrounds **104**. Such correspondence may be achieved by registering training masks **102** and training backgrounds **104** with reference mask **108**. Registration is described below with reference to **304** through **310** of FIG. 3, and with reference to re-orientation circuitry **109** and deformable mask registration circuitry **111** in FIG. 1.

At **304**, mask re-orientation circuitry **110** aligns or re-orient training masks **102** based on reference mask **108** to provide re-oriented training masks **130** and corresponding re-orientation parameters **132**. Mask re-orientation circuitry **110** may translate, rotate, and/or re-size training mask **102** until the respective training masks **102** align with reference mask **108** (e.g., within a threshold(s)). The re-orienting may be referred to as rigid registration. Mask re-orientation circuitry **110** may be useful to reduce or remove differences in positions/orientations of training masks **102** and reference mask **108**, which may be useful to avoid interpreting such differences as actual geometric variations amongst training masks **102**.

Mask re-orientation circuitry **110** may perform an iterative closest point (ICP) method, and may output re-orientation parameters **132** to include ICP transformation matrices for respective training masks **102**. The ICP method minimizes differences between two clouds of points by maintaining points of one cloud (i.e., reference mask **108**) fixed, while transforming points of the other cloud (i.e., training masks **102**) to best match reference mask **108**. The re-orientation (i.e., translation, rotation, and/or re-sizing) is iteratively estimated in order to minimize an error metric (e.g., a sum of squared differences between the coordinates of the respective points). Mask re-orientation circuitry **110** may convert training masks **102** and reference mask **108** to triangulated meshes, which may provide relatively fast and accurate results from the ICP algorithm. Alternatively, or additionally, mask re-orientation circuitry **110** may utilize scaling and/or a modified ICP algorithm.

At **306**, background re-orientation circuitry **116** re-orient (e.g., translates, rotates, and/or re-sizes) pre-processed training backgrounds **136** based on re-orientation parameters **132** (e.g., ICP transformation matrices) to provide re-oriented training backgrounds **138**.

At **308**, deformable mask registration circuitry **112** computes geometric differences/variations (e.g., biologically-induced variations) in shape between reference mask **108** and re-oriented training masks **130** as displacement fields **134**. Displacement fields **134** represent backward transforms that map from reference mask **108** to respective re-oriented training masks **130**. Deformable mask registration circuitry **112** may perform localized scaling of re-oriented training masks **130**.

In an embodiment, deformable mask registration circuitry **112** computes signed distance maps of re-oriented training masks **130**, and determines displacement fields **134** based on the signed distance maps (i.e., as approximations having pixel accuracy to Euclidean distances). Computing displacement fields **134** based on signed distance maps rather than mask volumes may improve performance and stability of the deformable mask registration process.

Deformable mask registration circuitry **112** may represent a displacement field **134** as an image with vector type pixels of N dimensions, where N is a dimension of reference mask **108**.

Deformable mask registration circuitry **112** may utilize a Diffeomorphic Demons deformable method that deformably registers re-oriented training masks **130** with reference mask **108** by computing displacement fields **134** that map re-oriented training masks **130** onto reference mask **108**. Diffeomorphic Demons is a non-parametric diffeomorphic image registration method, which is essentially an extension of a Demons method. The Demons method registers two images by computing a deformation field that maps a moving image onto a fixed image. The Demons method treats non-parametric image registration as an optimization problem that seeks the displacement of each pixel in order to obtain a reasonable alignment of the fixed and moving images. Diffeomorphic Demons uses a speed vector field instead of a deformation field use in the conventional Demons' expression to obtain a non-parametric diffeomorphic image registration.

In mathematics, a diffeomorphism is an isomorphism of smooth manifolds (an isomorphism is a structure-preserving mapping between two structures of the same type that can be reversed by an inverse mapping). A diffeomorphism is an invertible function that maps one differentiable manifold to another such that both the function and its inverse are differentiable. A diffeomorphic mapping system is a system designed to map, manipulate, and transfer information which is stored in multiple types of spatially distributed medical imagery.

Alternatively, or additionally, deformable mask registration circuitry **112** may utilize a free form deformation (FFD) method. The FFD method is widely used in image registration, and is often implemented using B-splines, in which the displacement of a point is represented as a linear combination of the displacements of a corresponding control point. Using a smooth B-spline basis, the transformations are implicitly regularized to ensure they are continuous and smooth. FFD registration uses a regular grid and is thus particularly suitable for intensity-based registration where a regular grid is easily defined.

At **310**, deformable background registration circuitry **118** deforms/warps re-oriented training backgrounds **138** based on displacement fields **134** computed at **308** to provide deformed training backgrounds **140**. Deformable background registration circuitry **118** essentially deforms re-oriented training backgrounds **138** to match the shape of reference mask **108**.

In an embodiment, SSAM generator **100** deformably registers re-oriented training masks **130** and re-oriented training backgrounds **138** iteratively, as illustrated at **311**. For example, in FIG. 1, deformable registration circuitry **111** may deformably register signed distance maps of re-oriented training masks **130** to provide an initial set of displacement fields **134-1**. Deformable background registration circuitry **118** may then generate an initial set of revised displacement fields **141-1** based on the initial set of displacement fields **134-1**. Deformable mask registration circuitry **112** may then generate a revised set of displacement fields **134-2** based on the initial set of revised displacement fields **141-1**. Deformable background registration circuitry **118** may then generate a revised set of displacement fields **141-2** based on the revised set of displacement fields **134-2**. The iterative process may continue for a predetermined number of iterations (i.e., n times), and/or until a threshold measure of refinement is obtained. At the conclusion of the iterative process,

deformable registration circuitry **111** outputs a final set of displacement fields **134** and a final set of deformed training backgrounds **140**.

At **312**, combining circuitry **120** combines (e.g., concatenate) deformed training backgrounds **140** and displacement fields **134**. Combining circuitry **120** may combine deformed training backgrounds **140** and displacement fields **134** in a matrix.

At **314**, scaling circuitry **122** scales an output **142** of combining circuitry **120**. Where output **142** includes a matrix, scaling circuitry **122** may divide rows of the matrix by the means or standard deviations of the respective rows. An output **144** of scaling circuitry **122** may include a scaled matrix of deformed training backgrounds **140** and displacement fields **134**. Scaling may be useful for principal component analysis (PCA), such as described below with reference to **316**.

At **316**, dimensionality reduction circuitry **124** reduces a dimensionality of output **144** of scaling circuitry **122** to provide SSAM **146**. Dimensionality reduction circuitry **124** may perform a principal component analysis (PCA) that provides SSAM **146** with a mean dataset, modes of variation (e.g., Eigen vectors), and weighting (e.g., Eigen values), where the modes of variation and the weighting reflect variations in the training objects relative to a mean of training population dataset **101**.

Dimensionality reduction circuitry **124** may also perform PCA separately for deformed training backgrounds **140** and displacement fields **134** (i.e., bypassing combining circuitry **120**, and scaling deformed training backgrounds **140** and displacement fields **134** separately), to generate separate shape and appearance models, which may be used or compared separately. Alternatively, method **300** may generate separate shape and appearance models in place of a SSAM. In this embodiment, method **300** may omit the combining at **312** (and SSAM generator **100** may omit combining circuitry **120**), perform the scaling at **134** separately for deformed training backgrounds **140** and displacement fields **134** with respective scaling circuitry, and perform PCM separately for the scaled deformed training backgrounds and displacement fields.

At **318**, SSAM application circuitry **126** applies or uses SSAM **146** in one or more applications. For example, and without limitation, SSAM application circuitry **126** may use SSAM **146** to generate virtual objects (i.e., masks and backgrounds), analyze variability in shape and material properties of the population of objects represented within training population dataset **101**, and/or predict missing information from a partial dataset of masks and backgrounds extracted from images of other objects. For example, wherein SSAM **146** includes a mean dataset, modes of variation, and weighting, SSAM application circuitry **126** may generate virtual objects for which shapes and intensities are based on the mean dataset, with variations based on the modes of variation and the weighting. In an embodiment, SSAM application circuitry **126** generates virtual objects by inverting displacement fields of SSAM **146**. For example, PCA circuitry (e.g., within dimensionality reduction circuitry **124**), may generate a covariance matrix that includes eigenvectors and eigenvalues, and SSAM application circuitry **126** may generate a virtual object by combining the eigenvectors and eigenvalues, an example of which is provided below.

Given a set of data points X , the PCA circuitry may compute a covariance matrix C as:

$$C = 1/(N - 1) * X^T * X,$$

where N is the number of data points and X^T is the transpose of X . The PCA circuitry may then compute eigenvectors and eigenvalues of C using an eigen decomposition:

$$C^{**} V = \Lambda * V,$$

where V is a matrix whose columns are the eigenvectors of C , and Λ is a diagonal matrix whose entries are the eigenvalues.

To generate a new sample, SSAM application circuitry **126** uses the eigenvectors and eigenvalues to compute a linear combination of the original data points. Given a set of weights w , the new sample may be computed as:

$$\text{new sample} = \text{mean} * w$$

SSAM application circuitry **126** may sort the eigenvectors and eigenvalues in decreasing order of importance to obtain the most significant modes of variability in the data. In practice, only the top K eigenvectors and eigenvalues may be used to generate new samples, where K is a user-specified parameter.

SSAM application circuitry **126** then extracts a displacement field and corresponding background from the covariance matrix C , inverts the displacement field that transforms the sample to its original image space, and uses the inverted displacement field to deform the reference mask and the extracted background to provide the virtual object.

An experimental SSAM was generated from a training set of CT scans of 15 pelvises. Experimental results are provided below with reference to FIGS. 5, 6A, and 6B. The experimental results are provided for illustrative purposes. Methods and systems disclosed herein are not limited to the experimental results. After building the experimental SSAM, synthetic (i.e., virtual) samples were generated using PCA. FIG. 4 is an image **400** of the synthetic samples. FIG. 4 shows shape geometries (i.e., masks) and corresponding background intensity distributions. FIG. 4 includes a mean model **402**, shapes **404** generated using -2 standard deviation, and shapes **406** generated using $+2$ standard deviation.

For these experimental results, the first eight principal modes, accounting for 95% of the total shape variation in which 48% variability was recorded by principal mode 1, 14.2% by mode 2, and 14% by mode 3, were found to represent variations in the shape morphology. These figures are provided for illustrative purposes. The generalization error is calculated with leave-one-out to measure how accurately the experimental SSAM can generate synthetic samples. The reconstruction error of the generated shape geometries was evaluated in term of point-to-surface method. The root mean square (RMS) is used to represent the reconstruction error.

A comparison of measured distances between three points of each of the synthetic samples and the training set of CT scans of the 15 pelvises was completed to indicate geometri-

cal differences between the synthetic samples generated using the experimental SSAM and the training set. The distances may be measured between selected anatomical landmarks of a pelvis (e.g., key points used to characterize a Pelvis). The comparison of the measured distances illustrates similarities between the training set and the synthetic samples. Having a good agreement between the training set and synthetic samples is an indicator of the quality of experimental SSAM.

FIG. 5A illustrates box plot distributions **500** for the experimental SSAM, according to an embodiment. Box plot distributions **500** are for distances between the posterior superior iliac spine and the pubic tubercle, and distances between the posterior superior iliac spine and the anterior superior iliac spine. Box plot distributions **500** include:

- distributions **502**, synthetic samples, posterior superior iliac spine—pubic tubercle;
- distributions **504**, training set, posterior superior iliac spine—pubic tubercle;
- distributions **506**, synthetic samples, posterior superior iliac spine—anterior superior iliac spine; and
- distributions **508**, training set, posterior superior iliac spine—anterior superior iliac spine.

FIG. 5B is an image of a representative synthetic pelvis **550** generated by the experimental SSAM (i.e., generated at **318** in FIG. 3).

FIG. 6 illustrates an example machine of a computer system **600** within which a set of instructions, for causing the machine to perform any one or more of the methodologies discussed herein, may be executed. In alternative implementations, the machine may be connected (e.g., networked) to other machines in a LAN, an intranet, an extranet, and/or the Internet. The machine may operate in the capacity of a server or a client machine in client-server network environment, as a peer machine in a peer-to-peer (or distributed) network environment, or as a server or a client machine in a cloud computing infrastructure or environment.

The machine may be a personal computer (PC), a tablet PC, a set-top box (STB), a Personal Digital Assistant (PDA), a cellular telephone, a web appliance, a server, a network router, a switch or bridge, or any machine capable of executing a set of instructions (sequential or otherwise) that specify actions to be taken by that machine. Further, while a single machine is illustrated, the term “machine” shall also be taken to include any collection of machines that individually or jointly execute a set (or multiple sets) of instructions to perform any one or more of the methodologies discussed herein.

The example computer system **600** includes a processing device **602**, a main memory **604** (e.g., read-only memory (ROM), flash memory, dynamic random access memory (DRAM) such as synchronous DRAM (SDRAM), a static memory **606** (e.g., flash memory, static random access memory (SRAM), etc.), and a data storage device **618**, which communicate with each other via a bus **630**.

Processing device **602** represents one or more processors such as a microprocessor, a central processing unit, or the like. More particularly, the processing device may be complex instruction set computing (CISC) microprocessor, reduced instruction set computing (RISC) microprocessor, very long instruction word (VLIW) microprocessor, or a processor implementing other instruction sets, or processors implementing a combination of instruction sets. Processing device **602** may also be one or more special-purpose processing devices such as an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a digital signal processor (DSP), network processor, or the

like. The processing device **602** may be configured to execute instructions **626** for performing the operations and steps described herein.

The computer system **600** may further include a network interface device **608** to communicate over the network **620**. The computer system **600** also may include a video display unit **610** (e.g., a liquid crystal display (LCD) or a cathode ray tube (CRT)), an alphanumeric input device **612** (e.g., a keyboard), a cursor control device **614** (e.g., a mouse), a graphics processing unit **622**, a signal generation device **616** (e.g., a speaker), graphics processing unit **622**, video processing unit **628**, and audio processing unit **632**.

The data storage device **618** may include a machine-readable storage medium **624** (also known as a non-transitory computer-readable medium) on which is stored one or more sets of instructions **626** or software embodying any one or more of the methodologies or functions described herein. The instructions **626** may also reside, completely or at least partially, within the main memory **604** and/or within the processing device **602** during execution thereof by the computer system **600**, the main memory **604** and the processing device **602** also constituting machine-readable storage media.

In some implementations, the instructions **626** include instructions to implement functionality corresponding to the present disclosure. While the machine-readable storage medium **624** is shown in an example implementation to be a single medium, the term “machine-readable storage medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, and/or associated caches and servers) that store the one or more sets of instructions. The term “machine-readable storage medium” shall also be taken to include any medium that is capable of storing or encoding a set of instructions for execution by the machine and that cause the machine and the processing device **602** to perform any one or more of the methodologies of the present disclosure. The term “machine-readable storage medium” shall accordingly be taken to include, but not be limited to, solid-state memories, optical media, and magnetic media.

Some portions of the preceding detailed descriptions have been presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the ways used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm may be a sequence of operations leading to a desired result. The operations are those requiring physical manipulations of physical quantities. Such quantities may take the form of electrical or magnetic signals capable of being stored, combined, compared, and otherwise manipulated. Such signals may be referred to as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the present disclosure, it is appreciated that throughout the description, certain terms refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage devices.

13

The present disclosure also relates to an apparatus for performing the operations herein. This apparatus may be specially constructed for the intended purposes, or it may include a computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, each coupled to a computer system bus.

The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various other systems may be used with programs in accordance with the teachings herein, or it may prove convenient to construct a more specialized apparatus to perform the method. In addition, the present disclosure is not described with reference to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the disclosure as described herein.

The present disclosure may be provided as a computer program product, or software, that may include a machine-readable medium having stored thereon instructions, which may be used to program a computer system (or other electronic devices) to perform a process according to the present disclosure. A machine-readable medium includes any mechanism for storing information in a form readable by a machine (e.g., a computer). For example, a machine-readable (e.g., computer-readable) medium includes a machine (e.g., a computer) readable storage medium such as a read only memory ("ROM"), random access memory ("RAM"), magnetic disk storage media, optical storage media, flash memory devices, etc.

In the foregoing disclosure, implementations of the disclosure have been described with reference to specific example implementations thereof. It will be evident that various modifications may be made thereto without departing from the broader spirit and scope of implementations of the disclosure as set forth in the following claims. Where the disclosure refers to some elements in the singular tense, more than one element can be depicted in the figures and like elements are labeled with like numerals. The disclosure and drawings are, accordingly, to be regarded in an illustrative sense rather than a restrictive sense.

What is claimed is:

1. A machine-implemented method, comprising:

receiving a reference mask, training masks, and training backgrounds, wherein the reference mask represents a 3-dimensional shape of a reference object, wherein the training masks represent external surfaces of training objects, wherein the training backgrounds comprise intensity data of the training objects, and wherein the intensity data represents one or more of color and texture;

re-orienting the training masks to align the training masks with the reference mask to provide re-orientation parameters for the training masks;

deforming the re-oriented training masks based on the reference mask to provide displacement fields indicative of differences between a 3-dimensional shape of the reference mask and 3-dimensional shapes of the re-oriented training masks;

14

re-orienting the training backgrounds based on the re-orientation parameters determined for the training masks to provide re-oriented training backgrounds;

deforming the re-oriented training backgrounds based on the displacement fields of the respective training masks to provide deformed training backgrounds;

combining the deformed training backgrounds and the displacement fields; and

reducing a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model (SSAM).

2. The method of claim 1, wherein the re-orienting training masks comprises:

converting the training masks and the reference mask to triangulated meshes; and

re-orienting the triangulated meshes of the training masks to the triangulated meshes of the reference mask based on an iterative closest point method to provide the re-orientation parameters to include iterative closest point transformation matrices.

3. The method of claim 1, wherein the deforming the re-oriented training masks comprises:

computing signed distance maps of the re-oriented training masks and the reference mask; and

computing the displacement fields based on the signed distance maps.

4. The method of claim 3, wherein the computing the displacement fields comprises computing the displacement fields with a diffeomorphic demons deformable method.

5. The method of claim 3, wherein the deforming the re-oriented training masks further comprises representing the displacement fields as images having vector-type pixels with N elements, where N is a dimensionality of the reference mask.

6. The method of claim 3, wherein:

the combining comprises combining the deformed training backgrounds and the displacement fields in a matrix; and

the method further comprises scaling the matrix, wherein the scaling comprises computing means of rows of the matrix and dividing the rows of the matrix by the means of the respective rows.

7. The method of claim 6, wherein the reducing the dimensionality comprises:

reducing a dimensionality of the matrix based on principal component analysis to provide the statistical shape and appearance model to include a mean dataset, modes of variation, and weighting, wherein the modes of variation and the weighting reflect variations in the objects relative to a mean of the objects.

8. The method of claim 3, further comprising:

iteratively refining the displacement fields and the deformed training backgrounds based on one another to provide a refined set of deformed training backgrounds and a refined set of displacement fields;

wherein the combining comprises combining the refined set of deformed training backgrounds and the refined set of displacement fields.

9. The method of claim 1, further comprising using the statistical shape and appearance model to perform one or more of:

generate virtual objects based on variations amongst the training masks and the training backgrounds;

analyze variability in shape and material properties of the training objects based on variations amongst the training masks and the training backgrounds; and

15

predict missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

10. A non-transitory computer readable medium encoded with a computer program that comprises instructions to cause a processor to:

compute signed distance maps based on training masks and of a reference mask, wherein the training masks represent 3-dimensional shapes of a population of objects extracted from 3-dimensional images of the objects, and wherein the reference mask represents a 3-dimensional shape of a reference object;

compute displacement fields for the training masks based on the respective signed distance maps, wherein the displacement fields represent geometric differences between the reference mask and the training masks;

deform training backgrounds based on the displacement fields computed for the training masks to provide deformed training backgrounds, wherein the training backgrounds comprise volumetric intensity data extracted from the 3-dimensional images of the objects, and wherein the intensity data represents one or more of color and texture;

combine the deformed training backgrounds and the displacement fields; and

reduce a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model (SSAM).

11. The non-transitory computer readable medium of claim 10, further comprising instructions to cause the processor to:

compute the displacement fields with a diffeomorphic demons deformable method.

12. The non-transitory computer readable medium of claim 10, further comprising instructions to cause the processor to:

represent the displacement fields as images having vector-type pixels with N elements, where N is a dimensionality of the reference mask.

13. The non-transitory computer readable medium of claim 10, further comprising instructions to cause the processor to:

combine the deformed training backgrounds and the displacement fields in a matrix.

14. The non-transitory computer readable medium of claim 13, further comprising instructions to cause the processor to scale the matrix, including to:

compute means of rows of the matrix; and
divide the rows of the matrix by the means of the respective rows.

15. The non-transitory computer readable medium of claim 13, further comprising instructions to cause the processor to:

reduce a dimensionality of the matrix based on principal component analysis to provide the statistical shape and appearance model to include a mean dataset, modes of variation, and weighting, wherein the modes of variation and the weighting reflect variations in the objects relative to a mean of the objects.

16. The non-transitory computer readable medium of claim 10, further comprising instructions to cause the processor to use the statistical shape and appearance model to perform one or more of:

16

generate virtual objects based on variations amongst the training masks and the training backgrounds;

analyze variability in shape and material properties of the population of objects based on variations amongst the training masks and the training backgrounds; and

predict missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

17. An integrated circuit (IC) device, comprising:

re-orientation circuitry to align training masks with a reference mask to provide re-orientation parameters for the training masks, and to re-orient training backgrounds based on the re-orientation parameters determined for the training masks to provide re-oriented training backgrounds, wherein the training masks represent external surfaces of training objects, wherein the training backgrounds comprise intensity data of the training objects, and wherein the intensity data represents one or more of color and texture;

deformable registration circuitry to deform the re-oriented training masks based on the reference mask to provide displacement fields indicative of differences between a 3-dimensional shape of the reference mask and 3-dimensional shapes of the re-oriented training masks, and to deform the re-oriented training backgrounds based on the displacement fields of the respective training masks to provide deformed training backgrounds;

combining circuitry to combine the deformed training backgrounds and the displacement fields; and

dimensionality reduction circuitry configured to reduce a dimensionality of the combined deformed training backgrounds and displacement fields to provide a statistical shape and appearance model (SSAM).

18. The IC device of claim 17, wherein the deformable registration circuitry is further configured to deform the re-oriented training masks and the re-oriented training backgrounds by:

deformably registering signed distance maps of the re-oriented training masks to provide an initial set of displacement fields;

deformably registering background intensity values of the re-oriented training backgrounds based on the initial set of displacement fields to provide an initial set of deformed training backgrounds and a refined set of displacement fields;

generating a revised set of displacement fields based on the revised set of displacement fields; and

generating a revised set of deformed training backgrounds based on the revised set of displacement fields,

deform the set of re-oriented training backgrounds based on the refined set of displacement fields to provide a final set of deformed training backgrounds.

19. The IC device of claim 17, further comprising SSAM application circuitry configured to perform one or more of:

generate virtual objects based on variations amongst the training masks and the training backgrounds;

analyze variability in shape and material properties of the training objects based on variations amongst the training masks and the training backgrounds; and

predict missing information from a partial dataset of masks and backgrounds extracted from 3-dimensional images of other objects.

* * * * *