

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407219
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Macaluso; Anthony

Vehicle energy generation system

Abstract

A system may generate energy in response to a movement of a vehicle. The system may include an energy recovery mechanism, a generator, an energy storage, and a motor. The energy recovery mechanism may include one or more rollers configured to rotate in response to a rotation of a drive shaft of the vehicle. The generator may be rotatably coupled to the roller and may be configured to generate an electrical output in response to a rotation of the roller. The energy storage may be electrically coupled with the generator and may be configured to receive a portion of the electrical output to store as energy. The motor may be electrically coupled with the energy storage and may be configured to receive a portion of the energy.

Inventors:	Macaluso; Anthony (San Diego, CA)
Applicant:	Macaluso; Anthony (San Diego, CA)
Family ID:	92802304
Appl. No.:	18/676279
Filed:	May 28, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240322647 A1	Sep. 26, 2024

Related U.S. Application Data

continuation parent-doc US 18381120 20231017 US 12003167 child-doc US 18676279
continuation parent-doc US 18243524 20230907 US 11955875 20240409 child-doc US 18381120
us-provisional-application US 63487515 20230228

Publication Classification

Int. Cl.: H02K7/18 (20060101); H02J7/14 (20060101)

U.S. Cl.:

CPC H02K7/1846 (20130101); H02J7/14 (20130101); H02J2207/50 (20200101)

Field of Classification Search

CPC: H02K (49/10); H02K (7/003); H02K (47/14)

USPC: 310/40R; 310/67A; 310/75C

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1751577	12/1929	Cole	105/109	B61D 43/00
2451965	12/1947	Longenecker	N/A	N/A
2660443	12/1952	Miller	N/A	N/A
3859589	12/1974	Rush	N/A	N/A
3891044	12/1974	Tiede	N/A	N/A
3943370	12/1975	Watanabe	N/A	N/A
3961678	12/1975	Hirano et al.	N/A	N/A
3978936	12/1975	Schwartz	N/A	N/A
3990098	12/1975	Mastrangelo	N/A	N/A
4214160	12/1979	Fies et al.	N/A	N/A
4314160	12/1981	Boodman et al.	N/A	N/A
4351405	12/1981	Fields	N/A	N/A
4364448	12/1981	Ikuma	N/A	N/A
4404513	12/1982	Campen	N/A	N/A
4476947	12/1983	Rynbrandt	N/A	N/A
4539496	12/1984	Thomas et al.	N/A	N/A
4579188	12/1985	Facer	N/A	N/A
4602694	12/1985	Weldin	N/A	N/A
5045646	12/1990	Musachio	N/A	N/A
5078227	12/1991	Becker	N/A	N/A
5086857	12/1991	Dale	N/A	N/A
5105776	12/1991	Tsuchiya	N/A	N/A
5316101	12/1993	Gannon	N/A	N/A
5412293	12/1994	Minezawa et al.	N/A	N/A
5491390	12/1995	McGreen	N/A	N/A
5671821	12/1996	McGreen	N/A	N/A
5680907	12/1996	Weihe	N/A	N/A
5710504	12/1997	Pascual et al.	N/A	N/A
5735363	12/1997	Horovitz et al.	N/A	N/A
5767663	12/1997	Lu	N/A	N/A
5921334	12/1998	Al-Dokhi	N/A	N/A
5982152	12/1998	Watanabe	N/A	N/A
5992553	12/1998	Morrison	N/A	N/A

6008626	12/1998	Sato	N/A	N/A
6064178	12/1999	Miller	N/A	N/A
6065557	12/1999	von Keyserling	N/A	N/A
6220381	12/2000	Damron et al.	N/A	N/A
6390215	12/2001	Kodama	N/A	N/A
6502842	12/2002	Ko	N/A	N/A
6531838	12/2002	Parks	N/A	N/A
6703716	12/2003	Chiu	N/A	N/A
6717280	12/2003	Bienville	N/A	N/A
6987327	12/2005	Lucatero	N/A	N/A
7145256	12/2005	Koharcheck	N/A	N/A
7183746	12/2006	Carter	N/A	N/A
7279799	12/2006	McCauley	N/A	N/A
7514803	12/2008	Wilks	N/A	N/A
7547980	12/2008	Harrison	N/A	N/A
7560904	12/2008	Alvarez-Troncoso	N/A	N/A
7628236	12/2008	Brown	N/A	N/A
7667438	12/2009	Ashtiani	N/A	N/A
7753010	12/2009	Rutledge	N/A	N/A
7913783	12/2010	Elmaleh	N/A	N/A
8063609	12/2010	Salasoo et al.	N/A	N/A
8089168	12/2011	Chevrette	N/A	N/A
8206263	12/2011	Tsuchikawa	N/A	N/A
8253359	12/2011	Tanaka	N/A	N/A
8347999	12/2012	Koelsch et al.	N/A	N/A
8573346	12/2012	Duignan	N/A	N/A
8643201	12/2013	Scott	N/A	N/A
8651209	12/2013	Hartjen, III	N/A	N/A
8712620	12/2013	Jackson	N/A	N/A
8723344	12/2013	Dierickx	N/A	N/A
8796987	12/2013	Scheucher	N/A	N/A
8872368	12/2013	Kim et al.	N/A	N/A
8907631	12/2013	Gurries	N/A	N/A
8928281	12/2014	Murase et al.	N/A	N/A
9048513	12/2014	Butzmann	N/A	N/A
9136729	12/2014	Ashinghurst	N/A	N/A
9236761	12/2015	Strothmann	N/A	N/A
9242698	12/2015	Frieden	N/A	N/A
9321357	12/2015	Caldeira et al.	N/A	N/A
9376971	12/2015	Luther et al.	N/A	N/A
9415660	12/2015	Koelsch	N/A	N/A
9457666	12/2015	Caldeira et al.	N/A	N/A
9575743	12/2016	Chun	N/A	N/A
9656660	12/2016	Baliff	N/A	N/A
9726240	12/2016	David et al.	N/A	N/A
9793833	12/2016	Johnson	N/A	N/A
9816475	12/2016	Buchanan et al.	N/A	N/A
9904948	12/2017	Taira	N/A	N/A
9981553	12/2017	Schafer et al.	N/A	N/A
10077056	12/2017	Fields et al.	N/A	N/A

10077752	12/2017	Lee et al.	N/A	N/A
10157050	12/2017	Kotani et al.	N/A	N/A
10252727	12/2018	Braun	N/A	N/A
10293702	12/2018	Tu et al.	N/A	N/A
10436167	12/2018	Namuduri	N/A	N/A
10513180	12/2018	Quill	N/A	N/A
10586024	12/2019	Patton	N/A	N/A
10664917	12/2019	Wasserman	N/A	N/A
10666077	12/2019	Dharia	N/A	N/A
10787089	12/2019	Macaluso	N/A	N/A
10795380	12/2019	Patton	N/A	N/A
10797564	12/2019	Griggs	N/A	N/A
10850713	12/2019	O'Hara	N/A	N/A
10889186	12/2020	Schutt	N/A	N/A
10903679	12/2020	Schmalzrieth et al.	N/A	N/A
11007878	12/2020	Kamino et al.	N/A	N/A
11072254	12/2020	Macaluso	N/A	N/A
11117481	12/2020	Macaluso	N/A	N/A
11130415	12/2020	Macaluso	N/A	N/A
11133729	12/2020	Macaluso	N/A	N/A
11159042	12/2020	Familiant et al.	N/A	N/A
11222750	12/2021	Macaluso	N/A	N/A
11289974	12/2021	Macaluso	N/A	N/A
11299054	12/2021	Macaluso	N/A	N/A
11318856	12/2021	Macaluso	N/A	N/A
11322311	12/2021	Macaluso	N/A	N/A
11362525	12/2021	Feng	N/A	N/A
11368031	12/2021	Griifiths et al.	N/A	N/A
11431225	12/2021	Macaluso	N/A	N/A
11432123	12/2021	Macaluso	N/A	N/A
11458853	12/2021	Macaluso	N/A	N/A
11472306	12/2021	Macaluso	N/A	N/A
11548399	12/2022	Macaluso	N/A	N/A
11551486	12/2022	Everett et al.	N/A	N/A
11577606	12/2022	Macaluso	N/A	B60K 25/08
11587740	12/2022	Macaluso	N/A	N/A
11615923	12/2022	Macaluso	N/A	N/A
11618332	12/2022	Macaluso	N/A	N/A
11626775	12/2022	Macaluso	N/A	N/A
11627449	12/2022	Macaluso	N/A	N/A
11628724	12/2022	Macaluso	N/A	N/A
11641572	12/2022	Macaluso	N/A	N/A
11685276	12/2022	Macaluso	N/A	N/A
11722869	12/2022	Macaluso	N/A	N/A
11738641	12/2022	Macaluso	N/A	N/A
11757332	12/2022	Macaluso	N/A	N/A
11780466	12/2022	Shah	N/A	N/A
11785433	12/2022	Macaluso	N/A	N/A
11837411	12/2022	Macaluso	N/A	N/A

11850963	12/2022	Macaluso	N/A	N/A
11897355	12/2023	Macaluso	N/A	N/A
11897506	12/2023	Shah	N/A	N/A
11904708	12/2023	Macaluso	N/A	N/A
11916466	12/2023	Macaluso	N/A	N/A
11919387	12/2023	Macaluso	N/A	N/A
11919412	12/2023	Macaluso	N/A	N/A
11919413	12/2023	Macaluso	N/A	N/A
11938825	12/2023	Sukhatankar et al.	N/A	N/A
11955875	12/2023	Macaluso	N/A	N/A
11970073	12/2023	Macaluso	N/A	N/A
11985579	12/2023	Macaluso	N/A	N/A
11999250	12/2023	Macaluso	N/A	N/A
12003167	12/2023	Macaluso	N/A	N/A
12090844	12/2023	Macaluso	N/A	N/A
12096324	12/2023	Macaluso	N/A	N/A
12157366	12/2023	Macaluso	N/A	N/A
2003/0071464	12/2002	Chiu	N/A	N/A
2003/0139859	12/2002	Hanada	N/A	N/A
2003/0184258	12/2002	VonderHaar	N/A	N/A
2003/0222502	12/2002	Takahashi	N/A	N/A
2004/0012205	12/2003	Sua-An	N/A	N/A
2004/0245783	12/2003	Gilbreth	N/A	N/A
2004/0257043	12/2003	Takaoka	N/A	N/A
2004/0262062	12/2003	Berberi et al.	N/A	N/A
2005/0093370	12/2004	Amano et al.	N/A	N/A
2005/0224263	12/2004	Vasilantone	N/A	N/A
2005/0284676	12/2004	King	N/A	N/A
2006/0091857	12/2005	Nakanishi	N/A	N/A
2006/0238258	12/2005	D'Amore	N/A	N/A
2006/0250902	12/2005	Bender	N/A	N/A
2007/0013244	12/2006	Kinkaid	N/A	N/A
2007/0024266	12/2006	Yurgil	N/A	N/A
2007/0075677	12/2006	Alvarez-Troncoso	N/A	N/A
2007/0090702	12/2006	Schiller	N/A	N/A
2007/0164693	12/2006	King	N/A	N/A
2007/0187957	12/2006	Harrison	N/A	N/A
2007/0208468	12/2006	Sankaran et al.	N/A	N/A
2008/0053716	12/2007	Scheucher	N/A	N/A
2008/0066979	12/2007	Carter	N/A	N/A
2008/0215700	12/2007	Pillar et al.	N/A	N/A
2008/0223637	12/2007	Bartilson	N/A	N/A
2008/0281663	12/2007	Hakim	N/A	N/A
2008/0289890	12/2007	Stoltzfus	N/A	N/A
2008/0297109	12/2007	Sandberg et al.	N/A	N/A
2009/0033254	12/2008	Nagashima et al.	N/A	N/A
2009/0079417	12/2008	Mort et al.	N/A	N/A
2009/0145674	12/2008	Lee	N/A	N/A
2009/0168305	12/2008	Fleig et al.	N/A	N/A
2009/0194998	12/2008	Lin	N/A	N/A

2009/0206779	12/2008	Wobben	N/A	N/A
2009/0230766	12/2008	Miyama	N/A	N/A
2009/0250276	12/2008	Goodwin et al.	N/A	N/A
2009/0256450	12/2008	Chevrette	N/A	N/A
2009/0261787	12/2008	Cegnar	N/A	N/A
2009/0295224	12/2008	Kobayashi	N/A	N/A
2010/0001866	12/2009	Ichikawa	N/A	N/A
2010/0019718	12/2009	Salasoo et al.	N/A	N/A
2010/0076825	12/2009	Sato	N/A	N/A
2010/0116574	12/2009	Gilmore	N/A	N/A
2010/0117600	12/2009	Fazakas	N/A	N/A
2010/0164334	12/2009	Schiller	N/A	N/A
2010/0168945	12/2009	Ohno	N/A	N/A
2010/0222952	12/2009	Yamaguchi	N/A	N/A
2010/0270810	12/2009	Liebermann et al.	N/A	N/A
2010/0327600	12/2009	Koelsch	N/A	N/A
2011/0012560	12/2010	Sakakibara et al.	N/A	N/A
2011/0014501	12/2010	Scheucher	N/A	N/A
2011/0025068	12/2010	Campbell	N/A	N/A
2011/0083918	12/2010	Kshatriya	N/A	N/A
2011/0089760	12/2010	Castelaz et al.	N/A	N/A
2011/0100735	12/2010	Flett	N/A	N/A
2011/0106329	12/2010	Donnelly et al.	N/A	N/A
2011/0140518	12/2010	Hattori	N/A	N/A
2011/0163717	12/2010	Gale	N/A	N/A
2011/0167455	12/2010	Gao	N/A	N/A
2011/0189507	12/2010	Reis	N/A	N/A
2011/0200193	12/2010	Blitz et al.	N/A	N/A
2011/0231044	12/2010	Fassnacht	N/A	N/A
2011/0302078	12/2010	Failing	N/A	N/A
2011/0320074	12/2010	Erlston et al.	N/A	N/A
2012/0012406	12/2011	Stoicoviciu	N/A	N/A
2012/0037438	12/2011	Schultz	N/A	N/A
2012/0054095	12/2011	Lesandro et al.	N/A	N/A
2012/0068537	12/2011	Hintz et al.	N/A	N/A
2012/0129577	12/2011	Vaknin	N/A	N/A
2012/0139487	12/2011	Kim	N/A	N/A
2012/0237799	12/2011	Jiang	N/A	N/A
2012/0309455	12/2011	Klose et al.	N/A	N/A
2012/0330486	12/2011	Jingu	N/A	N/A
2013/0015668	12/2012	Chang et al.	N/A	N/A
2013/0049459	12/2012	Hatanaka	N/A	N/A
2013/0067253	12/2012	Tsuda	N/A	N/A
2013/0081886	12/2012	Jaberian	N/A	N/A
2013/0091033	12/2012	Goodman	N/A	N/A
2013/0096759	12/2012	Breton et al.	N/A	N/A
2013/0119665	12/2012	Berberi	N/A	N/A
2013/0257144	12/2012	Caldeira et al.	N/A	N/A
2013/0257145	12/2012	Caldeira et al.	N/A	N/A
2013/0261907	12/2012	McQuade	N/A	N/A

2013/0266826	12/2012	Cowperthwaite	N/A	N/A
2013/0307479	12/2012	Kim	N/A	N/A
2013/0332014	12/2012	Jackson	N/A	N/A
2014/0001905	12/2013	Schawitsch	310/113	H02K 7/006
2014/0091573	12/2013	Berbari	N/A	N/A
2014/0132063	12/2013	Kakiuchi	N/A	N/A
2014/0132155	12/2013	Strothmann	N/A	N/A
2014/0197780	12/2013	Imamura	N/A	N/A
2014/0210398	12/2013	Powell	N/A	N/A
2014/0244082	12/2013	Caron	N/A	N/A
2014/0266004	12/2013	Andrews, Jr.	N/A	N/A
2014/0266070	12/2013	Kurtzman	N/A	N/A
2014/0283092	12/2013	Mowatt et al.	N/A	N/A
2014/0285209	12/2013	Stichowski et al.	N/A	N/A
2014/0350764	12/2013	Arai et al.	N/A	N/A
2014/0368041	12/2013	Tu et al.	N/A	N/A
2015/0008867	12/2014	Smychkovich	N/A	N/A
2015/0014991	12/2014	Al Jaeedi et al.	N/A	N/A
2015/0054428	12/2014	Osborne	N/A	N/A
2015/0089981	12/2014	Renfro	N/A	N/A
2015/0210287	12/2014	Penilla et al.	N/A	N/A
2015/0222553	12/2014	Macdonald et al.	N/A	N/A
2015/0249362	12/2014	Bridgelall et al.	N/A	N/A
2015/0260835	12/2014	Widmer et al.	N/A	N/A
2015/0262154	12/2014	Wolfson	N/A	N/A
2015/0343909	12/2014	Hikiri	N/A	N/A
2015/0346233	12/2014	Slepov	N/A	N/A
2015/0347121	12/2014	Harumoto	N/A	N/A
2015/0363855	12/2014	Wu et al.	N/A	N/A
2016/0034952	12/2015	Parkin et al.	N/A	N/A
2016/0071338	12/2015	McQuade et al.	N/A	N/A
2016/0089981	12/2015	Kodawara	N/A	N/A
2016/0105020	12/2015	Guo	N/A	N/A
2016/0111907	12/2015	Lynds	N/A	N/A
2016/0144720	12/2015	Nakabayashi	N/A	N/A
2016/0164373	12/2015	Liao et al.	N/A	N/A
2016/0185243	12/2015	Zhou	N/A	N/A
2016/0189311	12/2015	Erickson et al.	N/A	N/A
2016/0207418	12/2015	Bergstrom	N/A	N/A
2016/0236578	12/2015	Liao	N/A	N/A
2016/0243960	12/2015	Wood	N/A	N/A
2016/0297317	12/2015	Huang et al.	N/A	N/A
2016/0298589	12/2015	Setterberg	N/A	N/A
2016/0348788	12/2015	Lemmers	N/A	N/A
2017/0036551	12/2016	Wu	N/A	N/A
2017/0063124	12/2016	Yu et al.	N/A	N/A
2017/0077534	12/2016	Guidry et al.	N/A	N/A
2017/0086084	12/2016	Jarvis	N/A	N/A
2017/0117720	12/2016	Yung	N/A	N/A

2017/0131999	12/2016	Dolby et al.	N/A	N/A
2017/0142766	12/2016	Kim	N/A	N/A
2017/0176540	12/2016	Omi	N/A	N/A
2017/0190261	12/2016	Cheng	N/A	H02J 9/005
2017/0191459	12/2016	Zhang	N/A	N/A
2017/0217442	12/2016	Rios, III	N/A	N/A
2017/0259764	12/2016	Da Silva Carvalho	N/A	N/A
2017/0302094	12/2016	Lynds	N/A	N/A
2017/0305424	12/2016	Augst	N/A	N/A
2017/0363433	12/2016	Tennent et al.	N/A	N/A
2017/0366017	12/2016	Clay et al.	N/A	N/A
2017/0366112	12/2016	Zhou	N/A	N/A
2018/0009329	12/2017	Tellez	N/A	N/A
2018/0012196	12/2017	Ricci	N/A	N/A
2018/0062555	12/2017	Sagawa	N/A	N/A
2018/0083469	12/2017	Bauer et al.	N/A	N/A
2018/0126866	12/2017	Nozawa	N/A	N/A
2018/0154779	12/2017	Chol	N/A	N/A
2018/0156144	12/2017	Inoue	N/A	N/A
2018/0166750	12/2017	Chang	N/A	N/A
2018/0189049	12/2017	Madrid	N/A	N/A
2018/0198846	12/2017	Srinivasan	N/A	N/A
2018/0204173	12/2017	Painter et al.	N/A	N/A
2018/0204253	12/2017	Painter et al.	N/A	N/A
2018/0204281	12/2017	Painter et al.	N/A	N/A
2018/0205242	12/2017	Kelly-Morgan et al.	N/A	N/A
2018/0215272	12/2017	Vitullo et al.	N/A	N/A
2018/0254732	12/2017	Smolenaers	N/A	N/A
2018/0312159	12/2017	Jent, II	N/A	N/A
2018/0328745	12/2017	Nagy et al.	N/A	N/A
2018/0351397	12/2017	Aharoni	N/A	N/A
2018/0370537	12/2017	Wu	N/A	N/A
2019/0001804	12/2018	Wilhide	N/A	N/A
2019/0004580	12/2018	Wilhide	N/A	N/A
2019/0044359	12/2018	Gordon et al.	N/A	N/A
2019/0077254	12/2018	Stanley	N/A	N/A
2019/0081502	12/2018	Botts	N/A	N/A
2019/0103639	12/2018	Guglielmo et al.	N/A	N/A
2019/0138952	12/2018	Han	N/A	N/A
2019/0140245	12/2018	Mensch	N/A	N/A
2019/0176802	12/2018	Kim	N/A	N/A
2019/0184843	12/2018	Jung et al.	N/A	N/A
2019/0199104	12/2018	Shim	N/A	N/A
2019/0202429	12/2018	Richter	N/A	N/A
2019/0212997	12/2018	Sangameswaran et al.	N/A	N/A
2019/0215376	12/2018	Kang	N/A	N/A
2019/0217720	12/2018	Treharne et al.	N/A	N/A
2019/0245375	12/2018	Schmalzrieth et al.	N/A	N/A

2019/0263385	12/2018	Zhou	N/A	N/A
2019/0292973	12/2018	Jiang et al.	N/A	N/A
2019/0296541	12/2018	Mensch	N/A	N/A
2019/0308510	12/2018	Beaurepaire	N/A	N/A
2019/0329650	12/2018	Quill	N/A	N/A
2019/0351895	12/2018	Ben-Ari	N/A	N/A
2019/0351899	12/2018	Adam	N/A	N/A
2019/0351948	12/2018	Derissaint	N/A	N/A
2019/0353710	12/2018	Rocci	N/A	N/A
2019/0359080	12/2018	Hellgren	N/A	N/A
2019/0362922	12/2018	Bae et al.	N/A	N/A
2019/0383627	12/2018	Nangeroni et al.	N/A	N/A
2020/0006716	12/2019	Wagoner	N/A	N/A
2020/0039379	12/2019	Schlosser	N/A	N/A
2020/0062138	12/2019	Smolenaers	N/A	N/A
2020/0063640	12/2019	Lee	N/A	N/A
2020/0094695	12/2019	Bowman	N/A	N/A
2020/0101858	12/2019	Kuroda	N/A	N/A
2020/0136414	12/2019	Patsos	N/A	N/A
2020/0153351	12/2019	Jiao	N/A	N/A
2020/0174780	12/2019	Gintz	N/A	N/A
2020/0184591	12/2019	Balu et al.	N/A	N/A
2020/0186620	12/2019	Golgiri et al.	N/A	N/A
2020/0202645	12/2019	Gintz	N/A	N/A
2020/0203986	12/2019	Barreau	N/A	N/A
2020/0204702	12/2019	Park	N/A	N/A
2020/0207209	12/2019	Engel	N/A	N/A
2020/0226850	12/2019	Bower	N/A	N/A
2020/0238929	12/2019	Wippler	N/A	N/A
2020/0241555	12/2019	Dogishi	N/A	N/A
2020/0244088	12/2019	Will et al.	N/A	N/A
2020/0249822	12/2019	Penilla	N/A	N/A
2020/0258325	12/2019	Maria	N/A	N/A
2020/0265480	12/2019	Swinson	N/A	N/A
2020/0276904	12/2019	Deaton	N/A	N/A
2020/0277021	12/2019	Biderman	N/A	N/A
2020/0294401	12/2019	Kerecsen	N/A	N/A
2020/0295412	12/2019	Chen	N/A	N/A
2020/0324763	12/2019	Switkes et al.	N/A	N/A
2020/0353839	12/2019	Tarchinski et al.	N/A	N/A
2020/0353882	12/2019	Beiser	N/A	N/A
2020/0376967	12/2019	Furukawa	N/A	N/A
2020/0381784	12/2019	Yamamoto	N/A	N/A
2020/0384879	12/2019	Ebisu et al.	N/A	N/A
2021/0001737	12/2020	Hoess et al.	N/A	N/A
2021/0065073	12/2020	Maeda et al.	N/A	N/A
2021/0080943	12/2020	Iwamoto et al.	N/A	N/A
2021/0094433	12/2020	Badger, II	N/A	N/A
2021/0110323	12/2020	Munoz et al.	N/A	N/A
2021/0157571	12/2020	Ogawa	N/A	N/A

2021/0167988	12/2020	Harata et al.	N/A	N/A
2021/0173411	12/2020	Rao et al.	N/A	N/A
2021/0173635	12/2020	Shin	N/A	N/A
2021/0183175	12/2020	Dunger	N/A	N/A
2021/0188101	12/2020	Abu Qahouq et al.	N/A	N/A
2021/0188115	12/2020	Kazuno	N/A	N/A
2021/0197687	12/2020	Searcy	N/A	N/A
2021/0201599	12/2020	Shionoya	N/A	N/A
2021/0213952	12/2020	Willison	N/A	N/A
2021/0229687	12/2020	Hashimoto et al.	N/A	N/A
2021/0284043	12/2020	Wang et al.	N/A	N/A
2021/0288506	12/2020	Tanaka	N/A	N/A
2021/0312544	12/2020	Inoue et al.	N/A	N/A
2021/0334913	12/2020	Klein	N/A	N/A
2021/0342896	12/2020	Swinson	N/A	N/A
2021/0347225	12/2020	Johnson et al.	N/A	N/A
2021/0405996	12/2020	Takatsuna et al.	N/A	N/A
2022/0016941	12/2021	Sams	N/A	N/A
2022/0028627	12/2021	Macaluso	N/A	N/A
2022/0050143	12/2021	Maeda et al.	N/A	N/A
2022/0052582	12/2021	Giannotta	N/A	N/A
2022/0105793	12/2021	Sukhatankar	N/A	N/A
2022/0109314	12/2021	Pena	N/A	N/A
2022/0111758	12/2021	Ijaz et al.	N/A	N/A
2022/0144258	12/2021	Lind	N/A	N/A
2022/0179641	12/2021	Harata et al.	N/A	N/A
2022/0179644	12/2021	Harata et al.	N/A	N/A
2022/0204012	12/2021	Ko	N/A	N/A
2022/0212638	12/2021	Georgeson	N/A	N/A
2022/0229446	12/2021	Switkes	N/A	N/A
2022/0247201	12/2021	Chen	N/A	N/A
2022/0253301	12/2021	Harata et al.	N/A	N/A
2022/0261836	12/2021	Kimomura et al.	N/A	N/A
2022/0270177	12/2021	Chintakindi	N/A	N/A
2022/0301775	12/2021	Macaluso	N/A	N/A
2022/0314837	12/2021	Gupta	N/A	N/A
2022/0328271	12/2021	Patwardhan et al.	N/A	N/A
2022/0329019	12/2021	Lanjekar et al.	N/A	N/A
2022/0334818	12/2021	McFarland	N/A	N/A
2022/0334822	12/2021	Sakakibara et al.	N/A	N/A
2022/0340035	12/2021	Kim et al.	N/A	N/A
2022/0374027	12/2021	Watts et al.	N/A	N/A
2022/0399581	12/2021	Wood	N/A	N/A
2022/0402390	12/2021	Smolenaers	N/A	N/A
2022/0402399	12/2021	Staats	N/A	N/A
2023/0005305	12/2022	Sakurai et al.	N/A	N/A
2023/0038222	12/2022	Howell	N/A	N/A
2023/0068432	12/2022	Upadhyay et al.	N/A	N/A
2023/0104789	12/2022	Inui	N/A	N/A
2023/0123166	12/2022	Deighton	N/A	N/A

2023/0130832	12/2022	Dunn	N/A	N/A
2023/0142500	12/2022	Marzoughi et al.	N/A	N/A
2023/0154692	12/2022	Macaluso	N/A	N/A
2023/0155401	12/2022	Kuranuki et al.	N/A	N/A
2023/0171574	12/2022	Macaluso	N/A	N/A
2023/0187145	12/2022	Macaluso	N/A	N/A
2023/0187757	12/2022	Pouyadou	N/A	N/A
2023/0261509	12/2022	Dalal et al.	N/A	N/A
2023/0302962	12/2022	Couture et al.	N/A	N/A
2024/0087810	12/2023	Macaluso	N/A	N/A
2024/0109442	12/2023	Macaluso	N/A	N/A
2024/0174107	12/2023	Macaluso	N/A	N/A
2024/0178722	12/2023	Macaluso	N/A	N/A
2024/0208326	12/2023	Macaluso	N/A	N/A
2024/0258823	12/2023	Macaluso	N/A	N/A
2024/0258824	12/2023	Macaluso	N/A	N/A
2024/0259773	12/2023	Macaluso	N/A	N/A
2024/0286507	12/2023	Macaluso	N/A	N/A
2024/0367512	12/2023	Macaluso	N/A	N/A
2024/0406695	12/2023	Macaluso	N/A	N/A
2025/0010741	12/2024	Macaluso	N/A	N/A
2025/0196632	12/2024	Macaluso	N/A	N/A
2025/0201950	12/2024	Macaluso	N/A	N/A
2025/0209863	12/2024	Macaluso	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019025	12/1989	CA	N/A
2019025	12/1989	CA	A61G 5/045
202100372	12/2021	CH	N/A
202294336	12/2011	CN	N/A
102963263	12/2012	CN	N/A
102963263	12/2012	CN	N/A
108473063	12/2012	CN	N/A
104732790	12/2014	CN	N/A
106846153	12/2016	CN	N/A
107117038	12/2016	CN	N/A
108539841	12/2017	CN	N/A
108599384	12/2017	CN	N/A
109976778	12/2018	CN	N/A
110549902	12/2018	CN	N/A
110633815	12/2018	CN	N/A
107804326	12/2019	CN	N/A
110795138	12/2019	CN	N/A
110889601	12/2019	CN	N/A
111932337	12/2019	CN	N/A
111954615	12/2019	CN	N/A
112977043	12/2020	CN	N/A
113479111	12/2020	CN	N/A

215398141	12/2021	CN	N/A
215398141	12/2021	CN	N/A
102017008723	12/2017	DE	N/A
102019220366	12/2020	DE	N/A
102011018457	12/2021	DE	N/A
1 253 698	12/2001	EP	N/A
3 246 776	12/2019	EP	N/A
2 681 512	12/2020	EP	N/A
2880816	12/2020	ES	N/A
2325201	12/1997	GB	N/A
2325201	12/1997	GB	B60K 25/08
2511831	12/2013	GB	N/A
2585496	12/2020	GB	N/A
2002-257026	12/2001	JP	N/A
2003-278633	12/2002	JP	N/A
2011-132873	12/2010	JP	N/A
2015-027164	12/2014	JP	N/A
2016-170600	12/2015	JP	N/A
6687274	12/2019	JP	N/A
6898339	12/2020	JP	N/A
2020-0020016	12/2019	KR	N/A
102266609	12/2020	KR	N/A
WO 09/149769	12/2008	WO	N/A
WO 10/133863	12/2009	WO	N/A
WO 11/078748	12/2010	WO	N/A
WO 11/148531	12/2010	WO	N/A
WO 17/030354	12/2016	WO	N/A
WO 17/057528	12/2016	WO	N/A
WO 17/143079	12/2016	WO	N/A
WO 17/213079	12/2016	WO	N/A
WO 18/046979	12/2017	WO	N/A
WO 18/083279	12/2017	WO	N/A
WO 19/034169	12/2018	WO	N/A
WO 19/117894	12/2018	WO	N/A
WO 19/145777	12/2018	WO	N/A
WO 19/219997	12/2018	WO	N/A
WO 19/240783	12/2018	WO	N/A
WO 20/170233	12/2019	WO	N/A
WO 20/191367	12/2019	WO	N/A
WO 21/187071	12/2020	WO	N/A
WO 22/015017	12/2021	WO	N/A
WO 22/132807	12/2021	WO	N/A
WO-2022150288	12/2021	WO	B60L 50/30
WO-2022150303	12/2021	WO	B60L 50/30
WO 22/219510	12/2021	WO	N/A
WO 23/160878	12/2022	WO	N/A
WO 24/002525	12/2023	WO	N/A

Background/Summary

INCORPORATION BY REFERENCE TO ANY PRIORITY APPLICATIONS (1) Any and all applications for which a foreign or domestic priority claim is identified in the Application Data Sheet as filed with the present application are hereby incorporated by reference under 37 CFR 1.57. This application is a continuation of U.S. application Ser. No. 18/381,120, filed Oct. 17, 2023, which is a continuation of U.S. application Ser. No. 18/243,524, filed Sep. 7, 2023, which claims priority benefit of U.S. Provisional Application No. 63/487,515, filed Feb. 28, 2023, the entirety of each of which is hereby incorporated by reference.

FIELD OF THE DISCLOSURE

(1) The present disclosure relates generally to generating and providing energy for a vehicle powered, at least in part, by electricity, and more specifically, to generating and conveying the energy to the vehicle while the vehicle is mobile.

BACKGROUND

(2) Electric vehicles derive locomotion power from electricity often received from an energy storage device within the electric vehicle. Battery electric vehicles (BEVs) are often proposed to have an energy storage/containment device, such as a battery, charged through some type of wired or wireless connection at one or more stationary locations, for example household or commercial supply sources. The wired charging connections require cables or other similar connectors physically connected to a stationary power supply. The wireless charging connections require one or more antennas or other similar structures wirelessly connected to a power supply that generates a wireless field via its own antenna(s). However, such wired and wireless stationary charging systems may be inconvenient or cumbersome and have other drawbacks, such as degradation during energy transference, inefficiencies or losses, requiring a specific location for charging, and so forth. As such, alternatives for stationary wired or wireless charging systems and methods that efficiently and safely transfer energy for charging electric vehicles are desirable.

SUMMARY

(3) Various embodiments of systems, methods and devices within the scope of the appended claims each have several aspects, no single one of which is solely responsible for the desirable attributes described herein. Without limiting the scope of the appended claims, the description below describes some prominent features.

(4) Details of one or more embodiments of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages will become apparent from the description, the drawings, and the claims. Note that relative dimensions of the following figures may not be drawn to scale.

(5) The present disclosure provides a system and apparatus for generating energy in response to a rotating component of a vehicle. In a first aspect, a system for generating energy in response to a movement of a vehicle includes an energy recovery mechanism configured to receive rotational energy from a drive shaft of the vehicle where the energy recovery mechanism is secured to a feature of the vehicle. The system further includes an energy storage electrically coupled with the energy recovery mechanism and configured to receive a portion of an electrical output to store as energy, and a motor electrically coupled with the energy storage and configured to receive a portion of the energy.

(6) In some embodiments, the energy storage includes a battery and/or a capacitor. In some embodiments, the feature of the vehicle is one of a vehicle frame, capacitor, generator, gearbox, or battery. In some embodiments, the system includes a flexible arm coupling the energy recovery

mechanism to the feature of the vehicle. In some embodiments, the energy recovery mechanism is immovably fixed to the drive shaft. In some embodiments, the system includes a second energy recovery mechanism.

(7) In another aspect, a system for generating energy in response to a movement of a vehicle includes an energy recovery mechanism configured to receive rotational energy from a drive shaft of the vehicle, where the energy recovery mechanism includes a housing with one or more rollers positioned tangentially adjacent the drive shaft and configured to rotate in response to a rotation of the drive shaft of the vehicle. The system further includes a generator rotatably coupled to the energy recovery mechanism and configured to generate an electrical output in response to the rotation of the roller, a capacitor electrically coupled with the generator and configured to receive a portion of the electrical output to store as capacitor energy, and a motor electrically coupled with the capacitor and configured to receive a portion of the capacitor energy.

(8) In some embodiments, the system includes a flexible arm mechanically connected to the housing and a feature of the vehicle, where the flexible arm is configured to apply a force to the one or more rollers to cause the one or more rollers to contact the drive shaft. In some embodiments, the flexible arm is configured to bend. In some embodiments, the flexible arm is configured to pivot about one or more joints. In some embodiments, the flexible arm is configured to adjust a magnitude of the force. In some embodiments, the flexible arm is configured to adjust a magnitude of the force based on at least a braking of the vehicle. In some embodiments, the flexible arm is configured to adjust a magnitude of the force based on at least an acceleration of the vehicle. In some embodiments, the system further includes a battery electrically coupled with the capacitor and configured to receive a portion of the capacitor energy to store as a battery energy. In some embodiments, the motor is configured to receive a portion of the battery energy. In some embodiments, the drive shaft includes one or more grooves for accommodating the one or more rollers. In some embodiments, the one or more rollers fit substantially within the one or more grooves. In some embodiments, a material on a surface of the one or more grooves is different than a material of the drive shaft. In some embodiments, a surface of the one or more grooves is textured to increase friction with the one or more rollers. In some embodiments, the one or more rollers are positioned circumferentially around the drive shaft. In some embodiments, the one or more rollers are positioned longitudinally along the drive shaft. In some embodiments, the housing partially encompasses the drive shaft. In some embodiments, the housing fully encompasses the drive shaft.

(9) In another aspect, a system for generating energy in response to a movement of a vehicle includes an energy recovery mechanism configured to receive rotational energy from a magnetic drive shaft of the vehicle, the energy recovery mechanism including one or more wires positioned adjacent the magnetic drive shaft of the vehicle, where a current is induced in the one or more wires as the magnetic drive shaft rotates. The system further includes a capacitor electrically coupled with the energy recovery mechanism and configured to receive a portion of the electrical output to store as capacitor energy, and a motor electrically coupled with the capacitor and configured to receive a portion of the capacitor energy.

(10) In some embodiments, the system includes a battery electrically coupled with the capacitor and configured to receive a portion of the capacitor energy to store as battery energy. In some embodiments, the motor is configured to receive a portion of the battery energy. In some embodiments, the energy recovery mechanism is coupled to a feature of the vehicle via a flexible arm. In some embodiments, the flexible arm is configured to move from an engaged to a disengaged position. In some embodiments, the feature of the vehicle is one of a vehicle frame, capacitor, or battery. In some embodiments, the magnetic drive shaft includes a permanent magnet. In some embodiments, the magnetic drive shaft partially includes a permanent magnet. In some embodiments, the magnetic drive shaft includes a permanent electromagnet positioned between two semicylinders of metal.

(11) In another aspect, a method for generating energy in response to rotational movement of a

moving vehicle includes rotating a shaft, the shaft including a textured surface spanning an outer circumference, rotating a roller in response to the rotation of the shaft, where the roller contacts the textured surface of the shaft, applying a force to the roller to cause the roller to maintain contact with the textured surface, generating, via a generator, an electrical output based on the rotation of the roller, and conveying the electrical output to an energy storage device or motor.

(12) In some embodiments, the shaft is a drive shaft. In some embodiments, the textured surface is positioned within a groove of the drive shaft. In some embodiments, the textured surface is positioned on a shoulder of the drive shaft. In some embodiments, the energy storage device is a one or more capacitors. In some embodiments, the method further includes notifying a driver that the one or more capacitors is fully charged. In some embodiments, the force is applied to the roller based on a received signal from the driver. In some embodiments, method further includes transferring the energy from the capacitor to the motor based on a signal from the driver. In some embodiments, the force is reduced or eliminated while the energy is transferred from the capacitor to the motor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a schematic diagram illustrating an example embodiment of an apparatus for generating energy in response to rotation of a wheel of vehicle.

(2) FIG. 1B is a schematic diagram illustrating an example embodiment of the apparatus of FIG. 1A in a disengaged state.

(3) FIG. 2 is a schematic diagram illustrating that a roller of the apparatus can have various dimensions.

(4) FIGS. 3A-3B are schematic diagrams illustrating example embodiments of the apparatus comprising multiple rollers.

(5) FIGS. 4A-4B are schematic diagrams illustrating example embodiments of the apparatus implemented on multiple wheels of a vehicle.

(6) FIG. 5A is a schematic diagram illustrating an example embodiment of the apparatus comprising rollers implemented on a sidewall of a wheel of a vehicle.

(7) FIG. 5B is a schematic diagram illustrating an example embodiment of the apparatus of FIG. 5A in a disengaged state.

(8) FIGS. 6A-6B are schematic diagrams illustrating example embodiments of the apparatus comprising a shaft coupled to various portions of a roller.

(9) FIG. 6C is a schematic diagram illustrating an example embodiment of the apparatus on both sides of a wheel.

(10) FIG. 7A-7B is a schematic diagram illustrating various sizes of a roller of the apparatus implemented on a sidewall of a wheel.

(11) FIG. 7C is a schematic diagram illustrating an example embodiment of a roller of the apparatus coupled to a shaft of the apparatus.

(12) FIGS. 8A-8B are schematic diagrams illustrating example embodiments of the apparatus implemented on sidewalls of multiple wheels of a vehicle.

(13) FIG. 9 is a schematic diagram illustrating an example embodiment of the apparatus comprising rollers between two adjacent wheels of a vehicle.

(14) FIGS. 10A-10B are schematic diagrams illustrating example embodiments of the apparatus comprising rollers implemented on a sidewall surface and curved surface of a wheel of a vehicle.

(15) FIGS. 11A-11B is a diagram illustrating examples embodiments of generators coupled to roller(s) of the apparatus.

(16) FIG. 12 is a diagram illustrating an example vehicle incorporating the apparatus, a generator

and an energy storage device.

(17) FIG. 13 is a diagram illustrating an example embodiment of a hypercapacitor as an energy storage device.

(18) FIGS. 14A-14J illustrate example vehicles incorporating the apparatus, a generator, an energy storage device and a motor.

(19) FIG. 15A is a schematic diagram illustrating an example implementation of an energy generation system, according to some embodiments.

(20) FIG. 15B is another schematic diagram illustrating an example implementation of an energy generation system, according to some embodiments.

(21) FIG. 15C is another schematic diagram illustrating an example implementation of an energy generation system, according to some embodiments.

(22) FIG. 16 is a cross section view of an example drive shaft and rollers, according to some embodiments.

(23) FIG. 17 is a perspective view of an example energy recovery mechanism with a partial housing, according to some embodiments.

(24) FIG. 18 is a cross sectional view of an example energy recovery mechanism with a full housing, according to some embodiments.

(25) FIG. 19 is a cross sectional view of an example energy recovery mechanism, according to some embodiments.

(26) FIG. 20A is a side view of an example energy recovery mechanism and drive shaft, according to some embodiments.

(27) FIG. 20B is a side view of an example energy recovery mechanism and drive shaft with grooves, according to some embodiments.

(28) FIG. 21A is a side view of an example energy recovery mechanism in an engaged position.

(29) FIG. 21B is a side view of an example energy recovery mechanism in a disengaged position.

(30) FIG. 22 is a top down view of a drive shaft and several energy recovery mechanisms.

(31) FIG. 23A is a perspective view of an example energy recovery mechanism and drive shaft, according to some embodiments.

(32) FIG. 23B is a perspective view of an example energy recovery mechanism and drive shaft with a textured surface, according to some embodiments.

(33) FIG. 23C is a perspective view of an example energy recovery mechanism and drive shaft with a raised shoulder, according to some embodiments.

(34) FIG. 23D is a perspective view of an example energy recovery mechanism and drive shaft with a groove, according to some embodiments.

(35) FIG. 23E is a perspective view of an example energy recovery mechanism and drive shaft with a groove, according to some embodiments.

(36) FIG. 24 is a sectional view of an example energy recovery mechanism and magnetic drive shaft, according to some embodiments.

(37) FIG. 25 is a side view of an example energy recovery mechanism and magnetic drive shaft, according to some embodiments.

DETAILED DESCRIPTION

(38) Overview

(39) Example embodiments and implementations of an apparatus for generating energy (for example, in response to the rotation of a component of a vehicle) are described herein. The apparatus can be implemented in conjunction with a vehicle, such as an electric vehicle. The vehicle can include a car, a truck, a semi-truck, a tractor-trailer, a tractor, farm equipment, construction equipment, carts, scooters, motorcycles, bicycles, trains, trams, and the like, for example. The apparatus can comprise one or more rollers configured to be rotatably couplable (for example, removably coupled either through direct physical contact or through indirect operable coupling) to one or more components of a vehicle (for example, wheel, drive shaft, axle etc.) such

that rotation of the component of the vehicle causes rotation of the one or more rollers. The one or more rollers can be rotatably coupled (either through direct physical contact or through indirect operable coupling) to one or more generators. The generators can be configured to generate energy (for example, an electrical output), in response to rotation of the one or more rollers. In some embodiments, the one or more rollers can be rotatably coupled to the one or more generators via one or more flexible arms configured to rotate in response to a rotation of the one or more rollers. In some embodiments, the one or more rollers can be rotatably coupled to the one or more generators via one or more other mechanical coupling devices such as a chain, belt, gearing, pulley, sprocket and the like. In some embodiments, the one or more generators can provide generated energy (for example, electrical output) to the vehicle. The electrical output that is provided to the vehicle from the generator may be used to power the vehicle. For example, the electrical output may be conveyed to a motor of the vehicle and/or to an energy storage device of the vehicle for later use and/or consumption by the vehicle. In some embodiments, the energy of the rotating component is captured by inducing a current in one or more wires positioned adjacent the rotating component.

(40) Example Apparatus Embodiments and Implementations

(41) Various example embodiments of an apparatus for generating energy are described herein, for example, with reference to the figures. The various embodiments and their implementations are given as examples and are not meant to be limiting of the present disclosure.

(42) Furthermore, the structural and/or operational features described with reference to any of the example embodiments and/or figures are not meant to be limited to that embodiment and/or figure. Rather the structural and/or operation features of the various embodiments and figures may be implemented or otherwise combined in each of the various other embodiments.

(43) In some embodiments, the term “shaft” may refer to a “flexible arm” as described in U.S. Pat. No. 11,577,606 which is hereby incorporated by reference in its entirety.

(44) FIG. 1A is a diagram illustrating an example embodiment of an apparatus **100** comprising a roller rotatably couplable to a wheel of a vehicle. As shown in FIG. 1A, the apparatus **100** may comprise a roller **102**, a shaft **104** and a generator **106**. The roller **102** may comprise a substantially cylindrical shape comprising a length, a diameter, a curved surface and a center axis as described in greater detail with reference to FIG. 2. A curved surface of the roller **102** may be in substantial physical contact with a curved surface of the wheel **101**. The center axis of the roller **102** may be substantially parallel to a center axis of the wheel **101**. The roller **102** may be configured to rotate about its center axis. The roller **102** may be rotatably couplable to a wheel **101** of the vehicle such that rotation of the wheel **101** causes rotation of the roller **102**. The roller **102** may rotate in an opposite direction than the wheel **101**, for example as shown in FIG. 1A. The roller **102** may rotate at a greater rotational velocity than the wheel **101**.

(45) With continued reference to FIG. 1A, the roller **102** may be rotatably coupled to a shaft **104** such that rotation of the roller **102** can cause rotation of the shaft **104**. The shaft **104** may rotate about an axis that is substantially parallel to the axis of the roller **102** and may rotate in a same direction as the roller **102**, for example as shown in FIG. 1A. In some embodiments, the shaft **104** may be fixedly rotatably coupled to the roller **102** such that the shaft **104** can only rotate when the roller **102** rotates. In some embodiments, the shaft **104** may be configured to rotate when the roller **102** is not rotating. For example, after a roller **102** discontinues rotating, the shaft **104** may continue to rotate, for example due to rotational inertia. For example, the roller **102** and/or shaft **104** may comprise a one-way ratchet device that causes the shaft **104** to rotate when the roller **102** rotates and allows the shaft **104** to continue to rotate for a period of time even after the roller **102** stops rotating. In some embodiments, the shaft **104** may be configured to not rotate when the roller **102** is rotating. For example, in a disengaged state, as discussed in greater detail herein, the roller **102** may rotate in response to rotation of a vehicle wheel but may not cause rotation of the shaft **104** to generate energy at the generator **106**.

(46) The shaft **104** may be operably coupled to a generator **106**. The generator **106** may be configured to generate energy (for example, an electrical output) in response to mechanical movement such as the rotation of the shaft **104**. The generator **106** may be electrically coupled to the vehicle and may provide generated energy to the vehicle, for example to a motor of the vehicle and/or to an energy storage device of the vehicle that includes one or more batteries and/or capacitors (for example, ultracapacitors) or one or more supercapacitors.

(47) FIG. 1B is a diagram illustrating an example embodiment of the apparatus **100** comprising a roller that is removably coupled to a wheel of a vehicle. The apparatus **100** may exist in one of (1) an engaged state or (2) a disengaged state. In the engaged state, the roller **102** may be in physical contact with the wheel **101** (for example, rotatably coupled to the wheel **101**) in which the rotation of the wheel **101** causes the roller **102** to rotate. In some embodiments, in the disengaged state, the roller **102** may not be in physical contact with the wheel **101** such that rotation of the wheel **101** does not cause the roller **102** to rotate. In some embodiments, in the disengaged state, the roller **102** may be in physical contact with the wheel **101** such that rotation of the wheel **101** causes the roller **102** to rotate but the roller **102** may not be rotatably coupled to the shaft **104** such that rotation of the roller **102** does not cause the shaft **104** (or other similar component) to rotate to cause generation of energy at the generator **106**.

(48) FIG. 1B shows a roller **102** in an example disengaged state such that the roller **102** is not in physical contact with the wheel **101** and will not rotate in response to a rotation of the wheel **101**. The roller **102** may transition between the engaged and the disengaged states. In some embodiments, the roller **102** may transition between the engaged and the disengaged states automatically, for example, based at least in part on an energy demand of the vehicle (for example, an energy demand of a motor of the vehicle) and/or a rotational velocity of the wheel **101**. In some embodiments, the roller **102** may transition between the engaged and the disengaged states in response to a user input, such as a driver of the vehicle activating a user input device, such as a button, lever, or switch.

(49) FIG. 2 is a diagram illustrating an example embodiment of a roller **102**. As shown in FIG. 2, the roller **102** may comprise a length **213** and a diameter **211**. The roller **102** may have any length **213** such as is required or desired. The roller **102** may have any diameter **211** such as is required or desired. The diameter **211** of the roller **102** may be less than the diameter of the wheel **101** such that the roller **102** rotates at a greater rotational velocity than the wheel **101** in response to a rotation of the wheel **101**. In some embodiments comprising multiple rollers, one, some or each of the multiple rollers may have a length and/or diameter that is different than the length and/or diameters of the other rollers.

(50) In some embodiments, the roller **102** may be configured to change a size of diameter **211**. In response to changing size of diameter **211**, the roller **102** may rotate at various rotational velocities in response to rotation of the wheel **101** at a single rotational velocity. In some embodiments, the roller **102** may be configured to change size of diameter **211** automatically, for example, based at least in part on an energy demand of the vehicle (for example, an energy demand of a motor of the vehicle) and/or a rotational velocity of the wheel **101**.

(51) FIG. 3A is a diagram illustrating an example embodiment of the apparatus **100** comprising two rollers and two generators. As shown in FIG. 3A, the apparatus **100** may comprise a first roller **102a**, a first shaft **104a**, a first generator **106a**, a second roller **102b**, a second shaft **104b** and a second generator **106b**. The components of the example embodiment shown in FIG. 3A may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiment of FIG. 1A. For example, the rotation of the wheel **101** may cause the rollers **102a/102b** to rotate thereby causing shafts **104a/104b** to rotate thereby causing the generators **106a/106b** to generate energy. FIG. 3A is not meant to be limiting of the present disclosure. The apparatus **100** may comprise any number of rollers, shafts and/or generators as required and/or desired.

(52) FIG. 3B is a diagram illustrating an example embodiment of the apparatus **100** comprising two rollers and a generator. As shown in FIG. 3B, the apparatus **100** may comprise a first roller **102a**, a first shaft **104a**, a first sprocket **105a**, a first coupling device **107a**, a second roller **102b**, a second shaft **104b**, a second sprocket **105b**, a second coupling device **107b**, a third shaft **108** and generator **106**. The components of the example embodiment shown in FIG. 3B may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example FIG. 1A. The sprockets **105a/105b** may be rotatably coupled to the shafts **104a/104b** and may rotate in response to rotation of the shafts **104a/104b**. The sprockets **105a/105b** may be rotatably coupled to a third shaft **108**, for example via coupling devices **107a/107b** as shown in FIG. 3B. The coupling devices **107a/107b** may comprise one or more of a chain, belt, gearing, pulley or the like. The third shaft **108** may be operably coupled to the generator **106** such that rotation of the third shaft **108** causes the generator to generate energy. Thus, the generator **106** may generate energy in response to a rotation of the first and/or second rollers **102a/102b**.

(53) In some embodiments, the third shaft **108** may rotate in response to simultaneous rotations of the first and second rollers **102a/102b**. In some embodiments, the third shaft **108** may rotate in response to rotation of either the first or second rollers **102a/102b**.

(54) In some embodiments, the shafts **104a/104b** may be fixedly rotatably coupled to the sprockets **105a/105b** such that the sprockets **105a/105b** can only rotate when the shafts **104a/104b** rotate. In some embodiments, the sprockets **105a/105b** may be configured to rotate when the shafts **104a/104b** are not rotating, for example, after the shafts **104a/104b** discontinue rotating, the sprockets **105a/105b** may continue to rotate, for example due to rotational inertia. For example, the shafts **104a/104b** and/or sprockets **105a/105b** may comprise a one-way ratchet device that causes the sprockets **105a/105b** to rotate when the shafts **104a/104b** rotate and allows the sprockets **105a/105b** to continue to rotate when the shafts **104a/104b** are not rotating. The sprockets **105a/105b** and the third shaft **108** may comprise similar operational and/or structural features to allow the third shaft **108** to rotate when one or more of the sprockets **105a/105b** are not rotating in some embodiments or to cause the third shaft **108** to rotate only when the sprockets **105a/105b** are rotating in other embodiments.

(55) FIG. 4A is a diagram illustrating an example embodiment of the apparatus **100** implemented with multiple wheels of a vehicle. As shown in FIG. 4A, the apparatus **100** may comprise a first roller **102a** rotatably couplable to a first wheel **101a** of a vehicle, a second roller **102b** rotatably couplable to a second wheel **101b** of a vehicle. The components of the example embodiment shown in FIG. 4A may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiment of FIG. 1A. For example, rotation of the first and/or second rollers **102a/102b** may cause the generator **106** to generate energy.

(56) FIG. 4A is not meant to be limiting of the present disclosure. The apparatus **100** may comprise any number of rollers, shafts and/or generators as required and/or desired and may be implemented on any number of wheels of a vehicle as required or desired, for example on one, two, three or four wheels (for example, with reference to implementation with a car) or 18 wheels (for example, with reference to implementation with a semi-truck).

(57) FIG. 4B is a diagram illustrating an example embodiment of the apparatus **100** implemented with multiple wheels of a vehicle and comprising multiple generators. As shown in FIG. 4B, the apparatus **100** may comprise a first and second generator **106a/106b**. The components of the example embodiment shown in FIG. 4B may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiment of FIG. 1A. For example, rotation of the first roller **102a** may cause the first generator **106a** to generate energy and rotation of the second roller **102b** may cause the generator **106b** to generate energy. The generators **106a/106b** may be in electrical communication with the vehicle and/or each other.

(58) FIG. 5A is a diagram illustrating an example embodiment of the apparatus **100** comprising one or more rollers rotatably couplable to a sidewall of a wheel of a vehicle. As shown in FIG. 5A, the apparatus **100** may comprise one or more rollers **102**, a shaft **104** and a generator **106**. Each of the one or more rollers **102** may comprise a substantially cylindrical shape and may further comprise a length, a diameter, a curved surface and a center axis as described in greater detail with reference to FIG. 2 and/or FIGS. 7A-7B. A curved surface of each of the one or more rollers **102** may be in substantial physical contact with a sidewall surface of the wheel **101**. The center axis of each of the one or more rollers **102** may be substantially orthogonal to a center axis of the wheel **101**. Each of the one or more rollers **102** may be configured to rotate about its center axis. Each of the one or more rollers **102** may be rotatably couplable to the wheel **101** of the vehicle such that rotation of the wheel **101** causes rotation of each of the one or more rollers **102**. Each of the one or more rollers **102** may rotate at a greater rotational velocity than the wheel **101**.

(59) The roller(s) **102** may be configured to be in physical contact with a sidewall of the wheel **101** at any distance away from a center axis of the wheel. For example, the roller(s) **102** may be in physical contact with a sidewall of the wheel **101** close to the center axis of the wheel or far from a center axis of the wheel. The roller(s) **102** may rotate at a greater rotational velocity when in physical contact with the sidewall of the wheel **101** far from a center axis of the wheel **101** than when in physical contact with the sidewall of the wheel **101** near a center axis of the wheel **101**.

(60) With continued reference to FIG. 5A, the roller(s) **102** may be rotatably coupled to a shaft **104** such that rotation of the roller(s) **102** causes rotation of the shaft **104**. The roller **102** may be coupled (for example, rotatably coupled) to the shaft **104** for example via one or more coupling devices as required or desired such as gears, sprockets, chains, belts, pulleys and the like. The shaft **104** may rotate about an axis that is substantially orthogonal to the axes of the roller(s) **102**. In some embodiments, the shaft **104** may be fixedly rotatably coupled to the roller(s) **102** such that the shaft **104** can only rotate when the roller(s) **102** rotate. In some embodiments, the shaft **104** may be configured to rotate when one or more of the roller(s) **102** is not rotating, for example, after a roller **102** discontinues rotating, the shaft **104** may continue to rotate, for example due to rotational inertia. For example, the roller(s) **102** and/or shaft **104** may comprise a one-way ratchet device that causes the shaft **104** to rotate when the roller(s) **102** rotate and allows the shaft **104** to continue to rotate even when one of the roller(s) **102** is not rotating (for example, has stopped rotating). In some embodiments, the shaft **104** may be configured to not rotate when one or more of the roller(s) **102** are rotating. For example, in a disengaged state, as discussed in greater detail herein, the roller(s) **102** may rotate in response to rotation of a vehicle wheel but may not cause rotation of the shaft **104** to generate energy at the generator **106**.

(61) The shaft **104** may be operably coupled to a generator **106**. The generator **106** may be configured to generate energy (for example, an electrical output) in response to mechanical movement such as the rotation of the shaft **104**. The generator **106** may be electrically coupled to the vehicle and may provide generated energy to the vehicle, for example to a motor of the vehicle and/or to an energy storage device of the vehicle that includes one or more batteries and/or capacitors (for example, ultracapacitors) or one or more supercapacitors.

(62) FIG. 5B is a diagram illustrating an example embodiment of the apparatus **100** comprising one or more rollers that are removably coupled to a sidewall of a wheel of a vehicle. The apparatus **100** may exist in one of (1) an engaged state or (2) a disengaged state. In the engaged state, the roller(s) **102** may be in physical contact with the wheel **101** (for example, rotatably coupled to a sidewall of the wheel **101**) in which the rotation of the wheel **101** causes the roller(s) **102** to rotate. In some embodiments, in the disengaged state, the roller(s) **102** may not be in physical contact with the wheel **101** such that rotation of the wheel **101** does not cause the roller(s) **102** to rotate. In some embodiments, in the disengaged state, the roller(s) **102** may be in physical contact with the wheel **101** such that rotation of the wheel **101** causes the roller(s) **102** to rotate but the roller(s) **102** may not be rotatably coupled to the shaft **104** such that rotation of the roller(s) **102** does not cause the

shaft **104** (or other similar component) to rotate to cause generation of energy at the generator **106**. (63) FIG. 5B shows roller(s) **102** in an example disengaged state such that the roller(s) **102** are not in physical contact with the wheel **101** and will not rotate in response to a rotation of the wheel **101**. The roller(s) **102** may transition between the engaged and the disengaged states. In some embodiments, the roller(s) **102** may transition between the engaged and the disengaged states automatically, for example, based at least in part on an energy demand of the vehicle (for example, an energy demand of a motor of the vehicle) and/or a rotational velocity of the wheel **101**. In some embodiments, the roller(s) **102** may transition between the engaged and the disengaged states in response to a user input, such as a driver of the vehicle toggling a user input device such as a button, switch or lever.

(64) FIG. 6A is a diagram illustrating an example embodiment of the apparatus **100** comprising a roller rotatably couplable to a sidewall of a wheel of a vehicle. As shown in FIG. 6A, the apparatus **100** may comprise a single roller **102** which may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiments of FIG. 1 and/or FIG. 5A.

(65) FIG. 6B is a diagram illustrating an example embodiment of the apparatus **100** comprising a roller. As shown in FIG. 6B, the apparatus **100** may comprise a single roller **102** which may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiments of FIG. 1 and/or FIG. 5A. As shown in FIG. 6B, the shaft **104** may be rotatably coupled to either end of the roller **102**. In some embodiments, a shaft may be rotatably coupled at both ends of a roller **102**.

(66) FIG. 6C is a diagram illustrating an example embodiment of the apparatus **100**. As shown in FIG. 6C, the apparatus **100** may comprise a roller **102a** on one side of a wheel **101** and a roller **102b** on an opposite side of the wheel **101**. The rollers **102a**, **102b** can be configured to be rotatably couplable to a sidewall portion of the wheel **101** and rotate in response to a rotation of the wheel **101** as described herein. The apparatus **100** may exist in one of (1) an engaged state or (2) a disengaged state and transition between the two states as discussed herein, for example by changing a physical location of the rollers **102a**, **102b** to physically contact or not physically contact the wheel **101**.

(67) The example embodiment of FIG. 6C can be implemented in a vehicle, for example, in conjunction with a braking system of the vehicle. For example, a braking system of a vehicle may comprise a brake pad on one side of wheel and a brake pad on an opposite side of the wheel. The brake pads may normally exist in a state wherein the brake pads are not in physical contact with the wheel. An operator of the vehicle may cause each brake pad to physically contact their respective sides of the wheel to cause friction on the sidewall of the wheel to decelerate the rotation of the wheel. As an example, the apparatus may be implemented with a brake system such that the apparatus may normally exist in a disengaged state wherein the rollers **102a**, **102b** are not in physical contact with the wheel **101** and the brake pads are not in physical contact with the wheel **101**. When braking is desired, and the brake pads are caused to contact the wheel **101**, the rollers **102a**, **102b** may also contact the wheel **101** in an engaged state and thereby rotate in response to a rotation of the wheel **101**.

(68) In some implementations, in the engaged state, the rollers **102a**, **102b** may apply a friction force to the wheel **101** to decelerate the wheel **101**. In some implementations, the apparatus **100** may replace a braking system otherwise employed by the vehicle, such that when braking is desired, the rollers **102a**, **102b** of the apparatus transition to an engaged state thereby applying friction to the wheel **101** to decelerate the rotation of wheel **101** while simultaneously rotating in response to a rotation of the wheel **101** to generate energy at the generator **106** until the wheel **101** stops rotating.

(69) The rotational inertia of the rollers **102** in the example embodiment of FIG. 6C and other examples herein can be changed for example increased or decreased. Increasing the rotational

inertia of the rollers can cause more or less friction to be applied to the wheel **101** and also cause more or less energy to be generated at the generator **106**. For example, more energy would be required to rotate a roller **102** with a high rotational inertia than would be required to rotate a roller **102** with less rotational inertia. Thus, a roller **102** with high rotational inertia could more quickly decelerate the rotation of the wheel **101** while simultaneously causing more energy to be generated at the generator **106** than a roller with lower rotational inertia. For example, when acceleration or a constant speed of the vehicle is desired, the rotational inertia of the roller(s) **102** may be low to apply less friction to the wheel **101** (which may thereby cause less energy to be generated at the generator **106**) and when deceleration of the vehicle is desired (for example, stopping), the rotational inertia of the roller(s) **102** may be high to apply more friction to the wheel **101** (which may thereby cause more energy to be generated at the generator **106**). Thus, for any given desired mode of operation of the vehicle (for example, acceleration, deceleration) a maximum energy may be generated at the generator **106** by changing a rotational inertia of the rollers **102**.

(70) In some implementations, the rotational inertia of the rollers **102** can change automatically for example in response to an energy demand of the motor of the vehicle, a rotational velocity of the wheel, and/or desired braking etc. In some implementations, the rotational inertia of the rollers can change in response to a manual user input. The rotational inertia of the roller **102** can be changed by changing a state of the roller **102**, the shaft **104** (or other coupling device), and/or changing a state of the generator **106**.

(71) FIG. 7A is a diagram illustrating an example embodiment of a roller. As shown in FIG. 2, the roller **102** may comprise a length **713** and a diameter **711**. The roller **102** may have any length **713** such as is required or desired. The roller **102** may have any diameter **711** such as is required or desired. The diameter **711** of the roller **102** may be less than the diameter of the wheel **101** such that the roller **102** rotates at a greater rotational velocity than the wheel **101** in response to a rotation of the wheel **101**. In some embodiments comprising multiple rollers, one, some or each of the multiple rollers may have a length and/or diameter that is different than the lengths and/or diameters of the other rollers.

(72) FIG. 7B is a diagram illustrating an example embodiment of a roller. As shown in FIG. 7B, the roller **102** may comprise a diameter that varies in size along a length of the roller **102**. For example, one end of the roller **102** may comprise a diameter **711a** of a first size and the other end of the roller **102** may comprise a diameter **711b** of a second size that is different than the diameter **711a**. A roller **102** having a diameter that varies in size along a length of the roller **102** may facilitate the rotation of the roller **102** in response to a rotation of the wheel **101**.

(73) FIG. 7C is a diagram illustrating an example embodiment of the apparatus **100**. As shown in FIG. 7C, the apparatus **100** may comprise a roller shaft **703** rotatably coupled to the roller **102** and the shaft **104**. The roller shaft **703** may not be in physical contact with the wheel **103**. The roller shaft **703** may be any length to allow the roller **102** to be in contact with a sidewall of the wheel **101** at any distance away from a center axis of the wheel **101**.

(74) FIG. 8A is a diagram illustrating an example embodiment of the apparatus **100** implemented with multiple wheels of a vehicle. As shown in FIG. 8A, the apparatus **100** may comprise one or more first rollers **102a** rotatably couplable to a first wheel **101a** of a vehicle and one or more second rollers (not shown) rotatably couplable to a second wheel **101b** of the vehicle. The components of the example embodiment shown in FIG. 4A may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiment of FIG. 5A. For example, rotation of the one or more first rollers **102a** and/or rotation of the one or more second rollers (not shown) may cause the generator **106** to generate energy.

(75) FIG. 8A is not meant to be limiting of the present disclosure. The apparatus **100** may comprise any number of rollers, shafts and/or generators as required and/or desired and may be implemented on any number of wheels of a vehicle as required or desired, for example on one, two, three or four

wheels (for example with reference to implementation with a car) or 18 wheels (for example with reference to implementation with a semi-truck).

(76) FIG. 8B is a diagram illustrating an example embodiment of the apparatus **100** implemented with multiple wheels of a vehicle and comprising multiple generators. As shown in FIG. 8B, the apparatus **100** may comprise a first and second generator **106a/106b**. The components of the example embodiment shown in FIG. 8B may comprise similar structural and/or operational features as described with reference to other embodiments described herein, for example, the example embodiment of FIG. 5A. For example, rotation of the one or more first rollers **102a** may cause the first generator **106a** to generate energy and rotation of the one or more second rollers (not shown) may cause the generator **106b** to generate energy. The generators **106a/106b** may be in electrical communication with the vehicle and/or each other.

(77) FIG. 9 is a diagram illustrating an example embodiment of the apparatus **100** implemented between two wheels. As shown in FIG. 9, the apparatus **100** may comprise a first roller **102a** and a second roller **102b** located between two wheels **101a/101b** such as two adjacent wheels on a truck, van, semi-truck, tractor-trailer and the like. The first roller **102a** may be in physical contact with a sidewall surface of the first wheel **101a** and configured to rotate in response to a rotation of the first wheel **101a**. The second roller **102b** may be in physical contact with a sidewall surface of the second wheel **101b** and configured to rotate in response to a rotation of the second wheel **101b**. The first and second rollers **102a/102b** may be coupled to each other (for example, rotatably coupled) via one or more coupling devices such as a shaft as shown in FIG. 9 and/or any other coupling device as required or desired such as gears, sprockets, chains, belts, pulleys and the like.

(78) The first roller **102a** and/or second roller **102b** may be coupled (for example, rotatably coupled) to a shaft **104** for example via one or more coupling device such as a shaft as shown in FIG. 9 and/or any other coupling device as required or desired such as gears, sprockets, chains, belts, pulleys and the like. The shaft **104** may be configured to rotate in response to a rotation of the first roller **102a** and/or second roller **102b**. The shaft **104** may be operably coupled to a generator **106** and the generator **106** may be configured to generate energy (for example, electrical output) in response to a rotation of the shaft **104** as described elsewhere herein.

(79) FIG. 9 is given as an example and is not meant to be limiting. In some embodiments, the apparatus **100** may comprise any number of rollers, for example one roller or more than two rollers. Furthermore, the rollers **102a/102b** shown in example FIG. 9 may be arranged with any orientation between their respective axes of rotation, as required or desired. For example, the respective axes of rotation of rollers **102a/102b** may be substantially parallel, as shown in FIG. 9, or may be substantially orthogonal or may be oriented in any other way as required or desired. Additionally, the rollers **102a/102b** may be configured to rotate independently of each other such that one roller may rotate while the other does not or may be configured to be fixedly rotatably coupled to each other such that one roller may not rotate without the other roller also rotating.

(80) FIG. 10A is a diagram of an example embodiment of the apparatus **100** comprising various configurations of rollers and multiple generators. As shown in FIG. 10A, the apparatus **100** may comprise one or more first rollers **102a**, a first shaft **104a**, a first generator **106a** and one or more second rollers **102b**, a second shaft **104b** and a second generator **106b**. The example apparatus **100** of FIG. 10A and its various components may operate in a manner similar to that described in other example embodiments herein such as with reference to FIG. 1A and/or FIG. 5A, for example.

(81) FIG. 10B is a diagram of an example embodiment of the apparatus **100** comprising various configurations of rollers and a single generator. As shown in FIG. 10B, the apparatus **100** may comprise one or more first rollers **102a**, a first shaft **104a**, a first sprocket **105a**, a first coupling device **107a**, a third shaft **108** and a generator **106**. The apparatus **100** may further comprise one or more second rollers **102b**, a second shaft **104b**, a second sprocket **105b**, and a second coupling device **107b**. The example apparatus **100** of FIG. 10B and its various components may operate in a manner similar to that described in other example embodiments herein such as with reference to

FIG. 1A, FIG. 5A, and/or FIG. 3B, for example.

(82) Example Energy Generation and Storage Systems

(83) FIG. 11A is a diagram of two generators **106a** and **106b** configured to be mechanically coupled to roller(s) and that convert mechanical rotation of roller(s) **102** into electrical energy outputs, in accordance with an exemplary embodiment. In some embodiments, the generators **106a** and **106b** may be replaced with alternators or similar electricity generating devices. The generators **106a** and **106b** can be mechanically coupled to roller(s) via one or more of a shaft, linkage, gear, pulley, chain, belt, sprocket or other similar mechanism or device. The example embodiment of FIG. 11A illustrates the generator **106b** as mechanically coupled to roller(s) **102** via at least a chain **1101**. The chain **1101** may rotate, in response to rotation of the roller(s) **102**, causing a corresponding rotor of the generator **106b** to rotate and causing the generator **106b** to generate an electrical energy output via a cable (not shown in this figure). In some embodiments, the two generators **106a** and **106b** may be replaced by any number of generators **106**, from a single generator to many generators. In some embodiments, the generators **106** may generate AC electricity or DC electricity, depending on the application. When the generators **106** generate AC power, an AC-to-DC converter may be used to condition and convert the generated electricity for storage. When the generators **106** generate DC power, a DC-to-DC converter may be used to condition the generated electricity for storage.

(84) FIG. 11B is an alternate view of the two generators **106a** and **106b** of FIG. 11A and cabling **1103a** and **1103b** that couples the generators **106a** and **106b** to a charger (for example, a battery and/or capacitor charger) and/or to an energy storage device such as a battery and/or capacitor. The charger may comprise one or more other components or circuits used to rectify or otherwise condition the electricity generated by the generators **106a** and **106b**. For example, the one or more other components or circuits may comprise one or more of a matching circuit, an inverter circuit, a conditioning circuit, a rectifying circuit, a conversion circuit, and so forth. The matching circuit may match conditions of a load to the source (for example, impedance matching, and so forth). The conversion circuit may comprise a circuit that converts an alternating current (AC) signal to a direct current (DC) signal, a DC/DC conversion circuit, a DC/AC conversion circuit and so forth. The conditioning circuit may condition a signal input into the conditioning circuit, and the rectifying circuit may rectify signals.

(85) Additional details regarding FIGS. 11A-11B can be found in at least paragraphs [0080]-[0099] of U.S. patent application Ser. No. 17/332,824, which is hereby incorporated by reference.

(86) FIG. 12 is a diagram of an example vehicle **1200** incorporating an apparatus **100** comprising roller(s) **102**, a generator **106**, as well as an energy storage device **1203** electrically coupled with the generator **106**. Energy generated at the generator **106**, in response to a rotation of the roller(s) **102** can be provided to the energy storage device **1203**. The energy storage device **1203** can comprise one or more batteries **1202** and/or one or more capacitor modules **1204**. The energy storage device **1203** may comprise the one or more capacitor modules **1204** as a supplemental and/or intermediate energy storage device. In some embodiments, the capacitor modules **1204** are disposed alongside the one or more batteries **1202**. The capacitor modules **1204** and the battery **1202** can be electrically coupled to at least a motor of the vehicle, such as an electric motor.

(87) In some embodiments, the capacitor modules **1204** may be used in combination with the battery **1202**. For example, as shown in FIG. 12, the vehicle **1200** may include one or more the capacitor modules **1204** installed alongside the battery **1202**. In some embodiments, the vehicle **1200** includes a plurality of capacitor modules **1204**. In some embodiments, one or more batteries **1202** are replaced with one or more capacitor modules **1204**. As shown, the capacitor modules **1204** may be connected in series or in parallel with the battery **1202**, dependent on the use case. For example, the capacitor modules **1204** may be connected in series or parallel with the battery **1202** when supplementing the voltage in the battery **1202** or when charging the battery **1202** and/or the capacitor modules **1204**. Therefore, the battery **1202** and the capacitor modules **1204** may provide

voltage support to each other. As such, the capacitor modules **1204** may provide supplemental energy when the battery **1202** are discharged or be used in place of the battery **1202** altogether.

(88) In some embodiments, the energy storage device **1203** may comprise one or more hypercapacitors. FIG. **13** schematically illustrates a diagram of an example embodiment of a hypercapacitor **1302** for storing energy (for example, such as may be used in an electric vehicle), which may also be referred to as a hypercapacitor energy storage system or device. As shown, the hypercapacitor **1302** may comprise or consist essentially of an ultracapacitor portion **1304**, an energy retainer portion **1306**, one or more inbound diodes **1308**, and one or more outbound diodes **1310**. In some embodiments, the hypercapacitor **1302** may not comprise the inbound diode **1308** and/or the outbound diode **1310**.

(89) The ultracapacitor portion **1304** may be electrically coupled to the energy retainer portion **1306** and in some embodiments, together may comprise a single integrated unit or package (for example, the hypercapacitor **1302**). The ultracapacitor portion **1304** may provide energy to the energy retainer portion **1306** as the energy in the energy retainer portion **1306** is depleted (for example resulting from an energy demand at a load).

(90) The electrical connection between the ultracapacitor portion **1304** and the energy retainer portion **1306** may stabilize the voltage levels of the ultracapacitor portion **1304** and prevent self-discharge as the energy retainer portion **1306** retains energy provided from the ultracapacitor portion **1304** via their electrical connection. Advantageously, stabilizing the voltage levels in the ultracapacitor portion **1304** by reducing and/or substantially eliminating self-discharge provides a superior energy device capable of storing energy (for example, maintaining high voltage levels) for much longer than existing energy devices in widespread use today.

(91) The ultracapacitor portion **1304** of the hypercapacitor **1302** may comprise one or more ultracapacitors and/or supercapacitors. The ultracapacitor portion **1304** may incorporate structural and operational features described in connection with any of the embodiments of the capacitor module **1204** described herein.

(92) The energy retainer portion **1306** may comprise a device or multiple devices capable of storing energy such as a battery, a battery field and/or a capacitor. For example, in some embodiments the energy retainer portion **1306** may include a battery such as the battery **1202** described herein and may incorporate structural and operational features of the battery **1202**. In some embodiments, the energy retainer portion **1306** may include a battery field such as a battery field comprising batteries **1202** such as shown in FIG. **12**. In some embodiments, the energy retainer portion **1306** may comprise one or more capacitors, such as the capacitor module **1204** described herein.

(93) Additional details regarding FIG. **13** can be found in at least paragraphs [0211]-[0246] of U.S. patent application Ser. No. 17/332,824, which is hereby incorporated by reference.

(94) FIG. **14A** illustrates an example farm equipment such as a tractor that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(95) FIG. **14B** illustrates an example construction equipment that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing

energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(96) FIG. **14C** illustrates an example commercial vehicle such as a tractor-trailer or semi-truck that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(97) FIG. **14D** illustrates an example bus that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(98) FIG. **14E** illustrates an example train that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(99) FIG. **14F** illustrates an example bicycle that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(100) FIG. **14G** illustrates an example scooter that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(101) FIG. **14H** illustrates an example tram that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to

the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**. (102) FIG. **14I** illustrates an example cart such as a golf cart that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(103) FIG. **14J** illustrates an example motorcycle that may incorporate the various components and systems discussed herein such as the apparatus **100**, which may comprise a generator **106** and one or more rollers **102** rotatably couplable to a wheel of the vehicle, as well as a motor **1401**, such as an electric motor, and an energy storage device **1203** which may comprise a capacitor **1204**, a battery **1202** and/or a hypercapacitor **1302**, as discussed herein. The generator **106** may be electrically coupled to the energy storage device **1203** and may be capable of providing energy to the energy storage device **1203**, as discussed herein. The energy storage device **1203** may be electrically coupled to the motor **1401** and may be capable of providing energy to the motor **1401**.

(104) FIG. **15A** is a schematic diagram illustrating an example implementation of an energy generation system **1500**, also referred to herein as “system”. The system **1500** can include one or more of an energy recovery mechanism **1501**, a controller **1503**, a gearbox **1505**, a generator **1507**, and an energy storage **1508** such as a capacitor **1509** and/or a battery **1511**. Figure FIGS. **15A-C** are provided as an examples and are not intended to be limiting. In some implementations, the system **1500** may include less than each of the components shown and/or described in FIG. **15A**. For example, FIG. **15B** shows an energy generation system **1500** including one or more of a energy recovery mechanism **1501**, a controller **1503**, a generator **1507**, and an energy storage **1508**. Further, FIG. **15C** shows an energy regeneration system **1500** including one or more of the energy recovery mechanism **1501**, the controller **1503**, and the energy storage **1508**. In some implementations, the system **1500** may include a plurality of energy recovery mechanisms **1501**, a plurality of generators **1507**, a plurality of capacitors **1509**, and/or a plurality of batteries **1511**.

(105) The system **1500** may be disposed within a vehicle **1510**. The system **1500** may be mobile with the vehicle **1510**. The system **1500** may generate energy in response to a movement or motion of the vehicle **1510** and/or a movement or motion of components of the vehicle **1510** (for example, a drive shaft, axel, rotor). The system **1500** may generate energy when the vehicle **1510** is stationary. The system **1500** may generate energy to provide to the vehicle **1510**. The system **1500** may provide energy to the vehicle **1510** to cause the vehicle **1510** to move. The vehicle **1510** may be configured to travel on a ground surface. The vehicle **1510** may be configured to travel on a water surface. The vehicle **1510** may be configured to travel through air. The vehicle **1510** may be, and/or incorporate features of, any of the example vehicle shown and/or discussed herein, such as with references to FIGS. **14A-15J**.

(106) The vehicle **1510** can include one or more wheels **1512** (for example, wheel **1512A**, wheel **1512B**). The vehicle **1510** can include a drive shaft **1514**. The vehicle can include a motor **1516**. The motor **1516** may be a traction motor. The motor **1516** may provide locomotive power to the vehicle **1510** to cause the vehicle **1510** to move. The motor **1516** may be an electric motor. The motor **1516** may generate mechanical energy in response to electrical energy. The motor **1516** may be coupled with the drive shaft **1514**. The motor **1516** may cause the drive shaft **1514** to rotate. The drive shaft **1514** may be coupled with the wheels **1512**. The drive shaft **1514** may cause the wheels **1512** to rotate.

(107) The energy recovery mechanism **1501** may be rotatably coupled with the drive shaft **1514** or

another rotating component of the vehicle. The energy recovery mechanism **1501** may include one or more rollers that rotates in response to a rotation of the drive shaft **1514**. The generator **1507** may be rotatably coupled to the energy recovery mechanism **1501**. The generator **1507** may generate an electrical output in response to a rotation of the one or more rollers of the energy recovery mechanism **1501**. The generator **1507** may be coupled to the energy recovery mechanism **1501** via one or more of a flexible arm, shaft, rod, axle, gear, pulley, chain, or the like. The one or more rollers of the energy recovery mechanism **1501** may include similar structural and/or operational features as any of the other example rollers shown and/or discussed herein (for example, FIGS. **1-10B**).

(108) The energy recovery mechanism **1501** may be positioned adjacent to, but not in contact with, the drive shaft **1514**. In some embodiments, the drive shaft **1514** may be magnetic such that it includes a magnetic field. In some embodiments, the drive shaft **1514** may induce a current to flow in the energy recovery mechanism **1501**. In some embodiments, the current may be converted to voltage and stored in the energy storage **1508**.

(109) The energy recovery mechanism **1501** may be optionally coupled with the generator **1507** via a gearbox **1505** (for example, FIG. **15C**). The gearbox **1505** may include one or more gears which may be one or more sizes. The gearbox **1505** can be coupled to the energy recovery mechanism **1501** and to generator **1507**. The gearbox **1505** can adjust a rotational velocity of a rotatable component of the generator **1507** relative to a rotational velocity of a rotatable component of the one or more rollers. For example, the one or more rollers may be rotatably coupled to a first gear of the gearbox **1505** and the generator **1507** may be rotatably coupled to a second gear of the gearbox **1505**. The first and second gears of the gearbox **1505** may be rotatably coupled. The first and second gears may be different sizes, including having different diameters, such that rotation of the first gear at a first angular velocity causes rotation of the second gear at a second angular velocity. The gearbox **1505** can change a ratio of angular velocity between the one or more rollers and a rotational component of the generator **1507** by changing a gear to which the one or more rollers and/or generator **1507** is rotatably coupled. Changing a ratio of angular velocity between the one or more rollers and a rotatable component of the generator **1507** may change a rate at which the generator **1507** generates an electrical output such as for a given angular velocity of the one or more rollers. The gearbox **1505** can adjust the ratio of rotation, such as by changing the gear to which the one or more rollers and the generator **1507** is rotatably coupled, according to user input and/or according to operational settings, according to any of the examples discussed herein.

(110) In some implementations, the gearbox **1505** may rotatably decouple the one or more rollers from the generator **1507** such that rotation of the one or more rollers does not cause the generator **1507** to generate energy. For example, the gearbox **1505** may transition the one or more rollers between an engaged state and a disengaged state by rotatably decoupling the one or more rollers from the generator **1507**. The generator **1507** may not generate energy in response to a rotation of the one or more rollers in the disengaged state. In some implementations, the term “engaged state” and the term “extended state” may be used interchangeably. In some implementations, the term “disengaged state” and the term “retracted state” may be used interchangeably.

(111) The generator **1507** may be electrically coupled with the capacitor **1509**. The generator **1507** may be electrically coupled with the capacitor **1509** via one or more switches or relays. The generator **1507** may be electrically coupled with the battery **1511** via one or more diodes biased toward the capacitor **1509**. The generator **1507** may disperse energy to the capacitor **1509**. The capacitor **1509** may include one or more capacitors. The capacitor **1509** may include one or more ultracapacitors, supercapacitors, or the like. The capacitor **1509** may be configured to store up to 10V, 50V, 100V, 200V, 300V, 400V, or the like.

(112) The generator **1507** may be electrically coupled with the battery **1511**. The generator **1507** may be electrically coupled with the battery **1511** via one or more switches or relays. The generator **1507** may be electrically coupled with the battery **1511** via one or more diodes biased toward the

battery **1511**. The generator **1507** may disperse energy to the battery **1511**. The battery **1511** may include one or more batteries. The battery **1511** may include one or more lithium based batteries. The battery **1511** may not include lithium. The battery **1511** may be configured to store up to 10V, 50V, 100V, 200V, 300V, 400V, or the like.

(113) The generator **1507** may be electrically coupled with the motor **1516**. The generator **1507** may be electrically coupled with the motor **1516** via one or more switches or relays. The generator **1507** may be electrically coupled with the motor **1516** via one or more diodes biased toward the motor **1516**. The generator **1507** may disperse energy to the motor **1516**.

(114) The capacitor **1509** may be electrically coupled with the battery **1511**. The capacitor **1509** may be electrically coupled with the battery **1511** via one or more diodes. The diodes may be biased toward the battery **1511** and may prevent a flow of energy from the battery **1511** to the capacitor **1509**. The one or more diodes may allow energy to flow from the capacitor **1509** to the battery **1511**. The capacitor **1509** may be electrically coupled with the battery **1511** via one or more switches or relays. The capacitor **1509** may disperse energy to the battery **1511**. The battery **1511** may receive energy from the capacitor **1509**. In some implementations, the capacitor **1509** and/or the battery **1511** may include similar structural and/or operational features as the hypercapacitor **1302** shown and/or discussed herein.

(115) The capacitor **1509** may be electrically coupled with the motor **1516**. The capacitor **1509** may be electrically coupled with the motor **1516** via one or more switches or relays. The capacitor **1509** may be electrically coupled with the motor **1516** via one or more diodes biased toward the motor **1516**. The capacitor **1509** may disperse energy to the motor **1516**. The motor **1516** may receive energy from the capacitor **1509**.

(116) The battery **1511** may be electrically coupled with the motor **1516**. The battery **1511** may be electrically coupled with the motor **1516** via one or more switches or relays. The battery **1511** may be electrically coupled with the motor **1516** via one or more diodes biased toward the motor **1516**. The battery **1511** may disperse energy to the motor **1516**. The motor **1516** may receive energy from the battery **1511**.

(117) The controller **1503** may include one or more hardware processors configured to execute program instructions to cause the controller **1503** or other components of the system **1500** and/or vehicle **1510** to perform one or more operations. The controller **1503** may be in electrical communication with one or more components. The controller **1503** may receive data from one or more components. The controller **1503** may transmit instructions to one or more components. The controller **1503** may be in electrical communication with the energy recovery mechanism **1501**. The controller **1503** may receive data relating to an operation of the energy recovery mechanism **1501**. Such data may include a rotational velocity and/or acceleration of the roller or a magnitude of a voltage or current induced in the energy recovery mechanism **1501**. The controller **1503** may issue instructions, such as to an actuator, to cause the energy recovery mechanism **1501** to transition between the engaged state and the disengaged state. The controller **1503** may be in communication with the gearbox **1505**. The controller **1503** may receive data relating to an operation of the gearbox **1505**. The controller **1503** may issue instructions to cause the gearbox **1505** to perform one or more operations such as changing a gear to which the roller and/or the generator **1507** is coupled to change a ratio of rotational velocity between the roller and the generator **1507**. The controller **1503** may be in communication with the generator **1507**. The controller **1503** may receive data relating to an operation of the generator **1507** such as an amount of energy generated by the generator **1507** and/or a rate of energy generated by the generator **1507**. The controller **1503** may issue instructions to cause the generator **1507** to perform one or more operations. The controller **1503** may be in communication with the capacitor **1509**. The controller **1503** may receive data relating to an operation of the capacitor **1509** such as an amount of energy stored in the capacitor **1509**, a voltage of the capacitor **1509**, a rate of charge or discharge of the capacitor **1509**, or the like. The controller **1503** may be in communication with the battery **1511**.

The controller **1503** may receive data relating to an operation of the battery **1511** such as an amount of energy stored in the battery **1511**, a voltage of the battery **1511**, a rate of charge or discharge of the battery **1511**, or the like. The controller **1503** may be in communication with the motor **1516**. The controller **1503** may receive data relating to an operation of the motor **1516** such as an energy consumed by the motor **1516** or the like. The controller **1503** may be in communication with the wheels **1512**. The controller **1503** may receive data relating to one or more operations of the wheels **1512** such as an angular velocity or acceleration of the wheels **1512**.

(118) The controller **1503** may control whether the energy recovery mechanism **1501** is the engaged state or in the disengaged state. According to some embodiments, in the engaged state, the energy recovery mechanism **1501** may be in physical contact with the drive shaft **1514**. According to some embodiments, in the engaged state, the energy recovery mechanism **1501** is not in physical contact with the drive shaft **1514**. According to some embodiments, in the engaged state, the roller of the energy recovery mechanism **1501** may be rotatably coupled to the drive shaft **1514** and may rotate in response to a rotation of the drive shaft **1514**. In some implementations, in the disengaged state, the roller of the energy recovery mechanism **1501** may not be in physical contact with the drive shaft **1514** such that rotation of the drive shaft **1514** does not cause the roller to rotate. In some implementations, in the disengaged state, the roller may be in physical contact with the drive shaft **1514** such that rotation of the drive shaft **1514** causes the roller to rotate but the energy recovery mechanism **1501** may not be rotatably coupled to the generator **1507** such that rotation of the roller does not cause the generator **1507** to generate an electrical output. In some embodiments, the energy recovery mechanism **1501** may switch from an engaged state to a disengaged state rapidly by moving the energy recovery mechanism **1501** to and from contact with the drive shaft **1514**. The controller **1503** may cause the energy recovery mechanism **1501** to transition between the engaged and disengaged states in response to one or more of a velocity or acceleration of the vehicle **1510**, angular velocity or acceleration of the wheels **1512**, an amount of energy or rate of energy generated by the generator **1507**, an energy demand required by the motor **1516**, an amount of energy stored in the capacitor **1509**, an amount of energy stored in the battery **1511**, a rate of discharge of the capacitor **1509**, a rate of discharge of the battery **1511**, a user input, or the like.

(119) The controller **1503** may control the ratio of angular velocity between the energy recovery mechanism **1501** and a rotational member of the generator **1507**. The controller **1503** may adjust the ratio of angular velocity between the energy recovery mechanism **1501** and the generator **1507** to change a rate at which the generator **1507** generates energy. The controller **1503** may adjust the ratio of angular velocity between the energy recovery mechanism **1501** and the generator **1507** to change a torque applied by the roller of the energy recovery mechanism **1501** on the drive shaft **1514**. As an example, increasing a torque applied by the roller on the drive shaft **1514** may cause the drive shaft **1514** to decrease angular velocity which may be desirable such as when decelerating the vehicle. The controller **1503** may control the ratio of angular velocity between the roller and the generator **1507** in response to one or more of a velocity or acceleration of the vehicle **1510**, angular velocity or acceleration of the wheels **1512**, an amount of energy or rate of energy generated by the generator **1507**, an energy demand required by the motor **1516**, an amount of energy stored in the capacitor **1509**, an amount of energy stored in the battery **1511**, a rate of discharge of the capacitor **1509**, a rate of discharge of the battery **1511**, a user input, or the like.

(120) The controller **1503** may control the force exerted by the energy recovery mechanism **1501** on the drive shaft **1514**. The controller **1503** may adjust the force exerted by the energy recovery mechanism **1501** on the drive shaft **1514** to change a rate at which the generator **1507** generates energy. The controller **1503** may adjust the force exerted by the energy recovery mechanism **1501** on the drive shaft **1514** to change a torque applied by the roller on the drive shaft **1514**. As an example, increasing a torque applied by the roller on the drive shaft **1514** may cause the drive shaft **1514** to decrease angular velocity which may be desirable such as when decelerating the vehicle. The controller **1503** may control the force exerted by the energy recovery mechanism **1501** on the

drive shaft **1514** in response to one or more of a velocity or acceleration of the vehicle **1510**, angular velocity or acceleration of the wheels **1512**, an amount of energy or rate of energy generated by the generator **1507**, an energy demand required by the motor **1516**, an amount of energy stored in the capacitor **1509**, an amount of energy stored in the battery **1511**, a rate of discharge of the capacitor **1509**, a rate of discharge of the battery **1511**, a user input, or the like.

(121) The controller **1503** may control a flow of energy in the system **1500**. The controller **1503** can control whether energy generated at the generator **1507** or the energy recovery mechanism **1501** is dispersed to the capacitor **1509**, to the battery **1511**, and/or to motor **1516**. As an example, the controller **1503** may electrically couple and/or decouple the generator **1507** or energy recovery mechanism **1501** from any of the capacitor **1509**, the battery **1511**, and/or the motor **1516**. As another example, the controller **1503** may electrically couple and/or decouple the capacitor **1509** from the motor **1516**, may electrically couple and/or decouple the capacitor **1509** from the battery **1511**, and/or may electrically couple and/or decouple the battery **1511** from the motor **1516**. In some implementations, the controller **1503** may electrically couple and decouple various electrical components by controlling whether switches, relays, or the like that are disposed between electrical components are in an open or a closed state to control whether energy may flow between the electrical components. As an example, the controller **1503** may control whether one or more switches electrically coupled with the generator **1507** conducts energy or prevents energy from passing from the generator **1507** to the capacitor **1509**, the battery **1511**, and/or the motor **1516**.

(122) In an example embodiment, a driver of a vehicle may receive a signal from the controller **1503** when at least a portion of the energy storage **1508** is full. The driver may send a signal to the controller **1503** to transfer the energy within the energy storage **1508** to the motor **1516**. As the energy is transferred to the motor **1516**, the energy recovery mechanism **1501** is in a disengaged state. The driver may send a signal to the controller **1503** to stop the transfer of energy within the energy storage **1508** to the motor **1516**. When the energy transfer is stopped, the energy recovery mechanism **1501** may automatically switch to an engaged state.

(123) In some embodiments, a flexible arm attaches the energy recovery mechanism **1501** to a feature of the vehicle. In some embodiments, a shaft, rod, actuator or other connecting mechanical feature may be used instead of the flexible arm as described herein. The feature of the vehicle may include the vehicle housing, a structural component located within the vehicle, the gearbox **1505**, generator **1507**, or the energy storage **1508** (for example, one or both of the capacitor **1509** or battery **1511**). In some embodiments, the flexible arm may be rotatably coupled with the energy recovery mechanism **1501** and any of the above-mentioned features. In some embodiments, the flexible arm is attached to the **1501** via a joint. In some embodiments the joint may be rigidly fixed. In other embodiments, the joint may be a rotatable coupling. In other embodiments, the joint may be a ball and socket joint that allows for 360-degree rotation of the roller housing relative to the flexible arm. In other embodiments, the joint may be a universal joint that transmits motion and power from the roller of the energy recovery mechanism **1501**.

(124) In some embodiments, the flexible arm exerts a downward force on the energy recovery mechanism **1501**. In some embodiments, the flexible arm exerts a downward force only in an engaged state. In some embodiments, the flexible arm exerts a downward force in both the engaged state and the disengaged state. In some embodiments, the downward force ensures that the energy recovery mechanism **1501** maintains constant contact with the drive shaft **1514**. Further, the flexible arm may be configured to accommodate any oscillation of the drive shaft **1514** including vertical or horizontal movement. This allows the flexible arm to flex, bend, or move while maintaining the downward force. In some embodiments, the flexible arm is configured to pivot about one or more joints.

(125) The term “downward force,” is used to signify a force vector, comprising both magnitude and direction, that is normal to, or tangentially adjacent to, a plane of contact between the roller and the drive shaft **1514**. Further, the magnitude of the force vector may be adjustable while the system

or apparatus **1500** is in the engaged state. For example, the controller **1503** may control the amount of force exerted on the drive shaft **1514** by the flexible arm. This may be done automatically, or via user command. The controller **1503** may control the magnitude of the force in response to one or more of a velocity or acceleration of the vehicle **1510**, angular velocity or acceleration of the wheels **1512**, an amount of energy or rate of energy generated by the generator **1507**, an energy demand required by the motor **1516**, an amount of energy stored in the capacitor **1509**, an amount of energy stored in the battery **1511**, a rate of discharge of the capacitor **1509**, a rate of discharge of the battery **1511**, a user input, or the like.

(126) Frictional force is a function of the normal force between two objects. Thus, an increase in the downward force on the roller results in an increase in the amount of friction between the roller and the drive shaft **1514**. An increase in friction between the roller and the drive shaft **1514** results in greater contact and a decrease in slippage which in turn results in a greater conversion of rotational movement from the drive shaft **1514** to the energy recovery mechanism **1501** via the roller. Thus, the downward force serves to increase the overall energy efficiency of the system.

(127) The flexible arm may be made from a variety of materials, such as but not limited to, metals, polymers, or fiber-based materials. The flexible arm may be comprised of a single component or a combination thereof. These components may bend or flex to exert a downward force and accommodate any movement between the feature of the vehicle and the drive shaft **1514**.

Additionally, the flexible arm may be made up of a combination of components made of rigid material that are coupled together via joints or hinges such that the arm, as a whole, flexes. In some embodiments, the flexible arm is positioned parallel to the rotational axis of the drive shaft **1514**. In some embodiments, the shape of the flexible arm changes as the force exerted on the drive shaft **1514** increases. In some embodiments, a spring or actuator is coupled to the flexible arm and applies to cause or increase the downward force.

(128) In some embodiments, a surface of the one or more rollers and/or a surface of the drive shaft **1514** which contacts the one or more rollers, may include a material and/or texture designed to increase friction. In some embodiments, the material may include silicon, rubber, polymer or other composite with a high coefficient of friction. In some embodiments, this material may have a coefficient of friction that is higher than the surface of the drive shaft **1514** which does not contact the one or more rollers. Frictional force is a function of the coefficient of friction of the surface of an object. Thus, an increased coefficient of friction of either the surface of the one or more rollers or the drive shaft **1514** results in an increase in the amount of friction between those surfaces, minimize the amount of slippage that occurs between those surfaces and results in an increase to the overall energy efficiency of the system. Further, the material may be high in hardness or resistant to erosion and thus prolong the life of the drive shaft and/or rollers. In some embodiments, the texture includes bumps, ridges, and other irregularities to increase the roughness and friction. In some embodiments, the surface of the one or more rollers and drive shaft include interlocking teeth similar to a gear. In some embodiments, the flexible arm, energy recovery mechanism **1501**, or parts of the energy recovery mechanism **1501** are configured to be rapidly replaceable such as during a pit stop of a racing event.

(129) FIG. **16** illustrates a cross section view of an example drive shaft **1614** and rollers **1601** (for example, rollers **1601A**, **1601B**, **1601C**, **1601D**). The rollers **1601** may have a smaller diameter than the drive shaft **1614**. In some implementations, rollers **1601** may have a larger diameter than the drive shaft **1614**. In some implementations, one or more of the rollers **1601** may have a different diameter than one or more of the other rollers **1601**. In some implementations, each of the rollers **1601** may have the same diameter. The drive shaft **1614** may be encompassed by a plurality of rollers **1601**. In the example shown, four rollers **1601** contact the drive shaft **1614** at various locations around a circumference of the drive shaft **1614**. In some implementations, less than four rollers **1601** may encompass the drive shaft **1614**. In some implementations, more than four rollers **1601** may encompass the drive shaft **1614**. In some implementations, the rollers **1601** may

encompass the drive shaft **1614** at non-symmetrical locations around the drive shaft **1614**. In some implementations, the rollers **1601** may encompass the drive shaft **1614** at symmetrical locations around the drive shaft **1614**. The rollers **1601** may rotate at a different angular velocity than the drive shaft **1614**. The rollers **1601** may rotate as a same angular velocity as the drive shaft **1614**. (130) As shown in FIG. **16**, the rollers **1601** can include a smooth outer surface. In some implementations, a surface of the rollers **1601** may include texture such as gears, notches, grooves, or the like which may increase a friction between the drive shaft **1614** and the rollers **1601** to facilitate a rotational response of the rollers **1601** due to rotation of the drive shaft **1614**.

(131) FIG. **17** is a perspective view of an example drive shaft **1714** and energy recovery mechanism **1702**. The energy recovery mechanism **1702** includes one or more rollers **1701** (for example, roller **1701A**, **1701B**, **1701C**) disposed within a housing **1720**. The one or more rollers **1701** may each resemble a cylinder with a length that is substantially a length of the housing **1720**. In some embodiments, the length of the one or more rollers **1701** may be less than the length of the housing **1720**. The housing **1720** may encompass the drive shaft **1714**. In some implementations, the housing **1720** may encompass an entire circumference of the drive shaft **1714**. In some implementations, the housing **1720** may encompass less than an entire circumference of the drive shaft **1714**. The housing **1720** may house three rollers **1701**. The housing **1720** may house less than three rollers **1701**. The housing **1720** may house more than three rollers **1701**. A portion of the rollers **1701** may be exposed to an exterior surface of the housing **1720** to be coupled with a generator. The rollers **1701** may rotate relative to the housing **1720**. The drive shaft **1714** may rotate relative to the housing **1720**. The one or more rollers **1701** may be rotatably coupled to the housing **1720**.

(132) In some implementations, the housing **1720** may house a generator rotatably coupled to one or more of the rollers **1701** and configured to generate energy in response to a rotation of the roller(s) **1701**. In some implementations, a cable may electrically connect the energy recovery mechanism **1702** to an energy storage of the system. In some implementations, a shaft or flexible arm may connect the energy recovery mechanism **1702** to a feature of the vehicle.

(133) FIG. **18** illustrates a cross section view of an example drive shaft **1814** and energy recovery mechanism **1802**. The energy recovery mechanism **1802** includes a housing **1820** and one or more rollers **1801** (for example, roller **1801A**, **1801B**, **1801C**, **1801D**). The housing **1820** may ensure that the rollers **1801** remain in contact with the drive shaft **1814** as desired. The housing **1820** may apply a force to the rollers **1801** to ensure that the rollers **1801** remain in contact with the drive shaft **1814**. The housing **1820** may not contact the drive shaft **1814**. The housing **1820** may not rotate. In some implementations, the housing **1820** may change diameter to change a force applied to the rollers **1801** on the drive shaft **1814**. In some implementations, the housing **1820** may change a diameter to remove the rollers **1801** from contacting the drive shaft **1814**, such as in a disengaged state. In some implementations, the rollers **1801** may remain in contact with the drive shaft **1814** in a disengaged state.

(134) FIG. **19** illustrates a cross section view of an example drive shaft **1914** and energy recover mechanism **1902**. The energy recovery mechanism **1902** includes an housing **1920** and one or more rollers **1901** (for example, roller **1901A**, **1901B**, **1901C**, **1901D**). The housing **1920** may cover a portion of the drive shaft **1914**. The housing **1920** may encompass less than an entire circumference of the drive shaft **1914**. In some implementations, multiple energy recover mechanisms **1902** may encompass the drive shaft **1914**. For example, multiple energy recover mechanism **1902** may encompass various portions around a circumference of the drive shaft **1914** at a same length of the drive shaft **1914**.

(135) The housing **1920** may cause the rollers **1901** to contact the drive shaft **1914**. The housing **1920** may cause the rollers **1901** to remove from contacting the drive shaft **1914**. The housing **1920** may transition between causing the rollers **1901** to contact the drive shaft **1914** and causing the rollers **1901** to not contact the drive shaft **1914**. For example, a flexible arm, lever, or other actuator

may physically move the energy recover mechanism **1902** such that the rollers **1901** contact the drive shaft **1914** or do not contact the drive shaft **1914**. In some implementations, a flexible arm, lever, or other actuator may apply a force to the energy recover mechanism **1902** to change a force applied by the rollers **1901** on the drive shaft **1914**.

(136) FIG. **20A** illustrates a sideview of an energy recovery mechanism **2002** and a drive shaft **2014**. FIG. **20B** illustrates a sideview of the energy recovery mechanism **2002** and a drive shaft **2015** with a groove.

(137) The energy recovery mechanism **2002** includes a housing **2020** and one or more rollers **2001** (for example **2001A**, **2001B**, **2001C**, **2001D**, **2001E**, **2001F**). The one or more rollers **2001** are rotationally aligned and positioned tangentially adjacent to the drive shaft **2014**. The one or more rollers **2001A-C** are coupled to a roller axel **2012A**. The one or more rollers **2001D-F** are coupled to a roller axel **2012B**. Each roller axel **2012A, B** is attached to the housing **2020**. The roller axels **2012A, B** help to keep the one or more rollers aligned. In some embodiments, the roller axels **2012A, B** are rotationally coupled to a flexible arm, shaft, gear, pulley etc. to transmit the rotational energy received from the drive shaft **2014** to a generator, gear box, or energy storage.

(138) Drive shaft **2015** of FIG. **20B** includes one or more grooves **2024** positioned circumferentially along the shaft. The one or more grooves **2024** are spaced apart to match a spacing of the one or more rollers **2001**. The one or more grooves **2024** are positioned to accommodate each of the one or more rollers **2001**. The point of contact between each one or more rollers **2001** may be at the one or more grooves **2024**. Each of the one or more grooves **2024** may have a width that is substantially the same as the width of the one or more rollers **2001**. The cross-sectional shape of the one or more grooves **2024** may mirror that of the one or more rollers **2001** to maximize contact. The depth of the one or more grooves **2024** may vary depending on the diameter of the one or more rollers **2001** and the thickness of the drive shaft **2015**. The one or more grooves **2024** may operate to guide the one or more rollers **2001** as the drive shaft **2015** rotates. Further, the one or more grooves **2024** provides an increase in contact area between the one or more rollers **2001** and the drive shaft **2015**.

(139) FIG. **21A** illustrates a sideview of an energy recovery mechanism **2102** in contact with a drive shaft **2114**. FIG. **21B** illustrates a sideview of the energy recovery mechanism **2102** not in contact with the drive shaft **2114**. The energy recovery mechanism **2102** includes one or more rollers **2101** (for example **2101A**, **2101B**, **2101C**, **2101D**) and a housing **2120**. A joint **2113** is attached to a backside of the housing **2120** and couples the energy recovery mechanism **2102** to a flexible arm **2117**. The flexible arm **2117** moves the energy recovery mechanism **2102** between the contact and noncontact positions. In some embodiments, the contact position is an engaged state. In some embodiments, the noncontact position is the disengaged state. In some embodiments, the flexible arm **2117** is rotatably and/or pivotally coupled to the joint **2113** which is rotatably coupled to the one or more rollers **2101**.

(140) FIG. **22** is a top-down illustration of a system **2202** with multiple energy recovery mechanisms positioned adjacent a drive shaft **2214**. A first energy recovery mechanism **2202A** is positioned on one side of the drive shaft **2214** and attached to a first flexible arm **2217**. A second energy recovery mechanism **2202B** is positioned on another side of the drive shaft **2214** and attached to a second flexible arm **2217B**. The first energy recovery mechanism **2202A** is laterally spaced apart from the second energy recovery mechanism **2202B**. Both energy recovery mechanisms are in an engaged state with the drive shaft **2214**. In some embodiments, the energy recovery mechanisms may be positioned such that they are not laterally spaced apart. In some embodiments, more than two energy recovery mechanisms may engage the drive shaft **2214**.

(141) FIG. **23A** illustrates an embodiment with a cut-away view of an energy recovery mechanism **2302** engaged with a drive shaft **2314A**. The energy recovery mechanism **2302** includes one or more rollers **2301** (for example **2301A**, **2301B**, **2301C**) and a housing **2320**. A flexible arm **2317** is attached to the energy recovery mechanism **2302** and a feature of the vehicle.

(142) FIG. 23B illustrates another embodiment of the energy recovery mechanism **2302** engaged with the drive shaft **2314B**. The drive shaft **2314B** includes an outer surface **2321** which contacts the one or more rollers **2301**. The outer surface **2321** includes a material and/or texture with a high coefficient of friction.

(143) FIG. 23C illustrates another embodiment of the energy recovery mechanism **2302** engaged with a drive shaft **2314C**. The drive shaft **2314C** includes a shoulder **2322** which has a larger diameter than the rest of the shaft. The shoulder **2322** contacts the one or more rollers **2301**. The shoulder **2322** optionally includes an outer surface having a material and/or texture with a high coefficient of friction.

(144) FIG. 23D illustrates another embodiment of the energy recovery mechanism **2302** engaged with a drive shaft **2314D**. The drive shaft **2314D** includes a groove **2324** which has a smaller diameter than the rest of the shaft. The groove **2324** contacts the one or more rollers **2301**. The groove **2324** optionally may include an outer surface having a material and/or texture with a high coefficient of friction.

(145) FIG. 23E illustrates another embodiment of the energy recovery mechanism **2302** engaged with a drive shaft **2314E**. The drive shaft **2314E** includes the groove **2324** which has a smaller diameter than the rest of the shaft. The groove **2324** contacts the one or more rollers **2301**. The groove **2324** may include an outer surface having a material and/or texture with a high coefficient of friction. Additionally, portions of the shaft immediately surrounding the groove **2324** may include this material. Here, the one or more rollers **2301** may take a cylindrical form that contacts the outer surface of the drive shaft **2314E** not including the groove **2324**. The one or more rollers **2301** may have a raised portion that extends radially and forms a roller bump. The roller bump will have a diameter that is larger than the roller diameter. The difference between the roller diameter and the diameter of the roller bump shall be substantially equal to the depth of the groove **2324** multiplied by a factor of two. The depth of the groove is substantially equal to the distance between the surface of the drive shaft **2314E** and the surface of the groove **2324**. The width of the roller bump may be less than or in some embodiments substantially equal to, but not in excess of, the groove **2324** width.

(146) FIG. 24 illustrates a sideview of an example embodiment of an energy recovery mechanism **2402** and where the energy is recovered without physical contact with a drive shaft **2414**. The energy recovery mechanism **2402** includes a housing **2420** and one or more wires **2401** positioned within. A flexible arm **2417** connects the housing **2420** to a feature of the vehicle.

(147) The drive shaft **2414** is magnetic and includes a magnetic north and magnetic south which creates a magnetic field. In some embodiments, the whole drive shaft **2414** is magnetic. In some embodiments, only a portion of the drive shaft **2414** is magnetic. In some embodiments, one or more magnets are fastened to the drive shaft. In some embodiments, one or more magnets are placed within the drive shaft. The magnets and/or drive shaft include permanent magnets. In some embodiments, the magnets and/or drive shaft include electromagnets.

(148) A flexible arm **2417** is attached to the energy recovery mechanism **2402**. The flexible arm **2417** is configured to move the energy recovery mechanism **2402** to adjust the distance between the energy recovery mechanism **2402** and the drive shaft **2414** based on a signal received from a controller. The flexible arm **2417** may also electrically coupled the **2420** to a feature of the vehicle such as an energy storage (capacitor and/or battery), generator, or motor.

(149) The housing **2420** may be rectangular in shape. In some embodiments, the shape of the housing **2420** may be curved toward the drive shaft **2414**. In some embodiments, the housing **2420** may encompass the drive shaft **2414**.

(150) In use, the magnetic drive shaft **2414** rotates in a clockwise or counterclockwise direction. This rotation causes the magnetic field of the shaft to rotate/alternate, thus inducing an electromagnetic force (EMF) in the one or more wires of the energy recovery mechanism **2402** and a current to flow in the wires. According to Faraday's law, the resulting EMF is proportional to the

rate of change of the magnetic field and the number of turns in the coil of wire.

(151) The one or more wires **2401** may be oriented to optimize the magnitude of the induced current. This may include one or more hoops, coils etc. The one or more wires may be connected to a resistor to convert the current to voltage. In some embodiments, the resistor may be located within the energy recovery mechanism **2402**. In some embodiments, the current is transferred out of the energy recovery mechanism **2402** before the current is converted to voltage.

(152) A benefit of the energy recovery mechanism **2402** is that it does not require direct contact with the drive shaft **2414**. This increases the longevity of the energy recovery mechanism **2402** and drive shaft **2414** by eliminates friction and the associated wear from mechanical contact.

(153) FIG. **25** illustrates a sideview of an example embodiment of an energy recovery mechanism **2502** positioned adjacent a magnetic drive shaft **2514**. The energy recovery mechanism **2502** includes a housing **2520** and one or more wires **2501** positioned within. A flexible arm **2517** connects the energy recovery mechanism **2502** to a feature of the vehicle. The one or more wires **2501** within the housing **2520** are oriented to form hoops positioned parallel to the drive shaft **2514**. In some embodiments, one or more of the energy recovery mechanisms may be positioned adjacent to the drive shaft **2514**.

ADDITIONAL EMBODIMENTS

(154) As used herein, “system,” “instrument,” “apparatus,” and “device” generally encompass both the hardware (for example, mechanical and electronic) and, in some implementations, associated software (for example, specialized computer programs for graphics control) components.

(155) It is to be understood that not necessarily all objects or advantages may be achieved in accordance with any particular embodiment described herein. Thus, for example, those skilled in the art will recognize that certain embodiments may be configured to operate in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other objects or advantages as may be taught or suggested herein.

(156) Each of the processes, methods, and algorithms described in the preceding sections may be embodied in, and fully or partially automated by, code modules executed by one or more computer systems or computer processors including computer hardware. The code modules may be stored on any type of non-transitory computer-readable medium or computer storage device, such as hard drives, solid state memory, optical disc, and/or the like. The systems and modules may also be transmitted as generated data signals (for example, as part of a carrier wave or other analog or digital propagated signal) on a variety of computer-readable transmission mediums, including wireless-based and wired/cable-based mediums, and may take a variety of forms (for example, as part of a single or multiplexed analog signal, or as multiple discrete digital packets or frames). The processes and algorithms may be implemented partially or wholly in application-specific circuitry. The results of the disclosed processes and process steps may be stored, persistently or otherwise, in any type of non-transitory computer storage such as, for example, volatile or non-volatile storage.

(157) Many other variations than those described herein will be apparent from this disclosure. For example, depending on the embodiment, certain acts, events, or functions of any of the algorithms described herein can be performed in a different sequence, can be added, merged, or left out altogether (for example, not all described acts or events are necessary for the practice of the algorithms). Moreover, in certain embodiments, acts or events can be performed concurrently, for example, through multi-threaded processing, interrupt processing, or multiple processors or processor cores or on other parallel architectures, rather than sequentially. In addition, different tasks or processes can be performed by different machines and/or computing systems that can function together.

(158) The various illustrative logical blocks, modules, and algorithm elements described in connection with the embodiments disclosed herein can be implemented as electronic hardware, computer software, or combinations of both. To clearly illustrate this interchangeability of hardware and software, various illustrative components, blocks, modules, and elements have been

described herein generally in terms of their functionality. Whether such functionality is implemented as hardware or software depends upon the particular application and design constraints imposed on the overall system. The described functionality can be implemented in varying ways for each particular application, but such implementation decisions should not be interpreted as causing a departure from the scope of the disclosure.

(159) The various features and processes described herein may be used independently of one another, or may be combined in various ways. All possible combinations and sub-combinations are intended to fall within the scope of this disclosure. In addition, certain method or process blocks may be omitted in some implementations. The methods and processes described herein are also not limited to any particular sequence, and the blocks or states relating thereto can be performed in other sequences that are appropriate. For example, described blocks or states may be performed in an order other than that specifically disclosed, or multiple blocks or states may be combined in a single block or state. The example blocks or states may be performed in serial, in parallel, or in some other manner. Blocks or states may be added to or removed from the disclosed example embodiments. The example systems and components described herein may be configured differently than described. For example, elements may be added to, removed from, or rearranged compared to the disclosed example embodiments.

(160) The various illustrative logical blocks and modules described in connection with the embodiments disclosed herein can be implemented or performed by a machine, such as a general purpose processor, a digital signal processor (“DSP”), an application specific integrated circuit (“ASIC”), a field programmable gate array (“FPGA”) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor can be a microprocessor, but in the alternative, the processor can be a controller, microcontroller, or state machine, combinations of the same, or the like. A processor can include electrical circuitry configured to process computer-executable instructions. In another embodiment, a processor includes an FPGA or other programmable devices that performs logic operations without processing computer-executable instructions. A processor can also be implemented as a combination of computing devices, for example, a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Although described herein primarily with respect to digital technology, a processor may also include primarily analog components. For example, some, or all, of the signal processing algorithms described herein may be implemented in analog circuitry or mixed analog and digital circuitry. A computing environment can include any type of computer system, including, but not limited to, a computer system based on a microprocessor, a mainframe computer, a digital signal processor, a portable computing device, a device controller, or a computational engine within an appliance, to name a few.

(161) The elements of a method, process, or algorithm described in connection with the embodiments disclosed herein can be embodied directly in hardware, in a software module stored in one or more memory devices and executed by one or more processors, or in a combination of the two. A software module can reside in RAM memory, flash memory, ROM memory, EPROM memory, EEPROM memory, registers, hard disk, a removable disk, a CD-ROM, or any other form of non-transitory computer-readable storage medium, media, or physical computer storage known in the art. An example storage medium can be coupled to the processor such that the processor can read information from, and write information to, the storage medium. In the alternative, the storage medium can be integral to the processor. The storage medium can be volatile or nonvolatile. The processor and the storage medium can reside in an ASIC. The ASIC can reside in a user terminal. In the alternative, the processor and the storage medium can reside as discrete components in a user terminal.

(162) Conditional language, such as, among others, “can,” “could,” “might,” or “may,” unless

specifically stated otherwise, or otherwise understood within the context as used, is generally intended to convey that certain embodiments include, while other embodiments do not include, certain features, elements and/or steps. Thus, such conditional language is not generally intended to imply that features, elements and/or steps are in any way required for one or more embodiments or that one or more embodiments necessarily include logic for deciding, with or without user input or prompting, whether these features, elements and/or steps are included or are to be performed in any particular embodiment.

(163) Disjunctive language such as the phrase “at least one of X, Y, or Z,” unless specifically stated otherwise, is otherwise understood with the context as used in general to present that an item, term, and so forth, may be either X, Y, or Z, or any combination thereof (for example, X, Y, and/or Z). Thus, such disjunctive language is not generally intended to, and should not, imply that certain embodiments require at least one of X, at least one of Y, or at least one of Z to each be present.

(164) Any process descriptions, elements, or blocks in the flow diagrams described herein and/or depicted in the attached figures should be understood as potentially representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of the embodiments described herein in which elements or functions may be deleted, executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those skilled in the art.

(165) Unless otherwise explicitly stated, articles such as “a” or “an” should generally be interpreted to include one or more described items. Accordingly, phrases such as “a device configured to” are intended to include one or more recited devices. Such one or more recited devices can also be collectively configured to carry out the stated recitations. For example, “a processor configured to carry out recitations A, B and C” can include a first processor configured to carry out recitation A working in conjunction with a second processor configured to carry out recitations B and C.

(166) All of the methods and processes described herein may be embodied in, and partially or fully automated via, software code modules executed by one or more general purpose computers. For example, the methods described herein may be performed by the computing system and/or any other suitable computing device. The methods may be executed on the computing devices in response to execution of software instructions or other executable code read from a tangible computer readable medium. A tangible computer readable medium is a data storage device that can store data that is readable by a computer system. Examples of computer readable mediums include read-only memory, random-access memory, other volatile or non-volatile memory devices, CD-ROMs, magnetic tape, flash drives, and optical data storage devices.

(167) It should be emphasized that many variations and modifications may be made to the herein-described embodiments, the elements of which are to be understood as being among other acceptable examples. All such modifications and variations are intended to be included herein within the scope of this disclosure. The section headings used herein are merely provided to enhance readability and are not intended to limit the scope of the embodiments disclosed in a particular section to the features or elements disclosed in that section. The foregoing description details certain embodiments. It will be appreciated, however, that no matter how detailed the foregoing appears in text, the systems and methods can be practiced in many ways. As is also stated herein, it should be noted that the use of particular terminology when describing certain features or aspects of the systems and methods should not be taken to imply that the terminology is being re-defined herein to be restricted to including any specific characteristics of the features or aspects of the systems and methods with which that terminology is associated.

(168) Those of skill in the art would understand that information, messages, and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced

throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

Claims

1. A system for generating energy in response to a movement of a vehicle, the system comprising: an energy recovery mechanism configured to receive energy from the rotation of a component of the vehicle; an energy storage electrically coupled to the energy recovery mechanism and configured to store the energy as electrical energy; a motor electrically coupled to the energy storage and configured to receive a portion of the electrical energy; a generator electrically coupled with the energy recovery mechanism and the energy storage; and a controller in communication with the energy recovery mechanism, the energy storage, and the motor, wherein the controller further communicates with a driver of the vehicle, wherein the controller receives data from one or more of the energy recovery mechanism, energy storage, generator, and motor, wherein the controller transmits instructions to the energy recovery mechanism to change a total amount of energy received from the rotation of the vehicle component in response to the received data or an instruction from the driver, and wherein the controller transmits instructions to the energy recovery mechanism to control a ratio of angular velocity between the energy recovery mechanism and a rotational member of the generator in response to the received data or an instruction from the driver.
2. The system of claim 1, wherein the energy storage comprises one or more of a battery, a capacitor, or a combination thereof.
3. The system of claim 2, further comprising a generator electrically coupled with the energy recovery mechanism and the energy storage, wherein the controller further receives data from the generator.
4. The system of claim 1, wherein the data comprises a rotational velocity or acceleration of a roller of the energy recovery mechanism.
5. The system of claim 1, wherein the data comprises a magnitude of a voltage or current induced in the energy recovery mechanism.
6. The system of claim 3, wherein the data comprises an amount of energy or a rate of energy generated by the generator.
7. The system of claim 2, wherein the data comprises an amount of energy stored in the capacitor, a voltage of the capacitor, or a rate of charge or discharge of the capacitor.
8. The system of claim 2, wherein the data comprises an amount of energy stored in the battery, a voltage of the battery, or a rate of charge or discharge of the battery.
9. The system of claim 1, wherein the data comprises operational data of the motor.
10. The system of claim 1, wherein the data comprises the speed or acceleration of the vehicle.
11. The system of claim 3, wherein the controller transmits instructions to change a rate or an amount of energy generated by the generator in response to the received data or an instruction from the driver.
12. The system of claim 3, wherein the controller transmits instructions to control a flow of energy between two or more of the energy recovery mechanism, generator, capacitor, battery, and motor in response to the received data or an instruction from the driver.
13. The system of claim 1, wherein the controller transmits instructions to accelerate the vehicle based on the received data or an instruction from the driver.
14. The system of claim 1, wherein the controller transmits instructions to decelerate the vehicle based on received data or an instruction from the driver.
15. A method of generating energy in response to a movement of a vehicle, the method comprising: rotating a component of a vehicle to generate energy; receiving the energy in an energy recovery mechanism positioned adjacent the rotating component of the vehicle; storing the energy in an

energy storage; alerting the driver when a portion of the energy storage is charged; receiving, via the controller, data from one or more of the energy recovery mechanism, energy storage, and motor; changing, via the controller, a total amount of energy received by the energy recovery mechanism in response to the received data or an instruction from the driver; and changing, via the controller, a rate at which a generator rotates to generate energy.

16. The method of claim 15, wherein the energy storage comprises one or more of a battery, a capacitor, or a combination thereof.

17. The method of claim 15, further comprising receiving, via a controller, a signal to convey an electrical output of the energy from the energy storage to the motor; conveying the electrical output to the motor; and stopping the conveyance of the electrical output from the energy storage to the motor upon receipt of a second signal.

18. The method of claim 17, wherein the signal is manually sent by a driver of the vehicle.

19. The method of claim 17, where in the signal is sent automatically upon determining an acceleration of the vehicle or an energy demand of the motor.

20. The method of claim 15, wherein the data comprises a rotational velocity or acceleration of a roller of the energy recovery mechanism.

21. The method of claim 15, wherein the data comprises a magnitude of a voltage or current induced in the energy recovery mechanism.

22. A system for generating energy in response to a movement of a vehicle, the system comprising: an energy recovery mechanism configured to receive energy from the rotation of a component of the vehicle, the energy recovery mechanism comprising a roller; an energy storage electrically coupled to the energy recovery mechanism and configured to store the energy as electrical energy, wherein the energy storage comprises one or more of a battery, capacitor, or a combination thereof; a motor electrically coupled to the energy storage and configured to receive a portion of the electrical energy; a generator electrically coupled with the energy recovery mechanism and the energy storage; and a controller in communication with the energy recovery mechanism, the energy storage, and the motor, wherein the controller receives data from one or more of the energy recovery mechanism, energy storage, and motor, the data comprising a rotational velocity or acceleration of the roller of the energy recovery mechanism; and wherein the controller transmits instructions to change a rate or an amount of energy generated by the generator in response to the received data.

23. The system of claim 22, wherein the controller transmits instructions to control a flow of energy between two or more of the energy recovery mechanism, generator, capacitor, battery, and motor in response to the received data or an instruction from the driver.

24. The system of claim 22, wherein the data further comprises an amount of energy or a rate of energy generated by the generator.

25. The system of claim 22, wherein the data comprises an amount of energy stored in the capacitor, a voltage of the capacitor, or a rate of charge or discharge of the capacitor.

26. The system of claim 22, wherein the data comprises an amount of energy stored in the battery, a voltage of the battery, or a rate of charge or discharge of the battery.

27. The system of claim 22, wherein the data comprises operational data of the motor.

28. The system of claim 22, wherein the data comprises the speed or acceleration of the vehicle.

29. The system of claim 22, wherein the controller transmits instructions to accelerate the vehicle based on the received data or an instruction from the driver.

30. The system of claim 22, wherein the controller transmits instructions to decelerate the vehicle based on received data or an instruction from the driver.
