

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407521
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Elshani Rama; Donjete et al.

Safe and secure communication

Abstract

A device may compute redundancy information based on plaintext. The device may determine modified additional data based on the redundancy information and the additional data. The device may encrypt the plaintext to obtain ciphertext. The device may compute a message authentication code based on the ciphertext and the modified additional data. The device may transmit a message including the ciphertext, the additional data, and the message authentication code.

Inventors: Elshani Rama; Donjete (Unterhaching, DE), Zeh; Alexander (Munich, DE), Syassen; Jörg (Feldkirchen-Westerham, DE)

Applicant: Infineon Technologies AG (Neubiberg, DE)

Family ID: 92908388

Assignee: Infineon Technologies AG (Neubiberg, DE)

Appl. No.: 18/298602

Filed: April 11, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240348450 A1	Oct. 17, 2024

Publication Classification

Int. Cl.: H04L29/06 (20060101); H04L9/06 (20060101); H04L9/32 (20060101)

U.S. Cl.:

CPC H04L9/3242 (20130101); H04L9/0637 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2021/0089040	12/2020	Ebrahimi Afrouzi	N/A	G05D 1/0248
2021/0119780	12/2020	Hassan	N/A	H04L 9/088
2021/0211858	12/2020	Ellenbeck	N/A	H04W 72/0466

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2019014426	12/2018	WO	H04L 45/24

Primary Examiner: Steinle; Andrew J

Attorney, Agent or Firm: Harrity & Harrity, LLP

Background/Summary

BACKGROUND

(1) An authenticated encryption with additional data (AEAD) scheme is an encryption scheme that provides confidentiality and authenticity of data in addition to authenticated but not encrypted additional data. In general, AEAD aims to provide confidentiality, authenticity, and integrity for a message consisting of plaintext data and additional data (also referred to as associated data or additional authenticated data), such as header data. AEAD uses a message authentication code (MAC) to confirm that encrypted data is authentic. An AEAD scheme may be used in, for example, an automotive application, where functional safety, real-time constraints, reusability, cost, flexibility, strong/robust security, and energy consumption play an important role.

SUMMARY

(2) In some implementations, a device includes one or more components to compute redundancy information based on plaintext; determine modified additional data based on the redundancy information and the additional data; encrypt the plaintext to obtain ciphertext; compute a message authentication code (MAC) based on the ciphertext and the modified additional data; and transmit a message including the ciphertext, the additional data, and the MAC.

(3) In some implementations, a device includes one or more components to: receive a message including ciphertext, additional data, and a first MAC; decrypt the ciphertext to obtain decrypted plaintext; compute redundancy information based on the decrypted plaintext; determine modified additional data based on the redundancy information and the additional data; compute a second MAC based on the ciphertext and the modified additional data; and determine whether the second MAC matches the first MAC.

(4) In some implementations, a system includes a transmitter to: compute first redundancy information based on plaintext, determine first modified additional data based on the first redundancy information and additional data, encrypt the plaintext to obtain ciphertext, compute a first MAC based on the ciphertext and the first modified additional data, and transmit a message

including the ciphertext, the additional data, and the first MAC; and a receiver to: receive the message including the ciphertext, the additional data, and the first MAC; decrypt the ciphertext to obtain decrypted plaintext; compute second redundancy information based on the decrypted plaintext; determine second modified additional data based on the second redundancy information and the additional data; compute a second MAC based on the ciphertext and the second modified additional data; and determine whether second MAC matches the first MAC.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. 1A and 1B are diagrams of an example associated with safe and secure communication as described herein.
- (2) FIG. 2 is a diagram illustrating an example implementation of a transmitter configured for operation in an advanced encryption standard with Galois/counter mode (AES-GCM) operation mode in association with providing safe and secure communication as described herein.
- (3) FIG. 3 is a diagram illustrating an example implementation of a receiver configured for operation in an AES-GCM operation mode in association with providing safe and secure communication as described herein.
- (4) FIG. 4 is a diagram of example components of a device associated with providing safe and secure communication as described herein.
- (5) FIG. 5 is a flowchart of an example process associated with safe and secure communication as described herein.

DETAILED DESCRIPTION

- (6) The following detailed description of example implementations refers to the accompanying drawings. The same reference numbers in different drawings may identify the same or similar elements.
- (7) As described above, an AEAD scheme may be designed to ensure confidentiality, authenticity, and data integrity for a message consisting of plaintext data and (optional) additional data. In practice, a transmitter may be configured to implement an AEAD scheme that generates a message including ciphertext (i.e., encrypted plaintext) and a MAC (sometimes referred to as a tag). While the additional data is not encrypted, the additional data is protected by the tag. That is, only authenticity and integrity are provided for the additional data. However, according to a conventional AEAD scheme that uses an advanced encryption standard with Galois/counter mode (AES-GCM) algorithm, an error that occurs during encryption of plaintext at a transmitter or during decryption of ciphertext at a receiver may go undetected.
- (8) For example, the transmitter may obtain plaintext P and additional data A . The transmitter may provide the plaintext P as an input to a first function $f.sub.1$ to generate ciphertext. Here, if no error occurs during encryption, then the transmitter would generate ciphertext C . However, if an error occurs during encryption, then the transmitter generates erroneous ciphertext C'' (i.e., ciphertext that is different from ciphertext C). The transmitter may then provide the erroneous ciphertext C'' and the additional data A as inputs to a second function $f.sub.2$, an output of which is an erroneous tag T'' (rather than a tag T that would have been generated based on the ciphertext C). The transmitter then transmits a message including the additional data A , the erroneous ciphertext C'' , and the erroneous tag T'' . A receiver receives the message and provides the erroneous ciphertext C'' and the additional data A as inputs to an inverse second function $f.sub.2.sup.-1$, an output of which is a tag T' . Here, the receiver may authenticate the data by confirming that the tag T' matches the erroneous tag T'' . After authentication, the receiver provides the erroneous ciphertext C'' as an input to an inverse first function $f.sub.1.sup.-1$, an output of which is decrypted plaintext P'' (i.e., decrypted plaintext that is different from decrypted plaintext P' that matches the plaintext P). Thus,

in this scenario, the encryption error is undetected and the receiver does not successfully obtain decrypted plaintext P' that matches the plaintext P .

(9) As another example, the transmitter may obtain plaintext P and additional data A . The transmitter may provide the plaintext P as an input to a first function $f.sub.1$ to generate ciphertext. Here, if no error occurs during encryption, then the transmitter would generate ciphertext C . The transmitter may then provide the ciphertext C and the additional data A as inputs to a second function $f.sub.2$, an output of which is a tag T . The transmitter then transmits a message including the additional data A , the ciphertext C , and the tag T . A receiver receives the message and provides the ciphertext C and the additional data A as inputs to an inverse second function $f.sub.2.sup.-1$, an output of which is a tag T' . Here, the receiver may authenticate the data by confirming that the tag T' matches the tag T . After authentication, the receiver provides the ciphertext C as an input to an inverse first function $f.sub.1.sup.-1$. Here, if an error occurs during decryption, then an output of the inverse first function $f.sub.1.sup.-1$ is decrypted plaintext P'' (i.e., decrypted plaintext that is different from decrypted plaintext P' that matches the plaintext P). Thus, in this scenario, the decryption error is undetected and the receiver does not successfully obtain decrypted plaintext P' that matches the plaintext P .

(10) In some systems, to enable detection of an encryption or decryption error, end-to-end protection may be provided by adding a set of cyclic redundancy check (CRC) bits to the data. That is, the transmitter may add a set of CRC bits to the plaintext prior to encryption, and may generate a tag based on the plaintext that includes the set of CRC bits. The transmitter then transmits a message including additional data, ciphertext, and tag. On the receiver side, the receiver can utilize the set of CRC bits to confirm that the plaintext has been encrypted and decrypted without error. That is, the set of CRC bits may enable an encryption or decryption error to be detected, thereby improving functional safety. However, this technique may be undesirable due to the increase in overhead resulting from the need to transmit the set of CRC bits over the communication channel.

(11) Some implementations described herein provide safe and secure communication over a communication channel by enabling a cryptographic error (e.g., an encryption error or a decryption error) to be detected without increasing overhead. In some implementations, a transmitter may compute first redundancy information based on plaintext, determine first modified additional data based on the first redundancy information and additional data, and encrypt the plaintext to obtain ciphertext. The transmitter may then compute a first MAC based on the ciphertext and the first modified additional data, and may transmit a message including the ciphertext, the additional data, and the first MAC. A receiver may receive the message including the ciphertext, the additional data, and the first MAC, decrypt the ciphertext to obtain decrypted plaintext, compute second redundancy information based on the decrypted plaintext, and determine second modified additional data based on the second redundancy information and the additional data. The receiver may then compute a second MAC based on the ciphertext and the second modified additional data, and may determine whether the second MAC matches the first MAC. Notably, redundancy information is not transmitted by the transmitter in association with the safe and secure communication scheme, thereby reducing overhead while improving functional safety by enabling cryptographic error detection. Additional details are provided below.

(12) FIGS. 1A and 1B are diagrams of an example **100** associated with safe and secure communication as described herein. As shown in FIGS. 1A and 1B, the example **100** includes a transmitter **102** and a receiver **104**. In some implementations, the transmitter **102** and the receiver **104** may be network nodes in, for example, a bus-based communication system that connects a group of network nodes. In some implementations, the transmitter **102** and the receiver **104** are configured to operate in an advanced encryption standard with Galois/counter mode (AES-GCM) operation mode in association with providing AEAD for communications between the transmitter **102** and the receiver **104**. In some implementations, the transmitter **102** and the receiver **104** are configured to operate in an Ascon operation mode (e.g., using a light-weight cipher) in association

with providing AEAD for communications between the transmitter **102** and the receiver **104**.

(13) In some implementations, the transmitter **102** and the receiver **104** may communicate with one another according to a message-based communication protocol. For example, the transmitter **102** may transmit a message as a frame of bits that are serially introduced into a bus and serially received by the receiver **104**. Examples of protocols that may be used in a bus-based communication system **100** include controller area network (CAN) protocol, CAN flexible data-rate (FD) protocol, CAN extra-long (XL) protocol, local interconnect network (LIN) protocol, or an Ethernet protocol (e.g., 10base-T1S protocol), among other examples. In some implementations, the transmitter **102** and the receiver **104** are configured to communicate using an AEAD scheme (e.g., such that confidentiality and authenticity of a payload and authentication of additional data is provided for a message transmitted by the transmitter **102** and received by the receiver **104**).

(14) As shown in FIG. 1A at reference **106**, the transmitter **102** may obtain plaintext P and additional data A that is to be transmitted to the receiver **104** (e.g., via a bus of a bus-based communication system). The plaintext P may include, for example, a payload that is to be transmitted by the transmitter **102** and received by the receiver **104**. Notably, the plaintext P is not encrypted (i.e., unencrypted). In some implementations, the plaintext P and the additional data A are to be transmitted according to the AEAD scheme in order to provide confidentiality and authentication of the plaintext P and authentication of the additional data A.

(15) As shown at reference **108**, the transmitter **102** may compute first redundancy information R1 based on the plaintext P. Redundancy information is information associated with determining whether the plaintext P has been encrypted by the transmitter **102** without an encryption error and whether ciphertext C has been decrypted by the receiver **104** without a decryption error, as described herein. In some implementations, to compute the first redundancy information R1, the transmitter **102** may apply a redundancy function $f_{\text{sub.red}}$ (e.g., an error correction code (ECC) function, a cyclic redundancy check (CRC) function, an error detection code (EDC) function, or the like) to the plaintext P, as shown in FIG. 1A (e.g., $R1 = f_{\text{sub.red}}(P)$). Here, the first redundancy information R1 may be a result of applying the redundancy function $f_{\text{sub.red}}$ to the plaintext P. That is, the transmitter **102** may provide the plaintext P as an input to the redundancy function $f_{\text{sub.red}}$, and may receive the first redundancy information R1 as an output of the redundancy function $f_{\text{sub.red}}$.

(16) As shown at reference **110**, the transmitter **102** may determine first modified additional data A' based on the first redundancy information R1 and the additional data A. Modified additional data is a version of the additional data A that has been modified based on redundancy information. Thus, modified additional data depends on redundancy information based on which the additional data A is modified. As one example, the transmitter **102** may in some implementations append the first redundancy information R1 to the additional data A to generate the first modified additional data A', as indicated in FIG. 1A.

(17) As shown at reference **112**, the transmitter **102** may encrypt the plaintext P to obtain ciphertext C (i.e., encrypted plaintext). In some implementations, to encrypt the plaintext P, the transmitter **102** may apply a first function $f_{\text{sub.1}}$ (e.g., a first cryptographic function) to the plaintext P, as shown in FIG. 1A (e.g., $C = f_{\text{sub.1}}(P)$). Here, the ciphertext C may be a result of applying the first function $f_{\text{sub.1}}$ to the plaintext P. That is, the transmitter **102** may provide the plaintext P as an input to the first function $f_{\text{sub.1}}$, and may receive the ciphertext C as an output of the first function $f_{\text{sub.1}}$.

(18) As shown at reference **114**, the transmitter **102** may compute a first MAC T based on the ciphertext C and the first modified additional data A'. A MAC T is a value based on which authentication of data transmitted by the transmitter **102** can be confirmed by the receiver **104**. In some implementations, to compute the first MAC T, the transmitter **102** may apply a second function $f_{\text{sub.2}}$ (e.g., a second cryptographic function, which may be different from the first cryptographic function or the same as the first cryptographic function) to the ciphertext C and the

first modified additional data A' , as shown in FIG. 1A (e.g., $T=f.sub.2(C, A')$). Here, the first MAC T may be a result of applying the second function $f.sub.2$ to the ciphertext C and the first modified additional data A' . That is, the transmitter **102** may provide the ciphertext C and the first modified additional data A' as inputs to the second function $f.sub.2$, and may receive the first MAC T as an output of the second function $f.sub.2$.

(19) As shown at reference **116** in FIG. 1A, the transmitter **102** may transmit a message including the ciphertext C , the additional data A , and the first MAC T . Notably, the transmitter **102** does not transmit the first redundancy information $R1$ or the first modified additional data A' . Rather, the transmitter **102** transmits the original additional data A (i.e., the additional data A without any redundancy information). Thus, the transmitter **102** may in some implementations be configured to refrain from transmitting (e.g., configured not to transmit, or not configured to transmit) the first redundancy information $R1$ or the first modified additional data A' .

(20) As shown at reference **118** in FIG. 1B, the receiver **104** may receive the message including the ciphertext C , the additional data A , and the first MAC T .

(21) As shown at reference **120**, the receiver **104** may decrypt the ciphertext C to obtain decrypted plaintext P' . In some implementations, to decrypt the ciphertext C , the transmitter **102** may apply a first inverse function $f.sub.1.sup.-1$ (e.g., an inverse of the first cryptographic function) to the ciphertext C , as shown in FIG. 1B (e.g., $P'=f.sub.1.sup.-1(C)$). Here, the decrypted plaintext P' may be a result of applying the first inverse function $f.sub.1.sup.-1$ to the ciphertext C . That is, the transmitter **102** may provide the ciphertext C as an input to the first inverse function $f.sub.1.sup.-1$, and may receive the decrypted plaintext P' as an output of the first inverse function $f.sub.1.sup.-1$.

(22) As shown at reference **122**, the receiver **104** may compute second redundancy information $R2$ based on the decrypted plaintext P' . In some implementations, to compute the second redundancy information $R2$, the transmitter **102** may apply the redundancy function $f.sub.red$ (e.g., the same redundancy function applied by the transmitter **102** in association with computing the first redundancy information $R1$) to the decrypted plaintext P' , as shown in FIG. 1A (e.g., $R2=f.sub.red(P')$). Here, the second redundancy information $R2$ may be a result of applying the redundancy function $f.sub.red$ to the decrypted plaintext P' . That is, the transmitter **102** may provide the decrypted plaintext P' as an input to the redundancy function $f.sub.red$, and may receive the second redundancy information $R2$ as an output of the redundancy function $f.sub.red$.

(23) As shown at reference **124**, the receiver **104** may determine second modified additional data A'' based on the second redundancy information $R2$ and the additional data A . As one example, the receiver **104** may in some implementations append the second redundancy information $R2$ to the additional data A to generate the second modified additional data A'' , as indicated in FIG. 1B.

(24) As shown at reference **126**, the receiver **104** may compute a second MAC T' based on the ciphertext C and the second modified additional data A'' . In some implementations, to compute the second MAC T' , the transmitter **102** may apply the second function $f.sub.2$ (e.g., the same function applied by the transmitter **102** in association with computing the first MAC T) to the ciphertext C and the second modified additional data A'' , as shown in FIG. 1B (e.g., $T'=f.sub.2(C, A'')$). Here, the second MAC T' may be a result of applying the second function $f.sub.2$ to the ciphertext C and the second modified additional data A'' . That is, the transmitter **102** may provide the ciphertext C and the second modified additional data A'' as inputs to the second function $f.sub.2$, and may receive the second MAC T' as an output of the second function $f.sub.2$.

(25) As shown at reference **128**, the receiver **104** may determine whether the second MAC T' matches the first MAC T . That is, the receiver **104** may determine whether the second MAC T' computed by the receiver **104** matches (e.g., is identical to) the first MAC T received by the receiver **104**. Here, the second MAC T' matches the first MAC T only if the second modified additional data A'' matches the first modified additional data A' . Further, the second modified additional data A'' matches the first modified additional data A' only if the second redundancy

information R2 matches the first redundancy information R1. Here, because the second redundancy information R2 and the first redundancy information R1 are generated based on the decrypted plaintext P' and the plaintext P, respectively, the second redundancy information R2 matches the first redundancy information R1 only if the decrypted plaintext P' matches the plaintext P. Thus, if the second MAC T' matches the first MAC T, then the receiver **104** can determine that the plaintext P was encrypted by the transmitter **102** without error and that the decrypted plaintext P' was obtained (i.e., that the ciphertext C was decrypted) by the receiver **104** without error.

(26) In some implementations, the receiver **104** may provide an indication of a result of whether the second MAC T' matches the first MAC T. For example, if the receiver **104** determines that the second MAC T' matches (e.g., is identical to) the first MAC T, then the receiver **104** may provide an authentication indication indicating that the plaintext P and the additional data A have been authenticated. As another example, if the receiver **104** determines that the second MAC T' does not match (e.g., is not identical to) the first MAC T, then the receiver **104** may provide an error indication indicating that the plaintext P and the additional data A have not been authenticated. In some implementations, the error indication may serve as an indication that a cryptographic error (e.g., an error during encryption by the transmitter **102** or an error during decryption by the receiver **104**) has been detected.

(27) As noted above, the transmitter **102** and the receiver **104** may in some implementations be configured to operate in an AES-GCM operation mode in association with providing AEAD for messages communicated between the transmitter **102** and the receiver **104**.

(28) As indicated above, FIGS. 1A and 1B are provided as examples. Other examples may differ from what is described with regard to FIGS. 1A and 1B.

(29) FIG. 2 is a diagram illustrating an example implementation of a transmitter **102** configured for operation in an AES-GCM operation mode in association with providing safe and secure communication as described herein.

(30) In operation, the redundancy information R1 is computed by the transmitter **102** and appended to the additional data A, which comprises a ($a \geq 1$) blocks. A given block may comprise, for example, 128 bits. As shown, a first block A.sub.1 is provided as an input for multiplication over a Galois field (MUL.sub.K1) based on a first key K.sub.1. An output of the first multiplication over the Galois field is XORed with a second block A.sub.2, a result of which is provided as an input for multiplication over the Galois field based on the first key K.sub.1. This operation is repeated for the remaining blocks of the a blocks and the redundancy information R1. In the case of CANsec, the additional data A may comprise 112 bits, and so the additional data A plus redundancy information R1 of 16 bits (e.g., a 16 bit CRC) requires a single multiplication block.

(31) As further shown, the transmitter **102** may encrypt the plaintext P, which comprises p ($p \geq 1$) blocks. For example, the transmitter **102** may apply a cryptographic function (E.sub.K2) to a nonce N that is appended with a first counter value (e.g., 1) and using a second key K.sub.2, and may XOR an output of the cryptographic function with a first block P.sub.1, with a result of the XOR operation being a first block of ciphertext C.sub.1. The transmitter **102** may perform a similar operation for each block of the p blocks of the plaintext P (e.g., such that the transmitter **102** generates p blocks of ciphertext C based on p counter values).

(32) As shown, an output of the last Galois field multiplication associated with the additional data A and the redundancy information R1 is XORed with a first block of ciphertext C.sub.1, and a result is provided as an input for multiplication over the Galois field based on the first key K.sub.1. An output of this Galois field multiplication is XORed with a second block of ciphertext C.sub.2, a result of which is provided as an input for multiplication over the Galois field based on the first key K.sub.1. This operation is repeated for the remaining blocks of the p blocks of ciphertext C.

(33) As further shown, a length L of the ciphertext C is XORed with an output of the last Galois field multiplication associated with the ciphertext C, and a result is provided as an input for multiplication over the Galois fields based on the first key K.sub.1.

(34) As further shown, the transmitter **102** may apply the cryptographic function to the nonce N after appending a zero value and using the second key K.sub.2, and may XOR a result with an output of the Galois field multiplication associated with the length L, a result of which is the MAC T. The transmitter **102** may then transmit the additional data A, the ciphertext C, and the MAC T. Here, the transmitter **102** does not transmit the redundancy information R1.

(35) In this way, the transmitter **102** may provide authenticated encryption for the ciphertext C, as well as authentication for the additional data A, the length L, and the nonce N, while enabling detection of an encryption error without increasing overhead, as described above with respect to FIG. 1.

(36) As indicated above, FIG. 2 is provided as an example. Other examples may differ from what is described with regard to FIG. 2. The number and arrangement of devices shown in FIG. 2 are provided as an example. In practice, there may be additional devices, fewer devices, different devices, or differently arranged devices than those shown in FIG. 2. Furthermore, two or more devices shown in FIG. 2 may be implemented within a single device, or a single device shown in FIG. 2 may be implemented as multiple, distributed devices. Additionally, or alternatively, a set of devices (e.g., one or more devices) shown in FIG. 2 may perform one or more functions described as being performed by another set of devices shown in FIG. 2.

(37) FIG. 3 is a diagram illustrating an example implementation of a receiver **104** configured for operation in an AES-GCM operation mode in association with providing safe and secure communication as described herein. In the example shown in FIG. 3, the receiver **104** has received ciphertext C, additional data A, and a MAC T from the transmitter **102**, as described above with respect to FIG. 2.

(38) In operation, the receiver **104** may decrypt the ciphertext C, which comprises p ($p \geq 1$) blocks. For example, the receiver **104** may apply the cryptographic function (E.sub.K2) to the nonce N that is appended with the first counter value (e.g., 1) and using the second key K.sub.2, and may XOR an output of the cryptographic function with a first block C.sub.1, with a result of the XOR operation being a first block of decrypted plaintext P'. The receiver **104** may perform a similar operation for each block of the p blocks of the ciphertext C such that the receiver **104** generates p blocks of decrypted plaintext P' based on p counter values.

(39) Next, the receiver **104** may compute the redundancy information R2 (e.g., by applying a redundancy function to the decrypted plaintext P'), and may append the redundancy information R2 to the additional data A, which comprises a ($a \geq 1$) blocks. As shown, a first block A.sub.1 is provided as an input for multiplication over a Galois field (MUL.sub.K1) based on the first key K.sub.1. An output of the first multiplication over the Galois field is XORed with a second block A.sub.2, a result of which is provided as an input for multiplication over the Galois field based on the first key K.sub.1. This operation is repeated for the remaining blocks of the a blocks and the redundancy information R1.

(40) As shown, an output of the last Galois field multiplication associated with the additional data A and the redundancy information R2 is XORed with a first block of ciphertext C.sub.1, and a result is provided as an input for multiplication over the Galois field based on the first key K.sub.1. An output of this Galois field multiplication is XORed with a second block of ciphertext C.sub.2, a result of which is provided as an input for multiplication over the Galois field based on the first key K.sub.1. This operation is repeated for the remaining blocks of the p blocks of ciphertext C.

(41) As further shown, the length L of the ciphertext C is XORed with an output of the last Galois field multiplication associated with the ciphertext C, and a result is provided as an input for multiplication over the Galois fields based on the first key K.sub.1.

(42) As further shown, the receiver **104** may apply the cryptographic function to the nonce N after appending a zero value and using the second key K.sub.2, and may XOR a result with an output of the Galois field multiplication associated with the length L, a result of which is the MAC T'. The receiver **104** may then determine whether the MAC T' computed by the receiver **104** matches the

MAC T received in the message, and may perform authentication of the message accordingly, as described with respect to FIG. 1.

(43) In this way, the receiver **104** may provide authenticated encryption for the ciphertext C, as well as authentication for the additional data A, the length L, and the nonce N, while enabling detection of an encryption error at the transmitter **102** or a decryption error at the receiver **104**, as described above with respect to FIG. 1.

(44) As indicated above, FIG. 3 is provided as an example. Other examples may differ from what is described with regard to FIG. 3. The number and arrangement of devices shown in FIG. 3 are provided as an example. In practice, there may be additional devices, fewer devices, different devices, or differently arranged devices than those shown in FIG. 3. Furthermore, two or more devices shown in FIG. 3 may be implemented within a single device, or a single device shown in FIG. 3 may be implemented as multiple, distributed devices. Additionally, or alternatively, a set of devices (e.g., one or more devices) shown in FIG. 3 may perform one or more functions described as being performed by another set of devices shown in FIG. 3.

(45) FIG. 4 is a diagram of example components of a device **400** associated with associated with providing safe and secure communication as described herein. The device **400** may correspond to transmitter **102** and/or receiver **104**. In some implementations, the transmitter **102** and/or the receiver **104** may include one or more devices **400** and/or one or more components of the device **400**. As shown in FIG. 4, the device **400** may include a bus **410**, a processor **420**, a memory **430**, an input component **440**, an output component **450**, and/or a communication component **460**.

(46) The bus **410** may include one or more components that enable wired and/or wireless communication among the components of the device **400**. The bus **410** may couple together two or more components of FIG. 4, such as via operative coupling, communicative coupling, electronic coupling, and/or electric coupling. For example, the bus **410** may include an electrical connection (e.g., a wire, a trace, and/or a lead) and/or a wireless bus. The processor **420** may include a central processing unit, a graphics processing unit, a microprocessor, a controller, a microcontroller, a digital signal processor, a field-programmable gate array, an application-specific integrated circuit, and/or another type of processing component. The processor **420** may be implemented in hardware, firmware, or a combination of hardware and software. In some implementations, the processor **420** may include one or more processors capable of being programmed to perform one or more operations or processes described elsewhere herein.

(47) The memory **430** may include volatile and/or nonvolatile memory. For example, the memory **430** may include random access memory (RAM), read only memory (ROM), a hard disk drive, and/or another type of memory (e.g., a flash memory, a magnetic memory, and/or an optical memory). The memory **430** may include internal memory (e.g., RAM, ROM, or a hard disk drive) and/or removable memory (e.g., removable via a universal serial bus connection). The memory **430** may be a non-transitory computer-readable medium. The memory **430** may store information, one or more instructions, and/or software (e.g., one or more software applications) related to the operation of the device **400**. In some implementations, the memory **430** may include one or more memories that are coupled (e.g., communicatively coupled) to one or more processors (e.g., processor **420**), such as via the bus **410**. Communicative coupling between a processor **420** and a memory **430** may enable the processor **420** to read and/or process information stored in the memory **430** and/or to store information in the memory **430**.

(48) The input component **440** may enable the device **400** to receive input, such as user input and/or sensed input. For example, the input component **440** may include a touch screen, a keyboard, a keypad, a mouse, a button, a microphone, a switch, a sensor, a global positioning system sensor, an accelerometer, a gyroscope, and/or an actuator. The output component **450** may enable the device **400** to provide output, such as via a display, a speaker, and/or a light-emitting diode. The communication component **460** may enable the device **400** to communicate with other devices via a wired connection and/or a wireless connection. For example, the communication

component **460** may include a receiver, a transmitter, a transceiver, a modem, a network interface card, and/or an antenna.

(49) The device **400** may perform one or more operations or processes described herein. For example, a non-transitory computer-readable medium (e.g., memory **430**) may store a set of instructions (e.g., one or more instructions or code) for execution by the processor **420**. The processor **420** may execute the set of instructions to perform one or more operations or processes described herein. In some implementations, execution of the set of instructions, by one or more processors **420**, causes the one or more processors **420** and/or the device **400** to perform one or more operations or processes described herein. In some implementations, hardwired circuitry may be used instead of or in combination with the instructions to perform one or more operations or processes described herein. Additionally, or alternatively, the processor **420** may be configured to perform one or more operations or processes described herein. Thus, implementations described herein are not limited to any specific combination of hardware circuitry and software.

(50) The number and arrangement of components shown in FIG. **4** are provided as an example. The device **400** may include additional components, fewer components, different components, or differently arranged components than those shown in FIG. **4**. Additionally, or alternatively, a set of components (e.g., one or more components) of the device **400** may perform one or more functions described as being performed by another set of components of the device **400**.

(51) FIG. **5** is a flowchart of an example process **500** associated with safe and secure communication as described herein. In some implementations, one or more process blocks of FIG. **5** are performed by a transmitter (e.g., a transmitter **102**) or a receiver (e.g., a receiver **104**). Additionally, or alternatively, one or more process blocks of FIG. **5** may be performed by one or more components of a device **400**, such as processor **420**, memory **430**, input component **440**, output component **450**, and/or communication component **460**.

(52) As shown in FIG. **5**, process **500** may include computing first redundancy information based on plaintext (block **502**). For example, the transmitter may compute first redundancy information based on plaintext, as described above.

(53) As further shown in FIG. **5**, process **500** may include determining first modified additional data based on the first redundancy information and additional data (block **504**). For example, the transmitter may determine first modified additional data based on the first redundancy information and additional data, as described above.

(54) As further shown in FIG. **5**, process **500** may include encrypting the plaintext to obtain ciphertext (block **506**). For example, the transmitter may encrypt the plaintext to obtain ciphertext, as described above.

(55) As further shown in FIG. **5**, process **500** may include computing a first MAC based on the ciphertext and the first modified additional data (block **508**). For example, the transmitter may compute a first MAC based on the ciphertext and the first modified additional data, as described above.

(56) As further shown in FIG. **5**, process **500** may include transmitting a message including the ciphertext, the additional data, and the first MAC (block **510**). For example, the transmitter may transmit a message including the ciphertext, the additional data, and the first MAC, as described above.

(57) As shown in FIG. **5**, process **500** may include receiving the message including the ciphertext, the additional data, and the first MAC (block **512**). For example, the receiver may receive the message including the ciphertext, the additional data, and the first MAC, as described above.

(58) As further shown in FIG. **5**, process **500** may include decrypting the ciphertext to obtain decrypted plaintext (block **514**). For example, the receiver may decrypt the ciphertext to obtain decrypted plaintext, as described above.

(59) As further shown in FIG. **5**, process **500** may include computing second redundancy information based on the decrypted plaintext (block **516**). For example, the receiver may compute

second redundancy information based on the decrypted plaintext, as described above.

(60) As further shown in FIG. 5, process **500** may include determining second modified additional data based on the second redundancy information and the additional data (block **518**). For example, the receiver may determine second modified additional data based on the second redundancy information and the additional data, as described above.

(61) As further shown in FIG. 5, process **500** may include computing a second MAC based on the ciphertext and the second modified additional data (block **520**). For example, the receiver may compute a second MAC based on the ciphertext and the second modified additional data, as described above.

(62) As further shown in FIG. 5, process **500** may include determining whether the second MAC matches the first MAC (block **600**). For example, the receiver may determine whether second MAC matches the first MAC, as described above.

(63) Process **500** may include additional implementations, such as any single implementation or any combination of implementations described below and/or in connection with one or more other processes described elsewhere herein.

(64) In a first implementation, the transmitter, when computing the first redundancy information, is configured to apply a redundancy function to the plaintext, wherein the first redundancy information is a result of applying the redundancy to the plaintext.

(65) In a second implementation, alone or in combination with the first implementation, the transmitter, when determining the first modified additional data, is configured to append the first redundancy information to the additional data.

(66) In a third implementation, alone or in combination with one or more of the first and second implementations, the transmitter and the receiver are configured to operate in an AES-GCM operation mode.

(67) In a fourth implementation, alone or in combination with one or more of the first through third implementations, the transmitter is configured not to transmit the first redundancy information.

(68) In a fifth implementation, alone or in combination with one or more of the first through fourth implementations, the receiver, when computing the second redundancy information, is configured to apply a redundancy function to the decrypted plaintext, wherein the second redundancy information is a result of applying the redundancy to the decrypted plaintext.

(69) In a sixth implementation, alone or in combination with one or more of the first through fifth implementations, the receiver, when determining the second modified additional data, is configured to append the second redundancy information to the additional data.

(70) In a seventh implementation, alone or in combination with one or more of the first through sixth implementations, the receiver is further configured to provide an error indication based on a determination that the second MAC does not match the first MAC.

(71) In an eighth implementation, alone or in combination with one or more of the first through seventh implementations, the receiver is further configured to provide an authentication indication based on a determination that the second MAC matches the first MAC.

(72) Although FIG. 5 shows example blocks of process **500**, in some implementations, process **500** includes additional blocks, fewer blocks, different blocks, or differently arranged blocks than those depicted in FIG. 5. Additionally, or alternatively, two or more of the blocks of process **500** may be performed in parallel.

(73) The foregoing disclosure provides illustration and description, but is not intended to be exhaustive or to limit the implementations to the precise forms disclosed. Modifications and variations may be made in light of the above disclosure or may be acquired from practice of the implementations.

(74) As used herein, the term “component” is intended to be broadly construed as hardware, firmware, and/or a combination of hardware and software. It will be apparent that systems and/or methods described herein may be implemented in different forms of hardware, firmware, or a

combination of hardware and software. The actual specialized control hardware or software code used to implement these systems and/or methods is not limiting of the implementations. Thus, the operation and behavior of the systems and/or methods are described herein without reference to specific software code—it being understood that software and hardware can be designed to implement the systems and/or methods based on the description herein.

(75) Even though particular combinations of features are recited in the claims and/or disclosed in the specification, these combinations are not intended to limit the disclosure of various implementations. In fact, many of these features may be combined in ways not specifically recited in the claims and/or disclosed in the specification. Although each dependent claim listed below may directly depend on only one claim, the disclosure of various implementations includes each dependent claim in combination with every other claim in the claim set. As used herein, a phrase referring to “at least one of” a list of items refers to any combination of those items, including single members. As an example, “at least one of: a, b, or c” is intended to cover a, b, c, a-b, a-c, b-c, and a-b-c, as well as any combination with multiple of the same item.

(76) No element, act, or instruction used herein should be construed as critical or essential unless explicitly described as such. Also, as used herein, the articles “a” and “an” are intended to include one or more items, and may be used interchangeably with “one or more.” Further, as used herein, the article “the” is intended to include one or more items referenced in connection with the article “the” and may be used interchangeably with “the one or more.” Furthermore, as used herein, the term “set” is intended to include one or more items (e.g., related items, unrelated items, or a combination of related and unrelated items), and may be used interchangeably with “one or more.” Where only one item is intended, the phrase “only one” or similar language is used. Also, as used herein, the terms “has,” “have,” “having,” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based, at least in part, on” unless explicitly stated otherwise. Also, as used herein, the term “or” is intended to be inclusive when used in a series and may be used interchangeably with “and/or,” unless explicitly stated otherwise (e.g., if used in combination with “either” or “only one of”).

Claims

1. A transmitter, comprising: one or more processors configured to: compute redundancy information based on plaintext, the redundancy information being associated with determining whether the plaintext has been encrypted without an encryption error; determine modified additional data based on the redundancy information and additional data, wherein the one or more processors are configured to modify the additional data based on the redundancy information to obtain the modified additional data; encrypt the plaintext to obtain ciphertext; compute a message authentication code based on the ciphertext and the modified additional data; and transmit a message including the ciphertext, the additional data, and the message authentication code.
2. The transmitter of claim 1, wherein the one or more processors, when computing the redundancy information, are configured to apply a redundancy function to the plaintext, wherein the redundancy information is a result of applying the redundancy function to the plaintext.
3. The transmitter of claim 2, wherein the redundancy function comprises at least one of an error detection code function, a cyclic redundancy check function, or an error correction code function.
4. The transmitter of claim 1, wherein the modified additional data is determined by appending the redundancy information to the additional data.
5. The transmitter of claim 1, wherein the transmitter is configured to operate in an advanced encryption standard with Galois/counter mode (AES-GCM) operation mode or an Ascon operation mode.
6. The transmitter of claim 1, wherein the transmitter is configured to operate in an Ascon operation mode using a light-weight cipher.

7. The transmitter of claim 1, wherein the one or more processors are further configured to refrain from transmitting the redundancy information.
8. The transmitter of claim 1, wherein the plaintext, the redundancy information, and the additional data are mutually exclusive.
9. The transmitter of claim 1, wherein the message does not include the redundancy information or the modified additional data.
10. The transmitter of claim 1, wherein the transmitter is configured to not transmit the redundancy information or the modified additional data.
11. A receiver, comprising: one or more processors configured to: receive a message including ciphertext, additional data, and a first message authentication code; decrypt the ciphertext within the message to obtain plaintext; compute redundancy information based on the plaintext; determine modified additional data based on the redundancy information and the additional data within the message, wherein the one or more processors are configured to modify the additional data based on the redundancy information to obtain the modified additional data; compute a second message authentication code based on the ciphertext and the modified additional data; and determine whether the second message authentication code matches the first message authentication code within the message.
12. The receiver of claim 11, wherein the one or more processors, when computing the redundancy information, are configured to apply a redundancy function to the plaintext, wherein the redundancy information is a result of applying the redundancy function to the ciphertext.
13. The receiver of claim 12, wherein the redundancy function comprises at least one of an error detection code function, a cyclic redundancy check function, or an error correction code function.
14. The receiver of claim 11, wherein the modified additional data is determined by appending the redundancy information to the additional data.
15. The receiver of claim 11, wherein the receiver is configured to operate in an advanced encryption standard with Galois/counter mode (AES-GCM) operation mode or an Ascon operation mode.
16. The receiver of claim 11, wherein the receiver is configured to operate in an Ascon operation mode using a light-weight cipher.
17. The receiver of claim 11, wherein the one or more processors are further configured to provide an error indication based on a determination that the second message authentication code does not match the first message authentication code within the message.
18. The receiver of claim 11, wherein the one or more processors are further configured to provide an authentication indication based on a determination that the second message authentication code matches the first message authentication code within the message.
19. The receiver of claim 11, wherein the message does not include the redundancy information or the modified additional data.
20. A system, comprising: a transmitter configured to: compute first redundancy information based on plaintext, the first redundancy information being associated with determining whether the plaintext has been encrypted without an encryption error, determine first modified additional data based on the first redundancy information and additional data, wherein the transmitter is configured to modify the additional data based on the first redundancy information to obtain the first modified additional data, encrypt the plaintext to obtain ciphertext, compute a first message authentication code based on the ciphertext and the first modified additional data, and transmit a message including the ciphertext, the additional data, and the first message authentication code; and a receiver configured to: receive the message including the ciphertext, the additional data, and the first message authentication code; decrypt the ciphertext to obtain decrypted plaintext; compute second redundancy information based on the decrypted plaintext; determine second modified additional data based on the second redundancy information and the additional data wherein the receiver is configured to modify the additional data based on the second redundancy information to

obtain the second modified additional data; compute a second message authentication code based on the ciphertext and the second modified additional data; and determine whether the second message authentication code matches the first message authentication code.

21. The system of claim 20, wherein the transmitter, when computing the first redundancy information, is configured to apply a redundancy function to the plaintext, wherein the first redundancy information is a result of applying the redundancy function to the plaintext.

22. The system of claim 20, wherein the transmitter, when determining the first modified additional data, is configured to append the first redundancy information to the additional data.

23. The system of claim 20, wherein the receiver, when computing the second redundancy information, is configured to apply a redundancy function to the decrypted plaintext, wherein the second redundancy information is a result of applying the redundancy to the decrypted plaintext.

24. The system of claim 20, wherein the receiver, when determining the second modified additional data, is configured to append the second redundancy information to the additional data.
