

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12408463
B2
September 02, 2025
Niu; Chao et al.

Trench balance structure pattern in red photodiodes of a pixel array with quad bayer color filter

Abstract

A pixel array includes 2×2 groupings of photodiodes to generate image charge in response to incident light directed through a back side of the semiconductor layer. A Quad Bayer filter is disposed over the back side of the semiconductor layer over the 2×2 groupings of photodiodes. Each color filter of the Quad Bayer CFA is disposed over a respective one of the plurality of 2×2 groupings of photodiodes. Trench balance structures are disposed in the semiconductor layer. Each of the trench balance structures is disposed in the semiconductor layer between one of the photodiodes and a respective one of the red color filters of the Quad Bayer filter. None of the trench balance structures are disposed between any of the photodiodes and respective green color filters or blue color filters of the Quad Bayer filter.

Inventors: Niu; Chao (Santa Clara, CA), Zheng; Yuanwei (San Jose, CA), Lin; Zhiqiang (Fremont, CA)

Applicant: OMNIVISION TECHNOLOGIES, INC. (Santa Clara, CA)

Family ID: 92598585

Assignee: OMNIVISION TECHNOLOGIES, INC. (Santa Clara, CA)

Appl. No.: 18/180731

Filed: March 08, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240304642 A1	Sep. 12, 2024

Publication Classification

Int. Cl.: H10F39/00 (20250101); H04N25/78 (20230101); H10F39/18 (20250101)

U.S. Cl.:

CPC **H10F39/807** (20250101); **H04N25/78** (20230101); **H10F39/1825** (20250101);
H10F39/8053 (20250101); **H10F39/8063** (20250101); H10F39/182 (20250101)

Field of Classification Search

CPC: H10F (39/8053); H10F (39/1825); H10F (39/8063); H10F (39/807); H10F (39/182);
H10F (39/199); H04N (25/134); H04N (25/779); H04N (25/78)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10461109	12/2018	Wu et al.	N/A	N/A
10714522	12/2019	Choi et al.	N/A	N/A
11335718	12/2021	Zang et al.	N/A	N/A
2020/0404203	12/2019	Jung et al.	N/A	N/A
2021/0134863	12/2020	Suzuki	N/A	N/A
2021/0144321	12/2020	Yamashita et al.	N/A	N/A
2022/0020790	12/2021	Zang et al.	N/A	N/A
2022/0130876	12/2021	Park et al.	N/A	N/A

Primary Examiner: Geyer; Scott B

Attorney, Agent or Firm: Dorsey & Whitney LLP

Background/Summary

BACKGROUND INFORMATION

Field of the Disclosure

(1) This disclosure relates generally to image sensors, and in particular but not exclusively, relates to image sensors with pixel arrays with Quad Bayer color filters.

Background

(2) Image sensors have become ubiquitous and are now widely used in digital cameras, cellular phones, security cameras, as well as in medical, automotive, and other applications. As image sensors are integrated into a broader range of electronic devices, it is desirable to enhance their functionality, performance metrics, and the like in as many ways as possible (e.g., resolution, power consumption, dynamic range) through both device architecture design as well as image acquisition processing. The technology used to manufacture image sensors has continued to advance at a great pace. For example, the demands of higher resolution and lower power consumption have encouraged the further miniaturization and integration of these devices.

(3) A typical image sensor operates in response to image light from an external scene being incident upon the image sensor. The image sensor includes an array of pixels having photosensitive elements (e.g., photodiodes) that absorb a portion of the incident image light and generate image charge upon absorption of the image light. The image charge photogenerated by the pixels may be measured as analog output image signals on column bitlines that vary as a function of the incident

image light. In other words, the amount of image charge generated is proportional to the intensity of the image light, which is read out as analog image signals from the column bitlines and converted to digital values to produce digital images (e.g., image data) representing the external scene. The analog image signals on the bitlines are coupled to readout circuits, which include input stages having analog-to-digital conversion (ADC) circuits to convert those analog image signals from the pixel array into the digital image signals.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Non-limiting and non-exhaustive embodiments of the present disclosure are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.
- (2) FIG. 1 illustrates one example of an imaging system with example patterns of trench balance structures included with 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter over a pixel array in accordance with the teachings of the present disclosure.
- (3) FIG. 2A is top view illustrating one example of neighboring 2×2 groupings of photodiodes of a pixel array under red, green, and blue color filters of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (4) FIG. 2B is an example cross-section view of a 2×2 grouping of photodiodes of a pixel array with example trench balance structures under a red color filter of a Quad Bayer filter as illustrated in FIG. 2A in accordance with the teachings of the present disclosure.
- (5) FIG. 3A is an example top view of a 2×2 grouping of photodiodes including one example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (6) FIG. 3B is example top view of a 2×2 grouping of photodiodes including another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (7) FIG. 4A is an example top view of a 2×2 grouping of photodiodes including yet another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (8) FIG. 4B is example top view of a 2×2 grouping of photodiodes including still another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (9) FIG. 5 illustrates center and edge regions of an example pixel array including various examples of trench balance structures included with at least some of the 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter in accordance with the teachings of the present disclosure.
- (10) Corresponding reference characters indicate corresponding components throughout the several views of the drawings. Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of various embodiments of the present disclosure. In addition, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present disclosure.

DETAILED DESCRIPTION

- (11) Example patterns of trench balance structures are included with 2×2 groupings of photodiodes under color filters for sensing light having wavelengths greater than or equal to 600 nanometer with a Quad Bayer filter disposed over a pixel array are described in accordance with the teachings of

the present disclosure. Examples of Quad Bayer filters may include for instance a Red-Green-Blue (e.g., a RGGB pattern) Quad Bayer filter pattern, a Red-Green-Blue-infrared (e.g., a RGB-IR pattern) Quad Bayer filter, or the like. Various examples directed to example imaging systems with patterns of trench balance structures included with 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter over a pixel array are described herein. In the following description, numerous specific details are set forth to provide a thorough understanding of the examples. One skilled in the relevant art will recognize, however, that the techniques described herein can be practiced without one or more of the specific details, or with other methods, components, materials, etc. In other instances, well-known structures, materials, or operations are not shown or described in detail in order to avoid obscuring certain aspects.

(12) Reference throughout this specification to “one example” or “one embodiment” means that a particular feature, structure, or characteristic described in connection with the example is included in at least one example of the present disclosure. Thus, the appearances of the phrases “in one example” or “in one embodiment” in various places throughout this specification are not necessarily all referring to the same example. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more examples.

(13) Spatially relative terms, such as “beneath,” “below,” “over,” “under,” “above,” “upper,” “top,” “bottom,” “left,” “right,” “center,” “middle,” and the like, may be used herein for ease of description to describe one element or feature's relationship relative to another element(s) or feature(s) as illustrated in the figures. It will be understood that the spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is rotated or turned over, elements described as “below” or “beneath” or “under” other elements or features would then be oriented “above” the other elements or features. Thus, the exemplary terms “below” and “under” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated ninety degrees or at other orientations) and the spatially relative descriptors used herein are interpreted accordingly. In addition, it will also be understood that when an element is referred to as being “between” two other elements, it can be the only element between the two other elements, or one or more intervening elements may also be present.

(14) Throughout this specification, several terms of art are used. These terms are to take on their ordinary meaning in the art from which they come, unless specifically defined herein or the context of their use would clearly suggest otherwise. It should be noted that element names and symbols may be used interchangeably through this document (e.g., Si vs. silicon); however, both have identical meaning.

(15) As will be discussed, various examples of an imaging system with patterns of trench balance structures included with 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter over a pixel array are disclosed. An example Quad Bayer filter may include a plurality of minimum repeating units of a red color filter, two green color filters, and a blue color filter that is repeated over the surface of the pixel array thereby producing either a red pixel, a green pixel, or a blue pixel at each corresponding pixel location.

(16) In the various examples, the balance of G.sub.BG.sub.R signal crosstalk between 2×2 groupings of photodiodes under red color filters (R) to neighboring 2×2 groupings of photodiodes under green color filters (G.sub.B) in the same row as the blue color filters (e.g., green-blue (G.sub.B) color filters) and to neighboring 2×2 groupings of photodiodes under green color filters (G.sub.R) in the same row as the red color filters (e.g., green-red (G.sub.R) color filters) is improved with example trench balance structures in accordance with the teachings of the present disclosure by absorbing, scattering, reflecting, and/or refracting, etc., light that is directed to the groupings of photodiodes under red color filters, which therefore reduces signal sensing differences between 2×2 groupings of photodiodes under green color filters (G.sub.B) and 2×2 groupings of photodiodes under green color filters (G.sub.R) that neighbor 2×2 groupings of photodiodes under

red color filters (R) in accordance with the teachings of the present disclosure.

(17) As will be discussed, in various examples, the trench balance structures are disposed in a semiconductor layer between a respective one of the photodiodes and a respective one of the red color filters of a Quad Bayer color filter array (CFA). In the examples, none of the trench balance structures are disposed between any of the photodiodes and respective green color filters or blue color filters of the Quad Bayer CFA. In various examples, each of the trench balance structures extends from a central region of a respective opening in an isolation grid towards a center of a respective 2×2 grouping of photodiodes under a red color filter. In some examples, the trench balance structure is separated from an intersection of deep trench isolation (DTI) grid structures at the center of the respective 2×2 grouping of photodiodes by a central gap distance greater than or equal to zero. In other examples, each of the trench balance structures extends from a central region of a respective opening in the isolation grid towards first and second sides of the respective opening in the isolation grid of the 2×2 grouping of photodiodes under a red color filter. In some examples, the trench balance structure is separated from the first and second sides of the respective opening by lateral gap distances greater than or equal to zero. In some examples, the trench balance structure is structurally integrated with inner DTI grid structures that provide isolation among photodiodes within the respective 2×2 grouping of photodiodes.

(18) To illustrate, FIG. 1 illustrates one example of a complementary metal oxide semiconductor (CMOS) imaging system **100** with example patterns of trench balance structures included with 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter over a pixel array in accordance with the teachings of the present disclosure. As shown in the depicted example, the imaging system **100** includes an image sensor with pixel array **102**, a control circuit **110**, a readout circuit **106**, and function logic **108**. In one example, pixel array **102** is a two-dimensional (2D) array of pixel cells arranged into 2×2 groupings of photodiodes. In the examples, a Quad Bayer color filter array (CFA) is disposed over a back side of a semiconductor layer over the plurality of 2×2 groupings of photodiodes. The Quad Bayer CFA includes a plurality of color filters, including red color filters, green color filters, and blue color filters, with each color filter of the Quad Bayer CFA is disposed over a respective one of the plurality of 2×2 groupings of photodiodes. In the depicted example, 2×2 groupings of photodiodes under red color filters are labeled **104R**, 2×2 groupings of photodiodes under blue color filters are labeled **104B**, 2×2 groupings of photodiodes under green color filters in the same row as red color filters are labeled **104GR** (e.g., first green color filters), and 2×2 groupings of photodiodes under green color filters in the same row as blue color filters are labeled **104GB** (e.g., second green color filters). As will be discussed in greater detail below, a plurality of trench balance structures **114** is disposed in the semiconductor layer with each one of the plurality of trench balance structures **114** disposed in the semiconductor layer between a respective photodiode and a respective one of the red color filters of the Quad Bayer CFA. In the various examples, none of the plurality of trench balance structures **114** is disposed between any of the photodiodes and respective green color filters (G.sub.R and/or G.sub.B) or blue color filters of the Quad Bayer CFA.

(19) In the depicted example, the photodiodes included in the 2×2 groupings of photodiodes **104R**, **104B**, **104GR**, **104GB** arranged in rows and columns of the pixel array **102** to acquire image data of a person, place, object, etc., which can then be used to render an image of a person, place, object, etc. As will be discussed, a plurality of deep trench isolation (DTI) grid structures is disposed in the semiconductor layer of the pixel array **102** and arranged to form an isolation grid in the semiconductor layer. A plurality of openings is defined by the isolation grid with each one of the photodiodes isolated within a respective one of a plurality of openings defined in the isolation grid. In the various examples, the balance of G.sub.BG.sub.R signal crosstalk between 2×2 groupings of photodiodes under red color filters (R) **104R** to neighboring 2×2 groupings of photodiodes under green color filters (G.sub.B) in the same row as the blue color filters (e.g., green-blue (G.sub.B) color filters) and to neighboring 2×2 groupings of photodiodes under green

color filters (G.sub.R) in the same row as the red color filters (e.g., green-red (G.sub.R) color filters) is improved by absorbing, scattering, reflecting, and/or refracting, etc., light in accordance with the teachings of the present disclosure.

(20) After the photodiodes included in the 2×2 groupings of photodiodes **104R**, **104B**, **104GR**, **104GB** have acquired their image charge, the corresponding analog image signals are read out by readout circuit **106** through column bitlines **112**. In the various examples, readout circuit **106** includes an analog-to-digital conversion (ADC) circuit, which is coupled to convert the analog image signals received from the photodiodes included in the 2×2 groupings of photodiodes **104R**, **104B**, **104GR**, **104GB** through bitlines **112** to digital image signals, which may be then transferred to function logic **108**. Function logic **108** may simply store the image data or even manipulate the image data by applying post image processing or effects. Such image processing may, for example, include image processing, image filtering, image extraction and manipulation, determination of light intensity, crop, rotate, remove red eye, adjust brightness, adjust contrast, etc.

(21) In one example, a control circuit **110** is coupled to pixel array **102** to control operational characteristics of pixel array **102**. For instance, in one example, control circuit **110** generates the transfer gate signals and other control signals to control the transfer and readout of image data from all of the pixel cells **104** of pixel array **102**. In addition, control circuit **110** may generate a shutter signal for controlling image acquisition. In one example, the shutter signal is a rolling shutter signal such that each row of the pixel array **102** is read out sequentially row by row during consecutive acquisition windows. The shutter signal may also establish an exposure time, which is the length of time that the shutter remains open. In one embodiment, the exposure time is set to be the same for each of the frames.

(22) FIGS. 2A-2B illustrate 2×2 groupings of photodiodes of a pixel array with a Quad Bayer filter in accordance with the teachings of the present disclosure. In particular, FIG. 2A is top view illustrating one example of neighboring 2×2 groupings of photodiodes of a pixel array **202** under red, green, and blue color filters of a Quad Bayer filter. FIG. 2B is an example cross-section view through dashed line A-A' of FIG. 2A through two of the trench balance structures **214-3** and **214-4** and two of the photodiodes PD3 and PD4 of the 2×2 grouping of photodiodes **204R** under a red color filter **238** of pixel array **202** in accordance with the teachings of the present disclosure. It is noted that the example 2×2 groupings of photodiodes illustrated in FIGS. 2A-2B may be examples of one or more of the 2×2 groupings of photodiodes of the example pixel array **102** of FIG. 1, and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above.

(23) As shown in the example depicted in FIG. 2A, a 2×2 grouping of photodiodes **204B** is disposed under a blue color filter of the Quad Bayer filter, a 2×2 grouping of photodiodes **204GB** is disposed under a green color filter in the same row as a blue color filter of the Quad Bayer filter, a 2×2 grouping of photodiodes **204R** is disposed under a red color filter of the Quad Bayer filter, and a 2×2 grouping of photodiodes **204GR** is disposed under a green color filter in the same row as a red color filter of the Quad Bayer filter. In the example, a 2×2 grouping of photodiodes **204GR** disposed under a green color filter (e.g., first green color filter) is adjacent to a respective one of the 2×2 groupings of photodiodes **204R** disposed under the red color filter in the same row. A 2×2 grouping of photodiodes **204GB** disposed under a green color filter (e.g., second green color filter) is adjacent to a respective one of 2×2 groupings of photodiodes **204B** disposed under the blue color filter in the same row. The 2×2 grouping of photodiodes **204GB** disposed under the green color filter (e.g., second green color filter) is adjacent to a respective one of 2×2 groupings of photodiodes **204R** disposed under the red color filter in the same column.

(24) As shown in the depicted example, a plurality of DTI grid structures **216** is disposed in a semiconductor layer **236** proximate to a back side **234** of the semiconductor layer **236** and arranged to form an isolation grid in the semiconductor layer **236**. In some embodiments, the semiconductor layer **236** is a silicon wafer or substrate, a silicon germanium alloy, germanium, a silicon carbide

alloy, an indium gallium arsenide alloy, any other alloys formed of III-V compounds, other semiconductor materials or alloys, combinations thereof or bulk substrate. In some embodiments, the semiconductor layer **236** is an epitaxial layer grown on or otherwise disposed on a semiconductor substrate or a wafer substrate. In the example, a plurality of openings are defined by the isolation grid **216**. As shown, the back side **234** of semiconductor layer **236** is opposite a front side **232** of semiconductor layer **236**. In the example, each one of the photodiodes (e.g., PD1, PD2, PD3, PD4) is configured to be illuminated with incident light that is directed through the back side **234** of the semiconductor layer **236** through a microlens **220** and a color filter, such as red color filter **238** as illustrated. In the depicted example, the red color filter **238** is illustrated as being disposed in an opening of a metal grid **222** that is disposed over a filling material **224** and external side DTI grid structures **216E**, which will be described in greater detail below. In the various examples, metal grid **222** helps provide optical isolation between adjacent 2×2 groupings of photodiodes in the pixel array. For example, metal grid **222** helps provide optical isolation between 2×2 groupings of photodiodes under red color filter **238** and adjacent 2×2 groupings of photodiodes under green color filters (e.g., 2×2 grouping of photodiodes **204GR** or **204GB**). In various examples, microlens **220** is one of a plurality of microlenses included in a microlens array disposed over the Quad Bayer filter over the back side **234** of the semiconductor layer **236**. In one example, there is one microlens disposed over each 2×2 groupings of photodiodes or over each color filter of the Quad Bayer filter. In the example, each of the photodiodes is isolated in the semiconductor layer **236** within a respective one of the plurality of openings defined by the isolation grid **216**.

(25) In the example, a plurality of DTI grid structures **216** disposed in the semiconductor layer **236**, which are arranged to form an isolation grid in the semiconductor layer. As shown in the depicted example, each of the plurality of DTI grid structures **216** is arranged to extend into the semiconductor layer **236** from the back side **234** and has a depth or a grid structure depth $D_{sub.G}$ in the semiconductor layer **236** with respect to the back side **234** of the semiconductor layer **236**. The depth $D_{sub.G}$ in embodiments may be less than or equal to a thickness of the semiconductor layer **236**, wherein the thickness of semiconductor layer **236** may range from 2.5 micrometers to 7 micrometers. In one example, the DTI grid structures **216** include a filling material **224** that disposed in semiconductor layer **236**. In the example, a high-k lining material **240** is disposed between the filling material **224** and the semiconductor layer **236**. In one embodiment, the filling material **224** may be further disposed on the back side **234** of the semiconductor layer **236** forming a processing buffer layer providing process protection to underlying layers. In various examples, the filling material **224** may include a dielectric material such as an oxide-based material, a low N material, a conductive material such as polysilicon, tungsten (W), aluminum (Al), or other material, or a combination of dielectric material and conductive material. A low N material may be referred to a material having refractive index being less than that of the semiconductor layer **236**. In various examples, the high-k lining material **240** may include a passivation material, anti-reflective coating layer, or the like. In various examples, the high-k lining material **240** may be comprised of hafnium oxide, aluminum oxide, tantalum pentoxide, zinc oxide, and the like.

(26) In the example, each one of the photodiodes (e.g., PD1, PD2, PD3, PD4) in each 2×2 grouping of photodiodes is isolated within a respective one of a plurality of openings defined by the isolation grid formed with DTI grid structures **216**. For example, the isolation grid **216** may be arranged to provide electrical and/or optical isolation between a 2×2 grouping of photodiodes **204B** and neighboring 2×2 groupings of photodiodes such as 2×2 groupings of photodiodes **204GR** or 2×2 groupings of photodiodes **204GB**. As shown in the example, each 2×2 grouping of photodiodes (e.g., **204B**, **204GB**, **204GR**, **204R**) is surrounded by external side DTI grid structures **216E**, which form a “square” shape around each 2×2 grouping of photodiodes. In addition, interior side DTI grid structures **216I** are formed inside of each 2×2 grouping of photodiodes, which form a “plus” shape and to isolate each of the photodiodes (e.g., PD1, PD2, PD3, PD4) from each other within the 2×2 grouping of photodiodes inside the “square” shape formed by external side DTI grid structures

216E. The DTI grid structures **216** in other embodiments may form different geometric shape such as pentagon, octagonal, triangular, and rectangular or the like. As shown in the example, a center **218** of a respective 2×2 grouping of photodiodes is located at an intersection of orthogonal interior side DTI grid structures **2161** within each 2×2 grouping of photodiodes.

(27) As shown in the depicted example, a plurality of trench balance structures **214-1**, **214-2**, **214-3**, **214-4** is also disposed in the semiconductor layer. In the example, each one of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) is disposed in the semiconductor layer **236** between one of the photodiodes (e.g., PD1, PD2, PD3, PD4) within the 2×2 grouping of photodiodes and a respective one of the red color filters **238** of the Quad Bayer CFA. In addition, none of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) is disposed between any of the photodiodes and respective green color filters or blue color filters of the Quad Bayer CFA. It is appreciated therefore that each one of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) is disposed in the semiconductor layer between one of the plurality of 2×2 groupings of photodiodes (e.g., **204R**) and a respective one of the red color filters, which is neighboring another one of the 2×2 groupings (e.g., **204GR**) of photodiodes disposed beneath one of the green color filters (e.g., first green) in a same row of the pixel array.

(28) As shown in the depicted example, each of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) is arranged to extend into the semiconductor layer **236** from the back side **234** and has a depth or a balance structure depth DB in the semiconductor layer **236** with respect to back side **234** of the semiconductor layer **236**. In some embodiments, the depth DB is less than the respective depth of each the photodiodes PD1, PD2, PD3, and PD4 with respect to the back side **234** of the semiconductor layer **236**. In some embodiments, each of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) may partially extend into the respective photodiode region of corresponding photodiodes PD1, PD2, PD3, PD4. That is, each of the plurality of trench balance structures (e.g., **214-1**, **214-2**, **214-3**, **214-4**) may be in part surrounded by the respective photodiode region of corresponding photodiodes PD1, PD2, PD3, PD4. In various examples, the depth DB of the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** is less than or equal to the depth D.sub.G of the DTI grid structures **216** in the semiconductor layer **236** considering color separation within a pixel cell, processing, and G.sub.BG.sub.R balance performance. In various examples, the depth DB may be in the range of 0.5 μm to 2 μm depending on the thickness of the semiconductor layer **236**.

(29) In one example, the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** include the same materials as the DTI grid structures **216**. For instance, as shown in the depicted example, the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** include a filling material **224**, which may include a dielectric material such as an oxide-based material, a low N material, a conductive material such as polysilicon, tungsten (W), aluminum (Al), or other material, or a combination of dielectric material and conductive material. In the various examples, a high-k lining material **240** is disposed between the filling material **224** and the semiconductor layer **236**. In the various examples, the high-k lining material **240** may include a passivation material, anti-reflective coating layer, or the like. In one embodiment, the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** and the DTI grid structures **216** are structurally connected (e.g., formed at the same time in same lithography process sharing same photomask).

(30) In examples without the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** under the red color filters, it is appreciated that at the horizontal edge under red light, crosstalk mainly happens from the red color channel to the green-red G.sub.R color channel along the horizontal direction at the horizontal edge, but not from the red color channel to the G.sub.B color channel causing the G.sub.BG.sub.R difference or imbalance affecting image quality. The G.sub.BG.sub.R difference may vary across the plurality of Quad pixels included in pixel array and such variation of G.sub.BG.sub.R differences across pixel array occurs in relation of the chief ray angle. For example, minor or zero G.sub.BG.sub.R differences may be found at the center of the pixel array

where the chief ray angle is of 0 degrees, and G.sub.BG.sub.R differences increases as the distance between the Quad pixel and the center of the pixel array increases, i.e., as the chief ray angle increases. However, with the trench balance structures **214-1**, **214-2**, **214-3**, **214-4** under the red color filters, the balance of G.sub.BG.sub.R signal crosstalk between 2×2 grouping of photodiodes **204R** to neighboring 2×2 groupings of photodiodes **204GR** under green color filters (G.sub.R) and to neighboring 2×2 groupings of photodiodes **204GB** under green color filters (G.sub.B) is improved by absorbing, scattering, reflecting, and/or refracting, etc., light in accordance with the teachings of the present disclosure. That is, by absorbing, scattering, reflecting, and/or refracting light directed to 2×2 grouping of photodiodes under the red color filters with the trench balance structures **214-1**, **214-2**, **214-3**, **214-4**, signal differences between 2×2 grouping of photodiodes **204R** to neighboring 2×2 groupings of photodiodes **204GR** under green color filters (G.sub.R) and to neighboring 2×2 groupings of photodiodes **204GB** under green color filters (G.sub.B), can be reduced in accordance with the teachings of the present disclosure.

(31) FIG. 3A is an example top view illustrating increased detail of a 2×2 grouping of photodiodes **304R** including one example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure. It is noted that the example 2×2 grouping of photodiodes **304R** illustrated in FIG. 3A may be an example of the 2×2 grouping of photodiodes **204R** of the example pixel array **202** of FIGS. 2A-2B or the 2×2 groupings of photodiodes **104R** of the example pixel array **102** of FIG. 1 and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above.

(32) As shown in the depicted example, 2×2 grouping of photodiodes **304R** includes a 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4, which are included in a pixel array under a red color filter of a Quad Bayer filter disposed over the pixel array. In the example, the 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4 is isolated within or surrounded by external side DTI grid structures **316E** of isolation grid **316**. Each of the photodiodes PD1, PD2, PD3, PD4 is isolated within respective openings defined by the external DTI grid structures **316E** and the internal DTI grid structures **316I** of isolation grid **316** as shown. A center **318** of the 2×2 grouping of photodiodes **304R** is located at an intersection of orthogonal interior side DTI grid structures (e.g., the internal DTI grid structures **316I**) within the 2×2 grouping of photodiodes **304R**. The internal DTI grid structures **316I** in embodiments refer to part of isolation grid **316** that provide isolation between the 2×2 grouping of photodiodes within the same quad pixel cell and the external DTI grid structures **316E** provide isolation between adjacent 2×2 grouping of photodiodes.

(33) As shown in the depicted example, a plurality of trench balance structures **314-1**, **314-2**, **314-3**, **314-4** is disposed in the semiconductor layer. Each one of the plurality of trench balance structures **314-1**, **314-2**, **314-3**, **314-4** is disposed in the semiconductor layer between a respective one of the photodiodes (e.g., PD1, PD2, PD3, PD4) and a respective one of the red color filters of the Quad Bayer CFA. In various examples, each trench balance structure **314-1**, **314-2**, **314-3**, **314-4** that extends from a central region **328-1**, **328-2**, **328-3**, **328-4** of a respective opening in the isolation grid **316** towards the center **318** of 2×2 grouping of photodiodes **304R**. For instance, as shown in the depicted example, trench balance structure **314-1** extends from central region **328-1** to center **318**, trench balance structure **314-2** extends from central region **328-2** to center **318**, trench balance structure **314-3** extends from central region **328-3** to center **318**, and trench balance structure **314-4** extends from central region **328-4** to center **318**.

(34) In various examples, each of the trench balance structures **314-1**, **314-2**, **314-3**, **314-4** may have a length L (e.g., distance from the center **318** to the opposite ends of the respective trench balance structures) of for example approximately 0.3 μm to 0.5 μm for a 1 μm pixel. In various examples, each of the trench balance structures **314-1**, **314-2**, **314-3**, **314-4** may have a length that varies depending of the distance of the respective pixel from the center region of the pixel array. In the various examples, the width W or critical dimension of each of the trench balance structures

314-1, 314-2, 314-3, 314-4 may be less than or equal to the width of the DTI grid structures **316I** and **316E**. In the various examples, the trench balance structures **314-1, 314-2, 314-3, 314-4** may be fabricated or formed with the same mask used to fabricate or form the DTI grid structures **316I** and **316E** or separately from used to fabricate or form the DTI grid structures **316I** and **316E** with a different mask.

(35) In the depicted example, there is no gap or there is a central gap distance equal to zero between trench balance structures **314-1, 314-2, 314-3, 314-4** and the interior side DTI grid structures **316I** at the center **318**.

(36) FIG. 3B is example top view illustrating increased detail of a 2×2 grouping of photodiodes **304R** including another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure. It is noted that the example 2×2 grouping of photodiodes **304R** illustrated in FIG. 3B may be another example of the 2×2 grouping of photodiodes **204R** of the example pixel array **202** of FIGS. 2A-2B or the 2×2 groupings of photodiodes **104R** of the example pixel array **102** of FIG. 1 and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above. It is further appreciated that the example 2×2 grouping of photodiodes **304R** of FIG. 3B shares many similarities with the example 2×2 grouping of photodiodes **304R** of FIG. 3A.

(37) For instance, the example 2×2 grouping of photodiodes **304R** depicted in FIG. 3B includes a 2×2 arrangement of photodiodes **PD1, PD2, PD3, PD4**, which are included in a pixel array under a common red color filter of a Quad Bayer filter disposed over the pixel array. The red color filter of a Quad Bayer filter is disposed between a single microlens (not illustrated) and 2×2 grouping of photodiodes **304R**. In the example, the 2×2 arrangement of photodiodes **PD1, PD2, PD3, PD4** is isolated within or surrounded by external side DTI grid structures **316E**. Each of the photodiodes **PD1, PD2, PD3, PD4** is isolated within respective openings defined by the external DTI grid structures **316E** and the internal DTI grid structures **316I** as shown. A center **318** of the 2×2 grouping of photodiodes **304R** is located at an intersection of orthogonal interior side DTI grid structures **316I** within the 2×2 grouping of photodiodes **304R**.

(38) As shown in the depicted example, a plurality of trench balance structures **314-1, 314-2, 314-3, 314-4** is disposed in the semiconductor layer. Each one of the plurality of trench balance structures **314-1, 314-2, 314-3, 314-4** is disposed in the semiconductor layer between a respective one of the photodiodes (e.g., **PD1, PD2, PD3, PD4**) and a respective one of the red color filters of the Quad Bayer CFA. In various examples, each trench balance structure **314-1, 314-2, 314-3, 314-4** that extends from a central region **328-1, 328-2, 328-3, 328-4** of a respective opening in the isolation grid **316** towards the center **318** of 2×2 grouping of photodiodes **304R**. For instance, as shown in the depicted example, trench balance structure **314-1** extends from central region **328-1** towards center **318**, trench balance structure **314-2** extends from central region **328-2** towards center **318**, trench balance structure **314-3** extends from central region **328-3** towards center **318**, and trench balance structure **314-4** extends from central region **328-4** towards center **318**.

(39) In various examples, each of the trench balance structures **314-1, 314-2, 314-3, 314-4** may have a length (e.g., distance between opposite ends of the trench balance structures **314-1, 314-2, 314-3, 314-4**) of for example approximately 0.3 μm to 0.5 μm for a 1 μm pixel. In various examples, each of the trench balance structures **314-1, 314-2, 314-3, 314-4** may have a length that varies depending of the distance of the respective pixel from the center region of the pixel array. In the various examples, the width or critical dimension of each of the trench balance structures **314-1, 314-2, 314-3, 314-4** may be less than or equal to the width of the DTI grid structures **316I** and **316E**. In the various examples, the trench balance structures **314-1, 314-2, 314-3, 314-4** may be fabricated or formed with the same mask used to fabricate or form the DTI grid structures **316I** and **316E** or fabricated or formed separately using a different mask, for example for different trenches.

(40) One of the differences between the example 2×2 grouping of photodiodes **304R** of FIG. 3B

and the example 2×2 grouping of photodiodes **304R** of FIG. 3A is that in the example 2×2 grouping of photodiodes **304R** shown in FIG. 3B, there is a gap or there is a central gap distance of that is greater than zero between trench balance structures **314-1**, **314-2**, **314-3**, **314-4** and the intersection of the interior side DTI grid structures **316I** at the center **318**. For instance, in the example depicted in FIG. 3B, there is a central gap distance **330-1** between trench balance structure **314-1** and the center **318**, a central gap distance **330-2** between trench balance structure **314-2** and the center **318**, a central gap distance **330-3** between trench balance structure **314-3** and the center **318**, and a central gap distance **330-4** between trench balance structure **314-4** and the center **318**. In various examples, the central gap distances **330-1**, **330-2**, **330-3**, and **330-4** may be for example approximately 0.2 μm. In various examples, the minimum central gap distances **330-1**, **330-2**, **330-3**, and **330-4** may be determined based on processing design rules and the size of the corresponding pixel. In various examples, the smaller the central gap distances **330-1**, **330-2**, **330-3**, and **330-4**, the better the improvement on G.sub.BG.sub.R differences.

(41) FIG. 4A is an example top view illustrating increased detail of a 2×2 grouping of photodiodes **404R** including yet another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure. It is noted that the example 2×2 grouping of photodiodes **404R** illustrated in FIG. 4A may be yet another example of the 2×2 grouping of photodiodes **204R** of the example pixel array **202** of FIGS. 2A-2B or the 2×2 groupings of photodiodes **104R** of the example pixel array **102** of FIG. 1 and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above. In the example, the red color filter of a Quad Bayer filter is disposed between a single microlens (not illustrated) and 2×2 grouping of photodiodes **404R**.

(42) As shown in the depicted example, 2×2 grouping of photodiodes **404R** includes a 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4, which are included in a pixel array under a red color filter of a Quad Bayer filter disposed over the pixel array. In the example, the 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4 is isolated within or surrounded by external side DTI grid structures **416E**. Each of the photodiodes PD1, PD2, PD3, PD4 is isolated within respective openings defined by the external DTI grid structures **416E** and the internal DTI grid structures **416I** as shown. A center **418** of the 2×2 grouping of photodiodes **404R** is located at an intersection of orthogonal interior side DTI grid structures **416I** within the 2×2 grouping of photodiodes **404R**.

(43) As shown in the depicted example, a plurality of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** is disposed in the semiconductor layer. Each one of the plurality of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** is disposed in the semiconductor layer between a respective one of the photodiodes (e.g., PD1, PD2, PD3, PD4) and a respective one of the red color filters of the Quad Bayer CFA. As shown, each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** has a first end **415** and a second end **417** that is opposite the first end. In various examples, the first end **415** of each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** extends from a respective central region **428-1**, **428-2**, **428-3**, **428-4** of a respective opening in the isolation grid towards a first side **419** of the respective opening in the isolation grid. In the depicted example, the sides (e.g., **419**, **421**) of the respective opening in the isolation grid are formed with internal DTI grid structures **416I** as shown. Continuing with the example, the second end **417** (opposite the first end **415**) of each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** extends from the respective central region **428-1**, **428-2**, **428-3**, **428-4** of a respective opening in the isolation grid towards a second side **421** of the respective opening in the isolation grid. In the depicted example, the first side **419** and the second side **421** of the respective opening in the isolation grid are orthogonal internal DTI grid structures **416I** and intersect at the center **418** as shown. In the depicted examples, each the plurality of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** and the corresponding internal DTI grid structures **416I** may form a triangular shaped within a respective opening in the isolation grid **416**.

(44) In various examples, each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may have a length (e.g., distance between first and second ends **415** and **417**) of for example approximately 0.3 μm to 0.5 μm for a 1 μm pixel. In various examples, each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may have a length that varies depending of the distance of the respective pixel from the center region of the pixel array. In the various examples, the width or critical dimension of each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may be less than or equal to the width of the DTI grid structures **4161** and **416E**. In the various examples, the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may be fabricated or formed with the same mask used to fabricate or form the DTI grid structures **4161** and **416E** or a different mask.

(45) In the depicted example, there is no gap or there is a lateral gap distance equal to zero between trench balance structures **414-1**, **414-2**, **414-3**, **414-4** and the interior side DTI grid structures **4161**.

(46) FIG. 4B is example top view illustrating increased detail of a 2×2 grouping of photodiodes **404R** including still another example of trench balance structures under a red color filter of a Quad Bayer filter in accordance with the teachings of the present disclosure. It is noted that the example 2×2 grouping of photodiodes **404R** illustrated in FIG. 4B may be still another example of the 2×2 grouping of photodiodes **204R** of the example pixel array **202** of FIGS. 2A-2B or the 2×2 groupings of photodiodes **104R** of the example pixel array **102** of FIG. 1 and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above. It is further appreciated that the example 2×2 grouping of photodiodes **404R** of FIG. 4B shares many similarities with the example 2×2 grouping of photodiodes **404R** of FIG. 4A.

(47) For instance, the example 2×2 grouping of photodiodes **404R** depicted in FIG. 4B includes a 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4, which are included in a pixel array under a red color filter of a Quad Bayer filter disposed over the pixel array. In the example, the 2×2 arrangement of photodiodes PD1, PD2, PD3, PD4 is isolated within or surrounded by external side DTI grid structures **416E** of isolation grid **416**. Each of the photodiodes PD1, PD2, PD3, PD4 is isolated within respective openings defined by the external DTI grid structures **416E** and the internal DTI grid structures **4161** of isolation grid **416** as shown. A center **418** of the 2×2 grouping of photodiodes **404R** is located at an intersection of orthogonal interior side DTI grid structures **4161** within the 2×2 grouping of photodiodes **404R**.

(48) As shown in the depicted example, a plurality of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** is disposed in the semiconductor layer. Each one of the plurality of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** is disposed in the semiconductor layer between a respective one of the photodiodes (e.g., PD1, PD2, PD3, PD4) and a respective one of the red color filters of the Quad Bayer CFA. As shown, each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** has a first end **415** and a second end **417** that is opposite the first end **415**. In various examples, the first end **415** of each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** extends from a respective central region **428-1**, **428-2**, **428-3**, **428-4** of a respective opening in the isolation grid towards a first side **419** of the respective opening in the isolation grid **416**. In the depicted example, the sides (e.g., **419**, **421**) of the respective opening in the isolation grid **416** are formed with internal DTI grid structures **4161** as shown. Continuing with the example, the second end **417** (opposite the first end **415**) of each trench balance structure **414-1**, **414-2**, **414-3**, **414-4** extends from the respective central region **428-1**, **428-2**, **428-3**, **428-4** of a respective opening in the isolation grid **416** towards a second side **421** of the respective opening in the isolation grid **416**. In the depicted example, the first side **419** and the second side **421** of the respective opening in the isolation grid **416** are orthogonal internal DTI grid structures **4161** and intersect at the center **418** as shown.

(49) In various examples, each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may have a length (e.g., distance between opposite ends of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4**) of for example approximately 0.3 μm to 0.5 μm for a 1 μm pixel. In various examples, each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may have a length that

varies depending of the distance of the respective pixel from the center region of the pixel array. In the various examples, the width or critical dimension of each of the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may be less than or equal to the width of the DTI grid structures **4161** and **416E**. In the various examples, the trench balance structures **414-1**, **414-2**, **414-3**, **414-4** may be fabricated or formed with the same mask used to fabricate or form the DTI grid structures **4161** and **416E** or a different mask.

(50) One of the differences between the example 2×2 grouping of photodiodes **404R** of FIG. **4B** and the example 2×2 grouping of photodiodes **404R** of FIG. **4A** is that in the example 2×2 grouping of photodiodes **404R** shown in FIG. **4B**, there is a gap or there is a lateral gap distance of that is greater than zero between the first and second ends **415**, **417** of trench balance structures **414-1**, **414-2**, **414-3**, **414-4** and the respective interior side **419**, **421** formed with DTI grid structures **4161**. For instance, in the example depicted in FIG. **4B**, there is a lateral gap distance **430-1** between the first and second ends **415**, **417** of trench balance structure **414-1** and the respective interior side **419**, **421** formed with DTI grid structures **4161**, a lateral gap distance **430-2** between the first and second ends **415**, **417** of trench balance structure **414-2** and the respective interior side **419**, **421** formed with DTI grid structures **4161**, a lateral gap distance **430-3** between the first and second ends **415**, **417** of trench balance structure **414-3** and the respective interior side **419**, **421** formed with DTI grid structures **4161**, and a lateral gap distance **430-4** between the first and second ends **415**, **417** of trench balance structure **414-4** and the respective interior side **419**, **421** formed with DTI grid structures **4161**. In various examples, the lateral gap distances **430-1**, **430-2**, **430-3**, and **430-4** may be for example approximately 0.2 μm. In various examples, the minimum lateral gap distances **430-1**, **430-2**, **430-3**, and **430-4** may be determined based on processing design rules. In various examples, the smaller the central gap distances **430-1**, **430-2**, **430-3**, and **430-4**, the better the improvement on G.sub.BG.sub.R differences.

(51) FIG. **5** illustrates center and edge regions of an example pixel array **502** including various examples of trench balance structures included with at least some of the 2×2 groupings of photodiodes under red color filters of a Quad Bayer filter in accordance with the teachings of the present disclosure. It is noted that the example pixel array **502** illustrated in FIG. **5** may be another example of pixel array **102** of FIG. **1**, and it should be appreciated that similarly named and numbered elements referenced below are coupled and function as described above.

(52) As shown in the example depicted in FIG. **5**, pixel array **502** includes a center region **502C** and end or edge regions including a top edge region **502T**, a bottom edge region **502B**, a left edge region **502L**, and a right edge region **502R**. The center region **502C** and the edge regions **502T**, **502B**, **502L**, **502R** of pixel array **502** may be defined in terms of field of view, which is related to the size of pixel array **502** and an image height of an object. In one embodiment, the center region **502C** may be defined as an imaging region of the pixel array **502** between a central field of view and a 0.05 field of view, and the peripheral region may be defined as an imaging region of the pixel array **502** greater than a 0.05 field of view. In the example, pixel array **502** is a two-dimensional (2D) array of pixel cells arranged into 2×2 groupings of photodiodes including a Quad Bayer color filter array (CFA) disposed over the plurality of 2×2 groupings of photodiodes. The Quad Bayer CFA includes red color filters, green color filters, and blue color filters, with each color filter of the Quad Bayer CFA is disposed over a respective one of the plurality of 2×2 groupings of photodiodes. In the depicted example, 2×2 groupings of photodiodes under red color filters are labeled **504R**, 2×2 groupings of photodiodes under blue color filters are labeled **504B**, 2×2 groupings of photodiodes under green color filters in the same row as red color filters are labeled **504GR**, and 2×2 groupings of photodiodes under green color filters in the same row as blue color filters are labeled **504GB**. The 2×2 groupings of photodiodes under red color filters **504R** may be disposed neighboring to 2×2 groupings of photodiodes under green color filters in both row and column direction.

(53) In various examples, a plurality of trench balance structures **514A**, **514B** as described in detail

above are disposed in the semiconductor layer in 2×2 groupings of photodiodes between a respective photodiode and a respective one of the red color filters of the Quad Bayer CFA. In the various examples, none of the plurality of trench balance structures **514A**, **514B** are disposed between any of the photodiodes and respective green color filters (G.sub.R and/or G.sub.B) or blue color filters of the Quad Bayer CFA. In some examples, it is appreciated that some of the 2×2 groupings of photodiodes under red color filters of the Quad Bayer CFA may or may not include respective trench balance structures **514A**, **514B**.

(54) For instance, as shown in the example depicted in FIG. 5, trench balance structures **514A**, **514B** are not included in 2×2 groupings of photodiodes under red color filters in the center region **502C** of pixel array **202**. In particular, it is appreciated that at the center region **502C** of pixel array **502**, the chief ray angle (CRA) of incident light is zero degrees. As such, there is no G.sub.BG.sub.R difference and trench balance structures **514A**, **514B** are therefore not needed to balance any G.sub.BG.sub.R difference, which may enable center region **502C** to have better color separation of a 2×2 groupings of photodiodes under red color filters (quad pixel cell) as trench balance structures **514A**, **514B** may induce non-uniformity sensitivity among corresponding 2×2 groupings of photodiodes. However, towards the edge regions of the pixel array **502**, such as for example in the top, bottom, left, and right regions **502T**, **502B**, **502L**, **502R**, the CRA is increases, which increases the usefulness of trench balance structures **514A**, **514B**. As such, as shown in the depicted example, trench balance structures **514A**, **514B** are included in the 2×2 groupings of photodiodes under red color filters in the edge regions of the pixel array **502**, such as for example in the top, bottom, left, and right regions **502T**, **502B**, **502L**, **502R**. In some embodiments, the arrangement (number, positions) of trench balance structures **514A**, **514B** for red color filters across pixel array may be determined in view of G.sub.BG.sub.R difference level and color separation level.

(55) However, it is appreciated that in some embodiments, it may be desirable to have the same trench balance structures such as trench balance structures **514A** included in each one of 2×2 groupings of photodiodes under red color filters across the pixel array.

(56) In various examples, it is appreciated that structural parameters including one or more of width, length, depth, center gap distance, and lateral gap distance of the trench balance structures **514A**, **514B** included in the 2×2 groupings of photodiodes under red color filters may vary across pixel array **202** based on needed G.sub.BG.sub.R balance and improved color separation. As such, it is appreciated that the types of trench balance structures **514A**, **514B** may also vary across pixel array **502**. For instance, as shown in the example depicted in FIG. 5, trench balance structures **514A** illustrate trench balance structures similar to the examples described in FIG. 3A while trench balance structures **514B** illustrate trench balance structures similar to the examples described in FIG. 3B. In the various examples, the lengths of each of the trench balance structures **514A**, **514B** may be configured differently depending on location of red pixel relative to the center region **502C** and associated G.sub.BG.sub.R difference. It is further appreciated that the trench balance structures included in the 2×2 groupings of photodiodes may include any one kind structure or a combination of trench balance structures illustrated in FIG. 2A, 3A, 3B, 4A and 4B depending on pixel size, placement in the pixel array, color separation performance, and/or G.sub.BG.sub.R difference level.

(57) The above description of illustrated examples of the present disclosure, including what is described in the Abstract, is not intended to be exhaustive or to limit the examples of the present disclosure to the precise forms disclosed. While specific examples of the present disclosure are described herein for illustrative purposes, various modifications are possible within the scope of the present disclosure, as those skilled in the relevant art will recognize.

(58) These modifications can be made to the examples of the present disclosure in light of the above detailed description. The terms used in the following claims should not be construed to limit the examples of the present disclosure to the specific examples disclosed in the specification.

Rather, the scope of the examples of the present disclosure is to be determined entirely by the following claims, which are to be construed in accordance with established doctrines of claim interpretation.

Claims

1. A pixel array, comprising: a plurality of 2×2 groupings of photodiodes in a semiconductor layer to generate image charge in response to incident light directed through a back side of the semiconductor layer; a Quad Bayer color filter array (CFA) disposed over the back side of the semiconductor layer over the plurality of 2×2 groupings of photodiodes, wherein the Quad Bayer CFA includes a plurality of color filters, wherein the plurality of color filters includes red color filters, green color filters, and blue color filters, wherein each color filter of the Quad Bayer CFA is disposed over a respective one of the plurality of 2×2 groupings of photodiodes; and a plurality of trench balance structures disposed in the semiconductor layer, wherein each one of the plurality of trench balance structures is disposed in the semiconductor layer between one of the photodiodes and a respective one of the red color filters of the Quad Bayer CFA, wherein none of the plurality of trench balance structures are disposed between any of the photodiodes and respective green color filters or blue color filters of the Quad Bayer CFA.
2. The pixel array of claim 1, further comprising a plurality of DTI grid structures disposed in the semiconductor layer and arranged to form an isolation grid in the semiconductor layer, wherein a plurality of openings are defined by the isolation grid, wherein each one of the photodiodes is isolated within a respective one of the plurality of openings defined by the isolation grid.
3. The pixel array of claim 2, wherein the plurality of trench balance structures includes a trench balance structure that extends from a central region of a respective opening in the isolation grid towards a center of a respective 2×2 grouping of photodiodes.
4. The pixel array of claim 3, wherein the trench balance structure is separated from an intersection of DTI grid structures at the center of the respective 2×2 grouping of photodiodes by a central gap distance.
5. The pixel array of claim 4, wherein the central gap distance is zero.
6. The pixel array of claim 2, wherein the plurality of trench balance structures includes a trench balance structure having a first end that is opposite a second end, wherein the first end extends from a central region of a respective opening in the isolation grid towards a first side of the respective opening in the isolation grid, wherein the second end extends from the central region of the respective opening in the isolation grid towards a second side of the respective opening in the isolation grid, wherein the first and second sides of the respective opening in the isolation grid intersect with a center of a respective 2×2 grouping of photodiodes.
7. The pixel array of claim 6, wherein the first and second ends of the trench balance structure are separated from the first and second sides of the respective opening in the isolation grid by lateral gap distances.
8. The pixel array of claim 7, wherein the lateral gap distances are zero.
9. The pixel array of claim 2, wherein the plurality of trench balance structures and the plurality of DTI grid structures comprise: a filling material disposed in the semiconductor layer; and a high-k lining material disposed between the filling material and the semiconductor layer.
10. The pixel array of claim 2, wherein a balance structure depth of the plurality of trench balance structures is less than or equal to a grid structure depth of the plurality of DTI grid structures.
11. The pixel array of claim 1, further comprising a microlens array disposed over the back side of the semiconductor layer over the plurality of 2×2 groupings of photodiodes, wherein each microlens of the microlens array is disposed over a respective one of the plurality of 2×2 groupings of photodiodes.
12. The pixel array of claim 1, wherein no trench balance structures are disposed in a center region

of the pixel array.

13. The pixel array of claim 12, wherein each of the plurality of trench balance structures is disposed in an edge region of the pixel array.

14. The pixel array of claim 1, wherein each one of the plurality of trench balance structures is disposed in the semiconductor layer between one of the plurality of 2×2 groupings of photodiodes and the respective one of the red color filters that is neighboring another one of the 2×2 groupings of photodiodes disposed beneath one of the green color filters in a same row of the pixel array.

15. The pixel array of claim 1, wherein structural parameters including one or more of width, length, depth, center gap distance, and lateral gap distance of each one of the plurality of the trench balance structures vary across the pixel array.

16. An imaging system, comprising: a pixel array including: a plurality of 2×2 groupings of photodiodes in a semiconductor layer to generate image charge in response to incident light directed through a back side of the semiconductor layer; a Quad Bayer color filter array (CFA) disposed over the back side of the semiconductor layer over the plurality of 2×2 groupings of photodiodes, wherein the Quad Bayer CFA includes a plurality of color filters, wherein the plurality of color filters includes red color filters, green color filters, and blue color filters, wherein each color filter of the Quad Bayer CFA is disposed over a respective one of the plurality of 2×2 groupings of photodiodes; and a plurality of trench balance structures disposed in the semiconductor layer, wherein each one of the plurality of trench balance structures is disposed in the semiconductor layer between one of the photodiodes and a respective one of the red color filters of the Quad Bayer CFA, wherein none of the plurality of trench balance structures are disposed between any of the photodiodes and respective green color filters or blue color filters of the Quad Bayer CFA; control circuitry coupled to the pixel array to control operation of the pixel array; and readout circuitry coupled to the pixel array to read out image data from the pixel array.

17. The imaging system of claim 16, further comprising function logic coupled to the readout circuitry to store the image data read out from the pixel array.

18. The imaging system of claim 16, wherein the pixel array further comprises a plurality of DTI grid structures disposed in the semiconductor layer and arranged to form an isolation grid in the semiconductor layer, wherein a plurality of openings are defined by the isolation grid, wherein each one of the photodiodes is isolated within a respective one of the plurality of openings defined by the isolation grid.

19. The imaging system of claim 18, wherein the plurality of trench balance structures includes a trench balance structure that extends from a central region of a respective opening in the isolation grid towards a center of a respective 2×2 grouping of photodiodes.

20. The imaging system of claim 19, wherein the trench balance structure is separated from an intersection of DTI grid structures at the center of the respective 2×2 grouping of photodiodes by a central gap distance.

21. The imaging system of claim 20, wherein the central gap distance is zero.

22. The imaging system of claim 18, wherein the plurality of trench balance structures includes a trench balance structure having a first end that is opposite a second end, wherein the first end extends from a central region of a respective opening in the isolation grid towards a first side of the respective opening in the isolation grid, wherein the second end extends from the central region of the respective opening in the isolation grid towards a second side of the respective opening in the isolation grid, wherein the first and second sides of the respective opening in the isolation grid intersect with a center of a respective 2×2 grouping of photodiodes.

23. The imaging system of claim 22, wherein the first and second ends of the trench balance structure are separated from the first and second sides of the respective opening in the isolation grid by lateral gap distances.

24. The imaging system of claim 23, wherein the lateral gap distances are zero.

25. The imaging system of claim 18, wherein the plurality of trench balance structures and the

plurality of DTI grid structures comprise: a filling material disposed in the semiconductor layer; and a high-k lining material disposed between the filling material and the semiconductor layer.

26. The imaging system of claim 18, wherein a balance structure depth of the plurality of trench balance structures is less than or equal to a grid structure depth of the plurality of DTI grid structures.

27. The imaging system of claim 16, wherein the pixel array further comprises a microlens array disposed over the back side of the semiconductor layer over the plurality of 2×2 groupings of photodiodes, wherein each microlens of the microlens array is disposed over a respective one of the plurality of 2×2 groupings of photodiodes.

28. The imaging system of claim 16, wherein no trench balance structures are disposed in a center region of the pixel array.

29. The imaging system of claim 28, wherein each of the plurality of trench balance structures is disposed in an edge region of the pixel array, wherein the edge region surrounds the center region.

30. The imaging system of claim 16, wherein each one of the plurality of trench balance structures is disposed in the semiconductor layer between one of the plurality of 2×2 groupings of photodiodes and the respective one of the red color filters that is neighboring another one of the 2×2 groupings of photodiodes disposed beneath one of the green color filters in a same row of the pixel array.
