

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280753

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Markesteyn; Michelle et al.

ERGONOMIC DIBBLE GARDENING TOOL

Abstract

A garden dibble, comprising: a shank, wherein the shank is rectilinear and has a rectangular footprint and a rectangular cross-section, wherein the shank has a length, a width and a thickness, wherein the thickness is between a first face of the shank and a second face of the shank opposite the first face, wherein the length is at least 6 times the thickness and the width is at least twice the thickness; a plurality of rule marks on the first face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the first face and the second face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank, wherein the tooth is substantially triangular.

Inventors: Markesteyn; Michelle (Hubbard, OR), O'Brien; Seth R. (Corvallis, OR), Pohlschneider; Ethan N. (Corvallis, OR)

Applicant: Oregon State University (N/A, N/A)

Family ID: 1000007727745

Assignee: Oregon State University (Corvallis, OR)

Appl. No.: 18/600546

Filed: March 08, 2024

Publication Classification

Int. Cl.: A01C5/02 (20060101)

U.S. Cl.:

CPC A01C5/02 (20130101);

Background/Summary

BACKGROUND

[0001] Most garden tools designed for youth are miniature versions of less effective adult tools. They do not necessarily consider how youth leverage their bodies to work in a garden. The way that adults and children interact with the earth and the ergonomics needed for tools are very different. In the interest of safety, the utility of garden tools for youth is limited, often rendering them ineffective. For example, youth shovels may have such rounded edges they do not easily break up the soil.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0002] Material described herein is illustrated by way of example and not by way of limitation in accompanying figures. For simplicity and clarity of illustration, elements illustrated in figures are not necessarily drawn to scale and exact locations. For example, dimensions of some elements can be exaggerated relative to other elements for clarity. Also, various physical features can be represented in their simplified “ideal” forms and geometries for clarity of discussion, but it is nevertheless to be understood that practical implementations can only approximate illustrated ideals. For example, smooth surfaces and square intersections can be drawn in disregard of finite roughness, corner-rounding, and imperfect angular intersections characteristic of structures formed by nanofabrication techniques. Further, where considered appropriate, reference labels have been repeated among figures to indicate corresponding or analogous elements.

[0003] FIG. 1A illustrates a plan view of a binder dibble in accordance with at least one implementation.

[0004] FIG. 1B illustrates a profile view of the front edge of the binder dibble shown in FIG. 1A in accordance with at least one implementation.

[0005] FIG. 2A illustrates an enlarged plan view of a first tooth example of a binder dibble, in accordance with at least one implementation.

[0006] FIG. 2B illustrates an enlarged plan view of a second tooth example of a binder dibble, in accordance with at least one implementation.

[0007] FIG. 2C illustrates an enlarged plan view of a third tooth example of a binder dibble, in accordance with at least one implementation.

[0008] FIG. 3 illustrates a plan view of a binder dibble stowed in a three-ring binder, in accordance with at least one implementation.

[0009] FIG. 4 illustrates a view of a binder dibble in use to prepare a furrow for planting, in accordance with at least one implementation.

[0010] FIG. 5 illustrates a view of a binder dibble in use to finish planting, in accordance with at least one implementation.

[0011] FIG. 6 illustrates a flowchart summarizing a method for using a binder dibble, in accordance with at least one implementation.

DETAILED DESCRIPTION

[0012] Few, if any, garden tools designed for youth are created for the specific needs of school gardens. Tools for youth in school gardens are to be cleaned and sanitized. They also are to be easily stored as classroom space is limited. It is desirable for tools for school gardens to be brightly colored, so they may not get lost outdoors, and made from durable materials. Some dibbles may have sharp, pointed edges that may pose a safety hazard for children and adult users. Dibbles may be cylindrical in design, which may not allow for easy storage of multiple dibbles or personal

transport. Some dibbles are made of wood and therefore may not be easily sanitized as needed for the classroom setting. Some dibbles may not have a combination of multiple directional measurements, increasing the orientations that the dibble needs to maneuver to successfully plant seeds. Dibbles may have inch measurements demarcated up to six inches. Most seeds in school gardens are planted less than one inch deep. Lower elementary-aged students may not have been instructed in fractions and/or developed the cognitive capacity to infer fractional depth measurements from one-inch dibble markings and may require fractional markings for guidance. [0013] Disclosed herein is a dibble gardening implement that is ergonomically designed for specific use by elementary and middle school-aged children. In at least one implementation, the dibble is adapted for use by school-aged children in gardens that are commonly organized and managed by elementary schools. Research has shown that most school-aged children instinctively hold and use tools differently from adults, thus, in at least one implementation, the dibble is scaled and shaped to ergonomically fit in and be held by hands of school-age children. Compared to similar garden implements made for adults, the dibble of at least one implementation is significantly more efficient as a single tool for making holes in soil, digging shallow furrows to a desired depth, and for covering newly planted seeds within those holes or furrows by school-aged children.

[0014] In at least one implementation, the dibble (also referred to as a “binder dibble”) has a substantially two-dimensional body plan, comprising a flattened rectangular shank for grasping that has a similar shape to a measurement ruler. Contrary to conventional dibbles having a coaxial sharpened point at the end of a cylindrical shaft, in at least one implementation, the dibble comprises a triangular tooth that extends orthogonally from an edge of the shank, whereby the apex of the tooth is distal to the shank edge. In at least one implementation, the tooth may be shaped as an equilateral triangle, isosceles triangle (two equal sides), a scalene triangle (no equal sides), as a right triangle.

[0015] In at least one implementation, the point of the tooth is oriented such that the point is substantially vertical to the ground when the disclosed dibble is held by a child, whereby the shank is in line with the child's hand or wrist. When a child strikes the ground to make a smash-point, the child has a tendency to hold the shank in a manner that is natural to the child, so that the child does not have to hold the disclosed dibble at an angle that is mechanically awkward for the child. In this manner, the child may apply a maximal striking force to break the soil when striking garden soil (e.g., normally prepared garden soil) with the tooth of the disclosed dibble, enabling maximal efficiency of motion of the child's hand and arm.

[0016] In at least one implementation, the tooth is disposed at one end of the shank to provide highest ergonomic deployment of the disclosed dibble to enable highest striking and dragging (e.g., to dig a furrow by dragging the tooth through the soil) efficiency. For furrow formation, children tend to drag a tool towards them. In at least one implementation, the tooth is located substantially at an end of the shank of the disclosed dibble to maximize hand and arm motion, as the child may grasp the shank in line with the wrist. Such a grasp can be naturally intuitive and therefore ergonomic for a child. For example, a child may tend to pull the disclosed dibble toward or across themselves when dragging the tooth through the soil to dig a furrow. In at least one implementation, the apex of the tooth is rounded for safety, whereby the apex has a radius of curvature that is greater than 0.1 inch (e.g., approximately 2.5 mm) but not greater than 1 inch (e.g., approximately 25 mm) to permit a sufficient striking force to break through the surface of normally prepared garden soil.

[0017] In at least one implementation, the tooth comprises a plurality of depth marks to denote penetration depth of the tooth into soil. In at least one implementation, depth marks extend laterally (e.g., parallel to long edges of the shank) partially across a wide surface of the tooth. For example, the plurality of depth marks may have a maximum extent of several millimeters, whereby the tooth may have a width of, for instance, 0.5 inch to 3 inches (e.g., 12 to 75 millimeters) at its base. In at

least one implementation, the depth marks are raised (e.g., embossed) to a height of, for instance, 0.01 inch to 0.03 inch (e.g., 25 to 75 microns) above the wide surface of the tooth for visibility. In at least one implementation, partial lateral extension of the depth marks enables more efficient cleaning of the disclosed dibble, as full lateral extension across the width of the tooth may enable soil to accumulate on the tooth, necessitating more frequent and arduous cleaning. In at least one implementation, partial extension of the depth marks reduces the tendency of soil to adhere to the tooth, reducing the frequency yet increasing the ease of cleaning of the disclosed dibble.

[0018] In at least one implementation, the depth marks are spaced vertically (e.g., from point to base) by a constant distance. For example, four depth marks are arrayed in a stack and may be spaced apart vertically by 0.25 inch (e.g., approximately 6 mm), whereby a lowest depth mark may be offset from (e.g., above) the tip by 0.25 inch, and the three remaining depth marks may appear at incremental distances (offsets) of 0.25 inch above each other, where the fourth depth mark is in line with a lower edge of the shank (e.g., to which the widest portion of the tooth is attached).

[0019] Many conventional dibbles sold in the United States have depth markings spaced apart by one-inch intervals, requiring an ability to estimate fractional distances. In at least one implementation, depth marks are unlabeled with numerical indicators as many young children may not have had educational instruction in fractional distance until third or fourth grade. For example, for many plantings, seeds are commonly planted at depths of one inch (25 mm) or less. In at least one implementation, the tooth may have a height of one inch from base to tip. Instructing a child to make a hole that is one-half or three-quarters of an inch deep may not have meaning to the child, as they may not yet understand numerators and denominators even if they generally understand the concept of fractions. However, instructing a child to make a hole two marks or three marks deep, or four marks deep (e.g., burying the entire tooth) by striking the tooth into the soil to such a depth may be more easily understood and followed by the child, as the child may be able to count the marks and therefore aids in furthering conceptual understanding of fractional distance.

[0020] In at least one implementation, the shaft of the disclosed dibble is ruled with a plurality of ruler marks spaced apart by one-inch incremental distances. In at least one implementation, such marks may guide lateral placement of seeds. For example, if a child is instructed to plant seeds a distance of approximately 3 inches from each other within a row, and to separate rows by 12 inches apart, a child may be able to readily measure such a distance by using the shank as a ruler. In at least one implementation, numerical labels are included adjacent to the ruler marks to facilitate measurements using the ruled shank. In at least one implementation, the shank of the disclosed dibble has rounded corners for safety. In at least one implementation, the shank may have a length ranging from 3 inches to 14 inches and width ranging from 0.5 inch to 4 inches.

[0021] In at least one implementation, the shaft of the disclosed dibble includes two or more binder holes distributed along a long edge of the shank. For example, two or more binder holes may be adjacent to and distributed along a second (e.g., upper) long edge of the shank, parallel to the first (e.g., lower) long edge from which the tooth extends. In at least one implementation, the two or more binder holds may be dimensioned to enable the disclosed dibble to be secured within a binder notebook by clamping rings for ease of storage. For example, the disclosed dibble may include three binder holes dimensioned to align to the three clamping rings of a standard three-ring binder notebook sold in the United States (binder holes may be distanced to accommodate other ring notebook standards as well). In at least one implementation, a center-located binder hole may be oval-shaped, while end binder holes may be circular. In at least one implementation, the two or more binder holes enable the disclosed dibble to be conveniently stowed and carried within a notebook or clipboard by a school child from classroom to garden at a school, for example. Similar remarks apply to home gardens as well.

[0022] In at least one implementation, the disclosed dibble may be dimensioned to have a thickness suitable (e.g., between 0.1 inch to 0.5 inch) for portable storage of multiple dibbles within a notebook such as a three-ring binder, or on a clipboard, for example. Stowage of multiple dibbles

within a notebook or clipboard may facilitate carrying a plurality of dibbles from classroom to garden by a teacher, teaching assistant, parent, or student, for example. In at least one implementation, the indicated thickness range may be suitable for stowing and carrying the disclosed dibble in a convenient pants pocket, a shirt pocket or in a backpack compartment.

[0023] Here, some methods and devices may be shown in block diagram form, rather than in detail, to avoid obscuring present disclosure. Reference throughout this specification to “an implementation” or “one implementation” or “some implementations” means that a particular feature, structure, function, or characteristic described in connection with an implementation is included in at least one implementation of disclosure. Thus, appearances of phrase “in an implementation” or “in one implementation,” “in at least one implementation,” or “some implementations” in various places throughout this specification are not necessarily referring to same implementation of disclosure. Furthermore, particular features, structures, functions, or characteristics can be combined in any suitable manner in one or more implementations. For example, a first implementation can be combined with a second implementation anywhere particular features, structures, functions, or characteristics associated with two implementations are not mutually exclusive. A list of definitions follows, whereby following definitions may provide or augment literal support for claims.

[0024] Here, “garden dibble” may generally refer to a garden or agricultural implement for creating holes in soil for planting seeds. A conventional dibble is a wooden, plastic or metal stick with a sharp point on one end. A dibble may be used by simply poking a hole in soil to certain depth.

[0025] Here, “coupled” and “connected,” along with their derivatives, can be used to describe functional or structural relationships between components. These terms are not intended as synonyms for each other. Rather, in particular implementations, term “connected” can be used to indicate that two or more elements are in direct physical, optical, or electrical contact with each other. Here, “coupled” can be used to indicate that two or more elements are in either direct or indirect (with other intervening elements between them) physical, electrical or in magnetic contact with each other, and/or that two or more elements co-operate or interact with each other (e.g., as in a cause-and-effect relationship). Here, “coupled” can also generally refer to direct attachment of one electronic component to another. An electric or magnetic field can couple one component to another, where field may be controlled by one component to influence other in some manner.

[0026] Here, “over,” “under,” “between,” and “on” can generally refer to a relative position of one component or material with respect to other components or materials where such physical relationships are noteworthy. Unless these terms are modified with “direct” or “directly,” one or more intervening components or materials can be present. Similar distinctions are to be made in context of component assemblies. As used throughout this description, and in claims, a list of items joined by term “at least one of” or “one or more of” can mean any combination of listed terms.

[0027] Here, “adjacent” can generally refer to a position of a thing being next to (e.g., immediately next to or close to with one or more things between them) or adjoining another thing (e.g., abutting it).

[0028] Unless otherwise specified in explicit context of their use, terms “substantially equal,” “about equal,” and “approximately equal” can generally mean that there is no more than incidental variation between two things so described. In at least one implementation, such variation is no more than $\pm 10\%$ of referred value.

[0029] FIG. 1A illustrates a plan view of a binder dibble **100**, in accordance with at least one implementation. In at least one implementation, binder dibble **100** comprises a shank **102** and a tooth **104** extending from shank **102**. In at least one implementation, shank **102** is substantially rectangular, comprising an upper edge **106** and an opposing parallel lower edge **108**. In at least one implementation, upper edge **106** and lower edge **108** are long edges, in contrast to orthogonally oriented opposing short edges described below. In at least one implementation, upper edge **106** and lower edge **108** are separated by width w . In at least one implementation, width w ranges between

0.5 and 4 inches (e.g., approximately between 1 cm to 10 cm). Here, “upper” and “lower” in this context refer to a working orientation of binder dibble **100**, whereby upper edge **106** is generally oriented above lower edge **108** (relative to ground) when binder dibble **100** is in use. In at least one implementation, upper edge **106** may be oriented below lower edge **108**, for example, when binder dibble **100** is used to scrape soil into a furrow or hole to cover newly planted seeds.

[0030] In at least one implementation, shank **102** comprises a front edge **110** adjacent to tooth **104**, and an opposing rear edge **112**. In at least one implementation, front edge **110** and rear edge **112** extend orthogonally from upper edge **106** and lower edge **108**. In at least one implementation, shank **102** is elongated, having a length L extending between, for example, 3 and 14 inches (e.g. approximately 7.5 to 35 cm) between front edge **110** and rear edge **112**. Here, “front” and “rear” in this context refer to a working orientation of binder dibble **100**, whereby shank **102** is grasped behind tooth **104** so that tooth **104** may be struck against the ground to produce holes or dug into the soil and dragged toward the user. For reference purposes, tooth **104** is positioned at or near the front or head of implement (e.g., binder dibble **100**) for maximal ergonomic utility. In at least one implementation, binder dibble **100** has a length-to-width aspect ratio between 6:1 and 30:1.

[0031] In at least one implementation, upper edge **106** is joined to front edge **110** by and rear edge **112** by fillet **114** and fillet **116**, respectively. In at least one implementation, fillets **114** and **116** are round-shaped as approximately 90-degree circular arcs. In at least one implementation, fillets **114** and **116** have a radius of curvature ranging between 0.1 inch and 1 inch (e.g., approximately 2.5 mm to 25 mm). In at least one implementation, rear edge **112** is joined to lower edge **108** by a fillet **118**. In at least one implementation, fillet **118** also follows a circular arc having a radius of curvature ranging between 0.1 inch and 1 inch. In at least one implementation, lower edge **108** is joined to a trailing edge **120** of tooth **104** by a fillet **122**. In at least one implementation, fillet **122** has a circular or oval arc shape, having a radius of curvature ranging between 0.1 inch and 1 inch. In at least one implementation, leading edge **124** is joined to front edge **110** by fillet **126**. In at least one implementation, fillet **126** has a radius of curvature ranging between 0.1 and 1 inch. Rounded corners enable safe handling and storage of binder dibble **100**.

[0032] In at least one implementation, shank **102** comprises a front face **128**, where front face **128** is substantially rectangular. In at least one implementation, a plurality of rule marks **130** are distributed on front face **128** along length L of shank **102**. In at least one implementation, rule marks **130** have an extruded prismatic shape raised above front face **128**. For example, rule marks **130** extend above front face **128** by a height ranging between 0.01 inch to 0.03 inch (e.g., approximately 0.25 mm to 0.75 mm). In at least one implementation, rule marks **130** have a separation of approximately 1 inch along length L of shank **102**. In at least one implementation, a plurality of numerical indicators **132** are included to label individual rule marks **130** by distance in inches from front edge **110**. Numerical indicators **132** may enable use of shank **102** as a ruler. In at least one implementation, rule marks **130** may be used for measuring distances between seeds during planting.

[0033] In at least one implementation, tooth **104** comprises a plurality of depth marks **134** disposed at a regular interval in a stack. In at least one implementation, depth marks **134** also have an extruded prismatic shape raised above tooth **104** by a height ranging between 0.01 inch to 0.03 inch. In at least one implementation, depth marks **134** extend laterally partially across the width of tooth **104**. For example, depth marks **134** have a length of 0.25 inch, whereas tooth **104** has an expanding width ranging between 0.2 at the apex to 3 inches at the base. Partial extension of depth marks **134** may reduce accumulation of soil on tooth **104**, whereas full extension across the width of tooth **104** may encourage accumulation of soil. In at least one implementation, depth marks **134** are separated from one another by, for instance, 0.25 to 0.5 inch (e.g., approximately 6 mm to 12 mm). In at least one implementation, depth marks **134** aid estimation of fractional inches to produce precise hole or furrow depths.

[0034] In at least one implementation, shank **102** comprises two or more binder holes **136**. In at

least one implementation, shank **102** comprises three binder holes **136**. In at least one implementation, binder holes **136** are circular holes (e.g., binder hole **136A** having a diameter of 0.2 inch to 0.3 inch), or short, oval-shaped slots (e.g., binder holes **136B**) are separated by a distance d , symmetrical about center binder hole **136A**. In at least one implementation, d is approximately, for example, 4.25 inches to enable insertion of binder dibble **100** into a ring binder (e.g., standard dimensions for a three-ring binder sold in the U.S.). In at least one implementation, binder holes **136** may be dimensioned and spaced apart by other distances to accommodate other ring binder standards.

[0035] In at least one implementation, binder dibble **100** comprises a semiflexible polymeric material, such as polystyrene, high-density polyethylene or high-density polypropylene, Acrylonitrile Butadiene Styrene (ABS), polyimide (e.g., Nylon), polyethylene terephthalate (PET), or a polycarbonate composition, such as Makrolon **2407**. The polymer may be resistant to outdoor ultraviolet exposure and have sufficient mechanical strength to withstand repeated striking and digging in garden soil.

[0036] FIG. **1B** illustrates a profile view of the front edge of binder dibble **100**, in accordance with at least one implementation. In at least one implementation, binder dibble **100** has a thickness t between front face **128** and opposing rear face **138**. In at least one implementation, thickness t ranges between 0.1 and 0.5 inch. In at least one implementation, binder dibble **100** has a width-to-thickness aspect ratio between 5:1 and 40:1. In at least one implementation, apex **140** of tooth **104** is chamfered by a chamfer angle q . In at least one implementation, the chamfer may aid penetration of tooth **104** into soil. In at least one implementation, chamfer angle q ranges between 3 degrees and 10 degrees.

[0037] FIG. **2A** illustrates an enlarged plan view of tooth **104A**, in accordance with at least one implementation. Tooth **104A** has been substantially described in reference to tooth **104** in FIGS. **1A** and **1B**. In at least one implementation, tooth **104A** approximates an isosceles triangle, whereby leading edge **124** and trailing edge **120** are approximately the same length. In at least one implementation, tooth **104A** extends a height $h1$ from apex **140** to base **142**, whereby base **142** is colinear with lower edge **108** (see FIG. **1A**). In at least one implementation, height $h1$ ranges between 0.5 inch and 2 inches. In at least one implementation, tooth **104A** has a width $w1$ that may be measured from the top of leading edge **124** (e.g., at junction with fillet **126**) and the top of trailing edge **120** (e.g., at junction with fillet **122**). In at least one implementation, $w1$ ranges between 1 inch and 3 inches. In at least one implementation, angle p' of apex **140** is subtended by leading edge **124** and trailing edge **120**. In at least one implementation, angle p' is an acute angle that ranges from 15 degrees to 60 degrees. In at least one implementation, angle p' may be adjusted to blunt apex **140** for safety purposes yet have enough of a point to enable penetration of tooth **104A** into prepared garden soil with relatively low force as may be imparted by an elementary or middle school-aged student wielding binder dibble **100**.

[0038] FIG. **2B** illustrates an enlarged plan view of tooth **104B** in accordance with at least one implementation. In at least one implementation, tooth **104B** approximates a right triangle. In at least one implementation, leading edge **124** extends orthogonally (e.g., at a right angle) from base **142**, and trailing edge **120** extends at an oblique angle with respect to base **142**. In at least one implementation, angle p'' at apex **140** is subtended by leading edge **124** and trailing edge **120**. In at least one implementation, angle p'' ranges between 20 degrees and 60 degrees.

[0039] In at least one implementation, tooth **104B** extends a height $h2$ from base **142** to apex **140**. In at least one implementation, height $h2$ ranges from 0.5 inch to 2 inches. In at least one implementation, tooth **104B** has a width $w2$ extending the top of leading edge **124** to the top of trailing edge **120**. In at least one implementation, width $w2$ ranges from 1 inch to 3 inches.

[0040] FIG. **2C** illustrates an enlarged plan view of tooth **104C**, in accordance with at least one implementation. In at least one implementation, tooth **104C** approximates a scalene triangle. In at least one implementation, leading edge **124** and trailing edge **120** have different lengths and extend

at oblique angles from base **142**. In at least one implementation, tooth **104C** extends a height **h3** from base **142** to apex **140**. In at least one implementation, height **h3** ranges from 0.5 inch to 2 inches. In at least one implementation, tooth **104B** has a width **w3** extending the top of leading edge **124** to the top of trailing edge **120**. In at least one implementation, width **w3** ranges from 1 inch to 3 inches. The illustrated implementation shown in FIG. 2C shows tooth **104C** to have a wide base **142** whereby width **w3** is 2 inches to 3 inches. This is contrasted with tooth **104A** and tooth **104B**, where widths **w1** and **w2** are approximately 1 inch in the illustrated implementations. [0041] FIG. 3 illustrates a plan view of binder dibble **100** stowed in a three-ring binder **300**, in accordance with at least one implementation. In at least one implementation, binder holes **136** are aligned with clamp rings **302** in three-ring binder **300**. In at least one implementation, binder dibble **100** can be stowed in three-ring binder **300** by attaching clamp rings **302** through binder holes **136**. In at least one implementation, the flat geometry of binder dibble **100** enables stowage within three-ring binder **300** within a minimal space. Multiple binder dibbles may be stowed in a single three-ring binder. While a three-ring binder **300** is shown in FIG. 3, binder dibble **100** may be configured to accommodate two-ring binders as well.

[0042] FIG. 4 illustrates a view of binder dibble **100** in use to prepare for planting, in accordance with one implementation. In the illustrated implementation, binder dibble **100** is employed to create a furrow **400** in soil **402**. In at least one implementation, tooth **104** of binder dibble **100** is inserted into soil **402** and pulled through soil **402** toward the user to form furrow **400**. Tooth **104** may be inserted into soil **402** by a smashing or pounding action, for example, then dragged through soil **402**. In a similar manner, binder dibble **100** may form holes in soil **402** by poking tooth **104** into soil by a hammer action. Furrow creation using binder dibble **100** is explained in greater detail in reference to the method flowchart shown in FIG. 6.

[0043] FIG. 5 illustrates a view of binder dibble **100** in use to finish planting, in accordance with at least one implementation. In the illustrated implementation, binder dibble **100** is employed to cover a plurality of seeds **500** deposited in furrow **400**. In at least one implementation, binder dibble **100** is employed to scrape loose soil **502** into furrow **400**, covering deposited seeds **500**. Details

[0044] FIG. 6 illustrates flowchart **600** summarizing a method of using binder dibble **100**, in accordance with at least one implementation. Referring to FIG. 1A, at operation **602**, binder dibble **100** is grasped by shank **102** with hand of user behind front edge **110**. Tooth **104** protrudes below lower edge **108**. In at least one implementation, binder dibble **100** is held in a manner similar to grasping a hammer.

[0045] At operation **604**, tooth **104** of binder dibble **100** is inserted into garden soil (e.g., soil **402**). Garden soil may be prepared to be worked by binder dibble **100** by prior digging, plowing, or turning. By such preparation, garden soil may be soft. Tooth **104** may be inserted into the soil by a striking the soil with binder dibble **100** as one would use a hammer, firmly grasping shank **102** and driving tooth **104** into the soil to create a smash point (e.g., break) in the soil. Low striking force, such as that exerted by an elementary school or middle school student, may be sufficient to insert tooth **104** into the garden soil. The depth of penetration into the soil may be guided by depth marks **134** on tooth **104**. For example, depth marks **134** are spaced apart by increments of 0.25 inch. A depth of 0.5 inch may be achieved by sinking tooth **104** to the second depth mark on tooth **104**.

[0046] At operation **606**, tooth **104** may form a furrow (e.g., furrow **400**) in the soil. In at least one implementation, a pulling action may be employed by the user to drag tooth **104** a distance through the soil, for example, in a line by pulling tooth **104** toward the user, to create a rough furrow. In at least one implementation, a long edge of shank **102**, for example upper edge **106**, may be used to smooth over the worked soil so it is level prior to making the furrow. At operation **608**, seeds are deposited into the furrow. Rule marks along shank **102** may be used to gauge distance between seeds within a row containing the furrow. For example, shank **102** may be employed as a ruler, measuring distances of 3 inches using the rule marks to place seeds at regular 3-inch intervals in the furrow. For example, binder dibble **100** may be inverted to contact upper edge **106** to soil,

where shank **102** may be employed to scrape a mass of loose soil (e.g., loose soil **502**) into the furrow to cover newly deposited seeds and smooth the soil over the seeds. In at least one implementation, multiple furrows may be created in parallel by repeating the steps in operations **604** through **608**. In at least one implementation, rule marks **130** on shank **102** may be used to gauge distance between furrows (e.g., rows). For example, furrows may be created in parallel rows at 12-inch intervals using shank **102** to measure 12 inches.

[0047] In the following paragraphs, examples are provided that illustrate various implementations. Here, examples can be combined with other examples. As such, various implementations can be combined with other implementations without changing scope of disclosure.

[0048] Example 1 is a garden dibble, comprising a shank, wherein the shank is rectilinear and has a rectangular footprint and a rectangular cross section, wherein the shank has a length, a width and a thickness, wherein the thickness is between a first face of the shank and a second face of the shank opposite the first face, wherein the length is at least 6 times the thickness and the width is at least twice the thickness a plurality of rule marks on the first face of the shank, wherein the plurality of rule marks is distributed along the length of the shank at least two holes extending through the thickness of the shank between the first face and the second face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank, wherein the tooth is substantially triangular, wherein the tooth extends from a long edge of the shank and comprises an apex that is oriented orthogonally to a long axis of the shank, and wherein a plurality of depth marks is distributed on a third face of the tooth, and wherein the third face is substantially coplanar and contiguous with the first face.

[0049] Example 2 is an apparatus according to any example herein, in particular example 1, wherein the shank has a length to width aspect ratio that is between 6:1 and 30:1.

[0050] Example 3 is an apparatus according to any example herein, in particular example 1, wherein the shank has a width to thickness aspect ratio that is between 2:1 and 40:1.

[0051] Example 4 is an apparatus according to any example herein, in particular example 1, wherein the shank includes two opposing long edges and two opposing short edges, where the two opposing long edges extend along the length of the shank and the two opposing short edges extend along the width of the shank, wherein the two opposing long edges are joined to the two opposing short edges by a plurality of fillets, wherein individual fillets of the plurality of fillets extend between an individual long edge of the two opposing long edges and an individual short edge of the two opposing short edges, and wherein the individual fillets follow substantially circular arcs having a radius of curvature between 0.1 inch and 0.5 inch.

[0052] Example 5 is an apparatus according to any example herein, in particular example 4, wherein the tooth extends between one inch and two inches from a base of the tooth to the apex, and wherein the base is colinear with a first long edge of the two opposing long edges of the shank.

[0053] Example 6 is an apparatus according to any example herein, in particular example 5, wherein the base of the tooth extends between 0.5 inch and 3 inches.

[0054] Example 7 is an apparatus according to any example herein, in particular example 5, wherein the tooth comprises a leading edge and a trailing edge, and wherein the leading edge and the trailing edge extend at a first oblique angle and at a second oblique angle, respectively, from the base.

[0055] Example 8 is an apparatus according to any example herein, in particular example 7, wherein the leading edge extends at a right angle from the base.

[0056] Example 9 is an apparatus according to any example herein, in particular example 7, wherein the apex has an angle that is subtended by the leading edge and the trailing edge, and wherein the angle is between 30 degrees and 60 degrees.

[0057] Example 10 is an apparatus according to any example herein, in particular example 7, wherein the plurality of depth marks is distributed along the trailing edge of the tooth.

[0058] Example 11 is an apparatus according to any example herein, in particular example 5,

wherein the plurality of depth marks is distributed between the base and the apex of the tooth, wherein individual depth marks of the plurality of depth marks are separated by an incremental distance ranging between 0.1 and 0.5 inch.

[0059] Example 12 is an apparatus according to any example herein, in particular example 1, wherein individual depth marks of the plurality of depth marks extend partially across the third face of the tooth.

[0060] Example 13 is an apparatus according to any example herein, in particular example 1, wherein the apex of the tooth has a radius of curvature between 0.1 inch and 0.5 inch.

[0061] Example 14 is a garden dibble, comprising a shank, wherein the shank comprises a front face and a rear face, wherein the front face and the rear face are rectangular, a first long edge and an opposing second long edge, a first short edge and an opposing second short edge, wherein the first short edge and the opposing second short edge extend orthogonally between the first long edge and the opposing second long edge, wherein the shank has a length, a width and a thickness, wherein the thickness extends between the front face and the rear face; a plurality of rule marks on the front face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the front face and the rear face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank and is contiguous with the shank, wherein the tooth is substantially triangular, wherein the tooth extends from the opposing second long edge of the shank and comprises an apex that is oriented orthogonally to the opposing second long edge of the shank, and wherein a plurality of depth marks is distributed on a marked face of the tooth, and wherein the marked face is substantially coplanar and contiguous with the front face.

[0062] Example 15 is an apparatus according to any example herein, in particular example 14, wherein the at least two holes comprise three holes distributed along the length of the shank, wherein the at least two holes are adjacent to the first long edge of the shank, and wherein the at least two holes are configured to align to at least two clamp rings of a ring binder.

[0063] Example 16 is an apparatus according to any example herein, in particular example 15, wherein the three holes comprise a first hole, a second hole and a third hole, wherein the first hole is located within a first end portion of the shank, wherein the third hole is located within a second end portion of the shank, wherein the first end portion is opposite the second end portion, wherein the second hole is located in a center portion of the shank, and wherein the first hole and the third hole are oval-shaped and the second hole is circular.

[0064] Example 17 is an apparatus according to any example herein, in particular example 14, wherein the first long edge is joined to the first short edge by a first fillet and is joined to the opposing second short edge by a second fillet, wherein the first fillet and the second fillet follow circular arcs having a radius of curvature between 0.1 inch and 0.5 inch.

[0065] Example 18 is an apparatus according to any example herein, in particular example 14, wherein the opposing second long edge is joined to the opposing second short edge by a third fillet, wherein the third fillet follows a circular arc having a radius of curvature between 0.1 and 0.5 inch, and wherein the opposing second long edge is joined to the tooth by a fourth fillet, wherein the fourth fillet follows a circular arc or oval arc having a radius of curvature between 0.1 inch and 0.5 inch.

[0066] Example 19 is an apparatus according to any example herein, in particular example 14, wherein individual rule marks of the plurality of rule marks are separated by an incremental distance of one inch.

[0067] Example 20 is an apparatus according to any example herein, in particular example 14, wherein individual depth marks of the plurality of depth marks are separated by an incremental distance of 0.25 inch to 0.5 inch.

[0068] Example 21 is an apparatus according to any example herein, in particular example 14, wherein the shank and the tooth have a polycarbonate composition.

[0069] Example 22 is a method for using a garden dibble, wherein the garden dibble comprises a shank, wherein the shank comprises a front face and a rear face, wherein the front face and the rear face are rectangular, a first long edge and an opposing second long edge, a first short edge and an opposing second short edge, wherein the first short edge and the opposing second short edge extend orthogonally between the first long edge and the opposing second long edge, wherein the shank has a length, a width and a thickness, wherein the thickness extends between the front face and the rear face; a plurality of rule marks on the front face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the front face and the rear face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank, wherein the tooth is substantially triangular, wherein the tooth extends from the opposing second long edge of the shank and comprises an apex that is oriented orthogonally to the opposing second long edge of the shank, and wherein a plurality of depth marks is distributed on a marked face of the tooth, and wherein the marked face is substantially coplanar and contiguous with the front face, wherein the method comprises smoothing a portion of worked garden soil with the shank of the garden dibble; inserting the tooth into the portion of the garden soil; forming a furrow in the portion of the garden soil with the tooth; planting seeds in the furrow; and covering the furrow with the shank with the shank of the garden dibble.

[0070] Example 23 is a method according to any example herein, in particular example 22, wherein smoothing the portion of the garden soil with the shank of the garden dibble includes scraping the portion of the garden soil with the first long edge of the shank.

[0071] Example 24 is a method according to any example herein, in particular example 22, wherein forming the furrow in the portion of the garden soil with the tooth includes dragging the tooth a distance through the portion of the garden soil.

[0072] Example 25 is a method according to any example herein, in particular example 22, wherein covering the furrow with the shank includes inverting the garden dibble and scraping a mass of loose soil into the furrow with the first long edge of the shank.

[0073] Example 26 is a method according to any example here, in particular example 22, wherein the furrow is a first furrow in a first row, and wherein forming a furrow within the portion of the garden soil further includes forming a second furrow in a second row a distance from the first furrow in the first row, wherein the distance is gauged by measuring the distance with at least some of the plurality of rule marks on the shank.

[0074] Besides what is described herein, various modifications can be made to disclosed implementations and implementations thereof without departing from their scope. Therefore, illustrations of implementations herein should be construed as examples, and not restrictive to scope of present disclosure.

Claims

1. A garden dibble, comprising: a shank, wherein the shank is rectilinear and has a rectangular footprint and a rectangular cross section, wherein the shank has a length, a width and a thickness, wherein the thickness is between a first face of the shank and a second face of the shank opposite the first face, wherein the length is at least 6 times the thickness and the width is at least twice the thickness; a plurality of rule marks on the first face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the first face and the second face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank, wherein the tooth is substantially triangular, wherein the tooth extends from a long edge of the shank and comprises an apex that is oriented orthogonally to a long axis of the shank, and wherein a plurality of depth marks is distributed on a third face of the tooth, and wherein the third face is

substantially coplanar and contiguous with the first face.

2. The garden dibble of claim 1, wherein the shank has a length to width aspect ratio that is between 6:1 and 30:1.

3. The garden dibble of claim 1, wherein the shank has a width to thickness aspect ratio that is between 2:1 and 40:1.

4. The garden dibble of claim 1, wherein the shank includes two opposing long edges and two opposing short edges, where the two opposing long edges extend along the length of the shank and the two opposing short edges extend along the width of the shank, wherein the two opposing long edges are joined to the two opposing short edges by a plurality of fillets, wherein individual fillets of the plurality of fillets extend between an individual long edge of the two opposing long edges and an individual short edge of the two opposing short edges, and wherein the individual fillets follow substantially circular arcs having a radius of curvature between 0.1 inch and 0.5 inch.

5. The garden dibble of claim 4, wherein the tooth extends between one inch and two inches from a base of the tooth to the apex, and wherein the base is colinear with a first long edge of the two opposing long edges of the shank.

6. The garden dibble of claim 5, wherein the base of the tooth extends between 0.5 inch and 3 inches.

7. The garden dibble of claim 5, wherein the tooth comprises a leading edge and a trailing edge, and wherein the leading edge and the trailing edge extend at a first oblique angle and at a second oblique angle, respectively, from the base.

8. The garden dibble of claim 7, wherein the leading edge extends at a right angle from the base.

9. The garden dibble of claim 7, wherein the apex has an angle that is subtended by the leading edge and the trailing edge, and wherein the angle is between 30 degrees and 60 degrees and wherein the apex of the tooth has a radius of curvature between 0.1 inch and 0.5 inch.

10. The garden dibble of claim 7, wherein: the plurality of depth marks is distributed between the base and the apex of the tooth; individual depth marks of the plurality of depth marks are separated by an incremental distance ranging between 0.1 and 0.5 inch; individual depth marks of the plurality of depth marks extend partially across the third face of the tooth; and the plurality of depth marks is distributed along the trailing edge of the tooth.

11. A garden dibble, comprising: a shank, wherein the shank comprises a front face and a rear face, wherein the front face and the rear face are rectangular, a first long edge and an opposing second long edge, a first short edge and an opposing second short edge, wherein the first short edge and the opposing second short edge extend orthogonally between the first long edge and the opposing second long edge, wherein the shank has a length, a width and a thickness, wherein the thickness extends between the front face and the rear face; a plurality of rule marks on the front face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the front face and the rear face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank and is contiguous with the shank, wherein the tooth is substantially triangular, wherein the tooth extends from the opposing second long edge of the shank and comprises an apex that is oriented orthogonally to the opposing second long edge of the shank, and wherein a plurality of depth marks is distributed on a marked face of the tooth, and wherein the marked face is substantially coplanar and contiguous with the front face.

12. The garden dibble of claim 11, wherein the at least two holes comprise three holes comprising a first hole, a second hole and a third hole distributed along the length of the shank, wherein the first hole is located within a first end portion of the shank, wherein the third hole is located within a second end portion of the shank, wherein the first end portion is opposite the second end portion, wherein the second hole is located in a center portion of the shank wherein the first hole and the third hole are oval-shaped and the second hole is circular, and wherein the at least two holes are configured to align to at least two clamp rings of a ring binder.

- 13.** The garden dibble of claim 11, wherein: the first long edge is joined to the first short edge by a first fillet and is joined to the opposing second short edge by a second fillet, wherein the first fillet and the second fillet follow circular arcs having a radius of curvature between 0.1 inch and 0.5 inch; the opposing second long edge is joined to the opposing second short edge by a third fillet, wherein the third fillet follows a circular arc having a radius of curvature between 0.1 and 0.5 inch; and the opposing second long edge is joined to the tooth by a fourth fillet, wherein the fourth fillet follows a circular arc or oval arc having a radius of curvature between 0.1 inch and 0.5 inch.
- 14.** The garden dibble of claim 11, wherein individual rule marks of the plurality of rule marks are separated by an incremental distance of one inch, and wherein individual depth marks of the plurality of depth marks are separated by an incremental distance of 0.25 inch to 0.5 inch.
- 15.** The garden dibble of claim 11, wherein the shank and the tooth have a polycarbonate composition.
- 16.** A method for using a garden dibble, wherein the garden dibble comprises: a shank, wherein the shank comprises a front face and a rear face, wherein the front face and the rear face are rectangular, a first long edge and an opposing second long edge, a first short edge and an opposing second short edge, wherein the first short edge and the opposing second short edge extend orthogonally between the first long edge and the opposing second long edge, wherein the shank has a length, a width and a thickness, wherein the thickness extends between the front face and the rear face; a plurality of rule marks on the front face of the shank, wherein the plurality of rule marks is distributed along the length of the shank; at least two holes extending through the thickness of the shank between the front face and the rear face, wherein the at least two holes are distributed along the length of the shank; and a tooth that extends from an end of the shank, wherein the tooth is substantially triangular, wherein the tooth extends from the opposing second long edge of the shank and comprises an apex that is oriented orthogonally to the opposing second long edge of the shank, and wherein a plurality of depth marks is distributed on a marked face of the tooth, and wherein the marked face is substantially coplanar and contiguous with the front face, wherein the method comprises: smoothing a portion of a garden soil with the shank of the garden dibble; inserting the tooth into the portion of the garden soil; forming a furrow in the portion of the garden soil with the tooth; planting seeds in the furrow; and covering the furrow with the shank with the shank of the garden dibble.
- 17.** The method of claim 16, wherein smoothing the portion of the garden soil with the shank of the garden dibble includes scraping the portion of the garden soil with the first long edge of the shank.
- 18.** The method of claim 16, wherein forming the furrow in the portion of the garden soil with the tooth includes dragging the tooth a distance through the portion of the garden soil.
- 19.** The method of claim 16, wherein covering the furrow with the shank includes scraping a mass of loose soil into the furrow with the first long edge of the shank.
- 20.** The method of claim 16, wherein the furrow is a first furrow in a first row, and wherein forming the furrow within the portion of the garden soil further includes forming a second furrow in a second row a distance from the first furrow in the first row, wherein the distance is gauged by measuring the distance with at least some of the plurality of rule marks on the shank.
-