

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281011

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Chuang; Paul

WATERLESS TOILET

Abstract

A waterless toilet comprises: a base, a first roller, a second roller, two support brackets, two support plates, two cloth rolls having a plastic sheet respectively, a driver, a seat cushion bracket, and a toilet seat; wherein the plastic sheets of the two cloth rolls are laid on the two support plates, thus excrement from the toilet seat is captured completely; thereby human waste is collected without using water and small of collected human waste is prevented, furthermore, consumable costs of plastic sheet are saved.

Inventors: Chuang; Paul (Tainan City, TW)

Applicant: Chuang; Paul (Tainan City, TW)

Family ID: 96948170

Appl. No.: 18/596574

Filed: March 05, 2024

Publication Classification

Int. Cl.: A47K11/02 (20060101)

U.S. Cl.:

CPC A47K11/026 (20130101);

Background/Summary

FIELD OF THE INVENTION

[0001] The present invention relates to a waterless toilet, particularly to a waterless toilet having two plastic sheets, which catch excrement completely.

BACKGROUND OF THE INVENTION

[0002] Toilets today can not only collect human waste and prevent small of human waste with water but also facilitate cleaning, thus being very convenient. However, this kind of toilet requires a large amount of water. When used in public transportation, such as airplanes, transportation of required water causes great expenses.

[0003] To solve the problems mentioned above, the inventor disclosed a waterless toilet with a waterless sewage device and its structure, in patent applications Taiwan—U.S. Pat. No. 108120971, China—U.S. Pat. No. 201910567841.3, and U.S. Pat. No. 16,549,797, wherein plastic bags are mainly used to initially collected human waste and prevent from dispersing smell of human waste. However, plastic bags are not easy to install and need to be replaced frequently.

[0004] Regarding above points, the conventional method implies the above-mentioned problems. It is urgent to solve these problems. Therefore, the inventor began to think about the improvement of methods and devices.

SUMMARY OF THE INVENTION

[0005] The main object of the present invention is to provide a waterless toilet, wherein excrement is captured without using water and smell of collected human waste is prevented, furthermore, consumables costs of plastic cloth are saved.

[0006] For achieving above mentioned objects, the present invention comprises: a base having a frame on the top, wherein the frame is a rectangular structure consisting of a front rod, a back rod, a left rod and a right rod building up a penetration opening in the middle; a first roller pivoted between the front rod and the back rod, wherein the first roller has at least one recess; a second roller pivoted parallel to the first roller between the front rod and the back rod; when the recess of the first roller turns away the frame or the second roller, the frame opening is airtightly sealed by both the first roller and the second roller together; two support brackets set on the top of the frame; two support plates, wherein the first sides of the two support plates are set above the two support brackets, while the second sides of the two support plates oppositely extend inward and downward for a predetermined length and between the second sides of the two support plates there is a gap; two cloth rolls, set at both sides of the frame, holding a plastic sheet respectively, wherein the plastic sheets of the two cloth rolls are laid on the two support plates and pass through the gap between the two support plates, then pass through between the first roller and the second roller; a driver, to drive rotating the first roller and the second roller, then relatedly drive the plastic sheets of the two cloth rolls moving downward; a seat cushion bracket set on the base; a toilet seat set on the seat cushion bracket, wherein the toilet seat has a excretion opening in the middle.

[0007] Preferably, at the side of the recess of the first roller is provided at least one radial cushion set in the radial direction all around the surface of the first roller, to drive the plastic sheets surely moving downward.

[0008] Preferably, the second roller, correspondingly to the radial cushion of the first roller, has a radial cushion to drive the plastic sheets moving downward.

[0009] Preferably, at the side of the recess of the first roller is provided at least one radial cushion along the central axis of the first roller, thereby smell of human waste in the storage tank is reliably prevented.

[0010] Preferably, the second roller has a radial cushion, correspondingly to the radial cushion of the first roller, thereby smell of human waste is reliably prevented.

[0011] Preferably, the second roller has a recess, correspondingly to the recess of the first roller, for collecting human waste.

[0012] Other aspects and advantages of the present invention will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, illustrating by way of example the principles of the present invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0013] FIG. 1 is a perspective view of the first embodiment of the present invention.

[0014] FIG. 2 is an exploded view of the first embodiment of the present invention.

[0015] FIG. 3 is a schematic view of the frame and the storage tank of the present invention.

[0016] FIG. 4 is a schematic view of airtight closing the penetration opening of the frame with both the first roller and the second roller in the first embodiment of the present invention.

[0017] FIG. 5 is a schematic view of the two support plates in the first embodiment of the present invention.

[0018] FIG. 6 is a top view of the first roller in the first embodiment of the present invention.

[0019] FIG. 7 is a perspective view of the first roller in the first embodiment of the present invention.

[0020] FIG. 8 is a schematic view of rolling the first roller in the first embodiment of the present invention.

[0021] FIG. 9 is a schematic view of the two cloth rolls in the first embodiment of the present invention.

[0022] FIG. 10 is a perspective view of the first roller in the second embodiment of the present invention.

[0023] FIG. 11 is a perspective view of the first roller in the third embodiment of the present invention.

[0024] FIG. 12 is a schematic view of the second roller having recesses in the fourth embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0025] Each embodiment of the present invention will be described based on the drawings below. To make features easier to understand, features may be enlarged or exaggerated in the drawings, and the dimensional proportions of constituent elements may deviate from reality.

[0026] FIGS. 1-9 refer to the first embodiment of the present invention. As shown in FIGS. 1-9, a waterless toilet of the present invention comprises: a base 1, having a frame 2 on the top, wherein the frame is a rectangular structure consisting of a front rod 21, a back rod 22, a left rod 23 and a right rod 24 building up an penetration opening 25 in the middle; a first roller 3 pivoted between the front rod 21 and the back rod 22, wherein the first roller 3 has at least one recess 31; a second roller 4 pivoted parallel to the first roller 3 between the front rod 21 and the back rod 22, when the recess 31 of the first roller 3 turns away the frame 2 or the second roller 4, the penetration opening 25 of the frame 2 is airtightly sealed by both the first roller 3 and the second roller 4 together; two support brackets 5 set on the top of the frame 2; two support plates 6, wherein the first sides 61 of the two support plates 6 are set above the two support brackets 5, wherein the second sides 62 of the two support plates 6 oppositely extend inwardly and downwardly for a predetermined length and between the second sides 62 of the two support plates 6 there is a gap 63; two cloth rolls 7 set at both sides of the frame 1, holding a plastic sheet 71 respectively, wherein the plastic sheets 71 of the two cloth rolls 7 are laid on the two support plates 6 and pass through the gap 63 between the two support plates 6, then pass through between the first roller 3 and the second roller 4; a driver 8, to drive rotating the first roller 3 and the second roller 4 and relatedly drive the plastic sheets 71 of the two cloth rolls 7 to move downward; a seat cushion bracket 9 set on the base 1; a toilet seat 91 set on the seat cushion bracket 9, wherein the toilet seat has a excretion opening 911 in the middle; thereby, excrement is captured without using water and small of collected human waste is prevented, furthermore consumables costs of plastic cloth are saved. This will be explained in detail below.

[0027] As shown in FIGS. 2 and 3, a base 1 having a frame 2 on the top. The frame 2 is a

rectangular structure consisting of a front rod **21**, a back rod **22**, a left rod **23**, and a right rod **24** which build up a penetration opening **25** in the middle. The base **1** is used mainly for supporting the frame **2** and other components, besides, at the position of the base **1** under the penetration opening **25** of the frame **2** there is a detachable storage tank **11**, on the top of the storage tank **11** there is an opening **111** connecting the penetration opening **25** of the frame **2** to collect human waste for subsequent processing.

[0028] As shown in FIG. **4**, the first roller **3** and the second roller **4** are in parallel orientations pivoted between the front rod **21** and the back rod **22**. The first roller **3** has at least one recess **31**.

[0029] When the recess **31** of the first roller **3** turns away the frame **2** or the second roller **4**, the penetration opening **25** of the frame **2** is airtightly sealed by both the first roller **3** and the second roller **4** together, to prevent small of human waste in the storage tank **11**.

[0030] In the first embodiment, it is consisted mainly of the first roller **3** and the second roller **4** leaning inside the frame **2**, wherein the first roller **3** and the second roller **4** are leaning close together and interrupted through the plastic sheets **71**, thereby it is achieved that the penetration opening **25** of the frame **2** is airtightly sealed by both the first roller **3** and the second roller **4** together. Between the first roller **3** and the second roller **4** and the frame **2** there can also be a cushion or another airtight structure (not shown).

[0031] Around the opening **111** of the storage tank **11** can also be airtightly sealed with the frame **2** and furthermore, smell of human waste in the storage tank **11** is prevented. In particular, as shown in FIG. **3**, smell of human waste in the storage tank **11** can only disperse through the opening **111** passing the penetration opening **25** of the frame **2**, thus, as shown in FIG. **4**, when the frame **2** is airtightly sealed by both the first roller **3** and the second roller **4** together, it can reliably prevent small of human waste in the storage tank **11**.

[0032] As shown in FIGS. **6-8**, for plain explanation, here assumed the diameter direction **X** as the width direction of the recess **31** of the first roller **3**. The width **W1** of the recess **31** of the first roller **3** is less than the diameter **D1** of the first roller, so that the first roller **3** has at least two sealing sides **32** (in the FIG. **7**, the position of the sealing side **32** is shown as a grid). The two sealing sides **32** are the widest part of the first roller **3**, together with the second roller **4**, by which the penetration opening **25** of the frame **2** is airtightly sealed. Contrarily, when the first roller **3** is rotated so that the recess **31** of the first roller **3** faces to the second roller **4**, human waste can pass through the penetration opening **25** of the frame **2**. When the recess **31** of the first roller **3** turns away the frame **2** or the second roller **4**, the two sealing sides **32** of the first roller **3** lean against the second roller **4** and the frame **2** respectively, so that the penetration opening **25** of the frame **2** is airtightly sealed by both the first roller **3** and the second roller **4** together, thereby small of human waste in the storage tank **11** is prevented.

[0033] As shown in FIG. **5**, the gap **63** between the two support plates **6** is positioned corresponding to the upper part between the first roller **3** and the second roller **4**, thereby it is convenient to collect human waste.

[0034] As shown in FIG. **9**, the plastic sheets **71** of the cloth rolls **7** are laid on the two support plates **6** respectively, then pass through the gap **63** between the two support plates **6**, and further pass through between the first roller **3** and the second roller **4**. As shown in FIG. **8** there is no human waste yet, now the plastic sheets **71** are clamped by the first roller **3** and the second roller **4**, so they are in a tightened state. When human waste has fallen on the plastic sheets **71**, the cloth rolls **7** will be driven to rotate and more plastic sheets **71** will be stretched out, so that the plastic sheets **71** and human waste are collected in the recess **31** of the first roller **3**.

[0035] The plastic sheets **71** of the two cloth rolls **7** are shaped as sheets, as compared with conventional long strip bags, hence being easy to produce, saving costs. Besides, since the plastic sheet is easy to produce, it can be used even in a longer shape, which can increase the endurance of the cloth roll **7** and reduce the frequency of replacements of consumables such as the cloth sheets **7**. The plastic sheet **71** can be made of biodegradable materials to facilitate subsequent processing.

[0036] In each drawing, the dimensions of components such as the first roller **3**, the second roller **4**, and the storage tank **11** are shown for illustrative purposes. In practice, the size of the recess **31** of the first roller **3** will be larger than the amount of human waste generated once, and the capacity of the storage tank **11** may accommodate the entire cloth rolls **7** with the plastic sheets until it is used up.

[0037] The driver **8** can be a device powered by manual or pedal power, or an electric mechanism, such as a motor. In this embodiment, a structure with a manual rocker is taken as an example.

Therein, the driver **8** furthermore comprises: a first gear **81**, linked with the first roller **3**; a second gear **82**, linked with the second roller **4** and meshed with the first gear **81**; a rocker **83**, linked with the first gear **81**, wherein the first roller **3** is rotated to drive the second roller **4**, and by both the first roller **3** and the second roller **4** the plastic sheets **71** of the two cloth rolls **7** are clamped and driven to move downward.

[0038] The seat cushion bracket **9** is used to support the toilet seat **91**. In this case, the vertical upward area of the two support plates **6** is larger than the excretion opening **911** of the toilet seat **91**, so that the plastic sheets **71** laid on the support plates **6** can completely capture human waste falling from the excretion opening **911** of the toilet seat **91**. Besides, the height of the seat cushion bracket **9** is slightly higher than the second support bracket **5**, which means, without affecting the rotation of the cloth rolls **7**, keeping the bottom of the toilet seat **91** possibly close to the first sides **61** of the support plates **6**, to use the plastic sheets **71** on the support plates **6** to completely capture human waste falling from the excretion opening **911** of the toilet seat **91**.

[0039] As shown in FIG. **4**, when the penetration opening **25** of the frame **2** is airtightly sealed by both the first roller **3** and the second roller **4** together, smell of human waste in the storage tank **11** is prevented. As shown in FIG. **2** and FIG. **9**, when human waste has fallen from the excretion opening **911** of the toilet seat **91**, since the vertical upward area of the two support plates **6** is larger than the excretion opening **911** of the toilet seat **91**, even if human waste splashes downward and outward, it will be captured by the plastic sheets **71** on the support plates and will fall through the gap **63** between the two support plates **6** to the recess **31** of the first roller **3**. As shown in FIG. **8**, when human waste needs to be collected, the first roller **3** and the second roller **4** are rotated by the driver **8** for more than half a turn, until all human waste has fallen into the storage tank **11** completely, and then both the first roller **3** and the second roller **4** are returned to that, as shown in FIG. **4**, the penetration opening **25** of the frame **2** is airtightly sealed. Thereby, human waste can be collected without using water, and the costs of consumables such as plastic sheets can be saved.

[0040] FIG. **10** refers to the second embodiment of the present invention. As shown in FIG. **10**, next to the recess **31a** of the first roller **3a** there is at least one radial cushion **33a**. The radial cushion **33a** is arranged around the surface of the first roller **3a** along the diameter direction of the first roller **3a**. The radial cushion **33a** can cooperate with the first roller and the second roller to clamp the plastic sheets with a predetermined pressure, so that when the first roller and the second roller are rotated, the plastic sheets can be reliably driven to move downward.

[0041] FIG. **11** refers to the third embodiment of the present invention. As shown in FIG. **11**, next to the recess **31b** of the first roller **3b** there is at least one axial cushion **34b**, arranged on the surface of the first roller **3b** along the central axis of the first roller **3b**. The axial cushion **34b** is filled between the first roller and the second roller, when the penetration opening of the frame is airtightly sealed both the first roller and the second roller together, thereby smell of human waste in the storage tank is reliably prevented.

[0042] For achieving an effect of airtight sealing, the axial cushion **34b** is used together with the said radial cushion **33a**.

[0043] FIG. **12** refers to the fourth embodiment of the present invention. As shown in FIG. **12**, the second roller **4c** has a recess **41c** corresponding to the recess **31c** of the first roller **3c** to collect human waste. In addition, the second roller **4c** may also be set with a radial cushion **43c** and/or an axial cushion **44c** corresponding to the first roller **3c**.

Claims

1. A waterless toilet, comprises: A base, having a frame on the top, wherein the frame is a rectangular structure consisting of a front rod, a back rod, a left rod, and a right rod building up a penetration opening in the middle; a first roller, pivoted between the front rod, and the back rod; wherein the first roller has at least one recess; a second roller, pivoted parallel to the first roller between the front rod and the back rod, when the recess of the first roller turns away the frame or the second roller, the penetration opening of the frame is airtightly sealed by both the first roller and the second roller; two support brackets set on the top of the frame; two support plates, wherein the first sides of the two support plates are set above the two support brackets, wherein the second sides of the two support plates oppositely extend inwardly and downwardly for a predetermined length and between the second side of the two support plates there is a gap; two cloth rolls set at both sides of the frame; wherein the two cloth rolls hold a plastic cloth respectively, wherein the plastic sheets of the two cloth rolls are laid on the two support plates and pass through the gap between the two support plates, then pass through between the first roller and the second roller; a driver, to rotate the first roller and the second roller and drive the plastic sheets of the two cloth rolls to move downward; a seat cushion bracket set on the base; a toilet seat set on a seat cushion bracket; wherein the toilet seat has an excretion opening in the middle.
 2. The waterless toilet of claim 1, wherein next to the recess of the first roller is provided at least one radial cushion, arranged around the surface of the first roller along the diameter direction of the first roller.
 3. The waterless toilet of claim 2, wherein the second roller has a radial cushion corresponding to the radial cushion of the first roller.
 4. The waterless toilet of claim 1, wherein next to the recess of the first roller is provided at least one axial cushion, arranged on the surface of the first roller along the central axis of the first roller.
 5. The waterless toilet of claim 4, wherein the second roller has an axial cushion corresponding to the axial cushion of the first roller.
 6. The waterless toilet of claim 1, wherein the second roller has a recess corresponding to the recess of the first roller.
-