

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283424

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

TAKAOKA; Kazuya et al.

CONTROL DEVICE FOR INTERNAL COMBUSTION ENGINE

Abstract

A control device for an internal combustion engine includes a filter for collecting PM in an exhaust pipe connected to an engine body, and a PM regeneration function for regenerating the filter for collecting PM. The control device of the internal combustion engine includes a filter differential pressure acquisition unit that acquires a filter differential pressure, a pre-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit prior to regeneration of the filter, a pre-post regeneration differential pressure difference acquisition unit that acquires a pre-regeneration differential pressure difference that is a difference between a post-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit after regeneration of the filter, and a PM generation function determination unit that performs an anomaly determination of PM regeneration function when the acquired pre-regeneration differential pressure difference is equal to or less than a preset threshold.

Inventors: TAKAOKA; Kazuya (Tokyo, JP), OBUCHI; Tsuyoshi (Susono-shi, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Family ID: 1000008349511

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi, JP)

Appl. No.: 18/975532

Filed: December 10, 2024

Foreign Application Priority Data

JP 2024-035128

Mar. 07, 2024

Publication Classification

Int. Cl.: F01N9/00 (20060101); F01N11/00 (20060101)

CPC **F01N9/002** (20130101); **F01N11/002** (20130101); F01N2550/04 (20130101);
F01N2900/0601 (20130101); F01N2900/1406 (20130101); F01N2900/1411 (20130101);
F01N2900/1606 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Japanese Patent Application No. 2024-035128 filed on Mar. 7, 2024, incorporated herein by reference in its entirety.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to a control device for an internal combustion engine.

2. Description of Related Art

[0003] There has hitherto been known an internal combustion engine that includes a filter provided in an exhaust passage of the internal combustion engine to trap particulate matter (PM) in an exhaust gas. The filter that has trapped predetermined PM is subjected to a regeneration process. The filter is exposed to a high temperature during the regeneration process. As a result, the filter may be damaged or melted. Japanese Unexamined Patent Application Publication No. 2011-220233 (JP 2011-220233 A), for example, proposes determining the presence or absence of a failure of a filter based on the pressure difference between the upstream side and the downstream side of the filter in a state in which a regeneration process is completed.

SUMMARY

[0004] When an internal combustion engine has a PM regeneration function, it may be necessary to make an abnormality determination as to whether an abnormality is caused in the regeneration function. As a method of determining an abnormality in the regeneration function, it is conceivable to use the pressure difference between the upstream side and the downstream side of the filter as disclosed in JP 2011-220233 A. However, the pressure difference between the upstream side and the downstream side of the filter may be affected by variations in tolerance during manufacture of the filter or aging of the filter. When the pressure difference between the upstream side and the downstream side of the filter is affected by the variations in tolerance or the aging as described above, there is a possibility that an abnormality in the regeneration function is erroneously determined.

[0005] Thus, the disclosure disclosed in the present specification addresses an issue of avoiding erroneously determining an abnormality in the function to regenerate a filter.

[0006] An aspect of the present disclosure provides a control device for an internal combustion engine, in which [0007] an exhaust pipe connected to an engine body is provided with a filter that traps particulate matter (PM), the control device including a PM regeneration function to regenerate the filter that has trapped the PM. [0008] The control device for an internal combustion engine includes: a filter differential pressure acquisition unit that acquires a filter differential pressure that is a front-rear differential pressure of the filter; [0009] a pre-post regeneration differential pressure difference acquisition unit that acquires a pre-post regeneration differential pressure difference that is a difference between a pre-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit before regeneration of the filter and a post-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit after regeneration of the filter; and a PM generation function determination unit that determines an abnormality in the PM regeneration function when the pre-post regeneration differential pressure difference acquired

by the pre-post regeneration differential pressure difference acquisition unit is equal to or less than a threshold value set in advance.

[0010] In an aspect, the filter differential pressure acquisition unit may acquire the pre-regeneration filter differential pressure when a PM accumulation amount estimated by a PM accumulation amount estimation unit is equal to or more than a first predetermined value, and acquire the post-regeneration filter differential pressure when a PM accumulation amount estimated by the PM accumulation amount estimation unit after start of operation of the PM regeneration function is equal to or less than a second predetermined value that is less than the first predetermined value.

[0011] In an aspect, the control device for an internal combustion engine may further include a filter differential pressure correction unit including a volume flow rate calculation unit that calculates a volume flow rate at a time when the pre-regeneration filter differential pressure is acquired and a volume flow rate at a time when the post-regeneration filter differential pressure is acquired, the filter differential pressure correction unit correcting the pre-regeneration filter differential pressure and the post-regeneration filter differential pressure such that the volume flow rates calculated by the volume flow rate calculation unit have the same value; and [0012] the pre-post regeneration differential pressure difference acquisition unit may acquire a difference between the pre-regeneration filter differential pressure and the post-regeneration filter differential pressure corrected by the filter differential pressure correction unit.

[0013] In an aspect, the volume flow rate calculation unit may acquire the volume flow rate at the time of acquisition of the pre-regeneration filter differential pressure based on a temperature and a flow rate of a gas that has passed through the filter at the time of acquisition of the pre-regeneration filter differential pressure, and acquire the volume flow rate at the time of acquisition of the post-regeneration filter differential pressure based on a temperature and a flow rate of a gas that has passed through the filter at the time of acquisition of the post-regeneration filter differential pressure.

[0014] In an aspect, the pre-post regeneration differential pressure difference acquisition unit may acquire the pre-post regeneration differential pressure difference in a region in which the volume flow rate is equal to or more than a predetermined value.

[0015] According to the disclosure disclosed in the present specification, it is possible to avoid erroneously determining an abnormality in the function to regenerate a filter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] Features, advantages, and technical and industrial significance of exemplary embodiments of the disclosure will be described below with reference to the accompanying drawings, in which like signs denote like elements, and wherein:

[0017] FIG. 1A is a schematic view of an internal combustion engine incorporating a control device according to a first embodiment;

[0018] FIG. 1B is a functional block diagram of a control device according to a second embodiment;

[0019] FIG. 2A is a graph illustrating the relation among the filter differential pressure before regeneration, the filter differential pressure after regeneration, and the differential pressure before and after regeneration;

[0020] FIG. 2B is a diagram illustrating an abnormal determination of a PM regeneration function based on a differential pressure difference before and after regeneration;

[0021] FIG. 3 is a chart illustrating differences in pre-regeneration filter differential pressure and post-regeneration filter differential pressure due to aging of GPF;

[0022] FIG. 4 is a flowchart illustrating an example of control according to the first embodiment;

[0023] FIG. 5A is a graph illustrating the effect of the passing gas flow rate and the passing gas temperature on the filter differential pressure;

[0024] FIG. 5B is a graph illustrating the effect of volume flow rate on the differential pressure of filters;

[0025] FIG. 5C is a graph illustrating that the differential pressure before and after regeneration is obtained by the pre-regeneration filter differential pressure corrected so that the volume flow rate becomes the same value and the differential pressure after regeneration is obtained; and

[0026] FIG. 6 is a flowchart illustrating an example of control according to the second embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

[0027] Hereinafter, embodiments of the present disclosure will be described with reference to the accompanying drawings.

First Embodiment

Internal Combustion Engine

[0028] As illustrated in FIG. 1A, the internal combustion engine **100** includes an intake pipe **11** and an exhaust pipe **14** connected to the engine body **10**. The intake pipe **11** is provided with an airflow meter **12** and a throttle valve **13**. The throttle valve **13** is provided with a throttle valve opening degree sensor **13a**. The exhaust pipe **14** is provided with the first catalyst **15** and the second catalyst **16** in order from the side close to the engine body **10**. In addition, the internal combustion engine **100** includes an ECU (Electronic Control Unit) **50** that functions as a control device. The internal combustion engine **100** is mounted on a vehicle. The vehicles may be hybrid electric vehicle. In this case, the internal combustion engine **100** is combined with a motor or a battery (not shown) to form a hybrid system.

[0029] The engine body **10** in the present embodiment is a gasoline engine using gasoline as a fuel. Gasoline engines may generate PM by direct injection of fuel. The engine body **10** may be a diesel engine that uses light oil as a fuel. PM can also occur in diesel engines.

[0030] The airflow meter **12** detects an amount of intake air that flows through the intake pipe **11** and is fed to the engine body **10**. The throttle valve **13** adjusts an amount of intake air fed to the engine body **10**. The throttle valve opening degree sensor **13a** detects the opening degree of the throttle valve **13**.

[0031] The first catalyst **15** is a three-way catalyst. The first catalyst **15** generates heat during regeneration control of the second catalyst **16**. The temperature of the second catalyst **16** rises due to the heat generated by the first catalyst **15**. As the temperature of the second catalyst **16** rises, PM deposited on the second catalyst **16** burns out. Thus, the second catalyst **16** is regenerated.

[0032] The second catalyst **16** is GPF (Gasoline Particulate Filter). When the engine body **10** is a diesel engine, a DPF (Diesel Particulate Filter) is provided instead of GPF. GPF and DPF collect PM discharged from the body **10**. When clogging occurs due to the collected PM, PM collecting function of the second catalyst **16** is deteriorated. Therefore, the second catalyst **16** is subjected to a regeneration treatment under a predetermined condition.

[0033] A first pressure sensor **18a** is provided upstream of the second catalyst **16**. The first pressure sensor **18a** detects a pressure $P_{sub.upst}$ upstream of the second catalyst **16**. A second pressure sensor **18b** is provided downstream of the second catalyst **16**. The second pressure sensor **18b** detects a pressure $P_{sub.downst}$ downstream of the second catalyst **16**.

[0034] ECU **50** includes CPU (Central Processing Unit), RAM (Random Access Memory), ROM (Read Only Memory), and a storage device. ECU **50** executes a program stored in a ROM or a storage device to control the internal combustion engine **100**. Although not described here, a large number of sensors for controlling the internal combustion engine **100** are connected to ECU **50**.

[0035] ECU **50** functions as a PM regeneration control unit **51** and a PM accumulation amount estimation unit **52**. ECU **50** functions as a filter differential pressure acquisition unit **53**, a pre-regeneration filter differential pressure storage unit **54**, and a post-regeneration filter differential

pressure storage unit **55**. ECU **50** functions as a pre-post regeneration differential pressure difference acquisition unit **56** and a PM regeneration function determining unit **57**.

[0036] PM regeneration control unit **51** performs control for PM regeneration in the second catalyst **16**. PM reproduction control unit **51** may employ various conventionally known methods for PM reproduction. For example, PM regeneration control unit **51** can perform F/C (Fuel Cut) control or forcibly perform lean operation. Further, PM reproduction control unit **51** may instruct the driver to perform high-load operation for promoting PM reproduction, for example. When the engine body **10** is a diesel engine, PM regeneration control unit **51** may execute post injection.

[0037] PM accumulation amount estimation unit **52** estimates PM deposition amount in the second catalyst **16**. An airflow meter **12** and a throttle valve opening degree sensor **13a** are electrically connected to PM accumulation amount estimation unit **52**. PM accumulation amount estimation unit **52** estimates PM accumulation amount using an estimation model that uses the detected values of these sensors as parameters. The estimation model is created by an experiment or a simulation. PM accumulation amount estimation unit **52** can use a conventionally known estimator. Therefore, a detailed description of the estimation model is omitted in this specification. PM accumulation amount estimation unit **52** also estimates PM deposition amount after PM regeneration is performed. PM accumulation after PM regeneration is performed can be estimated based on, for example, the degree of progress of PM regeneration by PM regeneration control unit **51**.

[0038] The first pressure sensor **18a** and the second pressure sensor **18b** are electrically connected to the filter differential pressure acquisition unit **53**. The filter differential pressure acquisition unit **53** calculates the filter differential pressure by subtracting the pressure P.sub.upst at the downstream side of the second catalyst **16** detected by the second pressure sensor **18b** from the pressure P.sub.downst at the upstream side of the second catalyst **16** detected by the first pressure sensor **18a**. As illustrated in FIG. 2A, there are two types of filter differential pressures: a pre-regeneration filter differential pressure dP1 and a post-regeneration filter differential pressure dP2. The pre-regeneration filter differential pressure dP1 is a differential pressure obtained when a large amount of PM is deposited on the second catalyst **16** prior to PM regeneration. The post-regeneration filtered differential pressure dP2 is a differential pressure obtained after PM regeneration is performed and PM process proceeds.

[0039] The pre-regeneration filter differential pressure storage unit **54** stores pre-regeneration filter differential pressure dP1.

[0040] The post-regeneration filter differential pressure storage unit **55** stores the post-regeneration filter differential pressure dP2.

[0041] The pre-post regeneration differential pressure difference acquisition unit **56** acquires a pre-regeneration differential pressure difference ΔP . The pre-regeneration and post-regeneration differential pressure difference ΔP is a difference between the pre-regeneration filter differential pressure dP1 and the post-regeneration filter differential pressure dP2 as illustrated in FIG. 2A.

[0042] PM regeneration function determination unit **57** determines whether or not the pre-regeneration differential pressure difference ΔP is greater than a preset threshold P. PM regeneration function determination unit **57** determines that PM regeneration function is normal when the pre-regeneration differential pressure difference ΔP is greater than the threshold P, as illustrated in FIG. 2B. PM regeneration function determination unit **57** determines that PM regeneration function is abnormal when the pre-regeneration differential pressure difference ΔP is equal to or less than the threshold P. The threshold P is set in advance by an experiment or a simulation. The threshold P is set from the viewpoint of whether the differential pressure difference ΔP before and after regeneration according to the content of the executed PM regeneration control is obtained.

[0043] Here, referring to FIG. 3, an advantage of determining PM regeneration function using the differential pressure difference ΔP before and after regeneration will be described. In FIG. 3, the filter differential pressure in the second catalyst **16** of the vehicle having a small travel distance is

illustrated by a solid line. In FIG. 3, the filter differential pressure in the second catalyst **16** of the vehicle having a large travel distance is illustrated by a broken line. It is considered that the second catalyst **16** of the vehicle having a large travel distance is aged. The aging in the second catalyst **16** proceeds, for example, by the deposition of ash. The ash is, for example, a metal component contained in the fuel. Ash tends to accumulate with the accumulation of travel distances. Ash cannot be removed by PM regeneration. Therefore, even if PM regeneration function is normal, the differential pressure of the filters may be detected high.

[0044] As illustrated in FIG. 3, it is assumed that PM deposit in the second catalyst **16** prior to regeneration is 4 g. The pre-regeneration filter differential pressure $dP1'$ in a vehicle having a large travel distance is larger than the pre-regeneration filter differential pressure $dP1$ in a vehicle having a small travel distance. Further, it is assumed that the amount of PM deposited in the second catalyst **16** after regeneration is 2 g. The pre-regeneration filter differential pressure $dP1'$ in a vehicle having a large travel distance is larger than the pre-regeneration filter differential pressure $dP1$ in a vehicle having a small travel distance. Here, it is assumed that PM regeneration function is determined based on whether the filtered differential pressure after regeneration is greater than the threshold P' . In this case, since the post-regeneration filter differential pressure $dP2$ is smaller than the threshold P' , it is determined that PM regeneration function is normal. On the other hand, in vehicles having a large travel distance, since the post-regeneration filter differential pressure $dP2'$ is larger than the threshold P' , it is determined that PM regeneration function is abnormal. PM regeneration amount in a vehicle having a large travel distance is equal to PM regeneration amount in a vehicle having a small travel distance. In other words, there is a possibility that an erroneous determination is made that PM reproduction function in vehicles having a large traveling range is abnormal despite being normally performed. Such an erroneous determination may occur due to a product error (tolerance) that occurs when the second catalyst **16** is manufactured.

[0045] When the differential pressure difference ΔP before and after regeneration is compared with the threshold P as in the present embodiment, erroneous determination can be avoided.

PM Reproduction Function Determination

[0046] Referring to the flow chart illustrated in FIG. 4, PM reproduction function determination in the first embodiment will be described. FIGS. 2A and 2B are referred to as appropriate.

[0047] In S1, ECU **50** determines whether PM reproduction control unit **51** is performing PM reproduction control. This is because PM reproduction function cannot be determined during PM reproduction control. When a negative determination (No determination) is made in S1, ECU **50** proceeds to S2. ECU **50** repeats the process from S1 when an affirmative determination (Yes determination) is made in S1.

[0048] In S2, ECU **50** determines whether or not a first predetermined PM or more is deposited on the second catalyst **16** based on PM deposition amount estimated by PM accumulation amount estimation unit **52**. Specifically, ECU **50** determines whether the estimated PM deposit is in the pre-regeneration filter differential pressure detecting area shown in FIG. 2A. The pre-regeneration filter differential pressure detecting region is set as a region in which the pre-regeneration filter differential pressure $dP1$ that can calculate the pre-regeneration differential pressure ΔP used in PM regeneration function determination is detected. When an affirmative determination is made in S2, ECU **50** proceeds to S3. When a negative determination is made in S2, ECU **50** proceeds to S4.

[0049] In S3, the filter differential pressure acquisition unit **53** obtains the pre-regeneration filter differential pressure $dP1$. The obtained pre-regeneration filter differential pressure $dP1$ is stored in the pre-regeneration filter differential pressure storage unit **54**. After S3 process, ECU **50** repeats the process from S1.

[0050] In S4, ECU **50** determines, based on PM deposition amount estimated by PM accumulation amount estimation unit **52**, whether or not the regeneration of the second catalyst **16** has been completed until PM deposition amount is equal to or less than a second predetermined value. Specifically, ECU **50** determines whether the estimated PM deposit is in the post-regeneration

filtered differential pressure detecting area shown in FIG. 2A. The post-regeneration filter differential pressure detecting region is set as a region in which the post-regeneration filter differential pressure $dP2$ that can calculate the pre-regeneration differential pressure ΔP used in PM regeneration function determination is detected. When an affirmative determination is made in **S4**, ECU **50** proceeds to **S5**. When a negative determination is made in **S4**, ECU **50** repeats the process from **S1**.

[0051] In **S5**, ECU **50** determines whether the pre-regeneration filtered differential pressure $dP1$ has been acquired. If it is through **S3**, ECU **50** makes a positive determination. On the other hand, when **S3** is not passed, ECU **50** makes a negative determination. When an affirmative determination is made in **S5**, ECU **50** proceeds to **S6**. When a negative determination is made in **S5**, ECU **50** repeats the process from **S1**.

[0052] In **S6**, the filter differential pressure acquisition unit **53** obtains the post-regeneration filter differential pressure $dP2$. The obtained post-regeneration filter differential pressure $dP2$ is stored in the post-regeneration filter differential pressure storage unit **55**. ECU **50** proceeds to **S7** after **S6** process.

[0053] In **S7**, the pre-post regeneration differential pressure difference acquisition unit **56** acquires the pre-regeneration differential pressure difference ΔP . The pre-post regeneration differential pressure difference acquisition unit **56** subtracts the post-regeneration filter differential pressure $dP2$ stored in the post-regeneration filter differential pressure storage unit **55** from the pre-regeneration filter differential pressure $dP1$ stored in the pre-regeneration filter differential pressure storage unit **54**. ECU **50** proceeds to **S8** after **S7**.

[0054] In **S8**, PM regeneration function determination unit **57** determines whether or not the pre-regeneration differential pressure difference ΔP is greater than the threshold P . PM reproduction function determination unit **57** determines that **S8** is affirmative, the process proceeds to **S9**, and PM reproduction function is normal. ECU **50** repeats the process from **S1** after **S9**. PM reproduction function determination unit **57** determines that **S8** is negative, the process proceeds to **S10**, and PM reproduction function is abnormal. ECU **50** repeats the process from **S1** after **S10**. When ECU **50** determines that PM reproduction function is abnormal, an alert to that effect may be displayed.

Effect

[0055] According to the present embodiment, since the differential pressure difference ΔP before and after regeneration is compared with the threshold P , it is possible to avoid erroneous determination as to whether or not PM regeneration function is operating properly without being affected by aging or the like of the second catalyst **16**.

Second Embodiment

[0056] In the second embodiment, an ECU **150** exemplified in FIG. 1B is provided instead of ECU **50** in the first embodiment. ECU **150** functions as each unit included in ECU **50** and also functions as a filter differential pressure correction unit **58**. The filter differential pressure correction unit **58** includes a passing gas temperature acquisition unit **61**, a passing gas flow rate acquisition unit **60**, and a volume flow rate calculation unit **62**. Other configurations of the second embodiment are the same as those of the first embodiment.

[0057] FIG. 5A illustrates the effect of the passing gas flow rate and the passing gas temperature on the differential pressure of the filters. In FIG. 5A, the differential pressure of the filters when the flow rate of the passing gas is 30 g/s is plotted for each passing gas temperature. In FIG. 5A, the differential pressure of the filters when the flow rate of the passing gas is 40 g/s is plotted for each passing gas temperature. When the flow rate of the passing gas is 45 g/s, the differential pressure is plotted for each passing gas temperature. The filter differential pressure increases as the flow rate of the passing gas increases. The filter differential pressure increases as the passing gas temperature increases. Therefore, in the second embodiment, PM regeneration function determination is performed using the regeneration pre-and-post differential pressure difference $\Delta P_{sub.uni}$ in which

the effects of the passing gas flow rate and the passing gas temperature are taken into account. [0058] The horizontal axis of the plot illustrated in FIG. 5B is the volume flow rate V of the passing gases passing through the second catalyst **16**. In the graph in FIG. 5B, the values converted into the volume flow rates V are plotted for the respective gases for which the differential pressure of the filters is illustrated in FIG. 5A. By using the value converted into the volume flow rate V , the filter differential pressure can be compared under the same condition. That is, even if the passing gas flow rate and the passing gas temperature are different, it is possible to accurately determine PM regeneration function by using the filtered differential pressure corrected so that the volume flow rate V becomes the same value.

[0059] For conversion of each gas to the volume flow rate V , the following equation shown in [Equation 1] is used. The conversion to the volume flow rate V is performed by the volume flow rate calculation unit **62**. G_a in Equation 1 is the flow rate of the passing gases. The passing gas flow rate G_a is detected by the airflow meter **12**. The passing gas flow rate acquisition unit **60** acquires a detection value of the airflow meter **12**. G_f in Equation 1 is the fuel-injection quantity. ECU **50** holds the fuel-injection quantity. The volume flow rate calculation unit **62** calculates a material amount n of the passing gas flow rate G_a and the fuel-injection amount G_f . GPF interior temperature $th.sub.ci$ in Equation 1 is the interior temperature of the second catalyst **16**. The internal temperature of the second catalyst **16** corresponds to the passing gas temperature. GPF inner-temperature $th.sub.ci$ is obtained using a calculation model set in advance by experimentation or simulation. GPF inner temperature $th.sub.ci$ is acquired by the passing gas temperature acquisition unit **61**. The upstream pressure $P.sub.upst$ is a detected value of the first pressure sensor **18a**. The upstream pressure $P.sub.upst$ may be estimated from the passing gas flow rate G_a .

[0060] By converting to the volume flow rate V , gases with differing flow rates and temperatures can be plotted in a generally single straight line, as shown in FIG. 5B.

Volume flow rate $V = (\text{Material amount of } G_a \text{ and } G_f n) \times \text{Gas constant } R \times (GPF \text{ interior temperature } th.sub.ci) / \text{upstream pressure } P.sub.upst$ (Mathematical formula 1)

[0061] Referring to the flow chart illustrated in FIG. 6, PM reproduction function determination in the second embodiment will be described. However, in the following description, differences from the first embodiment will be described. The flowchart of the second embodiment illustrated in FIG. 6 is different from the first embodiment in the following points.

[0062] In a second embodiment, a **S1a** is performed between **S1** and **S2**. In the second embodiment, instead of **S3**, **S5** to **S8** in the first embodiment, **S8'** is performed from **S3'**, **S5'**.

[0063] In **S1a**, ECU **50** determines whether the internal combustion engine **100** is in an operating condition capable of detecting the differential pressure difference $\Delta P.sub.uni$. Specifically, ECU **50** determines whether the volume flow rate V falls within the differential pressure difference detecting area before and after regeneration, which is exemplified in FIG. 5C. When the volume flow rate V is small, it becomes difficult to detect the differential pressure difference $\Delta P.sub.uni$ before and after regeneration. Therefore, the pre-regeneration differential pressure difference detection area is set as a range in which the pre-regeneration differential pressure difference $\Delta P.sub.uni$ can be detected. When an affirmative determination is made in **S1a**, ECU **50** proceeds to **S2**. When a negative determination is made in **S1a**, ECU **50** repeats the process from **S1**.

[0064] In **S3'**, the filter differential pressure acquisition unit **53** obtains the pre-regeneration filter differential pressure $dP1.sub.uni$ corrected by the filter differential pressure correction unit **58**. The obtained pre-regeneration filter differential pressure $dP1.sub.uni$ is stored in the pre-regeneration filter differential pressure storage unit **54**. The acquired pre-regeneration filter differential pressure $dP1.sub.uni$ is stored in the pre-regeneration filter differential pressure storage unit **54**. The line segment **L1** shown in FIG. 5C is drawn by storing the data of the pre-regeneration filter differential pressure $dP1.sub.uni$. After the process of **S3'**, ECU **50** repeats the process from **S1**.

[0065] At **S5'**, ECU **50** determines whether the pre-regeneration filtered differential pressure

dP1.sub.uni has been acquired. When an affirmative determination is made in S5', ECU 50 proceeds to S6'. When a negative determination is made in S5', ECU 50 repeats the process from S1.

[0066] In S6', the filter differential pressure acquisition unit 53 obtains the post-regeneration filter differential pressure dP2.sub.uni corrected by the filter differential pressure correction unit 58. The obtained post-regeneration filter differential pressure dP2.sub.uni is stored in the post-regeneration filter differential pressure storage unit 55. The obtained data of the post-regeneration filter differential pressure dP2.sub.uni is stored in the post-regeneration filter differential pressure storage unit 55. After regeneration, the differential pressure dP2.sub.uni is accumulated, and thus the line segment L2 shown in FIG. 5C is drawn. After the process of S6', ECU 50 proceeds to S7'.

[0067] In S7', the pre-post regeneration differential pressure difference acquisition unit 56 obtains a pre-regeneration differential pressure difference ΔP .sub.uni. The pre-post regeneration differential pressure difference acquisition unit 56 extracts a combination of the pre-regeneration filter differential pressure dP1.sub.uni and the post-regeneration filter differential pressure dP2.sub.uni in which the volume flow rate V is the same from the line segment L1 and the line segment L2 in FIG. 5C. The combination of the pre-regeneration filter differential pressure dP1.sub.uni and the post-regeneration filter differential pressure dP2.sub.uni is extracted from the pre-regeneration differential pressure difference detecting area. The pre-post regeneration differential pressure difference acquisition unit 56 subtracts the post-regeneration filter differential pressure dP2.sub.uni from the extracted pre-regeneration filter differential pressure dP1.sub.uni. ECU 50 proceeds after S7' to S8'.

[0068] In S8', PM regeneration function determination unit 57 determines whether or not the pre-regeneration differential pressure difference ΔP .sub.uni is greater than the threshold P. Subsequent processing is the same as that of the first embodiment.

[0069] According to the present embodiment, it is possible to accurately determine PM regeneration function by using the filtered differential pressure corrected so that the volume flow rate V becomes the same value.

[0070] The above-described embodiments are merely examples for carrying out the present disclosure. The present disclosure is not limited thereto. Various modifications to these embodiments are within the scope of the present disclosure. Furthermore, it will be apparent from the above description that various other embodiments are possible within the scope of the present disclosure.

Claims

1. A control device for an internal combustion engine, in which an exhaust pipe connected to an engine body is provided with a filter that traps particulate matter (PM), the control device including a PM regeneration function to regenerate the filter that has trapped the PM, the control device comprising: a filter differential pressure acquisition unit that acquires a filter differential pressure that is a front-rear differential pressure of the filter; a pre-post regeneration differential pressure difference acquisition unit that acquires a pre-post regeneration differential pressure difference that is a difference between a pre-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit before regeneration of the filter and a post-regeneration filter differential pressure acquired by the filter differential pressure acquisition unit after regeneration of the filter; and a PM generation function determination unit that determines an abnormality in the PM regeneration function when the pre-post regeneration differential pressure difference acquired by the pre-post regeneration differential pressure difference acquisition unit is equal to or less than a threshold value set in advance.

2. The control device for an internal combustion engine according to claim 1, wherein the filter differential pressure acquisition unit acquires the pre-regeneration filter differential pressure when a

PM accumulation amount estimated by a PM accumulation amount estimation unit is equal to or more than a first predetermined value, and acquires the post-regeneration filter differential pressure when a PM accumulation amount estimated by the PM accumulation amount estimation unit after start of operation of the PM regeneration function is equal to or less than a second predetermined value that is less than the first predetermined value.

3. The control device for an internal combustion engine according to claim 1, further comprising a filter differential pressure correction unit including a volume flow rate calculation unit that calculates a volume flow rate at a time when the pre-regeneration filter differential pressure is acquired and a volume flow rate at a time when the post-regeneration filter differential pressure is acquired, the filter differential pressure correction unit correcting the pre-regeneration filter differential pressure and the post-regeneration filter differential pressure such that the volume flow rates calculated by the volume flow rate calculation unit have the same value, wherein the pre-post regeneration differential pressure difference acquisition unit acquires a difference between the pre-regeneration filter differential pressure and the post-regeneration filter differential pressure corrected by the filter differential pressure correction unit.

4. The control device for an internal combustion engine according to claim 3, wherein the volume flow rate calculation unit acquires the volume flow rate at the time of acquisition of the pre-regeneration filter differential pressure based on a temperature and a flow rate of a gas that has passed through the filter at the time of acquisition of the pre-regeneration filter differential pressure, and acquires the volume flow rate at the time of acquisition of the post-regeneration filter differential pressure based on a temperature and a flow rate of a gas that has passed through the filter at the time of acquisition of the post-regeneration filter differential pressure.

5. The control device for an internal combustion engine according to claim 3, wherein the pre-post regeneration differential pressure difference acquisition unit acquires the pre-post regeneration differential pressure difference in a region in which the volume flow rate is equal to or more than a predetermined value.
