

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286419

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ITASAKA; Naoki

ROTOR STRUCTURE

Abstract

A rotor structure that supplies an oil to a cooling target part inside a synchronous motor in which a rotor rotates in synchronization with a rotating magnetic field generated by a stator, being configured such that the rotor comprises a plurality of permanent magnets, which are one of the cooling target parts, and a cylindrical rotor core in which a plurality of axially extending magnet holes are formed in which the respective permanent magnets are embedded, and an oil flows axially inside the rotor core through the plurality of magnet holes.

Inventors: ITASAKA; Naoki (Hiroshima City, JP)

Applicant: MCF Electric Drive Corporation (Hiroshima City, Hiroshima, JP)

Family ID: 1000008309850

Appl. No.: 18/967048

Filed: December 03, 2024

Foreign Application Priority Data

JP 2024-033421

Mar. 05, 2024

Publication Classification

Int. Cl.: H02K1/32 (20060101); H02K1/276 (20220101); H02K1/30 (20060101); H02K7/00 (20060101); H02K9/193 (20060101)

U.S. Cl.:

CPC H02K1/32 (20130101); H02K1/276 (20130101); H02K1/30 (20130101); H02K7/003 (20130101); H02K9/193 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is based on Japanese Application No. 2024-33421 filed on Mar. 5, 2024, the contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to a rotor structure, and more particularly to a rotor structure for supplying an oil to a cooling target part inside a synchronous motor.

Background of the Disclosure

[0003] As electric vehicles become more widespread, there is a demand for the motors that drive them to be easier to install and more productive, easier to deploy in a wide range of vehicle models, and cheaper to manufacture, and to achieve these goals, there is a demand to reduce the size of the motor while maintaining its output, in other words, to increase the output density of the motor.

[0004] In order to increase the output density of a motor, it is unavoidable to increase the density of the current flowing through the stator coil, however, increasing the current density in a synchronous motor increases the amount of heat generated by the permanent magnets, causing the temperature of various parts inside the motor to rise, therefore, in some cases, this may lead to demagnetization of the permanent magnets and ultimately a decrease in motor torque.

[0005] Then, in order to cool permanent magnets inside a rotor core, for example, JP-A No. 2014-176235 discloses a rotor for a rotating electric machine in which a coolant flow passage extending in the axial direction is provided near the magnets housed in the rotor core.

[0006] In a motor, the rotor core itself generates heat, and in a configuration in which the cooling target part (permanent magnet) is cooled by a coolant (cooling oil) supplied to a coolant flow path provided near the cooling target part, as in the above-mentioned JP-A No. 2014-176235, the cooling oil may rise in temperature due to heat exchange with the rotor core before the cooling target part is cooled, which may result in insufficient cooling of the cooling target part. Therefore, the configuration in JP-A No. 2014-176235 leaves room for improvement in terms of efficient cooling of the cooling target part inside the motor.

[0007] The present invention has been made in consideration of the above-mentioned points, and an object of the present invention is to provide a rotor structure capable of efficiently cooling the cooling target part inside a synchronous motor.

SUMMARY

[0008] In order to achieve the above object, in a rotor structure according to the present invention, the permanent magnets embedded in the rotor are directly cooled by an oil.

[0009] Specifically, the present invention is directed to a rotor structure that supplies an oil to a cooling target part inside a synchronous motor in which a rotor rotates in synchronization with a rotating magnetic field generated by a stator.

[0010] This rotor structure is characterized by being configured such that: the rotor comprises a plurality of permanent magnets, which are one of the cooling target parts, and a cylindrical rotor core in which a plurality of axially extending magnet holes are formed in which the respective permanent magnets are embedded, and an oil flows axially inside the rotor core through the plurality of magnet holes.

[0011] According to this configuration, an oil flows axially inside the rotor core through the magnet holes in which the permanent magnets are embedded, and the oil can directly cool the permanent magnets, which are one of the cooling target parts. This makes it possible to cool the permanent magnets, which are one of the cooling target parts, more efficiently than, for example, a structure in which an oil flows in holes (oil passages) provided near the permanent magnets in the rotor core.

[0012] By the way, when an oil is sent to the rotor, it is common to send the oil from an oil passage provided in the rotor shaft, but if a configuration is adopted in which the oil passage in the rotor shaft is directly connected to the magnet holes, it is assumed that there will be variations in the amount of an oil supplied to the magnet holes. If such variations in the amount of an oil occur, some of the multiple permanent magnets embedded in the rotor core will not be sufficiently cooled, and some of the permanent magnets may be demagnetized, resulting in a decrease in torque.

[0013] Therefore, the rotor structure described above may be configured such that: the rotor further comprises a rotor shaft that is inserted into the rotor core so as not to rotate relative to the rotor core, and an annular one-side end plate that is attached concentrically with an axis center of the rotor core to the end on one axial side of the rotor core, the one-side end plate has a chamber space formed having an annular shape as viewed in the axial direction concentrically with the axis center of the rotor core, and at the one-side end plate, an oil is filled into the chamber space from an oil passage in the rotor shaft and the oil is distributed from the chamber space to the plurality of magnet holes.

[0014] According to this configuration, rather than sending an oil directly from the oil passage in the rotor shaft to the magnet holes, the oil is first filled into the chamber space formed in the one-side end plate, and then the oil is distributed from the annular chamber space to the plurality of magnet holes, allowing the oil to be evenly supplied to the plurality of magnet holes formed in the rotor core.

[0015] In addition, the oil distributed to the magnet hole is only filled into the chamber space once, and is supplied to the magnet hole in a sufficiently cooled state, rather than after cooling the rotor core, etc. (raising the temperature), so that the oil can effectively cool the permanent magnets.

[0016] As a result, it is possible to prevent some of the permanent magnets from being cooled insufficiently, and therefore it is possible to reliably prevent the permanent magnets from being demagnetized, and ultimately, to prevent a decrease in torque.

[0017] Furthermore, in the rotor structure described above, it may be permissible that the one-side end plate has a plurality of radial oil passages formed that extend radially on an other axial side than the chamber space, whose radially inner end communicates with the chamber space, and whose radially outer end communicates with a plurality of the magnet holes, and in each of the radial oil passages, a surface that defines the radial oil passage on one axial side and a surface that defines the radial oil passage on the radially outer side are connected in an R-shape when viewed in a circumferential direction.

[0018] According to this configuration, a plurality of radial oil passages are formed, extending radially on the other axial side than the chamber space (the side closer to the rotor core), with their radially inner ends communicating with the chamber space and their radially outer ends communicating with the plurality of magnet holes, therefore, the oil filled in the chamber space can be evenly distributed to the plurality of magnet holes through these multiple radial oil passages.

[0019] Here, an oil flows radially outward in the radial oil passage, while flows axially when supplied to the magnet hole, and in a structure in which if a surface that defines the radial oil passage on one axial side (referred to as the “first defining surface”) and a surface that defines the radial oil passage on the radially outer side (referred to as the “second defining surface”) are perpendicular to each other, it is also assumed that the oil will not change direction smoothly. In addition, during motor operation when the need for cooling is high, the rotor is constantly rotating and centrifugal force acts on the oil, so the oil that flows radially in the radial oil passage is easily pressed against the second defining surface, and it is assumed that in a structure in which the first defining surface and the second defining surface are perpendicular to each other, it will be even more difficult for the oil to change direction.

[0020] In this regard, the first defining surface and the second defining surface are connected in an R-shape when viewed in the circumferential direction, in this configuration, so that when the oil that flows radially outward through the radial oil passage under centrifugal force is supplied to the

magnet hole, a smooth change of direction in the axial direction can be achieved, thereby making it possible to more efficiently cool the permanent magnet, which is the cooling target part.

[0021] Furthermore, in the rotor structure described above, it may be permissible that the one-side end plate has a plurality of radial oil passages formed that extend radially on an other axial side than the chamber space, whose radially inner end communicates with the chamber space, and whose radially outer end communicates with a plurality of the magnet holes, and the radially outer end of each of the radial oil passages is in communication with a radially inner portion of each of the magnet holes.

[0022] As described above, during motor operation when the need for cooling is high, the rotor is constantly rotating and centrifugal force acts on the oil, so that the oil flowing axially inside the magnet hole also tends to collect in the radially outer part of the magnet hole. For this reason, if the radially outer end of the radial oil passage is connected to the radially outer part of the magnet hole where the oil collects, it is assumed that the oil will not be able to be smoothly introduced into the magnet hole.

[0023] In this regard, the radially outer end of the radial oil passage is connected to the radially inner portion of each magnet hole, in other words, connected to the portion of the magnet hole where an oil is less likely to collect, in this configuration, so that an oil can be smoothly introduced from the radial oil passage into the magnet hole, thereby making it possible to more efficiently cool the permanent magnet, which is the cooling target part.

[0024] Furthermore, in the rotor structure described above, it may be permissible that the one-side end plate is disposed so as to overlap, as viewed in a radial direction, a coil end on one axial side, which is one of the cooling target parts, of a stator coil attached to the stator, the one-side end plate has a plurality of first diffusion oil passages formed that extend radially on one axial side than the chamber space, whose radially inner end communicates with the chamber space, and that open on an outer peripheral surface of the one-side end plate, and each of the first diffusion oil passages is formed so that its cross-sectional area increases toward the radially outer side.

[0025] According to this configuration, a plurality of first diffusion oil passages are formed, which extend radially on one axial side than the chamber space (the opposite side of the rotor core across the chamber space), have radially inner ends communicating with the chamber space, and open on the outer circumferential surface of the one-side end plate, so that a portion of the oil filled in the chamber space can be scattered radially outward from the outer circumferential surface of the one-side end plate by centrifugal force through the plurality of first diffusion oil passages. Thus, the one-side end plate in which the first diffusion oil passages are formed is arranged so as to overlap the coil end on one axial side when viewed in the radial direction, so that the coil end on one axial side, which is one of the cooling target parts, can be cooled.

[0026] In addition, the oil that is scattered to the coil end, like the oil distributed to the magnet hole, is simply filled into the chamber space once, and is supplied to the coil ends in a sufficiently cooled state, rather than after cooling the rotor core, etc. (raising the temperature), so that not only the permanent magnet but also the coil end can be cooled efficiently.

[0027] Here, if the first diffusion oil passage is clogged with an oil, negative pressure would be generated within the first diffusion oil passage, which would impair the uniformity of the oil within the chamber space and hinder the even distribution of the oil to the plurality of magnet holes. In this regard, the first diffusion oil passage is formed so that the cross-sectional area increases as it goes radially outward, in this configuration, hence, it is possible to prevent the first diffusion oil passage from becoming clogged with an oil, and thereby making it possible to maintain efficient cooling of the permanent magnets while cooling the coil end.

[0028] Furthermore, in the rotor structure described above, it may be permissible that the rotor further comprises an annular other-side end plate attached concentric with the axis center of the rotor core to the end on an other axial side of the rotor core, the other-side end plate is disposed so as to overlap, as viewed in a radial direction, the coil end on the other axial side, which is one of

the cooling target parts, of the stator coil, the other-side end plate has a plurality of second diffusion oil passages formed that extend radially, whose radially inner end communicates with a plurality of the magnet holes, that open on the outer peripheral surface of the other end plate, and whose cross-sectional area increases toward the radially outer side, and a number of the second diffusion oil passages is set to be greater than a number of the first diffusion oil passages.

[0029] According to this configuration, as in the case of the first diffusion oil passage described above, it is possible to cool the coil end on the other axial side, which is one of the cooling target parts. Also, like the first diffusion oil passage, the second diffusion oil passage is formed so that the cross-sectional area increases as it goes radially outward, so that it is possible to prevent the second diffusion oil passage from being blocked by an oil, and thus it is possible to prevent the occurrence of a phenomenon in which even distribution of an oil is impaired by an increase in the amount of an oil flowing through the magnet hole communicating with the second diffusion oil passage where negative pressure is generated.

[0030] Unlike the coil ends on one axial side, the coil end on the other axial side is supplied with an oil after cooling the rotor core, etc. (temperature-raised to a certain extent), but since the number of the second diffusion oil passages is set to be greater than the number of the first diffusion oil passages (so that the amount of an oil supplied to the coil end on the other axial side is relatively greater), hence, the coil end on the other axial side can also be cooled efficiently.

[0031] In the rotor structure described above, the rotor core may have a skew angle of 0 degrees.

[0032] According to this configuration, by making the rotor core so-called skewless, the flow passage resistance to the oil flowing inside the magnet hole can be reduced, thereby making it possible to more efficiently cool the permanent magnets, which are the cooling target parts.

Advantageous Effect of the Invention

[0033] As described above, the rotor structure according to the present invention can efficiently cool the cooling target parts inside a synchronous motor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] FIG. 1 is a vertical sectional view schematically showing the outline of a synchronous motor according to an embodiment of the present invention.

[0035] FIG. 2 is a block diagram schematically illustrating an example of a cooling system in an electric vehicle.

[0036] FIG. 3 is a perspective view schematically showing a space in a rotor through which an oil flows.

[0037] FIG. 4 is a perspective view schematically illustrating the direction of an oil flowing in a rotor.

[0038] FIG. 5A is a perspective view schematically showing an oil introduction section.

[0039] FIG. 5B is a view showing the surface of the oil introduction section on the output axis side.

[0040] FIG. 5C is a sectional arrow view taken along the line c-c in FIG. 5A.

[0041] FIG. 6A is a perspective view schematically showing a main part of a shaft main body.

[0042] FIG. 6B is a sectional arrow view taken along the line b-b in FIG. 6A.

[0043] FIG. 6C is a sectional arrow view taken along the line c-c in FIG. 6A.

[0044] FIG. 7A is a perspective view schematically showing a main part of the shaft main body of a rotor shaft.

[0045] FIG. 7B is a sectional arrow view taken along the line b-b in FIG. 7A.

[0046] FIG. 7C is a sectional arrow view taken along the line c-c in FIG. 7A.

[0047] FIG. 7D is a perspective view showing the flow of an oil in the rotor shaft.

[0048] FIG. 8A is an overall cross-sectional view schematically showing a rotor core and a

permanent magnet.

[0049] FIG. **8B** is an enlarged view of the magnetic pole divided by the dashed lines in FIG. **8A**.

[0050] FIG. **9A** is a view schematically showing the surface of a second end plate on the anti-output axis side.

[0051] FIG. **9B** is a sectional arrow view taken along the line b-b in FIG. **9A** and FIG. **9C**.

[0052] FIG. **9C** is a view schematically showing the surface of the second end plate on the output axis side.

[0053] FIG. **9D** is a perspective view schematically showing a first diffusion groove.

[0054] FIG. **9E** is a perspective view schematically showing an annular groove and a connecting groove.

[0055] FIG. **10A** is a view schematically showing the surface of a third end plate on the anti-output axis side.

[0056] FIG. **10B** is a sectional arrow view taken along the line b-b in FIG. **10A** and FIG. **10C**.

[0057] FIG. **10C** is a view schematically showing the surface of the third end plate on the output axis side.

[0058] FIG. **10D** is a perspective view schematically showing an annular groove and a connecting groove.

[0059] FIG. **10E** is a perspective view schematically showing a first radial groove and a second radial groove.

[0060] FIG. **11A** is a cross-sectional view schematically showing a state where the second and the third end plate are stacked.

[0061] FIG. **11B** is a perspective view schematically showing a space formed by stacking the second and third end plates.

[0062] FIG. **11C** is a cross-sectional view schematically showing a state where the rotor shaft and the second and third end plates are combined.

[0063] FIG. **11D** is a perspective view schematically showing a state where the rotor shaft and the second and third end plates are combined.

[0064] FIG. **11E** is a perspective view schematically showing the flow of an oil in the rotor shaft and the second and third end plates.

[0065] FIG. **12A** is a cross-sectional view schematically showing a state in which the first end plate and the second end plate are stacked.

[0066] FIG. **12B** is a perspective view schematically showing a space formed by stacking the first and second end plates.

[0067] FIG. **12C** is a perspective view schematically showing the flow of an oil in the rotor shaft and the first to third end plates.

[0068] FIG. **13A** is a partial perspective view schematically showing a state in which a third end plate is attached to the end surface on the anti-output axis side of a rotor core.

[0069] FIG. **13B** is a sectional arrow view taken along the line b-b in FIG. **13A**.

[0070] FIG. **13C** is a sectional arrow view taken along the line c-c in FIG. **13A**.

[0071] FIG. **13D** is a perspective view schematically showing the flow of an oil in the first to third end plates and in the rotor core.

[0072] FIG. **14A** is a cross-sectional view schematically showing a main portion of a rotor core.

[0073] FIG. **14B** is a cross-sectional view schematically showing a state where centrifugal force acts on the oil shown in FIG. **14A**.

[0074] FIG. **15A** is a perspective view schematically showing a radial oil passage.

[0075] FIG. **15B** is a perspective view schematically showing a radial oil passage.

[0076] FIG. **16A** is a view schematically showing the surface of a fourth end plate on the anti-output axis side.

[0077] FIG. **16B** is a sectional arrow view taken along the line b-b in FIG. **16A** and FIG. **16C**.

[0078] FIG. **16C** is a view schematically showing the surface of the fourth end plate on the output

axis side.

[0079] FIG. **17A** is a view schematically showing the surface of a fifth end plate on the anti-output axis side.

[0080] FIG. **17B** is a perspective view schematically showing second diffusion grooves.

[0081] FIG. **18A** is a partial perspective view schematically showing a state in which the fourth end plate and the fifth end plate are overlapped.

[0082] FIG. **18B** is a perspective view schematically showing a space formed by overlapping the fourth and fifth end plates.

[0083] FIG. **18C** is a cross-sectional view schematically showing a state in which the fourth and fifth end plates are attached to the rotor core, which correspond to the sectional arrow view taken along the line c-c in FIG. **18A**.

[0084] FIG. **18D** is a cross-sectional view schematically showing a state in which the fourth and fifth end plates are attached to the rotor core, which correspond to the sectional arrow view taken along the line d-d in FIG. **18A**.

[0085] FIG. **18E** is a perspective view schematically showing the flow of an oil in the rotor core and the fourth and fifth end plates.

[0086] FIG. **19** is a perspective view schematically showing outer and inner through holes.

[0087] FIG. **20A** is a view schematically illustrating an example of an oil passage according to another embodiment.

[0088] FIG. **20B** is a view schematically illustrating an example of an oil passage according to another embodiment.

[0089] FIG. **20C** is a view schematically illustrating an example of an oil passage according to another embodiment.

[0090] FIG. **21** is a perspective view schematically showing a rotor core according to another embodiment of the present invention.

DETAILED DESCRIPTION

[0091] Hereinafter, embodiments of the present invention will be described with reference to the drawings.

-Motor Overview-

[0092] FIG. **1** is a vertical cross-sectional view schematically showing the overview of a synchronous motor **1** according to this embodiment. In FIG. **1**, the symbol AC indicates the axis center of the synchronous motor **1**, the symbol OS indicates an output axis side (the other axial side), and the symbol AOS indicates an anti-output axis side (one axial side), respectively. In FIG. **1**, with respect to the stator **90**, in order to make the drawing easier to see, a detailed cross section of a stator core **91** is not shown, and only the outer shape of the stator core **91** and coil ends **93a**, **93b** of a stator coil **93** attached to the stator core **91** are shown.

[0093] The synchronous motor **1** according to this embodiment is mounted, for example, on an electric vehicle, and as shown in FIG. **1**, comprises a rotor **10** having a rotor core **30** with a rotor shaft **20** passing through the center, and a stator **90** having a stator core **91** arranged to surround the outer periphery of the rotor core **30**, and is configured so that the rotor **10** rotates in synchronization with the rotating magnetic field generated by the stator **90**.

[0094] The rotor shaft **20** has an oil introduction section **21** and a shaft main body **27**, and an oil introduction passage **20a** through which an oil flows is formed therein. In addition to the rotor shaft **20** and the rotor core **30**, the rotor **10** has permanent magnets **101**, **102**, **103**, **106** (see FIG. **3**, etc.) embedded in magnet holes **31** (see FIG. **8A** and FIG. **8B**) formed in the rotor core **30**, and first to fifth end plates **40**, **50**, **60**, **70**, **80** attached to the ends of the rotor core **30** in the axial direction (the direction in which the axis AC extends). Note that FIG. **1** merely shows an outline of the synchronous motor **1**, and since emphasis is placed on ease of understanding, the circumferential positions of the components in the rotor **10** are not necessarily consistently aligned.

-Cooling System-

[0095] FIG. 2 is a block diagram schematically illustrating an example of a cooling system 2 in an electric vehicle. As shown in FIG. 2, the cooling system 2 includes an inverter cooling system 3 and a motor cooling system 4, and a heat exchanger 8 is interposed between the inverter cooling system 3 and the motor cooling system 4.

[0096] The inverter cooling system 3 has a circulation path 3a through which the cooling water circulates, and an inverter 5, a radiator 6, and a water pump 7 for circulating the cooling water, each of which is provided on the circulation path 3a. In the inverter cooling system 3, heat generated by the inverter 5 is absorbed by the cooling water, and the heat absorbed by the cooling water is dissipated to the outside by the radiator 6, thereby maintaining the cooling water and the inverter 5 at low temperatures.

[0097] On the other hand, the motor cooling system 4 has a circulation path 4a through which an oil circulates, and the motor 1 and an oil pump 9 that pumps an oil to an oil introduction section 21 of a rotor shaft 20, each of which is provided on the circulation path 4a. In this motor cooling system 4, heat generated in the synchronous motor 1 is absorbed by the oil, and the oil that has absorbed the heat accumulates at the bottom of a motor housing (not shown) and then returns to the circulation path 4a. In this motor cooling system 4, the heat absorbed by the oil is absorbed by the cooling water through indirect heat exchange between the circulation paths 3a and 4a in the heat exchanger 8, and then dissipated to the outside by the radiator 6, thereby maintaining the oil at a relatively low temperature.

[0098] In this embodiment, the cooling system 2 configured as described above allows an oil maintained at a relatively low temperature (for convenience, also referred to as “fresh oil”) to be sent to the oil introduction section 21 of the rotor shaft 20.

-Outline of Rotor Structure-

[0099] FIG. 3 is a perspective view schematically showing a space in the rotor 10 through which an oil flows, and FIG. 4 is a perspective view schematically illustrating a direction in which an oil flows in the rotor 10. In the rotor structure employed in this embodiment, a fresh oil sent to the oil introduction section 21 of the rotor shaft 20 as described above is appropriately distributed in the second and third end plates 50, 60 and is supplied directly to the gaps 31a in the magnet holes 31 in which the permanent magnets 101, 102, - - -, which are one of the cooling target parts inside the synchronous motor 1, are embedded, as shown by the thick arrow in FIG. 1, so that the permanent magnets 101, 102, - - - are efficiently cooled.

[0100] Similarly, a fresh oil is supplied directly also to the coil end 93a on the axially anti-output axis side AOS (hereinafter simply referred to as the “anti-output axis side AOS”), which is one of the cooling target parts, so that the coil end 93a is efficiently cooled. Furthermore, in this rotor structure, the coil end 93b on the axially output axis side OS (hereinafter simply referred to as the “output axis side OS”), which is one of the cooling target parts, is also efficiently cooled by the oil although after cooling the permanent magnets 101, 102, - - -.

[0101] More specifically, in the rotor structure of this embodiment, a space S through which an oil flows is formed inside the rotor shaft 20, the rotor core 30, and the first to fifth end plates 40, 50, - - -, as shown by hatching in FIG. 3. As a result, in this rotor structure, as shown by the thick arrows in FIG. 4, an oil flows circumferentially, radially, and axially, in other words, three-dimensionally, inside the rotor shaft 20, the rotor core 30, and the first to fifth end plates 40, 50, - - -, and is supplied to the cooling target part.

[0102] The rotor structure that enables such a three-dimensional oil flow will be described in detail below.

-Details of Rotor Structure-

<Rotor Shaft>

[0103] The rotor shaft 20 is inserted into a central hole 38 (see FIG. 8A and FIG. 8B) of the cylindrical rotor core 30 so as to be non-rotatable relative to this rotor core 30, and is rotatably supported by the motor housing, thereby enabling the rotor core 30 to rotate relative to the motor

housing and also serving to introduce a fresh oil from the anti-output axis side AOS of the rotor **10** through the oil introduction passage **20a**. As described above, the rotor shaft **20** has the oil introduction section **21** and the shaft main body **27**.

<Oil Introduction Section>

[0104] FIG. 5A is a perspective view schematically showing the oil introduction section **21**. FIG. 5B is a view showing the surface of the oil introduction section **21** on the output axis side OS. FIG. 5C is a sectional arrow view taken along the line c-c in FIG. 5A. As shown in FIG. 5A, the oil introduction section **21** is formed in such a shape that a cylindrical small diameter portion **22** and a cylindrical large diameter portion **23** having an outer diameter larger than that of the small diameter portion **22** are connected in the axial direction via a step surface so as to be concentric about the axis center AC.

[0105] The oil introduction section **21** has an oil introduction hole **24** formed that passes through the small diameter portion **22** and the large diameter portion **23** in the axial direction through their axial centers. In addition, a recess **25** having a circular cross section that is recessed into the anti-output axis side AOS is formed at the end on the output axis side OS of the large diameter portion **23**, as shown in FIG. 5A, FIG. 5B and FIG. 5C. The recess **25** communicates with the oil introduction hole **24** at its center. In addition, eight oil discharge grooves **26** that are recessed into the anti-output axis side AOS, radially extending from the recess **25** radially outward at equal intervals of 45 degrees in the circumferential direction, are formed at the end on the output axis side OS of the large diameter portion **23**, as shown in FIG. 5A and FIG. 5B. The radially inner end, of each oil discharge groove **26**, communicates with the recess **25**, and the radially outer end thereof opens on the outer circumferential surface of the large diameter portion **23**.

<Shaft Main Body>

[0106] FIG. 6A is a perspective view schematically showing a main part of the shaft main body **27**. FIG. 6B is a sectional arrow view taken along the line b-b in FIG. 6A. FIG. 6C is a sectional arrow view taken along the line c-c in FIG. 6A. As shown in FIG. 6A, the shaft main body **27** is formed in a cylindrical shape centered on the axis center AC, and the inner diameter thereof is set to be slightly larger than the outer diameter of the large diameter portion **23**.

[0107] As shown in FIG. 6A and FIG. 6C, the shaft main body **27** is provided with a disk-shaped partition plate **28** that divides the hollow portion in the axial direction. The length from the end on the anti-output axis side AOS of the shaft main body **27** to the anti-output axis side AOS surface of the partition plate **28** is set to the same length as the axial length of the large diameter portion **23**. Also, as shown in FIG. 6A and FIG. 6B, the shaft main body **27** has eight oil discharge holes **29** formed that extend radially outward at equal intervals of 45 degrees in the circumferential direction and penetrate the shaft main body **27**. The oil discharge holes **29** are circular holes with a diameter substantially equal to the depth of the oil discharge groove **26**, and are formed at positions that contact the anti-output axis side AOS surface of the partition plate **28**.

<Oil Introduction Passage>

[0108] FIG. 7A is a perspective view schematically showing a main part of the shaft main body **27** of the rotor shaft **20**. FIG. 7B is a sectional arrow view taken along the line b-b in FIG. 7A. FIG. 7C is a sectional arrow view taken along the line c-c in FIG. 7A. FIG. 7D is a perspective view showing the flow of an oil in the rotor shaft **20**. The rotor shaft **20** is a combination of the oil introduction section **21** and the shaft main body **27** configured as described above. Specifically, the rotor shaft **20** is configured by fitting the large diameter portion **23** into the hollow part of the shaft main body **27** so that the circumferential positions of the eight oil discharge grooves **26** and the eight oil discharge holes **29** coincide with each other, and then joining the two by welding or the like.

[0109] When the oil introduction section **21** and the shaft main body **27** are combined, the recess **25** and the oil discharge groove **26** are covered by the surface of the partition plate **28** on the anti-output axis side AOS, thereby forming a disk-shaped space **25'** and an oil discharge passage **26'**

having a closed cross section. As a result, the oil introduction passage **20a** is formed, in which a fresh oil flows through the oil introduction hole **24** to the output axis side OS, fills the disk-shaped space **25'**, flows from the disk-shaped space **25'** through the oil discharge passage **26'** radially outward, and is then sent out radially to the outside of the rotor shaft **20** through the oil discharge hole **29**.

[0110] In this manner, the oil flow as shown in FIG. 7D, in other words, the portion of the oil flow in the rotor **10** shown in FIG. 4 that corresponds to the rotor shaft **20**, is realized.

<Rotor Core>

[0111] FIG. 8A is an overall cross-sectional view schematically showing the rotor core **30** and the permanent magnets **101**, **102**, - - -. FIG. 8B is an enlarged view of the magnetic pole divided by the dashed lines in FIG. 8A. The rotor core **30** is a laminated body in which a predetermined number of annular magnetic thin plates formed into a predetermined shape are stacked in the axial direction, and as shown in FIG. 8A, it is formed into a cylindrical shape having a central hole **38** to which the rotor shaft **20** is fixed by shrink fitting. As the material of the magnetic thin plates, electromagnetic steel plates, which are a type of silicon steel plates, can be used.

[0112] In the rotor core **30**, a plurality of magnet holes **31**, **33**, **34**, **35**, **36** extending in the axial direction are formed so that the number of magnetic poles of the rotor **10** is eight and the prospect angle ϕ along the circumferential direction of one magnetic pole as seen from the axis AC is 45 degrees, and permanent magnets **101**, **102**, **103**, **104**, **105**, **106** are embedded in the plurality of magnet holes **31**, **33**, - - -. The rotor core **30** is configured so that the skew angle is 0 degrees, and therefore the magnet holes **31**, **33**, - - - and the permanent magnets **101**, **102**, - - - extend straight in the axial direction from the end on the anti-output axis side AOS to the end on the output axis side OS of the rotor core **30**. Although the positions and shapes of the magnet holes **31**, **33**, - - - and the permanent magnets **101**, **102**, - - - of each magnetic pole are different, the basic configuration is the same, so the magnet holes **31**, **33**, - - - and permanent magnets **101**, **102**, - - - of each magnetic pole will be explained by referring to the magnetic pole shown in the enlarged view of FIG. 8B as a representative of the eight magnetic poles.

[0113] As shown in FIG. 8B, each magnetic pole is configured with a two-layer structure of an outer embedded magnet section **100A** including two permanent magnets **101**, **102** arranged in a V-shape on the radially outer side, and an inner embedded magnet section **100B** including four permanent magnets **103**, **104**, **105**, **106** arranged in a U-shape on the radially inner side. Note that the protrusions **37** and the gaps **37a** in the protrusions **37** shown in FIG. 8A and FIG. 8B are intended to suppress the generation of harmonic components contained in the magnetic flux, and are not related to this embodiment, so detailed description will be omitted.

[0114] The outer embedded magnet section **100A** has one magnet hole **31**, and the two permanent magnets **101**, **102** are inserted into the magnet hole **31** so as to form a V-shape in which the distance between them increases radially outward and decreases radially inward. The portions of the magnet hole **31** that are not filled with the two permanent magnets **101**, **102** and the portions defined by the bridge **39** remain as gaps (flux barriers) **31a**, **31b**, **31c**, **31d**, and **31e**. Of these gaps **31a**, **31b**, **31c**, **31d**, and **31e**, the gap **31c** serves as an oil passage through which an oil flows to cool the permanent magnets **101**, **102**, as described below.

[0115] The inner embedded magnet section **100B** has four magnet holes **33**, **34**, **35**, and **36**. The permanent magnets **103** and **106** are inserted into the magnet holes **33** and **36**, respectively, so that the distance between them increases toward the radially outward direction and decreases toward the radially inward direction. The portions of the magnet holes **33** and **36** that are not filled with the permanent magnets **103** and **106** remain as gaps **33a**, **33b**, **36a**, and **36b**. The permanent magnets **104** and **105** are inserted into the magnet holes **34** and **35**, respectively, and the portions of the magnet holes **34** and **35** that are not filled with the permanent magnets **104** and **105** remain as gaps **34a** and **35a**. Of these gaps **33a**, **33b**, **34a**, **35a**, **36a**, and **36b**, the gaps **33b** and **36a** serve as oil paths through which an oil flows for cooling the permanent magnets **103** and **106**, as will be

described later.

<End Plate on Anti-Output Axis Side>

[0116] As shown in FIG. 1, FIG. 3 and FIG. 4, the end plates attached to the end on the anti-output axis side AOS of the rotor core **30** include first to third end plates **40**, **50**, **60**. Note that, in relation to the claims, the first to third end plates **40**, **50**, **60** of this embodiment correspond to what is referred to in the present invention as “annular one-side end plate attached concentrically with the axis center of the rotor core to the end on one axial side of the rotor core.”

[0117] The first to third end plates **40**, **50**, **60** are annular aluminum plates having the same outer shapes as the outer and inner circumferential surfaces of the rotor core **30**, and are assembled by welding or the like to form the end plates on the anti-output axis side AOS. As shown in FIG. 1, the first to third end plates **40**, **50**, **60** are arranged so as to overlap the coil end **93a** on the anti-output axis side AOS, which is one of the cooling target parts, when viewed in the radial direction. As shown in FIG. 12A below, the first end plate **40** has a flat surface **40a** (surface on the anti-output axis side AOS) and a flat back surface **40b** (surface on the output axis side OS), and does not have any special features, so a detailed description thereof will be omitted.

<Second End Plate>

[0118] FIG. 9A is a view schematically showing the surface (surface **50a**) of the second end plate **50** on the anti-output axis side AOS. FIG. 9B is a sectional arrow view taken along the line b-b in FIG. 9A and FIG. 9C. FIG. 9C is a view showing the surface (back surface **50b**) on the output axis side OS. FIG. 9D is a perspective view showing the first diffusion groove **51**. FIG. 9E is a perspective view showing the annular groove **53** and the connecting groove **55**. The figures shown in the bold frames in FIG. 9A and FIG. 9C are partial enlarged views of the dashed frame. In FIG. 9B, the thickness of the second end plate **50** is exaggerated in comparison with the diameter in order to make the figure easier to see.

[0119] As shown in FIG. 9A and FIG. 9D, eight first diffusion grooves **51**, extending radially outward at equal intervals of 45 degrees in the circumferential direction and recessed into the output axis side OS, are formed on the surface **50a** of the second end plate **50**. Each first diffusion groove **51** extends to the outer circumferential surface **50c** of the second end plate **50** and opens at the outer circumferential surface **50c**, and is formed so that the groove width increases radially outward.

[0120] On the other hand, as shown in FIG. 9C and FIG. 9E, an annular groove **53** having a circular ring shape, which is recessed toward the anti-output axis side AOS and is concentric with the axis center AC of the second end plate **50**, is formed on the back surface **50b** of the second end plate **50**. In addition, eight connecting grooves **55**, which extend radially outward from the inner circumferential surface of the second end plate **50** at equal intervals of 45 degrees in the circumferential direction and connect to the annular groove **53**, and which are recessed into the anti-output axis side AOS, are formed on the back surface **50b** of the second end plate **50**.

[0121] As shown in the bold frames in FIG. 9A and FIG. 9C and in FIG. 9B, the radially inner end of the first diffusion groove **51** formed on the surface **50a** overlaps with the annular groove **53** formed on the back surface **50b** when viewed in the axial direction. The eight first diffusion grooves **51** formed on the surface **50a** and the eight connecting grooves **55** formed on the back surface **50b** are aligned in the circumferential direction and extend radially on the same radius. The first diffusion grooves **51** formed on the surface **50a** and the annular groove **53** formed on the back surface **50b** communicate with each other through a communication hole **57** that has a circular cross section and extends in the axial direction at the overlapping portion.

<Third End Plate>

[0122] FIG. 10A is a view schematically showing the surface (surface **60a**) of the third end plate **60** on the anti-output axis side AOS. FIG. 10B is a sectional arrow view taken along the line b-b in FIG. 10A and FIG. 10C. FIG. 10C is a view schematically showing the surface (back surface **60b**) of the third end plate **60** on the output axis side OS. FIG. 10D is a perspective view schematically

showing the annular groove **63** and the connecting groove **65**. FIG. **10E** is a perspective view schematically showing the first and second radial grooves **61**, **62**. The figures shown in the bold frames in FIG. **10A** and FIG. **10C** are partial enlarged views of the dashed frame. In FIG. **10B**, the thickness of the third end plate **60** is exaggerated in comparison with the diameter in order to make the figure easier to see.

[0123] As shown in FIG. **1C** and FIG. **10E**, a circular annular groove **63** recessed toward the output axis side OS, concentric with the axis center AC of the third end plate **60**, is formed on the surface **60a** of the third end plate **60**. In addition, eight connecting grooves **65** recessed toward the output axis side OS, extending radially outward from the inner circumferential surface of the third end plate **60** at equal intervals of 45 degrees in the circumferential direction and connecting to the annular groove **63**, are formed on the surface **60a** of the third end plate **60**.

[0124] On the other hand, as shown in FIG. **1C** and FIG. **10E**, eight first radial grooves **61** recessed into the anti-output axis side AOS, which extend radially outward at equal intervals of 45 degrees in the circumferential direction, are formed on the back surface **60b** of the third end plate **60**. Also, sixteen rows of second radial grooves **62**, two of which are provided between circumferentially adjacent first radial grooves **61**, which extend at an inclination in the circumferential direction as they move radially outward, and which are recessed into the anti-output axis side AOS, are formed on the back surface **60b** of the third end plate **60**. The length of the second radial grooves **62** is set shorter than the length of the first radial grooves **61**.

[0125] As shown in the bold frames in FIG. **10A** and FIG. **10C** and in FIG. **10B**, the radially inner ends of the first and second radial grooves **61**, **62** formed on the back surface **60b** overlap with the annular groove **63** formed on the surface **60a** when viewed in the axial direction. The first and second radial grooves **61**, **62** formed on the back surface **60b** communicate with the annular groove **63** formed on the surface **60a** through a communication hole **67** having a circular cross section and extending in the axial direction at the overlapping portion.

[0126] However, unlike the relationship between the first diffusion groove **51** and the connecting groove **55** in the second end plate **50**, the eight first radial grooves **61** and the sixteen rows of second radial grooves **62** formed on the back surface **60b** do not coincide in circumferential position with the eight connecting grooves **65** formed on the surface **60a**. In other words, the communication hole **67** that communicates the first and second radial grooves **61**, **62** formed on the back surface **60b** with the annular groove **63** formed on the surface **60a** do not coincide in circumferential position with the connecting groove **65**.

[0127] Furthermore, as shown in FIG. **10C** and FIG. **10E**, eight U-shaped discharge recesses **69** at equal intervals of 45 degrees in the circumferential direction, with the outer peripheral edge recessed toward the anti-output axis side AOS, are formed on the back surface **60b** of the third end plate **60**.

<Chamber Space>

[0128] FIG. **11A** is a cross-sectional view schematically showing a state where the second and the third end plates **50**, **60** are stacked. FIG. **11B** is a perspective view schematically showing a space formed by stacking the second and third end plates **50**, **60**. FIG. **11C** and FIG. **11D** are a cross-sectional view and a perspective view, respectively, schematically showing a state where the rotor shaft **20** and the second and third end plates **50**, **60** are combined. FIG. **11E** is a perspective view schematically showing the flow of an oil in the rotor shaft **20** and the second and third end plates **50**, **60**. In FIG. **11A**, the thicknesses of the second and third end plates **50**, **60** are exaggerated compared to the diameters in order to make the figure easier to see.

[0129] As shown in FIG. **11A**, when the back surface **50b** of the second end plate **50** and the surface **60a** of the third end plate **60** are overlapped concentrically in the axial direction so that the connecting grooves **55** and **65** coincide in the circumferential direction, a chamber space **43** that is annular when viewed in the axial direction, defined by the annular grooves **53** and **63** is formed concentrically with the axis center AC as shown in FIG. **11B**. In addition, eight connecting flow

paths **45** are also formed that extend radially outward from the inner circumferential surfaces of the second and third end plates **50**, **60**, defined by the connecting grooves **55** and **65**, at equal intervals of 45 degrees in the circumferential direction, and connect (communicate) with the chamber space **43**.

[0130] As shown in FIG. **11C**, when the rotor shaft **20** is combined with the second and third end plates **50**, **60** so that the eight oil discharge holes **29** and the eight connecting passages **45** coincide in the circumferential direction, in other words, so that the eight oil discharge holes **29** and the eight connecting passages **45** communicate with each other, the oil introduction passage **20a** of the rotor shaft **20** communicates with the chamber space **43** via the connecting passage **45**, as shown in FIG. **11D**. As a result, a fresh oil radially sent out from the oil introduction passage **20a** of the rotor shaft **20** fills the chamber space **43**.

[0131] In this manner, the oil flow as shown in FIG. **11E**, in other words, the portion of the oil flow in the rotor **10** shown in FIG. **4** that corresponds to the rotor shaft **20** and the second and third end plates **50**, **60**, is realized.

<First Diffusion Oil Passage>

[0132] FIG. **12A** is a cross-sectional view schematically showing a state wherein the first and second end plates **40**, **50** are stacked. FIG. **12B** is a perspective view schematically showing a space formed by stacking the first and second end plates **40**, **50**. FIG. **12C** is a perspective view schematically showing the flow of an oil in the rotor shaft **20** and the first to third end plates **40**, **50**, **60**. FIG. **11A** shows the thicknesses of the first and second end plates **40**, **50** exaggerated in comparison with their diameters in order to make the drawing easier to see.

[0133] As shown in FIG. **12A**, when the back surface **40b** of the first end plate **40** and the surface **50a** of the second end plate **50** are overlapped concentrically in the axial direction, the first diffusion groove **51** is covered by the back surface **40b** of the first end plate **40**, and eight first diffusion oil passages **41** are formed as spaces extending radially on the anti-output axis side AOS than the chamber space **43**, as shown in FIG. **12B**. Since each first diffusion oil passage **41** is formed by covering the first diffusion groove **51**, the passage **41** is formed so that the radially inner end communicates with the chamber space **43** via a communication hole **57**, opening is formed on the outer circumferential surface **50c** of the second end plate **50**, and the cross-sectional area increases as it goes radially outward, like the first diffusion groove **51**.

[0134] By forming these eight first diffusion oil passages **41**, it becomes possible for a portion of the fresh oil filled in the chamber space **43** to be scattered radially outward from the outer circumferential surface **50c** of the second end plate **50** by centrifugal force through these first diffusion oil passages **41**. In this way, the first to third end plates **40**, **50**, **60** are arranged so as to overlap radially with the coil end **93a** on the anti-output axis side AOS, and therefore it is possible to cool the coil end **93a**, which is one of the cooling target parts.

[0135] Furthermore, the oil that is scattered to the coil end **93a** is simply filled once into the chamber space **43** formed in the second and third end plates **50**, **60**, which are separate from the rotor core **30**, and is supplied to the coil end **93a** while still in a sufficiently cooled state, rather than after cooling the rotor core **30**, etc. (raising the temperature), so that the coil end **93a** can be cooled efficiently.

[0136] Here, if the first diffusion oil passage **41** is blocked by an oil, a case is also assumed in which negative pressure would be generated within the first diffusion oil passage **41**, which could result in loss of uniformity of the oil within the chamber space **43**. However, in this embodiment, the first diffusion oil passage **41** is formed so that the cross-sectional area increases as it goes radially outward, making it possible to prevent the first diffusion oil passage **41** from being blocked by an oil, and thus making it possible to maintain uniformity of the oil within the chamber space **43** while cooling the coil end **93a**.

[0137] In this manner, the oil flow as shown in FIG. **12C**, in other words, the portion of the oil flow in the rotor **10** shown in FIG. **4** that corresponds to the first to third end plates **40**, **50**, **60**, is

realized.

<Radial Oil Passage>

[0138] FIG. 13A is a partial perspective view schematically showing a state in which the third end plate **60** is attached to the end surface **30a** on the anti-output axis side AOS of the rotor core **30**. FIG. 13B and FIG. 13C are sectional arrow views taken along the lines b-b and c-c in FIG. 13A, respectively. FIG. 13D is a perspective view schematically showing the flow of an oil in the first to third end plates **40**, **50**, and **60** and in the rotor core **30**. In FIG. 13A, dashed lines are used to show those other than the radial oil passages **61'** and **62'** in order to make the drawing easier to see. In FIG. 13B and FIG. 13C, the thickness of the third end plate **60** is exaggerated compared to the diameter in order to make the drawing easier to see.

[0139] As shown in FIG. 13A, when the back surface **60b** of the third end plate **60** is attached to the end surface **30a** on the anti-output axis side AOS of the rotor core **30** by welding or the like so that the first radial grooves **61** and the center lines (so-called d-axis) of the magnetic poles coincide in the circumferential direction, the first radial groove **61** is covered by the end surface **30a** on the anti-output axis side AOS of the rotor core **30**, and eight first radial oil passages **61'** extending radially on the output axis side OS than the chamber space **43** are formed, as shown in FIG. 13B. Since each of the first radial oil passages **61'** is obtained by covering the first radial groove **61**, the radially inner end communicates with the chamber space **43** via the communication hole **67**, similar to the first radial groove **61**. The length of the first radial oil passage **61'** is set so that the radially outer end communicates with the gap **31c** of the magnet hole **31**.

[0140] The second radial groove **62** is also covered by the end surface **30a** on the anti-output axis side AOS of the rotor core **30**, and sixteen rows of second radial oil passages **62'** are formed, extending at an inclination in the circumferential direction toward the radially outer side on the output axis side OS than the chamber space **43**. Since each second radial oil passage **62'** is obtained by covering the second radial groove **62**, the radially inner end communicates with the chamber space **43** via a communication hole **67**, similar to the second radial groove **62**. The length and inclination direction of the second radial oil passage **62'** are set so that the radially outer end communicates with the gap **36a** (or gap **33b**) of the magnet hole **36**.

[0141] FIG. 14A is a cross-sectional view schematically showing a main part of the rotor core **30**. In FIG. 14A, the oil is shown as a black portion. FIG. 14B is a cross-sectional view schematically showing a state where centrifugal force acts on the oil shown in FIG. 14A. In the rotor structure of this embodiment, by forming such eight first radial oil passages **61'** and sixteen rows of second radial oil passages **62'**, the oil flows from the anti-output axis side AOS to the output axis side OS through **24** gaps **31c**, **33b**, **36a** (in magnet holes **31**, **33**, **36**) inside the rotor core **30**, as shown by the black portion in FIG. 13A.

[0142] In this way, the oil flows axially inside the rotor core **30** through the plurality of gaps **31c**, **33b**, **36a**, and the oil can directly cool the permanent magnets **101**, **102**, **103**, **106**, which are one of the cooling target parts. This allows the permanent magnets **101**, **102**, - - - to be cooled more efficiently than, for example, a structure in which an oil flows through holes (oil passages) provided near the permanent magnets **101**, **102**, - - - in the rotor core **30**.

[0143] Furthermore, the rotor structure of this embodiment is configured such that an oil is filled into the chamber space **43** from the oil introduction passage **20a** of the rotor shaft **20**, and the oil is distributed from the chamber space **43** to the plurality of gaps **31c**, **33b**, and **36a**, therefore, compared to a structure in which an oil is sent directly from the oil introduction passage **20a** to the gaps **31c**, **33b**, and **36a**, for example, the oil can be distributed evenly to the plurality of gaps **31c**, **33b**, and **36a**.

[0144] As described above, the communication hole **67** that communicates the first and second radial grooves **61**, **62** formed in the back surface **60b** with the annular groove **63** formed in the surface **60a** does not coincide in circumferential position with the connecting groove **65**. Therefore, a fresh oil that is filled into the chamber space **43** through the eight connecting flow paths **45** tends

to flow evenly to the eight first radial oil passages **61'** and the sixteen rows of second radial oil passages **62'**, making it possible to distribute the oil more evenly to the plurality of gaps **31c**, **33b**, **36a**.

[0145] In addition, the oil distributed to the gaps **31c**, **33b**, **36a** is simply temporarily filled in the chamber space **43** formed in the second and third end plates **50**, **60** that are separate from the rotor core **30**, and is supplied to the gaps **31c**, **33b**, **36a** in a sufficiently cooled state, rather than after cooling the rotor core **30**, etc. (raising the temperature), so that the permanent magnets **101**, **102**, - - - can be effectively cooled. This makes it possible to prevent the permanent magnets **101**, **102**, - - - from being insufficiently cooled, and therefore makes it possible to prevent the permanent magnets **101**, **102**, - - - from being demagnetized, and thus to prevent a decrease in torque.

[0146] In addition, in the rotor structure of this embodiment, as described above, the rotor core **30** is so-called skewless, so that the flow passage resistance to the oil flowing through the gaps **31c**, **33b**, **36a** can be reduced, thereby making it possible to cool the permanent magnets **101**, **102**, - - - even more efficiently.

[0147] In this embodiment, as shown in FIG. **14A**, no oil is flowed into the gaps **34a**, **35a** (the permanent magnets **104**, **105** are not targeted for cooling), and this is because, if too much oil is flowed from the chamber space **43** toward the rotor core **30**, the amount of a fresh oil supplied to the coil end **93a** will be reduced too much, and because the permanent magnets **101**, **102**, **103**, and **106** closer to the stator **90** are more likely to reach high temperatures than the permanent magnets **104**, **105** farther from the stator **90**.

[0148] In contrast, during motor operation when the need for cooling is high, the rotor **10** is constantly rotating, and centrifugal force acts on the oil (see the thick arrow in FIG. **14B**), so that the oil flowing axially through the gaps **31c**, **33b**, **36a** (inside the magnet holes **31**, **33**, **36**) also tends to collect in the radially outer portions of the gaps **31c**, **33b**, **36a**, as shown in FIG. **14B**. For this reason, if the radially outer ends of the first and second radial oil passages **61'**, **62'** were connected to the radially outer portions of the gaps **31c**, **33b**, **36a** where the oil collects, it is conceivable that the oil would not be smoothly introduced into the gaps **31c**, **33b**, **36a**.

[0149] In addition, while the oil flows radially outward through the first and second radial oil passages **61'**, **62'**, it flows axially when supplied to the gaps **31c**, **33b**, **36a**, then, if surfaces **61a**, **62a** defining the first and second radial oil passages **61'**, **62'** on the anti-output axis side AOS (referred to as "first defining surface") and surfaces **61b**, **62b** defining the first and second radial oil passages **61'**, **62'** on the radially outer side (referred to as "second defining surface") are perpendicular to each other, it is supposed that the oil will not change direction smoothly. In addition, as described above, centrifugal force also acts on the oil, so that the oil flowing radially through the first and second radial oil passages **61'**, **62'** is likely to be pressed against the second defining surfaces **61b**, **62b**, therefore, in cases where the first defining surfaces **61a**, **62a** and the second defining surfaces **61b**, **62b** are perpendicular to each other, it is expected that the oil will have even more difficulty in changing direction.

[0150] Therefore, in the rotor structure of this embodiment, the radially outer ends of the first and second radial oil passages **61'**, **62'** are connected to the radially inner portions of the gaps **31c**, **33b**, **36a**, and the first defining surfaces **61a**, **62a** and the second defining surfaces **61b**, **62b** are connected in an R-shape when viewed in the circumferential direction.

[0151] FIG. **15A** and FIG. **15B** are perspective views schematically showing the first and second radial oil passages **61'**, **62'**. In this embodiment, as shown in FIG. **13B** and FIG. **13C** and FIG. **15A**, the radially outer ends of the first and second radial oil passages **61'**, **62'** communicate with the radially inner portions of the gaps **31c**, **33b**, **36a**, in other words, communicate with the parts of the gaps **31c**, **33b**, **36a** where the oil does not collect, so that the oil can be smoothly introduced from the first and second radial oil passages **61'**, **62'** to the gaps **31c**, **33b**, **36a**.

[0152] As shown in FIG. **13B** and FIG. **13C** and FIG. **15B**, the first defining surfaces **61a**, **62a** and the second defining surfaces **61b**, **62b** are connected by the R-shaped portions **61c**, **62c** when

viewed in the circumferential direction, so that when the oil flowing radially outward through the first and second radial oil passages **61'**, **62'** is supplied to the gaps **31c**, **33b**, **36a** under centrifugal force, smooth direction change to the axial direction can be realized. As a result, the permanent magnets **101**, **102**, **103**, **106**, which are one of the cooling target parts, can be cooled more efficiently.

[0153] In this manner, the oil flow as shown in FIG. **13D**, in other words, the portion of the oil flow in the rotor **10** shown in FIG. **4** that corresponds to the second and third end plates **50**, **60** and the rotor core **30**, is realized.

<End Plate on Output Axis Side>

[0154] As shown in FIG. **1**, FIG. **3** and FIG. **4**, the end plates attached to the end on the output axis side OS of the rotor core **30** include fourth and fifth end plates **70**, **80**. In relation to the claims, the fourth and fifth end plates **70**, **80** of this embodiment correspond to “annular other-side end plate attached concentrically with the axis center of the rotor core to the end on the other axial side of the rotor core” referred to in the present invention.

[0155] The fourth and fifth end plates **70**, **80**, like the first to third end plates **40**, **50**, **60**, are annular aluminum plates that have the same outer shapes as the outer and inner peripheral surfaces of the rotor core **30** and are assembled by welding or the like to form the end plates on the output axis side OS. As shown in FIG. **1**, the fourth and fifth end plates **70**, **80** are arranged to overlap, when viewed in the radial direction, with the coil end **93b** on the output axis side OS, which is one of the cooling target parts.

<Fourth End Plate>

[0156] FIG. **16A** is a view schematically showing the surface (surface **70a**) of the fourth end plate **70** on the anti-output axis side AOS. FIG. **16B** is a sectional arrow view taken along the line b-b in FIG. **16A** and FIG. **16C**. FIG. **16C** is a view schematically showing the surface (back surface **70b**) of the fourth end plate **70** on the output axis side OS. FIG. **16B** shows the thickness of the fourth end plate **70** exaggerated in comparison with its diameter in order to make the drawing easier to see.

[0157] As shown in FIG. **16A**, FIG. **16B** and FIG. **16C**, the fourth end plate **70** has eight outer through holes **71** formed that penetrate the fourth end plate **70** at equal intervals of 45 degrees in the circumferential direction. The radial positions of these outer through holes **71** correspond to the eight gaps **31c**, respectively. In addition, the fourth end plate **70** has sixteen inner through holes **73** formed that penetrate the fourth end plate **70** radially inward of the outer through holes **71** and have a larger diameter than the outer through holes **71**. The radial positions of these inner through holes **73** correspond to the sixteen gaps **33b**, **36a**, respectively.

[0158] As shown in FIG. **16A**, eight U-shaped discharge recesses **79** with the outer circumferential edge recessed toward the output axis side OS are formed, at equal intervals of 45 degrees in the circumferential direction, on the surface **70a** of the fourth end plate **70**. Meanwhile, as shown in FIG. **16C**, the back surface **70b** of the fourth end plate **70** has trapezoidal communication grooves **75**, **77** formed, as views in the axial direction, which protrude radially outward from the outer through hole **71** and the inner through hole **73** and are recessed toward the anti-output axis side AOS.

<Fifth End Plate>

[0159] FIG. **17A** is a view schematically showing the surface (surface **80a**) of the fifth end plate **80** on the anti-output axis side AOS. FIG. **17B** is a perspective view schematically showing the second diffusion grooves **81**, **83**. Note that the surface (back surface **80b** (see FIG. **18A**, FIG. **18B**, FIG. **18C**, FIG. **18D** and FIG. **18E**)) of the fifth end plate **80** on the output axis side OS is formed flat and has no distinctive features, so a detailed description thereof will be omitted.

[0160] As shown in FIG. **17A** and FIG. **17B**, eight second short diffusion grooves **81**, extending radially outward at equal intervals of 45 degrees in the circumferential direction and recessed into the output axis side OS, are formed on the surface **80a** of the fifth end plate **80**. The second short

diffusion grooves **81** have radially inner ends that substantially coincide with the outer through holes **71**, and extend to the outer peripheral surface **80c** of the fifth end plate **80** and open at the outer peripheral surface **80c**. The second short diffusion grooves **81** are formed so that their groove width increases radially outward.

[0161] Further, sixteen second long diffusion grooves **83**, that extend radially outward in the radial direction, are recessed toward the output axis side OS, and are longer than the second short diffusion grooves **81**, are formed on the surface **80a** of the fifth end plate **80**. The radially inner ends of the second long diffusion grooves **83** are approximately aligned with the inner through holes **73**, and extend to the outer circumferential surface **80c** of the fifth end plate **80** and open at the outer circumferential surface **80c**. Like the second short diffusion grooves **81**, the second long diffusion grooves **83** are formed so that their groove width increases radially outward.

<Second Diffusion Oil Passage>

[0162] FIG. **18A** is a partial perspective view schematically showing a state where the fourth end plate **70** and the fifth end plate **80** are overlapped. FIG. **18B** is a perspective view schematically showing a space formed by overlapping the fourth and fifth end plates **70**, **80**. FIG. **18C** and FIG. **18D** are cross-sectional views schematically showing a state in which the fourth and fifth end plates **70**, **80** are attached to the rotor core **30**, which correspond to the sectional arrow views taken along the lines c-c and d-d in FIG. **18A**, respectively. FIG. **18E** is a perspective view schematically showing the flow of an oil in the rotor core **30** and the fourth and fifth end plates **70**, **80**. In FIG. **18C** and FIG. **18D**, the thicknesses of the fourth and fifth end plates **70**, **80** are exaggerated compared to the diameters in order to make the drawings easier to see.

[0163] As shown in FIG. **18A**, when the back surface **70b** of the fourth end plate **70** and the surface **80a** of the fifth end plate **80** are concentrically stacked in the axial direction, the second short diffusion groove **81** is covered by the back surface **70b** of the fourth end plate **70**, and eight second short diffusion oil passages **81'**, which are spaces extending in the radial direction, are formed as shown in FIG. **18B**. Since each second short diffusion oil passage **81'** is obtained by covering the second short diffusion groove **81**, like the second short diffusion groove **81**, the radially inner end communicates with the outer through hole **71** and opens on the outer peripheral surface **80c** of the fifth end plate **80**, and is formed so that the cross-sectional area increases as it goes radially outward.

[0164] Similarly, the second long diffusion grooves **83** are covered by the back surface **70b** of the fourth end plate **70**, forming 16 second long diffusion oil passages **83'** which are spaces extending in the radial direction. Since each second long diffusion oil passage **83'** is obtained by covering the second long diffusion groove **83**, like the second long diffusion groove **83**, the radially inner end communicates with the inner through hole **73** and opens on the outer circumferential surface **80c** of the fifth end plate **80**, and is formed so that the cross-sectional area increases radially outward.

[0165] When the surface **70a** of the fourth end plate **70** is attached to the end surface **30b** on the output axis side OS of the rotor core **30** by welding or the like so that the outer through hole **71** and the gap **31c** (the inner through hole **73** and the gaps **33b**, **36a**) are aligned in the circumferential direction, the second short diffusion oil passage **81'** and the gap **31c** communicate via the outer through hole **71**, and the second long diffusion oil passage **83'** and the gaps **33b**, **36a** communicate via the inner through hole **73**, as shown in FIG. **18C**.

[0166] FIG. **19** is a perspective view schematically showing the outer and inner through holes **71**, **73**. Meanwhile, since the oil flows in the axial direction through the gaps **31c**, **33b**, **36a**, and flows radially outward through the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'**, a case is also supposed in which the oil does not change direction smoothly.

Therefore, in the rotor structure of this embodiment, the communication grooves **75**, **77** having an R-shape when viewed in the circumferential direction are formed in the portion where the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'** communicate with the outer and inner through holes **71**, **73**. This allows the oil to be smoothly introduced from the gaps

31c, 33b, 36a to the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'**.

[0167] By forming such second short diffusion oil passage **81'** and second long diffusion oil passage **83'**, it becomes possible for the oil that has flowed through the gaps **31c, 33b, 36a** to be scattered radially outward from the outer circumferential surface **80c** of the fifth end plate **80** by centrifugal force through the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'**. In this way, since the fourth and fifth end plates **70, 80** are arranged so as to overlap with the coil end **93b** on the output axis side OS when viewed in the radial direction, it is possible to cool the coil end **93b** on the output axis side OS, which is one of the cooling target parts.

[0168] In addition, the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'** are also formed so that the cross-sectional area increases toward the radially outer side, similar to the first diffusion oil passage **41**, so that the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'** can be prevented from being blocked by an oil. This makes it possible to prevent, for example, a phenomenon in which oil even distribution is impaired due to an increase in the amount of an oil flowing through the magnet holes communicating with the second short diffusion oil passage **81'** and the second long diffusion oil passage **83'** where negative pressure is generated.

[0169] Here, unlike the coil end **93a** on the anti-output axis side AOS, the coil end **93b** on the output axis side OS is supplied with an oil after cooling the rotor core **30**, etc. (that has been heated to a certain extent), but since the number (**24**) of the second short diffusion oil passages **81'** and the second long diffusion oil passages **83'** is set to be greater than the number (**8**) of the first diffusion oil passages **41**, in other words, the amount of an oil supplied to the coil end **93b** is relatively greater, thus, the coil end **93b** can also be cooled efficiently.

[0170] In this manner, the oil flow as shown in FIG. **18E**, in other words, the portion of the oil flow in the rotor **10** shown in FIG. **4** that corresponds to the rotor core **30** and the fourth and fifth end plates **70, 80**, is realized.

[0171] In the above rotor structure, the rotor core **30** is sandwiched between the third end plate **60** and the fourth end plate **70** in the axial direction, but because the rotor core **30** is a laminate of stacked magnetic thin plates, a case is also supposed in which an oil flowing in the axial direction inside the rotor core **30** may leak into the gaps between the magnetic thin plates. In this case, it may seem that the leaked oil would have nowhere to escape because it is sandwiched between the third end plate **60** and the fourth end plate **70**, but in this embodiment, because the third and fourth end plates **60, 70** have discharge recesses **69, 79** formed therein, the oil that has leaked into the gaps between the magnetic thin plates can be discharged to the outside of the rotor core **30** through the discharge recesses **69, 79**.

Other Embodiments

[0172] The present invention is not limited to the embodiments, and can be embodied in various other forms without departing from the spirit or main characteristics thereof.

[0173] In the above embodiments, the permanent magnets **101, 102, 103**, and **106** and the coil ends **93a** and **93b** are the parts to be cooled, however, there is no limitation to them, and for example, a separate cooling means may be provided for the coil ends **93a** and **93b**, and only the permanent magnets **101, 102, 103**, and **106** may be cooled.

[0174] In the above embodiments, four permanent magnets **101, 102, 103, 106** of the six permanent magnets **101, 102, 103, 104, 105, 106** constituting each magnetic pole are targeted for cooling, but this is no limitation to them, and for example, as shown in FIG. **20A**, a radial oil passage **62''** communicating with the chamber space **43** may be provided, and an oil may be caused to flow also into the gaps **34a, 35a** as shown by the blackened areas in FIG. **20B** to target the permanent magnets **104, 105** to be cooled. In addition, as shown by the blackened areas in FIG. **20C**, an oil may be caused to flow also into the gaps **31a, 31e, 37a** that are not in contact with the permanent magnets **101, 102, 103, 104, 105, 106** to indirectly cool the permanent magnets **103, 106**.

[0175] Furthermore, in the above embodiments, the rotor core **30** is so-called skewless, however, there is not limitation to this, and for example, the present invention may be applied to a rotor core **30'** having a skew angle θ , which is formed by combining four laminates **30A'**, **30B'**, **30C'**, and **30D'**, each of which is made up of a predetermined number of magnetic thin plates stacked in the axial direction, with each laminate being shifted by an angle θ , as shown in FIG. **21**.

[0176] In addition, in the above embodiments, the number of oil discharge holes **29**, connecting flow paths **45**, first diffusion oil passages **41**, first radial oil passages **61'**, second short diffusion oil passages **81'**, etc. is eight, and the number of second radial oil passages **62'**, second long diffusion oil passages **83'**, etc. is sixteen, but there is no limitation to them, and these numbers may be set appropriately.

[0177] Furthermore, in the above embodiments, the rotor **10** has eight magnetic poles, but this is no limitation to this, and the number of magnetic poles may be less than eight, or may be more than eight.

[0178] In addition, in the above embodiments, each magnetic pole has a two-layer structure with an outer embedded magnet section **100A** arranged in a V-shape on the radially outer side and an inner embedded magnet section **100B** arranged in a U-shape on the radially inner side, but this is no limitation to this, and it may also have a single-layer structure with outer embedded magnet sections arranged in a V-shape or a straight line, for example.

[0179] Furthermore, in the above embodiments, the end plates on the anti-output axis side AOS are made up of the first to third end plates **40**, **50**, **60**, and the end plates on the output axis side OS are made up of the fourth and fifth end plates **70**, **80**, however, there is not limitation to this, and for example, the end plates on the anti-output axis side AOS and the output axis side OS may each be made from a single member, using a sand mold for casting.

[0180] As mentioned above, the above-described embodiments are merely illustrative in all respects and should not be construed as limiting. Furthermore, all modifications and variations within the scope of the claims are within the scope of the present invention.

[0181] Although the present disclosure has been described based on examples, it is understood that the present disclosure is not limited to the examples or structures. The present disclosure also includes various modifications and variation within the equivalent range. In addition, various combinations and forms, and other combinations and forms including only one element, more than one element, or less than one element, are also within the scope and concept of the present disclosure.

INDUSTRIAL APPLICABILITY

[0182] According to the present invention, the parts to be cooled inside a synchronous motor can be efficiently cooled, and therefore, it is extremely beneficial when applied to the rotor structure of a synchronous motor.

Claims

1. A rotor structure that supplies an oil to a cooling target part inside a synchronous motor in which a rotor rotates in synchronization with a rotating magnetic field generated by a stator, characterized by being configured such that: the rotor comprises a plurality of permanent magnets, which are one of the cooling target parts, and a cylindrical rotor core in which a plurality of axially extending magnet holes are formed in which the respective permanent magnets are embedded, and an oil flows axially inside the rotor core through the plurality of magnet holes.

2. The rotor structure according to claim 1, characterized by being configured such that: the rotor further comprises a rotor shaft that is inserted into the rotor core so as not to rotate relative to the rotor core, and an annular one-side end plate that is attached concentrically with an axis center of the rotor core to the end on one axial side of the rotor core, the one-side end plate has a chamber space formed having an annular shape as viewed in the axial direction concentrically with the axis

center of the rotor core, and at the one-side end plate, an oil is filled into the chamber space from an oil passage in the rotor shaft and the oil is distributed from the chamber space to the plurality of magnet holes.

3. The rotor structure according to claim 2, characterized in that: the one-side end plate has a plurality of radial oil passages formed that extend radially on an other axial side than the chamber space, whose radially inner end communicates with the chamber space, and whose radially outer end communicates with a plurality of the magnet holes, and in each of the radial oil passages, a surface that defines the radial oil passage on one axial side and a surface that defines the radial oil passage on the radially outer side are connected in an R-shape when viewed in a circumferential direction.

4. The rotor structure according to claim 2, characterized in that: the one-side end plate has a plurality of radial oil passages formed that extend radially on an other axial side than the chamber space, whose radially inner end communicates with the chamber space, and whose radially outer end communicates with a plurality of the magnet holes, and the radially outer end of each of the radial oil passages is in communication with a radially inner portion of each of the magnet holes.

5. The rotor structure according to claim 2, characterized in that: the one-side end plate is disposed so as to overlap, as viewed in a radial direction, a coil end on one axial side, which is one of the cooling target parts, of a stator coil attached to the stator, the one-side end plate has a plurality of first diffusion oil passages formed that extend radially on one axial side than the chamber space, whose radially inner end communicates with the chamber space, and that open on an outer peripheral surface of the one-side end plate, and each of the first diffusion oil passages is formed so that its cross-sectional area increases toward the radially outer side.

6. The rotor structure according to claim 5, characterized in that: the rotor further comprises an annular other-side end plate attached concentric with the axis center of the rotor core to the end on an other axial side of the rotor core, the other-side end plate is disposed so as to overlap, as viewed in a radial direction, the coil end on the other axial side, which is one of the cooling target parts, of the stator coil, the other-side end plate has a plurality of second diffusion oil passages formed that extend radially, whose radially inner end communicates with a plurality of the magnet holes, that open on the outer peripheral surface of the other end plate, and whose cross-sectional area increases toward the radially outer side, and a number of the second diffusion oil passages is set to be greater than a number of the first diffusion oil passages.

7. The rotor structure according to claim 1, characterized in that: the rotor core has a skew angle of 0 degrees.
