

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402722
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Huang; Chenglan

Supporting assembly and supporting frame thereof

Abstract

Disclosed is a support frame, comprising: a base plate for supporting the support frame; a connecting plate for attaching to and fixing the base plate; a back plate, wherein a first bending part is provided between the back plate and the connecting plate; a support plate, wherein a second bending part is provided between the support plate and the back plate, a third bending part is provided between the support plate and the base plate, and the first, second and third bending parts are parallel; and when the support frame is bent and deformed through the first, second and third bending parts, the support plate and the back plate are erected, the connecting plate is attached and connected to the base plate, and an included angle is formed between the support plate and the back plate. A support assembly is further disclosed.

Inventors:	Huang; Chenglan (Shenzhen, CN)
Applicant:	Shenzhen Lemo Marketing Consultancy Co.,Ltd (Shenzhen, CN); Li; Jiecong (Shenzhen, CN)
Family ID:	82912695
Assignee:	Shenzhen Lemo Marketing Consultance Co., Ltd (Shenzhen, CN); Li; Jiecong (Shenzhen, CN)
Appl. No.:	18/572166
Filed (or PCT Filed):	June 24, 2022
PCT No.:	PCT/CN2022/101245
PCT Pub. No.:	WO2022/268211
PCT Pub. Date:	December 29, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

CN

202121438317.5

Jun. 24, 2021

Publication Classification**Int. Cl.:** A47B23/04 (20060101)**U.S. Cl.:**CPC **A47B23/044** (20130101); **A47B23/043** (20130101); A45C2200/15 (20130101);
A47B2023/049 (20130101)**Field of Classification Search****CPC:** A47B (23/044); A47B (23/043); A47B (2023/049); A45C (2200/15); F16M (11/38)**USPC:** 248/174; 248/459

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5722628	12/1997	Menaged	248/455	A47B 23/043
8434601	12/2012	Hou	248/455	A45C 13/02
8746446	12/2013	Chiang	206/320	G06F 1/1628
9489015	12/2015	Gioscia	N/A	A45C 11/00
9545139	12/2016	Kim	N/A	A45C 11/00
9671057	12/2016	Lin	N/A	F16M 11/10
9730345	12/2016	Wu	N/A	F16M 13/00
10211874	12/2018	Kao	N/A	A45C 13/1069
10302243	12/2018	Scholz	N/A	A47B 23/04
10606314	12/2019	Takano	N/A	F16M 11/2021
10842237	12/2019	Takano	N/A	A47B 23/044
11169576	12/2020	Campbell	N/A	G06F 1/1637
D1025998	12/2023	He	D14/447	N/A
2004/0240164	12/2003	Lee	361/679.55	G06F 1/1616
2008/0230672	12/2007	Pachowski	248/459	A47B 23/044
2012/0037047	12/2011	Moldovan	108/3	F16M 11/10
2012/0305739	12/2011	Huang	248/397	F16M 11/10
2016/0066667	12/2015	Yu	224/191	G06F 1/1628
2020/0060420	12/2019	Hu	N/A	A47B 23/043
2020/0397105	12/2019	Kim	N/A	A45C 11/00
2021/0310600	12/2020	Sawaqedy	N/A	F16M 11/38
2023/0346094	12/2022	Hsu	N/A	F16M 13/022

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
-------------------	-------------------------	----------------	------------

211145816	12/2019	CN	N/A
211779986	12/2019	CN	H04M 1/04
211821384	12/2019	CN	N/A
214405480	12/2020	CN	A47B 23/043
102021002347	12/2021	DE	A47B 23/044
742152	12/1954	GB	G09F 1/00
2449115	12/2007	GB	A47B 23/044
WO-2023030526	12/2022	WO	N/A

OTHER PUBLICATIONS

Translation of CN-211145816-U (Year: 2020). cited by examiner

Primary Examiner: Morris; Taylor

Attorney, Agent or Firm: IPro, PLLC

Background/Summary

TECHNICAL FIELD

(1) The present utility model belongs to the field of supporting frames, and particularly relates to a supporting assembly and a supporting frame thereof.

BACKGROUND

(2) Most of the existing supporting frames have a single and fixed structure, which cannot be folded or deformed, occupies a large space, and is inconvenient to carry.

(3) Therefore, how to enable the supporting frame to support stably and how to fold and deform the supporting frame so as to reduce an occupied space and facilitate carrying are technical problems to be solved by those skilled in the art.

SUMMARY

(4) A main technical problem solved by the present utility model is to provide a supporting assembly and a supporting frame thereof, so as to solve the problems that the supporting frame in the conventional technology is not firmly supported, occupies a large space, is inconvenient to carry, and cannot be folded and deformed.

(5) To solve the above technical problems, a technical solution adopted by the present utility model is to provide a supporting frame, comprising: a base plate, configured to support the supporting frame; a connecting plate, configured to attach to and fix the base plate; a back plate, wherein a first bending part is provided between the back plate and the connecting plate; a supporting plate, wherein a second bending part is provided between the supporting plate and the back plate, a third bending part is provided between the supporting plate and the base plate, and the first bending part, the second bending part and the third bending part are parallel to each other; and when the supporting frame is bent and deformed through the first bending part, the second bending part and the third bending part, the supporting plate and the back plate are erected, the connecting plate is attached and connected to the base plate, and an included angle is formed between the supporting plate and the back plate.

(6) Preferably, at least two dividing holes are provided between the connecting plate and the base plate to separate the first bending part, the second bending part and the third bending part.

(7) Preferably, the dividing holes extend from the connecting plate to the base plate, an auxiliary supporting plate is formed between adjacent dividing holes in a dividing manner, and the auxiliary supporting plate is provided with a fourth bending part that allows the auxiliary supporting plate to

be folded and attached.

(8) Preferably, the fourth bending part is parallel to the first bending part.

(9) Preferably, the dividing holes are parallel to each other, and the dividing holes are perpendicular to the first bending part, the second bending part and the third bending part.

(10) Preferably, the included angle between the supporting plate and the back plate is in a range of 30° to 70°.

(11) Preferably, the connecting plate and the base plate are provided at least partially with magnetic attraction layers that can attract each other.

(12) Preferably, the connecting plate and the base plate are at least partially provided with a sticky adhesive layer.

(13) Preferably, an adhesive fixing layer is provided at a bottom of the base plate.

(14) The present utility model further discloses a supporting assembly, comprising a desktop stand and a supporting frame, wherein the supporting frame can be provided on a surface of the desktop stand, and the supporting frame is the supporting frame described above.

(15) The present utility model has the following beneficial effects: disclosed is a supporting frame, comprising: a base plate, configured to support the supporting frame; a connecting plate, configured to attach to and fix the base plate; a back plate, wherein a first bending part is provided between the back plate and the connecting plate; a supporting plate, wherein a second bending part is provided between the supporting plate and the back plate, a third bending part is provided between the supporting plate and the base plate, and the first bending part, the second bending part and the third bending part are parallel to each other; and when the supporting frame is bent and deformed through the first bending part, the second bending part and the third bending part, the supporting plate and the back plate are erected, the connecting plate is attached and connected to the base plate, and an included angle is formed between the supporting plate and the back plate. The present utility model further discloses a supporting assembly. The supporting frame stably supports mobile devices and is deformed into a flat-plate shape, making it simple and portable.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a schematic diagram of an embodiment of a supporting frame according to the present utility model;

(2) FIG. 2 is a schematic diagram of the folding and deformation of the embodiment shown in FIG. 1;

(3) FIG. 3 is a schematic diagram of the embodiment shown in FIG. 2 from a rear view; and

(4) FIG. 4 is a schematic diagram of a desktop stand in another embodiment of a supporting frame according to the present utility model.

DETAILED DESCRIPTION OF EMBODIMENTS

(5) To facilitate understanding of the present utility model, the present utility model will be further described in detail below in conjunction with the accompanying drawings and specific embodiments. Preferred embodiments of the present utility model are shown in the drawings. The present utility model may, however, be embodied in many different forms and is not limited to the embodiments described herein. Rather, these embodiments are provided so that this disclosure of the present utility model will be understood thoroughly and completely.

(6) It should be noted that, unless otherwise defined, all technical and scientific terms used in this specification have the same meanings as those usually understood by those skilled in the art of the present utility model. The terms used in the specification of the present utility model are merely for the purpose of describing specific embodiments, and are not intended to limit the present utility model.

(7) In the drawings, an arrow X indicates a front-rear direction, i.e., front-side and rear-side directions, an arrow Y indicates a lateral direction, i.e., left and right directions, and an arrow Z indicates a vertical direction, i.e., upper and lower directions.

(8) With reference to FIGS. 1, 2 and 3, the supporting frame comprises: a base plate 1, configured to support the supporting frame and playing a role in stably supporting; a connecting plate 2, configured to attach to and fix the base plate 1 to allow the entire supporting frame to be more solid and stable; a back plate 3, wherein a first bending part 5 is provided between the back plate 3 and the connecting plate 2, that is, the first bending part 5 can be used for folding and deformation between the back plate 3 and the connecting plate 2; a supporting plate 4, wherein a second bending part 6 is provided between the supporting plate 4 and the back plate 3, a third bending part 7 is provided between the supporting plate 4 and the base plate 3, and the first bending part 5, the second bending part 6 and the third bending part 7 are parallel to each other, so that the first bent part 5, the second bent part 6 and the third bent part 7 can be coordinated when being bent and deformed simultaneously; and when the supporting frame is bent and deformed through the first bending part, the second bending part and the third bending part, the supporting plate 4 and the back plate 3 are erected, the connecting plate 2 is attached and connected to the base plate 1, an included angle is formed between the supporting plate 4 and the back plate 3, the mobile device is supported by the erected back plate 3 and comprises a mobile phone, a tablet computer and a notebook computer, the back plate 3 can also support books, music scores and the like, and the erected supporting plate 4 can stably support the back plate 3, so that the supporting stability of the back plate 3 is enhanced.

(9) Preferably, at least two dividing holes 8 are provided between the connecting plate 2 and the base plate 1 to separate the first bending part 5, the second bending part 6 and the third bending part 7. The arrangement of the dividing holes 8 can reduce the overall weight of the supporting frame. Meanwhile, when the back plate 3 supports the mobile device, the dividing holes 8 can also serve as heat dissipation holes.

(10) Preferably, the dividing holes 8 are strip-shaped holes.

(11) Preferably, the dividing holes 8 extend from the connecting plate 2 to the base plate 1, an auxiliary supporting plate 9 is formed between adjacent dividing holes 8 in a dividing manner, and the auxiliary supporting plate 9 is provided with a fourth bending part 10 that allows the auxiliary supporting plate to be folded and attached. The auxiliary supporting plates 9 can be bent and attached by the fourth bent part 10, which plays a role in enhancing the supporting stability of the supporting frame in the front-rear direction. Since the supporting frame is folded and deformed, the attached auxiliary supporting plates 9 are projected in the front-rear direction, that is, a supporting area in the front-rear direction is increased, thereby enhancing the supporting stability of the entire supporting frame in the front-rear direction. The connecting plate 2 and the base plate 1 have a supporting contact area with a long length in the lateral direction, so that the supporting stability of the supporting frame on the whole plane is improved.

(12) Preferably, the fourth bending part 10 is parallel to the first bending part 5, so that the auxiliary supporting plate 9 can be bent and deformed more quickly along with the bending of the first bending part 5, the second bending part 6 and the third bending part 7, so that the bending and deformation speed of the entire supporting frame is increased.

(13) Preferably, the dividing holes 8 are parallel to each other, and the dividing holes 8 are perpendicular to the first bending part 5, the second bending part 6 and the third bending part 7. The dividing holes 8 are parallel to each other, so that the auxiliary supporting plates 9 can have more contact areas when they are attached to each other, thereby enhancing the supporting capability.

(14) Preferably, the included angle between the supporting plate 4 and the back plate 3 is in a range of 30° to 70°. An inclination angle of the back plate 3 is adjusted along with the change of the included angle between the supporting plate 4 and the back plate 3, so that the supporting angle of

the supported mobile device is finally adjusted, and the supporting angle of the mobile device can be adjusted.

(15) Preferably, the connecting plate 2 and the base plate 1 are provided at least partially with magnetic attraction layers that can attract each other, so that the connecting plate 2 and the base plate 1 can be attracted and attached quickly.

(16) Preferably, the connecting plate 2 and the base plate 1 are at least partially provided with a sticky adhesive layer, so that the connecting plate 2 and the base plate 1 are fixed and attached quickly.

(17) Preferably, a material of the supporting frame comprises leather or plastic.

(18) Preferably, an adhesive fixing layer is provided at a bottom of the base plate 1. A size and shape of the adhesive fixing layer are the same as those of the base plate 1, or the adhesive fixing layer extends out of the base plate 1, that is, an area of the adhesive fixing layer is greater than that of the base plate 1, so that the supporting frame can be more firmly adhered and fixed. The adhesive fixing layer is arranged to enable the supporting frame to be fixed on a vertical plane (such as a wall) so as to support an object on the vertical plane.

(19) With reference to FIGS. 2 and 4, the present utility model discloses a supporting assembly, comprising a desktop stand X1 and a supporting frame, wherein the supporting frame can be provided on a surface of the desktop stand X1, and the supporting frame is the supporting frame described above.

(20) Based on the foregoing embodiments, the present utility model provides a supporting frame, comprising: a base plate, configured to support the supporting frame; a connecting plate, configured to attach to and fix the base plate; a back plate, wherein a first bending part is provided between the back plate and the connecting plate; a supporting plate, wherein a second bending part is provided between the supporting plate and the back plate, a third bending part is provided between the supporting plate and the base plate, and the first bending part, the second bending part and the third bending part are parallel to each other; and when the supporting frame is bent and deformed through the first bending part, the second bending part and the third bending part, the supporting plate and the back plate are erected, the connecting plate is attached and connected to the base plate, and an included angle is formed between the supporting plate and the back plate. The present utility model further discloses a supporting assembly. The supporting frame stably supports mobile devices and is deformed into a flat-plate shape, making it simple and portable.

(21) The above mentioned contents are merely embodiments of the present utility model and are not intended to limit the patent scope of the present utility model. The equivalent structural transformations made by using the contents of the specification and the drawings of the present utility model, or direct or indirect applications to other related technical fields, are all included in the patent protection scope of the present utility model.

Claims

1. A supporting frame, comprising: a base plate, configured to support the supporting frame; a connecting plate, configured to attach to and fix the base plate; a back plate, wherein a first bending part is provided between the back plate and the connecting plate; a supporting plate, wherein a second bending part is provided between the supporting plate and the back plate, a third bending part is provided between the supporting plate and the base plate, and the first bending part, the second bending part and the third bending part are parallel to each other; and wherein at least two dividing holes are provided between the connecting plate and the base plate to separate the first bending part, the second bending part and the third bending part; wherein the dividing holes extend from the connecting plate to the base plate, auxiliary supporting plates are formed between adjacent dividing holes in a dividing manner, and the auxiliary supporting plates are provided with a fourth bending part that allows the auxiliary supporting plates to be folded and attached; and the auxiliary

supporting plates are integrally connected with both the base plate and the connecting plate; when the supporting frame is bent and deformed through the first bending part, the second bending part, the third bending part and the forth bending part, the supporting plate and the back plate are erected, the connecting plate is attached and connected to the base plate, the auxiliary supporting plates are folded and attached, and an included angle is formed between the supporting plate and the back plate; and during use, bottom surfaces of both the base plate and the auxiliary supporting plates are attached to a same external plane, while the erected back plate is configured to conform to a rear surface of a mobile device and provides structural support.

2. The supporting frame according to claim 1, wherein the fourth bending part is parallel to the first bending part.
 3. The supporting frame according to claim 2, wherein the dividing holes are parallel to each other, and the dividing holes are perpendicular to the first bending part, the second bending part and the third bending part.
 4. The supporting frame according to claim 3, wherein the included angle between the supporting plate and the back plate is in a range of 30° to 70°.
 5. The supporting frame according to claim 1, wherein the connecting plate and the base plate are provided at least partially with magnetic attraction layers that can attract each other.
 6. The supporting frame according to claim 1, wherein the connecting plate and the base plate are at least partially provided with a sticky adhesive layer.
 7. The supporting frame according to claim 1, wherein an adhesive fixing layer is provided at a bottom of the base plate.
-