

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402883
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yee; Kristopher et al.

Surgical instrument with linear and purse string suture staples

Abstract

A surgical stapling instrument is configured to dissect tissue, apply a linear staple line along one side of the tissue dissection and apply a suture, such as a purse string suture, to the other side of the tissue dissection. The instrument comprises an elongate shaft, first and second jaws configured to open and close and a cutting element. The instrument includes a first row of staples in each of the first and second jaws having a suture extending therethrough and a second row of staples in the second jaw. A drive member is configured to translate distally through the end effector to dissect tissue with the cutting element, drive the second row of staples into the tissue on one side of the dissection and to apply the first row of staples and suture in combination to form a purse string suture on the other side of the tissue dissection.

Inventors:	Yee; Kristopher (San Jose, CA), Cooper; Emily (San Francisco, CA), Corbet; Heath (Campbell, CA), Godin; Charles (Palo Alto, CA), Millman; Paul (Denver, CO)
Applicant:	INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)
Family ID:	82357565
Assignee:	INTUITIVE SURGICAL OPERATIONS, INC. (Sunnyvale, CA)
Appl. No.:	18/271432
Filed (or PCT Filed):	December 28, 2021
PCT No.:	PCT/US2021/065308
PCT Pub. No.:	WO2022/150212
PCT Pub. Date:	July 14, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Related U.S. Application Data

us-provisional-application US 63134961 20210108

Publication Classification

Int. Cl.: A61B17/115 (20060101); A61B17/11 (20060101); A61B17/3209 (20060101)

U.S. Cl.:

CPC A61B17/115 (20130101); A61B17/1114 (20130101); A61B17/3209 (20130101); A61B2017/1142 (20130101)

Field of Classification Search

CPC: A61B (17/115); A61B (17/105); A61B (17/068); A61B (17/072)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
75364	12/1867	Case	N/A	N/A
3792597	12/1973	Orain et al.	N/A	N/A
4305539	12/1980	Korolkov et al.	N/A	N/A
4319576	12/1981	Rothfuss	N/A	N/A
4352276	12/1981	Smith	N/A	N/A
4403892	12/1982	Kane	N/A	N/A
4407286	12/1982	Noiles et al.	N/A	N/A
4429695	12/1983	Green	N/A	N/A
4509518	12/1984	McGarry et al.	N/A	N/A
4509932	12/1984	Weible	N/A	N/A
4605001	12/1985	Rothfuss et al.	N/A	N/A
4608981	12/1985	Rothfuss et al.	N/A	N/A
4610383	12/1985	Rothfuss et al.	N/A	N/A
4633874	12/1986	Chow et al.	N/A	N/A
4767044	12/1987	Green	N/A	N/A
4809695	12/1988	Gwathmey	N/A	N/A
4848637	12/1988	Pruitt	N/A	N/A
4892244	12/1989	Fox et al.	N/A	N/A
4930503	12/1989	Pruitt	N/A	N/A
4978049	12/1989	Green	N/A	N/A
5007300	12/1990	Siva	N/A	N/A
5027834	12/1990	Pruitt	N/A	N/A
5040715	12/1990	Green et al.	N/A	N/A
5133735	12/1991	Slater et al.	N/A	N/A
5133736	12/1991	Bales, Jr. et al.	N/A	N/A

5142931	12/1991	Menahem	N/A	N/A
5147357	12/1991	Rose et al.	N/A	N/A
5180092	12/1992	Crainich	N/A	N/A
5242457	12/1992	Akopov	606/220	A61B 17/1114
5275323	12/1993	Schulze et al.	N/A	N/A
5307976	12/1993	Olson et al.	N/A	N/A
5312023	12/1993	Green et al.	N/A	N/A
5316435	12/1993	Mozingo	N/A	N/A
5334183	12/1993	Wuchinich	N/A	N/A
5342395	12/1993	Jarrett et al.	N/A	N/A
5342396	12/1993	Cook	N/A	N/A
5366133	12/1993	Geiste	N/A	N/A
5452836	12/1994	Huitema et al.	N/A	N/A
5452837	12/1994	Williamson, IV et al.	N/A	N/A
5465895	12/1994	Knodel et al.	N/A	N/A
5480089	12/1995	Blewett	N/A	N/A
5484095	12/1995	Green et al.	N/A	N/A
5484451	12/1995	Akopov et al.	N/A	N/A
5487500	12/1995	Knodel et al.	N/A	N/A
5497931	12/1995	Nakamura	N/A	N/A
5533521	12/1995	Granger	N/A	N/A
5540375	12/1995	Bolanos et al.	N/A	N/A
5554164	12/1995	Wilson et al.	N/A	N/A
5560530	12/1995	Bolanos et al.	N/A	N/A
5562239	12/1995	Boiarski et al.	N/A	N/A
5564615	12/1995	Bishop et al.	N/A	N/A
5571116	12/1995	Bolanos et al.	N/A	N/A
5571285	12/1995	Chow et al.	N/A	N/A
5573534	12/1995	Stone	N/A	N/A
5573543	12/1995	Akopov	227/176.1	A61B 17/04
5607449	12/1996	Tontarra	N/A	N/A
5615820	12/1996	Viola	N/A	N/A
5624452	12/1996	Yates	N/A	N/A
5628446	12/1996	Geiste et al.	N/A	N/A
5632432	12/1996	Schulze et al.	N/A	N/A
5651491	12/1996	Heaton et al.	N/A	N/A
5652849	12/1996	Conway et al.	N/A	N/A
5667626	12/1996	Cayford et al.	N/A	N/A
5673840	12/1996	Schulze et al.	N/A	N/A
5673842	12/1996	Bittner et al.	N/A	N/A
5676674	12/1996	Bolanos et al.	N/A	N/A
5688269	12/1996	Newton et al.	N/A	N/A
5690269	12/1996	Bolanos et al.	N/A	N/A
5693042	12/1996	Boiarski et al.	N/A	N/A
5697542	12/1996	Knodel et al.	N/A	N/A
5700270	12/1996	Peyser et al.	N/A	N/A
5700276	12/1996	Benecke	N/A	N/A
5704534	12/1997	Huitema et al.	N/A	N/A

5709680	12/1997	Yates et al.	N/A	N/A
5738474	12/1997	Blewett	N/A	N/A
5752644	12/1997	Bolanos et al.	N/A	N/A
5752973	12/1997	Kieturakis et al.	N/A	N/A
5762255	12/1997	Chrisman et al.	N/A	N/A
5762256	12/1997	Mastri et al.	N/A	N/A
5779130	12/1997	Alesi et al.	N/A	N/A
5782396	12/1997	Mastri et al.	N/A	N/A
5792135	12/1997	Madhani et al.	N/A	N/A
5820009	12/1997	Melling et al.	N/A	N/A
5826776	12/1997	Schulze et al.	N/A	N/A
5833695	12/1997	Yoon	N/A	N/A
5865361	12/1998	Milliman et al.	N/A	N/A
5871135	12/1998	Williamson, IV et al.	N/A	N/A
5911353	12/1998	Bolanos et al.	N/A	N/A
5915616	12/1998	Viola et al.	N/A	N/A
5919198	12/1998	Graves, Jr. et al.	N/A	N/A
5941442	12/1998	Geiste et al.	N/A	N/A
5954259	12/1998	Viola et al.	N/A	N/A
5959892	12/1998	Lin et al.	N/A	N/A
6032849	12/1999	Mastri et al.	N/A	N/A
6050996	12/1999	Schmaltz et al.	N/A	N/A
6079606	12/1999	Milliman et al.	N/A	N/A
6113598	12/1999	Baker	N/A	N/A
6126666	12/1999	Trapp et al.	N/A	N/A
6174309	12/2000	Wrublewski et al.	N/A	N/A
6202914	12/2000	Geiste et al.	N/A	N/A
6241139	12/2000	Milliman et al.	N/A	N/A
6250532	12/2000	Green et al.	N/A	N/A
6312426	12/2000	Goldberg et al.	N/A	N/A
6330956	12/2000	Willinger	N/A	N/A
6330965	12/2000	Milliman et al.	N/A	N/A
6488196	12/2001	Fenton, Jr.	N/A	N/A
6503259	12/2002	Huxel et al.	N/A	N/A
6582451	12/2002	Marucci et al.	N/A	N/A
6585735	12/2002	Frazier et al.	N/A	N/A
6644532	12/2002	Green et al.	N/A	N/A
6656193	12/2002	Grant et al.	N/A	N/A
6669073	12/2002	Milliman et al.	N/A	N/A
6692363	12/2003	Heutschi et al.	N/A	N/A
6770072	12/2003	Truckai et al.	N/A	N/A
6786382	12/2003	Hoffman	N/A	N/A
6817974	12/2003	Cooper et al.	N/A	N/A
6840938	12/2004	Morley et al.	N/A	N/A
6877647	12/2004	Green et al.	N/A	N/A
6905057	12/2004	Swayze et al.	N/A	N/A
6953139	12/2004	Milliman et al.	N/A	N/A
6955608	12/2004	Lutz	N/A	N/A

6959852	12/2004	Shelton, IV et al.	N/A	N/A
6964363	12/2004	Wales et al.	N/A	N/A
6978921	12/2004	Shelton, IV et al.	N/A	N/A
6978922	12/2004	Bilotti et al.	N/A	N/A
6985133	12/2005	Rodomista et al.	N/A	N/A
6986451	12/2005	Mastri et al.	N/A	N/A
6988649	12/2005	Shelton, IV et al.	N/A	N/A
7000818	12/2005	Shelton, IV et al.	N/A	N/A
7000819	12/2005	Swayze et al.	N/A	N/A
7044352	12/2005	Shelton, IV et al.	N/A	N/A
7044353	12/2005	Mastri et al.	N/A	N/A
7055731	12/2005	Shelton, IV et al.	N/A	N/A
7059508	12/2005	Shelton, IV et al.	N/A	N/A
7070083	12/2005	Jankowski	N/A	N/A
7114642	12/2005	Whitman	N/A	N/A
7128253	12/2005	Mastri et al.	N/A	N/A
7140527	12/2005	Ehrenfels et al.	N/A	N/A
7140528	12/2005	Shelton, IV et al.	N/A	N/A
7258262	12/2006	Mastri et al.	N/A	N/A
7296722	12/2006	Ivanko	N/A	N/A
7308998	12/2006	Mastri et al.	N/A	N/A
7328828	12/2007	Ortiz et al.	N/A	N/A
7380695	12/2007	Doll et al.	N/A	N/A
7380696	12/2007	Shelton, IV et al.	N/A	N/A
7398908	12/2007	Holsten et al.	N/A	N/A
7401721	12/2007	Holsten et al.	N/A	N/A
7407075	12/2007	Holsten et al.	N/A	N/A
7455676	12/2007	Holsten et al.	N/A	N/A
7472814	12/2008	Mastri et al.	N/A	N/A
7481349	12/2008	Holsten et al.	N/A	N/A
7491202	12/2008	Odom et al.	N/A	N/A
7494039	12/2008	Racenet et al.	N/A	N/A
7561141	12/2008	Shahoian et al.	N/A	N/A
7565993	12/2008	Milliman et al.	N/A	N/A
7588174	12/2008	Holsten et al.	N/A	N/A
7654431	12/2009	Hueil et al.	N/A	N/A
7658312	12/2009	Vidal et al.	N/A	N/A
7673783	12/2009	Morgan et al.	N/A	N/A
7699835	12/2009	Lee et al.	N/A	N/A
7721930	12/2009	McKenna et al.	N/A	N/A
7726539	12/2009	Holsten et al.	N/A	N/A
7770774	12/2009	Mastri et al.	N/A	N/A
7780577	12/2009	Arnold	N/A	N/A
7794475	12/2009	Hess et al.	N/A	N/A
7832611	12/2009	Boyden et al.	N/A	N/A
7837079	12/2009	Holsten et al.	N/A	N/A
7866526	12/2010	Green et al.	N/A	N/A
7942303	12/2010	Shah et al.	N/A	N/A
7950561	12/2010	Aranyi	N/A	N/A
8070035	12/2010	Holsten et al.	N/A	N/A

8083118	12/2010	Milliman et al.	N/A	N/A
8127975	12/2011	Olson et al.	N/A	N/A
8157152	12/2011	Holsten et al.	N/A	N/A
8272553	12/2011	Mastri et al.	N/A	N/A
8308042	12/2011	Aranyi	N/A	N/A
8348127	12/2012	Marczyk	N/A	N/A
8365972	12/2012	Aranyi et al.	N/A	N/A
8371492	12/2012	Aranyi et al.	N/A	N/A
8439246	12/2012	Knodel	N/A	N/A
8490851	12/2012	Blier et al.	N/A	N/A
8551091	12/2012	Couture et al.	N/A	N/A
8573465	12/2012	Shelton, IV	N/A	N/A
8579178	12/2012	Holsten et al.	N/A	N/A
8608047	12/2012	Holsten et al.	N/A	N/A
8672206	12/2013	Aranyi et al.	N/A	N/A
8672939	12/2013	Garrison	N/A	N/A
8701960	12/2013	Manoux et al.	N/A	N/A
8783541	12/2013	Shelton, IV et al.	N/A	N/A
8800841	12/2013	Ellerhorst et al.	N/A	N/A
8834518	12/2013	Faller et al.	N/A	N/A
8851355	12/2013	Aranyi et al.	N/A	N/A
8852174	12/2013	Burbank	N/A	N/A
8858547	12/2013	Brogna	N/A	N/A
8864010	12/2013	Williams	N/A	N/A
8876857	12/2013	Burbank	N/A	N/A
8905287	12/2013	Racenet et al.	N/A	N/A
8925785	12/2014	Holsten et al.	N/A	N/A
9010606	12/2014	Aranyi et al.	N/A	N/A
9016545	12/2014	Aranyi et al.	N/A	N/A
9055961	12/2014	Manzo et al.	N/A	N/A
9161807	12/2014	Garrison	N/A	N/A
9192378	12/2014	Aranyi et al.	N/A	N/A
9192379	12/2014	Aranyi et al.	N/A	N/A
9211120	12/2014	Scheib et al.	N/A	N/A
9216019	12/2014	Schmid et al.	N/A	N/A
9307986	12/2015	Hall et al.	N/A	N/A
9316267	12/2015	Lenz et al.	N/A	N/A
9345479	12/2015	Racenet et al.	N/A	N/A
9498215	12/2015	Duque et al.	N/A	N/A
9717497	12/2016	Zerkle et al.	N/A	N/A
9717498	12/2016	Aranyi et al.	N/A	N/A
9777459	12/2016	Zuritis	N/A	N/A
9936949	12/2017	Measamer et al.	N/A	N/A
10111659	12/2017	Racenet et al.	N/A	N/A
10130367	12/2017	Cappola et al.	N/A	N/A
10231732	12/2018	Racenet et al.	N/A	N/A
10231733	12/2018	Ehrenfels et al.	N/A	N/A
10285693	12/2018	Kimsey et al.	N/A	N/A
10335147	12/2018	Rector et al.	N/A	N/A
10363037	12/2018	Aronhalt et al.	N/A	N/A

10646219	12/2019	Racenet et al.	N/A	N/A
10722233	12/2019	Wellman	N/A	N/A
10828027	12/2019	Racenet et al.	N/A	N/A
10863988	12/2019	Patel et al.	N/A	N/A
10912556	12/2020	Burbank	N/A	N/A
10973517	12/2020	Wixey	N/A	N/A
11020138	12/2020	Ragosta	N/A	N/A
11166773	12/2020	Ragosta et al.	N/A	N/A
11234700	12/2021	Ragosta et al.	N/A	N/A
11439390	12/2021	Patel et al.	N/A	N/A
11504124	12/2021	Patel et al.	N/A	N/A
11517312	12/2021	Wixey	N/A	N/A
11607219	12/2022	Shelton, IV et al.	N/A	N/A
11642129	12/2022	Burbank	N/A	N/A
11696758	12/2022	Murphy et al.	N/A	N/A
11723661	12/2022	Wixey et al.	N/A	N/A
11759202	12/2022	Morgan et al.	N/A	N/A
11786325	12/2022	Mustufa et al.	N/A	N/A
11806015	12/2022	Wixey et al.	N/A	N/A
11857188	12/2023	Hites	N/A	N/A
11864762	12/2023	Wixey	N/A	N/A
11896224	12/2023	Wellman	N/A	N/A
11903583	12/2023	Burbank et al.	N/A	N/A
11944301	12/2023	Wixey et al.	N/A	N/A
11944302	12/2023	Wixey et al.	N/A	N/A
11986184	12/2023	Patel et al.	N/A	N/A
12000280	12/2023	King	N/A	N/A
12011168	12/2023	Wixey	N/A	N/A
12029426	12/2023	Millman et al.	N/A	N/A
12029473	12/2023	Whitlock et al.	N/A	N/A
12089844	12/2023	Patel et al.	N/A	N/A
12137903	12/2023	Patel et al.	N/A	N/A
12156654	12/2023	Wellman	N/A	N/A
2002/0165562	12/2001	Grant et al.	N/A	N/A
2002/0177843	12/2001	Anderson et al.	N/A	N/A
2002/0188293	12/2001	Manzo	N/A	N/A
2002/0188294	12/2001	Couture et al.	N/A	N/A
2003/0078577	12/2002	Truckai et al.	N/A	N/A
2003/0135204	12/2002	Lee et al.	N/A	N/A
2003/0144652	12/2002	Baker et al.	N/A	N/A
2003/0171747	12/2002	Kanehira et al.	N/A	N/A
2003/0181910	12/2002	Dycus et al.	N/A	N/A
2004/0006340	12/2003	Latterell et al.	N/A	N/A
2004/0049185	12/2003	Latterell et al.	N/A	N/A
2004/0143263	12/2003	Schechter et al.	N/A	N/A
2004/0232199	12/2003	Shelton et al.	N/A	N/A
2004/0267310	12/2003	Racenet et al.	N/A	N/A
2005/0006430	12/2004	Wales	N/A	N/A
2005/0006434	12/2004	Wales et al.	N/A	N/A
2005/0021027	12/2004	Shields et al.	N/A	N/A

2005/0070925	12/2004	Shelton, IV et al.	N/A	N/A
2005/0070958	12/2004	Swayze et al.	N/A	N/A
2005/0101991	12/2004	Ahlberg et al.	N/A	N/A
2005/0113826	12/2004	Johnson et al.	N/A	N/A
2005/0171533	12/2004	Latterell et al.	N/A	N/A
2005/0178813	12/2004	Swayze et al.	N/A	N/A
2005/0187576	12/2004	Whitman et al.	N/A	N/A
2005/0273084	12/2004	Hinman et al.	N/A	N/A
2005/0273085	12/2004	Hinman et al.	N/A	N/A
2006/0000868	12/2005	Shelton, IV et al.	N/A	N/A
2006/0016853	12/2005	Racenet	N/A	N/A
2006/0020287	12/2005	Lee et al.	N/A	N/A
2006/0022014	12/2005	Shelton, IV et al.	N/A	N/A
2006/0022015	12/2005	Shelton, IV et al.	N/A	N/A
2006/0024817	12/2005	Deguchi et al.	N/A	N/A
2006/0025809	12/2005	Shelton, IV	N/A	N/A
2006/0025810	12/2005	Shelton, IV	N/A	N/A
2006/0025811	12/2005	Shelton, IV	N/A	N/A
2006/0025812	12/2005	Shelton, IV	N/A	N/A
2006/0025813	12/2005	Shelton, IV et al.	N/A	N/A
2006/0025816	12/2005	Shelton, IV	N/A	N/A
2006/0049230	12/2005	Shelton, IV et al.	N/A	N/A
2006/0097026	12/2005	Shelton, IV	N/A	N/A
2006/0111209	12/2005	Hinman et al.	N/A	N/A
2006/0111210	12/2005	Hinman	N/A	N/A
2006/0124689	12/2005	Arad et al.	N/A	N/A
2006/0161190	12/2005	Gadberry et al.	N/A	N/A
2006/0190031	12/2005	Wales et al.	N/A	N/A
2006/0199999	12/2005	Ikeda et al.	N/A	N/A
2006/0217706	12/2005	Lau et al.	N/A	N/A
2006/0217709	12/2005	Couture et al.	N/A	N/A
2006/0271042	12/2005	Latterell et al.	N/A	N/A
2007/0010838	12/2006	Shelton, IV et al.	N/A	N/A
2007/0045379	12/2006	Shelton, IV	N/A	N/A
2007/0250113	12/2006	Hegeman et al.	N/A	N/A
2007/0262116	12/2006	Hueil et al.	N/A	N/A
2008/0023522	12/2007	Olson et al.	N/A	N/A
2008/0029577	12/2007	Shelton et al.	N/A	N/A
2008/0064572	12/2007	Nardone	N/A	N/A
2008/0065100	12/2007	Larkin	N/A	N/A
2008/0078804	12/2007	Shelton et al.	N/A	N/A
2008/0086114	12/2007	Schmitz et al.	N/A	N/A
2008/0093517	12/2007	Chen	N/A	N/A
2008/0108446	12/2007	Faude	N/A	N/A
2008/0161174	12/2007	Lo	N/A	N/A
2008/0196533	12/2007	Bergamasco et al.	N/A	N/A
2008/0210738	12/2007	Shelton et al.	N/A	N/A
2008/0280736	12/2007	D'Eredita	N/A	N/A
2008/0305934	12/2007	Medina	N/A	N/A

2008/0308607	12/2007	Timm et al.	N/A	N/A
2009/0181832	12/2008	Bell	N/A	N/A
2009/0277947	12/2008	Viola	N/A	N/A
2010/0006620	12/2009	Sorrentino et al.	N/A	N/A
2010/0009818	12/2009	Simonson et al.	N/A	N/A
2010/0057081	12/2009	Hanna	N/A	N/A
2010/0057085	12/2009	Holcomb et al.	N/A	N/A
2010/0076461	12/2009	Viola et al.	N/A	N/A
2010/0076474	12/2009	Yates et al.	N/A	N/A
2010/0108740	12/2009	Pastorelli et al.	N/A	N/A
2010/0145334	12/2009	Olson et al.	N/A	N/A
2010/0179545	12/2009	Twomey et al.	N/A	N/A
2010/0198248	12/2009	Vakharia	N/A	N/A
2010/0213240	12/2009	Kostrzewski	N/A	N/A
2010/0331857	12/2009	Doyle et al.	N/A	N/A
2011/0022078	12/2010	Hinman	N/A	N/A
2011/0036891	12/2010	Zemlok et al.	N/A	N/A
2011/0087238	12/2010	Wang et al.	N/A	N/A
2011/0118707	12/2010	Burbank	N/A	N/A
2011/0118778	12/2010	Burbank	N/A	N/A
2011/0121050	12/2010	Nicholas et al.	N/A	N/A
2011/0152879	12/2010	Williams	N/A	N/A
2011/0174863	12/2010	Shelton, IV et al.	N/A	N/A
2011/0186614	12/2010	Kasvikis	N/A	N/A
2011/0251612	12/2010	Faller et al.	N/A	N/A
2011/0251613	12/2010	Guerra et al.	N/A	N/A
2011/0282339	12/2010	Weizman et al.	N/A	N/A
2011/0288573	12/2010	Yates et al.	N/A	N/A
2011/0290851	12/2010	Shelton, IV	N/A	N/A
2011/0290853	12/2010	Shelton, IV et al.	N/A	N/A
2011/0290854	12/2010	Timm et al.	N/A	N/A
2011/0295270	12/2010	Giordano et al.	N/A	N/A
2011/0301603	12/2010	Kerr et al.	N/A	N/A
2011/0319886	12/2010	Chojin et al.	N/A	N/A
2012/0000962	12/2011	Racenet et al.	N/A	N/A
2012/0022584	12/2011	Donnigan et al.	N/A	N/A
2012/0071891	12/2011	Itkowitz et al.	N/A	N/A
2012/0205419	12/2011	Weir et al.	N/A	N/A
2012/0209253	12/2011	Donhowe	N/A	N/A
2012/0223121	12/2011	Viola et al.	N/A	N/A
2012/0228358	12/2011	Zemlok et al.	N/A	N/A
2012/0248167	12/2011	Flanagan et al.	N/A	N/A
2012/0255986	12/2011	Petty et al.	N/A	N/A
2012/0289999	12/2011	Frank	N/A	N/A
2012/0298719	12/2011	Shelton, IV et al.	N/A	N/A
2013/0015231	12/2012	Kostrzewski	N/A	N/A
2013/0046303	12/2012	Evans et al.	N/A	N/A
2013/0056521	12/2012	Swensgard	N/A	N/A
2013/0068821	12/2012	Huitema et al.	N/A	N/A
2013/0075448	12/2012	Schmid et al.	N/A	N/A

2013/0087599	12/2012	Krumanaker et al.	N/A	N/A
2013/0098965	12/2012	Kostrzewski et al.	N/A	N/A
2013/0126586	12/2012	Zhang et al.	N/A	N/A
2013/0148577	12/2012	Terry et al.	N/A	N/A
2013/0240604	12/2012	Knodel	N/A	N/A
2013/0248577	12/2012	Leimbach et al.	N/A	N/A
2013/0277410	12/2012	Fernandez et al.	N/A	N/A
2013/0296922	12/2012	Allen, IV et al.	N/A	N/A
2013/0327808	12/2012	Chen et al.	N/A	N/A
2014/0001236	12/2013	Shelton, IV et al.	N/A	N/A
2014/0005653	12/2013	Shelton, IV et al.	N/A	N/A
2014/0005654	12/2013	Batross et al.	N/A	N/A
2014/0005662	12/2013	Shelton, IV	N/A	N/A
2014/0021239	12/2013	Kostrzewski	N/A	N/A
2014/0025071	12/2013	Sims et al.	N/A	N/A
2014/0027492	12/2013	Williams	N/A	N/A
2014/0100569	12/2013	Lawes et al.	N/A	N/A
2014/0100600	12/2013	Kendrick	N/A	N/A
2014/0103093	12/2013	Koch, Jr. et al.	N/A	N/A
2014/0110455	12/2013	Ingmanson et al.	N/A	N/A
2014/0131418	12/2013	Kostrzewski	227/176.1	A61B 17/07292
2014/0175152	12/2013	Hess et al.	N/A	N/A
2014/0180286	12/2013	Marczyk et al.	N/A	N/A
2014/0183244	12/2013	Duque et al.	N/A	N/A
2014/0200596	12/2013	Weir et al.	N/A	N/A
2014/0200612	12/2013	Weir et al.	N/A	N/A
2014/0200851	12/2013	Weir et al.	N/A	N/A
2014/0214049	12/2013	Jeong et al.	N/A	N/A
2014/0239036	12/2013	Zerkle et al.	N/A	N/A
2014/0239044	12/2013	Hoffman	N/A	N/A
2014/0239046	12/2013	Milliman et al.	N/A	N/A
2014/0246477	12/2013	Koch, Jr. et al.	N/A	N/A
2014/0249557	12/2013	Koch, Jr. et al.	N/A	N/A
2014/0257331	12/2013	Kim et al.	N/A	N/A
2014/0263546	12/2013	Aranyi	N/A	N/A
2014/0263552	12/2013	Hall et al.	N/A	N/A
2014/0263559	12/2013	Williams et al.	N/A	N/A
2014/0263567	12/2013	Williams et al.	N/A	N/A
2014/0263569	12/2013	Williams et al.	N/A	N/A
2014/0276731	12/2013	Voegelé et al.	N/A	N/A
2014/0276776	12/2013	Parihar et al.	N/A	N/A
2014/0284372	12/2013	Kostrzewski	N/A	N/A
2014/0305989	12/2013	Parihar et al.	N/A	N/A
2014/0309666	12/2013	Shelton, IV et al.	N/A	N/A
2014/0343550	12/2013	Faller et al.	N/A	N/A
2014/0343569	12/2013	Turner	N/A	N/A
2014/0364851	12/2013	Batross et al.	N/A	N/A

2015/0018856	12/2014	Poo et al.	N/A	N/A
2015/0073746	12/2014	Gris et al.	N/A	N/A
2015/0088131	12/2014	Weisshaupt et al.	N/A	N/A
2015/0141981	12/2014	Price et al.	N/A	N/A
2015/0141993	12/2014	Schechter et al.	N/A	N/A
2015/0173756	12/2014	Baxter, III et al.	N/A	N/A
2015/0173789	12/2014	Baxter, III et al.	N/A	N/A
2015/0209030	12/2014	Kostrzewski et al.	N/A	N/A
2015/0209037	12/2014	Kostrzewski et al.	N/A	N/A
2015/0250530	12/2014	Manzo et al.	N/A	N/A
2015/0256609	12/2014	Morton et al.	N/A	N/A
2015/0272575	12/2014	Leimbach et al.	N/A	N/A
2015/0272576	12/2014	Cappola	N/A	N/A
2015/0272583	12/2014	Leimbach et al.	N/A	N/A
2015/0272606	12/2014	Nobis	N/A	N/A
2015/0297227	12/2014	Huitema et al.	N/A	N/A
2015/0297230	12/2014	Schellin et al.	N/A	N/A
2015/0297235	12/2014	Harris et al.	N/A	N/A
2015/0316431	12/2014	Collins et al.	N/A	N/A
2015/0369277	12/2014	Fevre et al.	N/A	N/A
2015/0374396	12/2014	Strobl et al.	N/A	N/A
2016/0038227	12/2015	Garrison	N/A	N/A
2016/0058441	12/2015	Morgan et al.	N/A	N/A
2016/0058450	12/2015	Shelton, IV et al.	N/A	N/A
2016/0066916	12/2015	Overmyer et al.	N/A	N/A
2016/0089148	12/2015	Harris et al.	N/A	N/A
2016/0120544	12/2015	Shelton, IV et al.	N/A	N/A
2016/0157863	12/2015	Williams et al.	N/A	N/A
2016/0174973	12/2015	Shelton, IV et al.	N/A	N/A
2016/0174977	12/2015	Lytle, IV et al.	N/A	N/A
2016/0175033	12/2015	Le	N/A	N/A
2016/0192999	12/2015	Stulen et al.	N/A	N/A
2016/0199124	12/2015	Thomas et al.	N/A	N/A
2016/0235473	12/2015	Hagland	N/A	N/A
2016/0235489	12/2015	Gombert et al.	N/A	N/A
2016/0242782	12/2015	Shelton, IV et al.	N/A	N/A
2016/0249921	12/2015	Cappola et al.	N/A	N/A
2016/0270780	12/2015	Hall et al.	N/A	N/A
2016/0287251	12/2015	Shelton, IV et al.	N/A	N/A
2016/0287316	12/2015	Worrell et al.	N/A	N/A
2016/0296226	12/2015	Kostrzewski	N/A	N/A
2016/0317216	12/2015	Hermes et al.	N/A	N/A
2016/0338764	12/2015	Krastins et al.	N/A	N/A
2017/0010578	12/2016	Miyakawa	N/A	N/A
2017/0042604	12/2016	McFarland et al.	N/A	N/A
2017/0056098	12/2016	Crews et al.	N/A	N/A
2017/0065331	12/2016	Mayer et al.	N/A	N/A
2017/0079710	12/2016	Deville et al.	N/A	N/A

2017/0097035	12/2016	Zimmerman et al.	N/A	N/A
2017/0105754	12/2016	Boudreaux et al.	N/A	N/A
2017/0135746	12/2016	Tetzlaff et al.	N/A	N/A
2017/0143335	12/2016	Gupta et al.	N/A	N/A
2017/0156788	12/2016	Johnson et al.	N/A	N/A
2017/0189028	12/2016	Aranyi	N/A	N/A
2017/0231853	12/2016	Kapadia	N/A	N/A
2017/0245857	12/2016	Shelton, IV et al.	N/A	N/A
2017/0290584	12/2016	Jasemian et al.	N/A	N/A
2017/0296172	12/2016	Harris et al.	N/A	N/A
2017/0296173	12/2016	Shelton, IV et al.	N/A	N/A
2018/0008265	12/2017	Hatanaka et al.	N/A	N/A
2018/0021042	12/2017	Nicholas et al.	N/A	N/A
2018/0078268	12/2017	Messerly et al.	N/A	N/A
2018/0125570	12/2017	Rioux	N/A	N/A
2018/0161052	12/2017	Weir et al.	N/A	N/A
2018/0168581	12/2017	Hunter et al.	N/A	N/A
2018/0168585	12/2017	Shelton, IV et al.	N/A	N/A
2018/0168620	12/2017	Huang et al.	N/A	N/A
2018/0168622	12/2017	Shelton, IV et al.	N/A	N/A
2018/0168628	12/2017	Hunter et al.	N/A	N/A
2018/0168637	12/2017	Harris et al.	N/A	N/A
2018/0168641	12/2017	Harris et al.	N/A	N/A
2018/0168642	12/2017	Shelton, IV et al.	N/A	N/A
2018/0168644	12/2017	Shelton, IV et al.	N/A	N/A
2018/0168649	12/2017	Shelton, IV et al.	N/A	N/A
2018/0168650	12/2017	Shelton, IV et al.	N/A	N/A
2018/0206844	12/2017	Harris et al.	N/A	N/A
2018/0214200	12/2017	Nanditale et al.	N/A	N/A
2018/0232951	12/2017	Alterovitz et al.	N/A	N/A
2018/0250085	12/2017	Simi et al.	N/A	N/A
2018/0296213	12/2017	Strobl	N/A	N/A
2018/0310935	12/2017	Wixey	N/A	N/A
2018/0310948	12/2017	Stamm et al.	N/A	N/A
2018/0317915	12/2017	McDonald, II	N/A	N/A
2019/0000454	12/2018	Swayze et al.	N/A	N/A
2019/0000525	12/2018	Messerly et al.	N/A	N/A
2019/0015124	12/2018	Williams et al.	N/A	N/A
2019/0029746	12/2018	Dudhedia et al.	N/A	N/A
2019/0059894	12/2018	Kumada et al.	N/A	N/A
2019/0076143	12/2018	Smith	N/A	N/A
2019/0083086	12/2018	Klaffenböck et al.	N/A	N/A
2019/0083819	12/2018	Mitchell et al.	N/A	N/A
2019/0099181	12/2018	Shelton, IV et al.	N/A	N/A
2019/0125347	12/2018	Stokes et al.	N/A	N/A
2019/0133571	12/2018	Racenet et al.	N/A	N/A
2019/0142531	12/2018	Wentworth et al.	N/A	N/A
2019/0167266	12/2018	Patel et al.	N/A	N/A

2019/0192137	12/2018	Shelton, IV et al.	N/A	N/A
2019/0201146	12/2018	Shelton, IV et al.	N/A	N/A
2019/0231350	12/2018	Scott et al.	N/A	N/A
2019/0239881	12/2018	Laurent et al.	N/A	N/A
2019/0282233	12/2018	Burbank et al.	N/A	N/A
2019/0290374	12/2018	Ramadorai	N/A	N/A
2019/0298346	12/2018	Shelton, IV et al.	N/A	N/A
2019/0298356	12/2018	Shelton, IV et al.	N/A	N/A
2019/0314107	12/2018	Worrell et al.	N/A	N/A
2019/0365458	12/2018	Whitlock et al.	N/A	N/A
2020/0205811	12/2019	Posey et al.	N/A	N/A
2021/0000557	12/2020	Mustufa et al.	N/A	N/A
2021/0153927	12/2020	Ross et al.	N/A	N/A
2021/0161529	12/2020	Wixey	N/A	N/A
2021/0177412	12/2020	Wilson et al.	N/A	N/A
2021/0177495	12/2020	Ross et al.	N/A	N/A
2021/0177500	12/2020	Khalaji	N/A	N/A
2021/0196350	12/2020	Fiebig et al.	N/A	N/A
2021/0236119	12/2020	Chavan et al.	N/A	N/A
2021/0267596	12/2020	Fanelli et al.	N/A	N/A
2021/0386427	12/2020	Millman et al.	N/A	N/A
2022/0015763	12/2021	Wixey et al.	N/A	N/A
2022/0015823	12/2021	Wilson et al.	N/A	N/A
2022/0031346	12/2021	Parks	N/A	N/A
2022/0054130	12/2021	Overmyer et al.	N/A	N/A
2022/0061836	12/2021	Parihar et al.	N/A	N/A
2022/0061840	12/2021	Hites	N/A	N/A
2022/0061841	12/2021	Wixey et al.	N/A	N/A
2022/0071632	12/2021	Patel et al.	N/A	N/A
2022/0079585	12/2021	Egan	N/A	N/A
2022/0125428	12/2021	Ragosta et al.	N/A	N/A
2022/0160358	12/2021	Wixey	N/A	N/A
2022/0167985	12/2021	George et al.	N/A	N/A
2022/0183686	12/2021	Wixey et al.	N/A	N/A
2022/0192665	12/2021	Wellman	N/A	N/A
2022/0346790	12/2021	Wellman	N/A	N/A
2022/0378537	12/2021	Hites et al.	N/A	N/A
2022/0395270	12/2021	Patel et al.	N/A	N/A
2023/0020577	12/2022	Kerver et al.	N/A	N/A
2023/0047784	12/2022	Patel et al.	N/A	N/A
2023/0052074	12/2022	Wixey	N/A	N/A
2023/0101993	12/2022	Baril et al.	N/A	N/A
2023/0120209	12/2022	Parks et al.	N/A	N/A
2023/0210527	12/2022	Shelton, IV et al.	N/A	N/A
2023/0225731	12/2022	Burbank	N/A	N/A
2023/0329711	12/2022	Wixey et al.	N/A	N/A
2024/0023961	12/2023	Wixey et al.	N/A	N/A
2024/0065690	12/2023	Jasemian et al.	N/A	N/A
2024/0081824	12/2023	Hites	N/A	N/A
2024/0108343	12/2023	Wixey	N/A	N/A

2024/0138834	12/2023	Wellman	N/A	N/A
2024/0252171	12/2023	Wixey et al.	N/A	N/A
2024/0260959	12/2023	Wixey et al.	N/A	N/A
2024/0293122	12/2023	Wixey	N/A	N/A
2024/0315761	12/2023	Whitlock et al.	N/A	N/A
2024/0335194	12/2023	Patel et al.	N/A	N/A
2024/0341766	12/2023	Millman et al.	N/A	N/A
2024/0407782	12/2023	Patel et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
103889344	12/2013	CN	N/A
104042275	12/2013	CN	N/A
105007836	12/2014	CN	N/A
105769331	12/2015	CN	N/A
106232026	12/2015	CN	N/A
106491203	12/2016	CN	N/A
107920819	12/2017	CN	N/A
108024809	12/2017	CN	N/A
112165909	12/2020	CN	N/A
694747	12/1939	DE	N/A
3724525	12/1987	DE	N/A
102012103503	12/2012	DE	N/A
0277532	12/1989	EP	N/A
0469396	12/1991	EP	N/A
0277529	12/1992	EP	N/A
0641546	12/1994	EP	N/A
0986336	12/1999	EP	N/A
1090592	12/2000	EP	N/A
1479348	12/2003	EP	N/A
1728473	12/2005	EP	N/A
1479346-81	12/2006	EP	N/A
1621141	12/2006	EP	N/A
2374419	12/2010	EP	N/A
1316290-81	12/2011	EP	N/A
2517639	12/2011	EP	N/A
2540231	12/2012	EP	N/A
1754445	12/2012	EP	N/A
2777529	12/2013	EP	N/A
2777530	12/2013	EP	N/A
2777532	12/2013	EP	N/A
2779921	12/2013	EP	N/A
2944275	12/2014	EP	N/A
2992834	12/2015	EP	N/A
2992849	12/2015	EP	N/A
3000408	12/2015	EP	N/A
3120780	12/2016	EP	N/A
3135225	12/2016	EP	N/A
3158947	12/2016	EP	N/A

3173029	12/2016	EP	N/A
3205291	12/2016	EP	N/A
3338703	12/2017	EP	N/A
2828952	12/2004	FR	N/A
S5794132	12/1981	JP	N/A
2001170069	12/2000	JP	N/A
5301166	12/2012	JP	N/A
2014530653	12/2013	JP	N/A
2016508792	12/2015	JP	N/A
2016513570	12/2015	JP	N/A
2017500146	12/2016	JP	N/A
2017513564	12/2016	JP	N/A
2017527396	12/2016	JP	N/A
6411461	12/2017	JP	N/A
2019141659	12/2018	JP	N/A
405234	12/1974	SU	N/A
886900	12/1980	SU	N/A
1333319	12/1986	SU	N/A
1442191	12/1987	SU	N/A
1459659	12/1988	SU	N/A
WO-8602254	12/1985	WO	N/A
WO-9005489	12/1989	WO	N/A
WO-9734533	12/1996	WO	N/A
WO-03094743	12/2002	WO	N/A
WO-03094746	12/2002	WO	N/A
WO-03094747	12/2002	WO	N/A
WO-2004020859	12/2003	WO	N/A
WO-2009112802	12/2008	WO	N/A
WO-2012142872	12/2011	WO	N/A
WO-2014106275	12/2013	WO	N/A
WO-2016073538	12/2015	WO	N/A
WO-2017026141	12/2016	WO	N/A
WO-2017034803	12/2016	WO	N/A
WO-2017156070	12/2016	WO	N/A
WO-2017214243	12/2016	WO	N/A
WO-2018005750	12/2017	WO	N/A
WO-2018071497	12/2017	WO	N/A
WO-2018118402	12/2017	WO	N/A
WO-2019090047	12/2018	WO	N/A
WO-2020081960	12/2019	WO	N/A
WO-2020131685	12/2019	WO	N/A
WO-2020131692	12/2019	WO	N/A
WO-2022150215	12/2021	WO	N/A

OTHER PUBLICATIONS

Anonymous: “Slip Joint Pliers—Wikipedia,” Sep. 2017, 1 Pages. Retrieved from internet URL:https://en.wikipedia.org/w/index.php?title=split_joint_pliers&oldid=801407143. cited by applicant

Extended European Search Report for Application No. EP19757451.0, mailed on May 19, 2022, 16 pages. cited by applicant

Extended European Search Report for Application No. EP19898247.2, mailed on Jan. 10, 2023, 12 pages. cited by applicant

Extended European Search Report for Application No. EP19900059.7, mailed on Dec. 5, 2022, 10 pages. cited by applicant

Extended European Search Report for Application No. EP20790773.4, mailed on Nov. 29, 2022, 09 pages. cited by applicant

Extended European Search Report for Application No. EP20815112.6, mailed on Jan. 5, 2023, 11 pages. cited by applicant

Extended European Search Report for Application No. EP20875978.7, mailed on Jan. 31, 2024, 26 pages. cited by applicant

Extended European Search Report for Application No. EP24155564.8, mailed on Jul. 8, 2024, 12 pages. cited by applicant

European Search Report (Corrected version) for Application No. EP19750317.0, mailed on Mar. 28, 2022, 26 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2020/054568. mailed Jan. 29, 2021, 13 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2019/017646, mailed on Aug. 27, 2020, 10 pages. cited by applicant

International Preliminary Report on Patentability for Application No. PCT/US2019/019501, mailed Sep. 3, 2020, 7 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2020/025655, mailed Jul. 22, 2020, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US19/17646, mailed on Apr. 16, 2019, 11 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/019501. mailed May 9, 2019, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/056979, mailed Dec. 18, 2019, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/062344, mailed Mar. 23, 2020, 17 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/062768, mailed Mar. 9, 2020, 15 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/064861, mailed Mar. 30, 2020, 18 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/066513, mailed Apr. 21, 2020, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2019/066530, mailed Apr. 21, 2020, 8 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US202 1/065544 mailed Jun. 2, 2022, 21 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2020/020672, mailed Jun. 29, 2020, 10 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2020/033481, mailed Sep. 3, 2020, 22 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2021/012284 mailed May 6, 2021, 23 pages. cited by applicant

Partial European Search Report for Application No. EP19757451.0, mailed on Feb. 2, 2022, 12 pages. cited by applicant

Supplementary European Search Report for Application No. EP19873128.3, mailed on Jun. 22, 2022, 7 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2021/065308, mailed Apr. 21, 2022, 13 pages. cited by applicant

Vertut, J, and Coiffet, P., "Robot Technology: Teleoperation and Robotics Evolution and Development," English translation, Prentice-Hall, Inc., Inglewood Cliffs, NJ, USA 1986, vol. 3A, 332 pages. cited by applicant

Field Application Note—Journal Bearings, Retrieved from Wayback Machine URL: <https://web.archive.org/web/20100110095051/http://www.reliabilitydirect.com/appnotes/jb.html>, on Mar. 12, 2024, 04 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2016/059527, mailed on Feb. 16, 2017, 13 pages. cited by applicant

Nicholson, C., et al., "Plane Bearings," ESC Report, BSA Educational Services Committee, Oct. 1994, vol. 5(1), 02 pages. cited by applicant

Burstein M.D., "8 MM Sureform 30 Staplers and Reloads," Sages, Jun. 2022, 1 Page. Retrieved from internet URL: https://www.accessdata.fda.gov/cdrh_docs/pdf21/K211997.pdf. cited by applicant

Extended European Search Report for Application No. EP18823002.3 mailed on Mar. 5, 2021, 11 pages. cited by applicant

International Search Report and Written Opinion for Application No. PCT/US2018/039912, mailed on Oct. 12, 2018, 15 pages. cited by applicant

Jaggi A., "8 mm SureForm 30 Curved-Tip Stapler, 8 mm SureForm 30 Stapler, SureForm 30 Reloads," U.S Food & Drug Administration, Dec. 2021. 11 pages. Retrieved from the internet URL: <https://www.sages.org/publications/tavac/8-mm-sureform-30-staplers-and-reloads/>. cited by applicant

Primary Examiner: Chukwurah; Nathaniel C

Attorney, Agent or Firm: Farber LLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is the National Stage of International Application No. PCT/US21/65308, filed on Dec. 28, 2021, which claims benefit of U.S. Provisional Application No. 63/134,961, filed Jan. 8, 2021, the entire disclosure of which is incorporated herein by reference for all purposes.

BACKGROUND

(1) Minimally invasive medical techniques are intended to reduce the amount of extraneous tissue that is damaged during diagnostic or surgical procedures, thereby reducing patient recovery time, discomfort, and deleterious side effects. One effect of minimally invasive surgery, for example, is reduced post-operative hospital recovery times. The average hospital stay for a standard open surgery is typically significantly longer than the average stay for an analogous minimally invasive surgery (MIS). Thus, increased use of MIS could save millions of dollars in hospital costs each year. While many of the surgeries performed each year in the United States could potentially be performed in a minimally invasive manner, only a portion of the current surgeries uses these advantageous techniques due to limitations in minimally invasive surgical instruments and the additional surgical training involved in mastering them.

(2) Improved surgical instruments such as tissue access, navigation, dissection and sealing instruments have enabled MIS to redefine the field of surgery. These instruments allow surgeries and diagnostic procedures to be performed with reduced trauma to the patient. A common form of

minimally invasive surgery is endoscopy, and a common form of endoscopy is laparoscopy, which is minimally invasive inspection and surgery inside the abdominal cavity. In standard laparoscopic surgery, a patient's abdomen is insufflated with gas, and cannula sleeves are passed through small (approximately one-half inch or less) incisions to provide entry ports for laparoscopic instruments. (3) Laparoscopic surgical instruments generally include an endoscope (e.g., laparoscope) for viewing the surgical field and tools for working at the surgical site. The working tools are typically similar to those used in conventional (open) surgery, except that the working end or end effector of each tool is separated from its handle by an extension tube (also known as, e.g., an instrument shaft or a main shaft). The end effector can include, for example, a clamp, grasper, scissor, stapler, cautery tool, linear cutter, or needle holder.

(4) To perform surgical procedures, the surgeon passes working tools through cannula sleeves to an internal surgical site and manipulates them from outside the abdomen. The surgeon views the procedure from a monitor that displays an image of the surgical site taken from the endoscope. Similar endoscopic techniques are employed in, for example, arthroscopy, retroperitoneoscopy, pelviscopy, nephroscopy, cystoscopy, cisternoscopy, sinoscopy, hysteroscopy, urethroscopy, and the like.

(5) Minimally invasive telesurgical robotic systems are being developed to increase a surgeon's dexterity when working on an internal surgical site, as well as to allow a surgeon to operate on a patient from a remote location (outside the sterile field). In a telesurgery system, the surgeon is often provided with an image of the surgical site at a control console. While viewing a three dimensional image of the surgical site on a suitable viewer or display, the surgeon performs the surgical procedures on the patient by manipulating master input or control devices of the control console, which in turn control motion of the servo-mechanically operated slave instruments.

(6) The servomechanism used for telesurgery will often accept input from two master controllers (one for each of the surgeon's hands) and may include two or more robotic arms on each of which a surgical instrument is mounted. Operative communication between master controllers and associated robotic arm and instrument assemblies is typically achieved through a control system. The control system typically includes at least one processor that relays input commands from the master controllers to the associated robotic arm and instrument assemblies and back from the instrument and arm assemblies to the associated master controllers in the case of, for example, force feedback or the like. One example of a robotic surgical system is the DA VINCI™ system commercialized by Intuitive Surgical, Inc. of Sunnyvale, California.

(7) A variety of structural arrangements have been used to support the surgical instrument at the surgical site during robotic surgery. The driven linkage or "slave" is often called a robotic surgical manipulator, and exemplary linkage arrangements for use as a robotic surgical manipulator during minimally invasive robotic surgery are described in U.S. Pat. No. 7,594,912 (filed Sep. 30, 2004), U.S. Pat. No. 6,758,843 (filed Apr. 26, 2002), U.S. Pat. No. 6,246,200 (filed Aug. 3, 1999), and U.S. Pat. No. 5,800,423 (filed Jul. 20, 1995), the full disclosures of which are incorporated herein by reference in their entirety for all purposes. These linkages often manipulate an instrument holder to which an instrument having a shaft is mounted. Such a manipulator structure can include a parallelogram linkage portion that generates motion of the instrument holder that is limited to rotation about a pitch axis that intersects a remote center of manipulation located along the length of the instrument shaft. Such a manipulator structure can also include a yaw joint that generates motion of the instrument holder that is limited to rotation about a yaw axis that is perpendicular to the pitch axis and that also intersects the remote center of manipulation. By aligning the remote center of manipulation with the incision point to the internal surgical site (for example, with a trocar or cannula at an abdominal wall during laparoscopic surgery), an end effector of the surgical instrument can be positioned safely by moving the proximal end of the shaft using the manipulator linkage without imposing potentially hazardous forces against the abdominal wall. Alternative manipulator structures are described, for example, in U.S. Pat. No. 6,702,805 (filed Nov. 9, 2000),

U.S. Pat. No. 6,676,669 (filed Jan. 16, 2002), U.S. Pat. No. 5,855,583 (filed Nov. 22, 1996), U.S. Pat. No. 5,808,665 (filed Sep. 9, 1996), U.S. Pat. No. 5,445,166 (filed Apr. 6, 1994), and U.S. Pat. No. 5,184,601 (filed Aug. 5, 1991), the full disclosures of which are incorporated herein by reference in their entirety for all purposes.

(8) During the surgical procedure, the telesurgical system can provide mechanical actuation and control of a variety of surgical instruments or tools having end effectors that perform various functions for the surgeon, for example, holding or driving a needle, grasping a blood vessel, dissecting tissue, or the like, in response to manipulation of the master input devices. Manipulation and control of these end effectors is a particularly beneficial aspect of robotic surgical systems. Such mechanisms should be appropriately sized for use in a minimally invasive procedure and relatively simple in design to reduce possible points of failure. In addition, such mechanisms should provide an adequate range of motion to allow the end effector to be manipulated in a wide variety of positions.

(9) Surgical anastomosis joins together two hollow organs, usually to restore continuity after resection, or less commonly to bypass an unresectable disease process. For example, during a lower anterior resection (LAR) procedure, a portion of the intestines near the rectum is removed. The surgeon typically applies a linear staple line across the bowel to seal the healthy portion of the bowel and to resect the tissue to be removed, leaving at least one linear staple line on the distal stump of the rectum. During the anastomosis, a circular stapler is advanced through the bowel and the two remaining ends of the bowel are drawn together so that they can be joined in an anastomosis with the circular stapler.

(10) Unfortunately, there are often complications with this procedure because the linear staple line interacts with the circular stapler when the circular staple line crosses over the linear staple line to form the anastomosis. To resolve this problem, a purse string suture can be applied to the bowel to cinch the bowel and prevent or eliminate the linear and circular staple lines from crossing. The purse string suture is typically placed using a needle, staples or other suitable means for attaching the suture to the tissue. After attachment, the ends of the suture remain loose for pulling to contract or cinch close the bowel tissue.

(11) One of the drawbacks with this procedure is that the purse-string suture is difficult to perform manually (i.e., hand-sewn) in a closed abdomen procedure. In addition, the purse string hoop is typically held down via a series of knots, which makes the purse string hoop non-compliant. If the purse string hoop is too tight, it will rupture when the either the spike or the anvil posts of the circular stapler enter the purse string hoop.

(12) Another drawback with existing devices and procedures is that the distance between the linear stapler line and the transection plane (i.e., the line of dissection of the bowel) is limited by the geometry of the stapler device. In order to provide a successful interaction between the purse string suture and the circular stapler, a sufficient amount of tissue must be preserved between the purse string staples and the transection plane. This is known as a “tissue cuff”. Tissue cuff provides compliance within the purse string hoop. The more “tissue cuff” that can be achieved, the less likely there will be complications with the circular stapler. Tissue within the purse string hook makes it less likely that an interaction will occur. In addition, it provides confidence to the user that tissue will completely cover the staple zone of the circular stapler.

(13) In minimally invasive surgical anastomosis procedures, it would be advantageous to provide surgical instruments and devices that enable faster, easier and more consistent purse string suture hoops to be applied to tissue, such as bowel tissue. In addition, it would be desirable to increase the tissue cuff between the purse string suture hoop and the transection plane to facilitate the user drawing the purse string hoop closed and to minimize complications with the circular stapler performing the anastomosis.

SUMMARY

(14) The following presents a simplified summary of the claimed subject matter in order to provide

a basic understanding of some aspects of the claimed subject matter. This summary is not an extensive overview of the claimed subject matter. It is intended to neither identify key or critical elements of the claimed subject matter nor delineate the scope of the claimed subject matter. Its sole purpose is to present some concepts of the claimed subject matter in a simplified form as a prelude to the more detailed description that is presented later.

(15) In one aspect, a surgical stapling instrument comprises an elongate shaft and an end effector coupled to the distal end of the shaft and comprising first and second jaws configured to move between open and closed positions. The instrument includes a first row of staples in each of the first and second jaws having a suture extending therethrough and a second row of staples in the second jaw on an opposite side of the longitudinal axis from the first row of staples. A drive member is configured to translate distally through the end effector to drive the first and second row of staples into tissue such that the suture is disposed between the first row of staples and the tissue. The instrument may further include a cutting element coupled to the drive member and configured to dissect tissue as the drive member translates distally through the first and second jaws.

(16) The drive member is preferably configured to drive the first row of staples into tissue such that the suture, in combination with the staples, forms a purse string with the tissue. This is achieved by securing a suture to the outer surface of the tissue via staples that pinch the surface of the tissue.

(17) Accordingly, surgical instruments disclosed herein can simultaneously transect tissue, apply a linear staple line along one side of the tissue dissection and apply a suture, such as a purse string suture, to the other side of the tissue dissection. These instruments are particularly useful for dissection of bowel tissue. For example, the tissue dissection allows for the two ends of the bowel to be separated for eventual removal of the resected specimen. The application of the linear staple line allows the user to close one end of the specimen to prevent content spillage. The application of a purse-string suture on the other end allows the user to cinch the bowel and prepare it for eventual anastomosis after the unwanted tissue has been removed. Performing all three of these functions with a single instrument makes the entire procedure faster, easier and more consistent for the user. In addition, it minimizes complications associated with crossing staple lines when used with an end-to-end circular stapler (e.g., during bowel resection procedures).

(18) In certain embodiments, the distance between the purse string staples and the cutting element along the tissue contacting surfaces of the jaws is greater than a distance between the linear staples and the cutting element. This increases the amount of “tissue cuff” between the resection line and the purse string staples, thereby minimizing complications between the purse string staples and the circular stapler during the anastomosis.

(19) In one such embodiment, the cutting element is disposed laterally from the longitudinal axis on an opposite side from the purse string suture staples. Thus, the distance between the cutting element and the purse string staples is increased, thereby increasing the size of the tissue cuff.

(20) In another embodiment, the purse string staples in the first and second jaws are oriented at a transverse angle relative to the longitudinal axis of the shaft such that one of the staple legs of each staple is distal to the other staple leg. This configuration angles the purse string staples away from the transection line, thereby increasing the size of the tissue cuff.

(21) In yet another embodiment, the first and second jaws each comprise an angled portion on their tissue contacting surfaces that extends downwardly from a first axis to a second axis. The first axis is closer to the upper portion of the shaft than the second axis. The angled portion of the tissue contacting surfaces extends downwardly from the cutting element towards the purse string staples. This creates a jog in the plane in which the tissue sits between the jaws of the device, thereby increasing the length of the tissue contacting surfaces between the cutting element and the purse string staples.

(22) The surgical instruments may include one of the above embodiments, all of them, or any combination of them.

(23) The first row of staples in the first jaw may be offset longitudinally from the first row of

staples in the second jaw such that each staple in the first jaw is disposed between two staples in the second jaw in the longitudinal direction (and vice versa). This allows the staples in the first jaw to be positioned closer to the staples in the second jaw in the pre-fired position (i.e., before the staples are driven into tissue). Offsetting the staples in this manner provides more space in the jaws, thereby providing a more compact and maneuverable instrument.

(24) The instrument may further comprise a cartridge removably coupled to the first and second jaws. The cartridge includes a shuttle configured to engage the first row of staples in the second jaw and the second row of staples as the drive member is translated distally through the first and second jaws. The shuttle engages the staples and drives them into tissue. The drive member may comprise a distal portion configured to engage the first row of staples in the first jaw as the drive member is translated distally through the first and second jaws. This distal portion may be integral with the drive member and is configured to drive the staples into tissue.

(25) The drive member may comprise a main body and a lateral portion extending laterally outward from the main body. The lateral portion includes one or more distal inclined ramps configured for engaging the staples in the first jaw to drive them into tissue. The lateral portion may be integral with the drive member, which eliminates the requirement for a separate shuttle in the staple cartridge for actuating the row of staples in the first jaw. This creates more space in the suture cartridge, thereby allowing for the design of a more compact and maneuverable instrument.

(26) The instrument may further comprise an actuation mechanism configured to translate the drive member distally through the end effector. The actuation mechanism may be coupled to a control device of a robotic telesurgical system that may, for example, allow for mechanical actuation and control of the surgical instrument to perform a variety of functions, such as closing the jaws, dissecting and stapling tissue, or the like, in response to manipulation of master input devices located remotely from the surgical instrument.

(27) In another aspect, a surgical stapling instrument comprises an elongate shaft and an end effector coupled to the distal end of the shaft having first and second jaws configured to move between open and closed positions. The instrument includes a first row of staples in each of the first and second jaws with a suture extending therethrough. A suture holding member is disposed within the end effector such that at least one of the free ends of the suture is coupled to the suture holding member. A drive member is configured to translate distally through the first and second jaws to drive the first and second rows of staples into tissue such that the suture extends between the staples and the tissue.

(28) The suture holding member allows the user to apply a purse string hoop around tissue without having to tie knots to hold the purse string hoop tight, thereby making the procedure easier, faster and more consistent than conventional procedures. In addition, the suture holding member provides some degree of compliance to the purse string hoop, such that the purse string has some “give” when the circular stapler spike and/or anvil post enters the purse string hoop. This minimizes or eliminates rupture of the purse string suture when the circular stapler is performing the anastomosis. In addition, the suture holding member allows the operator to loosen the purse string hoop, if desired.

(29) In certain embodiments, the suture holding member may be configured such that both the first and second free ends of the suture extend therethrough. This allows the user to easily tighten down the purse string hoop simply by holding the suture holding member and pulling the free ends of the suture.

(30) In one such embodiment, the suture holding member comprises a tissue contacting surface and the suture extends through the suture holding member such that the first and second free ends extend substantially tangential to the tissue contacting surface. Thus, the suture extends through the suture holding member such that the first and second free ends extend away from the suture holding member in substantial opposite directions from each other. This minimizes the tension on the adjacent staples as the suture is tightened, i.e., the holding member acts as a passive pulley that

absorbs at least some of force applied by the sutures as they are pulled and tightened.

(31) In another such embodiment, the suture holding member comprises a tissue contacting surface and the suture extends through the suture holding member such that the first and second free ends extend substantially radially to the tissue contacting surface. Thus, the suture extends through the suture holding member such that the first and second free ends extend away from the suture holding member in substantial the same direction. This allows the user to tighten the purse string suture via a surgical “draw down” technique in which one hand holds the suture holding member down, while the other hand pulls both suture ends away from the holding member.

(32) The suture holding member may have a tissue contacting surface, and a second surface opposite the tissue contacting surface. The suture holding member is disposed within the end effector such that the second surface faces a distal end of the end effector when the staples have been driven into the tissue. In this manner, the suture holding member will be facing the same direction that the instrument approached the tissue after the purse string hoop has been applied to the bowel. This improves visualization of the suture holding member and positions the suture holding member closer to the user, thereby allowing the user to immediately visualize the suture holding member after the purse string hoop has been applied to the tissue. This makes it easier to tighten down the suture holding member (e.g., without having to search for the suture holding member on the other side of the bowel).

(33) The first and second jaws may each comprise a longitudinal channel for receiving a portion of the suture that is substantially parallel with the row of staples. The suture holding member is disposed proximal to the row of staples. The suture extends from the suture holding member distally through the row of staples in the first jaw, proximally through the channel in the first jaw, distally through the channel in the second jaw and then proximally through the row of staples in the second jaw such that the second free end is disposed proximally of the first row of staples. Thus, the suture forms a substantially U-shape in each of the first and second jaws, thereby allowing a user to apply the suture and suture holding member to tissue with the instrument such that the suture holding member is facing the instrument.

(34) The suture may be coupled to the suture holding member and configured to release under a threshold level of tension. This allows the suture holding member to hold the suture when tightened down and generally manipulated, but would release under some level of tension. For example, as the circular stapler enters the purse string hoop and stretches it wider, the suture holding member will release if the tension level becomes sufficiently high to rupture the purse string hoop.

(35) The suture holding member may comprise a compliant material, such as rubber or a similarly compliant material. The suture holding member may be designed with compliant features to allow such functionality. The suture may be woven through the suture holding member to create a friction fit between the suture and the holding member. This friction fit is strong enough to hold the suture holding member down against the tissue, but compliant enough to minimize or avoid rupture of the purse string hoop during the anastomosis.

(36) The suture holding member may include one or more locking elements that provide a non-linear path for the suture either through the suture holding member, or as the suture exits the holding member. The locking elements are configured to hold the suture under a certain level of tension, while providing sufficient compliance to prevent rupture of the purse string hoop during the anastomosis.

(37) The first and second ends of the suture may extend through openings in the suture holding member. The suture holding member is configured to hold the suture with friction, while allowing the suture to have some degree of movement relative to the suture holding member at a threshold force. In an exemplary embodiment, the suture has a length selected to allow the bowel to expand to its natural, unconstrained configuration with the free ends of the suture extending through the suture holding member. In one such embodiment, the free ends of the suture are coupled to each other (or designed as a loop such that there is no “free end”) to ensure that the suture does not

withdraw through the suture holding member. This allows the bowel to expand while ensuring that the suture will remain in position around the bowel and secure within the suture holding member. (38) In another embodiment, a first free end of the suture is coupled to the suture holding member, and the suture holding member comprises an opening for receiving the second free end of the suture. The opening includes an enlarged region for passing the second free end of the suture therethrough, and a narrowed slot for securing the second free end of the suture to the suture holding member. This allows the user to feed the second free end of the suture into the opening, cinch the purse string hoop tight, and then draw the suture into the narrowed slot to secure the suture and keep the purse string hoop tight throughout the remainder of the procedure. In other embodiments, the suture holding member and/or the suture includes one or more features (e.g., directional barbs on the suture, zip ties, crimps or other locking elements on the suture holding member) that allow the suture to be easily fed or pulled therethrough in one direction, while resisting movement in the opposite direction.

(39) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the disclosure. Additional features of the disclosure will be set forth in part in the description which follows or may be learned by practice of the disclosure

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of the present surgical instruments will become more apparent in light of the following detailed description when taken in conjunction with the accompanying drawings in which:

(2) FIG. 1 is a perspective view of an illustrative surgical instrument;

(3) FIG. 2A is a side view of the distal end portion of the surgical instrument of FIG. 1 having an end effector mounted to an elongated shaft;

(4) FIG. 2B illustrates the other side of the end effector of FIG. 1 with the jaws in a substantially closed position;

(5) FIG. 2C is a perspective view of the end effector of FIG. 1 with the jaws in the angled open position;

(6) FIG. 2D is a top-down view of one of the jaws of the end effector of FIG. 1;

(7) FIG. 2E is another side view of the end effector of FIG. 1, illustrating a position of staples in the jaws according to certain embodiments;

(8) FIG. 3 is an exploded view of staple cartridges for use with the surgical instrument of FIG. 1;

(9) FIG. 3A is a perspective view of a suture configured in the shape that the suture is disposed in the end effector;

(10) FIG. 4 is a perspective view of the jaws of the end effector of FIG. 1;

(11) FIG. 5 is a close-up view of one of the jaws of FIG. 4, illustrating placement of a suture relative to a row of staples in the jaw;

(12) FIG. 6A is a partial cross-sectional and partial perspective view of one embodiment of an end effector;

(13) FIG. 6B is a partial cross-sectional and partial perspective view of the end effector of FIG. 6A with parts removed;

(14) FIG. 7 is a cross-sectional view of the end effector of FIG. 1, illustrating a staple cartridge and a drive member for engaging staples within the staple cartridge;

(15) FIG. 8A is a cross-sectional view of another embodiment of the staple cartridge and the end effector;

(16) FIG. 8B is a cross-sectional view of another embodiment of the staple cartridge and the end

effector;

(17) FIG. 9 is a cross-sectional view of yet another embodiment of the staple cartridge and the end effector;

(18) FIG. 10 is a perspective view of a shuttle for engaging staples within the staple cartridge;

(19) FIG. 11A is a perspective view of a drive member for actuating the end effector;

(20) FIG. 11B is a front view of the drive member of FIG. 11A;

(21) FIG. 11C is a side view of the drive member of FIG. 11A;

(22) FIG. 12 is a partial cross-sectional view of the jaw closure mechanism of the surgical instrument of FIG. 1;

(23) FIG. 13 is a perspective view of the first and second links of the jaw closure mechanism;

(24) FIG. 14 is a perspective view of a portion of a jaw of the surgical instrument of FIG. 1;

(25) FIG. 15 is a perspective view of the articulation mechanism of the surgical instrument of FIG. 1 with parts removed to reveal internal structures;

(26) FIG. 16 illustrates a top view of an operating room employing a robotic surgical system;

(27) FIG. 17 illustrates a simplified side view of a robotic arm assembly that is usable various devices disclosed herein;

(28) FIG. 18A illustrates a suture holding member for retaining a suture against tissue;

(29) FIG. 18B illustrates the suture holding member of FIG. 18A being used to cinch representative tissue;

(30) FIG. 19A illustrates another embodiment of a suture holding member;

(31) FIG. 19B illustrates the suture holding member of FIG. 19A being used to cinch representative tissue;

(32) FIGS. 20A-20C illustrate other embodiments of a suture holding member with a locking element;

(33) FIG. 21 illustrates another embodiment of a suture holding member with a locking element;

(34) FIG. 22 illustrates a wrap-around suture holding member;

(35) FIG. 23 illustrates a “feed and cinch” embodiment of a suture holding member;

(36) FIG. 24 illustrates another embodiment of a “feed and cinch” suture holding member;

(37) FIG. 25 illustrates yet another embodiment of a “feed and cinch” suture holding member;

(38) FIG. 26 illustrates a locking lasso embodiment of a suture holding member;

(39) FIG. 27 illustrates a “wrap and cinch” anchor suture holding member;

(40) FIGS. 28A and 28B illustrate one-step feed suture holding members;

(41) FIGS. 29A and 29B schematically illustrate a method of resecting tissue in a lower anterior resection (LAR) procedure;

(42) FIG. 30 schematically illustrates a linear staple line and a purse string staple hoop placed onto two sections of the bowel; and

(43) FIGS. 31A and 31B schematically illustrate a surgical instrument placing a purse string suture hoop onto tissue.

DETAILED DESCRIPTION

(44) Particular embodiments of the present surgical instruments are described hereinbelow with reference to the accompanying drawings; however, it is to be understood that the disclosed embodiments are merely exemplary of the disclosure and may be embodied in various forms. Therefore, specific structural and functional details disclosed herein are not to be interpreted as limiting, but merely as a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present disclosure in virtually any appropriately detailed structure. Well-known functions or constructions are not described in detail to avoid obscuring the present disclosure in any unnecessary detail. Like numbers in two or more figures represent the same or similar elements. Furthermore, elements and their associated aspects that are described in detail with reference to one embodiment may, whenever practical, be included in other embodiments in which they are not specifically shown or described. For example, if an element is

described in detail with reference to one embodiment and is not described with reference to a second embodiment, the element may nevertheless be claimed as included in the second embodiment. Moreover, the depictions herein are for illustrative purposes only and do not necessarily reflect the actual shape, size, or dimensions of the system or illustrated components.

(45) While the following is presented with respect to a surgical instrument for forming purse strings and linear staples, it should be understood that certain features of the presently described surgical instruments may be readily adapted for use in any type of surgical clamping, cutting, or sealing instruments. In addition the surgical clamping and cutting instrument may be a minimally invasive (e.g., laparoscopic) instrument or an instrument used for open surgery.

(46) Additionally, the features of the presently described surgical stapling instruments may be readily adapted for use in surgical instruments that are activated using any technique within the purview of those skilled in the art, such as, for example, manually activated surgical instruments, powered surgical instruments (e.g., electro-mechanically powered instruments), robotic surgical instruments, and the like.

(47) FIG. 1 is a perspective view of an illustrative surgical instrument **100** having a backend mechanism **120**, and an end effector **110** with first and second jaws **111**, **112** mounted on an elongated shaft **106**. Backend mechanism **120** typically provides a mechanical coupling between the drive tendons or cables of the instrument and motorized axes of the mechanical interface of a drive system. Further details of known backend mechanisms and surgical systems are described, for example, in U.S. Pat. Nos. 8,597,280, 7,048,745, and 10,016,244. Each of these patents is hereby incorporated by reference in its entirety.

(48) Actuation mechanisms of surgical instrument **100** employ drive cables that are used in conjunction with a system of motors and pulleys. Powered surgical systems, including robotic surgical systems that utilize drive cables connected to a system of motors and pulleys for various functions including opening and closing of jaws, as well as for movement and actuation of end effectors are well known. Further details of known drive cable surgical systems are described, for example, in U.S. Pat. Nos. 7,666,191 and 9,050,119 both of which are hereby incorporated by reference in their entireties.

(49) FIGS. 2A-2E illustrate the distal end portion of surgical instrument **100**, including an end effector **110** defining a longitudinal axis X-X and having a first jaw **111**, a second jaw **112**, a lower cartridge **122a**, an upper cartridge **122b**, a clevis **140** for mounting jaws **111**, **112** to the instrument, and an articulation mechanism, such as wrist **160**. First and second jaws **111**, **112** are configured to move from an open position (FIGS. 2C and 2E) to a closed position (FIGS. 2A and 2B). In certain embodiments, second jaw **112** is a movable jaw configured to move from an open position to a closed position relative to first jaw **111**. In other embodiments, first jaw **111** is a movable jaw configured to move between open and closed positions relative to second jaw **112**. In still other embodiments, both jaws **111**, **112** are movable relative to each other. In the open position, fresh stapling cartridges **122a**, **122b** (sometimes referred to as reloads and shown more clearly in FIG. 3) can be loaded into jaws **111**, **112** and tissue may be positioned between the jaws **111**, **112**. In the closed position, jaws **111**, **112** cooperate to clamp, sever and staple tissue, as discussed in more detail below.

(50) In certain embodiments, jaws **111**, **112** are attached to surgical instrument **100** via a suitable coupling device, such as a clevis **140** (see also FIG. 15). Clevis **140** includes an opening for receiving a pivot pin **114** defining a pivot axis around which jaw **112** pivots. A more complete description of a suitable clevis **140** for use with the devices disclosed herein may be found in commonly-assigned, provisional patent application Nos.: 62/783,444, filed Dec. 21, 2018; 62/783,481, filed Dec. 21, 2018; 62/783,460, filed Dec. 21, 2018; 62/747,912, filed Oct. 19, 2018; and 62/783,429, filed Dec. 21, 2018, the complete disclosures of which are hereby incorporated by reference in their entirety for all purposes. Of course, it will be recognized by those skilled in the art that other coupling mechanisms known by those skilled in the art may be used to attach the jaws

111, 112 to shaft **106** of surgical instrument **100**.

(51) Referring now to FIGS. **2D** and **3**, lower cartridge **122a** includes an elongate body designed to fit within a cavity **125** of lower jaw **112** such that lower cartridge **122a** is removably coupled to jaw **112**. Alternatively, the entire lower jaw **112** may comprise the cartridge and cartridge **122a** will be removably attached to a proximal portion of end effector **110**. Lower cartridge **122a** includes first and second sides **123a, 123b** at least partially separated by a center knife channel **153** (see FIG. **7**). Side **123a** defines a tissue contacting surface **198a** and includes staple retaining pockets **133a** and side **123b** defines a tissue contacting surface **198b** and includes staple retaining pockets **133b**. Side **123b** further includes suture retaining channels (not shown) formed therein for retaining a suture **129**. In certain embodiments, tissue contacting surfaces **198a, 198b** may further include protrusions (not shown) positioned about staple receiving pockets **133a, 133b**. Protrusions help to further secure clamped tissue and to resist movement that might be induced from forces created by the severing and stapling of clamped tissue.

(52) Side **123a** of lower cartridge **122a** further includes a plurality of staple assemblies, each comprising one or more staples **124** supported on corresponding staple drivers or pushers **126** provided within staple receiving pockets **133a**. Staple receiving pockets **133a** may be cutouts that are substantially parallel to the longitudinal axis X-X of end effector **110**, and similar in length to the desired size of staples **124** to be fired.

(53) The staple assemblies may be designed to have one row of staples **124**, two rows of staples **124** oriented parallel to each other along the longitudinal axis of end effector **110**, or three or more rows of staples **124**. In an exemplary embodiment, each staple assembly includes three staples oriented to form two linear rows of staples extending along side **123a** of lower cartridge **122a**. The term “linear staple” generally means that the staples extend substantially parallel to the longitudinal axis X-X of the end effector such that a linear staple line is applied to the tissue along this axis. The staple assemblies are preferably arranged within the compartments such that staple pushers **126** are situated near a bottom surface of lower cartridge **122a** and staples **124** have their legs facing a top surface of cartridge **122a**. For ease of reference, the top surface of cartridge **122a** faces jaw **111** (see FIG. **2B**).

(54) Side **123b** of lower cartridge **122a** includes a row of staples **127a** supported on corresponding staple drivers or pushers **128a** provided within staple receiving pockets **133b**. Staple receiving pockets **133b** may be cutouts that are disposed at a partially or completely transverse angle to the longitudinal axis of end effector **110**, and similar in length to the desired size of staples **127a** to be fired. Side **123b** of lower cartridge **122a** further includes suture retaining channels **159a, 159b** that extend substantially parallel to the longitudinal axis of end effector **110** (see FIGS. **4** and **5**). Suture retaining channel **159a** is substantially aligned with the center of staple receiving pockets **133b** so that upon firing of staples **127a**, a portion of suture **129** is captured at various locations between staples **127a** and the tissue, as described in more detail below. Suture retaining channel **159b** extends parallel to channel **159a**, but is offset from staple receiving pockets **133b** so that a portion of suture **129** extends through channel **159b** without being received within staples **127a** during firing. This configuration allows suture **129** to form a substantially U-shape within lower cartridge **122a** (discussed in more detail below and shown in FIGS. **3A** and **5**).

(55) Upper cartridge **122b** also includes an elongate body designed to fit within a longitudinal cavity in upper jaw **11** (not shown). Alternatively, the entire jaw **111** may comprise upper cartridge **122b**. Similar to lower cartridge **122a**, upper cartridge **122b** includes a row of staples **127b** supported on corresponding staple drivers or pushers **128b** provided within staple receiving pockets **133c**. Staple receiving pockets **133c** may be cutouts that are partially or completely transverse to the longitudinal axis of end effector **110**, and similar in length to the desired size of staples **127b** to be fired. Upper cartridge **122b** further includes suture retaining channels **159c, 159d** that extend substantially parallel to the longitudinal axis of end effector **110** (see FIGS. **4** and **6B**). Suture retaining channel **159c** is substantially aligned with the center of the staple receiving pockets **133c**

so that upon firing of staples **127b**, a portion of suture **129** is captured at various locations between staples **127b** and the tissue, as described in more detail below. Suture retaining channel **159d** extends parallel to channel **159c**, but is offset from staples **127b** so that a portion of suture **129** extends through channel **159d** without being received within staples **127b** during firing. This configuration allows suture **129** to form a substantially U-shape within upper and lower cartridges **122a**, **122b** (discussed in more detail below and shown in FIG. 3).

(56) At least a portion of upper cartridge **122b** is disposed over side **123b** of lower cartridge **122a** such that staples **127a**, **127b** are fired on either side of the end effector and suture **129** is captured between staples **127a**, **127b** and the tissue. This configuration allows for the placement of staples **127a**, **127b** and suture **129** around a tubular tissue or organ, such as bowel tissue, in the form of a purse string suture hoop, as discussed in more detail below. In certain embodiments, upper cartridge **122b** fits into a longitudinal cavity on one side of jaw **111**, and the other side of jaw **111** includes an anvil with staple forming pockets (not shown) for receiving linear staples **124**. In other embodiments, the upper cartridge **122b** includes the entire upper portion of jaw (including the anvil and staple forming pockets).

(57) Referring now to FIG. 2E, staple drivers **128b** in upper cartridge **122b** are preferably offset in the longitudinal direction from staple drivers **128a** in lower cartridge **122a**. This allows staples **127a** in lower jaw **112** to be positioned closer to staples **127b** in upper jaw **111** in the pre-fired position (i.e., before the staples are driven into tissue). Offsetting the staples in this manner provides more space in the jaws, thereby providing a more compact and maneuverable instrument. Note that only one staple **127a** is shown in FIG. 2E although it will be recognized that each of the staple drivers **128a**, **128b** has a corresponding staple coupled thereto.

(58) As best shown in FIGS. 2A, 2B and 2E, in certain embodiments, upper jaw **111** (or in some embodiments, upper cartridge **122b**) includes a distal end portion **190** that, upon closing of jaws **111**, **112**, overlaps a distal end portion **195** of lower cartridge **122a**. Distal end portion **190** prevents cartridges **122a**, **122b** from sliding out of the jaws after installation. Distal end portion **190** may include a flexing latch member (not shown), that upon installation of cartridges **122a**, **122b** in jaws **111**, **112** would engage with a recess (not shown) contained within jaw **111**, retaining the latch member in place until defeated by application of finger pressure to release it. Flexure would provide an over-center snap feeling between the latched and the unlatched position, such that a surgeon would be able to feel the difference between the latched and unlatched positions. It is envisioned that the latch may be held in place by any number of desired mating features, such as a protrusion, or a cutout formed on jaw **111**. In an alternative embodiment, cartridge **122a** may further include cutouts or recesses configured to engage at least one hook or other protrusion contained within jaws **111**, **112**. Upon installation, cartridge **122a** may slightly pivot such that the hooks catch within the recesses helping to retain the cartridge **122** in place.

(59) As shown in FIG. 10, lower cartridge **122a** also may include a shuttle **130** having one or more inclined distal portions **131a** that, upon distal movement, sequentially acts on staple pushers **126**, camming them towards grasped tissue thereby forcing staples **124** towards the grasped tissue. Shuttle **130** further includes inclined distal portion **131b** that, upon distal movement, sequentially acts on staple drivers **128a**, camming them towards grasped tissue thereby forcing staples **127a** towards grasped tissue. The legs of staples **127a** are positioned on either side of suture **129** and are configured to secure suture **129** to grasped tissue upon actuation of the surgical instrument. Details of the mechanism for formation of staples **127a**, **127b** to provide purse strings are described below.

(60) Referring to FIGS. 3A and 4, suture **129** preferably includes first and second free ends **129a**, **129b** disposed proximal to the rows of staples **127a** and **127b**. In certain embodiments, suture **129** is designed to extend from one free end **129a** through suture retaining channel **159a** to a distal end of lower cartridge **122a** such that it extends through sutures **127a**. Suture **129** then forms a U-shape as it passes back through suture retaining channel **159b** to the proximal end of lower cartridge **122a**. From this point, suture **129** passes upwards into suture retaining channel **159d** and extends to

the distal end of upper cartridge **122b**, where it reverses and passes proximally through suture retaining channel **159c** to second free end **129b**. In this manner, suture **129** can be installed into tissue between staples **127a**, **127b** such that it forms an open loop **630** on one side of the tissue and two free ends **129a**, **129b** on the other side (see FIGS. **31A** and **31B**). The two free ends **129a**, **129b** can then be pulled to tighten suture **129** around the tissue, as discussed in more detail below.

(61) Referring now to FIGS. **11A-11C**, a preferred embodiment of a drive member **150** may include a body, an upper shoe **152**, a lower shoe **154**, a central portion **156** and a lateral portion **159** coupled to, or integral with, upper shoe **152**. Lower shoe **154** is configured to engage shuttle **130** as drive member **150** is translated distally through lower cartridge **122a**. Lateral portion **159** includes a distal inclined surface or ramp **161** that engages with pushers **128b** of upper cartridge **122b** to drive pushers **128b** (and the associated staples **127b**) vertically or perpendicular to the longitudinal axis when drive member **150** is translated distally (see also FIG. **6B**). In a preferred embodiment, lateral portion **159** is integrated into upper shoe **152** of drive member **150**. Integrating lateral portion **159** into drive member **150** provides more flexibility in the design of staple cartridge **122b**. For example, this may allow for a reduction in the size of staple cartridge **122b** and surgical instrument **100**.

(62) Surgical instrument **100** further includes an actuation assembly that includes a drive cable (not shown) coupled to a drive rod (also not shown) that extends through a bore **158** in drive member **150**. A more complete description of suitable actuation assemblies for surgical instrument **100** can be found in co-pending, commonly assigned PCT Application Nos. PCT/US2020/54568, filed Oct. 7, 2020, and PCT/US2020/20672, filed Mar. 2, 2020, the competed disclosures of which are incorporated herein by reference in their entirety for all purposes.

(63) The drive cable is operationally connected to an actuator, which allows distal translation and proximal retraction of the actuation assembly and drive member **150**. Drive member **150** may be coupled to any known actuation mechanisms including manually-activated actuators, motor-driven or powered actuators, or other types of actuation mechanisms. Those skilled in the art will recognize that in a manually actuated instrument, the actuator may be a movable handle; in a powered instrument the actuator may be a button (not shown) that causes a motor to act on the drive rod; and in a robotic system, the actuator may be a control device such as the control devices described below in connection with FIGS. **18** and **19**. Any suitable backend actuation mechanism for driving the components of the surgical stapling instrument may be used. For additional details relating to exemplary actuation mechanisms using push/pull drive cables see, e.g., commonly assigned, co-pending International Application WO 2018/049217, the disclosure of which is hereby incorporated by reference in its entirety.

(64) Upon actuation of surgical instrument **100**, drive member **150** is pushed distally or pulled proximally through center knife channel **153** of cartridges **122a**, **122b** by the drive cable and the drive rod. Drive member **150** includes knife edge **151** positioned on main body **156** for severing clamped tissue upon distal translation of drive member **150** through center knife channel **153** during firing of surgical instrument **100**. The central position of knife channel **153** ensures that knife edge **151** severs tissue that is adjacent to and between the two portions of tissue that are stapled and sutured, as discussed below.

(65) The drive member is preferably configured to drive staples **127a**, **127b** into tissue such that suture **129**, in combination with the staples, forms a purse string with the tissue. This is achieved by securing a purse string suture to the outer surface of the bowel via staples that pinch the surface of the bowel (discussed in further detail below). Simultaneously, drive member **150** drives staples **124** into tissue on the other side of knife edge **151** to form a linear staple line in the tissue.

(66) Accordingly, the surgical instrument can simultaneously transect tissue, apply a linear staple line along one side of the tissue dissection with staples **124** and apply a suture **129**, such as a purse string suture, to the other side of the tissue dissection (in combination with staples **127a**, **127b**). The tissue dissection allows for the two ends of the bowel to be separated for eventual removal of

the resected specimen. The application of the linear staple line allows the user to close one end of the specimen to prevent content spillage. The application of a purse-string suture on the other end allows the user to cinch the bowel and prepare it for eventual anastomosis after the unwanted tissue has been removed. Performing all three of these functions with a single instrument makes the entire procedure faster, easier and more consistent for the user. In addition, it minimizes complications associated with crossing staple lines when used with an end-to-end circular stapler (e.g., during bowel resection procedures).

(67) In certain embodiments, one of the jaws **110**, **112** may include one or more indicia or visual markings one side of the jaw to differentiate the linear staple side from the purse string suture side of the jaw. The markings may be disposed on movable jaw **110**, fixed jaw **112** or both. These markings allow the operator to easily visualize and differentiate the two different sides of the instrument during a surgical procedure so that the instrument can be properly oriented with respect to the tissue that will be dissected. In some embodiments, one side of the jaw, such as the linear staple side or the purse string suture side, have such markings or indicia and the other side has no markings. In other embodiments, both sides of the jaw have different markings to clearly differentiate one from the other.

(68) The markings may include numbers (e.g., 1 for linear staple side and 2 for purse string suture or the reverse), letters (e.g., L and P or similar such letters), words, arrows, pictures, symbols, names, characters, shapes, graphics, colors and the like. For example, one side of the jaw could have the word staple and/or the other side of the jaw could have the word suture. Alternatively, one side of the jaw could be marked with a shape of a linear staple or a row of linear staples and/or the other side of the jaw could be marked with a shape of a purse string staple or a row of purse string staples. Alternatively, one side of the jaw could be marked with the overall configuration of the staples (i.e., parallel rows of linear lines indicating the linear staple side and/or a single non-linear line for the purse string side).

(69) One embodiment of a surgical instrument is shown in FIGS. **6A** and **7**. As shown, drive member **150** is configured to pass through center knife channels **153** of upper and lower suture cartridges **122a**, **122b**. Linear staples **124** are disposed laterally on one side of knife channel **153** and purse string staples **127a**, **127b** and suture **129** are disposed laterally on the other side of knife channel **153**. In this embodiment, purse string staples **127a**, **127b** are laterally offset from each other such that lower staples **127a** are disposed closer to knife channel **153** than upper staples **127b**. In another embodiment, upper and lower staples **127a**, **127b** are offset from each other in the longitudinal direction such that each lower staple **127a** is disposed between two upper staples **127b** (see FIG. **2E**). In some embodiments, upper and lower staples **127a**, **127b** are offset from each other both laterally and longitudinally. These embodiments allow staples **127a** in lower jaw **112** to be positioned closer to staple **127b** in upper jaw **111** in the pre-fired position (i.e., before the staples are driven into tissue). Offsetting the staples in this manner provides more space in the jaws, thereby providing a more compact and maneuverable instrument.

(70) FIGS. **8A** and **8B** illustrate alternative embodiments of surgical instrument **100**. In the embodiment of FIG. **8A**, staples **127a**, **127b** are disposed a substantially equal distance from knife channel **153** (i.e., they are not offset laterally from each other), but they are offset from each other in the longitudinal direction. In addition, the distance along tissue contacting surfaces **198a**, **198b** between purse string staples **127a**, **127b** and knife edge **151** is substantially equal to the distance along tissue contacting surfaces **198a**, **198b** and linear staples **124**. Note that tissue contacting surfaces **198a**, **198b** are shown schematically with the dotted horizontal line in FIG. **8A**.

(71) In the embodiment of FIG. **8B**, the distance along tissue contacting surfaces **198a**, **198b** (shown as the dotted horizontal lines) between purse string staples **127a**, **127b** and knife edge **151** is greater than the distance along tissue contacting surfaces **198a**, **198b** and linear staples **124**. Knife edge **151** is shown schematically as the dotted vertical line in FIG. **8B**. This increases the amount of “tissue cuff” between the resection plane (i.e., the line of dissection from knife edge **151**

of drive member **150**) and the purse string staples **127**, thereby minimizing complications between the purse string staples and the circular stapler during the anastomosis. Note that although only one row of linear staples **124** is shown in FIG. **6B**, it will be recognized that the instrument may contain more than one row, as is shown in FIG. **8A**.

(72) In certain embodiments, purse string staples **127a**, **127b** are disposed at a transverse angle to the longitudinal axis of end effector **110** such that one leg of each staple is disposed distally of the other leg. As shown in FIGS. **2D** and **8B**, this configuration moves purse string staples **127a**, **127b** laterally away from the longitudinal axis of end effector **110** and the knife edge **151**, thereby increasing the width of the tissue therebetween.

(73) In other embodiments, knife channel **153** is laterally offset from the central longitudinal axis of end effector **110** towards staples **124**. This disposes the knife channel **153** closer to linear staples **124** than purse string staples **127a**, **127b**, thereby increasing the width of tissue between the line of dissection and the purse string staples **127a**, **127b**.

(74) In yet another embodiment, upper and lower jaws **111**, **112** each comprise an angled portion **199a**, **199b** on their tissue contacting surfaces **198a**, **198b** that extends downwardly from knife channel **153** towards purse string staples **127a**, **127b**. This creates a jog in the plane in which the tissue sits between the jaws **111**, **112** of the device, thereby increasing the distance along tissue contacting surfaces **198a**, **198b** between knife channels **153a**, **153b** and staples **127a**, **127b**.

(75) Of course, it will be recognized that the devices disclosed herein are not limited to one or all of the above embodiments. For example, the end effector **110** may comprise all of these embodiments or any combination of these embodiments; i.e., jogged tissue plane and angles staples, angles staples and knife channels **153** offset from the axis, etc. Alternatively, the tissue cuff between the knife channels and the purse string staples may be increased in other ways, such as increasing the size of end effector **100**, decreasing the number of rows of linear staples **124** and the like. However, the embodiments of the disclosed herein have the advantage of increasing the tissue cuff without having to increase the size of end effector and/or reduce the number of rows of linear staples **124**.

(76) FIG. **9** illustrates yet another embodiment of an end effector **110**. In this embodiment, purse string staples **127a**, **127b** may be disposed at a transverse angle to the longitudinal axis of end effector **110** as in the previous embodiment shown in FIG. **8B**. In addition, or in the alternative, staples **127a**, **127b** are disposed at a transverse angle to a lateral axis of shaft (2-2) such that one leg of each staple is higher than the other leg of the staple. In addition, tissue contacting surfaces **198a**, **198b** have a second angled portion **201a**, **201b**. Angled portion **201a** extends downwards towards jaw **112** angled portion **201b** extend upwards towards jaw **111**. This configuration further increases the distance along tissue contacting surfaces **198a**, **198b** between knife channel **153** and staples **127a**, **127b**.

(77) FIG. **12** shows a portion of surgical instrument **100** configured to open and close the jaws including clevis **140**, first link member **145**, second link member **146**, and drive cables **170a**, **170b**. As shown, two drive cables **170a**, **170b** route symmetrically to the backend of surgical instrument **100**, and terminate in a knot **172** within the proximal end **141** of a first link member **145**. As cables **170a**, **170b** are pulled by the force of the motor (not shown) or via some other mechanism, first link member **145** rotates about pivot pin **143** on clevis **140**, causing a second link member **146** to rotate about pivot pin **144** on clevis **140**, thereby moving the jaws towards an open or closed position depending on which drive cable was pulled. The resulting jaw force is substantially similar to the cable pull force. One of ordinary skill will appreciate that a pair of drive cables may be present on each side, of surgical instrument **100**, each pair of drive cables including a first cable for closing a first link, and a second cable for opening the first link. Using four cables in total for opening and closing of the jaw reduces the stress on each cable, and allows for symmetrically balanced cable forces through the wrist **160** such that actuating the jaw does not impart pitch or yaw forces into the wrist. (See FIG. **10**.)

(78) As illustrated in FIGS. **13** and **14**, link member **145** includes upper outer pin **148a**, and link

member **146** includes lower outer pin **148b**. Upper outer pin **148a** is configured to be positioned within an opening of jaw **111** (not shown), while lower outer pin **148b** is configured to be positioned within an opening of jaw **112**. Link member **145** also include cam slot pin **149a** configured to engage and ride within cam slot **118** formed on jaw **111**. Cam slot **118** is designed such that the proximal portion **118a** of cam slot **118** allows for parallel closure of jaw **111**, while the distal portion **118b** of cam slot **118** allows for angular closure of jaws **111** upon rotation of link members **145**, **146** due to the force of the drive cable **170a**, **170b** upon actuation of the surgical instrument (see FIG. **15**). A second set of link members **145a**, **145b** and corresponding openings and cam slot, similar to link members **145**, **146** is present on the far side of clevis **140** jaws **111**, **112** and function similarly to link members **145**, **146**. Links members **145**, **146** also include gear teeth **147** to enforce equally symmetric motion of jaws **111**, **112**.

(79) FIG. **15** illustrates the articulation mechanism including an articulating wrist **160**, and drive cables **170c**, **170d** running from the proximal end of the instrument to wrist links **162**, **164**. Wrist **160** includes a number of links that provide a desired amount of motion, such as ± 90 degrees in a pitch or yaw direction. In embodiments, a single joint can provide up to a 90 degree angular deflection. According to an exemplary embodiment, a wrist may include a plurality of links to achieve higher ranges of motion, such as, for example, wrists having a range of motion of up to ± 180 degrees in a pitch or yaw direction. Typically, actuation elements such as, for example, pull/pull tendons or push/pull rods, and electrical conductors that are connected to a wrist and/or end effector of an instrument may extend through the elongated shaft of the instrument. Further, the actuation elements may extend through the elongated shaft and connect to a transmission mechanism that typically provides a mechanical coupling of the drive tendons to drive motors. As noted above, surgical instrument **100** may include two pairs of drive cables for opening and closing of the jaws, reducing the stress on each cable, and allowing for symmetrically balanced cable forces through wrist **160** such that actuating the jaw does not impart pitch or yaw forces into the wrist. Additionally, it is envisioned that the cables may merge within the mid-section of surgical instrument **100** such that only two cables are presented at the input capstans (not shown). This type of merging allows for a pulley to maintain cable length conservation as the wrist pitches or yaws. Additional details of other joints and wrist actuation elements usable with the embodiments disclosed herein, are disclosed in Int'l. Pub. No. WO 2015/127250A1, the entire disclosure of which is incorporated by reference herein.

(80) The present surgical instrument for applying one or more purse string sutures may be used in a robotic surgical system. FIG. **16** illustrates, as an example, a top view of an operating room employing a robotic surgical system. The robotic surgical system in this case is a robotic surgical system **300** including a Console (“C”) utilized by a Surgeon (“S”) while performing a minimally invasive diagnostic or surgical procedure, usually with assistance from one or more Assistants (“A”), on a Patient (“P”) who is lying down on an Operating table (“O”).

(81) The Console includes a monitor **304** for displaying an image of a surgical site to the Surgeon, left and right manipulatable control devices **308** and **309**, a foot pedal **305**, and a processor **302**. The control devices **308** and **309** may include any one or more of a variety of input devices such as joysticks, gloves, trigger-guns, hand-operated controllers, or the like. The processor **302** may be a dedicated computer that may be integrated into the Console or positioned next to it.

(82) The Surgeon performs a minimally invasive surgical procedure by manipulating the control devices **308** and **309** (also referred to herein as “master manipulators”) so that the processor **302** causes their respectively associated robotic arm assemblies, **328** and **329**, (also referred to herein as “slave manipulators”) to manipulate their respective removably coupled surgical instruments **338** and **339** (also referred to herein as “tools”) accordingly, while the Surgeon views the surgical site in 3-D on the Console monitor **304** as it is captured by a stereoscopic endoscope **340**.

(83) Each of the tools **338** and **339**, as well as the endoscope **340**, may be inserted through a cannula or other tool guide (not shown) into the Patient so as to extend down to the surgical site

through a corresponding minimally invasive incision such as incision **366**. Each of the robotic arms is conventionally formed of links, such as link **362**, which are coupled together and manipulated through motor controlled or active joints, such as joint **363**.

(84) The number of surgical tools used at one time and consequently, the number of robotic arms being used in the system **300** will generally depend on the diagnostic or surgical procedure and the space constraints within the operating room, among other factors. If it is necessary to change one or more of the tools being used during a procedure, the Assistant may remove the tool no longer being used from its robotic arm, and replace it with another tool **331** from a Tray ("T") in the operating room.

(85) The monitor **304** may be positioned near the Surgeon's hands so that it will display a projected image that is oriented so that the Surgeon feels that he or she is actually looking directly down onto the operating site. To that end, images of the tools **338** and **339** may appear to be located substantially where the Surgeon's hands are located.

(86) The processor **302** performs various functions in the system **300**. One important function that it performs is to translate and transfer the mechanical motion of control devices **308** and **309** to their respective robotic arms **328** and **329** through control signals over bus **310** so that the Surgeon can effectively manipulate their respective tools **338** and **339**. Another important function is to implement various control system processes as described herein.

(87) Although described as a processor, it is to be appreciated that the processor **302** may be implemented in practice by any combination of hardware, software and firmware. Also, its functions as described herein may be performed by one unit, or divided up among different components, each of which may be implemented in turn by any combination of hardware, software and firmware.

(88) For additional details on robotic surgical systems, see, e.g., U.S. Pat. Nos. 6,493,608 and 6,671,581, the entire contents of which are incorporated herein by this reference.

(89) FIG. **17** illustrates, as an example, a side view of a simplified (not necessarily in proportion or complete) illustrative robotic arm assembly **400** (which is representative of robotic arm assemblies **328** and **329**) holding a surgical instrument **450** (which is representative of tools **338** and **339**) for performing a surgical procedure. The surgical instrument **450** is removably held in tool holder **440**. The arm assembly **400** is mechanically supported by a base **401**, which may be part of a patient-side movable cart or affixed to the operating table or ceiling. It includes links **402** and **403** which are coupled together and to the base **401** through setup joints **404** and **405**.

(90) The setup joints **404** and **405** in this example are passive joints that allow manual positioning of the arm **400** when their brakes are released. For example, setup joint **404** allows link **402** to be manually rotated about axis **406**, and setup joint **405** allows link **403** to be manually rotated about axis **407**.

(91) Although only two links and two setup joints are shown in this example, more or less of each may be used as appropriate in this and other robotic arm assemblies in conjunction with the devices disclosed herein. For example, although setup joints **404** and **405** are useful for horizontal positioning of the arm **400**, additional setup joints may be included and useful for limited vertical and angular positioning of the arm **400**. For major vertical positioning of the arm **400**, however, the arm **400** may also be slidably moved along the vertical axis of the base **401** and locked in position.

(92) The robotic arm assembly **400** also includes three active joints driven by motors. A yaw joint **410** allows arm section **430** to rotate around an axis **461**, and a pitch joint **420** allows arm section **430** to rotate about an axis perpendicular to that of axis **461** and orthogonal to the plane of the drawing. The arm section **430** is configured so that sections **431** and **432** are always parallel to each other as the pitch joint **420** is rotated by its motor. As a consequence, the instrument **450** may be controllably moved by driving the yaw and pitch motors so as to pivot about the pivot point **462**, which is generally located through manual positioning of the setup joints **404** and **405** so as to be at the point of incision into the patient. In addition, an insertion gear **445** may be coupled to a linear

drive mechanism (not shown) to extend or retract the instrument **450** along its axis **463**.

(93) Although each of the yaw, pitch and insertion joints or gears, **410**, **420** and **445**, is controlled by an individual joint or gear controller, the three controllers are controlled by a common master/slave control system so that the robotic arm assembly **400** (also referred to herein as a “slave manipulator”) may be controlled through user (e.g., surgeon) manipulation of its associated master manipulator.

(94) Referring now to FIGS. **18A** and **18B**, in another aspect, a suture holding member **500** comprises one or more openings for receiving suture **129** therethrough. In certain embodiments, suture holding member **500** is disposed within end effector **100** such that at least one of the free ends **129a**, **129b** of the suture is coupled to suture holding member **100**. Suture holding member **500** allows the user to apply a purse string hoop around tissue **506** without having to tie knots to hold the purse string hoop tight, thereby making the procedure easier, faster and more consistent than conventional procedures. In addition, suture holding member **500** provides some degree of compliance to the purse string hoop, such that the purse string has some “give” when the circular stapler spike and/or anvil post enters the purse string hoop. This minimizes or eliminates rupture of the purse string suture when the circular stapler is performing the anastomosis.

(95) In certain embodiments, drive member **150** is configured to translate distally through the first and second jaws **111**, **112** to drive purse string staples **127a**, **127b** into tissue such that suture **129** extends between the staples **127a**, **127b** and tissue **506**. Suture holding member **500** has a tissue contacting surface **502**, and a second surface **504** opposite tissue contacting surface **502**. Suture holding member **500** is disposed within end effector **110** such that second surface **504** faces a distal end of end effector **110** when staples **127a**, **127b** have been driven into tissue **506** (see also FIGS. **29A** and **29B**). In this manner, suture holding member **500** will be facing the instrument after the purse string hoop has been applied to the tissue. This allows the user to immediately visualize suture holding member **500** after the purse string hoop has been applied to the tissue, thereby making it easier to tighten down the suture holding member (e.g., without having to search for the suture holding member on the other side of the bowel).

(96) In a preferred embodiment, first and second jaws **111**, **112** each comprise suture retaining channels **159a**, **159b**, **159c**, **159d** for receiving a portion of the suture that is substantially parallel with the row of staples, as discussed above and shown in FIG. **4**. Suture holding member **500** is disposed proximal to the row of staples **127a**, **127b** within end effector **110**. Suture **129** extends from the suture holding member **150** distally through the row of staples in the first jaw, proximally through the channel in the first jaw, distally through the channel in the second jaw and then proximally through the row of staples in the second jaw such that the second free end is disposed proximally of the first row of staples. Thus, the suture forms a substantially U-shape in each of the first and second jaws, thereby allowing a user to apply the suture and suture holding member to tissue with the instrument such that the suture holding member is facing the instrument.

(97) As shown in FIGS. **18A** and **18B**, suture holding member **500** is configured such that both first and second free ends **129a**, **129b** of the suture extend therethrough. This allows the user to easily tighten down the purse string hoop simply by holding suture holding member **500** and pulling the free ends **129a**, **129b** of the suture. In this embodiment, suture **129** extends through openings in suture holding member **500** such that the first and second free ends **129a**, **129b** extend substantially tangential to tissue contacting surface **502**. Thus, the suture **129** extends through suture holding member **500** such that the first and second free ends **129a**, **129b** extend away from suture holding member **500** in substantial opposite directions from each other. This minimizes the tension on the adjacent staples as the suture **129** is tightened, i.e., suture holding member **500** acts as a passive pulley that absorbs at least some of force applied by the sutures as they are pulled and tightened.

(98) In certain embodiments, suture **129** is coupled to suture holding member **500** with a friction fit configured to release under a threshold level of tension. This allows suture holding member **500** to hold the suture when tightened down and generally manipulated, but would release under some

level of tension. For example, as the circular stapler enters the purse string hoop and stretches it wider, suture holding member **500** will release if the tension level becomes sufficiently high to rupture the purse string hoop.

(99) In one such embodiment, suture holding member **500** comprises a compliant material, such as rubber or a similarly compliant material. In other embodiments, suture holding member **500** is designed with compliant features to allow such functionality. In an exemplary embodiment shown in FIGS. **18A** and **18B**, suture **129** is woven through suture holding member **500** to create friction between suture **129** and holding member **500**. This friction is preferably strong enough to generally maintain a strong enough hold on tissue **506** to keep the tissue cinched after it has been dissected, but compliant enough to minimize or avoid rupture of the purse string hoop during the anastomosis (discussed in detail below).

(100) Referring now to FIGS. **19A** and **19B**, another embodiment of a suture holding member **510** will now be described. As shown, suture holding member **510** comprises a tissue contacting surface **512** and suture **129** extends through channels **514** in suture holding member **510** such that first and second free ends **129a**, **129b** extend substantially radially to tissue **506**. Thus, suture **129** extends through suture holding member **510** such that the first and second free ends extend away from suture holding member **510** in substantially the same direction. This allows the user to tighten the purse string suture via a surgical “draw down” technique in which one hand holds suture holding member **510** down, while the other hand pulls both suture ends **129a**, **129b** away from holding member **510**.

(101) FIGS. **20A-20C** illustrate other embodiments for providing some degree of compliance to suture holding member **500**. As shown, suture holding member **500** includes a locking element **520** that forces suture **129** to be routed through a non-linear path from the opening of suture holding member **500**. This provides sufficient resistance to movement of the suture **129** to hold the suture in place while cinching the tissue. However, locking element **520** provides some degree of compliance such that suture **129** may release under a threshold level of tension, e.g., when the bowel is being opened up during the anastomosis. This embodiment allows the user to feed suture **129** through suture holding member **510**, while locking element **520** “auto locks” the position of the suture.

(102) FIG. **21** illustrates another embodiment of a suture holding member **524** that includes a locking element **526**. Similar to the previous embodiment, suture **129** can be feed through suture holding member **524** while locking member **526** auto locks suture **129** in position, while still maintaining sufficient compliance to allow expansion of the tissue during, for example, an anastomosis procedure.

(103) FIG. **22** illustrates another embodiment of a suture holding member **530**. As shown, one end **129a** of suture **129** is coupled to a suture holding member **530** while the other free end **129b** remains unattached to suture holding member **530**. This “wrapping anchor” design allows the user to take one free end of the suture and wrap it around the base of suture holding member **530**, and pull to tighten the suture and cinch the tissue. The wrapping of the suture causes the purse sting hoop to tightly hold together. The suture may be coupled to suture holding member **530** in a variety of methods, such as tying, weaving and the like.

(104) As shown in FIG. **23**, another embodiment of a suture holding member **540** comprises an opening **542** for receiving one of the free ends **129b** of suture **129**. The other free end **129a** may be coupled to suture holding member **540** in any of the methods discussed above. Opening **542** includes an enlarged region **544** for passing the free end of suture **129** therethrough, and a narrowed slot **546** for securing the free end of the suture to suture holding member **540**. This allows the user to feed the free end of the suture into the opening **542**, cinch the purse string hoop tight, and then draw the suture into the narrowed slot **546** to secure the suture and keep the purse string hoop tight throughout the remainder of the procedure.

(105) Referring now to FIGS. **24-26**, additional embodiments of suture holding members that allow

the user to feed one end of a suture therethrough and cinch it tight are provided. As shown in FIG. 24, a suture holding member **550** includes a trough **552** for receiving one end of the suture **129**. Trough **552** may include a number of locking or friction resistance elements therein to hold suture **129** and prevent it from backing out of suture holding member **550**. The other free end of suture **129** is suitably fixed to one end of suture holding member **550**.

(106) FIG. 25 illustrates a similar embodiment wherein a suture holding member **560** includes a channel **562** for receiving one free end **129b** of suture **129**. The other free end **129a** is fixed to suture holding member **560**. Channel **562** may further include a narrowed region **564** for cinching suture **129** therein.

(107) FIG. 26 illustrates a locking lasso suture holding member **570** that includes an opening **572** for receiving one end of suture **129**. In this embodiment, one end of suture **129** is formed into an open loop **574** and the other end of suture **129** is feed through loop **574** and then pulled to tighten loop **574** around suture **129** within suture holding member **570**.

(108) In yet another embodiments suture holding member can be designed as a cinch bead, a loop or similar structure. The suture has a length selected to allow the bowel to expand to its natural, unconstrained configuration with the free ends of the suture extending through the suture holding member. In one such embodiment, the free ends of the suture are coupled to each other (or designed as a loop such that there is no “free end”) to ensure that the suture does not withdraw through the suture holding member. This allows the bowel to expand while ensuring that the suture will remain in position around the bowel and secure within the suture holding member.

(109) Referring now to FIG. 27, another embodiment of a suture holding member **590** includes an anchor **592** for receiving one free end of suture **129**, while the other free end is fixed to another end **594** of suture holding member **590**. As shown, suture **129** may be wrapped around anchor **592** and then pulled to tighten suture **129** down and cinch the tissue.

(110) FIGS. 28A and 28B illustrate embodiments of a suture holding member that allow suture **129** to be fed into the suture holding member and locked with one simple step. FIG. 28A illustrates an example of a “soda tab” suture holding member **596**. FIG. 28B illustrates an example of a “Double-D” suture holding member **597**.

(111) Of course it will be recognized by those skilled in the art that the devices disclosed herein are not limited to the specific embodiments of a suture holding member described above and shown in the representative drawings. For example, suture **129** may include direction elements, such as barbs (not shown), that allow the suture to be easily fed through a suture holding member in one direction while resisting movement of the suture in the opposite direction. Alternatively, the suture holding member may include elements similar to a zip tie that allow the user to easily pull suture through the zip tie, while resisting movement in the opposite direction.

(112) FIGS. 29-31 illustrate a method of resecting tissue during, for example, a lower anterior resection (LAR). In an LAR procedure, an unhealthy portion **600** of the intestines **602** near the rectum **604** is removed. As shown in FIGS. 29A and 29B, the portion from A to B will be removed and then the two remaining portions **612** will be brought together in an anastomosis **606**.

(113) As shown in FIG. 30, the surgeon typically dissects an unhealthy portion **600** of the bowel **602** and applies a linear staple line **608** across either end of the unhealthy portion **600** of the bowel to prevent its contents from spilling out during the procedure. In addition, the surgeon will place a staple line or a purse string hoop **610** on the healthy portions **612** of the bowel to cinch these portions closed until they are brought together during the anastomosis portion of the procedure. FIG. 30 also illustrates the ability to roll the instrument around to apply the purse string to the other side of the bowl **602**. After the unhealthy portion **600** has been removed, a circular stapler **613** is advanced through the bowel **602** and the two remaining ends of the bowel are drawn together so that they can be joined in an anastomosis **606** with the circular stapler **613** (see FIG. 29B).

(114) According to one method, a surgical instrument such as one of the instruments described above, is used to place the linear staple line **608**, dissect the bowel and place a purse string suture

hoop **610** around the other portion of the bowel **602** near the distal stump of the rectum. FIGS. **31A** and **31B** illustrate one portion of this procedure, wherein a purse string suture hoop **610** is placed around the healthy portion **612** of the bowel **602**. As shown, surgical instrument **100** is maneuvered in place such that jaws **111**, **112** are placed around the tissue **612**. As the jaws **111**, **112** are closed, drive member **150** is translated distally to engage the various staple pushers within end effector **110** and dissect the tissue along knife cutting edge **151**, as discussed above. The staple pushers drive linear staples **124** into tissue on one side of the cutting edge **151** (not shown) and purse string staples **127a**, **127b** into the tissue on the other side of the cutting edge.

(115) As shown in FIG. **31A**, staples **127a** are driven into the top portion of tissue **612** and staples **127b** are driven into the bottom portion of tissue **612** to ensure that the entire circular cross-section of the bowel has staples therearound. At the same time, suture **129** is placed between staples **127a**, **127b** and the bowel tissue such that a purse string suture hoop **610** is formed around the bowel. Suture **129** includes an open loop **630** that is connected to the top and bottom portions of suture, and free ends **129a**, **129b** that pass through suture holding member **500**. With this design, suture holding member **500** is facing the instrument (and the user), thereby making it much easier for the user to visualize the suture holding member **500** and cinch the bowel.

(116) As shown in FIG. **31B**, once the purse string suture hoop **610** has been placed around the bowel, the surgeon can easily grab the two free ends **129a**, **129b** of suture **129** and pull. As the free ends **129a**, **129b** are pulled away from suture holding member **500**, suture holding member **500** provides the necessary tension to bowel **612** to cinch it closed. The open loop **630** of suture **129** is pulled through staples **127a**, **127b** until it has tightened around the bowel **612**. At this point, further pulling of the free ends **129a**, **129b** begins to cinch the bowel closed. The surgeon can then tie a knot in the free ends of suture, or tighten suture **129** using other methods described above to close the bowel until the surgeon has resected the unhealthy tissue and is ready to complete the anastomosis.

(117) The unique features of surgical instrument **100** described above provide a wider tissue cuff **650** between the line of dissection **652** and the purse string suture hoop **610**. The more “tissue cuff” that can be achieved, the more likely that there will be tissue within the purse string hoop as it is drawn closed. In addition, increasing the width of the tissue cuff **650** between the purse string sutures **127a**, **127b** and the transection plane **652** facilitates the user drawing the purse string hoop **610** closed and minimizes complications with the circular stapler performing the anastomosis.

(118) While several embodiments have been shown in the drawings, it is not intended that the disclosure be limited thereto, as it is intended that the disclosure be as broad in scope as the art will allow and that the specification be read likewise. Therefore, the above description should not be construed as limiting, but merely as exemplifications of presently disclosed embodiments. Thus, the scope of the embodiments should be determined by the appended claims and their legal equivalents, rather than by the examples given.

(119) Persons skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Various alternatives and modifications can be devised by those skilled in the art without departing from the disclosure. Accordingly, the present disclosure is intended to embrace all such alternatives, modifications and variances. As well, one skilled in the art will appreciate further features and advantages of the present disclosure based on the above-described embodiments. Accordingly, the present disclosure is not to be limited by what has been particularly shown and described, except as indicated by the appended claims.

Claims

1. A surgical stapling instrument, comprising: an elongate shaft having a longitudinal axis, a distal end, and a proximal end; an end effector coupled to the distal end of the shaft and comprising first and second jaws configured to move between open and closed positions; a first row of staples in each of the first and second jaws; a second row of staples in the second jaw on an opposite side of the longitudinal axis from the first row of staples; a suture extending through the first row of staples; and a drive member configured to translate distally through the end effector to drive the first and second row of staples into tissue such that the suture is disposed between the first row of staples and the tissue.
2. The surgical stapling instrument of claim 1, further comprising a cutting element coupled to the drive member and configured to dissect tissue as the drive member translates distally through the first and second jaws, wherein the second row of staples comprises at least two rows of linear staples.
3. The surgical stapling instrument of claim 2, wherein the first and second jaws each have a tissue contacting surface, wherein a distance between the first row of staples and the cutting element along the tissue contacting surfaces is greater than a distance between the second row of staples and the cutting element.
4. The surgical stapling instrument of claim 3, wherein the cutting element is disposed laterally from the longitudinal axis on an opposite side from the first row of staples.
5. The surgical stapling instrument of claim 3, wherein the first row of staple is oriented at a transverse angle relative to the longitudinal axis of the shaft.
6. The surgical stapling instrument of claim 3, wherein the instrument defines an upper portion and a lower portion, wherein the first and second jaws each comprise a tissue contacting surface having an angled portion that extends downwardly from a first axis to a second axis closer to the lower portion of the shaft than the first axis.
7. The surgical stapling instrument of claim 6, wherein the angled portion of the tissue contacting surfaces extends downwardly from the cutting element towards the first row of staples.
8. The surgical stapling instrument of claim 1, wherein the drive member is configured to drive the first row of staples into tissue such that the suture, in combination with the staples, forms a purse string with the tissue.
9. The surgical stapling instrument of claim 1, wherein the first row of staples in the first jaw is offset along the longitudinal axis from the first row of staples in the second jaw.
10. The surgical stapling instrument of claim 1, wherein each staple in the first row of staples in the first jaw is positioned longitudinally between two of the staples in the first row of staples in the second jaw.
11. The surgical stapling instrument of claim 1, further comprising a suture holding member within the end effector, wherein at least the first end of the suture is coupled to the holding member.
12. A surgical stapling instrument comprising: an elongate shaft having a longitudinal axis, a distal end, and a proximal end; an end effector coupled to the distal end of the shaft and having first and second jaws configured to move between open and closed positions; a row of staples in each of the first and second jaws; a suture extending through each row of staples, the suture having first and second free ends; a suture holding member within the end effector, wherein at least the first free end of the suture is coupled to the suture holding member; and a drive member configured to translate distally through the first and second jaws to drive the row of staples into tissue such that the suture extends between the staples and the tissue.
13. The surgical stapling instrument of claim 12, wherein the first and second free ends of the suture extend through the suture holding member.
14. The surgical stapling instrument of claim 13, wherein the first and second free ends of the suture extend through openings in the suture holding member, and wherein the suture is movable relative to the suture holding member.

15. The surgical stapling instrument of claim 14, wherein the tissue is a bowel tissue having a diameter in an unconstrained configuration, and wherein the suture has a length selected to allow the bowel tissue to expand to the diameter in the unconstrained configuration with the first and second free ends extending through the suture holding member.
 16. The surgical stapling instrument of claim 12, wherein the suture holding member has a tissue contacting surface, and a second surface opposite the tissue contacting surface; and wherein the suture holding member is disposed within the end effector such that the second surface faces a distal end of the end effector when the row of staples have been driven into the tissue.
 17. The surgical stapling instrument of claim 12, further comprising a channel in each of the first and second jaws for receiving a portion of the suture.
 18. The surgical stapling instrument of claim 17, wherein the suture holding member is disposed proximal to the row of staples, the suture extending from the suture holding member through the row of staples in the first jaw, through the channel in the first jaw, through the channel in the second jaw and through the row of staples in the second jaw such that the second free end is disposed proximally of the row of staples.
 19. The surgical stapling instrument of claim 18, wherein the suture forms a substantially U-shape in each of the first and second jaws.
 20. The surgical stapling instrument of claim 12, wherein the suture is coupled to the suture holding member with a friction fit configured to release under a threshold level of tension.
-