

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404097
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Chupinski; Timothy

Collapsible yard refuse bag stand

Abstract

An apparatus and method of use for a collapsible yard refuse bag stand. In a deployed configuration the collapsible refuse bag stand can hold one or more bags in an upright and open positions for the depositing of yard refuse in the one or more bags allowing for easier use of yard refuse bags by a single individual. The collapsible yard refuse bag stand can be collapsed for easier transportation and storage when not in use.

Inventors:	Chupinski; Timothy (Marlborough, MA)
Applicant:	Chupinski; Timothy (Marlborough, MA)
Family ID:	82495378
Appl. No.:	17/576534
Filed:	January 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220234820 A1	Jul. 28, 2022

Related U.S. Application Data

us-provisional-application US 63141246 20210125

Publication Classification

Int. Cl.: **B65F1/14 (20060101)**

U.S. Cl.:

CPC **B65F1/1415 (20130101);**

Field of Classification Search

CPC: B65F (1/1415); B65B (67/1205); B65B (67/1238)

USPC: 294/214

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3387134	12/1967	Treharne	338/18	G01J 5/20
3410328	12/1967	Sasai	5/98.1	B65D 7/26
4273167	12/1980	Stillwell	141/391	B65B 67/12
5671858	12/1996	Hsu	220/9.4	B65D 11/18
6076782	12/1999	Alderman	248/97	B65B 67/1205
D447845	12/2000	Neil	D34/6	B65F 1/1415
6315143	12/2000	Dotts	220/904	B65F 1/1415
6419193	12/2001	Rodriquez	248/101	B62B 3/106
7066432	12/2005	Wood	248/150	B65F 1/1415
7731134	12/2009	Mutert	248/97	B65B 67/1205
8479780	12/2012	Fernandez	141/10	B65F 1/1468
11547206	12/2022	Choi	N/A	F16B 12/32

Primary Examiner: Chin; Paul T

Attorney, Agent or Firm: Morse, Barnes-Brown & Pendleton, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application claims priority to, and the benefit of, U.S. Provisional Application 63/141,246, filed Jan. 25, 2021, for all subject matter common to both applications. The disclosure of said provisional application is hereby incorporated by reference in its entirety.

FIELD OF THE INVENTION

(1) The present invention relates to the clean-up and storage of yard refuse. In particular, the present invention relates to a collapsible yard refuse bag stand suitable for maintaining yard refuse bags in an upright and operable position to receive yard refuse.

BACKGROUND

(2) Generally, yard refuse, such as leaves, grass clippings, weeds, brush, or trimmings are collected and put into piles or transferred into containers for disposal or collection. Many municipalities have implemented the use and collection of yard refuse bags for this purpose. Such yard refuse bags are typically large paper bags designed to be filled with yard refuse for easier transportation, collection, and disposal/removal of the yard refuse.

(3) However, the use of such yard refuse bags experiences some shortcomings. Filling such yard refuse bags is typically a two-person job with one person holding the bag in an open and upright operable position while the other person transfers collected yard refuse into the bag. Without someone holding the yard bag in an upright and open operable position, the yard refuse bags tend

to close, collapse, or fall over while they are being filled.

SUMMARY

(4) There is a need for a solution to keep yard refuse bags in an open and upright operable position while depositing yard refuse in the yard refuse bag such that the task can be performed by a single individual because a second individual is not required to hold the yard refuse bag in the open and upright operable position. The present invention is directed toward further solutions to address this need, in addition to having other desirable characteristics.

(5) In accordance with an embodiment of the present invention, a collapsible yard refuse bag stand is provided. The collapsible yard refuse bag stand includes a frame and a feeder guide.

(6) The frame has a collapsed configuration and a deployed configuration. The deployed configuration is configured, sized, and dimensioned to support one or more yard refuse bags in an upright and open position. The frame includes a plurality of legs and a collapsible truss. Each leg of the plurality of legs has an upper end and a lower end. The collapsible truss is connected to each of the legs. The collapsible truss includes at least four sides. Each side is formed of a scissor linkage.

(7) The feeder guide is configured, sized, and dimensioned to fit over the truss in the deployed configuration. The feeder guide includes one or more chutes that are configured, sized, and dimensioned to extend downward from the frame on a same side of the frame as the plurality of legs. When the one or more yard refuse bags are placed in an upright position under the one or more chutes, each of the one or more chutes supports a yard refuse bag of the one or more yard refuse bags in an upright and open position in such a way that any yard refuse placed through the feeder guide is directed via gravitational force through the one or more chutes into one of the one or more yard refuse bags.

(8) In accordance with an aspect of the present invention, one of the chutes that extends downward extend into one of the yard refuse bags serves as a guide holding the yard refuse bag in place aligned under the chute.

(9) In accordance with an aspect of the present invention, the lower ends of the plurality of legs further include adjustable extensions enabling adjustment of a length of the plurality of legs.

(10) In accordance with an aspect of the present invention, the feeder guide is formed of fabric. In some such aspects, the fabric comprises reinforced canvas.

(11) In accordance with an aspect of the present invention, the frame is generally formed of aluminum.

(12) In accordance with an aspect of the present invention, the one or more chutes are each 20.5 inches long in the downward direction.

(13) In accordance with an aspect of the present invention, the one or more chutes comprise two chutes. In some aspects, the one or more chutes comprise four chutes.

(14) In accordance with an aspect of the present invention, each of the one or more chutes is sized and dimensioned to receive and support a conventional thirty (30) gallon yard refuse bag.

(15) In accordance with an aspect of the present invention, one or more chutes further includes one or more securing means for securing the one or more yard refuse bags in an upright position under the one or more chutes.

(16) In accordance with an aspect of the present invention, each scissor linkage of the truss includes a first link, a second link, a third link, and a fourth link. The first link has a first end and a second end. The first end of the first link is pivotably coupled to an upper end of a leg of the plurality of legs. The second link also has a first end and a second end. The first end of the second link is slidably coupled to the leg of the plurality of legs to which the first link is pivotably coupled. The first link and second link are pivotably coupled together in a scissor configuration. The third link has a first end and a second end. The first end of the third link is pivotably coupled to an upper end of an adjacent leg of the plurality of legs and the second end of the third link is pivotably coupled to the second end of the first link. The fourth link also has a first end and a second end. The first end of the fourth link is slidably coupled to the adjacent leg of the plurality of legs to

which the third link is pivotably coupled and the second end of the fourth link is pivotably linked to the second end of the second link. The third link and fourth link are pivotably coupled together in a scissor configuration. The scissor configuration of the first link and second link and the scissor configuration of the third link and the fourth link operate in conjunction with the pivotable coupling of the first link to the third link and the pivotable coupling of the second link to the fourth link so as to transition from a collapsed configuration to a deployed configuration.

(17) In accordance with an embodiment of the present invention, a method of collecting yard refuse is provided. The method involves deploying a collapsible yard refuse bag stand as set forth herein, providing one or more yard refuse bags in an upright and open position within the deployed collapsible yard refuse bag stand, and placing collected yard refuse through the feeder guide of the deployed collapsible yard refuse bag stand. The yard refuse falls via gravitational force through the one or more chutes into the one of the one or more yard refuse bags supported in an upright and open position by the frame.

(18) In accordance with an aspect of the present invention, the collapsible yard refuse bag stand further includes one or more securing means on the one or more chutes for securing one or more yard refuse bags in an upright position under the one or more chutes.

(19) In accordance with an aspect of the present invention, the method further involves removing the one or more yard refuse bags from the collapsible yard refuse bag stand when the one or more yard refuse bags are full. In some such aspects, the method further involves collapsing the collapsible yard refuse bag stand retracting the scissor linkage of each side of the collapsible truss, and retracting the plurality of legs.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) These and other characteristics of the present invention will be more fully understood by reference to the following detailed description in conjunction with the attached drawings, in which:
- (2) FIG. 1 is an isometric view of a collapsible yard refuse bag stand in a deployed configuration in accordance with an embodiment of the present invention;
- (3) FIG. 2 is an exploded isometric view of the collapsible yard refuse bag stand in a deployed configuration;
- (4) FIG. 3 is an isometric view of a frame of the collapsible yard refuse bag stand in a collapsed configuration;
- (5) FIG. 4 is an isometric view of the frame of the collapsible yard refuse bag stand in a deployed configuration;
- (6) FIG. 5 depicts an isometric view and a front view of a feeder guide of the collapsible yard refuse bag stand;
- (7) FIG. 6 depicts the frame of the collapsible yard refuse bag stand in a deployed configuration holding yard refuse bags in an open and upright operable position in accordance with aspects of the present invention;
- (8) FIG. 7 depicts the collapsible yard refuse bag stand in a deployed configuration holding yard refuse bags in an open and upright operable position;
- (9) FIG. 8 is a close-up view of a chute of a feeder guide of the collapsible yard refuse bag stand in a deployed configuration holding yard refuse bags in the open and upright operable position; and
- (10) FIG. 9 depicts a flow diagram of a methodology of collecting yard refuse using a collapsible yard refuse bag stand in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

- (11) An illustrative embodiment of the present invention relates to a collapsible yard refuse bag stand for use with one or more yard refuse bags. In a deployed configuration the collapsible yard

refuse bag stand can hold one or more yard refuse bags in an open and upright operable position suitable for the depositing of yard refuse into the one or more yard refuse bags, thereby allowing for easier management or handling of yard refuse bags by an individual. The collapsible yard refuse bag stand can be collapsed for easier transportation and storage when not in use.

(12) FIGS. **1** through **9**, wherein like parts are designated by like reference numerals throughout, illustrate an example embodiment or embodiments of a collapsible refuse bag stand and method of use, according to the present invention. Although the present invention will be described with reference to the example embodiment or embodiments illustrated in the figures, it should be understood that many alternative forms can embody the present invention. One of skill in the art will additionally appreciate different ways to alter the parameters of the embodiment(s) disclosed, such as the size, shape, or type of elements or materials, in a manner still in keeping with the spirit and scope of the present invention.

(13) FIG. **1** depicts an embodiment of collapsible yard refuse bag stand **100** in a deployed configuration. FIG. **2** shows an exploded view of a deployed collapsible yard refuse bag stand **100** in accordance with an embodiment. The collapsible yard refuse bag stand **100** comprises a frame **102** and a feeder guide **104**.

(14) The frame **102** has a collapsed configuration as seen in FIG. **3** and a deployed configuration as seen in FIG. **4**. In the deployed configuration, the frame **102** is configured, sized, and dimensioned to support one or more yard refuse bags in an open and upright operable position. The frame **102** includes a plurality of legs **106** and a collapsible truss **108**. In certain embodiments, the frame **102** or its components, are formed of metal, such as aluminum. Other possible materials will be apparent to one skilled in the art given the benefit of this disclosure.

(15) Each leg **106** has an upper end **110** and a lower end **112**. In some embodiments, the lower ends **112** of the plurality of legs **106** further comprise adjustable extensions **114** enabling adjustment of a length of the plurality of legs **106** and a resulting height of the collapsible yard refuse bag stand **100**.

(16) The collapsible truss **108** is connected to each of the legs **106**, with the collapsible truss **108** comprising at least four sides. Each side of the collapsible truss **108** is formed of a scissor linkage **116**. In certain embodiments, each scissor linkage **116** of the truss **108** comprises a series of links coupled together. Other possible configurations will be apparent to one skilled in the art given the benefit of this disclosure.

(17) In the embodiment depicted, a first link **118** has a first end **120** and a second end **122**. The first end **120** is pivotably coupled to an upper end **110** of a leg **106** of the plurality of legs. In certain embodiments, the first end **120** is pivotably coupled to the upper end **110** via a hinge **124** where the first link **118** pivots around a pin, in this case a bolt **126** having washers **128** secured with a locknut **130**. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(18) A second link **132** has a first end **134** and a second end **136**. The first end **134** is slidably coupled to the leg **106** of the plurality of legs to which the first link **118** is pivotably coupled. In certain embodiments, the first end **134** is pivotably coupled to a sliding hinge assembly **138** where the sliding hinge assembly **138** is configured to slide along the length of the leg **106** from upper end **110** to the lower end **112** while the second link **132** pivots around a pin, in this case a bolt **126** with washers **128** secured by a locknut **130**. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(19) The first link **118** and second link **132** are pivotably coupled together in a scissor configuration. In certain embodiments, such as depicted, the first link **118** and second link **132** are pivotably coupled by a pin, in this case a bolt **140** with washer **128** secured by a locknut **130** at around a midpoint of the first link **118** and second link **132** located between the first end **120** and the second end **122** for the first link **118** and between the first end **134** and the second end **136** of the second link **132**. In some such embodiments, a washer or spacer **142** is provided between the

first link **118** and second link **132** at the coupling. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(20) The third link **144** has a first end **146** and a second end **148**, wherein the first end **146** is pivotably coupled to an upper end **110** of an adjacent leg **106** of the plurality of legs and the second end **148** is pivotably coupled to the second end **122** of the first link **118**. In certain embodiments, the first end **146** is pivotably coupled to the upper end **110** via a hinge **150** where the first link **118** pivots around a pin, in this case a bolt **126** having washers **128** secured with a locknut **130**. In certain embodiments, the second end **122** of the first link **118** and the second end **148** of the third link **144** are pivotably coupled by a pin, in this case bolt **140** with washer **128** secured by a locknut **130**. In some such embodiments, a spacer **142** is provided between the first link **118** and third link **144** at the coupling. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(21) The fourth link **152** has a first end **154** and a second end **156**, wherein the first end **154** is slidably coupled to the adjacent leg **106** of the plurality of legs to which the third link **144** is pivotably coupled and the second end **156** is pivotably linked to the second end **136** of the second link **132**. In certain embodiments, the first end **134** is pivotably coupled to a sliding hinge assembly **138** where the sliding hinge assembly **138** is configured to slide along the length of the leg **106** from upper end **110** to the lower end **112** while the fourth link **152** pivots around a pin, in this case a bolt **126** with washers **128** secured by a locknut **130**. In certain embodiments, the second end **136** of the second link **132** and the second end **156** of the fourth link **152** are pivotably coupled by a pin, in this case a bolt **140** with washer **128** secured by a locknut **130**. In some such embodiments, a spacer **142** is provided between the second link **132** and fourth link **152** at the coupling. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(22) The third link **144** and fourth link **152** are pivotably coupled together in a scissor configuration. In certain embodiments, such as depicted, the third link **144** and fourth link **152** are pivotably coupled by a pin, in this case bolt **140** with washer **128** secured by a locknut **130** at around a midpoint of the third link **144** and fourth link **152** located between the first end **146** and the second end **148** for the third link **144** and between the first end **154** and the second end **156** of the fourth link **152**. In some such embodiments, a washer or spacer **142** is provided between the first link **118** and second link **132** at the coupling. Other suitable couplings will be apparent to one skilled in the art given the benefit of this disclosure.

(23) The scissor configuration of the first link **118** and second link **132** and the scissor configuration of the third link **144** and the fourth link **152** work in conjunction with the pivotable coupling of the first link **118** to the third link **144** and the pivotable coupling of the second link **132** to the fourth link **152** so as to transition from a collapsed configuration to a deployed configuration.

(24) FIG. 3 depicts the frame **102** in a collapsed configuration. As can be seen, as the legs **106** are moved together, the individual links of the scissor linkage **116** on each side of the collapsible truss **108** move in relation to each other with the sliding hinge assembly **138** on each leg **106** sliding from the upper end **110** to the lower end **112** allowing the truss **108** to collapse. In certain embodiments, the adjustable extensions **114** are retracted into the legs **106** in the collapsed configuration.

(25) FIG. 4 depicts the frame **102** in a deployed configuration. As can be seen, as the legs **106** are moved apart the individual links of the scissor linkage **116** on each side of the collapsible truss **108** move in relation to each other with the sliding hinge assembly **138** on each leg **106** sliding from the lower end **112** to the upper end **110** allowing the truss **108** to expand. In certain embodiments, the adjustable extensions **114** are extended from the legs **106** in the deployed configuration.

(26) FIG. 5 depicts various views of the feeder guide **104** as seen in FIG. 1 and FIG. 2 in isolation. The feeder guide **104** and is configured, sized, and dimensioned to fit over the truss **108** in the deployed configuration as seen in FIG. 4. In certain embodiments, the feeder guide **104** is formed of fabric. In some such embodiments, the feeder guide **104** is formed of reinforced canvas.

(27) The feeder guide **104** includes one or more chutes **160**. The one or more chutes **160** are configured, sized, and dimensioned to extend downward from the frame **102** on a same side of the frame **102** as the plurality of legs **106**. There can be any number of chutes **160**. In some embodiments, there are two chutes of the one or more chutes **160**. In other embodiments, there are four chutes of the one or more chutes **160**. In certain embodiments, one of the chutes **160** that extends downward extends into a yard refuse bag and serves as a guide holding the yard refuse bag in place aligned under each of the one or more chutes **160**. In some embodiments, the one or more chutes **160** further include one or more securing means **162** such as tabs, clips, or other securing means. The securing means **162** serve to secure a yard refuse bag in place around a chute **160** in an upright position. In some such embodiments, the securing means **162** can be used to secure lawn refuse bags that would ordinarily not be able to stand in open upright position around the chute **160**. For example, a conventional plastic trash bag could be used as a yard refuse bag with the securing means **162** holding the trash bag in place around the chute **160**.

(28) In some embodiments, the one or more chutes **160** are each 20.5 inches long in the downward direction. In some such embodiments, each of the one or more chutes **160** is sized and dimensioned to receive and support a conventional thirty (30) gallon paper yard refuse bag. In embodiments with securing means **162**, thirty (30) gallon trash bags could also be used. Overall dimensions of the various components of the collapsible yard refuse bag stand **100** described herein are appropriately sized and dimensioned to correspond to supporting four conventional thirty (30) gallon yard refuse bags as depicted and as would be readily understood by those of skill in the art, such that additional dimensional ranges are not necessary for this disclosure.

(29) When one or more yard refuse bags **164** are placed in an upright position under the one or more chutes **160**, each of the one or more chutes **160** supports one yard refuse bag of the one or more yard refuse bags **164** in an upright and open position in such a way that any yard refuse placed through the feeder guide **104** is directed via gravitational force through the one or more chutes **160** into one of the one or more yard refuse bags **164**. In embodiments having securing means **162**, the securing means **162** can further be used to secure the one or more yard refuse bags **164** in an upright and open position around the chute **160**.

(30) FIG. 6 depicts an example embodiment where multiple yard refuse bags **164** are deployed within a deployed frame **102** of the bag stand **100**. In this embodiment, four of the one or more yard refuse bags **164**, in this case conventional paper yard refuse bags, are in an upright and open position within the frame **102**. It should be understood that the stand can be configured, sized, and dimensioned to accommodate any number of bags **164**.

(31) FIG. 7 depicts the deployed frame **102** and the one or more yard refuse bags **164** of FIG. 6 where the feeder guide **104** has been fitted over the truss **108** framework of the frame **102** structure with the chutes **160** of the feeder guide **104** extending down into each of the one or more yard refuse bags **164** supporting the yard refuse bags in an upright and open position. A close-up view of the chute **160** extending into a yard refuse bag **164** of the one or more yard refuse bags **164** can be seen in FIG. 8.

(32) FIG. 9 is a flow diagram **200** of a methodology for collecting yard refuse using the collapsible yard refuse bag stand **100** of the present invention in accordance with embodiments of the present invention. The first step is deploying the yard refuse bag stand (Step **202**). The yard refuse bag stand **100** can be seen in various stages of deployment in FIG. 1, FIG. 3, and FIG. 4. Next, the one or more yard refuse bags **164** are inserted into the stand **100** (Step **204**). Examples of this can be seen in FIGS. 6-8. In embodiments having one or more securing means **162** on the one or more chutes **160**, the one or more securing means **162** can be used to secure the one or more yard refuse bags **164** in an upright and open position. Once the one or more yard refuse bags **164** are installed (and optionally secured using securing means **162**), yard refuse can be placed upon the feeder guide **104** of the stand **100** wherein yard refuse placed onto and through the feeder guide **104** is directed via gravitational force through the one or more chutes **160** into one of the one or more yard refuse

bags **164** (Step **206**). In certain embodiments, when one of the one or more yard refuse bags **164** is full, the bag can be removed and/or replaced with a new yard refuse bag **164** (Step **208**). In some embodiments, when a user is finished using the yard refuse bag stand **100**, the stand **100** can be collapsed for transportation and storage (Step **210**).

(33) The present invention provided a collapsible yard refuse bag stand **100** that is easy to deploy or collapse. In a deployed configuration the collapsible yard refuse bag stand **100** can hold one or more bags in an upright and open positions for the depositing of yard refuse in the one or more bags allowing for easier use of yard refuse bags by a single individual. The collapsible yard refuse bag stand can be collapsed for easier transportation and storage when not in use.

(34) As utilized herein, the terms “comprises” and “comprising” are intended to be construed as being inclusive, not exclusive. As utilized herein, the terms “exemplary”, “example”, and “illustrative”, are intended to mean “serving as an example, instance, or illustration” and should not be construed as indicating, or not indicating, a preferred or advantageous configuration relative to other configurations. As utilized herein, the terms “about”, “generally”, and “approximately” are intended to cover variations that may existing in the upper and lower limits of the ranges of subjective or objective values, such as variations in properties, parameters, sizes, and dimensions. In one non-limiting example, the terms “about”, “generally”, and “approximately” mean at, or plus 10 percent or less, or minus 10 percent or less. In one non-limiting example, the terms “about”, “generally”, and “approximately” mean sufficiently close to be deemed by one of skill in the art in the relevant field to be included. As utilized herein, the term “substantially” refers to the complete or nearly complete extent or degree of an action, characteristic, property, state, structure, item, or result, as would be appreciated by one of skill in the art. For example, an object that is “substantially” circular would mean that the object is either completely a circle to mathematically determinable limits, or nearly a circle as would be recognized or understood by one of skill in the art. The exact allowable degree of deviation from absolute completeness may in some instances depend on the specific context. However, in general, the nearness of completion will be so as to have the same overall result as if absolute and total completion were achieved or obtained. The use of “substantially” is equally applicable when utilized in a negative connotation to refer to the complete or near-complete lack of an action, characteristic, property, state, structure, item, or result, as would be appreciated by one of skill in the art.

(35) Numerous modifications and alternative embodiments of the present invention will be apparent to those skilled in the art in view of the foregoing description. Accordingly, this description is to be construed as illustrative only and is for the purpose of teaching those skilled in the art the best mode for carrying out the present invention. Details of the structure may vary substantially without departing from the spirit of the present invention, and exclusive use of all modifications that come within the scope of the appended claims is reserved. Within this specification embodiments have been described in a way which enables a clear and concise specification to be written, but it is intended and will be appreciated that embodiments may be variously combined or separated without parting from the invention. It is intended that the present invention be limited only to the extent required by the appended claims and the applicable rules of law.

(36) It is also to be understood that the following claims are to cover all generic and specific features of the invention described herein, and all statements of the scope of the invention which, as a matter of language, might be said to fall therebetween.

Claims

1. A collapsible yard refuse bag stand comprising: a frame having a collapsed configuration and a deployed configuration, wherein the deployed configuration is configured, sized and dimensioned to support one or more yard refuse bags in an upright and open position, the frame comprising: a

plurality of legs, each leg having an upper end and a lower end; and a collapsible truss connected to each of the legs, the collapsible truss comprising at least four sides, each side formed of a scissor linkage; and a feeder guide configured, sized, and dimensioned to fit over the truss in the deployed configuration, the feeder guide comprising one or more chutes configured, sized, and dimensioned to extend downward from the frame on a same side of the frame as the plurality of legs; wherein when the one or more yard refuse bags are placed in an upright position under the one or more chutes, each of the one or more chutes supports a yard refuse bag of the one or more yard refuse bags in an upright and open position in such a way that any yard refuse placed through the feeder guide is directed via gravitational force through the one or more chutes into one of the one or more yard refuse bags.

2. The collapsible yard refuse bag stand of claim 1, wherein one of the chutes that extend downward extend into one of the yard refuse bags serves as a guide holding the one yard refuse bag in place aligned under the one of the chutes.

3. The collapsible yard refuse bag stand of claim 1, wherein the lower ends of the plurality of legs further comprise adjustable extensions enabling adjustment of a length of the plurality of legs.

4. The collapsible yard refuse bag stand of claim 1, wherein the feeder guide is formed of fabric.

5. The collapsible yard refuse bag stand of claim 4, wherein the fabric comprises reinforced canvas.

6. The collapsible yard refuse bag stand of claim 1, wherein the frame is generally formed of aluminum.

7. The collapsible yard refuse bag stand of claim 1, wherein the one or more chutes are each 20.5 inches long in the downward direction.

8. The collapsible yard refuse bag stand of claim 1, wherein the one or more chutes comprise two chutes.

9. The collapsible yard refuse bag stand of claim 1, wherein the one or more chutes comprise four chutes.

10. The collapsible yard refuse bag stand of claim 1, wherein each of the one or more chutes is sized and dimensioned to receive and support a conventional 30 gallon yard refuse bag.

11. The collapsible yard refuse bag stand of claim 1, wherein one or more chutes further comprises one or more securing means for securing the one or more yard refuse bags in an upright position under the one or more chutes.

12. The collapsible yard refuse bag stand of claim 1, wherein each scissor linkage of the truss comprises: a first link having a first end and second end, wherein the first end is pivotably coupled to an upper end of a leg of the plurality of legs; and a second link having a first end and second end, wherein the first end is slidably coupled to the leg of the plurality of legs to which the first link is pivotably coupled; wherein the first link and second link are pivotably coupled together in a scissor configuration; a third link having a first end and second end, wherein the first end is pivotably coupled to an upper end of an adjacent leg of the plurality of legs and the second end is pivotably coupled to the second end of the first link; and a fourth link having a first end and second end, wherein the first end is slidably coupled to the adjacent leg of the plurality of legs to which the third link is pivotably coupled and the second end is pivotably linked to the second end of the second link; wherein the third link and fourth link are pivotably coupled together in a scissor configuration; wherein the scissor configuration of the first link and second link and the scissor configuration of the third link and the fourth link operate in conjunction with the pivotable coupling of the first link to the third link and the pivotable coupling of the second link to the fourth link so as to transition from a collapsed configuration to a deployed configuration.

13. A method of collecting yard refuse comprising: deploying a collapsible yard refuse bag stand; the collapsible yard refuse bag stand comprising: a frame having a collapsed configuration and a deployed configuration, wherein the deployed configuration is configured, sized and dimensioned to support one or more yard refuse bags in an upright and open position, the frame comprising: a plurality of legs, each leg having an upper end and a lower end; a collapsible truss connected to

each of the legs, the collapsible truss comprising at least four sides, each side formed of a scissor linkage; a feeder guide configured, sized, and dimensioned to fit over the truss in the deployed configuration, the feeder guide comprising one or more chutes configured, sized, and dimensioned to extend downward from the frame on a same side of the frame as the plurality of legs; wherein when the one or more yard refuse bags are placed in an upright position under the one or more chutes, each of the one or more chutes supports a yard refuse bag of the one or more yard refuse bags in an upright and open position in such a way that any yard refuse placed through the feeder guide is directed via gravitational force through one or more chutes into one of the one or more yard refuse bags; providing the one or more yard refuse bags in an upright and open position within the deployed collapsible yard refuse bag stand; and placing collected yard refuse through the feeder guide of the deployed collapsible yard refuse bag stand, the yard refuse falling via gravitational force through the one or more chutes into the one of the one or more yard refuse bags supported in an upright and open position by the frame.

14. The method of claim 13, wherein the collapsible yard refuse bag stand further comprises one or more securing means on the one or more chutes for securing one or more yard refuse bag in an upright position under the one or more chutes.

15. The method of claim 13, further comprising: removing the one or more yard refuse bags from the collapsible yard refuse bag stand when the one or more yard refuse bags are full.

16. The method of claim 15, further comprising: collapsing the collapsible yard refuse bag stand retracting the scissor linkage of each side of the collapsible truss and retracting the plurality of legs.
