

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405062
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Takahashi; Kenzo

Metal melt pump with heat insulating hood

Abstract

A metal melt pump includes a bottomed cylinder body including a side wall, a melt flow passage body including a melt flow passage and being a body separate from the bottomed cylinder body, and a melt driving part including a magnetic field device and an electric motor and adapted to drive metal melt in the melt flow passage. The magnetic field device includes a plurality of permanent magnets arranged such that different magnetic poles are alternately arrayed along a circumference of a rotary shaft, and the melt flow passage body is removably provided on the bottomed cylinder body at a position around the side wall and where a magnetic force line from one of the permanent magnets penetrates through the side wall and an inner side flow passage wall of the melt flow passage body to reach the melt flow passage.

Inventors:	Takahashi; Kenzo (Shiroi, JP)
Applicant:	ZMAG, LTD. (Shiroi, JP)
Family ID:	82157719
Assignee:	ZMAG, LTD. (Shiroi, JP)
Appl. No.:	18/330994
Filed:	June 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230314079 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2020-211443	Dec. 21, 2020
----	-------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: F27D27/00 (20100101); F04D7/06 (20060101); H02K44/02 (20060101)

U.S. Cl.:

CPC F27D27/005 (20130101); H02K44/02 (20130101); F04D7/065 (20130101)

Field of Classification Search

CPC: F27D (27/005); F04D (7/065)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5947705	12/1998	Mordue	417/423.15	F04D 7/065
8703043	12/2013	Takahashi	266/200	H02K 44/02
9395120	12/2015	Rauch	N/A	C21C 1/06
2006/0133194	12/2005	Takahashi	N/A	N/A
2011/0248432	12/2010	Takahashi	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
200963579	12/2006	CN	N/A
101382153	12/2008	CN	F04D 13/027
201335610	12/2008	CN	N/A
101382153	12/2010	CN	F04D 13/027
112737275	12/2020	CN	N/A
2453564	12/2011	EP	H02K 44/06
2004254437	12/2003	JP	N/A
2006-177612	12/2005	JP	N/A
2011139611	12/2010	JP	N/A
2011-230187	12/2010	JP	N/A
5546974	12/2013	JP	N/A

OTHER PUBLICATIONS

Machine English Translation of CN-201335610-Y (Year: 2009). cited by examiner
PCT International Search Report of PCT Application No. PCT/JP2021/045304 Mailed on Feb. 15, 2022. cited by applicant
PCT International Preliminary Report on Patentability of PCT Application No. PCT/JP2021/045304 Mailed on Jun. 29, 2023. cited by applicant
Extended European Search Report of Ep Application No. 21910347.0 mailed on Sep. 2, 2024. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a bypass continuation application of International PCT Application No. PCT/JP2021/045304, filed on Dec. 9, 2021, which claims priority to Japanese Patent Application No. 2020-211443, filed on Dec. 21, 2020, which are incorporated by reference herein in their entirety.

TECHNICAL FIELD

(1) The present invention relates to a metal melt pump, and more particularly to a metal melt pump that circulates or transfers metal melt inside a furnace.

BACKGROUND ART

(2) Conventionally, there has been known a metal melt pump that drives non-ferrous metal melt (hereinafter simply referred to as “metal melt”) using an electromagnetic force. For example, Patent Literature 1 describes a metal melt pump that drives metal melt using an electromagnetic force generated by a magnetic force line, which is output from a permanent magnet, moving while penetrating the metal melt. In this metal melt pump, the permanent magnet is rotatably disposed inside a cylindrical container and a spiral melt flow passage is provided inside a side wall of the cylindrical container.

SUMMARY

(3) The metal melt pump of Japanese Patent No. 5546974 has been invented by the inventor of the present invention. Since then, the inventor has continued earnest efforts on research and development for realization of a more practical metal melt pump with a high performance. In such efforts, the following problems have uniquely been found.

(4) When the use of the metal melt pump is halted, the metal melt gradually solidifies inside the flow passage so that the cross-sectional area of the flow passage of the melt flow passage is narrowed. As a result, the ejection amount (ejection pressure) of the metal melt pump decreases or in the worst case scenario, the metal melt pump becomes no longer usable. On the other hand, during the use of the metal melt pump, the melt flow passage is scraped off by the metal melt flowing through the melt flow passage in some cases. In any case, it is inevitable that the melt flow passage wears out as the metal melt pump is used.

(5) In an attempt to renew the melt flow passage for the purpose of maintaining the performance of the metal melt pump, in the case of the aforementioned metal melt pump, since the melt flow passage is formed in the cylindrical container, the cylindrical container constituting the main body portion needs to be replaced with new one, which requires enormous cost (money and time).

(6) Further, it is desirable to increase the ejection amount of the metal melt pump, but in an attempt to enlarge the cross-sectional area of the flow passage of the melt flow passage, in the case of the conventional metal melt pump, problems occur in handling in that the weight of the cylindrical container increases due to the side wall thickened, resulting in difficulty in performing installing work of the metal melt pump in a furnace, and the like.

(7) The present invention has been made on the basis of the aforementioned recognition, and an object of the present invention is to provide a metal melt pump capable of renewing a melt flow passage easily and at low cost.

(8) A metal melt pump according to the present invention is a metal melt pump that drives metal melt inside a furnace that includes a bottomed cylinder body including a side wall and a bottom wall, a melt flow passage body including a melt flow passage that connects a suction port and an ejection port, the melt flow passage body being a body separate from the bottomed cylinder body, and a melt driving part including a magnetic field device rotatably disposed around a vertically

oriented rotary shaft inside the bottomed cylinder body and an electric motor that rotates the magnetic field device, the melt driving part adapted to drive metal melt in the melt flow passage, in which the magnetic field device includes a plurality of permanent magnets arranged such that different magnetic poles are alternately arrayed along a circumference of the rotary shaft, and the melt flow passage body is removably provided on the bottomed cylinder body at a position around the side wall of the bottomed cylinder body and where a magnetic force line from a first permanent magnet among the plurality of permanent magnets penetrates through the side wall of the bottomed cylinder body and an inner side flow passage wall of the melt flow passage body to reach the melt flow passage and penetrates from the melt flow passage through the inner side flow passage wall of the melt flow passage body and the side wall of the bottomed cylinder body to return to a second permanent magnet adjacent to the first permanent magnet.

(9) Further, in the metal melt pump, the longitudinal cross-sectional shape of the melt flow passage may be a vertically-long and substantially rectangular shape.

(10) Furthermore, in the metal melt pump, the plurality of permanent magnets of the magnetic field device may be greater in a longitudinal length than the melt flow passage, and may encompass the melt flow passage in a longitudinal direction in a side view.

(11) Further, in the metal melt pump, the melt flow passage body may be provided so as to surround the side wall of the bottomed cylinder body.

(12) Furthermore, in the metal melt pump, the melt flow passage body may have a planar shape in a substantially U-shape.

(13) Moreover, the metal melt pump may further include a heat insulating hood configured to cover the magnetic field device and the electric motor of the melt driving part and to define a cooling air flow passage for cooling air to flow through the magnetic field device and the electric motor.

(14) In addition, in the metal melt pump, the heat insulating hood may include a fixed hood fixed to a base plate that defines, together with the bottomed cylinder body, a space that houses the magnetic field device, the fixed hood covering the electric motor and provided with an air intake hole that takes in the cooling air, and a movable hood attached to the magnetic field device so as to define, together with the fixed hood, the cooling air flow passage and to cover an outer periphery surface of the magnetic field device, the movable hood adapted to rotate together with the magnetic field device.

(15) Furthermore, in the metal melt pump, the fixed hood may include an upper side fixed hood with a lower end portion fixed to an upper face of the base plate, and a lower side fixed hood with an upper end portion fixed to a lower face of the base plate.

(16) In addition, in the metal melt pump, a heat insulating material may be affixed to the fixed hood and the movable hood.

(17) Further, in the metal melt pump, the fixed hood and the movable hood may be formed of metal material.

(18) Further, in the metal melt pump, a lower end portion of the fixed hood may be loosely inserted into an upper end portion of the movable hood or the upper end portion of the movable hood may be loosely inserted into the lower end portion of the fixed hood.

(19) Furthermore, in the metal melt pump, the base plate is provided with a first air hole positioned on an inner side of the fixed hood and a second air hole positioned on an outer side of the fixed hood, and cooling air taken in from the air intake hole of the fixed hood passes the first air hole to flow through the cooling air flow passage downward, passes the magnetic field device, and is released from a lower end portion of the movable hood, and subsequently, passes a space between the side wall of the bottomed cylinder body and the heat insulating hood and is discharged to the outside from the second air hole.

(20) Further, in the metal melt pump, the bottomed cylinder body may include a support part projecting radially outward from the side wall, and the melt flow passage body may be removably supported on the bottomed cylinder body by means of the support part.

- (21) Furthermore, in the metal melt pump, the electric motor may be configured such that the number of rotation of the magnetic field device is variable in accordance with an ejection amount of the metal melt.
- (22) Moreover, the metal melt pump may further include a melt discharge pipe connected to the ejection port of the melt flow passage and adapted to pump the metal melt.
- (23) According to the present invention, a metal melt pump capable of renewing a melt flow passage easily and at low cost can be provided.
-

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a cross-sectional view showing the schematic configuration of a metal melt pump according to an embodiment.
- (2) FIG. 2 is a plan view showing the schematic configuration of the metal melt pump according to the embodiment.
- (3) FIG. 3 is a plan view showing the metal melt pump with a melt flow passage body removed according to the embodiment.
- (4) FIG. 4 is a plan view showing the melt flow passage body of the metal melt pump according to the embodiment.
- (5) FIG. 5 is a plan view showing a magnetic field device according to the embodiment.
- (6) FIG. 6 is a plan view showing a magnetic field device according to a modification of the embodiment.
- (7) FIG. 7 is a cross-sectional view of the metal melt pump in a state of being immersed in metal melt inside a furnace according to the embodiment.
- (8) FIG. 8 is a plan view of the metal melt pump in the state of being immersed in the metal melt inside the furnace according to the embodiment.
- (9) FIG. 9 is a side view showing the metal melt pump with a melt discharge pipe mounted in an ejection port of the melt flow passage body according to the embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

- (10) Hereinafter, an embodiment according to the present invention will be described with reference to the drawings. It should be noted that in the drawings, constituent elements having equivalent functions are assigned the same reference signs.
- (11) <Metal Melt Pump>
- (12) With reference to FIG. 1 to FIG. 5, the configuration of a metal melt pump 1 according to the embodiment will be described. FIG. 1 is a cross-sectional view taken along line A-A of FIG. 2, showing the schematic configuration of the metal melt pump 1.
- (13) The metal melt pump 1 according to the present embodiment is configured so as to be partially (at least a melt flow passage body 20) immersed in metal melt inside a furnace, such as a melting furnace and a holding furnace, to drive the metal melt using an electromagnetic force caused by eddy current as will be described later.
- (14) As illustrated in FIG. 1, the metal melt pump 1 includes a bottomed cylinder body (main body) 10, the melt flow passage body 20 provided with a melt flow passage C where metal melt flows, a melt driving part 30 that drives the metal melt in the melt flow passage C, a heat insulating hood 40 that thermally protects the melt driving part 30, and a base plate 50 that partitions an inner space of the bottomed cylinder body 10 and supports the melt driving part 30.
- (15) Hereinafter, the configuration of the metal melt pump 1 will be described in detail.
- (16) The bottomed cylinder body 10 is a cylinder body with a bottom including a side wall 11 and a bottom wall 12. The side wall 11 is cylindrically formed. The bottom wall 12 closes a lower end portion of the side wall 11. In the present embodiment, as illustrated in FIG. 1 and FIG. 3, the

bottomed cylinder body **10** includes a support part (flange portion) **13** projecting radially outward from the side wall **11**. By means of the support part **13**, the melt flow passage body **20** is removably supported on the bottomed cylinder body **10**.

(17) The bottomed cylinder body **10** is formed of a non-magnetic and fire-resistant material.

(18) It should be noted that the bottomed cylinder body **10** is preferably formed by integrating the side wall **11** and the bottom wall **12**. In this case, the integrally formed bottomed cylinder body **10** is produced by casting mortar or the like into a frame mold.

(19) The melt flow passage body **20** is provided at a position around the side wall **11** of the bottomed cylinder body **10**, as a body separate from the bottomed cylinder body **10**. When the metal melt pump **1** is used, the melt flow passage body **20** is immersed in the metal melt inside the furnace and the melt flow passage C is filled with the metal melt (see FIG. 7). The melt flow passage body **20** is formed of a non-magnetic and fire-resistant material, for example, the same material as that of the bottomed cylinder body **10**.

(20) The inside of the melt flow passage body **20** is provided with the melt flow passage C that connects a suction port **P1** and an ejection port **P2**. The melt flow passage C of the present embodiment is formed in a shape with the longitudinal cross-section closed. Specifically, as illustrated in FIG. 1, the melt flow passage body **20** includes an inner side flow passage wall **21**, an outer side flow passage wall **22**, an upper side flow passage wall **23**, and a lower side flow passage wall **24**, and the melt flow passage C with a substantially rectangular longitudinal cross-sectional shape is formed by these flow passage walls. Since an upper side of the melt flow passage C is not open in such a manner, the ejection pressure of the metal melt can be easily increased. The melt flow passage body **20** is preferably formed by integrating the inner side flow passage wall **21**, the outer side flow passage wall **22**, the upper side flow passage wall **23**, and the lower side flow passage wall **24**.

(21) It should be noted that the longitudinal cross-sectional shape of the melt flow passage C is preferably a vertically-long and substantially rectangular shape. In this manner, since the radial length of the melt flow passage C becomes relatively shorter under conditions where the cross-sectional area of the flow passage is constant, a magnetic force line from a magnetic field device **31** easily penetrates the metal melt in the melt flow passage C, to thus be able to improve the force to drive the metal melt.

(22) Further, as illustrated in FIG. 1, a longitudinal length (**L1**) of a plurality of permanent magnets **31a** of the magnetic field device **31** may be greater than a longitudinal length (**L2**) of the melt flow passage C (i.e., $L1 > L2$), and the melt flow passage C may be encompassed in a longitudinal direction in a side view. In this manner, the magnetic force lines from the magnetic field device **31** are substantially parallel to each other in the melt flow passage C. Consequently, the driving force of the metal melt pump is more easily controlled so that the ejection amount of the metal melt is more easily adjustable.

(23) It should be noted that the longitudinal cross-sectional shape of the melt flow passage C is not limited to a rectangle, but may be a round, elliptic, or polygonal shape, or the like. Further, in a case where a high ejection pressure is not required, the upper side of the melt flow passage C may be opened by eliminating the upper side flow passage wall **23**. In this case, a melt level of the metal melt inside the furnace needs to be lower than an upper end of the outer side flow passage wall **22**.

(24) Furthermore, as illustrated in FIG. 2, for easier sucking of the metal melt, the vicinity of an inlet of the melt flow passage C may be tapered so as to widen the suction port **P1** as compared to the ejection port **P2**.

(25) In addition, the width of the melt flow passage C may be greater than the thickness of the side wall **11** of the bottomed cylinder body **10**. In this manner, as compared to the conventional case in which the side wall is provided with the flow passage, the cross-sectional area of the flow passage is enlarged to thus be able to increase the ejection amount.

(26) In the present embodiment, as illustrated in FIG. 2, the melt flow passage body **20** has a planar

shape in a substantially U-shape. The melt flow passage C is disposed so as to surround the side wall **11** in such a manner to thus be able to efficiently drive the metal melt in the melt flow passage C. However, the planar shape of the melt flow passage body **20** is not limited to a U-shape, but may be, for example, a substantially C-shape or L-shape. Further, the melt flow passage body **20** may include a spiral melt flow passage C.

(27) As illustrated in FIG. **3** and FIG. **4**, the melt flow passage body **20** is removably provided on the bottomed cylinder body **10**. FIG. **3** shows a plan view of a main body portion of the metal melt pump **1** with the melt flow passage body **20** removed, and FIG. **4** shows a plan view of the melt flow passage body **20** that is removed from the metal melt pump **1**.

(28) The melt flow passage body **20** is removably provided on the bottomed cylinder body **10** at a position around the side wall **11** of the bottomed cylinder body **10** and where the magnetic force line from a first permanent magnet among the plurality of permanent magnets **31a** of the magnetic field device **31** penetrates through the side wall **11** and the inner side flow passage wall **21** of the melt flow passage body **20** to reach the melt flow passage C and penetrates from the melt flow passage C through the inner side flow passage wall **21** and the side wall **11** to return to a second permanent magnet adjacent to the first permanent magnet.

(29) It should be noted that the connecting arrangement between the bottomed cylinder body **10** and the melt flow passage body **20** is not limited to the arrangement using the support part **13** of the bottomed cylinder body **10**. As another example, the melt flow passage body **20** may be removably connected to the bottomed cylinder body **10** such that the side wall **11** of the bottomed cylinder body **10** is provided with a projection (or a recess) and the inner side flow passage wall **21** of the melt flow passage body **20** is provided with a recess (or a projection), and the projection of the side wall **11** and the recess of the inner side flow passage wall **21** fit together. As further another example, the melt flow passage body **20** may be removably connected to the bottomed cylinder body **10** such that a fixation hole (not shown) is formed in each of the side wall **11** and the outer side flow passage wall **22** and an end of a coupling member (e.g., a connecting member in a U-shape facing sideways) is inserted into each hole.

(30) Further, a plurality of melt flow passage bodies **20** with different cross-sectional areas (e.g., height) of the flow passage of the melt flow passage C may be prepared and selectively used in accordance with a desired ejection amount or the like.

(31) It should be noted that in FIG. **1**, the inner side flow passage wall **21** of the melt flow passage body **20** contacts, without a gap, the side wall **11** of the bottomed cylinder body **10**. In this manner, the distance between the melt flow passage C and the magnetic field device **31** is reduced to thus intensify the magnetic field penetrating the metal melt in the melt flow passage C, thereby enabling the force to drive the metal melt to be enhanced. However, the present invention is not limited thereto, but a gap may be provided between the side wall **11** and the inner side flow passage wall **21**.

(32) Next, the melt driving part **30** will be described.

(33) The melt driving part **30** is configured so as to drive the metal melt in the melt flow passage C formed in the melt flow passage body **20**, using an electromagnetic force. The melt driving part **30** drives the metal melt in the melt flow passage C from the suction port **P1** toward the ejection port **P2**, thereby ejecting the metal melt from the ejection port **P2** and causing the metal melt inside the furnace to be sucked into the melt flow passage C from the suction port **P1**.

(34) The melt driving part **30** includes the magnetic field device (rotary magnet body) **31**, an electric motor **32** for rotating the magnetic field device **31**, a rotary shaft (rotary shaft) **33** connected to the magnetic field device **31**, a coupling (shaft coupling) **34**, a mount **35**, and a bearing housing **36**.

(35) As illustrated in FIG. **1**, the magnetic field device **31** is rotatably disposed around the rotary shaft **33** vertically oriented inside the bottomed cylinder body **10**. As illustrated in FIG. **1** and FIG. **5**, the magnetic field device **31** includes the plurality of permanent magnets (magnet pieces) **31a**

and support plates **31b** and **31c** that support the plurality of permanent magnets **31a**. It should be noted that in FIG. 5, the support plate **31c** is not shown (the same in FIG. 6). In the present embodiment, four permanent magnets **31a** are fixed on the support plate **31b**. The support plate **31b** and the support plate **31c** fix the plurality of permanent magnets **31a** so as to sandwich the permanent magnets **31a** from above and below.

(36) Each permanent magnet **31a** has an outer face magnetic pole and an inner face magnetic pole that are magnetized such that an outer periphery portion and an inner periphery portion become magnetic poles, and the magnetic field device **31** is disposed inside the bottomed cylinder body **10** such that the outer face magnetic poles face the side wall **11** of the bottomed cylinder body **10**.

(37) As illustrated in FIG. 5, the plurality of permanent magnets **31a** is arranged on the circumference of the rotary shaft **33**. More specifically, the plurality of permanent magnets **31a** is arranged such that different outer face magnetic poles are alternately arrayed along the circumference of the rotary shaft **33**. In this manner, the magnetic force line ML output from the N-pole of a certain permanent magnet **31a** (first permanent magnet) enters the S-pole of another permanent magnet **31a** (second permanent magnet) adjacent to the certain permanent magnet **31a**. It should be noted that for forming such magnetic force lines ML for all the permanent magnets **31a**, the number of the permanent magnets **31a** is preferably an even number.

(38) As illustrated in FIG. 5, the support plate **31b** is provided with an air hole H5 to allow cooling air introduced into the heat insulating hood **40** to flow around the plurality of permanent magnets **31a**. The shape of the support plate **31b** is not limited to that shown in FIG. 5, but may be, for example, a substantially cross shape. The support plate **31c** in the same shape as that of the support plate **31b** may be used.

(39) It should be noted that in the magnetic field device **31**, either the support plate **31b** or the support plate **31c** may be omitted. In the case where the support plate **31b** is omitted, the plurality of permanent magnets **31a** is supported (suspended) by the support plate **31c**.

(40) FIG. 6 is a plan view of a magnetic field device **31A** according to a modification. In the magnetic field device **31A**, the support plate **31b** is in a plate rod shape, and the permanent magnet **31a** is fixed to each of the opposite ends of the support plate **31b**. In the present modification also, two permanent magnets **31a** are arranged such that different magnetic poles are alternately arrayed along the circumference of the rotary shaft **33**.

(41) Other than the above, the magnetic field device having six permanent magnets **31a**, eight permanent magnets **31a**, and so forth is conceivable. In general, the magnetic field device with a fewer number of permanent magnets has an advantage in that the magnetic force line ML reaches farther. Meanwhile, when the rotation speed of the magnetic field device **31** is the same, the magnetic field device with a greater number of permanent magnets **31a** has a greater temporal change in the magnetic force line in the metal melt, so that the melt driving force can be increased.

(42) As illustrated in FIG. 1, the electric motor **32** includes a rotary shaft **32a** and is installed on the mount **35** such that the rotary shaft **32a** is vertically oriented. The rotary shaft **32a** is connected to the rotary shaft **33** via the coupling **34**. The magnetic field device **31** rotates about the rotary shaft **33** by the rotation of the rotary shaft **32a**.

(43) As illustrated in FIG. 1, the electric motor **32** is electrically connected to a power control panel **60** via a connecting conductor **61**. For example, the electric motor **32** is a DC motor and is connected to a positive electrode terminal **60a** and a negative electrode terminal **60b** of the power control panel **60**. The rotation speed (namely, the rotation speed of the magnetic field device **31**) of the electric motor **32** can be controlled by adjusting the output (voltage, current, and the like) of the power control panel **60**. The ejection amount of the metal melt from the ejection port P2 of the melt flow passage body **20** can be increased by increasing the rotation speed of the electric motor **32**. In this manner, the electric motor **32** is configured such that the number of rotation of the magnetic field device **31** is variable in accordance with the ejection amount of the metal melt.

(44) It should be noted that the type of the electric motor **32** is not particularly limited, and may be

an AC motor or the like. Further, in the case of the AC motor, the rotation speed of the electric motor **32** may be controlled by an inverter (not shown) of the power control panel **60**.

(45) As illustrated in FIG. **1**, the rotary shaft **33** is inserted through the bearing housing **36** and the base plate **50** (shaft insertion hole **H4**) and connects the magnetic field device **31** and the electric motor **32**. A lower end of the rotary shaft **33** is fixed to the magnetic field device **31** (support plate **31b**) and an upper end of the rotary shaft **33** is connected to the rotary shaft **32a** of the electric motor **32** via the coupling **34**.

(46) The base plate **50** is a plate-like member provided so as to partition the inner space of the bottomed cylinder body **10**. A space that houses the magnetic field device **31** is defined by the base plate **50** and the bottomed cylinder body **10**. The base plate **50** is provided with air holes **H2** and **H3** and the shaft insertion hole **H4**. Specifically, as illustrated in FIG. **1**, the base plate **50** is provided with the air hole **H2** positioned on an outer side of a fixed hood **41**, and the air hole **H3** and the shaft insertion hole **H4** that are positioned on an inner side of the fixed hood **41**. It should be noted that the base plate **50** may be a cover plate that closes an upper end portion of the bottomed cylinder body **10**.

(47) The coupling **34** is a shaft coupling member that couples the rotary shaft **32a** of the electric motor **32** and the rotary shaft **33** fixed to the magnetic field device **31**.

(48) The mount **35** is fixed on the base plate **50**. The electric motor **32** is installed on the mount **35**. An upper face of the mount **35** is configured so as to allow cooling air to pass through. For example, the upper face of the mount **35** is formed in a mesh or a grid shape. It should be noted that in a case where the rotary shaft **32a** and the rotary shaft **33** are integrally formed or the like, the electric motor **32** may be directly installed on the base plate **50** by omitting the mount **35**.

(49) The bearing housing **36** houses a bearing (not shown) and is fixed to a lower face of the base plate **50** as illustrated in FIG. **1**.

(50) Next, the heat insulating hood **40** will be described.

(51) The heat insulating hood **40** is provided for protecting the melt driving part **30** (in particular, the magnetic field device **31**) from the heat of the metal melt inside the furnace. As illustrated in FIG. **1**, the heat insulating hood **40** is configured to cover the magnetic field device **31** and the electric motor **32** of the melt driving part **30** and to define a cooling air flow passage **S** for allowing the cooling air introduced from the outside to flow through the magnetic field device **31** and the electric motor **32**.

(52) In the present embodiment, the heat insulating hood **40** includes the fixed hood **41** fixed to the base plate **50** and a movable hood **42** that rotates together with the magnetic field device **31**.

(53) The fixed hood **41** covers the electric motor **32** and is provided with an air intake hole **H1** for taking in the cooling air from the outside. In the present embodiment, the air intake hole **H1** is provided on an upper face of an upper side fixed hood **41a**. A blower (not shown) may be connected to the air intake hole **H1**.

(54) The movable hood **42** is attached to the magnetic field device **31** so as to define, together with the fixed hood **41**, the cooling air flow passage **S** and to cover an outer periphery surface of the magnetic field device **31**. As illustrated in FIG. **1**, in the present embodiment, the inner diameter of an upper end portion of the movable hood **42** is adjusted to be slightly greater than the outer diameter of the fixed hood **41** (lower side fixed hood **41b**) and a lower end portion of the fixed hood **41** (lower side fixed hood **41b**) is loosely inserted into the upper end portion of the movable hood **42**. With a small gap provided between the fixed hood **41** and the movable hood **42**, the movable hood **42** is rotatable while the cooling air is prevented from leaking. It should be noted that the upper end portion of the movable hood **42** may be loosely inserted into the lower end portion of the fixed hood **41** (lower side fixed hood **41b**).

(55) The heat insulating hood **40** (fixed hood **41** and movable hood **42**) is preferably formed of material that is relatively thin, but still satisfies required mechanical strength and heat resistance, for example, metal material, such as stainless steel. Even in the case where the movable hood **42** is

formed of metal material, since the movable hood **42** rotates together with the magnetic field device **31**, no eddy current occurs in the movable hood **42**. Thus, by adopting the configuration of the movable hood **42**, the rotation speed of the electric motor **32** can be significantly increased (e.g., 500 to 750 r/min at the maximum), as compared to the case in which the fixed hood **41** covers the magnetic field device **31**. As a result, the force to drive the metal melt can be significantly improved.

(56) It should be noted that in order to improve the heat insulating effect, a heat insulating material is preferably affixed to the fixed hood **41** and the movable hood **42**.

(57) The fixed hood **41** of the present embodiment includes the upper side fixed hood **41a** and the lower side fixed hood **41b**.

(58) The upper side fixed hood **41a** is a cylinder body with a lower end portion fixed to an upper face of the base plate **50**. As illustrated in FIG. **1**, in the upper side fixed hood **41a** of the present embodiment, an upper end portion is closed and the upper face is provided with the air intake hole **H1**. It should be noted that the air intake hole **H1** may be provided on a side face of the upper side fixed hood **41a**. Further, the upper side fixed hood **41a** may be a cylinder body with the upper end portion opened. The shape of the upper side fixed hood **41a** is not limited to a cylinder shape, but may be a dome shape or the like.

(59) The lower side fixed hood **41b** is a cylinder body with an upper end portion fixed to the lower face of the base plate **50**. In the present embodiment, in the lower side fixed hood **41b**, the upper end portion and the lower end portion are opened and the upper end portion is fixed to the lower face of the base plate **50**.

(60) It should be noted that the fixed hood **41** may be integrally formed instead of being formed with separate bodies, such as the upper side fixed hood **41a** and the lower side fixed hood **41b**. In this case, for example, the fixed hood **41** is fixed to the base plate **50** in a state of penetrating the base plate **50**.

(61) <Operation of Metal Melt Pump **1**>

(62) Next, the operation of the above-described metal melt pump **1** according to the embodiment will be described.

(63) As illustrated in FIG. **7**, the metal melt pump **1** is sunk in metal melt **M** inside a furnace **100**. The furnace **100** is, for example, a melting furnace for melting non-ferrous metal, such as aluminum, or a holding furnace for holding metal melt. It should be noted that the non-ferrous metal may be, for example, Al, Cu, and Zn or at least two alloys of these, or an Mg alloy.

(64) It should be noted that it is preferable that before installing the metal melt pump **1** inside the furnace **100**, the bottomed cylinder body **10** and the melt flow passage body **20** be pre-heated for reducing the thermal impact. The pre-heating processing is performed by, for example, blowing hot air from the air intake hole **H1**.

(65) Subsequently, the power control panel **60** is operated to drive the electric motor **32** at a rotation speed in accordance with a desired ejection amount. With the rotation of the magnetic field device **31**, the magnetic force line **ML** that is output from a certain permanent magnet **31a** to enter the adjacent permanent magnet **31a** moves while penetrating metal melt **M'** in the melt flow passage **C**. The movement of the magnetic force line **ML** generates eddy current in the metal melt **M'**. By the electromagnetic force acting on the metal melt **M'** due to the eddy current, the metal melt **M'** in the melt flow passage **C** is driven in the circumferential direction of the rotary shaft **33** as illustrated in FIG. **8**. In this manner, the metal melt **M'** in the melt flow passage **C** is ejected from the ejection port **P2** and the external metal melt **M** in the furnace **100** is sucked from the suction port **P1** into the melt flow passage **C**. As a result, the metal melt inside the furnace **100** circulates.

(66) It should be noted that during the operation of the metal melt pump **1**, cooling air **A** is blown into the heat insulating hood **40** via the air intake hole **H1** to cool the magnetic field device **31** and the electric motor **32**. As illustrated in FIG. **7**, the cooling air taken in from the air intake hole **H1** of the fixed hood **41** cools the electric motor **32**, and then passes the air hole **H3** to flow through the

cooling air flow passage S downward, passes the magnetic field device **31**, and is released from the lower end portion of the movable hood **42**, and subsequently, passes a space (cooling air flow passage T) between the side wall **11** of the bottomed cylinder body **10** and the heat insulating hood **40** and is discharged to the outside from the air hole H2 of the base plate **50**. In this manner, the cooling air is prevented from stagnating on a bottom portion of the bottomed cylinder body **10** so that the magnetic field device **31** and the electric motor **32** can be effectively cooled.

(67) Further, the metal melt pump **1** is usable not only for circulating the metal melt inside the furnace, but also for pumping the metal melt. In this case, as illustrated in FIG. **9**, a melt discharge pipe **25** is connected to the ejection port P2 of the melt flow passage C. The melt discharge pipe **25** is connected at one end to the ejection port P2 of the melt flow passage body **20** and the other end (discharge port P3) is opened. The discharge port P3 is positioned above a melt level M.L in the state in which the metal melt pump **1** is installed inside the furnace. In this manner, the metal melt in the melt flow passage C is driven to be ejected from the ejection port P2, and then passes through the melt discharge pipe **25** to be pumped up into an external tub (not shown) or the like.

(68) As described above, in the metal melt pump **1** according to the present embodiment, the melt flow passage body **20** is removably provided on the bottomed cylinder body **10** as a body separate from the bottomed cylinder body **10**. More specifically, the melt flow passage body **20** is removably provided on the bottomed cylinder body **10** at a position around the side wall **11** of the bottomed cylinder body **10** and where the magnetic force line from the first permanent magnet among the plurality of permanent magnets **31a** penetrates through the side wall **11** and the inner side flow passage wall **21** to reach the melt flow passage C and penetrates from the melt flow passage C through the inner side flow passage wall **21** and the side wall **11** to return to the second permanent magnet adjacent to the first permanent magnet. In this manner, according to the present embodiment, the melt flow passage C can be renewed easily and at low cost. Consequently, the metal melt in the melt flow passage C can be efficiently driven in use, and in a case where the ejection amount decreases, the performance of the metal melt pump can be recovered quickly and at low cost by replacing the melt flow passage body **20**.

(69) Further, according to the present embodiment, since the melt flow passage body **20** that is a body separate from the bottomed cylinder body **10** is provided with the melt flow passage C, the cross-sectional area of the flow passage can be easily enlarged as compared to the case in which the melt flow passage is provided inside the side wall as in the conventional metal melt pump. In this manner, the ejection amount of the metal melt can be significantly increased. Even when the cross-sectional area of the flow passage of the melt flow passage C is enlarged, the weight of the bottomed cylinder body **10** is unchanged, thereby being able to suppress the increase in the weight of the metal melt pump **1**. Therefore, operability of the metal melt pump **1** is prevented from degrading, thereby allowing the installation work or the like in the furnace to be relatively easily performed.

(70) Furthermore, according to the present embodiment, the heat insulating hood **40** thermally protects the melt driving part **30** and defines the cooling air flow passages S and T. In this manner, stagnation of the cooling air on the bottom portion of the bottomed cylinder body **10** as in the conventional metal melt pump is suppressed so that the cooling efficiency can be improved.

(71) In addition, according to the present embodiment, even in the case where the movable hood **42** is formed of metal material, since the movable hood **42** of the heat insulating hood **40** is configured so as to rotate together with the magnetic field device **31**, eddy current can be prevented from occurring in the movable hood **42** during the rotation of the magnetic field device **31**. In this manner, the rotation speed of the magnetic field device **31** can be set high to thus be able to significantly increase the ejection amount of the metal melt while saving the power consumption. As a result, the metal melt inside the furnace can be sufficiently circulated using the metal melt pump **1**.

(72) It should be noted that the heat insulating hood may be applied to a metal melt pump in which

the melt flow passage is formed in the side wall of the bottomed cylinder body, without limiting to the configuration of the aforementioned embodiment. Thus, for example, the cooling efficiency of the permanent magnets or the like of the metal melt pump of Japanese Patent No. 5546974 can be improved.

(73) A person skilled in the art may be able to conceive of additional effects or various modifications of the present invention on the basis of the above description, but the aspect of the present invention is not limited to the aforementioned embodiment. Various additions, modifications, and partial deletion are available without departing the conceptual idea and the gist of the present invention derived from the content defined in the claims and the equivalents thereof.

REFERENCE NUMERAL LIST

(74) **1** metal melt pump **10** bottomed cylinder body **11** side wall **12** bottom wall **13** support part **20** melt flow passage body **21** inner side flow passage wall **22** outer side flow passage wall **23** upper side flow passage wall **24** lower side flow passage wall **25** melt discharge pipe **30** melt driving part **31**, **31A** magnetic field device **31a** permanent magnet **31b**, **31c** support plate **32** electric motor **32a** rotary shaft **33** rotary shaft **34** coupling **35** mount **36** bearing housing **40** heat insulating hood **41** fixed hood **41a** upper side fixed hood **41b** lower side fixed hood **42** movable hood **50** base plate **60** power control panel **60a**, **60b** terminal **61** connecting conductor **100** furnace A cooling air C melt flow passage H1 air intake hole H2, H3 air hole H4 shaft insertion hole H5, H6 air hole M, M' metal melt ML magnetic force line P1 suction port P2 ejection port P3 discharge port S, T cooling air flow passage

Claims

1. A metal melt pump that drives metal melt inside a furnace, the metal melt pump comprising: a bottomed cylinder body including a side wall and a bottom wall; a melt flow passage body including a melt flow passage that connects a suction port and an ejection port, the melt flow passage body being a body separate from the bottomed cylinder body; and a melt driving part including a magnetic field device rotatably disposed around a vertically oriented rotary shaft inside the bottomed cylinder body and an electric motor that rotates the magnetic field device, the melt driving part adapted to drive metal melt in the melt flow passage, wherein the magnetic field device includes a plurality of permanent magnets arranged such that different magnetic poles are alternately arrayed along a circumference of the rotary shaft, and the melt flow passage body is removably provided on the bottomed cylinder body at a position around the side wall of the bottomed cylinder body and where a magnetic force line from a first permanent magnet among the plurality of permanent magnets penetrates through the side wall of the bottomed cylinder body and an inner side flow passage wall of the melt flow passage body to reach the melt flow passage and penetrates from the melt flow passage through the inner side flow passage wall of the melt flow passage body and the side wall of the bottomed cylinder body to return to a second permanent magnet adjacent to the first permanent magnet, the metal melt pump further comprising: a heat insulating hood configured to cover the magnetic field device and the electric motor of the melt driving part and to define a cooling air flow passage for cooling air to flow through the magnetic field device and the electric motor, wherein the heat insulating hood comprises: a fixed hood fixed to a base plate that defines, together with the bottomed cylinder body, a space that houses the magnetic field device, the fixed hood covering the electric motor and provided with an air intake hole that takes in the cooling air; and a movable hood attached to the magnetic field device so as to define, together with the fixed hood, the cooling air flow passage and to cover an outer periphery surface of the magnetic field device, the movable hood adapted to rotate together with the magnetic field device, wherein a lower end portion of the fixed hood is loosely inserted into an upper end portion of the movable hood or the upper end portion of the movable hood is loosely inserted into the lower end portion of the fixed hood.

2. The metal melt pump according to claim 1, wherein a longitudinal cross-sectional shape of the melt flow passage is a vertically-long and substantially rectangular shape.
 3. The metal melt pump according to claim 1, wherein the plurality of permanent magnets of the magnetic field device is greater in a longitudinal length than the melt flow passage, and encompasses the melt flow passage in a longitudinal direction in a side view.
 4. The metal melt pump according to claim 1, wherein the melt flow passage body is provided so as to surround the side wall of the bottomed cylinder body.
 5. The metal melt pump according to claim 4, wherein the melt flow passage body has a planar shape in a substantially U-shape.
 6. The metal melt pump according to claim 1, wherein the fixed hood comprises: an upper side fixed hood with a lower end portion fixed to an upper face of the base plate; and a lower side fixed hood with an upper end portion fixed to a lower face of the base plate.
 7. The metal melt pump according to claim 1, wherein a heat insulating material is affixed to the fixed hood and the movable hood.
 8. The metal melt pump according to claim 1, wherein the fixed hood and the movable hood are formed of metal material.
 9. The metal melt pump according to claim 1, wherein the base plate is provided with a first air hole positioned on an inner side of the fixed hood and a second air hole positioned on an outer side of the fixed hood, and the cooling air taken in from the air intake hole of the fixed hood passes the first air hole to flow through the cooling air flow passage downward, passes the magnetic field device, and is released from a lower end portion of the movable hood, and subsequently, passes a space between the side wall of the bottomed cylinder body and the heat insulating hood and is discharged to an outside from the second air hole.
 10. The metal melt pump according to claim 1, wherein the bottomed cylinder body comprises a support part projecting radially outward from the side wall, and the melt flow passage body is removably supported on the bottomed cylinder body by means of the support part.
 11. The metal melt pump according to claim 1, wherein the electric motor is configured to change a rotation speed of the magnetic field device in accordance with an ejection amount of the metal melt.
 12. The metal melt pump according to claim 1, further comprising a melt discharge pipe connected to the ejection port of the melt flow passage and adapted to pump the metal melt.
-