

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405858
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Park; Sanghyun et al.

Electronic device for supporting data backup, and operation method thereof

Abstract

An electronic device is provided. The electronic device includes a processor, a communication circuit that establishes a connection between external storage and a device, and a memory operatively connected to the processor and storing instructions. When executed by the processor, the instructions may cause the electronic device to execute an application that provides a backup function, identify first data in response to a first user input to the application, identify a backup history stored in the memory, identify a data type of the first data in response to a fact that the at least one backup history is present, generate all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and store the generated backup data in the external storage.

Inventors: Park; Sanghyun (Suwon-si, KR), Kim; Heangsu (Suwon-si, KR), Oh; Myungkeun (Suwon-si, KR), Jung; Jieun (Suwon-si, KR), Lim; Yeunwook (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 82447440

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/351062

Filed: July 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230359530 A1	Nov. 09, 2023

Foreign Application Priority Data

KR	10-2021-0004038	Jan. 12, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/KR2021/018753 20211210 PENDING child-doc US 18351062

Publication Classification

Int. Cl.: **G06F12/00** (20060101); **G06F11/14** (20060101); **G06F21/31** (20130101); **G06F21/45** (20130101)

U.S. Cl.:

CPC **G06F11/1458** (20130101); **G06F11/1451** (20130101); **G06F21/31** (20130101); **G06F21/45** (20130101);

Field of Classification Search

CPC: G06F (11/1458); G06F (11/1451); G06F (21/31); G06F (21/45); G06F (11/14); G06F (11/1448); G06F (11/1456); G06F (11/1461); G06F (11/1464); G06F (11/1469)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7062621	12/2005	Mizuno et al.	N/A	N/A
7085904	12/2005	Mizuno et al.	N/A	N/A
7756833	12/2009	Ingen et al.	N/A	N/A
8031522	12/2010	Jang et al.	N/A	N/A
8223544	12/2011	Jang et al.	N/A	N/A
8533189	12/2012	Ingen et al.	N/A	N/A
8805953	12/2013	Murphy et al.	N/A	N/A
9317369	12/2015	Freedman et al.	N/A	N/A
9411687	12/2015	Freedman et al.	N/A	N/A
9894510	12/2017	Kortunov et al.	N/A	N/A
9904597	12/2017	Freedman et al.	N/A	N/A
10095715	12/2017	Yin	N/A	N/A
10455015	12/2018	Procopio et al.	N/A	N/A
11178224	12/2020	Procopio et al.	N/A	N/A
11245758	12/2021	Procopio et al.	N/A	N/A
2002/0107886	12/2001	Gentner	715/255	G06F 40/166
2005/0108484	12/2004	Park	N/A	N/A
2010/0250939	12/2009	Adams	713/168	H04L 63/10

2011/0016089	12/2010	Freedman	711/E12.001	G06F 11/1469
2013/0311597	12/2012	Arrouye et al.	N/A	N/A
2014/0188808	12/2013	Wolf	707/654	G06F 16/21
2018/0267862	12/2017	Aseev et al.	N/A	N/A
2018/0341556	12/2017	Lin	N/A	G06F 11/1464
2020/0279048	12/2019	Jang	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
06-168079	12/1993	JP	N/A
2005-122611	12/2004	JP	N/A
2006-211051	12/2005	JP	N/A
2019-159477	12/2018	JP	N/A
10-0359423	12/2001	KR	N/A
10-2007-0023129	12/2006	KR	N/A
10-0889781	12/2008	KR	N/A
10-1153023	12/2011	KR	N/A
10-1374533	12/2013	KR	N/A
10-2017-0088160	12/2016	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Mar. 24, 2022, issued in International Patent Application No. PCT/KR2021/0187 53. cited by applicant

Primary Examiner: Talukdar; Arvind

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This application is a continuation application, claiming priority under § 365(c), of an International application No. PCT/KR2021/018753, filed on Dec. 10, 2021, which is based on and claims the benefit of a Korean patent application number 10-2021-0004038, filed on Jan. 12, 2021, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(1) The disclosure relates to an electronic device supporting a data backup and an operating method thereof.

2. Description of Related Art

(2) A user of an electronic device may back up data, which is stored in the electronic device, in external storage in preparation for unexpected data loss or unintentional data deletion. When the user needs data thus backed up, the electronic device may restore the backup data.

(3) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

- (4) An electronic device may perform a plurality of backups at different points in time. In this case, backup data at a last point in time may be overwritten with backup data at a previous point in time.
- (5) Moreover, a plurality of electronic devices may store backup data in one external memory. In this case, backup data generated by one electronic device may be overwritten with backup data previously stored by another electronic device.
- (6) Aspects of the disclosure are to address at least the above-mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device supporting a data backup and an operating method thereof.
- (7) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.
- (8) In accordance with an aspect of the disclosure, an electronic device is provided. The electronic device includes at least one processor, a communication circuit that establishes a connection between external storage and a device, and a memory operatively connected to the at least one processor and storing instructions. When executed by the at least one processor, the instructions may cause the electronic device to execute an application that provides a backup function, to identify first data in response to a first user input to the application, to identify a backup history stored in the memory, to identify a data type of the first data in response to a fact that the at least one backup history is present, to generate all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and to store the generated backup data in the external storage.
- (9) In accordance with another aspect of the disclosure, a method of operating an electronic device is provided. The method includes executing an application that provides a backup function, identifying first data in response to a first user input to the application, identifying a backup history, identifying a data type of the first data in response to a fact that the at least one backup history is present, generating all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and storing the generated backup data in external storage.
- (10) According to embodiments disclosed in the specification, an electronic device may efficiently manage the storage space of external storage by providing a differential backup according to various points in time.
- (11) According to embodiments disclosed in the specification, an electronic device may enhance the security of backup and restoration functions by generating encrypted backup data based on a user account.
- (12) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a block diagram of an electronic device in a network environment according to an embodiment of the disclosure;
- (3) FIG. 2 illustrates a configuration of an electronic device according to an embodiment of the disclosure;

- (4) FIG. 3A is a flowchart illustrating generation and storage of backup data according to an embodiment of the disclosure;
- (5) FIG. 3B is a flowchart illustrating generation and storage of backup data according to an embodiment of the disclosure;
- (6) FIG. 4 is a flowchart illustrating an encryption operation of backup data according to an embodiment of the disclosure;
- (7) FIG. 5 is a flowchart illustrating data restoration according to an embodiment of the disclosure; and
- (8) FIG. 6 illustrates an application screen for data restoration according to an embodiment of the disclosure.
- (9) Throughout the drawings, like reference numerals will be understood to refer to like parts, components, and structures.

DETAILED DESCRIPTION

- (10) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit of the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.
- (11) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.
- (12) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.
- (13) FIG. 1 is a block diagram illustrating an electronic device in a network environment according to an embodiment of the disclosure.
- (14) Referring to FIG. 1, an electronic device **101** in a network environment **100** may communicate with an external electronic device **102** via a first network **198** (e.g., a short-range wireless communication network), or at least one of an external electronic device **104** or a server **108** via a second network **199** (e.g., a long-range wireless communication network). According to an embodiment of the disclosure, the electronic device **101** may communicate with the external electronic device **104** via the server **108**. According to an embodiment of the disclosure, the electronic device **101** may include a processor **120**, a memory **130**, an input module **150**, a sound output module **155**, the display module **160**, an audio module **170**, a sensor module **176**, an interface **177**, a connecting terminal **178**, a haptic module **179**, a camera module **180**, a power management module **188**, a battery **189**, a communication module **190**, a subscriber identification module (SIM) **196**, or an antenna module **197**. In some embodiments of the disclosure, at least one of the components (e.g., the connecting terminal **178**) may be omitted from the electronic device **101**, or one or more other components may be added in the electronic device **101**. In some embodiments of the disclosure, some of the components (e.g., the sensor module **176**, the camera module **180**, or the antenna module **197**) may be implemented as a single component (e.g., the display module **160**).
- (15) The processor **120** may execute, for example, software (e.g., a program **140**) to control at least one other component (e.g., a hardware or software component) of the electronic device **101** coupled with the processor **120**, and may perform various data processing or computation.

According to one embodiment of the disclosure, as at least part of the data processing or computation, the processor **120** may store a command or data received from another component (e.g., the sensor module **176** or the communication module **190**) in a volatile memory **132**, process the command or the data stored in the volatile memory **132**, and store resulting data in a non-volatile memory **134**. According to an embodiment of the disclosure, the processor **120** may include a main processor **121** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **123** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **121**. For example, when the electronic device **101** includes the main processor **121** and the auxiliary processor **123**, the auxiliary processor **123** may be adapted to consume less power than the main processor **121**, or to be specific to a specified function. The auxiliary processor **123** may be implemented as separate from, or as part of the main processor **121**.

(16) The auxiliary processor **123** may control at least some of functions or states related to at least one component (e.g., the display module **160**, the sensor module **176**, or the communication module **190**) among the components of the electronic device **101**, instead of the main processor **121** while the main processor **121** is in an inactive (e.g., a sleep) state, or together with the main processor **121** while the main processor **121** is in an active state (e.g., executing an application). According to an embodiment of the disclosure, the auxiliary processor **123** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **180** or the communication module **190**) functionally related to the auxiliary processor **123**. According to an embodiment of the disclosure, the auxiliary processor **123** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **101** where the artificial intelligence is performed or via a separate server (e.g., the server **108**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(17) The memory **130** may store various data used by at least one component (e.g., the processor **120** or the sensor module **176**) of the electronic device **101**. The various data may include, for example, software (e.g., the program **140**) and input data or output data for a command related thereto. The memory **130** may include the volatile memory **132** or the non-volatile memory **134**.

(18) The program **140** may be stored in the memory **130** as software, and may include, for example, an operating system (OS) **142**, middleware **144**, or an application **146**.

(19) The input module **150** may receive a command or data to be used by another component (e.g., the processor **120**) of the electronic device **101**, from the outside (e.g., a user) of the electronic device **101**. The input module **150** may include, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(20) The sound output module **155** may output sound signals to the outside of the electronic device **101**. The sound output module **155** may include, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment of the disclosure, the receiver may be implemented as separate from, or as part of the speaker.

(21) The display module **160** may visually provide information to the outside (e.g., a user) of the electronic device **101**. The display module **160** may include, for example, a display, a hologram

device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment of the disclosure, the display module **160** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(22) The audio module **170** may convert a sound into an electrical signal and vice versa. According to an embodiment of the disclosure, the audio module **170** may obtain the sound via the input module **150**, or output the sound via the sound output module **155** or a headphone of an external electronic device (e.g., the external electronic device **102**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **101**.

(23) The sensor module **176** may detect an operational state (e.g., power or temperature) of the electronic device **101** or an environmental state (e.g., a state of a user) external to the electronic device **101**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment of the disclosure, the sensor module **176** may include, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(24) The interface **177** may support one or more specified protocols to be used for the electronic device **101** to be coupled with the external electronic device (e.g., the external electronic device **102**) directly (e.g., wiredly) or wirelessly. According to an embodiment of the disclosure, the interface **177** may include, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(25) A connecting terminal **178** may include a connector via which the electronic device **101** may be physically connected with the external electronic device (e.g., the external electronic device **102**). According to an embodiment of the disclosure, the connecting terminal **178** may include, for example, a HDMI connector, a USB connector, a SD card connector, or an audio connector (e.g., a headphone connector).

(26) The haptic module **179** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment of the disclosure, the haptic module **179** may include, for example, a motor, a piezoelectric element of the disclosure, or an electric stimulator.

(27) The camera module **180** may capture a still image or moving images. According to an embodiment of the disclosure, the camera module **180** may include one or more lenses, image sensors, image signal processors, or flashes.

(28) The power management module **188** may manage power supplied to the electronic device **101**. According to one embodiment of the disclosure, the power management module **188** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(29) The battery **189** may supply power to at least one component of the electronic device **101**. According to an embodiment of the disclosure, the battery **189** may include, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(30) The communication module **190** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **101** and the external electronic device (e.g., the external electronic device **102**, the external electronic device **104**, or the server **108**) and performing communication via the established communication channel. The communication module **190** may include one or more communication processors that are operable independently from the processor **120** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment of the disclosure, the communication module **190** may include a wireless communication module **192** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or

a wired communication module **194** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **198** (e.g., a short-range communication network, such as Bluetooth™, wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **199** (e.g., a long-range communication network, such as a legacy cellular network, a 5th generation (5G) network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **192** may identify and authenticate the electronic device **101** in a communication network, such as the first network **198** or the second network **199**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **196**.

(31) The wireless communication module **192** may support a 5G network, after a 4th generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **192** may support a high-frequency band (e.g., the mmWave band) to achieve, e.g., a high data transmission rate. The wireless communication module **192** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **192** may support various requirements specified in the electronic device **101**, an external electronic device (e.g., the external electronic device **104**), or a network system (e.g., the second network **199**). According to an embodiment of the disclosure, the wireless communication module **192** may support a peak data rate (e.g., 20 Gbps or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 ms or less for each of downlink (DL) and uplink (UL), or a round trip of 1 ms or less) for implementing URLLC.

(32) The antenna module **197** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **101**. According to an embodiment of the disclosure, the antenna module **197** may include an antenna including a radiating element including a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment of the disclosure, the antenna module **197** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **198** or the second network **199**, may be selected, for example, by the communication module **190** (e.g., the wireless communication module **192**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **190** and the external electronic device via the selected at least one antenna. According to an embodiment of the disclosure, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **197**.

(33) According to various embodiments of the disclosure, the antenna module **197** may form a mmWave antenna module. According to an embodiment of the disclosure, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(34) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(35) According to an embodiment of the disclosure, commands or data may be transmitted or received between the electronic device **101** and the external electronic device **104** via the server **108** coupled with the second network **199**. Each of the external electronic devices **102** or **104** may be a device of a same type as, or a different type, from the electronic device **101**. According to an embodiment of the disclosure, all or some of operations to be executed at the electronic device **101** may be executed at one or more of the external electronic devices **102**, **104**, or **108**. For example, if the electronic device **101** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **101**, instead of, or in addition to, executing the function or the service, may request the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **101**. The electronic device **101** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **101** may provide ultra low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment of the disclosure, the external electronic device **104** may include an internet-of-things (IoT) device. The server **108** may be an intelligent server using machine learning and/or a neural network. According to an embodiment of the disclosure, the external electronic device **104** or the server **108** may be included in the second network **199**. The electronic device **101** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(36) The electronic device according to various embodiments of the disclosure may be one of various types of electronic devices. The electronic devices may include, for example, a portable communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(37) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit the technological features set forth herein to particular embodiments and include various changes, equivalents, or replacements for a corresponding embodiment. With regard to the description of the drawings, similar reference numerals may be used to refer to similar or related elements. It is to be understood that a singular form of a noun corresponding to an item may include one or more of the things, unless the relevant context clearly indicates otherwise. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include any one of, or all possible combinations of the items enumerated together in a corresponding one of the phrases. As used herein, such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). It is to be understood that if an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(38) As used in connection with various embodiments of the disclosure, the term “module” may include a unit implemented in hardware, software, or firmware, and may interchangeably be used

with other terms, for example, “logic,” “logic block,” “part,” or “circuitry”. A module may be a single integral component, or a minimum unit or part thereof, adapted to perform one or more functions. For example, according to an embodiment of the disclosure, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(39) Various embodiments as set forth herein may be implemented as software (e.g., the program **140**) including one or more instructions that are stored in a storage medium (e.g., an internal memory **136** or an external memory **138**) that is readable by a machine (e.g., the electronic device **101**). For example, a processor (e.g., the processor **120**) of the machine (e.g., the electronic device **101**) may invoke at least one of the one or more instructions stored in the storage medium, and execute it, with or without using one or more other components under the control of the processor. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Wherein, the term “non-transitory” simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between where data is semi-permanently stored in the storage medium and where the data is temporarily stored in the storage medium.

(40) According to an embodiment of the disclosure, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., a compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) online via an application store (e.g., PlayStore™), or between two user devices (e.g., smart phones) directly. If distributed online, at least part of the computer program product may be temporarily generated or at least temporarily stored in the machine-readable storage medium, such as a memory of the manufacturer's server, a server of the application store, or a relay server.

(41) According to various embodiments of the disclosure, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately disposed in different components. According to various embodiments of the disclosure, one or more of the above-described components may be omitted, or one or more other components may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated into a single component. In such a case, according to various embodiments of the disclosure, the integrated component may still perform one or more functions of each of the plurality of components in the same or similar manner as they are performed by a corresponding one of the plurality of components before the integration. According to various embodiments of the disclosure, operations performed by the module, the program, or another component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(42) FIG. 2 illustrates a configuration of an electronic device according to an embodiment of the disclosure.

(43) Referring to FIG. 2, according to an embodiment of the disclosure, an electronic device **200** (e.g., the electronic device **101** of FIG. 1) may include a processor **210**, a communication circuit **220**, and/or a memory **230**.

(44) The electronic device **200** may include at least part of components of the electronic device **101** of FIG. 1. For example, the electronic device **200** may further include the battery **189** of FIG. 1.

(45) According to an embodiment of the disclosure, the processor **210**, the communication circuit **220**, or the memory **230** may correspond to the processor **120**, the communication module **190**, or the memory **130** of FIG. 1, respectively.

(46) According to an embodiment of the disclosure, the processor **210** may establish a connection

between external storage **240** (e.g., the external electronic device **102** or the external electronic device **104** in FIG. **1**) and a device by using the communication circuit **220**. A connection between devices provided by the communication circuit **220** may be wired communication or wireless communication. For example, the external storage **240** may be memory included in at least one server **250** (e.g., the server **108** of FIG. **1**). For another example, the external storage **240** may include magnetic storage (e.g., an external hard disk drive) and/or a flash memory device (e.g., a memory card, a memory stick, or a universal serial bus (USB) drive). According to an embodiment of the disclosure, the processor **210** may establish a connection between the external storage **240** and a device through a USB interface (e.g., the interface **177** in FIG. **1**).

(47) According to an embodiment of the disclosure, the processor **210** may execute an application (e.g., the application **146** of FIG. **1**) providing a backup function.

(48) The processor **210** may generate backup data based on a user input for the application. According to an embodiment of the disclosure, the processor **210** may generate backup data based on a backup method (e.g., a full backup or a differential backup).

(49) According to an embodiment of the disclosure, the differential backup method may be a method of generating some data, which is generated after a point in time according to the latest backup history, from among data identified based on a user input as backup data. The processor **210** may reduce the amount of redundant data between pieces of backup data through the differential backup. The full backup method may be a method of generating all of the data identified based on a user input as backup data.

(50) In an embodiment of the disclosure, a backup method may be determined based on backup history information stored in the external storage **240**. In an embodiment of the disclosure, the backup method may be determined based on a data type of data to be backed up. In an embodiment of the disclosure, the backup method may be determined based on the size of data to be backed up. In an embodiment of the disclosure, the data to be backed up may be identified by a user input.

(51) According to an embodiment of the disclosure, the data type may include a first data type and a second data type. The first data type may include at least one of a photo, music, a video, a document, a voice record, a lyric, a certificate, or a playlist. According to an embodiment of the disclosure, the first data type may be stored in a data format (e.g., a file) having a specified extension name. For example, the photo may be stored in a jpg or png file; the music may be stored in an mp3 file; and, the document may be stored in a doc or ppt file. According to an embodiment of the disclosure, the second data type may include at least one of a contact, a calendar, a text, a memo, an android application package (APK), a homescreen setting (e.g., a layout, a wallpaper, or a setting value), a Wi-Fi setting, a Bluetooth setting, a keyboard setting, an accessibility setting, a font setting, a camera setting, an always on display (AOD) setting, an edge panel setting, and a notification setting. According to an embodiment of the disclosure, the second data type may be stored in a personal information management system (PIMS) data format.

(52) The processor **210** may store the generated backup data in the external storage **240** through the connection between devices.

(53) According to an embodiment of the disclosure, the processor **210** may encrypt backup data based on a user account. According to an embodiment of the disclosure, the processor **210** may make a request for user authentication to the at least one server **250** (e.g., the server **108** of FIG. **1**) in response to a user input. When the at least one server **250** succeeds in the user authentication, the processor **210** may receive an encryption key from the at least one server **250**. According to an embodiment of the disclosure, the encryption key may be understood as an account key based on a user account. The processor **210** may encrypt the generated backup data based on the encryption key. The processor **210** may store the encrypted backup data in the external storage **240**.

(54) According to an embodiment of the disclosure, the processor **210** may perform data restoration by using the backup data stored in the external storage **240**. According to an embodiment of the disclosure, the external storage **240** may store pieces of backup data generated by the electronic

device **200** or at least one external electronic device **260**. The pieces of backup data may be identified based on a user account. For example, the pieces of backup data may include user account information linked to an electronic device (e.g., the electronic device **200** or the at least one external electronic device **260**) that has generated corresponding backup data. Alternatively, the pieces of backup data may be encrypted based on a user account linked to an electronic device that has generated the corresponding backup data. The processor **210** may perform data restoration by using only backup data generated based on the same user account as a user account linked to the electronic device **200**, from among the pieces of backup data stored in the external storage **240**.

(55) According to an embodiment of the disclosure, the processor **210** may perform data restoration by using at least one backup data stored in the external storage **240**. The at least one backup data may be understood as backup data generated based on the same user account as a user account linked to the electronic device **200**. The processor **210** may select at least one backup data to be used for data restoration based on a user input to an application. For example, when pieces of backup data generated at different time points are stored in the external storage **240**, the processor **210** may perform data restoration by using at least part of the pieces of backup data based on a user input.

(56) According to an embodiment of the disclosure, the processor **210** may perform data restoration based on a user account. According to an embodiment of the disclosure, when performing the data restoration, the processor **210** may make a request for user authentication to the at least one server **250** in response to a user input. When the at least one server **250** succeeds in the user authentication, the processor **210** may receive a decryption key from the at least one server **250**. The decryption key may be understood as an account key based on a user account. In this case, the encryption key and decryption key may be symmetric keys. The processor **210** may decrypt at least one encrypted backup data based on the decryption key. The processor **210** may perform data backup by using the decrypted at least one backup data.

(57) According to an embodiment of the disclosure, the electronic device **200** may include the processor **210**, the communication circuit **220** that establishes a connection between the external storage **240** and a device, and the memory **230** operatively connected to the processor **210** and storing instructions. When executed by the processor **210**, the instructions may cause the electronic device **200** to execute an application that provides a backup function, to identify first data in response to a first user input to the application, to identify a backup history, which is associated with the first data and stored in the memory **230**, to identify a data type of the first data in response to a fact that the at least one backup history is present, to generate all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and to store the generated backup data in the external storage **240**. According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to generate all of the first data as backup data in response to a fact that the backup history is not present.

(58) According to an embodiment of the disclosure, the data type may include a first data type and a second data type. The first data type may include at least one of a video file or an image file. The second data type may include at least one of a contact, a message history, or calendar information. According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to generate the part of the first data, which is generated after a point in time according to the latest backup history, as backup data when a data type of the first data is the first data type, and to generate all of the first data as backup data when the data type of the first data is the second data type. For example, the external storage **240** may include magnetic storage (e.g., an external hard disk drive) and/or a flash memory device (e.g., a memory card, a memory stick, or a USB drive). According to an embodiment of the disclosure, the processor **210** may establish a connection between the external storage **240** and a device through a USB interface.

(59) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to make a request for user authentication to at least one server in response to the first user input, to receive an encryption key from the at least one server **250** based on the user authentication result, and to encrypt the backup data based on the encryption key.

(60) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to receive a second user input for data restoration to the application, to identify at least one of pieces of backup data stored in the external storage based on the second user input, and to decrypt the identified at least one backup data. The pieces of backup data may have different generation time points, respectively. According to an embodiment of the disclosure, the pieces of backup data stored in the external storage may be generated based on a user account linked to the electronic device.

(61) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to make a request for user authentication to the at least one server **250** in response to the second user input, to receive a decryption key from the at least one server **250** based on the user authentication result, and to decrypt the identified at least one backup data based on the decryption key. The decryption key may correspond to the encryption key.

(62) According to an embodiment of the disclosure, the electronic device may further include a display (e.g., the display module **160** of FIG. **1**). When executed by the processor **210**, the instructions may cause the electronic device **200** to display, through the display, a graphic object corresponding to the pieces of backup data stored in the external storage **240** together with at least one of a generation time of each of the pieces of backup data, information about a device generating the pieces of backup data, or a data capacity.

(63) According to an embodiment of the disclosure, the electronic device **200** may include the processor **210**, the communication circuit **220** that establishes a connection between the external storage **240** and a device, and the memory **230** operatively connected to the processor **210** and storing instructions. When executed by the processor **210**, the instructions may cause the electronic device **200** to execute an application that provides a backup function, to identify first data in response to a first user input to the application, to identify a backup history, which is stored in the memory **230**, to identify a data type of the first data in response to a fact that the at least one backup history is present, to generate all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and to store the generated backup data in the external storage **240**. For example, when executed by the processor **210**, the instructions may cause the electronic device **200** to generate all of the first data as backup data in response to a fact that the backup history is not present.

(64) According to an embodiment of the disclosure, the data type may include a first data type and a second data type. The first data type may include at least one of a video file or an image file. The second data type may include at least one of a contact, a message history, or calendar information. According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to generate the part of the first data, which is generated after a point in time according to the latest backup history, as backup data when a data type of the first data is the first data type, and to generate all of the first data as backup data when the data type of the first data is the second data type.

(65) According to an embodiment of the disclosure, the external storage **240** may include at least one of a solid state drive (SSD), a hard disk drive (HDD), or a universal serial bus (USB) drive.

(66) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to make a request for user authentication to at least one server **250** in response to the first user input, to receive an encryption key from the at least one server **250** based on the user authentication result, and to encrypt the backup data based on the

encryption key.

(67) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to receive a second user input for data restoration to the application, to identify at least one of pieces of backup data stored in the external storage based on the second user input, and to decrypt the identified at least one backup data. The pieces of backup data may have different generation time points, respectively. According to an embodiment of the disclosure, the pieces of backup data stored in the external storage may be generated based on a user account linked to the electronic device.

(68) According to an embodiment of the disclosure, when executed by the processor **210**, the instructions may cause the electronic device **200** to make a request for user authentication to the at least one server **250** in response to the second user input, to receive a decryption key from the at least one server **250** based on the user authentication result, and to decrypt the identified at least one backup data based on the decryption key. The decryption key may correspond to the encryption key.

(69) According to an embodiment of the disclosure, the electronic device may further include a display (e.g., the display module **160** of FIG. **1**). When executed by the processor **210**, the instructions may cause the electronic device **200** to display, through the display, a graphic object corresponding to the pieces of backup data stored in the external storage **240** together with at least one of a generation time of each of the pieces of backup data, information about a device generating the pieces of backup data, or a data capacity. The second user input may include a user input to a graphic object.

(70) FIG. **3A** is a flowchart illustrating generation and storage of backup data according to an embodiment of the disclosure.

(71) Referring to FIG. **3A**, operation **300**, a processor (e.g., the processor **210** in FIG. **2**) may execute an application providing a backup function.

(72) In operation **310**, the processor **210** may receive a first user input to an application. For example, the first user input may be understood as a user's touch input to a display (e.g., the display module **160** of FIG. **1**). Besides, the user input may include all the specified interactions (e.g., gestures or voice commands) to cause an electronic device (e.g., the electronic device **101** in FIG. **1** or the electronic device **200** in FIG. **2**) to perform the specified operation. According to an embodiment of the disclosure, the first user input may include at least one user input for performing operations of FIG. **3A**.

(73) In operation **320**, the processor **210** may identify first data in response to the first user input. The first data may be understood as data to be backed up.

(74) In operation **330**, the processor **210** may identify a backup history stored in a memory (e.g., the memory **230** of FIG. **2**). The backup history may include information related to the backup performed before operation **310**. According to an embodiment of the disclosure, the backup history of operation **330** may include information related to the backup performed based on a user account linked to the electronic device **200**.

(75) In operation **340**, the processor **210** may determine whether at least one backup history is present, based on the backup history.

(76) When the at least one backup history is present (operation **340**—YES), the processor **210** may proceed to operation **350**. In operation **350**, the processor **210** may identify the data type of first data. According to an embodiment of the disclosure, the first data may correspond to a first data type or a second data type. Alternatively, some of the first data may correspond to the first data type, and the others thereof may correspond to the second data type.

(77) According to an embodiment of the disclosure, the first data type may include at least one of a photo, music, a video, a document, a voice record, a lyric, a certificate, or a playlist. The second data type may include at least one of a contact, a calendar, a text, a memo, APK, a homescreen setting (e.g., a layout, a wallpaper, or a setting value), a Wi-Fi setting, a Bluetooth setting, a

keyboard setting, an accessibility setting, a font setting, a camera setting, an AOD setting, an edge panel setting, and a notification setting. According to an embodiment of the disclosure, the first data type may be understood as a data type that generally has a larger data capacity than the second data type.

(78) In operation **355**, the processor **210** may generate all of the first data or a part of the first data, which is generated after a point in time according to the latest backup history, as backup data based on the data type of the first data.

(79) According to an embodiment of the disclosure, when the data type of the first data is the first data type, the processor **210** may perform a differential backup on the first data. In other words, the processor **210** may generate a part of the first data, which is generated after a point in time according to the latest backup history as backup data. Through the differential backup, the processor **210** may reduce the amount of redundant data between pieces of backup data. The processor **210** may efficiently manage the storage space of the external storage **240** by reducing the total data capacity of accumulated backup data.

(80) According to an embodiment of the disclosure, when the data type of the first data is the second data type, the processor **210** may perform a full backup on the first data. In other words, the processor **210** may generate all of the first data as backup data. Data of the second data type may have a data capacity smaller than data of the first data type. Accordingly, the possibility of causing the external storage **240** to run out of storage space due to the accumulated backup data may be low. Accordingly, the processor **210** may generate all of the first data of the second data type as backup data regardless of the backup history.

(81) When the part of the first data corresponds to the first data type and the other(s) thereof corresponds to the second data type, the processor **210** may perform an operation according to operation **355** depending on each data type. For example, the processor **210** may perform a differential backup on a part of the first data corresponding to the first data type, and may perform a full backup on a part of the first data corresponding to the second data type.

(82) When there is no at least one backup history (operation **340**—NO), the processor **210** may proceed to operation **360**. In operation **360**, the processor **210** may generate all of the first data as backup data. According to an embodiment of the disclosure, the backup data generated in operation **360** may be the first backup data generated based on a user account linked to the electronic device **200**.

(83) In operation **370**, the processor **210** may store the backup data, which is generated in operation **355** or operation **360**, in the external storage **240**. For example, the external storage **240** may include magnetic storage (e.g., an external hard disk drive) and/or a flash memory device (e.g., a memory card, a memory stick, or a USB drive). According to an embodiment of the disclosure, the processor **210** may establish a connection between the external storage **240** and a device through a USB interface. For another example, the external storage **240** may be a memory included in the at least one server **250**.

(84) According to an embodiment of the disclosure, a method of operating the electronic device **200** may include executing an application that provides a backup function, identifying first data in response to a first user input to the application, identifying a backup history associated with first data, identifying a data type of the first data in response to a fact that the at least one backup history is present, generating all of the first data or a part of the first data, which is generated after a point in time according to a latest backup history, as backup data based on the data type, and storing the generated backup data in external storage. According to an embodiment of the disclosure, the method of the electronic device **200** may further include generating all of the first data as backup data in response to a fact that the backup history is not present.

(85) According to an embodiment of the disclosure, the data type may include a first data type and a second data type. The first data type may include at least one of a video file or an image file. The second data type may include at least one of a contact, a message history, or calendar information.

(86) According to an embodiment of the disclosure, the method of the electronic device **200** may further include generating the part of the first data, which is generated after a point in time according to the latest backup history, as backup data when a data type of the first data is the first data type, and generating all of the first data as backup data when the data type of the first data is the second data type.

(87) According to an embodiment of the disclosure, the external storage **240** may include at least one of a solid state drive (SSD), a hard disk drive (HDD), or a universal serial bus (USB) drive.

(88) FIG. **3B** is a flowchart illustrating generation and storage of backup data according to an embodiment of the disclosure.

(89) Referring to FIG. **3B**, the same reference numerals among reference numerals of FIG. **3B** as those of FIG. **3A** may be referenced by the description of FIG. **3A**. Hereinafter, differences between FIGS. **3B** and **3A** will be mainly described.

(90) In operation **352**, the processor **210** may identify the size of first data. According to an embodiment of the disclosure, the processor **210** may identify the size of the entire first data. According to an embodiment of the disclosure, the processor **210** may identify a data type of the first data. When first data includes data based on a plurality of data types, the processor **210** may identify the size of data according to each data type. A description of a data type may be referenced by the description of the data type of FIG. **3A**.

(91) In operation **357**, the processor **210** may generate all of the first data or a part of the first data, which is generated after a point in time according to the latest backup history, as backup data based on the size of the first data. According to an embodiment of the disclosure, the processor **210** may determine whether to perform a full backup or a differential backup, by comparing the size of first data with a threshold value. The threshold value may be set to a value that allows the storage space occupied by backup data in the external storage **240** to be less than or equal to a specific level.

(92) According to an embodiment of the disclosure, when the size of the first data is not less than the threshold value, the processor **210** may perform the differential backup. When the size of the first data is less than the threshold value, the processor **210** may perform the full backup. For example, when the size of the entire first data is less than the threshold value, the processor **210** may efficiently manage the storage space of the external storage **240** by performing a full backup regardless of the data type. For another example, the processor **210** may differently set threshold values for first data type-based data and second data type-based data. The processor **210** may determine each backup method by comparing the size of the first data type-based data with a first threshold value and comparing the size of the second data type-based data with a second threshold value.

(93) According to another embodiment of the disclosure, the processor **210** may identify data types of data included in the first data. In some cases, the second data type of data may occupy storage space larger than the first data type of data. For example, when a memo (e.g., the second data type of data) having attached images and/or videos (e.g., the first data type of data) is backed up, the size of memo data may be larger than the size of the first data type-based data. According to an embodiment of the disclosure, the processor **210** may set different threshold values depending on the relative ratio of data based on the first data type and data based on the second data type. For example, the processor **210** may determine a threshold value for the second data type by comparing the size of the second data type-based data included in the first data with the size of the first data type-based data. The processor **210** may determine a backup method by comparing the size of the second data type-based data with a threshold value. In this case, the processor **210** may perform a differential backup on the first data type-based data. Alternatively, the processor **210** may determine a backup method by comparing the first data type-based data with a threshold value (e.g., the same as or different from the threshold value for the second data type-based data).

(94) FIG. **4** is a flowchart illustrating an encryption operation of backup data according to an embodiment of the disclosure.

(95) Referring to FIG. 4, operations of the electronic device (e.g., the electronic device **200** of FIG. 2) of FIG. 4 are obtained by adding a security operation to the operations of the electronic device **200** of FIG. 3A. Operation **400** and operation **410** of FIG. 4 may correspond to operation **300** and operation **310** of FIG. 3A, respectively.

(96) In operation **400**, the processor **210** may execute an application providing a backup function.

(97) In operation **410**, the processor **210** may receive a first user input to an application.

(98) In operation **420**, the processor **210** may make a request for user authentication to at least one server (e.g., the at least one server **250** of FIG. 2) in response to a first user input. The at least one server **250** may perform user authentication based on a user account in response to a user authentication request.

(99) According to an embodiment of the disclosure, in operation **430**, the processor **210** may determine whether user authentication is successful. For example, the user authentication of the at least one server **250** may require a user to enter an identifier (ID) and password. The at least one server **250** may determine whether the user of the electronic device **200** is a user registered in the at least one server **250**, based on the ID and password that are entered by the user. For another example, the user authentication of the at least one server **250** may make a request for biometric information (e.g., a fingerprint or an iris) to the user. The at least one server **250** may determine whether the user of the electronic device **200** is a user registered in the at least one server **250**, by comparing biometric information of the user with biometric information stored in the at least one server **250**. When the user of the electronic device **200** matches user information registered in the at least one server **250**, the at least one server **250** may determine that user authentication of the electronic device **200** is successful.

(100) When the at least one server **250** fails to the user authentication (operation **430**—NO), the processor **210** may terminate the operation.

(101) When the at least one server **250** succeeds in the user authentication (operation **430**—YES), the processor **210** may proceed to operation **440**.

(102) In operation **440**, the processor **210** may receive an encryption key from the at least one server **250**. According to an embodiment of the disclosure, the encryption key of operation **440** may be understood as an account key generated based on the user's account. According to an embodiment of the disclosure, the at least one server **250** may assign different unique values to users registered in the at least one server **250**. The account key may be generated based on a unique value assigned to a user of the electronic device **200**.

(103) In operation **450**, the processor **210** may encrypt the generated backup data based on the encryption key. A description of the generation of backup data may be referenced by the description of FIG. 3A. The backup data of operation **450** may correspond to the backup data generated in operation **355** or operation **360** of FIG. 3A.

(104) In operation **460**, the processor **210** may store the encrypted backup data in an external storage (e.g., the external storage **240** of FIG. 2). Operation **460** may correspond to operation **370** of FIG. 3A.

(105) FIG. 5 is a flowchart illustrating data restoration according to an embodiment of the disclosure.

(106) Referring to FIG. 5, in operation **500**, a processor (e.g., the processor **210** of FIG. 2) may receive a second user input to an application. The second user input may include at least one user input for performing operations of FIG. 5.

(107) In operation **510**, the processor **210** may make a request for user authentication to at least one server (e.g., the at least one server **250**) in response to a second user input. The user authentication in operation **510** may be user authentication based on a user account. The user authentication of operation **510** may correspond to the user authentication of operation **420** of FIG. 4.

(108) In operation **520**, the processor **210** may determine whether user authentication is successful. When the at least one server **250** fails to the user authentication (operation **520**—NO), the

processor **210** may terminate the operation.

(109) When the at least one server **250** succeeds in the user authentication (operation **520**—YES), the processor **210** may proceed to operation **530**. In operation **530**, the processor **210** may receive a decryption key from the at least one server **250**. According to an embodiment of the disclosure, the decryption key may be generated based on a unique value assigned to a user account. According to an embodiment of the disclosure, the decryption key may be the same as the encryption key of FIG. **4**. In this case, the decryption key and encryption key may be symmetric keys.

(110) In operation **540**, the processor **210** may identify whether at least one backup data generated based on a user account linked to the electronic device **200** is present in the external storage **240**.

(111) When at least one backup data generated based on the user account linked to the electronic device **200** is present in the external storage **240** (operation **540**—YES), the processor **210** may proceed to operation **550**.

(112) According to an embodiment of the disclosure, when there is no backup data stored in the external storage **240** (operation **540**—NO), the processor **210** may terminate the operation.

Alternatively, when the backup data stored in the external storage **240** is generated based on a user account of a user different from the user of the electronic device **200** (operation **540**—NO), the processor **210** may terminate the operation.

(113) In operation **550**, the processor **210** may determine whether there are pieces of backup data stored in the external storage **240**. The backup data generated in operation **550** may be backup data generated based on a user account linked to the electronic device **200**.

(114) When there are pieces of backup data (operation **550**—YES), the processor **210** may proceed to operation **560**. In operation **560**, the processor **210** may identify at least one of the pieces of backup data stored in the external storage **240** in response to the second user input. According to an embodiment of the disclosure, a user may desire to restore only backup data at a specified point in time among pieces of backup data stored in the external storage **240**. The user may assign backup data at a desired point in time as the restoration target by entering the second user input.

(115) When there is only one backup data (operation **550**—NO), the processor **210** may proceed to operation **565**. In operation **565**, the processor **210** may identify backup data stored in the external storage **240** as a restoration target. In this case, because there is only one backup data stored in the external storage **240**, the processor **210** may identify the stored backup data as the restoration target in response to the second user input, or may not perform data restoration.

(116) In operation **570**, the processor **210** may decrypt the identified backup data based on the decryption key. The decryption key of operation **570** may be the decryption key received in operation **530**. When the decryption key matches the encryption key obtained by encrypting the backup data, operation **570** may be successfully performed. When the decryption key does not match the encryption key obtained by encrypting the backup data, the processor **210** may fail to decrypt the identified backup data. In this case, the processor **210** may terminate the operation.

(117) In operation **580**, the processor **210** may restore the decrypted backup data. The processor **210** may store the restored data in a memory (e.g., the memory **230** of FIG. **2**) of the electronic device **200**.

(118) FIG. **6** illustrates an application screen for data restoration according to an embodiment of the disclosure.

(119) Referring to FIG. **6**, according to an embodiment of the disclosure, a processor (e.g., the processor **210** of FIG. **2**) may display a screen **600** and a screen **650** through a display (e.g., the display module **160** of FIG. **1**). Based on a user input (e.g., the second user input in FIG. **6**) to the screen **600**, the processor **210** may select backup data to be restored.

(120) Referring to FIG. **6**, the screen **600**, the processor **210** may display, through the display, graphic objects **610**, **620**, **622**, **624**, and **626** corresponding to pieces of backup data. The processor **210** may display, through the graphic objects **610**, **620**, **622**, **624**, and **626**, information about a generation time of backup data corresponding to each of the graphic objects **610**, **620**, **622**, **624**,

and **626**, a device (or a user account) that has generated the backup data, and/or the capacity of the backup data.

(121) According to an embodiment of the disclosure, backup data corresponding to the graphic object **610** has been generated by Galaxy S20 (e.g., a device name) on Nov. 6, 2020, and the data capacity thereof may be about 2.6 G. It may be understood that the backup data corresponding to the graphic object **610** and backup data corresponding to each of the graphic objects **620**, **622**, **624**, and **626** are generated by different electronic devices. In this case, it may be understood that the backup data corresponding to the graphic object **610** and the backup data corresponding to each of the graphic objects **620**, **622**, **624**, and **626** are generated based on different user accounts.

(122) According to an embodiment of the disclosure, a user account linked to the Galaxy S20 may be different from a user account linked to the Galaxy Note10 5G. When the electronic device **200** is a Galaxy Note10 5G, the processor **210** may not perform data restoration by using backup data (e.g., corresponding to the graphic object **610**) generated based on the user account of the Galaxy S20. In this case, the processor **210** may perform data restoration by using at least one of backup data (e.g., corresponding to the graphic objects **620**, **622**, **624**, and **626**) generated based on the user account of the Galaxy Note10 5G.

(123) According to an embodiment of the disclosure, the processor **210** may receive a user input **630** (e.g., the second user input in FIG. 4) to at least one of the graphic objects **620**, **622**, **624**, and **626**. FIG. 6 illustrates that the user input **630** is a touch input to the graphic object **622**. However, for example, the user input **630** may be a drag input for selecting all of the graphic objects **622**, **624**, and **626**. For another example, the user input **630** may include a plurality of touch inputs for respectively selecting at least one of the graphic objects **620**, **622**, **624**, and **626**.

(124) According to an embodiment of the disclosure, when the user input **630** to the graphic object **622** is received, the processor **210** may identify that all backup data generated before backup data corresponding to the graphic object **622** is selected in addition to the backup data corresponding to the graphic object **622**. Referring to the screen **650**, the processor **210** may display a plurality of icons **640** in conjunction with the graphic objects **622**, **624**, and **626** to indicate that the graphic objects **622**, **624**, and **626** have been selected as restoration targets based on the user input **630**. The processor **210** may display a plurality of icons **645** in conjunction with the graphic objects **610** and **620** that are not selected as restoration targets.

(125) According to an embodiment of the disclosure, the processor **210** may perform data restoration by using backup data corresponding to the graphic objects **622**, **624**, and **626** selected on the screen **650**.

(126) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. An electronic device comprising: at least one processor; a communication circuit configured to establish a connection between external storage and a device; and memory operatively connected to the at least one processor and configured to store instructions, wherein the instructions, when executed by the at least one processor, cause the electronic device to: execute an application that provides a backup function, identify first data in response to a first user input to the application, identify a size of the first data, generate all of the first data as a backup data or a part of the first data, which is generated after a point in time according to a latest backup history, as the backup data based on a comparison of the identified size of the first data and a threshold value, and store the backup data in the external storage, wherein the first data includes a first data type stored in a first data format and a second data type stored in a second data format, the first data format and the

second data format associated with different applications, and wherein the threshold value includes a first threshold value corresponding to the first data type and a second threshold value corresponding to the second data type, wherein the instructions, when executed by the at least one processor, further cause the electronic device to: in response to identifying the first data of the first data type, compare the identified size of the first data and the first threshold value, and in response to identifying the first data of the second data type, compare the identified size of the first data and the second threshold value.

2. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, cause the electronic device to: generate all of the first data as the backup data when the size of the first data is less than the threshold value.

3. The electronic device of claim 1, wherein the first data type includes at least one of a video file or an image file, and wherein the second data type includes at least one of a contact, a message history, or calendar information.

4. The electronic device of claim 1, wherein the external storage includes at least one of a solid state drive (SSD), a hard disk drive (HDD), or a universal serial bus (USB) drive.

5. The electronic device of claim 1, wherein the instructions, when executed by the at least one processor, further cause the electronic device to: make a request for user authentication to at least one server in response to the first user input; receive an encryption key from the at least one server based on a user authentication result; and encrypt the backup data based on the encryption key.

6. The electronic device of claim 5, wherein the instructions, when executed by the at least one processor, further cause the electronic device to: receive a second user input for data restoration to the application, identify at least one of pieces of the backup data stored in the external storage based on the second user input, and decrypt the identified at least one of pieces of the backup data, and wherein the pieces of the backup data have different generation time points, respectively.

7. The electronic device of claim 6, wherein the pieces of the backup data stored in the external storage are generated based on a user account linked to the electronic device.

8. The electronic device of claim 7, wherein the instructions, when executed by the at least one processor, further cause the electronic device to: make a request for user authentication to the at least one server in response to the second user input, receive a decryption key from the at least one server based on the user authentication result, and decrypt the identified at least one of the pieces of the backup data based on the decryption key, and wherein the decryption key corresponds to the encryption key.

9. The electronic device of claim 1, further comprising: a display, wherein the instructions, when executed by the at least one processor, further cause the electronic device to: display, through the display, a graphic object corresponding to pieces of the backup data stored in the external storage together with at least one of a generation time of each of the pieces of the backup data, information about a device generating the pieces of the backup data, or a data capacity, and wherein a second user input includes a user input to the graphic object.

10. A method of operating an electronic device, the method comprising: executing an application that provides a backup function; identifying first data in response to a first user input to the application; identifying a size of the first data; generating all of the first data as a backup data or a part of the first data which is generated after a point in time according to a latest backup history, as the backup data based on a comparison of the identified size of the first data and a threshold value; and storing the backup data in external storage, wherein the first data includes a first data type stored in a first data format and a second data type stored in a second data format, the first data format and the second data format associated with different applications, and wherein the threshold value includes a first threshold value corresponding to the first data type and a second threshold value corresponding to the second data type, wherein the generating of the backup data comprises: in response to identifying the first data of the first data type, comparing the identified size of the first data and the first threshold value, and in response to identifying the first data of the second

data type, comparing the identified size of the first data and the second threshold value.

11. The method of claim 10, further comprising: generating all of the first data as the backup data when the size of the first data is less than the threshold value.

12. The method of claim 10, wherein the first data type includes at least one of a video file or an image file, and wherein the second data type includes at least one of a contact, a message history, or calendar information.

13. The method of claim 10, wherein the external storage includes at least one of a solid state drive (SSD), a hard disk drive (HDD), or a universal serial bus (USB) drive.

14. The method of claim 10, further comprising: making a request for user authentication to at least one server in response to the first user input; receiving an encryption key from the at least one server based on a user authentication result; and encrypting the backup data based on the encryption key.

15. The method of claim 14, further comprising: receiving a second user input for data restoration to the application; identifying at least one of pieces of the backup data stored in the external storage based on the second user input; and decrypting the identified at least one of the pieces of the backup data, wherein the pieces of the backup data have different generation time points, respectively.

16. The method of claim 15, wherein the pieces of the backup data are generated based on a user account linked to the electronic device.

17. The method of claim 16, further comprising: making a request for user authentication to the at least one server in response to the second user input; receiving a decryption key from the at least one server based on a user authentication result; and decrypting the identified at least one of the pieces of the backup data based on the decryption key, wherein the decryption key corresponds to the encryption key.

18. The method of claim 10, further comprising: displaying, through a display, a graphic object corresponding to pieces of the backup data together with at least one of a generation time of each of the pieces of the backup data, information about a device generating the pieces of the backup data, or a data capacity, wherein a second user input includes a user input to the graphic object.

19. The electronic device of claim 1, wherein the first data format has a first specified file extension name and the second data format has a second specified file extension name, the first specified file extension name being different from the second specified file extension name.
