

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406599
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Liu; Chao

Innovative magnetic light-emitting sign

Abstract

The disclosure relates to the field of lamp technology, and provides innovative magnetic light-emitting sign, including a light-emitting character bottom housing structure, both front and rear sides of the light-emitting character bottom housing structure are hollow, two bottom covers are fixedly mounted on a bottom wall surface of light-emitting character bottom housing structure, an LED light panel is provided inside the light-emitting character bottom housing structure, the LED light panel is fixed on an inner wall of the light-emitting character bottom housing structure by means of a colloid, a side wall of the LED light panel is provided with a plurality of LED lamp beads spaced equally, light guide covers are fixedly mounted on both front and rear ends of the inner wall of the light-emitting character bottom housing structure, a bottom end of each of the light guide covers is fitted to the side wall of the bottom cover.

Inventors:	Liu; Chao (Vancouver, CA)
Applicant:	HiNeon Technologies Inc (Vancouver, CA)
Family ID:	82212748
Assignee:	HiNeon Technologies Inc (Vancouver, CA)
Appl. No.:	18/273345
Filed (or PCT Filed):	November 18, 2022
PCT No.:	PCT/CN2022/133017
PCT Pub. No.:	WO2023/134301
PCT Pub. Date:	July 20, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240087484 A1	Mar. 14, 2024

Foreign Application Priority Data

CN

202220075442.2

Jan. 12, 2022

Publication Classification

Int. Cl.: G09F13/04 (20060101); F21V3/02 (20060101); G09F7/18 (20060101); F21Y115/10 (20160101)

U.S. Cl.:

CPC G09F13/0404 (20130101); F21V3/02 (20130101); G09F7/18 (20130101); F21Y2115/10 (20160801); G09F2007/1852 (20130101)

Field of Classification Search

CPC: G09F (13/0404); G09F (7/18); G09F (2007/1852)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1169254	12/1915	Gast	362/812	G09F 13/0404
1192982	12/1915	Bristol et al.	40/552	G09F 13/0404
3440749	12/1968	Jonz	40/552	G09F 13/0404
3755943	12/1972	Cesarotti	40/552	G09F 13/0404
6042248	12/1999	Hannah	362/249.14	G09F 13/0404
7118251	12/2005	Chambers	362/311.03	G09F 13/0404
2002/0159257	12/2001	Grajcar	40/551	F21S 4/20
2003/0009924	12/2002	Sajadian	362/362	G09F 13/0404
2004/0255497	12/2003	Venkataraman	40/551	G09F 13/04
2005/0231943	12/2004	Sloan	362/225	G09F 13/22
2010/0064559	12/2009	Dal Cavaliere	40/564	B26F 3/004
2014/0016298	12/2013	Lind	362/23.14	F21S 4/20
2014/0268741	12/2013	Quaal	362/235	G09F 13/0404
2016/0225295	12/2015	Yoon	N/A	G09F 13/22
2017/0025048	12/2016	Lee	N/A	G09F 13/0404
2017/0184290	12/2016	Chiu	N/A	N/A
2019/0160512	12/2018	Lim	N/A	B29C 53/40
2020/0273383	12/2019	Deng	N/A	G09F 13/22

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
204494269	12/2014	CN	N/A
110197631	12/2018	CN	N/A
110197633	12/2018	CN	N/A
209543845	12/2018	CN	N/A
110707446	12/2019	CN	N/A
209947359	12/2019	CN	N/A

210777717	12/2019	CN	N/A
216902174	12/2021	CN	N/A
20140122591	12/2013	KR	N/A
101626724	12/2015	KR	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/CN2022/133017 mailed Feb. 10, 2023.
cited by applicant

Primary Examiner: Hoge; Gary C

Attorney, Agent or Firm: Dorsey & Whitney LLP

Background/Summary

CROSS REFERENCES TO RELATED APPLICATION

(1) The present application is a US national stage application of PCT international application PCT/CN2022/133017, filed on Nov. 18, 2022, which claims priority to Chinese patent application No. 202220075442.2, titled “Innovative Magnetic Light-Emitting Sign”, and filed on Jan. 12, 2022, the contents of each of which are hereby incorporated by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the field of lamp technology, and particularly to an innovative magnetic light-emitting sign.

BACKGROUND

(3) Signage, as the name implies, is a signboard for making a sign with text, patterns and other content on it to indicate the direction and serve as a warning. Common signages include public welfare signages, cultural signages, indicator signages, and warning signages.

(4) The contents of the signages and signs of traditional crafts need to be customized, and the customized contents are used once. The entire signage needs to be customized again while changing the contents, accordingly the entire cost is high and the manufacturing period is long. Customers can not freely change the content, which needs to be manufactured by the manufacturer. A lot of material and time are wasted.

(5) To this end, an innovative magnetic light-emitting sign is provided.

SUMMARY

(6) In view of this, in order to address the above technical problem, it is necessary to provide an innovative magnetic light-emitting sign.

(7) In order to achieve the above purpose, the present disclosure provides the following technical solution. An innovative magnetic light-emitting sign includes a light-emitting character bottom housing structure, wherein both front and rear sides of the light-emitting character bottom housing structure are hollow, two bottom covers are fixedly mounted on a bottom wall surface of the light-emitting character bottom housing structure, an LED light panel is provided inside the light-emitting character bottom housing structure, the LED light panel is fixed on an inner wall of the light-emitting character bottom housing structure by means of a colloid, a side wall of the LED light panel is provided with a plurality of LED lamp beads spaced equally, light guide covers are fixedly mounted on both front and rear ends of the inner wall of the light-emitting character bottom housing structure, a bottom end of each of the light guide covers is fitted to the side wall of the bottom cover, stepped processing is performed on an edge of a side of each of the light guide covers fitted to the light-emitting character bottom housing structure.

(8) Optionally, a screw is provided outside the bottom cover, a lateral wall of the bottom cover adjacent to the rear side is provided with a hole, an inner wall of the bottom cover adjacent to the front side is provided with a central round hole corresponding to the hole, the screw passes through the hole and is connected to an inner wall thread of the central round hole, two pogo pins are provided inside the bottom cover, a side wall inside the bottom cover is provided with two corresponding fixing grooves, two bottom ends of the two fixing grooves are both in communication with an outside, side walls of the two pogo pins are respectively fixedly mounted in the corresponding fixing grooves, the bottom ends of the pogo pins extend to the outside through the fixing grooves, positive and negative ends of the LED lamp panel are electrically connected to two wires, bottom ends of the two wires are electrically connected to the two pogo pins, a magnetic block is fixedly mounted on a bottom wall surface of the bottom cover, wherein a top end of the magnetic block extends inside the bottom cover, left and right sidewalls of the magnetic block correspond to the two fixing grooves adjacent respectively.

(9) Optionally, the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form an N-shape.

(10) Optionally, the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a heart shape.

(11) Optionally, the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a triangular shape.

(12) Optionally, the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a B-shape.

(13) Optionally, the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a C-shape.

(14) Advantages:

(15) (1) As for the innovative magnetic light-emitting sign, through the embodiments I to VI, the shape formed by the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel can be changed arbitrarily. English letter-shaped signs, Chinese character-shaped signs, and sign patterns produced by using the innovative magnetic light-emitting sign technique, can be freely combined on the mounting rail, and information can be replaced conveniently at any time. Since the bottom cover is arranged inside the external rail, a distance among various shapes can be adjusted by pushing the light-emitting character bottom housing structure, so that a distance between different light-emitting character bottom housing structures can be changed conveniently according to actual requirements, thereby implementing a rapid DIY of sign display.

(16) (2) As for the innovative magnetic light-emitting sign, the two pogo pins are exposed outside the bottom cover, the bottom cover is placed inside the external rail; when there exists a magnetic material inside the external rail attracting the magnetic block, the magnetic force may push the pogo pins to form a complete contact with a power supply terminal on the other side, to implement a circuit path. The pogo pins are connected to the external power supply, the current may be transmitted to the interior of the LED lamp panel, which is convenient to control the LED lamp beads to work. The light emitted by LED lamp beads passes through the light guide covers to form the neon-like light-emitting sign effect.

(17) (3) As for the innovative magnetic light-emitting sign, the stepped processing is performed on an edge of a side of the light guide cover fitted to the light-emitting character bottom housing structure, in order to facilitate the light guide cover to completely cover the groove structure of the light-emitting character bottom housing structure, and further facilitate ultrasonic bonding therebetween. The bottom end of the light guide cover is fitted to the side wall of the bottom cover, thereby avoiding an interspace on the side wall of the light-emitting character bottom housing structure which may result in light infiltration.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) In order to illustrate more clearly the embodiments of the present disclosure or the technical solutions in the existing technique, accompanying drawings required in the description of the embodiments or the existing technique will be briefly described below. Obviously, the drawings in the following description are merely exemplary, and drawings of other embodiments may be obtained by those skilled in the art according to the provided drawings without creative efforts.
- (2) The structure, proportion, size and the like shown in the specification are merely used for cooperating with the content disclosed in the specification for people familiar with the technology to understand and read, rather than limiting the implementation of the disclosure, accordingly have no technical substantive meaning. Any structural modification, change in the proportion relation or adjustment of the size shall all fall within the scope of the disclosure without affecting the effects generated and the purposes achieved by the present disclosure.
- (3) FIG. 1 is a disassembling side view of a light-emitting character according to the present disclosure.
- (4) FIG. 2 is a disassembling desktop flat view of a light-emitting character according to the present disclosure.
- (5) FIG. 3 is a disassembling desktop side view of a light-emitting character according to the present disclosure.
- (6) FIG. 4 is a disassembling bottom side view of a light-emitting character according to the present disclosure.
- (7) FIG. 5 is a side view of a combination of light-emitting characters according to the present disclosure.
- (8) FIG. 6 is a schematic diagram illustrating shapes according to a plurality of embodiments of the present disclosure.

REFERENCE SIGNS

- (9) **11**, light-emitting character bottom housing structure; **31**, LED lamp panel; **32**, pogo pin; **33**, magnetic block; **14**, bottom cover; **21**, light guide cover; **35**, wire; **14**, bottom cover; **12**, screw; **13**, a fixing groove; **17**, hole; **15**, central round hole; **34**, LED lamp bead; **41**, housing I; **42**, housing II; **43**, housing III; **44**, housing IV; **45**, housing V.

DETAILED DESCRIPTION

- (10) The technical solution in the embodiments of the present disclosure will be elaborated clearly and comprehensively in combination with the accompanying drawings. Obviously, the described embodiments are merely some embodiments of the present disclosure, not all the embodiments. Based on the embodiments in the present disclosure, all other embodiments obtained by those skilled in the art without creative efforts belong to the scope of protection of the present disclosure.
- (11) Example I: An innovative magnetic light-emitting sign, as shown in FIGS. 1-5, includes a light-emitting character bottom housing structure **11**. Both front and rear sides of the light-emitting character bottom housing structure **11** are hollow, and two bottom covers **14** are fixedly mounted on a bottom wall surface of the light-emitting character bottom housing structure **11**. The light-emitting character bottom housing structure **11** and the bottom covers **14** can be manufactured by injection molding with an ABS material, or by cutting an acrylic material.
- (12) An LED light panel **31** is provided inside the light-emitting character bottom housing structure **11**. The LED light panel **31** is fixed on an inner wall of the light-emitting character bottom housing structure **11** by means of a colloid. A side wall of the LED light panel **31** is provided with a plurality of LED lamp beads **34** spaced equally. By choosing different color light sources, and replacing different LED lamp beads **34**, the interior of the light-emitting character bottom housing structure **11** can display different luminous colors.

(13) Light guide cover **21** are fixedly mounted on both front and rear ends of the inner wall of the light-emitting character bottom housing structure **11**. A bottom end of the light guide cover **21** is fitted to the side wall of the bottom cover **14**. The light guide cover **21** is a light guide material, such as PC or acrylic material. The bottom end of the light guide cover **21** is fitted to the side wall of the bottom cover **14**, thereby avoiding an interspace on the side wall of the light-emitting character bottom housing structure **11** which may result in light infiltration.

(14) Two pogo pins **32** are provided inside the bottom cover **14**.

(15) The opposing sidewalls of the two bottom covers **14** are each provided with two corresponding fixing grooves **13**, two bottom ends of the fixing grooves **13** are both in communication with the outside. Side walls of the two pogo pins **32** are respectively fixedly mounted in the corresponding fixing grooves **13**. The bottom ends of the pogo pins **32** extend to the outside through the fixing grooves **13**.

(16) The positive and negative ends of the LED lamp panel **31** are electrically connected to wires **35**. Bottom ends of the two wires **35** are electrically connected to the two pogo pins **32**. The pogo pins **32** are connected to an external power supply, a current may be transmitted to the interior of the LED lamp panel **31**, which is convenient to control the LED lamp beads **34** to work. The light emitted by LED lamp beads **34** passes through the light guide covers **21** to form a neon-like light-emitting sign effect.

(17) A magnetic block **33** is fixedly mounted on a bottom wall surface of the bottom cover **14**, in which a top end of the magnetic block **33** extends inside the bottom cover **14**. Left and right sidewalls of the magnetic block **33** correspond to the two fixing grooves **13** adjacent respectively.

(18) A stepped structure is performed on an edge of a side of the light guide cover **21** fitted to the light-emitting character bottom housing structure **11**, in order to facilitate the light guide cover to completely cover the groove structure of the light-emitting character bottom housing structure **11**, and also facilitate ultrasonic bonding therebetween.

(19) A screw **12** is provided outside the bottom cover **14**. A lateral wall of the bottom cover **14** adjacent to the rear side is provided with a hole **17**. An inner wall of the bottom cover **14** adjacent to the front side is provided with a central round hole **15** corresponding to the hole **17**. The screw **12** passes through the hole **17** and is connected to an inner wall thread of the central round hole **15**.

(20) Two ends of the two pogo pins **32** are exposed outside the bottom cover **14**. The bottom cover **14** is placed inside an external rail. When there exists a magnetic material inside the external rail attracting the magnetic block, a magnetic force may push the pogo pins to form a complete contact with a power supply terminal on the other side, to implement a circuit path.

(21) The light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form an N-shape, respectively.

(22) Embodiment II: based on the embodiment I and referring to FIG. 6, the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form a heart shape, respectively.

(23) Embodiment III: based on the embodiment I and referring to FIG. 6, the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form a D-shape, respectively.

(24) Embodiment IV: based on the embodiment I and referring to FIG. 6, the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form a triangular shape, respectively.

(25) Embodiment V: based on the embodiment I and referring to FIG. 6, the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form a B-shape, respectively.

(26) Embodiment VI: based on the embodiment I and referring to FIG. 6, the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** form a C-shape.

(27) The working principle of the present disclosure is provided as follows.

(28) When in use, through the embodiments I to VI, the shape formed by the light-emitting character bottom housing structure **11**, the light guide cover **21** and the LED lamp panel **31** can be changed flexibly. English letter-shaped signs, Chinese character-shaped signs, and sign patterns produced by using the innovative magnetic light-emitting sign technique, can be freely combined on the mounting rail, and information can be replaced conveniently at any time. Since the bottom cover **14** is arranged inside the external rail, a distance among signs of various shapes can be adjusted by moving the light-emitting character bottom housing structure **11**, a distance between different light-emitting character bottom housing structures **11** can be changed conveniently according to actual requirements, thereby implementing a rapid DIY of sign display.

(29) When in use, the two pogo pins **32** are exposed outside the bottom covers **14**, the bottom cover **14** is placed inside the external rail; when there exists a magnetic material inside the external rail attracting the magnetic block, the magnetic force may push the pogo pins to form a complete contact with a power supply terminal on the other side, to implement a circuit path. The pogo pins **32** are connected to the external power supply, the current may be transmitted to the interior of the LED lamp panel **31**, which is convenient to control the LED lamp beads **34** to work. The light emitted by LED lamp beads **34** passes through the light guide covers **21** to form the neon-like light-emitting sign effect.

(30) When in use, the stepped processing is performed on an edge of a side of the light guide cover **21** fitted to the light-emitting character bottom housing structure **11**, in order to facilitate the light guide cover to completely cover the groove structure of the light-emitting character bottom housing structure **11**, and further facilitate ultrasonic bonding therebetween. The bottom end of the light guide cover **21** is fitted to the side wall of the bottom cover **14**, thereby avoiding an interspace on the side wall of the light-emitting character bottom housing structure **11** which may result in light infiltration.

(31) The basic principle, main limitations and the advantages of the present disclosure are shown and described above. Those skilled in the art should appreciate that the present disclosure is not limited by the above embodiments, the above embodiments and description only illustrate the principle of the present disclosure, and those skilled in the art can make various variations and improvements to the present disclosure without departing from the spirit and scope of the present disclosure, and these variations and improvements all fall within the scope of protection of the present disclosure. The protection scope of the present disclosure shall be subject to the appended claims and equivalents thereof.

Claims

1. An innovative magnetic light-emitting sign, comprising: a light-emitting character bottom housing structure, wherein both front and rear sides of the light-emitting character bottom housing structure are hollow, two bottom covers are fixedly mounted on a bottom wall surface of the light-emitting character bottom housing structure, and a light emitting diode (LED) light panel is provided inside the light-emitting character bottom housing structure, the LED light panel is fixed on an inner wall of the light-emitting character bottom housing structure by a colloid, a side wall of the LED light panel is provided with a plurality of LED lamp beads spaced equally, a light guide cover is fixedly mounted on a front end of the inner wall of the light-emitting character bottom housing structure, a bottom end of each of the light guide covers is fitted to the side wall of the bottom cover, a stepped structure is performed on an edge of a side of each of the light guide covers fitted to the light-emitting character bottom housing structure; wherein a screw is provided outside the bottom cover, a lateral wall of the bottom cover adjacent to the rear side is provided with a hole, an inner wall of the bottom cover adjacent to the front side is provided with a central round hole corresponding to the hole, the screw passes through the hole and is connected to an

inner wall thread of the central round hole, two pogo pins are provided inside the bottom cover, a side wall inside the bottom cover is provided with two corresponding fixing grooves, two bottom ends of the two fixing grooves are both in communication with an outside, side walls of the two pogo pins are respectively fixedly mounted in the corresponding fixing grooves, the bottom ends of the pogo pins extend to the outside through the fixing grooves, positive and negative ends of the LED lamp panel are electrically connected to two wires, bottom ends of the two wires are electrically connected to the two pogo pins, a magnetic block is fixedly mounted on a bottom wall surface of the bottom cover, wherein a top end of the magnetic block extends inside the bottom cover, left and right sidewalls of the magnetic block correspond to the two fixing grooves adjacent respectively.

2. The innovative magnetic light-emitting sign according to claim 1, wherein the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form an N-shape.

3. The innovative magnetic light-emitting sign according to claim 1, wherein the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a heart shape.

4. The innovative magnetic light-emitting sign according to claim 1, wherein the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a triangular shape.

5. The innovative magnetic light-emitting sign according to claim 1, wherein the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a B-shape.

6. The innovative magnetic light-emitting sign according to claim 1, wherein the light-emitting character bottom housing structure, the light guide cover and the LED lamp panel form a C-shape.
