

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12396446
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Christensen; Everett

Interchangeable fishing jig head

Abstract

A fishing jig having interchangeable jig heads that quickly interchanges various weighted jig heads without needing to disconnect the fishing jig hook from the fishing line. The jig head is aligned below a lengthwise axis of the hook and the eyelet of the hook is aligned above the lengthwise axis of the hook.

Inventors:	Christensen; Everett (Hawley, MN)
Applicant:	Christensen; Everett (Hawley, MN)
Family ID:	1000005901611
Appl. No.:	17/476897
Filed:	September 16, 2021

Related U.S. Application Data

us-provisional-application US 63080517 20200918

Publication Classification

Int. Cl.: A01K95/00 (20060101); A01K83/00 (20060101)

U.S. Cl.:

CPC A01K95/00 (20130101); A01K83/00 (20130101);

Field of Classification Search

CPC: A01K (95/00); A01K (85/029); A01K (85/16); A01K (85/1831); A01K (85/1833); A01K (83/00); A01K (85/1837)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3061968	12/1961	Stroud	43/44.8	A01K 83/06
3750323	12/1972	Weis	D22/128	A01K 85/00
4450646	12/1983	Maltese	N/A	N/A
4530180	12/1984	Gwaldacz, Sr.	43/44.81	A01K 85/00
4972623	12/1989	Delricco	N/A	N/A
5105575	12/1991	Robertaccio	43/44.8	A01K 85/00
5233786	12/1992	Biss	N/A	N/A
5537775	12/1995	Crumrine	N/A	N/A
6052938	12/1999	Marusak et al.	N/A	N/A
6058643	12/1999	Marusak et al.	N/A	N/A
6061948	12/1999	Boucek	N/A	N/A
6898894	12/2004	Anderson	43/42.39	A01K 85/00
7263798	12/2006	Nichols	N/A	N/A
7827731	12/2009	Gibson	N/A	N/A
7877923	12/2010	Dudley	N/A	N/A
8635804	12/2013	Lefebvre	N/A	N/A
8640378	12/2013	Rye et al.	N/A	N/A
8991095	12/2014	Roberts et al.	N/A	N/A
9003689	12/2014	Rye et al.	N/A	N/A
9185891	12/2014	Nakamichi	N/A	N/A
9253966	12/2015	Scholfield	N/A	N/A
9288972	12/2015	Link	N/A	A01K 85/00
9485974	12/2015	Rye et al.	N/A	N/A
9713321	12/2016	Smith et al.	N/A	N/A
2010/0175305	12/2009	Heikkila et al.	N/A	N/A
2011/0035987	12/2010	Nicholson, III	43/42.4	A01K 85/00
2012/0005946	12/2011	Bennis	N/A	N/A
2014/0144063	12/2013	Hamilton, Jr.	N/A	N/A
2014/0237899	12/2013	Tamburro	N/A	N/A
2015/0272095	12/2014	Furuya	N/A	N/A
2019/0008128	12/2018	Walsh	N/A	A01K 85/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2004275432	12/2005	AU	A01K 85/00

OTHER PUBLICATIONS

Deepto Chakrabarty, et al., Classical Mechanics: Chapter 3 Vectors, 8.01SC 22, OpenCourseWare, Massachusetts Institute of Technology, Chapter 3, pp. 8-10 (Fall 2016), available at https://ocw.mit.edu/courses/8-01sc-classical-mechanics-fall-2016/resources/mit8_01scs22_chapter3/. cited by examiner

Primary Examiner: Collins; Timothy D

Assistant Examiner: Lowery; Brittany A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims the filing benefit and priority of U.S. Provisional Application Ser. No. 63/080,517 filed Sep. 18, 2020, the contents of which are incorporated herein by reference in its entirety.

FEDERAL SPONSORSHIP

(1) Not Applicable

JOINT RESEARCH AGREEMENT

(2) Not Applicable

TECHNICAL FIELD

(3) This invention pertains generally to fish hooks used by fisherman. More particularly, this invention pertains to a fishing jig having interchangeable jig heads. The invention further pertains to a fishing jig assembly that quickly interchanges various weighted jig heads without needing to disconnect the fishing jig hook from the fishing line.

BACKGROUND

(4) Over the years many variations of fishing lures have been made in an attempt to lure fish. Generally, the lure includes a hook portion, a body portion that is intended to attract fish, and an eyelet portion through which a fishing line is attached. Typically, bait will be attached to the hook end of the lure. Oftentimes, a fisherman will disconnect the lure from the fishing line to try a different lure having a different color, weight, or shape. This interchange of lures tends to waste bait. The present invention provides a lure that allows the fisherman to change the weight of the lure, predominant color of the lure, and the shape of the lure without the need to remove bait from the hook or disconnect the lure from the fishing line.

SUMMARY

(5) Embodiments according to aspects of the invention include a jig assembly having interchangeable jig heads for interchanging jig heads without removing the hook from the fishing line. The jig assembly includes a jig hook, a jig head, a collar, and a coupler. The hook has a curved end portion, a straight spanning portion, a neck portion extending perpendicular from the straight spanning portion, and an eyelet end portion formed from an end of the neck portion. The collar is cylindrical and is engaged to the neck portion of the hook. The coupler includes a tube, wherein the tube has an aperture extending through the tube. The aperture is sized to engage an outer surface of the cylindrical collar. Also, a portion of the straight spanning portion of the hook extends through a mid portion of the tube. The interchangeable jig head has an end of the jig head shaped to engage with a sidewall of the aperture extending through the tube.

(6) In an embodiment according to certain aspects of the invention the cylindrical collar has a length that approximates a length of the neck portion of the hook. Further, the length of the tube may be approximately twice a length of the neck portion of the hook. In this manner approximately half of the tube encompasses the collar and neck portion of the hook and the other approximate half of the tube encompasses a rim and stem portion of the jig head. The bulb of the interchangeable jig head extends out of an end of the tube. The end of the jig that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the jig head.

(7) Embodiments according to aspects of the invention may further provide a length of the stem of the jig head that is slightly less than the length of the tube. Further, in accordance with certain embodiments of the invention the jig head may be aligned below a lengthwise axis of the hook while the eyelet portion of the hook is aligned above the lengthwise axis of the hook.

(8) The accompanying drawings, which are incorporated in and constitute a portion of this

specification, illustrate embodiments of the invention and, together with the detailed description, serve to further explain the invention. The embodiments illustrated herein are presently preferred; however, it should be understood, that the invention is not limited to the precise arrangements and instrumentalities shown. For a fuller understanding of the nature and advantages of the invention, reference should be made to the detailed description in conjunction with the accompanying drawings.

Description

DESCRIPTION OF THE DRAWINGS

- (1) In the various figures, which are not necessarily drawn to scale, like numerals throughout the figures identify substantially similar components.
- (2) FIG. 1 is a perspective view of a jig assembly in accordance with an embodiment of the invention;
- (3) FIG. 2 is a bottom perspective view of a jig assembly in accordance with an embodiment of the invention;
- (4) FIG. 3 is a perspective view of a jig assembly in accordance with an embodiment of the invention;
- (5) FIG. 4 is a bottom perspective view of a jig assembly in accordance with an embodiment of the invention;
- (6) FIG. 5 is a partial sectional view of a jig assembly in accordance with an embodiment of the invention;
- (7) FIG. 6 is a perspective view of various components of the jig assembly in accordance with an embodiment of the invention;
- (8) FIG. 7 is a top front left perspective view of the jig assembly in accordance with an embodiment of the invention having a bait retainer combined with the hook portion of the jig;
- (9) FIG. 8 is a bottom front right perspective view of the jig assembly in accordance with an embodiment of the invention having a bait retainer combined with the hook portion of the jig;
- (10) FIG. 9 is a top front perspective view of a bait retainer in accordance with an embodiment of the invention;
- (11) FIG. 10 is a bottom back perspective view of a bait retainer in accordance with an embodiment of the invention;
- (12) FIG. 11 is a top front perspective view of a jig head of the jig assembly in accordance with an embodiment of the invention; and
- (13) FIG. 12 is a bottom back perspective view of a jig head of a jig head assembly in accordance with an embodiment of the invention.

DETAILED DESCRIPTION

- (14) The following description provides detail of various embodiments of the invention, one or more examples of which are set forth below. Each of these embodiments are provided by way of explanation of the invention, and not intended to be a limitation of the invention. Further, those skilled in the art will appreciate that various modifications and variations may be made in the present invention without departing from the scope or spirit of the invention. By way of example, those skilled in the art will recognize that features illustrated or described as part of one embodiment, may be used in another embodiment to yield a still further embodiment. Thus, it is intended that the present invention also cover such modifications and variations that come within the scope of the appended claims and their equivalents.
- (15) The jig assembly **10** of the present invention includes a jig hook **20**, a jig head **40**, a collar **60** and a coupler **80**. The jig head **40** is interchangeable. The collar **60** is positioned on the neck portion **24** of the hook **20**. A user may interchange various shaped and colored jig heads **40** without

the need to remove the collar **60** and without the need to remove the hook from the fishing line. In this manner, the bait may remain on the hook while the fisherman interchanges different colored, weighted, or shaped jig heads.

(16) Traditional fishing jigs include a jig head that is permanently molded onto a fishing hook with an eyelet sticking out of one end of the jig head and the remaining portion of the hook extending out the other side of the jig head. After the jig head is molded onto the hook, paint is applied to the jig head. Unfortunately, the paint tends to clog the eyelet making it difficult to thread a fishing line through the eyelet. When using the traditional jig head any change in color, size or shape of the jig requires removal of the jig from the fishing line, tying on a new lure, and replacing the bait.

(17) The orientation of the jig head of the present invention is below the longitudinal axis of the fishing hook. This orientation changes the center of mass of the jig as compared to the traditional fishing jig. Further, orienting the jig head below the longitudinal axis of the fish hook tends to improve the likelihood that the hook sets securely into the fish's mouth. Also, at times a fisherman may desire to let the jig assembly drop to the bottom of the lake and then lift the jig up slightly while reeling in the line. The length of the coupler **80** may be varied to change the distance between the bottom of the lake and the hook as the weight touches the bottom during this jiggling motion. Increasing the distance between the lake bottom and the hook may help prevent snags and increase the success of setting the hook.

(18) Turning attention now to the Figures, embodiments of the jig assembly **10** of the present invention will now be described in more detail. The jig assembly **10** includes a jig hook **20**, a jig head **40**, a collar **60**, and a coupler **80**. The hook **20** has a curved end portion **28**, a straight spanning portion **26** that defines the primary lengthwise axis of the hook, a neck portion **24** extending perpendicular from the straight spanning portion **26**, and an eyelet **22** end portion formed from an end of the neck portion **24**. The collar **60** has a cylindrical body **62** wherein an aperture **64** extends through the lengthwise axis of the cylindrical body. The neck portion **24** of the hook **20** extends through the aperture **64** of the collar **60**. Once in position, the collar remains engaged to the neck **24** of the hook **20**. The collar is preferably made from a stiff material (such as an ABS polymer) to further provide rigidity to the neck portion of the hook. When the coupler **80** is made of a transparent material the collar may be made from a variety of colors to allow a fisherman to change the appearance near the eyelet **22**.

(19) The coupler **80** includes a hollow tube **82** having an aperture **84** extending through the tube. The aperture **84** is sized to engage an outer surface of the cylindrical collar **60**. The length of the tube **82** is selected so that the straight spanning portion of the hook extends through and out of a mid portion of the tube **82**. The remaining portion of the tube extends downward below a lengthwise axis of the hook. In this manner the eyelet portion **22** of the hook **20** is aligned above the lengthwise axis of the hook **20**.

(20) The interchangeable jig head **40** has an end or rim **46** of the jig head that is shaped to engage with a sidewall of the aperture **84** extending through the tube **82**. A stem portion **44** interconnects the bulb or main body **42** with the rim **46**. The diameter of the rim **46** may be sized larger than the diameter of the stem **44** so that only the rim contacts the inside sidewall of the tube **82**.

Alternatively, the diameter of both the rim **46** and stem **44** may both be larger than the aperture of the tube **82** such that tubing contacts and presses against both the rim and stem. The shape of the main body **42** may be spherical, elliptical, oblong, square, diamond, spoon, flattened sides or many or shapes to provide a varying appearance to the jig assembly. See FIGS. **11** and **12** that illustrate an alternate shaped jig head **40** of the present invention. Further the size of the main body and amount of material used to make the jig head may be varied to affect the weight of the jig head **40**. Without limitation intended, the size may be modified such that the weight of the jig head **40** may range from 1/16 ounce to as much as 10 ounces or more. Also, as noted above, the bulb or main body of the jig head extends below an end of the tube and below the lengthwise axis of the hook **20**.

(21) The tube **82** is made from a pliable material and may be made from a variety of colors or transparent material (such as silicone). The aperture **84** is sized slightly smaller than the diameter of the rim **46**. In this manner, the tube stretches over the rim and stem **44** and the jig head **40** is firmly held in place relative to the hook **20**. Tubing may be provided with varying aperture diameters to allow the fisherman to choose how snug the rim **46** and stem **44** are held in place by the flexible tube. In some instances, such as jigging on the bottom, the fisherman may want the jig head to release from the tubing when the jig head snags on the bottom of the lake. Further, the length of the tubing may be selected to increase the probability that only the jig head snags on the lake bottom and the hook is elevated above the lake bottom to avoid snags.

(22) With reference to FIGS. 7-10, the jig assembly **10** of the present invention may further include a bait retainer **90** positioned on the straight span **26** of the jig hook **20**. The bait retainer includes a main body **92**, an aperture **94** extending through the main body **92**, and barbs **96** formed on one end of the main body. The bait retainer **90** is oriented on the hook **20** such that the bait will slide over the main body **92** but the barbs **96** restrict the bait from slipping over the main body in the opposite direction. The bait retainer is made from a suitable material and the aperture is sized such that the bait retainer may be slid over the hook **20** but stays in place on the hook once slid into position. Although not shown, those skilled in the art will appreciate that a spinner could be slid over the hook and the bait retainer could retain the spinner in a desired position on the hook.

(23) These and various other aspects and features of the invention are described with the intent to be illustrative, and not restrictive. This invention has been described herein with detail in order to comply with the patent statutes and to provide those skilled in the art with information needed to apply the novel principles and to construct and use such specialized components as are required. It is to be understood, however, that the invention can be carried out by specifically different constructions, and that various modifications, both as to the construction and operating procedures, can be accomplished without departing from the scope of the invention. Further, in the appended claims, the transitional terms comprising and including are used in the open ended sense in that elements in addition to those enumerated may also be present. Other examples will be apparent to those of skill in the art upon reviewing this document.

Claims

1. A fishing jig assembly, for interchanging jig heads without removing the hook from the fishing line, the fishing jig assembly comprising: a hook having a curved end portion, a straight spanning portion, a neck portion extending perpendicular from the straight spanning portion, and an eyelet end portion formed from an end of the neck portion; a cylindrical collar engaged to the neck portion of the hook, whereby a longitudinal axis of the cylindrical collar extends perpendicular to the straight spanning portion of the hook; a coupler including a tube, wherein the tube has an aperture extending through the tube, whereby a longitudinal axis of the tube aligns parallel with the longitudinal axis of the cylindrical collar, and wherein the aperture is sized to engage an outer surface of the cylindrical collar and wherein a portion of the straight spanning portion of the hook extends through a mid portion of the tube; and an interchangeable jig head having an end of the interchangeable jig head shaped to engage with a sidewall of the aperture extending through the tube.

2. The fishing jig assembly as recited in claim 1, wherein the cylindrical collar has a length that approximates a length of the neck portion of the hook.

3. The fishing jig assembly as recited in claim 1, wherein a length of the tube is approximately twice a length of the neck portion of the hook.

4. The fishing jig assembly as recited in claim 1, wherein the interchangeable jig head has a bulb, a stem and a rim, wherein the end of the interchangeable jig head that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the interchangeable jig head.

5. The fishing jig assembly as recited in claim 3, wherein the interchangeable jig head has a bulb, a stem and a rim, wherein the end of the interchangeable jig head that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the interchangeable jig head.
6. The fishing jig assembly as recited in claim 5, wherein a length of the stem of the interchangeable jig head is slightly less than the length of the tube.
7. The fishing jig assembly as recited in claim 1, wherein the bulb, stem and rim of the interchangeable jig head is aligned below a lengthwise axis of the hook and the eyelet portion of the hook is aligned above the lengthwise axis of the hook.
8. A fishing jig assembly, for interchanging jig heads without removing the hook from the fishing line, the fishing jig assembly comprising: a hook having a curved end portion, a straight spanning portion, a neck portion extending perpendicular from the straight spanning portion, and an eyelet end portion formed from an end of the neck portion; a cylindrical collar engaged to the neck portion of the hook, wherein the cylindrical collar has a length that approximates a length of the neck portion of the hook, whereby a lengthwise axis of the cylindrical collar aligns perpendicular to the straight spanning portion of the hook; a coupler including a tube, wherein the tube has an aperture extending through the tube and wherein the aperture is sized to engage an outer surface of the cylindrical collar and wherein a portion of the straight spanning portion of the hook extends through a mid portion of the tube, wherein a length of the tube is approximately twice a length of the neck portion of the hook whereby a lengthwise axis of the tube aligns perpendicular to the straight spanning portion of the hook; and an interchangeable jig head having an end of the interchangeable jig head shaped to engage with a sidewall portion of the aperture extending through the tube opposite the cylindrical collar.
9. The fishing jig assembly as recited in claim 8, wherein the interchangeable jig head has a bulb, a stem and a rim, wherein the end of the interchangeable jig head that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the interchangeable jig head.
10. The fishing jig assembly as recited in claim 9, wherein a length of the stem of the interchangeable jig head is slightly less than the length of the tube.
11. A fishing jig assembly, for interchanging jig heads without removing the hook from the fishing line, the fishing jig assembly comprising: a hook having a curved end portion, a straight spanning portion, a neck portion extending perpendicular from the straight spanning portion, and an eyelet end portion formed from an end of the neck portion; a cylindrical collar engaged to the neck portion of the hook whereby a lengthwise axis of the cylindrical collar aligns perpendicular to the straight spanning portion of the hook; a coupler including a tube, wherein the tube has an aperture extending through the tube and wherein the aperture is sized to engage an outer surface of the cylindrical collar and wherein a portion of the straight spanning portion of the hook extends through a mid portion of the tube such that approximately half of a length of the tube extends outwardly perpendicularly above the straight spanning portion of the hook and an other approximately half of the length of the tube extends outwardly perpendicularly below the straight spanning portion of the hook; an interchangeable jig head having an end of the interchangeable jig head shaped to engage with a sidewall of the aperture extending through the tube below the straight spanning portion of the hook; and a bait retainer positioned on the hook between the curved end portion and neck portion of the hook.
12. The fishing jig assembly as recited in claim 11, wherein the cylindrical collar has a length that approximates a length of the neck portion of the hook.
13. The fishing jig assembly as recited in claim 11, wherein a length of the tube is approximately twice a length of the neck portion of the hook.
14. The fishing jig assembly as recited in claim 11, wherein the interchangeable jig head has a bulb, a stem and a rim, wherein the end of the interchangeable jig head that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the interchangeable jig head.
15. The fishing jig assembly as recited in claim 13, wherein the interchangeable jig head has a bulb,

a stem and a rim, wherein the end of the interchangeable jig head that is shaped to engage with the sidewall of the aperture extending through the tube is the rim of the interchangeable jig head.

16. The fishing jig assembly as recited in claim 15, wherein a length of the stem of the interchangeable jig head is slightly less than the length of the tube.

17. The fishing jig assembly as recited in claim 15, wherein the bulb, stem and rim of the interchangeable jig head is aligned below a lengthwise axis of the hook and the eyelet portion of the hook is aligned above the lengthwise axis of the hook.
