

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397689
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Saucier; Shain A. et al.

Infant transport system and assembly

Abstract

A system to transport infant children is provided. The system includes a base configured to be secured to a portion of an automobile; a chassis independent from the base; a first release mechanism releasably coupling the chassis to the base; an infant car seat independent from the base and the chassis; a second release mechanism releasably coupling the infant car seat to the chassis; wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism; and wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism.

Inventors: Saucier; Shain A. (Charlotte, NC), Keegan; Charles H. (Milton, MA), Meng; Zhang (Suzhou, CN), Xiaoyong; Yang (Suzhou, CN), Xiang; Gao (Suzhou, CN), Wenlong; Lv (Suzhou, CN), Bo; Feng (Suzhou, CN)

Applicant: Evenflo Company, Inc. (Miamisburg, OH)

Family ID: 1000008778085

Assignee: Evenflo Company, Inc. (Miamisburg, OH)

Appl. No.: 18/098305

Filed: January 18, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240239248 A1	Jul. 18, 2024

Publication Classification

Int. Cl.: B60N2/28 (20060101)

U.S. Cl.:

CPC **B60N2/2848** (20130101); **B60N2/2821** (20130101); **B60N2/2845** (20130101);
B60N2205/30 (20130101)

Field of Classification Search

CPC: B60N (2/2848); B60N (2/2821)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4371206	12/1982	Johnson, Jr.	N/A	N/A
4634175	12/1986	Wise	N/A	N/A
4685688	12/1986	Edwards	N/A	N/A
4733909	12/1987	Single et al.	N/A	N/A
4736959	12/1987	Van Steenburg	N/A	N/A
4762331	12/1987	Tucker et al.	N/A	N/A
4832354	12/1988	LaFreniere	N/A	N/A
4834403	12/1988	Yanus et al.	N/A	N/A
4852894	12/1988	Dyer	N/A	N/A
4872692	12/1988	Steenburg	N/A	N/A
4872693	12/1988	Kennel	N/A	N/A
4874182	12/1988	Clark	N/A	N/A
4878680	12/1988	Molnar	N/A	N/A
4896894	12/1989	Singletary	N/A	N/A
4902026	12/1989	Maldonado	N/A	N/A
4946180	12/1989	Baer	N/A	N/A
4986599	12/1990	Wise	N/A	N/A
4989888	12/1990	Qureshi et al.	N/A	N/A
5104134	12/1991	Cone	N/A	N/A
5133567	12/1991	Owens	N/A	N/A
5143419	12/1991	Tepper et al.	N/A	N/A
5149113	12/1991	Alldredge	N/A	N/A
5230523	12/1992	Wilhelm	N/A	N/A
5318311	12/1993	Bofill	N/A	N/A
5360221	12/1993	Chai	N/A	N/A
5395154	12/1994	Wang	N/A	N/A
5398951	12/1994	Ryu	280/47.38	B62B 7/12
5403022	12/1994	Snider	N/A	N/A
5431478	12/1994	Noonan	N/A	N/A
5478096	12/1994	Ting	N/A	N/A
5527090	12/1995	Cone, II	N/A	N/A
5673924	12/1996	Demick et al.	N/A	N/A
5707106	12/1997	Clark	N/A	N/A
5772279	12/1997	Johnson, Jr.	N/A	N/A
5823547	12/1997	Otobe et al.	N/A	N/A
5890762	12/1998	Yoshida	N/A	N/A
5893606	12/1998	Chiang	N/A	N/A
5961180	12/1998	Greger et al.	N/A	N/A

6070890	12/1999	Haut et al.	N/A	N/A
6170911	12/2000	Kassai et al.	N/A	N/A
6183044	12/2000	Koyanagi et al.	N/A	N/A
6237995	12/2000	Dierickx	N/A	N/A
6253392	12/2000	Conforti et al.	N/A	N/A
6296259	12/2000	Anderson	N/A	N/A
6299249	12/2000	Mori	N/A	N/A
6322142	12/2000	Yoshida et al.	N/A	N/A
6416272	12/2001	Suehiro et al.	N/A	N/A
6511105	12/2002	Sakamoto	N/A	N/A
6561577	12/2002	Kelly	N/A	N/A
6655702	12/2002	Senger	N/A	N/A
6695400	12/2003	Washizuka et al.	N/A	N/A
6793280	12/2003	Washizuka et al.	N/A	N/A
6910696	12/2004	Bargery et al.	N/A	N/A
6979057	12/2004	Sedlack	N/A	N/A
6983986	12/2005	Jane Santamaria	N/A	N/A
6986518	12/2005	Besaw	N/A	N/A
7040694	12/2005	Sedlack	N/A	N/A
7104603	12/2005	Keegan et al.	N/A	N/A
7311353	12/2006	Johnson	N/A	N/A
7485086	12/2008	Dickie	N/A	N/A
7488034	12/2008	Ohren et al.	N/A	N/A
7497461	12/2008	Emerson	N/A	N/A
7506921	12/2008	Sigmon et al.	N/A	N/A
7540507	12/2008	Kennedy	N/A	N/A
7543886	12/2008	Gutierrez-Hedges et al.	N/A	N/A
7597396	12/2008	Longenecker et al.	N/A	N/A
7600766	12/2008	Erskine	N/A	N/A
7669927	12/2009	Zaid	N/A	N/A
7775532	12/2009	Chen et al.	N/A	N/A
7988230	12/2010	Heisey et al.	N/A	N/A
8123295	12/2011	Hutchinson et al.	N/A	N/A
8172253	12/2011	Song	N/A	N/A
8393678	12/2012	Keegan et al.	N/A	N/A
8434781	12/2012	Mazar et al.	N/A	N/A
8469389	12/2012	Mazar et al.	N/A	N/A
8469390	12/2012	Mazar et al.	N/A	N/A
8523218	12/2012	Doucette et al.	N/A	N/A
8651502	12/2013	Winterhalter et al.	N/A	N/A
8678498	12/2013	Heisey	N/A	N/A
8801028	12/2013	Mazar et al.	N/A	N/A
8876208	12/2013	Heisey et al.	N/A	N/A
8936254	12/2014	Viana et al.	N/A	N/A
8998242	12/2014	Wang	N/A	N/A
9027952	12/2014	Zhu	N/A	N/A
9090181	12/2014	Williams et al.	N/A	N/A
9119483	12/2014	Heisey	N/A	N/A
9168940	12/2014	Leszczak et al.	N/A	N/A

9227536	12/2015	Cary et al.	N/A	N/A
9227648	12/2015	Sundberg et al.	N/A	N/A
9242585	12/2015	Kozinski	N/A	N/A
9260036	12/2015	Walters et al.	N/A	N/A
9260039	12/2015	Satterfield	N/A	B62B 7/145
9308839	12/2015	Gleckler	N/A	N/A
9326900	12/2015	Bancroft	N/A	N/A
9339118	12/2015	Gubitosi et al.	N/A	N/A
9371017	12/2015	Spence et al.	N/A	N/A
9434279	12/2015	Williams	N/A	N/A
9469222	12/2015	Williams	N/A	N/A
9499074	12/2015	Strong et al.	N/A	N/A
9505321	12/2015	Mazar	N/A	N/A
9592846	12/2016	Hanson et al.	N/A	N/A
9603464	12/2016	Sclare et al.	N/A	N/A
9707987	12/2016	Hanson et al.	N/A	N/A
9738181	12/2016	Termini	N/A	N/A
9764755	12/2016	D'Anastasi	N/A	N/A
9868456	12/2017	Stiba et al.	N/A	N/A
10035437	12/2017	Ballard	N/A	N/A
10052981	12/2017	Wright	N/A	N/A
10058192	12/2017	Williams et al.	N/A	N/A
10427558	12/2018	Dickens	N/A	N/A
10710478	12/2019	Reaves et al.	N/A	N/A
10780800	12/2019	Kaiser	N/A	N/A
10933778	12/2020	Hinson	N/A	B60N 2/2821
11034266	12/2020	Heisey et al.	N/A	N/A
11267376	12/2021	Churilla et al.	N/A	N/A
11472316	12/2021	Olfers et al.	N/A	N/A
11584267	12/2022	Longenecker et al.	N/A	N/A
11723477	12/2022	Rogers et al.	N/A	N/A
11932300	12/2023	Jablonski	N/A	N/A
11958524	12/2023	Saucier et al.	N/A	N/A
11993301	12/2023	Cheng	N/A	N/A
12291258	12/2024	Hartenstine et al.	N/A	N/A
2002/0060444	12/2001	Cote	N/A	N/A
2003/0015894	12/2002	Bargery et al.	N/A	N/A
2004/0173997	12/2003	Voll	N/A	N/A
2009/0295128	12/2008	Nagelski et al.	N/A	N/A
2010/0019547	12/2009	Gray et al.	N/A	N/A
2010/0225150	12/2009	Duncan et al.	N/A	N/A
2011/0163518	12/2010	Song	N/A	N/A
2012/0032418	12/2011	Doucette et al.	N/A	N/A
2012/0032420	12/2011	Mazar et al.	N/A	N/A
2012/0119457	12/2011	Williams	N/A	N/A
2013/0229033	12/2012	Lee	N/A	N/A
2014/0265255	12/2013	Wang	N/A	N/A
2015/0329017	12/2014	Kozinski	N/A	N/A
2017/0240072	12/2016	Wright	N/A	B62B 7/12

2018/0009341	12/2017	Carlile	N/A	B62B 9/20
2018/0029625	12/2017	Ruggiero et al.	N/A	N/A
2018/0086235	12/2017	Anderson et al.	N/A	N/A
2020/0269733	12/2019	Heisey	N/A	B60N 2/2845
2021/0009012	12/2020	Olfers	N/A	B60N 2/2887
2022/0346569	12/2021	Liu	N/A	N/A
2022/0355713	12/2021	Longenecker et al.	N/A	N/A
2023/0014310	12/2022	Longenecker et al.	N/A	N/A
2023/0382446	12/2022	Crossgrove et al.	N/A	N/A
2024/0239249	12/2023	Saucier et al.	N/A	N/A
2024/0239250	12/2023	Saucier et al.	N/A	N/A
2024/0239396	12/2023	Saucier et al.	N/A	N/A
2024/0239398	12/2023	Saucier et al.	N/A	N/A
2024/0246462	12/2023	Saucier et al.	N/A	N/A
2024/0246593	12/2023	Saucier et al.	N/A	N/A
2024/0246594	12/2023	Saucier et al.	N/A	N/A
2024/0246595	12/2023	Saucier et al.	N/A	N/A
2024/0246596	12/2023	Saucier et al.	N/A	N/A
2024/0246597	12/2023	Saucier et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201124777	12/2007	CN	N/A
202686025	12/2012	CN	N/A
203637612	12/2013	CN	N/A
204687877	12/2014	CN	N/A
207257442	12/2017	CN	N/A
216861236	12/2021	CN	N/A
115402164	12/2021	CN	N/A
115402165	12/2021	CN	N/A
218558646	12/2022	CN	N/A
218750429	12/2022	CN	N/A
1918155	12/2007	EP	N/A
2024/046335	12/2023	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion received for PCT Patent Application No. PCT/CN2023/115629, mailed on Oct. 24, 2023, 15 pages (11 pages of original copy and 4 pages of English Translation). cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/098,306, mailed on Mar. 13, 2025, 18 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/099,351, mailed on Mar. 25, 2025, 14 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/098,316, mailed on Apr. 9, 2025, 5 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/099,373, mailed on Mar. 28, 2025, 12 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/098,312, mailed on May 27, 2025, 16

pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/098,319, mailed on May 14, 2025, 9 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/099,356, mailed on Jun. 17, 2025, 17 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/099,361, mailed on May 28, 2025, 12 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/099,363, mailed on Jun. 10, 2025, 19 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/099,368, mailed on Jun. 10, 2025, 19 pages. cited by applicant

Primary Examiner: Dunn; David R

Assistant Examiner: Abraham; Tania

Attorney, Agent or Firm: Shook Hardy & Bacon L.L.P.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure generally relates to a modular, convertible infant transport system and an assembly.

BACKGROUND

(2) Traditionally, infants may be transported in infant carriers, which may also be a part of an infant car seat or as a part of a stroller (among other modes of transport). There have been some attempts to develop systems that may be used as a car seat, an infant carrier and a stroller, but these systems, to date, suffer from a number of disadvantages and drawbacks, such as not offering a desired level of optional configurations.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The drawings described herein are for illustrative purposes only, are schematic in nature, and are intended to be exemplary rather than to limit the scope of the disclosure.
- (2) FIG. 1 is a perspective view of an infant transport system in a first transport condition.
- (3) FIG. 2 is a perspective view of the base of the infant transport system decoupled from the chassis and the shell.
- (4) FIG. 3A is a perspective view of the chassis and the shell of the infant transport system, decoupled from the base and showing a first stage of repositioning a rear wheel.
- (5) FIG. 3B is a perspective view of the chassis and the shell of the infant transport system, decoupled from the base and showing a second stage of reposition a rear wheel.
- (6) FIG. 4 is a perspective view of the chassis and the shell of the infant transport system decoupled from the base and with the legs deployed in a second transport condition.
- (7) FIG. 5 is a perspective view of the chassis and the base of the infant transport system with the shell decoupled from the chassis and the base.
- (8) FIG. 6 is a perspective view of the shell of the infant transport system decoupled from the chassis and the base.

- (9) FIG. 7 is a view similar to FIGS. 3A and 3B from a different viewpoint.
- (10) FIG. 8 is a side view of the infant transport system in partial cross-section.
- (11) FIG. 9 is a perspective cross-section view of the infant transport system of FIG. 1.
- (12) FIG. 10 is a cross-section view of the chassis and the shell of the infant transport system decoupled from the base.
- (13) FIG. 11 is a bottom plan view of the chassis and the shell of the infant transport system decoupled from the base.
- (14) FIG. 12 is a perspective view of the chassis of the infant transport condition, shown with the legs deployed and with some parts broken away.
- (15) FIG. 13A is a partial perspective view of certain components of a first release mechanism in a first state.
- (16) FIG. 13B is a view similar to FIG. 13A with the first release mechanism in a second state.
- (17) FIG. 14 is a partial cross-section of the legs of the chassis of FIG. 12.
- (18) FIG. 15 is a partial perspective view of the chassis with parts being broken away.
- (19) FIG. 16 is a cross-section of the infant transport system of FIG. 1.
- (20) FIG. 17 is a partial exploded view of the interior of the shell of the infant transport system.
- (21) FIG. 18 is a partial cross-section of the shell of the infant transport system.
- (22) FIG. 19 is a cross-section of the chassis and the base of the infant transport system.
- (23) FIG. 20 is perspective view of the base of the infant transport system shown with the wheel guards removed.
- (24) FIG. 21 is a view with certain components shown in an environment and showing the cabling of the second release mechanism.

DETAILED DESCRIPTION

- (25) In an example aspect, an infant transport system is provided. The infant transport system may comprise: a base; a chassis releasably coupled to the base via a first release mechanism; and an infant car seat releasably coupled to the chassis via a second release mechanism. The chassis is intermediate the base and the infant car seat in a first transport condition. The chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism. Upon operation of the second release mechanism, the infant car seat is releasable from the combined unit of the base and chassis. In some configurations, the chassis includes a bar, and the first release mechanism and the second release mechanism are each releasably coupled to the bar in the first transport condition. In some aspects, the bar on the chassis is continuous and extends from one side of the chassis to an opposite side of the chassis, while in other aspects, the bar on the chassis is discontinuous and includes multiple segments.
- (26) In other configuration, the chassis comprises a frame, a pair of rear legs pivotally coupled to the frame and a pair of front legs, each front leg pivotally coupled to a respective rear leg. The rear legs and the front legs may be retracted to be proximate the frame in the first transport condition, and may be deployable away from the frame to a second transport condition when the chassis and infant car seat are released from the base. In some aspects, each of the front legs and each of the rear legs have a wheel at a respective distal end, and wherein the second transport condition is usable as a stroller
- (27) In other examples, the infant transport system may be configured such that any of the infant car seat, a combination of the chassis and the infant car seat, and a combination of the base, the chassis and the infant car seat, may be installed in an automobile to transport an infant.
- (28) In a further example, the frame of the chassis includes a pair of recesses, and the rear wheels are removable from the rear legs and are stow-able in the pair of recesses when the chassis and the infant car seat are removed from the base and the legs of the chassis are retracted.
- (29) The above features and advantages and other features and advantages of the present teachings are readily apparent from the following detailed description of the modes for carrying out the present teachings when taken in connection with the accompanying drawings.

(30) In some aspects, at a high-level, an infant transport system is provided that offers increased flexibility in the usable configurations of the system. The infant transport system, in some aspects, includes a base and an independent chassis that is releasably coupled to the base via a first release mechanism. The infant transport system also includes an infant car seat, (throughout this specification, the infant car seat may also be referred to as a shell), that is releasably coupled to the chassis via a second release mechanism. In a first transport condition, the chassis is intermediate the base and the infant car seat. In this first transport condition, the assembly of the base, the chassis and the infant car seat are usable within a vehicle to transport an infant. The chassis and the infant car seat are releasable from the base, as a combined unit, upon operation of the first release mechanism. In this condition, the front legs and rear legs of the chassis are deployable away from the frame of the chassis, such that the assembly is usable as an infant stroller. Additionally, in some aspects, the infant car seat is releasable from the combined unit of the base and the chassis upon operation of the second release mechanism. In this condition, the infant car seat is usable as an infant carrier. Other features and details of operation of the infant transport system are described below in connection with the drawing figures.

(31) Referring to the drawings, wherein like reference numbers refer to like components, FIGS. 1-21 depict an infant transport system, or assembly, **10**. The infant transport system **10**, in some aspects, includes a base **12**, an independent chassis **14** releasably coupled to the base **12**, and an infant car seat, or shell, **16**. The base **12**, the chassis **14** and the shell **16** are shown coupled together in FIG. 1 in a first transport condition, and is one example of the system **10** usable to secure an infant in a vehicle. While not shown to make other components more visible, the shell **16** is equipped with padding and an infant safety harness system. As shown in FIG. 2, the chassis **14** and the shell **16** are releasable from the base **12**. The base **12** may be installed in a vehicle and secured in place using anchoring straps or the seat belt of the vehicle. Once the base **12** is installed in the vehicle, the combined unit of the chassis **14** and the shell **16** may be releasably coupled to the base **12**, as further described below. FIG. 3 depicts the chassis **14** coupled to the shell **16** and removed from the base **12**. In this transport condition, the assembly of the shell **16** and the chassis **14** is usable as an infant carrier (using a carrier handle **18**), and may also be installed in a vehicle and used as a car seat as described in further detail below. As shown in FIG. 4, the chassis **14** includes a pair of front legs **20** that are each pivotally coupled to a respective one of a pair of rear legs **22** which are, in turn, pivotally coupled to the chassis **14**. The front legs **20** and rear legs **22** are deployable from the transport condition shown in FIG. 3 to the transport condition shown in FIG. 4, such that the assembly of the chassis **14** and shell **16** are usable as a stroller. In this transport condition, the handle **18** is rotatable and extendable for use in pushing the stroller. As depicted in FIGS. 5 and 6, the shell **16** is also releasable from the combined unit of the base **12** and the chassis **14**. In the transport condition shown in FIG. 6, the shell **16** is usable as an infant carrier and can also be secured within a vehicle and usable as a car seat. The infant transport system **10** thus allows for greater flexibility in the various transport conditions as is further described in detail below.

(32) As shown in FIGS. 8-9, a first release mechanism **24** is distributed between the chassis **14** and the base **12**. The first release mechanism **24** includes a release handle **26** movably disposed on a frame **28** of the chassis **14**. In some aspects, the release handle **26** is movably coupled to the frame **28**, allowing the release handle **26** to move generally upwardly and downwardly. The release handle **26** is coupled to a cable **30** that extends downwardly from the handle **26** within the interior of the frame **28**. The end of cable **30** opposite the handle **26** is coupled to a carriage **32** having a slot **34** formed therein. The carriage **32** is slidable along a stationary rod **35** fixed to the chassis **14** and that extends through the slot **34**. The carriage **32** moves rearwardly along the rod **35** when the handle **26** is pulled upwardly. As best seen in FIG. 8, the carriage **32** is coupled to a lever **36** that moves as the carriage **32** moves. In some aspects, the carriage **32** is coupled to the lever **36** via a separate cable **38**. In other aspects, the cable **38** is integrally formed as a part of lever **36** or as a part of carriage **32**. The cable **30** and the cable **38** (along with other cables discussed herein) may

be made from a flexible material, and in some aspects, are made from a steel wire or a plastic material. The lever **36** includes a downwardly extending hook **40** and a downwardly extending finger **42**. The hook **40** releasably engages a post **44** that is fixed to the base **12**. In some aspects, the post **44** is a U-bolt that is fastened to the base **12**. As the handle **26** is pulled upwardly, the hook **40** is moved rearwardly to release the hook **40** from the post **44**. The finger **42** engages one end **46** of an arm **48** that is slidably held within the base **12**. The end **46** of arm **48** has a portion that extends outwardly and is exposed on the exterior of the base **12** (see FIG. **20**). As best seen in FIG. **9**, the end **46** has another portion that is within the interior of the base **12**. The arm **48** extends from the end **46** upwardly to a distal end **50** that is pivotally coupled to a hook **52** at pivot point **54**. The hook **52** is also pivotally coupled to the base **12** at pivot point **56**. The hook **52** releasably engages a rod **58** on the chassis **14**. In some aspects, the rod **58** on the chassis **14** serves as an axle for wheels **60** on the end of rear legs **22**. In other aspects, the rod **58** is discontinuous and does not function as an axle.

(33) The first release mechanism **24** is operable, in a first function, to release the chassis **14** and the shell **16**, as a combined unit, from the base **12**. As the handle **26** is pulled upwardly, the cable **30** acts to move the carriage **32** and the lever **36** rearwardly, releasing the hook **40** from the post **44** on the base **12**. As the lever **36** moves rearwardly, the finger **42** engages the first end **46** of the arm **48**, moving the arm **48** rearwardly. This in turn rotates the hook **52** about pivot point **56**, releasing the hook **52** from the rod **58**. As these two attachment points (hook **40**/post **44** and hook **52**/rod **58**) release, the chassis **14** and the shell **16** are releasable as a combined unit from the base **12**. While only one side of the first release mechanism **24** is shown and described above, it should be understood that the handle **26** may be coupled to a similar series of components (cable **30**, carriage **32**, lever **36**, cable **38**, arm **48** and hook **52**) on each side of the chassis **14**.

(34) A second release mechanism **70** is operable, in a first function, to release the shell **16** from the combined unit of the base **12** and the chassis **14**. As best seen in FIG. **10**, the second release mechanism **70** includes a release handle **72** movably disposed within the shell **16**. As best seen in FIGS. **17** and **21**, the handle **72** is selectively coupled, via a cable **74**, to a release lever **76** positioned within the shell **16**. The lever **76** includes a downwardly extending hook **78** and a front finger **80**. As best seen in FIG. **17**, both the hook **78** and the finger **80** releasably engage a pair of upwardly extending U-bolts **82** that are coupled to the chassis **14**. The lever **76** is only operational when the chassis **14** is coupled to the base **12** (so that the shell **16** is removable from the combined unit of the chassis **14** and the base **12**, but the shell **16** is not removable from the chassis **14** when the chassis **14** is decoupled from the base **12**). To achieve this selective operation of the lever **76**, the chassis **14** includes a spring-loaded pin **84**. The pin **84** is moved upwardly and into the chassis **14** by the base **12** when the chassis **14** is coupled to the base **12**. Conversely, when the chassis **14** is decoupled from the base **12**, the pin **84** moves downwardly, biased by a spring. When the pin **84** moves upwardly (with the chassis **14** on the base **12**), the pin **84** moves through a hole **86** in the lever **76** and into a corresponding hole **88** in the cable **74**. With the pin **84** coupling the lever **76** and the cable **74**, an upward force on the handle **72** is translated into a rearward movement of the lever **76**, releasing the hook **78** and the finger **80** from engagement with the U-bolts **82**. This action releases the central section of the shell **16** from the chassis **14**. While not shown, the shell **16** may include a cover over the section of cable **74** having the hole **86** to ensure the pin **84** extends into the cable **74** (the cover acts to maintain cable **74** in close proximity to the lever **76**).

(35) In some aspects, as best seen in FIG. **21**, the cable **74** extends forwardly to engage another hook **90** that is pivotally coupled inside shell **16** at pivot point **92**. The hook **90** selectively engages a portion of the rod **58**, as best seen in FIG. **10**. The opposite end of the hook **90** has a tab **94** that is coupled to a terminal end of the cable **74**. With this connection, an upward force on the handle **72** is translated to a rotational movement of the hook **90**, releasing the hook **90** from the rod **58**. This action releases the forward end of the shell **16** from the chassis **14**. Therefore, when the shell **16** and chassis **14** are coupled to the base **12**, the second release mechanism **70** is operable, in a first

function through handle **72**, to release the shell **16** from the combined unit of the chassis **14** and the base **12**, allowing the shell **16** to be used as an infant carrier, without the chassis **14** and the base **12** (as shown in FIG. **6**). The shell **16** is also usable as an infant car seat and can be secured in place within a vehicle with the provided vehicle seat belts. In some aspects, the shell **16** is provided with seat belt anchors **96** to facilitate such a connection.

(36) In some aspects, the second release mechanism **70** is operable in a second function to deploy the front legs **20** and the rear legs **22** below the chassis **14** to allow use of the combined unit of the chassis **14** and the shell **16** as a stroller (transitioning from the transport condition shown in FIG. **3** to the transport condition shown in FIG. **4**). To achieve this second function, as best seen in FIGS. **10**, **17** and **21**, the second release mechanism **70** also includes a pivot arm **100** having a first end **102** that is coupled to the release handle **72** via a cable **104**. In some aspects, the cable **104** may be integrally formed with the cable **74**, and in other aspects, the cable **104** is a separate component from cable **74**. The pivot arm **100** is pivotally coupled within the shell **16** at pivot point **106**. A second end **108** of the arm **100** includes a downwardly extending plunger **110** that is positioned to selectively extend from the interior of the shell **16**. As the handle **72** is moved upwardly, the cable **104** moves the first end **102** upwardly (rotating about pivot point **106**), causing the plunger **110** to move downwardly and outside of the shell **16**. As best seen in FIG. **21**, when the shell **16** is coupled to the chassis **14**, the plunger **110** is positioned to interact with a release hook **120** that is pivotally coupled within the chassis **14** at pivot point **122**. The release hook **120** includes a tab **124** that interacts with the plunger **110** and a hook end **128** opposite the tab **124**. The hook end **128** releasably engages a front leg cross-brace **130** (see FIG. **11**). When the release handle **72** is pulled upwardly when the chassis **14** and shell **16** are in the transport condition shown in FIG. **3A**, the cable **74** and the cable **104** rotate the hook **90** and the hook **120** respectively. When the hook **90** rotates, the hook **90** disengages the rod **58** coupled to the rear legs **22**. Similarly, when the hook **120** rotates, the hook **120** disengages the front leg cross brace **130**. With the front legs **20** and the rear legs **22** disengaged, the combined unit of the chassis **14** and the shell **16** is allowed to move to the stroller transport condition shown in FIG. **4**. In some aspects, the front legs **20** and the rear legs **22** may be spring-biased to the stroller transport condition, such that when the release handle **72** is pulled, the front legs **20** and the rear legs **22** are moved via gravity and the spring-assist to the deployed, stroller condition of FIG. **4**.

(37) In some aspects, the second release mechanism **70** is operable in a third function to allow the shell **16**, when separated from the chassis **14** and the base **12**, to be releasably coupled to a standard tower stroller system, such as those already known in the art. To facilitate this connection, as best seen in FIG. **18**, the shell **16** includes a release latch **136** pivotally coupled to the shell **16** within a recessed area **138**. The recessed area **138** is located proximate a hub **140** of a handle assembly **142** on the shell **16**. The latch **136** is pivotally biased to a closed orientation, allowing the shell **16** to drop into a standard tower stroller system, with the latch **136** engaging a portion of the standard tower stroller system (such as a cylindrical attachment portion). As seen in FIG. **21**, the latch **136** is coupled, via a cable **144** to the release handle **72**. As the release handle **72** is pulled, the latch **136** rotates to release the latch from engagement with the standard tower stroller system. In some aspects, the cable **144** may be integrally formed with cable **74** and/or cable **104**, while in other aspects, the cable **144** is a separate component.

(38) The first release mechanism **24** is operable in a second function to allow the deployed front legs **20** and the rear legs **22** (as shown in FIG. **4**) to be retracted and returned to the transport condition shown in FIG. **3A**. To achieve this function, the chassis **14** includes a locking peg **150**, as best seen in FIGS. **13A** and **13B**. The locking peg **150** is spring loaded to extend outwardly (as viewed in FIG. **13A**, the spring biases peg **150** to the right). The chassis **14** includes a channel that extends through a hub **154** of the rear leg **22** and into a hub **156** of the front leg **20**. When the rear leg **22** rotates downwardly to the deployed transport condition shown in FIG. **4**, the locking peg **150** moves, via the spring force, through the channel extending through and into the hub **156** of the

front leg **20** (as shown in FIG. **13A**), locking the front legs **20** in the deployed condition. The locking peg **150** includes an upwardly extending cam pin **153** that extends through a triangular opening **155** in carriage **132**. The triangular opening **155** includes an angled cam surface **157**. As the handle **72** is pulled upwardly, the carriage **132** moves rearwardly. This rearward movement causes the cam surface **157** to act on the pin **153**, moving the locking peg **150** inwardly and out of engagement with the hub **156** of the front leg **20** (as shown in FIG. **13B**), allowing the front leg **20** to rotate. As best seen in FIG. **14**, the rear legs **22** are also locked in the deployed condition via a first lock **159** in the chassis **14**. The lock **159** is spring loaded to extend into a locking notch **161** in a hub extension **163** in the rear leg **22**, when the rear leg **22** is in the deployed position. The front leg **20** has a cam lobe **162** extending radially outwardly from the front leg hub **156**. The cam lobe **162** is shaped to engage a release cam **158** that is slidably disposed in a channel **160**, as the front leg **20** rotates from the deployed position to the retracted position. As the cam lobe **162** engages the release cam **158**, the release cam **158** is moved into engagement with the lock **159** to move the lock **159** out of the locking notch **161** in the rear leg **22**, allowing the rear leg to rotate about hub **154**. In some aspects, the release cam **158** has an angled cam surface that interacts with the lock **159** to achieve the inward movement of the lock **159** as it interacts with the release cam **158**. Further, in some aspects, the lock **159** may include a chamfer **165** that ensures the lock **159** will not interfere with the retracting motion of the front legs **20** (because the front legs **20** will first contact the chamfer **165** if the lock **159** is not properly fully retracted). When the chassis **14** and shell **16** are in the deployed stroller transport condition of FIG. **4**, the first release mechanism **24** may be operated via the handle **26** to allow the front legs **20** and the rear legs **22** to retract. When the handle **26** is pulled, the locking peg **150** moves out of engagement with the hub **156**, allowing the front legs **20** to retract. As the front leg **20** rotates, the cam lobe **162** interacts with the lock **158**, moving the lock **158** from engagement with the rear leg **22**, allowing the rear leg **22** to retract. In this way, the first release mechanism **24** is operable in a second function to allow the front legs **20** and the rear legs **22** to retract. In some aspects, as best seen in FIG. **15**, the chassis **14** includes a spring module **164** that acts on the front leg **20**. As the locking peg **150** moves out of engagement with the hub **156**, the spring module **164** acts to impart a rotational force on the front leg **20** (through the front cross brace **130**), assisting the front leg **20** in moving to a retracted position. In some aspects, the spring module **164** acts to only partially retract the front legs **20**.

(39) As described above, with the front legs **20** and the rear legs **22** retracted, the combined unit of the chassis **14** and the shell **16** may be used to transport an infant in a vehicle, without using the base **12**. In some aspects, to better orient and stabilize the combined unit of the chassis **14** and the shell **16** within the vehicle, it may be desirable to relocate the rear wheels **60**. As best seen in FIGS. **3A** and **3B**, each rear wheel **60** may be releasably coupled a lower hub **168**. In some aspects, the rear wheel **60** has an axle **170** that serves as a quick-release pin. The pin has a retractable ball, activated by a push-button **172** at the outer end of the axle **170**. When the button **172** is pressed, the ball retracts within the pin, allowing the axle **170** (and thus the rear wheel **60**) to be removed from the hub **168** as shown in FIG. **3A**. Other forms of quick-release may also be used in coupling the rear wheel **60** within the hub **168**. As best seen in FIG. **3B**, the removed rear wheel **60** and axle **170** may then be inserted into a vertical receiving cavity **174** (shown in FIG. **16**) on the chassis **14**. The same can be done for the other rear wheel **60**, such that both rear wheels **60** are received in a respective receiving cavity **174** (one on each side of the chassis **14**). With the wheels **60** in the receiving cavities **174**, the rear wheels **60** prevent the combined unit of the chassis **14** and the shell **16** from rocking or tipping when installed within a vehicle.

(40) Returning to FIG. **20**, the base **12** is shown decoupled from the chassis **14** and the shell **16**. As described above, the base **12** may be secured within a vehicle and will accept the combined unit of the chassis **14** and the shell **16** for convenient transport of an infant. The base **12**, in some aspects, includes a frame **178** having opposed sides **179**, a forward end **180** and a rearward end **181**. The frame **178** supports an anti-rebound panel **182** that extends upwardly along the rearward end **181**.

The frame **178** and the anti-rebound panel **182** may be formed as an integral part of the base **12**. The anti-rebound panel **182** reduces movement of the base **12** within the vehicle (especially in situations involving a sudden stop, or an impact incident). As best seen in FIG. **20**, the anti-rebound panel **182** extends upwardly and has an outer perimeter defined by top-line edge **183** and side edges **184**. In some aspects, a level indicator **185** is coupled to the anti-rebound panel **182** on the top-line edge **183**. The level indicator **185** may be coupled at the center of the top-line edge for easy viewing by a user when the base is installed on either side of the vehicle. In some aspects, the level indicator **185** includes an outer shell **186** and a bubble level **188**. Further, in some aspects, the level indicator **185** may be curved, and in some aspects, both the outer shell **186** and the bubble level **188** have a curved upper surface. In some aspects, the bubble level **188** is recessed below a top surface of the outer shell **186**. The level indicator **185** (and specifically the bubble level **188**) may be oriented in the longitudinal direction of the base **12**. The level indicator **185** is used to indicate proper installation of the base **12** within the vehicle. By locating the level indicator **185** along the top-line edge **183**, a user is able to better view the level indicator **185**, as opposed to the indicator being elsewhere on the base **12**.

(41) The base **12**, in some aspects, also includes a wheel guard **200** on each side of the base **12**. As best seen in FIG. **20**, the wheel guard **200** may include an outer raised lip **202** spaced from an inner wall **204** by a bottom wall **206**. On one end, the wheel guard **200** includes a rear wall **208** that extends from the bottom wall **206** and between the inner wall **204** and the outer lip **202**. In some aspects, the rear wall **208** is curved to match the outer diameter of the rear wheel **60**. Near the transition between the bottom wall **206** and the forward wall **208**, the wheel guard **200** may include a wheel bump **210** that extends upwardly from the bottom wall **206** and that is positioned to locate and support the rear wheel **60**. In some aspects, the wheel guard **200** may also include a wheel support **214** that extends upwardly from the bottom wall **206**. The wheel support **214** is positioned to support a front wheel **212** at the terminal end of the front leg **20**. The wheel support **214** may be a triangular shape whose apex above the bottom wall **206** supports the front wheel **212** when the chassis **14** is coupled to the base **12** (see FIG. **1**). The wheel guard **200** may be removably coupled to the base **12**, to allow a user to remove and clean the wheel guard **200** as needed. As best seen in FIG. **20**, a top wall **216** extends inwardly from the top of the inner wall **204**. In some aspects, a pair of locating pegs **218** extend downwardly from the top wall **216**. In some aspects, one locating peg **218** is near a forward end of the top wall **216** and one locating peg **218** is near a rearward end of the top wall **216**. The top wall **216** may also have a curved hub support section **220** that is positioned and shaped to support the hub **154** for the rear wheel **60**. As best seen in FIG. **20**, in some aspects, the hub support section **220** may include a pair of downwardly extending locating tabs **222**. The wheel guard **200** may also include, in some aspects, a pair of downwardly extending locating fingers **224**. The inner wall **204** may include an inwardly extending relief area **226** corresponding to each of the locating fingers **224**. The inner wall **204** may also include, in some aspects, a hole **228** that is shown as a circular hole (but that may be other shapes as well). The wheel guard **200** is coupled to the base **12** via the locating pegs **218**, the locating tabs **222**, the locating fingers **224** and the hole **228**. To facilitate this coupling, the frame **178** of the base **12** includes the side walls **179**. Each side wall **179** may have a ledge **232** that corresponds in size and shape to the top wall **216** of the wheel guard **200**. The ledge **232** includes, in some aspects, a curved depression **234** that corresponds to the curved hub support **220** on the wheel guard **200**. The side wall **230** includes a pair of spaced apart slots **236** (only one of which is shown in FIG. **20**) that are sized and spaced to accept the locating tabs **222**. Similarly, the ledge **232** may include a pair of holes **238** that are sized and spaced to accept the locating pegs **218**. As best seen in FIG. **20**, a pair of anchors **240** extend outwardly away from the side wall **230**. Each of the anchors **240** includes a slot that is sized and shaped to accept a corresponding finger **224** of the wheel guard **200**. Additionally, in some aspects, the side wall **230** includes a tab **242** that is resiliently coupled to the side wall **230**. In some aspects, the tab **242** is integrally formed with the side wall **230**, and is

coupled along a top edge to the side wall 230, while the sides and bottom of the tab 242 are not attached to the side wall 230. The lower section of the tab 242 includes a button 244 that is sized and shaped to correspond to the hole 228, such that the hole 228 is a negative form of the button 244. To couple the wheel guard 200 to the base 12, the locating pegs 218 are aligned with the holes 238, the tabs 222 are aligned with slots 236, and the fingers 224 are aligned with the slots in the anchors 240. The wheel guard 200 can then be moved downwardly to engage: the pegs 218 with the holes 230; the tabs 222 with the slots 236 and the fingers 224 with the slots in the anchors 240. As the wheel guard 200 is moved downwardly, the button 244 moves inwardly until the button 244 is aligned with the hole 228. Once the button 244 is aligned with the hole 228, the button 244 will move outwardly to engage the hole 228 and retain the wheel guard 200 in place on base 12. To remove the wheel guard 200, a user can depress the button 244 to move the button 244 from engagement with the hole 228 and allow the user to move the wheel guard 200 upwardly, disengaging the pegs 218, the tabs 222 and the fingers 224. In this manner, a user can remove the wheel guards 200 as desired, such as might be needed to clean the wheel guard 200. The wheel guards 200 can also be removed from the base 12 to allow for a more compact form for shipping. (42) The following clauses provide example configurations of an infant transport system and assembly as disclosed herein.

(43) Clause 1. An infant transport system, comprising: a base; a chassis releasably coupled to the base via a first release mechanism; and an infant car seat releasably coupled to the chassis via a second release mechanism; wherein the chassis is intermediate the base and the infant car seat in a first transport condition; wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism; and wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism.

(44) Clause 2. The system of clause 1, wherein the chassis includes a bar, and wherein the first release mechanism and the second release mechanism are each releasably coupled to the bar in the first transport condition.

(45) Clause 3. The system of any of clauses 1-2, wherein the bar on the chassis is continuous and extends from one side of the chassis to an opposite side of the chassis.

(46) Clause 4. The system of any of clauses 1-3, wherein the bar on the chassis is discontinuous and includes multiple segments.

(47) Clause 5. The system of any of clauses 1-4, wherein the chassis comprises a frame, a pair of rear legs pivotally coupled to the frame and a pair of front legs, each front leg pivotally coupled to a respective rear leg, wherein the rear legs and the front legs are retracted and proximate the frame in the first transport condition, and wherein the rear legs and the front legs are deployable away from the frame to a second transport condition when the chassis and infant car seat are released from the base.

(48) Clause 6. The system of any of clauses 1-5, wherein any of the infant car seat, a combination of the chassis and the infant car seat, and a combination of the base, the chassis and the infant car seat, are configured to be installed in an automobile.

(49) Clause 7. The system of any of clauses 1-6, wherein each of the front legs and each of the rear legs have a wheel at a respective distal end, and wherein the second transport condition is usable as a stroller.

(50) Clause 8. The system of any of clauses 1-7, wherein the frame of the chassis includes a pair of recesses, and wherein the rear wheels are removable from the rear legs and stow-able in the pair of recesses.

(51) Clause 9. An infant transport assembly, comprising: a base having a first end and a second end; an independent chassis releasably coupled to the base via a first release mechanism; and an infant car seat releasably coupled to the chassis via a second release mechanism, the infant car seat having a toe end and a head end distal from the toe end; wherein the infant car seat is releasable

from the combined unit of the base and chassis upon operation of the second release mechanism.

(52) Clause 10. The assembly of clause 9, wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism.

(53) Clause 11. The assembly of any of clauses 9-10, wherein the chassis comprises a frame housing a bar, and wherein the first release mechanism and the second release mechanism are each configured to be releasably coupled to the bar.

(54) Clause 12. The assembly of any of clauses 9-11, wherein the chassis is intermediate the infant car seat and the base in a first transport condition with the first release mechanism and the second release mechanism coupled to the bar, and wherein the bar on the chassis is proximate the first end of the base and proximate the toe end of the infant car seat in the first transport condition.

(55) Clause 13. The assembly of any of clauses 9-12, wherein the infant car seat comprises a tower coupling latch between the toe end and the head end, the tower coupling latch configured to allow the infant car seat to be releasably coupled to an alternative transport structure.

(56) Clause 14. The assembly of any of clauses 9-13, wherein any of the infant car seat, a combination of the chassis and the infant car seat, and a combination of the base, the chassis and the infant car seat, are configured to be installed in an automobile.

(57) Clause 15. The assembly of any of clauses 9-14, wherein the first end of the base comprises an upwardly extending rebound panel, and a level indicator on an upper portion of the rebound panel.

(58) Clause 16. The assembly of any of clauses 9-15, wherein the frame of the chassis includes a pair of recesses, and wherein the rear wheels are removable from the rear legs and stow-able in the pair of recesses when in the first transport condition.

(59) Clause 17. A system to transport infant children, comprising: a base configured to be secured to a portion of an automobile; a chassis independent from the base; a first release mechanism releasably coupling the chassis to the base; an infant car seat independent from the base and the chassis; a second release mechanism releasably coupling the infant car seat to the chassis; wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism; and wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism.

(60) Clause 18. The system of clause 17, wherein the chassis comprises a first handle coupled to the first release mechanism and configured to move the first release mechanism to selectively release the chassis and infant car seat as a unit from the base.

(61) Clause 19. The system of any of clauses 17-18, wherein the infant car seat comprises a second handle coupled to the second release mechanism and configured to move the second release mechanism to selectively release the infant car seat from the chassis and the base.

(62) Clause 20. The system of any of clauses 17-19, wherein the first release mechanism and the second release mechanism are spring-loaded to a closed configuration.

(63) To assist and clarify the description of various embodiments, various terms are defined herein. Unless otherwise indicated, the following definitions apply throughout this specification (including the claims). Additionally, all references referred to are incorporated herein in their entirety.

(64) “A”, “an”, “the”, “at least one”, and “one or more” are used interchangeably to indicate that at least one of the items is present. A plurality of such items may be present unless the context clearly indicates otherwise. All numerical values of parameters (e.g., of quantities or conditions) in this specification, unless otherwise indicated expressly or clearly in view of the context, including the appended claims, are to be understood as being modified in all instances by the term “about” whether or not “about” actually appears before the numerical value. “About” indicates that the stated numerical value allows some slight imprecision (with some approach to exactness in the value; approximately or reasonably close to the value; nearly). If the imprecision provided by “about” is not otherwise understood in the art with this ordinary meaning, then “about” as used herein indicates at least variations that may arise from ordinary methods of measuring and using such parameters. As used in the description and the accompanying claims, a value is considered to

be “approximately” equal to a stated value if it is neither more than 5 percent greater than nor more than 5 percent less than the stated value. In addition, a disclosure of a range is to be understood as specifically disclosing all values and further divided ranges within the range.

(65) The terms “comprising”, “including”, and “having” are inclusive and therefore specify the presence of stated features, steps, operations, elements, or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, or components. Orders of steps, processes, and operations may be altered when possible, and additional or alternative steps may be employed. As used in this specification, the term “or” includes any one and all combinations of the associated listed items. The term “any of” is understood to include any possible combination of referenced items, including “any one of” the referenced items. The term “any of” is understood to include any possible combination of referenced claims of the appended claims, including “any one of” the referenced claims.

(66) For consistency and convenience, directional adjectives may be employed throughout this detailed description corresponding to the illustrated embodiments. Those having ordinary skill in the art will recognize that terms such as “above”, “below”, “upward”, “downward”, “top”, “bottom”, etc., may be used descriptively relative to the figures, without representing limitations on the scope of the invention, as defined by the claims.

(67) While various embodiments have been described, the description is intended to be exemplary, rather than limiting and it will be apparent to those of ordinary skill in the art that many more embodiments and implementations are possible that are within the scope of the embodiments. Any feature of any embodiment may be used in combination with or substituted for any other feature or element in any other embodiment unless specifically restricted. Accordingly, the embodiments are not to be restricted except in light of the attached claims and their equivalents. Also, various modifications and changes may be made within the scope of the attached claims.

(68) While several modes for carrying out the many aspects of the present teachings have been described in detail, those familiar with the art to which these teachings relate will recognize various alternative aspects for practicing the present teachings that are within the scope of the appended claims. It is intended that all matter contained in the above description or shown in the accompanying drawings shall be interpreted as illustrative and exemplary of the entire range of alternative embodiments that an ordinarily skilled artisan would recognize as implied by, structurally and/or functionally equivalent to, or otherwise rendered obvious based upon the included content, and not as limited solely to those explicitly depicted and/or described embodiments.

Claims

1. An infant transport system, comprising: a base; a chassis releasably coupled to the base via a first release mechanism; and an infant car seat releasably coupled to the chassis via a second release mechanism; wherein the chassis comprises a frame, a pair of rear legs pivotally coupled to the frame and a pair of front legs, each front leg pivotally coupled to a respective rear leg, wherein the rear legs and the front legs are retracted and proximate the frame in a first transport condition, and wherein the rear legs and the front legs are deployable away from the frame to a second transport condition when the chassis and infant car seat are released from the base; wherein the chassis is intermediate the base and the infant car seat in the first transport condition; wherein the chassis includes a rod, and wherein the first release mechanism and the second release mechanism are each releasably coupled to the rod in the first transport condition; wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism; and wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism.

2. The system of claim 1, wherein the rod on the chassis is continuous and extends from one side of

the chassis to an opposite side of the chassis.

3. The system of claim 1, wherein the rod on the chassis is discontinuous and includes multiple segments.

4. The system of claim 1, wherein any of the infant car seat, a combination of the chassis and the infant car seat, and a combination of the base, the chassis and the infant car seat, are configured to be installed in an automobile.

5. The system of claim 1, wherein each of the front legs and each of the rear legs have a wheel at a respective distal end, and wherein the second transport condition is usable as a stroller.

6. The system of claim 5, wherein the frame of the chassis includes a pair of recesses, and wherein the rear wheels are removable from the rear legs and stow-able in the pair of recesses.

7. An infant transport assembly, comprising: a base having a first end and a second end; an independent chassis releasably coupled to the base via a first release mechanism, wherein the chassis comprises a frame, a pair of rear legs pivotally coupled to the frame and a pair of front legs, each front leg pivotally coupled to a respective rear leg, wherein the rear legs and the front legs are retracted and proximate the frame in a first transport condition, and wherein the rear legs and the front legs are deployable away from the frame to a second transport condition when the chassis and infant car seat are released from the base; and an infant car seat releasably coupled to the chassis via a second release mechanism, the infant car seat having a toe end and a head end distal from the toe end; wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism; and wherein the chassis includes a rod, and wherein the first release mechanism and the second release mechanism are each releasably coupled to the rod in the first transport condition.

8. The assembly of claim 7, wherein the chassis and the infant car seat are releasable from the base as a combined unit upon operation of the first release mechanism.

9. The assembly of claim 8, wherein the chassis is intermediate the infant car seat and the base in a first transport condition with the first release mechanism and the second release mechanism coupled to the rod, and wherein the rod on the chassis is proximate the first end of the base and proximate the toe end of the infant car seat in the first transport condition.

10. The assembly of claim 9, wherein the infant car seat comprises a tower coupling latch between the toe end and the head end, the tower coupling latch configured to allow the infant car seat to be releasably coupled to an alternative transport structure.

11. The assembly of claim 10, wherein any of the infant car seat, a combination of the chassis and the infant car seat, and a combination of the base, the chassis and the infant car seat, are configured to be installed in an automobile.

12. The assembly of claim 11, wherein the first end of the base comprises an upwardly extending rebound panel, and a level indicator on an upper portion of the rebound panel.

13. The assembly of claim 12, wherein each of the front legs and each of the rear legs have a wheel at a respective distal end, and wherein the frame of the chassis includes a pair of recesses, and wherein the rear wheels are removable from the rear legs and stow-able in the pair of recesses when in the first transport condition.

14. A system to transport infant children, comprising: a base configured to be secured to a portion of an automobile; a chassis independent from the base, wherein the chassis comprises a frame, a pair of rear legs pivotally coupled to the frame and a pair of front legs, each front leg pivotally coupled to a respective rear leg, wherein each of the front legs and each of the rear legs have a wheel at a respective distal end, wherein the rear legs and the front legs are retracted and proximate the frame in a first transport condition, and wherein the rear legs and the front legs are deployable away from the frame to a second transport condition when the chassis and infant car seat are released from the base; a first release mechanism releasably coupling the chassis to the base; an infant car seat independent from the base and the chassis; a second release mechanism releasably coupling the infant car seat to the chassis; wherein the chassis and the infant car seat are releasable

from the base as a combined unit upon operation of the first release mechanism; wherein the infant car seat is releasable from the combined unit of the base and chassis upon operation of the second release mechanism, and wherein the frame of the chassis includes a pair of recesses, and wherein the rear wheels are removable from the rear legs and stow-able in the pair of recesses.

15. The system of claim 14, wherein the chassis comprises a first handle coupled to the first release mechanism and configured to move the first release mechanism to selectively release the chassis and infant car seat as a unit from the base.

16. The system of claim 15, wherein the infant car seat comprises a second handle coupled to the second release mechanism and configured to move the second release mechanism to selectively release the infant car seat from the chassis and the base.

17. The system of claim 16, wherein the first release mechanism and the second release mechanism are spring-loaded to a closed configuration.
