

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397864
Kind Code	B1
Date of Patent	August 26, 2025
Inventor(s)	Hall; Nicholas Ryan

Convertible trailer

Abstract

A trailer convertible between step deck trailer and flatbed trailer configurations includes a frame, wheel and axle assemblies supported on the frame, an upper deck at the front of the frame, a lower deck configured for vertical movement on a vertical slide rail from a first step deck position to a second raised flatbed position wherein the lower deck and the upper deck are coplanar; a controller actuatable for upward and downward movement of the lower deck; at least one locking support beam; and landing gear deployable to support the convertible trailer while it is parked for loading. An air lift jack assembly is configured to raise the lower deck, and an air pressure release valve is configured to release air pressure to lower the lower deck, in response to actuation of the controller. The wheel and axle assemblies may be configured for forward-backward movement and/or upward-downward movement.

Inventors:	Hall; Nicholas Ryan (Runaway Bay, TX)
Applicant:	Hall; Nicholas Ryan (Runaway Bay, TX)
Family ID:	1000008367159
Appl. No.:	18/999518
Filed:	December 23, 2024

Publication Classification

Int. Cl.: **B62D33/02** (20060101); **B60P1/02** (20060101); **B60P3/08** (20060101); **B62D33/10** (20060101); **B62D53/06** (20060101); **B62D63/06** (20060101)

U.S. Cl.:

CPC **B62D33/10** (20130101); **B60P1/02** (20130101); **B60P3/08** (20130101); **B62D33/02** (20130101); **B62D53/062** (20130101); **B62D63/068** (20130101);

Field of Classification Search

CPC: B62D (33/02); B62D (33/08); B62D (33/10); B62D (53/06); B62D (53/061); B62D (53/062); B62D (63/06); B62D (63/068); B60P (1/02); B60P (1/025); B60P (3/06); B60P (3/08)

USPC: 280/6.151; 280/6.15; 280/30; 280/43.23; 280/415.1; 280/789; 280/423.1; 280/418; 280/418.1; 280/475; 296/25; 296/182.1; 296/184.1; 414/495; 410/26; 410/27; 410/28; 410/28.1; 410/29.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2687225	12/1953	Martin	280/491.1	B60P 3/07
2904340	12/1958	Simpson	280/789	B60P 7/12
4290642	12/1980	Wise	280/43.11	B62D 53/062
4806065	12/1988	Holt	280/425.2	B62D 53/065
5246241	12/1992	Baver	280/789	B60P 1/6481
6343825	12/2001	Gee	280/789	B62D 53/062
6497541	12/2001	Pawluk	410/27	B60P 3/08
9199568	12/2014	Dibdin	N/A	B60P 1/02
11752914	12/2022	Biagi	414/495	B60P 1/6418
2008/0001130	12/2007	Dibdin	414/495	B66F 7/085
2010/0289248	12/2009	Cesternino	280/425.2	B62D 53/062
2018/0057081	12/2017	O'Marra	N/A	B62D 53/067
2020/0180491	12/2019	Das	N/A	B62D 63/08
2021/0261031	12/2020	Bell	N/A	B60P 1/025

Primary Examiner: Frisby; Keith J

Attorney, Agent or Firm: Plager Schack LLP

Background/Summary

FIELD AND BACKGROUND OF THE INVENTION

(1) The embodiments herein relate generally to step deck trailers, and more particularly to a step deck trailer configured to function as a flatbed trailer.

(2) Step deck trailers and flatbed trailers are used to haul different types of loads. Step deck trailers may be used to haul loads that flatbed trailers are not able to haul, and vice versa. This may cause transportation problems when picking up various types of loads as commercial hauling companies would need two different trailers for commercial hauling to accommodate different types of loads.

(3) Companies having only one type of trailer may be turned away from opportunities to haul loads the trailer is not designed to haul. When a company and a driver are turned away, it results in wasted fuel, more downtime, more money spent, and potential delivery delay.

(4) Having two types of trailers does not offer an adequate solution, as maintaining two types of trailers increases costs. Extra round trips to bring an alternative trailer may still be required and may impact loading and delivery, which can be problematic for time-sensitive schedules. Delaying a time-sensitive scheduled loading and delivery may cost time and money and may impact safety of

the transport.

(5) Therefore, what is needed is a solution to one or more of these problems affecting both providers and receivers of hauling services.

SUMMARY OF THE INVENTION

(6) A trailer convertible between a step deck trailer and flatbed trailer includes a trailer frame, wheel and axle assemblies supported on the trailer frame, an upper deck at the front of the trailer frame, a lower deck configured for vertical movement on a vertical slide rail from a first step deck position to a second raised flatbed position, wherein the lower deck and the upper deck are coplanar; a controller actuatable for upward and downward movement of the lower deck; at least one locking support beam; and landing gear deployable to support the convertible trailer while it is parked for loading. An air lift jack assembly is configured to raise the lower deck, and an air pressure release valve is configured to release air pressure to lower the lower deck, in response to actuation of the controller. The wheel and axle assemblies may be configured for forward-backward movement and/or upward-downward movement for storage. A dovetail loading ramp may be reversibly deployed for use by outwardly pivoting a first dovetail ramp portion. A flip-top deck extension may be reversibly deployed to extend the lower deck by outwardly pivoting a flip-top deck top portion to a deployed position level with the lower deck.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) The detailed description of some embodiments of the invention is made below with reference to the accompanying figures, wherein like numerals represent corresponding parts of the figures.

(2) FIG. 1 is a schematic right side view of the invention configured for use as a step deck trailer, wherein the left side is a substantially identical mirror image of the right side;

(3) FIG. 2 is a schematic side view of the invention configured for use as a flat deck trailer, wherein the left side is a substantially identical mirror image of the right side;

(4) FIG. 3 is a schematic side view of the invention having three wheel and axle assemblies, wherein the left side is a substantially identical mirror image of the right side; and

(5) FIG. 4 is a schematic side view of the invention having four wheel and axle assemblies, wherein the left side is a substantially identical mirror image of the right side.

DETAILED DESCRIPTION OF CERTAIN EMBODIMENTS

(6) In the following detailed description of the invention, numerous details, examples, and embodiments of the invention are described. However, it will be clear and apparent to one skilled in the art that the invention is not limited to the embodiments set forth and that the invention can be adapted for any of several applications.

(7) Some embodiments of the present disclosure include a step deck trailer configured to function as a flatbed trailer, and may comprise the following elements related in the following exemplary fashion. This list of possible constituent elements and their interrelation described herein are intended to be exemplary only, and are not intended to be used to limit the trailer apparatus of the present application to just these elements or to limit the scope or nature of the relationships between the various elements. Persons having ordinary skill in the art relevant to the present disclosure may understand there to be equivalent elements that may be substituted within the present disclosure without changing the essential function or operation of the apparatus. The following examples are presented as illustrative examples only.

(8) Referring initially to FIGS. 1-2, a convertible trailer **100** is constructed and arranged for conversion from a step deck trailer configuration as shown at FIG. 1, to a flatbed trailer configuration as shown at FIG. 2. The convertible trailer **100** has a trailer front, a trailer rear, a trailer right side, a trailer left side, a trailer top, and a trailer bottom. The convertible trailer **100**

comprises a trailer frame **10** having a frame front, a frame rear, a frame right side, a frame left side, a frame top, and a frame bottom.

(9) A plurality of wheel and axle assemblies **12** are supported on the trailer frame **10**. Each wheel and axle assembly **12** of the plurality of wheel and axle assemblies **12** comprises a pair of wheels rotatably mounted on an axle. At least one wheel and axle assembly **12** of the plurality of wheel and axle assemblies **12** may comprise an air lift wheel and axle assembly **12A** having a pair of air lift wheels rotatably mounted on an air lift axle configured to raise the pair of air lift wheels from a lowered wheel position permitting the pair of air lift wheels to contact a ground or paved surface to a raised wheel position. At least one wheel and axle assembly **12** of the plurality of wheel and axle assemblies **12** may further comprise an advancing axle assembly **12B** having an advancing axle configured for selective forward and backward movement of the pair of wheels rotatably mounted on the advancing axle between a rearward wheel position and a forward wheel position. With reference to FIGS. **3** and **4**, the plurality of wheel and axle assemblies **12** may comprise any number of wheel and axle assemblies, such as three or four wheel and axle assemblies. Referring again to FIGS. **1** and **2**, an upper deck **16** is located at the frame front of the trailer frame **10**. A lower deck **18** is located rearward of the upper deck **16** and is constructed and arranged for vertical movement on a vertical slide rail **24** from a first step deck position to a second raised flatbed position wherein the lower deck **18** and the upper deck **16** are coplanar. A controller **20** is operably connected to the lower deck **18** and configured for actuation to move the lower deck **18** upward and downward on the vertical slide rail **24** with respect to the upper deck **16** to provide a flatbed trailer configuration. The controller **20** may be operably connected to a stationary air lift remote control with stationary built in cables. An air lift jack assembly **28** is operably connected to the controller **20**, the lower deck **18**, and the vertical slide rail **24** and is configured to raise the lower deck **18** to the level of the upper deck **16** in response to actuation of the controller **20**. The air lift jack assembly may include at least one pair of air lift jacks, such as a right front air lift jack and a left front air lift jack **28A**, a right intermediate air lift jack **28B** and a left intermediate air lift jack **28B**, and a right rear air lift jack **28C** and a left rear air lift jack. The air lift jack assembly **28** may further comprise air cylinders, pistons, rods, barrels, and seals, and may be operably connected to sealed high-pressure fittings and hose connections necessary for operation of the air lift jack assembly **28**. An air pressure release valve **22**, such as an emergency relief valve, is operably connected to the controller **20**, the lower deck **18**, the vertical slide rail **24**, and the air lift jack assembly **28** and is configured to release air pressure in response to actuation by the controller **20** to lower the lower deck **18**. The convertible trailer may include spring-action steel teeth hooks configured to support the weight of the lower deck **18** so the air lift jack **28** is not in use at all times under a load. While the lower deck **18** is being raised, the spring action steel teeth hooks operate and engage to support the lower deck **18** at each point of its ascent. Once the lower deck **18** has completed its ascent to a desired intermediate position or has raised completely to have a lower deck upper surface coplanar with an upper deck upper surface, the spring action steel teeth hooks will stay in a last open position, allowing an operator to push a control button on the controller **20** or an operably connected remote control to a down position to permit the lower deck **18** to rest on the spring action steel teeth hooks. When lowering the lower deck **18**, the operator may raise the lower deck **18** to the fully raised position (i.e., to the flatbed configuration of the convertible trailer **100**), turn the spring action steel teeth hooks to a position enabling the lower deck **18** to be lowered, depress a down button on the controller **20** or an operably connected remote control to lower the lower deck **18**, or disengage the air pressure release valve **22** to lower the lower deck **18**. After the lower deck **18** is lowered, the air pressure release valve **22** is closed to ensure no debris may enter it.

(10) At least one pair of self-extending locking support beams **26**, such as a right front locking support beam **26A** and a left front locking support beam **26A**, a right intermediate locking support beam **26B** and a left intermediate locking support beam **26B**, and a right rear locking support beam and a left rear locking support beam, extend when the lower deck **18** is raised to the flatbed

configuration. Each front, intermediate and rear locking support beam **26A,26B,26C** may be proximal to a front, intermediate and rear air lift jack **28A,28B,28C**, and are configured to reversibly lock in place when fully extended to support the lower deck **18** in the flatbed configuration, and to automatically retract as the lower deck **18** is lowered to the step deck configuration. Landing gear **14** includes a right landing gear **14** mounted to an underside of the upper deck **16** at the trailer right side and a left landing gear **14** mounted to an underside of the upper deck **16** at the trailer left side, the right landing gear **14** and the left landing gear **14** being deployable from a raised storage position to a deployed position contacting a ground or paved surface to support the convertible trailer **100** while it is parked for loading. At least one tool drawer **34** may be located at the frame right side and/or the frame left side. A dovetail ramp **30** located at the frame rear has a first dovetail ramp portion pivotally mounted to a second dovetail ramp portion, the second dovetail ramp portion being mounted to or integral with the frame rear. The dovetail ramp **30** is constructed and arranged to outwardly pivot the first dovetail ramp portion to deploy the dovetail ramp **30** from the frame rear for use in loading the convertible trailer **100**. A flip-top deck extension **32** has a flip-top deck top portion pivotally mounted to a flip-top deck bottom portion, wherein the flip-top deck top portion is configured to rest on the flip-top deck bottom portion when the flip-top deck extension **32** is not in use, and the flip-top deck top portion is level and coplanar with the lower deck **18** when deployed for use of the flip-top deck extension **32** to extend the usable length of the lower deck **18**. When the lower deck **18** is in the first step deck position, the deployed flip-top deck top portion may rest on the undeployed dovetail ramp **30**. Additional components of the convertible trailer **100** may include pins, rollers, and bushings permitting proper operation without unnecessary wear and tear; spring pins which return to an original set point; grease fittings permitting proper maintenance of a particular moving part; electrical lines and hoses providing a proper amount of electricity and a correct amount of air flow; over and under travel stops ensuring the convertible trailer **100** stops at a designated stopping place without damage; double inner and outer steel square slide components providing vertical and horizontal structural support of moving components; front slide catchers necessary for the complete structure of the moving convertible trailer **100** to maintain an ability to stay stationary in relation to another structure frame in front of the convertible trailer **100**, such as a vehicle towing the convertible trailer **100**; and an emergency stop button providing an operator a mechanism to stop all operation of the convertible trailer **100** in case of a mechanical or electrical malfunction.

(11) The convertible trailer **100** and its components may be made of any suitable materials, and fabricated by any suitable process. A commercially available step deck trailer on a rolling chassis may be customized to provide the convertible trailer **100**. The convertible trailer **100** and components may be made of welded steel or aluminum, and may have an inner support made of wood, aluminum, or steel. The convertible trailer **100** may have any size and dimensions, such as an overall length of 47 to 53 feet; an overall width of up to 102 inches, an upper deck length of 11 feet and height of 5 feet, and a lower deck length of 37 to 41 feet and height of 36 to 42 inches. In some embodiments, the convertible trailer **100** may have an overall length of 47 feet 10 inches, an overall width of 102 inches, an upper deck length of 10 feet and height of 49 inches, and a lower deck length of 37 feet 10 inches and height of 41 inches, wherein the height of a vertical section adjoining the planar horizontal upper deck and the planar horizontal lower deck (a slide rail for lower deck **18**) may have a length of 20 inches. The weight range of the lower deck **18** may be between 7500 and 11000 pounds (between 7500 and 8000 for an aluminum deck, a middle weight range for a wood deck, and between 9500 and 11000 pounds for a steel deck).

(12) Persons of ordinary skill in the art may appreciate that numerous design configurations may be possible to enjoy the functional benefits of the inventive systems. Thus, given the wide variety of configurations and arrangements of embodiments of the present invention, the scope of the invention is reflected by the breadth of the claims below rather than narrowed by the embodiments described above.

Claims

1. A convertible trailer constructed and arranged for conversion from a step deck trailer configuration to a flatbed trailer configuration, the convertible trailer having a trailer front, a trailer rear, a trailer right side, a trailer left side, a trailer top, and a trailer bottom, the convertible trailer comprising: a trailer frame having a frame front, a frame rear, a frame right side, a frame left side, a frame top, and a frame bottom; a plurality of wheel and axle assemblies supported on the trailer frame, wherein each wheel and axle assembly of the plurality of wheel and axle assemblies comprises a pair of wheels rotatably mounted on a respective axle; an upper deck located at the frame front of the trailer frame; a lower deck located rearward of the upper deck, the lower deck being constructed and arranged for vertical movement on a vertical slide rail from a first step deck position to a second raised flatbed position wherein the lower deck and the upper deck are coplanar; a controller operably connected to the lower deck, the controller being configured for actuation to move the lower deck upward and downward on the vertical slide rail with respect to the upper deck; at least one locking support beam extending from the frame right side to the frame left side; and a right landing gear mounted to an underside of the upper deck at the trailer right side and a left landing gear mounted to an underside of the upper deck at the trailer left side, the right landing gear and the left landing gear being deployable from a raised storage position to a deployed position contacting a ground or paved surface to support the convertible trailer while it is parked for loading.
2. The convertible trailer of claim 1, further comprising an air lift jack assembly operably connected to the controller, the lower deck, and the vertical slide rail, the air lift jack assembly being configured to raise the lower deck in response to actuation of the controller.
3. The convertible trailer of claim 2, further comprising an air pressure release valve operably connected to the controller, the lower deck, the vertical slide rail, and the air lift jack assembly, the air pressure release valve being configured to release air pressure in response to actuation by the controller to lower the lower deck.
4. The convertible trailer of claim 1, wherein at least one wheel and axle assembly of the plurality of wheel and axle assemblies further comprises an air lift wheel and axle assembly having a pair of air lift wheels rotatably mounted on an air lift axle configured to raise the pair of air lift wheels from a lowered wheel position permitting the pair of air lift wheels to contact a ground or paved surface to a raised wheel position.
5. The convertible trailer of claim 1, wherein at least one wheel and axle assembly of the plurality of wheel and axle assemblies further comprises an advancing axle assembly having an advancing axle configured for selective forward and backward movement of the pair of wheels rotatably mounted on the advancing axle between a rearward wheel position and a forward wheel position.
6. The convertible trailer of claim 1, wherein the plurality of wheel and axle assemblies comprises three wheel and axle assemblies.
7. The convertible trailer of claim 1, wherein the plurality of wheel and axle assemblies comprises four wheel and axle assemblies.
8. The convertible trailer of claim 1, wherein the at least one locking support beam comprises a plurality of locking support beams.
9. The convertible trailer of claim 8, wherein the plurality of locking support beams further comprises a right front locking support beam, a left front locking support beam, a right intermediate locking support beam, a left intermediate locking support beam, a right rear locking support beam, and a left rear locking support beam.
10. The convertible trailer of claim 1, further comprising at least one tool drawer located at the frame right side.
11. The convertible trailer of claim 1, further comprising at least one tool drawer located at the

frame left side.

12. The convertible trailer of claim 1, further comprising a dovetail ramp located at the frame rear, the dovetail ramp comprising a first dovetail ramp portion pivotally mounted to a second dovetail ramp portion, the dovetail ramp being constructed and arranged to outwardly pivot the first dovetail ramp portion to deploy the dovetail ramp from the frame rear for use of the dovetail ramp for loading the convertible trailer.

13. The convertible trailer of claim 1, further comprising: a flip-top deck extension comprising a flip-top deck top portion pivotally mounted to a flip-top deck bottom portion; wherein the flip-top deck top portion is configured to rest on the flip-top deck bottom portion when the flip-top deck extension is not in use; wherein the flip-top deck top portion is level and coplanar with the lower deck when deployed to extend the lower deck; and wherein when the lower deck is in the first step deck position, the dovetail ramp is undeployed, and the flip-top deck extension is deployed, the flip-top deck top portion is adjacent to and rests on the undeployed dovetail ramp.
