

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397868
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Tavares Miranda; Joao Filipe

Crank set with chain guard ring and fastening element

Abstract

A crank set for a two-wheeler, the crank set comprising a crank with a crank spider, a chainring and a chain guard ring, the chainring being fastened to the crank spider by fastening elements, and the fastening elements pressing the chainring and the crank spider against one another along a pressing direction. A clamped area of the chain guard ring is clamped in a clamping zone between at least one of the fasteners by which the chainring is secured to the crank spider and the crank spider or chainring and thereby secured to the crank set.

Inventors:	Tavares Miranda; Joao Filipe (Agueda, PT)
Applicant:	MIRANDA & IRMAO, LDA (Agueda, PT)
Family ID:	1000008777913
Assignee:	MIRANDA & IRMAO, LDA (Agueda, PT)
Appl. No.:	17/289929
Filed (or PCT Filed):	October 21, 2019
PCT No.:	PCT/EP2019/078595
PCT Pub. No.:	WO2020/088975
PCT Pub. Date:	May 07, 2020

Prior Publication Data

Document Identifier	Publication Date
US 20220001950 A1	Jan. 06, 2022

Foreign Application Priority Data

EP	18203214	Oct. 29, 2018
----	----------	---------------

Publication Classification

Int. Cl.: B62J13/00 (20060101); B62M1/36 (20130101); B62M3/00 (20060101)

U.S. Cl.:

CPC B62J13/00 (20130101); B62M1/36 (20130101); B62M3/00 (20130101);

Field of Classification Search

CPC: B62J (13/00); B62M (1/36); B62M (3/00); F16H (7/18); F16H (7/06); F16H (48/22); F16H (48/285)

USPC: 474/144; 184/6.12

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4475894	12/1983	Sugino	474/144	B62M 9/105
4573950	12/1985	Nagano	474/144	B62M 9/136
5003840	12/1990	Hinschlager	74/609	B62J 23/00
5232416	12/1992	Amborn	475/248	F16H 48/285
6213238	12/2000	Buell	180/219	B62M 7/00
6354973	12/2001	Barnett	474/140	B62J 13/00
6533690	12/2002	Barnett	474/140	B62M 9/138
8162791	12/2011	Cronin	475/249	F16H 48/22
8888629	12/2013	Ji	474/144	B62M 9/128
2002/0160869	12/2001	Barnett	474/144	B62M 9/138
2005/0284252	12/2004	Fukui	74/594.2	B62M 3/003
2006/0058139	12/2005	Fry	474/144	B62J 13/00
2007/0054771	12/2006	Fusegi	475/231	F16H 48/30
2008/0058151	12/2007	Curtis	475/232	F16H 48/08
2008/0161145	12/2007	Shiraishi	474/145	B62J 13/00
2010/0144484	12/2009	Bawks	475/226	F16H 48/11
2013/0161970	12/2012	Takasu	296/29	B62J 17/00
2015/0353155	12/2014	Ribeiro Miranda	474/144	B62J 13/00
2017/0328460	12/2016	Schulte	N/A	F16D 23/12

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
201437388	12/2009	CN	N/A
202379011	12/2011	CN	N/A
202013103872	12/2012	DE	N/A

OTHER PUBLICATIONS

Office Action dated Dec. 26, 2022, issued by the Taiwanese Patent Office for the corresponding Taiwanese Patent Application No. 108136655, with English translation (11 pages). cited by applicant

International Search Report and Written Opinion for corresponding International Application No.

Primary Examiner: Momper; Anna M

Assistant Examiner: Campos, Jr.; Juan J

Attorney, Agent or Firm: LUCAS & MERCANTI, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) This Application is a 371 of PCT/EP2019/078595 filed on Oct. 21, 2019, which in turn claims the benefit of European Application No. 18203214.4 filed on Oct. 29, 2018, both applications are incorporated herein by reference.

DESCRIPTION

(2) The invention relates to a crank set as well as a fixing element for a crank set.

(3) Crank sets of the type in question are used for two-wheeled vehicles. Two-wheeled vehicles are understood in particular to be conventional bicycles, but also e-bikes, pedelecs and the like.

(4) Two-wheelers of the type in question regularly have crank sets with which the two-wheeler can be driven. The crank sets of the type in question include at least one chainring attached to a crank spider. In this context, a crank spider in particular means the area of the crank that provides a plurality of attachment points for the chainring. The chainring is often fastened to the crank spider with fastening elements which press the chainring and the crank spider together along a pressing direction. This creates a reliable and rigid connection between chainring and the crank spider.

(5) According to the state of the art, a crank set can also have a chain guard ring. A chain guard ring is a ring-shaped element which is attached to the side of the crank set and extends laterally next to the chainring, especially in the area of the chainring teeth. The chain guard ring in particular serves to prevent the clothing of the rider of the two-wheeler from coming into contact with the teeth of the chainring and/or chain.

(6) According to the state of the art, further fastening elements are usually required for fastening the chain guard ring. On the one hand, this increases the effort involved in assembling the crank set, and on the other, the number of parts required and thus also the weight and costs of the crank set are increased.

(7) The invention therefore aims to providing a crankset for a two-wheeler and a fastening element for such a crankset, which allow simpler assembly and a simpler structure of the crankset, in particular from fewer individual parts.

(8) The problem is solved by a crank set and a fastening element with the following features: having a crank with a crank spider (12), a chainring (14) and a chain guard ring (22), the chainring (14) being fastened to the crank spider (12) by fastening elements, the fastening elements are pressing the chainring (14) and the crank spider (12) against each other along a pressing direction (20), characterised in that a clamped area (30) of the chain guard ring (22) is clamped in a clamping zone between at least one of the fastening elements with which the chainring (14) is fastened to the crank spider (12) and the crank spider (12) or the chainring (14) and is thereby fastened to the crank set (10). The features of the dependent claims relate to preferred embodiments.

(9) The crank set as shown and described has a chain guard ring which is attached to the crank set, in particular to the crank spider, by a clamped area of the chain ring being clamped in a clamping

zone between the fastening element and the crank spider or chainring. The fastener is at least one of the fasteners used to attach the chainring to the crank spider.

(10) In this way, it is possible to use the fixing elements required anyway to fix the chainring to the crank spider in order to also fix the chainring to the crank set.

(11) The fastening elements can each have a screw-in element and a screw-on element. The screw-in element and the screw-on element can be screwed together to press the chainring onto the crank spider. Fastening elements designed in this way enable simple and secure fastening of the chainring to the crank spider by inserting the screw-in element and screw-on element from different directions into openings in the chainring and crank spider and then screwing them together.

(12) The screw-on element and/or the screw-in element can have a pressing surface. The pressing surface serves to introduce the pressing force required for pressing the crank spider and chainring together into the chainring and/or crank spider.

(13) The pressing surface can be ring-shaped. A ring-shaped design is particularly advantageous with regard to the uniform distribution of the contact force around the opening through which the screw-on element and/or the screw-in element is introduced into the chainring and/or the crank spider. In addition, a ring-shaped design of the contact surface can often be easily achieved in the production of the fastening element, which is usually, at least essentially, rotationally symmetrical.

(14) The screw-in element and/or the screw-on element can also have a clamping surface which limits the clamping zone on the side facing away from the chainring and/or the crank spider. The clamping surface serves in particular to introduce the clamping force which acts on the chain guard ring when the clamped area of the chain guard ring is clamped in. The clamping surface can be ring-shaped. The clamping zone can also be ring-shaped. Such a design is particularly advantageous if the contact surface is arranged by an annular shoulder of the screw-in element and/or the screw-on element. In this case, the clamping zone may surround the annular shoulder. This provides a comparatively large clamping zone for clamping the area of the chain guard ring with a compact and simply designed fastening element. In addition, the design of the fastening element ensures a largely uniform application of force when the area is clamped.

(15) The clamped area can be deformed by screwing the fastening element in the direction parallel to the pressing direction. In particular, this can be made possible by the fact that the clamped area of the chain guard ring is thicker in the undeformed and unassembled state than the extension of the clamping zone in the pressing direction in the assembled state.

(16) In this context, it is particularly advantageous if the material of the chain guard ring is more easily deformable than the material of the chainring and the material of the crank spider. Then, the screw-in element and the screw-on element can be screwed together as tightly as necessary to create the necessary contact force between the chainring and the crank spider. The clamped area of the chain guard ring is deformed until the end position of the screw-in element and screw-on element is reached. In this way, when the chainring is attached to the crank spider, the chain guard ring is also attached to the crank set. The deformation of the chain guard ring is advantageous in that there is no double fit along the pressing direction which could influence the sufficient pressing of the chainring against the crank spider. There are also no increased demands on tolerances, especially with regard to the thickness of the components to be screwed together, since any excess dimension of the chain guard ring in the pressing direction is compensated by the deformation of the clamped area and the clamped area of the chain guard ring does not hinder the generation of the pressing force for pressing the chainring and crank spider against each other. The material of the chain guard ring can be a plastic material.

(17) Advantageously, the screw-on element can have a circular cylindrical surface pointing outwards in the area of the screw connection. This extends in the pressing direction in an advantageous way both over at least part of the chainring and over part of the crank spider. In this way, the screw-on element also ensures that the elements involved in the screw connection, in

particular the chainring and the crank spider, are correctly aligned when the contact force is applied by screwing them together.

Description

- (1) Further practical forms of implementation and advantages of the invention are described below in connection with the drawings. It is shown:
- (2) FIG. 1 a sectional view of a part of a crank set in the area of the connection between chainring and crank spider,
- (3) FIG. 2 a view of the chain guard ring of the crank set from FIG. 1,
- (4) FIG. 3 a sectional view of the chain guard ring from FIG. 2 along the section line A-A,
- (5) FIG. 4 an enlargement of area B in FIG. 3,
- (6) FIG. 5 a view of the screw-in element from FIG. 1
- (7) The crank set **10** shown as an example has a crank with a crank spider **12**. A chainring **14** is attached to the crank spider **12**. The chainring **14** can be fastened with a fastening element comprising a screw-in element **16** and a screw-on element **18**. The screw-in element **16** and the screw-on element **18** can be screwed together as shown in the example. As shown as an example, this screw connection can generate a pressing force which presses the chainring **14** and the crank spider **12** together along the pressing direction **20**.
- (8) The crank set **10** shown as an example also has a chain guard ring **22**. The chain guard ring **22** is also attached to the crank set **10** by the fastening element with which the chainring **14** is fastened to the crank spider **12**. For this purpose, the fastening element may have a ring-shaped shoulder **24** as shown in the example. As shown in the example, a pressing surface **26** can be provided on this annular shoulder **24**, which—as shown in the example—introduces the pressing force along the pressing direction **20** into the crank spider **12**. A clamping surface **28**, also ring-shaped and pointing in the same direction as the pressing surface **26**, surrounds the annular shoulder **24** in the example shown.
- (9) Between the clamping surface **28** and the chainring **12**, a ring-shaped clamping zone also forms in the example shown, which surrounds the annular shoulder **24**. Within this clamping zone, there is a clamped area **30** of the chain guard ring **22**. This area **30**, which is located within the clamping zone, is also ring-shaped. The area **30** is deformed, i.e. compressed along the pressing direction **20**. The compression path **32** by which the area **30** is compressed along the contact pressure direction **20** is at least 0.05 mm, preferably at least 0.15 mm, and/or at most 1 mm, especially at most 0.2 mm.
- (10) Correspondingly, the material thickness **34** of the area **30** before attaching the chain guard ring **22** to the crank set **10** can be at least 1 mm, preferably at least 1.15 mm, and/or at most 1.4 mm, preferably at most 1.2 mm.
- (11) The extension **36** of the clamping zone along the pressing direction **20** can be at least 0.8 mm, preferably at least 1 mm, and/or at most 1.2 mm, preferably at most 1.15 mm.
- (12) As can be seen in FIGS. 2 to 4, the material thickness **34** of the area **30** may be less than the material thickness of the surrounding areas of the chain guard ring **22**. The difference **38** of the material thicknesses may be at least 0.05 mm, preferably at least 0.15 mm, and/or at most 1 mm, preferably at most 0.2 mm.
- (13) As shown in FIG. 5, the distance between the clamping surface **28** and the pressing surface **26** may correspond to the extension **36**.
- (14) FIG. 5 shows an example of a screw-in element **16**, but in the view shown in FIG. 5 the thread of the screw-in element **16** is not shown. The diameter **40** of the annular shoulder **24** can be at least 10.2 mm, preferably at least 11.5 mm and/or at most 15 mm, preferably at most 12.5 mm.
- (15) The outer diameter **42** of the clamping surface **28** can be at least 11.7 mm, preferably at least

13 mm and/or at most 16.5 mm, preferably at most 15 mm.

(16) The features of the invention disclosed in the present description, in the drawings and in the claims may be essential both individually and in any combination for the realisation of the invention in its various forms. The invention is not limited to the described embodiments. It may be varied within the limits of the requirements and taking into account the knowledge of the competent person.

REFERENCE LIST

(17) **10** crank set **12** crank spider **14** chain ring **16** screw-in element **18** screw-on element **20** pressing direction **22** chain guard ring **24** annular shoulder **26** pressing surface **28** clamping surface **30** area **32** compression path **34** material thickness **36** extension **38** material thickness difference **40** diameter **42** diameter

Claims

1. A crank set for a two-wheeler, the crank set comprising a crank with a crank spider, a chainring and a chain guard ring, the chainring being fastened to the crank spider by fastening elements, the fastening elements are pressing the chainring and the crank spider against each other along a pressing direction, wherein a clamped area of the chain guard ring is clamped in a ring-shaped clamping zone between at least one of the fastening elements with which the chainring is fastened to the crank spider and the crank spider or the chainring and is thereby fastened to the crank set, wherein the at least one fastening element contacts the chain guard ring in the clamping zone, wherein the clamped area is deformed by the screwing of the at least one fastening element in a direction parallel to the pressing direction, wherein the fastening element has an annular shoulder, wherein a pressing surface is provided on the annular shoulder, wherein the fastening element has a ring-shaped clamping surface pointing in a same direction as the pressing surface, wherein the ring-shaped clamping surface delimits the ring-shaped clamping zone on a side remote from the chainring and/or the crank spider, wherein the clamping surface surrounds the annular shoulder, wherein the material of the clamping zone of the chain guard ring where the at least one fastening element contacts the chain guard ring is a plastic material that is more easily deformable than a second material of the chainring and a third material of the crank spider.
 2. The crank set according to claim 1, wherein the at least one fastening element has a screw-in element and a screw-on element, wherein the screw-in element and the screw-on element are screwed together for pressing the chainring onto the crank spider.
 3. The crank set according to claim 2, wherein the fastening screw-in element and/or the screw-on element has the pressing surface.
 4. The crank set according to claim 3, wherein the pressing surface is of ring-shaped design.
 5. The crank set according to claim 3, wherein the pressing surface is arranged on an annular shoulder of the screw-in element and/or of the screw-on element.
 6. The crank set according to claim 5, wherein the clamping zone surrounds the annular shoulder.
 7. The crank set according to claim 2, wherein the screw-on element has an outwardly pointing circular cylindrical surface in the region of the screw connection.
 8. The crank set according to claim 2, wherein the screw-in element and/or the screw-on element has the clamping surface which delimits the clamping zone on the side remote from the chainring and/or the crank spider.
 9. The crank set according to claim 1, wherein the clamped-in region clamped area is deformed by the screwing of the at least one fastening element in the direction parallel to the pressing direction.
-