

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12399052
B1
August 26, 2025
Shah; Darshan et al.

Fluid level monitoring

Abstract

Some aspects of the present disclosure involve an apparatus including: a sensor mounted on an electronic device submerged in a cooling fluid in an immersion tank. The sensor includes circuitry configured to: measure a value of a capacitance of the cooling fluid; and transmit the measured value of the capacitance to a controller device that is communicatively coupled to the at least one sensor. The controller device including one or more processors and configured to: receive the measured value of the capacitance from the at least one sensor; determine that the measured value of the capacitance is less than a threshold value; determine that a fluid level of the cooling fluid in the immersion tank is below a threshold level; and perform a remedial action in response to determining that the fluid level of the cooling fluid in the immersion tank is below the threshold level.

Inventors: Shah; Darshan (Milpitas, CA), Krishnamoorthy; Gobinath (Cupertino, CA)

Applicant: Auradine, Inc. (Santa Clara, CA)

Family ID: 1000008460166

Assignee: Auradine, Inc. (Santa Clara, CA)

Appl. No.: 19/033107

Filed: January 21, 2025

Publication Classification

Int. Cl.: G01F23/263 (20220101)

U.S. Cl.:

CPC G01F23/263 (20130101);

Field of Classification Search

CPC: H05K (7/203); H05K (7/20318); H05K (7/20327); H05K (7/20809); H05K (7/20272); H05K (7/20236); G01F (23/0076); G01F (23/263); G01F (23/268); G01N (27/228); G01N (29/2406); G01R (27/26)

USPC: 73/304C; 73/514.32; 73/718; 73/724; 73/335.04; 73/780; 73/862.337; 73/862.626

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2011/0317367	12/2010	Campbell et al.	N/A	N/A
2013/0091866	12/2012	Campbell et al.	N/A	N/A
2016/0003663	12/2015	Miatton	73/304C	G01F 23/266
2017/0135530	12/2016	Macleod	N/A	G01F 23/263
2017/0290198	12/2016	Shepard et al.	N/A	N/A
2018/0279507	12/2017	Midgley et al.	N/A	N/A
2020/0093037	12/2019	Enright et al.	N/A	N/A
2020/0323108	12/2019	Bilan et al.	N/A	N/A
2021/0018356	12/2020	Bean, Jr.	N/A	H05K 7/20809
2022/0418156	12/2021	Cushen	N/A	H05K 7/20236
2023/0156959	12/2022	Malouin	361/699	H05K 7/20781

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110231070	12/2018	CN	A24F 40/42
110347637	12/2018	CN	N/A
118119165	12/2023	CN	N/A

Primary Examiner: Breene; John E

Assistant Examiner: Phan; Truong D

Attorney, Agent or Firm: Fish & Richardson P.C.

Background/Summary

TECHNICAL FIELD

(1) The present disclosure generally relates to devices, systems, and methods to monitor a fluid level of an immersion cooling fluid in an immersion cooling tank.

BACKGROUND

(2) Immersion cooling fluid is a specialized dielectric substance used in an immersion cooling tank to submerge electronic components, such as high-performance integrated circuit chips, servers, and data center equipment, for efficient heat dissipation. A low fluid level of the immersion cooling fluid in an immersion cooling tank can lead to equipment overheating, corrosion, or even complete system failure.

SUMMARY

(3) One aspect of the present disclosure relates to an apparatus including: at least one sensor mounted on an electronic device submerged in a cooling fluid in an immersion tank, wherein the at

least one sensor includes circuitry configured to: measure a value of a capacitance of the cooling fluid; and transmit the measured value of the capacitance to a controller device that is communicatively coupled to the at least one sensor; and the controller device including one or more processors and configured to: receive the measured value of the capacitance from the at least one sensor; determine that the measured value of the capacitance is less than a threshold value; in response to determining that the measured value of the capacitance is less than the threshold value, determine that a fluid level of the cooling fluid in the immersion tank is below a threshold level; and perform at least one remedial action in response to determining that the fluid level of the cooling fluid in the immersion tank is below the threshold level.

(4) In some implementations, wherein the threshold value is a first threshold value of a plurality of threshold values, and wherein performing the remedial action includes transmitting, to a system operator, a notification of the fluid level in the immersion tank.

(5) In some implementations, wherein the threshold value is a second threshold value of the plurality of threshold values, the second threshold value corresponding to a fluid level in the immersion tank being lower than a fluid level corresponding to the first threshold value, and wherein performing the remedial action includes transmitting a first signal that causes the electronic device submerged in the cooling fluid in the immersion tank to enter a low power state.

(6) In some implementations, wherein the threshold value is a third threshold value of the plurality of threshold values, the third threshold value corresponding to a fluid level in the immersion tank being lower than a fluid level corresponding to the second threshold value, and wherein performing the remedial action includes transmitting a second signal that causes the electronic devices submerged in the cooling fluid in the immersion tank to shut down.

(7) In some implementations, wherein the cooling fluid includes a single-phase immersion cooling liquid or a two-phase immersion cooling liquid.

(8) In some implementations, wherein the at least one sensor includes: a capacitive sensor; and a capacitance-to-digital converter.

(9) In some implementations, the apparatus further including: a heat exchanger configured to dissipate heat generated by the electronic device using the cooling fluid; and a pump system configured to circulate the cooling fluid through the immersion tank and the heat exchanger.

(10) In some implementations, wherein the electronic device includes a printed circuit board (PCB) with a plurality of application-specific integrated circuit (ASIC) chips mounted thereon, and wherein the at least one sensor is mounted on the PCB adjacent to the plurality of ASIC chips.

(11) In some implementations, the at least one sensor includes a plurality of sensors mounted on the PCB, wherein the plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block including a plurality of columns and each column including a subset of the plurality of ASIC chips, and wherein a different sensor of the plurality of sensors is mounted adjacent to each block.

(12) In some implementations, wherein the electronic device includes a plurality of PCBs submerged in the cooling fluid in the immersion tank, each PCB including: a plurality of ASIC chips and a plurality of sensors, wherein the respective plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block including a plurality of columns and each column including a subset of the plurality of ASIC chips, and wherein a different sensor of the respective plurality of sensors is mounted adjacent to each block.

(13) Another aspect of the present disclosure relates to a method including: receiving a first measurement of a value of a capacitance of a cooling fluid from one or more sensors mounted on one or more electronic devices submerged in the cooling fluid of an immersion tank; determining, based at least on the first measurement, that the measured value of the capacitance is less than a first threshold value of a plurality of threshold values; and in response to determining that the measured value of the capacitance is less than the first threshold value, determining that a fluid level of the cooling fluid in the immersion tank is below a first threshold level corresponding to the first threshold value; transmitting, to a system operator, a notification of the fluid level in the

immersion tank in response to determining that the fluid level of the cooling fluid in the immersion tank is below the first threshold level.

(14) In some implementations, the method further including: receiving a second measurement of the value of the capacitance of the cooling fluid from the one or more sensors; determining, based at least on the second measurement, that the measured value of the capacitance is less than a second threshold value of the plurality of threshold values, wherein the second threshold value corresponds to a second threshold level in the immersion tank being lower than the first threshold level corresponding to the first threshold value; and in response to the determining, transmitting a first signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to enter a low power state.

(15) In some implementations, the method further including: receiving a third measurement of the value of the capacitance of the cooling fluid from the one or more sensors; determining, based at least on the third measurement, that the measured value of the capacitance is less than a third threshold value of the plurality of threshold values, wherein the third threshold value corresponds to a third threshold level in the immersion tank being lower than the second threshold level corresponding to the second threshold value; and in response to the determining, transmitting a second signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to shut down.

(16) In some implementations, wherein the cooling fluid includes a single-phase immersion cooling liquid or a two-phase immersion cooling liquid.

(17) In some implementations, wherein each electronic device includes a printed circuit board (PCB) with a plurality of application-specific integrated circuit (ASIC) chips mounted thereon, and wherein the one or more sensors are mounted on the PCB adjacent to the plurality of ASIC chips.

(18) In some implementations, the one or more sensors include a plurality of sensors mounted on the PCB, wherein the plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block including a plurality of columns and each column including a subset of the plurality of ASIC chips, and wherein a different sensor of the plurality of sensors is mounted adjacent to each block.

(19) In some implementations, wherein each electronic device includes a plurality of PCBs submerged in the cooling fluid in the immersion tank, each PCB including: a plurality of ASIC chips and a plurality of sensors, wherein the respective plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block including a plurality of columns and each column including a subset of the plurality of ASIC chips, and wherein a different sensor of the respective plurality of sensors is mounted adjacent to each block.

(20) Another aspect of the present disclosure relates to one or more non-transitory computer-readable media storing instructions that, when executed, cause one or more processors to perform operations including: receiving a first measurement of a value of a capacitance of a cooling fluid from one or more sensors mounted on one or more electronic devices submerged in the cooling fluid of an immersion tank; determining, based at least on the first measurement, that the measured value of the capacitance is less than a first threshold value of a plurality of threshold values; and in response to determining that the measured value of the capacitance is less than the first threshold value, determining that a fluid level of the cooling fluid in the immersion tank is below a first threshold level; transmitting, to a system operator, a notification of the fluid level in the immersion tank in response to determining that the fluid level of the cooling fluid in the immersion tank is below the first threshold level.

(21) In some implementations, the operations further including: receiving a second measurement of the value of the capacitance of the cooling fluid from the one or more sensors; determining, based at least on the second measurement, that the measured value of the capacitance is less than a second threshold value of the plurality of threshold values, wherein the second threshold value corresponds to a second threshold level in the immersion tank being lower than the first threshold level corresponding to the first threshold value; and in response to the determining, transmitting a first

signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to enter a low power state.

(22) In some implementations, the operations further including: receiving a third measurement of the value of the capacitance of the cooling fluid from the one or more sensors; determining, based at least on the third measurement, that the measured value of the capacitance is less than a third threshold value of the plurality of threshold values, wherein the third threshold value corresponds to a third threshold level in the immersion tank being lower than the second threshold level corresponding to the second threshold value; and in response to the determining, transmitting a second signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to shut down.

(23) Another aspect of the present disclosure relates to an apparatus that includes one or more processors and memory storing instructions that, when executed, cause the apparatus to perform any of the foregoing operations.

(24) Another aspect of the present disclosure relates to a non-transitory computer-readable medium storing instructions that, when executed, cause one or more processors to perform any of the foregoing operations.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1A is a schematic diagram of an example single-phase immersion cooling system, according to some implementations.

(2) FIG. 1B is a schematic diagram of an example dual-phase immersion cooling system, according to some implementations.

(3) FIG. 2 is a schematic diagram of an example electronic device immersed in dielectric cooling fluid, according to some implementations.

(4) FIG. 3 is a schematic diagram of an example electronic device immersed in dielectric cooling fluid, according to some implementations.

(5) FIG. 4 is a schematic diagram of an example fluid level sensor, according to some implementations.

(6) FIG. 5 is a schematic diagram of an example immersion cooling system, according to some implementations.

(7) FIG. 6 illustrates a flowchart of an example method for monitoring a fluid level of a cooling fluid in an immersion cooling tank, according to some implementations.

(8) FIG. 7 is a schematic diagram of an example computer system.

DETAILED DESCRIPTION

(9) An immersion cooling tank is a type of cooling apparatus that holds a thermally conductive but electrically non-conductive cooling fluid in which high-performance electronic devices, such as integrated circuit (IC) chips for hash computations, servers, or computer processors, are submerged directly. Immersion cooling is used to efficiently remove heat from high-performance electronic devices, which allows for higher energy efficiency, reduced noise, and improved performance due to lower operating temperatures, e.g., performing high-rate operations without thermal breakdown. In some cases, the cooling fluid is a specialized dielectric substance (e.g., a single-phase or two-phase dielectric liquid) used in the immersion cooling tank to submerge electronic devices for efficient heat dissipation. By fully immersing these devices in the cooling fluid, heat is directly transferred from the electronics to the fluid, which is then circulated to remove the heat, providing more effective cooling (in comparison to conventional air-based cooling methods). In some cases, however, the fluid level of the immersion cooling fluid may be low, e.g., due to a leak of the immersion cooling tank or fluid evaporation, which can potentially lead to equipment overheating,

corrosion, or system failure due to thermal breakdown.

(10) In accordance with aspects of the present disclosure, an immersion cooling system includes one or more fluid level sensors that are present in an immersion cooling tank. A fluid level sensor is configured to monitor a fluid level of cooling fluid in the immersion cooling tank. The immersion cooling system further includes a controller that is configured to perform one or more remedial actions if the fluid level of cooling fluid is detected to be below a predetermined threshold level based on measurements by the one or more sensors. In some implementations, each fluid level sensor includes a capacitive sensor and a capacitance-to-digital converter, and is mounted on an electronic device. For example, as described in the following sections, one such electronic device can be a printed circuit boards (PCB), with a plurality of IC chips configured to perform hash computations (e.g., for cryptocurrency tasks). One or more such PCBs can be immersed in the cooling fluid in an immersion cooling tank. Each PCB can have one or more fluid level sensors to monitor the level of fluid in which the PCB is immersed in the tank. The measurements by the fluid level sensors are transmitted to the controller. The controller may include a control board with one or more processors and memory storing instructions that are executed by the processors to perform remedial actions (e.g., shutting off power to the electronic devices immersed in the tank) if a low fluid level is detected based on the measurements by the fluid level sensors. In some implementations, the controller is configured to, or otherwise capable of communicating, with the electronic devices in the tank via wired communication like a docking procedure, or a wireless communication protocol like Bluetooth or Wi-Fi.

(11) FIG. 1A is a schematic diagram of an example single-phase immersion cooling system **100**, according to some implementations. The single-phase immersion cooling system **100** includes a container or tank **102A** that holds a volume of dielectric cooling fluid **112A**. Electronic devices **104A** (e.g., servers, processors, PCBs with IC chips performing high-performance computations such as hash operations for cryptocurrency mining, or other heat-generating electronic components) are immersed in the dielectric cooling fluid **112A**. In some implementations, the dielectric cooling fluid **112A** is an electrically non-conductive liquid, ensuring the safe operation of the electronic devices **104A** while maintaining thermal conductivity to absorb the heat produced by the electronic devices **104A** during operation.

(12) A pump **106A** is configured to circulate the dielectric cooling fluid **112A** throughout the tank **102A**, ensuring a consistent flow of the dielectric cooling fluid around the electronic devices **104A**. Circulating the dielectric cooling fluid **112A** through tank **102A** facilitates the absorption and distribution of heat away from the heat-generating electronic devices **104A**. The dielectric cooling fluid **112A** remains in a liquid state (single-phase) during the entire cooling process, avoiding any phase change to gas or vapor.

(13) The single-phase immersion cooling system **100** is further equipped with a heat exchanger **108A** that is thermally connected to the dielectric cooling fluid **112A**. The heat exchanger **108A** is responsible for transferring heat absorbed by the dielectric cooling fluid **112A** from the electronic devices **104A** to an external cooling medium, such as air or water. As the pump **106A** drives the dielectric cooling fluid **112A** through the heat exchanger **108A**, heat is dissipated from the dielectric cooling fluid **112A** to the external cooling medium, which cools the dielectric cooling fluid **112A** before it is recirculated back to the tank.

(14) During operation, the electronic devices **104A** generate heat, which is transferred directly to the surrounding dielectric cooling fluid **112A**. The dielectric cooling fluid **112A** has a high thermal conductivity, allowing the cooling fluid **112A** to efficiently absorb heat and prevent the electronic devices **104A** from overheating. The pump **106A** circulates the cooling fluid **112A** such that hotter fluid **112A** is continuously replaced with colder fluid **112A**.

(15) As the cooling fluid **112A** is circulated, it passes through the heat exchanger **108A**, where excess heat is transferred from the cooling fluid **112A** to the external cooling medium. The cooled fluid **112A** then flows back into the tank **102A** to continue the cooling cycle. This process aims to

maintain a stable operating temperature for the electronic devices **104A**.

(16) FIG. 1B is a schematic diagram of an example dual-phase immersion cooling system **101**, according to some implementations. The dual-phase immersion cooling system **101** includes tank **102B**, which holds a volume of dielectric cooling fluid **112A**. Electronic devices **104B**, such as servers, processors, PCBs with IC chips performing high-performance computations (e.g., hash operations for cryptocurrency mining), or other heat-generating components, are immersed in the dielectric cooling fluid **112A**. The dielectric cooling fluid **112A** is electrically non-conductive, which ensures the safe operation of the electronic devices **104B** while allowing effective thermal conductivity for heat absorption.

(17) Unlike the single-phase immersion cooling system **100**, the dielectric cooling fluid **112B** of the dual-phase immersion cooling system **101** undergoes a phase change from liquid to gas/vapor as it absorbs heat from the electronic devices **104B**. This phase change allows the dual-phase immersion cooling system **101** to manage high thermal loads more efficiently, as compared to the single-phase immersion cooling system **100**.

(18) The dual-phase immersion cooling system **101** includes a pump **106B** that is configured to circulate the dielectric cooling fluid **112B**, ensuring even distribution of the fluid and vapor throughout the tank. The dual-phase immersion cooling system **101** also includes a heat exchanger **108B**, which is configured to remove heat from the cooling fluid **112B** as part of the cooling cycle. Additionally, the dual-phase immersion cooling system **101** includes a condensation unit **110**, where gases/vapors are converted back to liquid by means of coils or other cooling mechanisms.

(19) During operation, the electronic devices **104B** generate heat, which is absorbed by the surrounding dielectric cooling fluid **112B**. As the cooling fluid **112B** absorbs heat, the cooling fluid **112B** vaporizes, transitioning from a liquid phase to a gas/vapor phase. This gas/vapor rises within the tank **102B** and passes through the heat exchanger **108B** before reaching the condensation unit **110**, where the vapor is converted back to a liquid. The cooled, recondensed dielectric cooling fluid **112B** is then returned to tank **102B** via pump **106B**.

(20) The single-phase immersion cooling system **100** and/or the dual-phase immersion cooling system **101** can provide improved thermal management and reduced energy consumption (e.g., by eliminating the need for traditional air-cooling methods), among other benefits. The use of dielectric cooling fluid prevents electrical interference, and the continuous circulation of dielectric cooling fluid helps to ensure a consistent and efficient dissipation of heat.

(21) Immersion cooling systems (both single and dual phase) for high performance computations rely on a consistent volume of immersion cooling fluid. Over time, the fluid level of the immersion cooling fluid in the tank may reduce to a low level (e.g., in the case of a leak in the tank or high evaporation in the cooling tank), which can cause one or more electronic devices **104A** or **104B** to lose the submersion in the cooling fluid, which may lead to overheating of the electronic devices **104A** or **104B** and consequent thermal failure.

(22) In accordance with aspects of the present disclosure, the single-phase immersion cooling system **100** and/or the dual-phase immersion cooling system **101** may be equipped with one or more fluid level sensors mounted on the electronic devices **104A** or **104B** and configured to monitor a fluid level of the dielectric cooling fluid, and a controller configured to take remedial actions if the fluid level is detected to be lower than a predetermined threshold. The remedial actions can include transmitting an alert to a system operator, powering down (e.g., entering a low power state) the electronic devices, or shutting down the electronic devices.

(23) FIG. 2 is a schematic diagram of an example electronic device **200** immersed in dielectric cooling fluid **201** in a tank, according to some implementations. As shown in FIG. 2, the electronic device **200** includes a printed circuit board (PCB) that includes a plurality of application-specific integrated circuit (ASIC) chips **204** mounted on the PCB. In some implementations, the size of the PCB is 12.6 inches×9.8 inches, although other dimensions are also possible. A fluid level sensor **202** is mounted on the PCB adjacent to the plurality of ASIC chips. The fluid level sensor **202** is on

the top side of the PCB when the PCB is immersed in the dielectric cooling fluid **201**. In some implementations, the electronic device **200** is an example of electronic device **104A** or **104B** described above.

(24) A plurality of the ASIC chips **204** are configured for high-performance computations (e.g., high data-rate computations). For example, one or more ASIC chips **204** can be configured to compute the specific hash algorithm of a cryptocurrency (e.g., SHA-256 for Bitcoin, Ethash for Ethereum, among others). The plurality of ASIC chips are integrated to perform these computations jointly or in parallel to increase computational power (e.g., hash rate).

(25) Although FIG. 2 shows a single sensor **202** mounted on the PCB of the electronic device **200**, other implementations can have electronic devices with a plurality of sensors. For example, FIG. 3 is a schematic diagram of an example electronic device **300** immersed in dielectric cooling fluid **301** in a tank, according to some implementations. In some implementations, the electronic device **300** is an example of electronic device **104A** or **104B** described above. The electronic device **300** includes a PCB that includes a plurality of blocks, e.g., blocks **302** and **304**. Each block includes a plurality of ASIC chips **306** mounted on the PCB. Each ASIC chip is configured for high-performance computations (e.g., high data-rate computations). For example, one or more ASIC chips **204** can be configured to compute a specific hash algorithm of a cryptocurrency (e.g., SHA-256 for Bitcoin, Ethash for Ethereum, among others). The plurality of ASIC chips **306** are integrated to perform these computations jointly or in parallel to increase computational power (e.g., hash rate). As shown in FIG. 3, a different fluid level sensor is mounted adjacent to each block. For example, fluid level sensor **308** is mounted on the PCB adjacent to block **302**, and fluid level sensor **310** is mounted on the PCB adjacent to block **304**.

(26) In some implementations, having a plurality of sensors mounted on a PCB as shown in the FIG. 3 facilitates detection of different levels of the cooling fluid **301**. If the detected fluid level is below the position of fluid level sensor **308**, a first remedial action (e.g., transmitting a notification of a fluid level to a system operator) is triggered. If the detected fluid level is below the position of fluid level sensor **310** indicating severe depletion in fluid level, a second remedial action (e.g., shutting down electronic device **200** or **300**) is triggered.

(27) FIG. 4 is a schematic diagram of an example fluid level sensor, according to some implementations. The fluid level sensor **400** is configured to measure the fluid level of dielectric cooling fluid **401**. In some implementations, the fluid level sensor **400** is similar to fluid level sensor **202** mounted on the electronic device **200** PCB, or fluid level sensor **308** or **310** mounted on the electronic device **300** PCB.

(28) As shown, the fluid level sensor **400** includes capacitive sensor **402** and capacitance-to-digital converter **404**. The capacitive sensor **402** includes sensing electrode **406** and sensing electrode **408**. A capacitance value measured by the capacitive sensor **402** is the capacitance between the sensing electrode **406** and the sensing electrode **408**. In some implementations, the fluid level sensor **400** is in physical contact with a dielectric cooling fluid **401** (similar to dielectric cooling fluid **201** or **301**) in a tank. If the level of the fluid decreases (e.g., due to evaporation or tank leakage) such that a surface area of fluid level sensor **400** that is in physical contact with the fluid is reduced (the fluid level sensor **400** is not fully submerged in the fluid), the capacitance between the sensing electrode **406** and the sensing electrode **408** decreases. For example, when the dielectric cooling fluid **401** is at level A as shown in FIG. 4, the fluid level sensor **400** is fully submerged in the cooling fluid and has a particular capacitance value corresponding to the amount of the dielectric fluid in contact with the capacitive sensor **402**. However, if the dielectric cooling fluid **401** reduces to level B (level B being lower than level A), then a portion **403** of the fluid level sensor **400** that is above level B is no longer in physical contact with the cooling fluid, and the capacitance value of the sensor **402** at level B is lower than the capacitance value at level A due to the amount of dielectric in contact with the capacitive sensor **402** being less at level B. This reduction in capacitance value indicates a lowering of the fluid level in the tank. In this manner, the capacitive sensor **402** can detect a low

fluid level. The capacitance to digital converter **404** converts the capacitance value measured by capacitive sensor **402** into a discrete digital value that can be easily interpreted by a microcontroller (e.g., control system **510** of FIG. 5). In some implementations, if the fluid level sensor **400** is fully exposed to the air, a capacitance value measured by the capacitive sensor **402** is a first value, e.g., 6 picofarad (pF). However, if the fluid level sensor **400** is fully immersed in the dielectric cooling fluid **401**, a capacitance value measured by the capacitive sensor **402** can change to a second value, e.g., 12 pF.

(29) FIG. 5 is a schematic diagram of an example immersion cooling system **500**, according to some implementations. The immersion cooling system **500** may implement one or more aspects of the single-phase immersion cooling system **100** and/or the dual-phase immersion cooling system **101**, as shown and described with reference to FIGS. 1A-1B. For example, the immersion cooling system **500** includes tank **502**, which may be similar to tank **102A** or tank **102B**. The immersion cooling system **500** also includes immersion cooling fluid **504**, which may be similar to the dielectric cooling fluid **112A** (e.g., a single-phase cooling fluid) or the dielectric cooling fluid **112B** (e.g., a two-phase cooling fluid).

(30) One or more electronic devices **506** are immersed in the cooling fluid **504**. Some or all of the electronic devices **506** are similar to electronic devices **104a**, **104b**, **200**, **300** described above. One or more fluid level sensors **508** are mounted on one or more electronic devices **506**. A fluid level sensor **508** is configured to monitor the fluid level of immersion cooling fluid **504** in tank **502**. The fluid level sensor **508** is similar to fluid level sensor **202**, **308**, **310** described above. For example, the fluid level sensor **508** includes a capacitive sensor (e.g., similar to capacitive sensor **402**) configured to measure the capacitance of the cooling fluid **504** and a capacitance-to-digital converter (e.g., similar to capacitance-to-digital converter **404**) configured to convert the analog capacitance signal detected by the capacitive sensor into a digital signal that can be processed by the control system **510**. Although electronic device **506** is shown with a single fluid sensor **508**, in some implementations, one or more of electronic devices **506** can have a plurality of fluid sensors **508**, e.g., as described with respect to sensors **308** and **310** mounted on the PCB of electronic device **300**.

(31) In some implementations, the control system **510** (also referred to as a controller) includes one or more processors and one or more memory devices storing instructions that, when executed, cause the one or more processors of the control system **510** to perform at least one remedial action based on measurements performed by the fluid level sensor **508**. The control system **510** may include a microcontroller, a central processing unit, or the like.

(32) In some implementations, the control system **510** is configured to communicate with the electronic devices **506** in the immersion tank **502** via a network connection, Wi-Fi, Bluetooth, or some other communication channel. This allows the control system **510** to notify or alert the electronic devices **506** of a low fluid level, so that the electronic devices **506** can switch to a low power state or shut themselves down before overheating of the electronic devices **506**. The control system **510** can also send an alert to a system operator, who can shut down or turn off one or more electronic devices **506**, or the whole system including the one or more electronic devices **506**. As described previously, the low fluid level can result from a leak or evaporation in the immersion tank **502**.

(33) In some implementations, if a capacitance value measured by the capacitive sensor is lower than a first threshold value (e.g., 10 pF) corresponding to a first fluid level threshold **512**, the control system **510** performs a first remedial action. For example, the control system **510** transmits a notification of a fluid level (the current fluid level corresponding to the current capacitance value) in the immersion tank **502** to a system operator. The system operator can perform additional remedial actions in response to the notification. For example, the system operator can add more immersion cooling fluid **504** into the immersion tank **502**, identify the location of the leak in the immersion tank **502**, seal the immersion tank **502** to minimize fluid loss due to evaporation, lower

the power of the electronic devices **506**, or shut down the electronic devices **506**.

(34) In some implementations, if a capacitance value measured by the capacitive sensor is lower than a second threshold value (e.g., 8.5 pF) corresponding to a second fluid level threshold **514** (close to a middle of the fluid level sensor **508**), the control system **510** can automatically perform a second remedial action. For example, the control system **510** can transmit a signal that causes at least one of the electronic devices **506** in the cooling fluid **216** in the immersion tank **218** to enter a low power state. It should be noted that the threshold values provided here are for exemplary purposes only; other values are possible in different implementations.

(35) In some implementations, if a capacitance value measured by the capacitive sensor is lower than a third threshold value (e.g., 6 pF) corresponding to a third fluid level threshold **516** (close to a bottom of the fluid level sensor **508**), the control system **510** can automatically perform a third remedial action. For example, the control system **510** can transmit a signal that causes at least one of the electronic devices **506** in the immersion tank **218** to shut down.

(36) FIG. **6** illustrates a flowchart of an example method for monitoring the fluid level of a cooling fluid in an immersion cooling tank, according to some implementations. For clarity of presentation, the method **600** is generally described in the context of the preceding figures. For example, the method **600** can be performed by the control system **510** of FIG. **5**, or any suitable system, environment, software, hardware, or combination thereof. In some implementations, operations of the method **600** can be run in parallel, in combination, in loops, or in any order. The example method **600** can be modified or reconfigured to include additional, fewer, or different steps (not shown in FIG. **6**), which can be performed in the order shown or in a different order.

(37) At **602**, the control system (e.g., control system **510**) receives a measurement of a value of the capacitance of a cooling fluid (e.g., immersion cooling fluid **504**) from one or more sensors (e.g., fluid level sensor **508**) mounted on one or more electronic devices (e.g., electronic devices **506**) submerged in the cooling fluid of an immersion tank (e.g., immersion tank **502**).

(38) At **604**, the control system determines, based at least on the measurement, that the measured value of the capacitance is less than a threshold value of a plurality of threshold values. The plurality of threshold values includes, e.g., a first threshold value (e.g., 10 pF) corresponding to a first fluid level threshold **512**, a second threshold value (e.g., 8.5 pF) corresponding to a second fluid level threshold **514**, and a third threshold value (e.g., 6 pF) corresponding to a third fluid level threshold **516**.

(39) At **606**, in response to determining that the measured value of the capacitance is less than the threshold value, the control system determines that the fluid level of the cooling fluid in the immersion tank is below the threshold level.

(40) At **608**, the control system performs one or more remedial actions in response to determining that the fluid level of the cooling fluid in the immersion tank is below the threshold level. The one or more remedial actions include transmitting a notification of a fluid level in the immersion tank to a system operator (in response to the first fluid level threshold), enabling the one or more electronic devices to enter a low power state (in response to the second fluid level threshold), or shutting down the one or more electronic devices (in response to the third fluid level threshold).

(41) After the cooling fluid is filled up to the normal level (e.g., level A in FIG. **4**), the one or more electronic devices can continue to perform computations or other work.

(42) FIG. **7** is a schematic diagram of an example computer system. In some implementations, the computer system **700** may include or be a part of one or more of the entities described herein. For example, in some implementations, the computer system **700** is similar to the control system **510** of FIG. **5**. As depicted in FIG. **7**, the computer system **700** includes a processor **710**, a memory **720**, a storage device **730**, and an input/output device **740**. Each of these components can be interconnected, for example, by a system bus **750**. The processor **710** is capable of processing instructions for execution within the computer system **700**. In some implementations, the processor **710** is a single-threaded processor, a multi-threaded processor, or another type of processor. The

processor **710** is capable of processing instructions stored in the memory **720** or on the storage device **730**. The memory **720** and the storage device **730** can store information within the computer system **700**. For example, the memory **720** and/or the storage device **730** can store measurement data from one or more fluid level sensors as they are received by the control system, as described in the preceding sections. Additionally or alternatively, the memory **720** and/or the storage device **730** can store historical measurement data. Although the computer system **700** is shown as having one processor **710**, one memory **720**, and one storage device **730** for illustrative purposes, the computer system **700** can include any number of processors **710**, memories **720**, and storage devices **730** based on system requirements.

(43) The input/output device **740** provides input/output operations for the computer system **700**. In some implementations, the input/output device **740** can include one or more of a network interface device (for example, an Ethernet card), a serial communication device (for example, an RS-232 port), or a wireless interface device (for example, an 802.11 card, a 3G wireless modem, a 4G wireless modem, or a 5G wireless modem), or some combination thereof. In some implementations, the input/output device can include driver devices configured to receive input data and send output data to other input/output devices, for example, a keyboard, printer, and/or display devices **760**. In some implementations, mobile computing devices, mobile communication devices, and other devices can also be used.

(44) While the present disclosure describes many examples, these should not be construed as limitations on the scope of an invention that is claimed or of what may be claimed, but rather as descriptions of features specific to particular embodiments. Certain features that are described in the context of separate embodiments can also be implemented in combination in a single embodiment. Conversely, various features that are described in the context of a single embodiment can also be implemented in multiple embodiments separately or in any suitable sub-combination. Although some features may be described as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination in some cases can be excised from the combination, and the claimed combination may be directed to a sub-combination or a variation of a sub-combination. Similarly, while some operations may be depicted in the drawings in a particular order, this should not be understood as requiring that such operations are performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results.

(45) A number of embodiments have been described. Nevertheless, it is understood that various modifications can be made without departing from the spirit and scope of the present disclosure. Accordingly, other embodiments are within the scope of the following claims.

Claims

1. An apparatus comprising: an electronic device submerged in a cooling fluid in an immersion tank, wherein the electronic device comprises a printed circuit board (PCB) with a plurality of application-specific integrated circuit (ASIC) chips mounted thereon, and a plurality of sensors mounted on the PCB adjacent to the plurality of ASIC chips, wherein at least one sensor of the plurality of sensors comprises circuitry configured to: measure a value of a capacitance of the cooling fluid; and transmit the measured value of the capacitance to a controller device that is communicatively coupled to the at least one sensor; and the controller device comprising one or more processors and configured to: receive the measured value of the capacitance from the at least one sensor; determine that the measured value of the capacitance is less than a threshold value; in response to determining that the measured value of the capacitance is less than the threshold value, determine that a fluid level of the cooling fluid in the immersion tank is below a threshold level; and perform at least one remedial action in response to determining that the fluid level of the cooling fluid in the immersion tank is below the threshold level.

2. The apparatus of claim 1, wherein the threshold value is a first threshold value of a plurality of threshold values, and wherein performing the remedial action comprises transmitting, to a system operator, a notification of the fluid level in the immersion tank.
3. The apparatus of claim 2, wherein the threshold value is a second threshold value of the plurality of threshold values, the second threshold value corresponding to a fluid level in the immersion tank being lower than a fluid level corresponding to the first threshold value, and wherein performing the remedial action comprises transmitting a first signal that causes the electronic device submerged in the cooling fluid in the immersion tank to enter a low power state.
4. The apparatus of claim 3, wherein the threshold value is a third threshold value of the plurality of threshold values, the third threshold value corresponding to a fluid level in the immersion tank being lower than a fluid level corresponding to the second threshold value, and wherein performing the remedial action comprises transmitting a second signal that causes the electronic device submerged in the cooling fluid in the immersion tank to shut down.
5. The apparatus of claim 1, wherein the cooling fluid comprises a single-phase immersion cooling liquid or a two-phase immersion cooling liquid.
6. The apparatus of claim 1, wherein the at least one sensor comprises: a capacitive sensor; and a capacitance-to-digital converter.
7. The apparatus of claim 1, further comprising: a heat exchanger configured to dissipate heat generated by the electronic device using the cooling fluid; and a pump system configured to circulate the cooling fluid through the immersion tank and the heat exchanger.
8. The apparatus of claim 1, wherein the plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block comprising a plurality of columns and each column comprising a subset of the plurality of ASIC chips, and wherein a different sensor of the plurality of sensors is mounted adjacent to each block.
9. The apparatus of claim 1, wherein the electronic device comprises a plurality of PCBs submerged in the cooling fluid in the immersion tank, each PCB comprising: a plurality of ASIC chips and a plurality of sensors, wherein the respective plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block comprising a plurality of columns and each column comprising a subset of the plurality of ASIC chips, and wherein a different sensor of the respective plurality of sensors is mounted adjacent to each block.
10. A method comprising: receiving a first measurement of a value of a capacitance of a cooling fluid from a plurality of sensors mounted on one or more electronic devices submerged in the cooling fluid of an immersion tank, wherein each electronic device comprises a printed circuit board (PCB) with a plurality of application-specific integrated circuit (ASIC) chips mounted thereon, and the plurality of sensors mounted on the PCB adjacent to the plurality of ASIC chips; determining, based at least on the first measurement, that the measured value of the capacitance is less than a first threshold value of a plurality of threshold values; in response to determining that the measured value of the capacitance is less than the first threshold value, determining that a fluid level of the cooling fluid in the immersion tank is below a first threshold level corresponding to the first threshold value; and transmitting, to a system operator, a notification of the fluid level in the immersion tank in response to determining that the fluid level of the cooling fluid in the immersion tank is below the first threshold level.
11. The method of claim 10, further comprising: receiving a second measurement of the value of the capacitance of the cooling fluid from the plurality of sensors; determining, based at least on the second measurement, that the measured value of the capacitance is less than a second threshold value of the plurality of threshold values, wherein the second threshold value corresponds to a second threshold level in the immersion tank being lower than the first threshold level corresponding to the first threshold value; and in response to the determining, transmitting a first signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to enter a low power state.

12. The method of claim 11, further comprising: receiving a third measurement of the value of the capacitance of the cooling fluid from the plurality of sensors; determining, based at least on the third measurement, that the measured value of the capacitance is less than a third threshold value of the plurality of threshold values, wherein the third threshold value corresponds to a third threshold level in the immersion tank being lower than the second threshold level corresponding to the second threshold value; and in response to the determining, transmitting a second signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to shut down.

13. The method of claim 10, wherein the cooling fluid comprises a single-phase immersion cooling liquid or a two-phase immersion cooling liquid.

14. The method of claim 10, wherein the plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block comprising a plurality of columns and each column comprising a subset of the plurality of ASIC chips, and wherein a different sensor of the plurality of sensors is mounted adjacent to each block.

15. The method of claim 10, wherein each electronic device comprises a plurality of PCBs submerged in the cooling fluid in the immersion tank, each PCB comprising: a plurality of ASIC chips and a plurality of sensors, wherein the respective plurality of ASIC chips are arranged in a plurality of blocks on the PCB, each block comprising a plurality of columns and each column comprising a subset of the plurality of ASIC chips, and wherein a different sensor of the respective plurality of sensors is mounted adjacent to each block.

16. One or more non-transitory computer-readable media storing instructions that, when executed, cause one or more processors to perform operations comprising: receiving a first measurement of a value of a capacitance of a cooling fluid from a plurality of sensors mounted on one or more electronic devices submerged in the cooling fluid of an immersion tank, wherein each electronic device comprises a printed circuit board (PCB) with a plurality of application-specific integrated circuit (ASIC) chips mounted thereon, and the plurality of sensors mounted on the PCB adjacent to the plurality of ASIC chips; determining, based at least on the first measurement, that the measured value of the capacitance is less than a first threshold value of a plurality of threshold values; and in response to determining that the measured value of the capacitance is less than the first threshold value, determining that a fluid level of the cooling fluid in the immersion tank is below a first threshold level; and transmitting, to a system operator, a notification of the fluid level in the immersion tank in response to determining that the fluid level of the cooling fluid in the immersion tank is below the first threshold level.

17. The non-transitory computer-readable media of claim 16, the operations further comprising: receiving a second measurement of the value of the capacitance of the cooling fluid from the plurality of sensors; determining, based at least on the second measurement, that the measured value of the capacitance is less than a second threshold value of the plurality of threshold values, wherein the second threshold value corresponds to a second threshold level in the immersion tank being lower than the first threshold level corresponding to the first threshold value; and in response to the determining, transmitting a first signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to enter a low power state.

18. The non-transitory computer-readable media of claim 17, the operations further comprising: receiving a third measurement of the value of the capacitance of the cooling fluid from the plurality of sensors; determining, based at least on the third measurement, that the measured value of the capacitance is less than a third threshold value of the plurality of threshold values, wherein the third threshold value corresponds to a third threshold level in the immersion tank being lower than the second threshold level corresponding to the second threshold value; and in response to the determining, transmitting a second signal that causes at least one of the one or more electronic devices submerged in the cooling fluid in the immersion tank to shut down.
