

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399927
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Charlton; Ebony James et al.

Contextual media filter search

Abstract

Method for receiving an input onto a graphical user interface at a client device, capturing an image frame at the client device, the image frame comprising a depiction of an object, identifying the object within the image frame, accessing media content associated with the object within a media repository in response to identifying the object, and causing presentation of the media content within the image frame at the client device.

Inventors: Charlton; Ebony James (Los Angeles, CA), Hu; Hao (Bellevue, WA), Li; Yanjia (Torrance, CA), Mei; Xing (Los Angeles, CA), Tang; Kevin Dechau (Los Angeles, CA)

Applicant: Snap Inc. (Santa Monica, CA)

Family ID: 1000008777478

Assignee: Snap Inc. (Santa Monica, CA)

Appl. No.: 18/299908

Filed: April 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230325430 A1	Oct. 12, 2023

Related U.S. Application Data

continuation parent-doc US 17306179 20210503 US 11651019 child-doc US 18299908
continuation parent-doc US 16814221 20200310 US 11017233 child-doc US 17306179
us-provisional-application US 62826679 20190329

Publication Classification

Int. Cl.: **G06F16/40** (20190101); **G06F3/0488** (20220101); **G06F16/51** (20190101); **G06F16/538** (20190101); **G06T7/60** (20170101); **G06T11/00** (20060101); **G06V10/75** (20220101); **G06V20/20** (20220101)

U.S. Cl.:

CPC **G06F16/40** (20190101); **G06F3/0488** (20130101); **G06F16/51** (20190101); **G06F16/538** (20190101); **G06T7/60** (20130101); **G06T11/00** (20130101); **G06V10/7553** (20220101); **G06V20/20** (20220101); G06T2207/30242 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5577135	12/1995	Grajski et al.	N/A	N/A
5862376	12/1998	Steele, Jr. et al.	N/A	N/A
6182115	12/2000	Cuomo et al.	N/A	N/A
6275935	12/2000	Barlow et al.	N/A	N/A
7046851	12/2005	Keaton	707/E17.02	G06F 18/21
8493353	12/2012	Blanchflower et al.	N/A	N/A
8719857	12/2013	Ellis et al.	N/A	N/A
9110541	12/2014	Zhou et al.	N/A	N/A
9272208	12/2015	Le et al.	N/A	N/A
9280560	12/2015	Dube et al.	N/A	N/A
9361523	12/2015	Chen et al.	N/A	N/A
9424461	12/2015	Yuan	N/A	G06V 20/647
9684941	12/2016	Filler	N/A	N/A
9720934	12/2016	Dube et al.	N/A	N/A
9830631	12/2016	Dhua et al.	N/A	N/A
9892242	12/2017	Hodge	N/A	N/A
9954996	12/2017	Christie et al.	N/A	N/A
10149958	12/2017	Tran et al.	N/A	N/A
10257202	12/2018	Jiang et al.	N/A	N/A
10282914	12/2018	Tran et al.	N/A	N/A
10467147	12/2018	Ahmed et al.	N/A	N/A
10503494	12/2018	Robinson et al.	N/A	N/A
10606824	12/2019	Fire et al.	N/A	N/A
10636062	12/2019	Mossoba et al.	N/A	N/A
10681063	12/2019	Silva et al.	N/A	N/A
10699124	12/2019	Herzberg et al.	N/A	N/A
10798574	12/2019	Indurkar et al.	N/A	N/A

11017233	12/2020	Charlton et al.	N/A	N/A
11182944	12/2020	Kondoh et al.	N/A	N/A
11341728	12/2021	Hu et al.	N/A	N/A
11386625	12/2021	Hu et al.	N/A	N/A
11410215	12/2021	Goetz et al.	N/A	N/A
11417154	12/2021	Moeykens	N/A	N/A
11562014	12/2022	Dermu	N/A	N/A
11620829	12/2022	Hu et al.	N/A	N/A
11651019	12/2022	Charlton et al.	N/A	N/A
11775132	12/2022	Mcdannald et al.	N/A	N/A
11823456	12/2022	Dela Rosa et al.	N/A	N/A
11922396	12/2023	Blumenthal	N/A	N/A
11922445	12/2023	Aery et al.	N/A	N/A
2004/0100483	12/2003	Russell	707/E17.024	G06V 10/46
2008/0030575	12/2007	Davies	348/92	H04N 7/185
2008/0080012	12/2007	Mock et al.	N/A	N/A
2009/0033679	12/2008	Borrel et al.	N/A	N/A
2009/0133037	12/2008	Allen et al.	N/A	N/A
2009/0293012	12/2008	Alter	715/848	G06T 15/10
2009/0322671	12/2008	Scott	345/173	G06F 3/013
2010/0255813	12/2009	Belrose et al.	N/A	N/A
2011/0115816	12/2010	Brackney	700/295	H05B 47/10
2012/0284297	12/2011	Aguera-Arcas et al.	N/A	N/A
2013/0080172	12/2012	Talwar et al.	N/A	N/A
2013/0201182	12/2012	Kuroki et al.	N/A	N/A
2013/0202213	12/2012	Adamek et al.	N/A	N/A
2013/0346297	12/2012	Zuck et al.	N/A	N/A
2014/0029798	12/2013	Flynn et al.	N/A	N/A
2014/0078144	12/2013	Berriman et al.	N/A	N/A
2014/0130182	12/2013	Yackanich et al.	N/A	N/A
2014/0195650	12/2013	Kelsen	709/219	H04L 67/02
2014/0214515	12/2013	Quirk et al.	N/A	N/A
2014/0247207	12/2013	Pahud et al.	N/A	N/A
2014/0267120	12/2013	Zhang et al.	N/A	N/A
2014/0289843	12/2013	Chiang et al.	N/A	N/A
2014/0317012	12/2013	Can et al.	N/A	N/A
2014/0340423	12/2013	Taylor et al.	N/A	N/A
2014/0362120	12/2013	Wohl et al.	N/A	N/A
2015/0070347	12/2014	Hofmann	345/419	G06F 3/04815
2015/0206343	12/2014	Mattila et al.	N/A	N/A
2015/0242444	12/2014	Campbell et al.	N/A	N/A
2015/0262036	12/2014	Song et al.	N/A	N/A
2015/0310667	12/2014	Young et al.	N/A	N/A
2015/0348329	12/2014	Carre et al.	N/A	N/A
2015/0350207	12/2014	Kim et al.	N/A	N/A
2016/0014196	12/2015	Azulay et al.	N/A	N/A

2016/0048665	12/2015	Alshinnawi et al.	N/A	N/A
2016/0098619	12/2015	Gaidon et al.	N/A	N/A
2016/0189000	12/2015	Dube et al.	N/A	N/A
2016/0358230	12/2015	Wilson et al.	N/A	N/A
2016/0364394	12/2015	Bostick et al.	N/A	N/A
2016/0364590	12/2015	Wadley	N/A	N/A
2017/0024384	12/2016	Kant	N/A	G06F 16/2246
2017/0061469	12/2016	Garrity et al.	N/A	N/A
2017/0323481	12/2016	Tran et al.	N/A	N/A
2017/0372046	12/2016	Thomee et al.	N/A	N/A
2018/0069937	12/2017	Kolleri	N/A	N/A
2018/0082430	12/2017	Sharma et al.	N/A	N/A
2018/0114087	12/2017	Kamen et al.	N/A	N/A
2018/0159971	12/2017	Yang et al.	N/A	N/A
2018/0164995	12/2017	Czupi	N/A	N/A
2018/0165888	12/2017	Duan et al.	N/A	N/A
2018/0184038	12/2017	Li	N/A	N/A
2018/0255947	12/2017	Wilkinson et al.	N/A	N/A
2018/0260660	12/2017	Gopalan et al.	N/A	N/A
2018/0286081	12/2017	Koperski et al.	N/A	N/A
2018/0350119	12/2017	Kocharalakota et al.	N/A	N/A
2019/0034667	12/2018	Zhou	N/A	N/A
2019/0096135	12/2018	Dal Mutto et al.	N/A	N/A
2019/0102922	12/2018	Gum	N/A	N/A
2019/0207678	12/2018	Aoyama et al.	N/A	N/A
2019/0236167	12/2018	Hu et al.	N/A	N/A
2019/0251570	12/2018	Song	N/A	N/A
2019/0253700	12/2018	Tornéus et al.	N/A	N/A
2019/0311335	12/2018	Greiner et al.	N/A	N/A
2019/0362154	12/2018	Moore et al.	N/A	N/A
2019/0392058	12/2018	Konow Krause et al.	N/A	N/A
2020/0050324	12/2019	Gavara	N/A	N/A
2020/0074672	12/2019	Hoff	N/A	N/A
2020/0077144	12/2019	Zavesky et al.	N/A	N/A
2020/0082668	12/2019	Foley et al.	N/A	N/A
2020/0090409	12/2019	Fink et al.	N/A	N/A
2020/0125707	12/2019	Lin	N/A	N/A
2020/0204739	12/2019	Beres et al.	N/A	N/A
2020/0279305	12/2019	Mossoba et al.	N/A	N/A
2020/0311426	12/2019	Charlton et al.	N/A	N/A
2020/0372294	12/2019	Koval et al.	N/A	N/A
2021/0004589	12/2020	Turkelson et al.	N/A	N/A
2021/0064728	12/2020	Kadambala et al.	N/A	N/A
2021/0073543	12/2020	Herzberg et al.	N/A	N/A
2021/0121782	12/2020	Døssing et al.	N/A	N/A
2021/0141880	12/2020	Pauli et al.	N/A	N/A
2021/0152975	12/2020	Hohman	N/A	N/A

2021/0256498	12/2020	Detitta	N/A	N/A
2021/0406041	12/2020	Saraiya et al.	N/A	N/A
2021/0409539	12/2020	Arellano et al.	N/A	N/A
2022/0067580	12/2021	Rho et al.	N/A	N/A
2022/0092307	12/2021	Charlton et al.	N/A	N/A
2022/0101011	12/2021	Dela Rosa et al.	N/A	N/A
2022/0101033	12/2021	Hu et al.	N/A	N/A
2022/0101608	12/2021	Hu et al.	N/A	N/A
2022/0101609	12/2021	Hu et al.	N/A	N/A
2022/0148302	12/2021	Bao et al.	N/A	N/A
2022/0157047	12/2021	Truong et al.	N/A	N/A
2022/0167161	12/2021	Sheffield et al.	N/A	N/A
2022/0179665	12/2021	Rathod	N/A	G06F 9/451
2022/0244989	12/2021	Ryan et al.	N/A	N/A
2022/0335815	12/2021	Dice et al.	N/A	N/A
2022/0382729	12/2021	Wu et al.	N/A	N/A
2022/0398306	12/2021	Misra et al.	N/A	N/A
2023/0029251	12/2022	Zhang et al.	N/A	N/A
2023/0117441	12/2022	Mcmichael et al.	N/A	N/A
2023/0120950	12/2022	Ranjan	N/A	N/A
2023/0252392	12/2022	Courcelle et al.	N/A	N/A
2023/0401802	12/2022	Maschmeyer et al.	N/A	N/A
2024/0265145	12/2023	Cheng et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101203170	12/2007	CN	N/A
104751475	12/2014	CN	N/A
107590453	12/2017	CN	N/A
108305317	12/2017	CN	N/A
109902190	12/2018	CN	N/A
111311758	12/2019	CN	N/A
113906413	12/2021	CN	N/A
WO-2016077493	12/2015	WO	N/A
WO-2020187705	12/2019	WO	N/A
2020205197	12/2019	WO	N/A
WO-2024167918	12/2023	WO	N/A

OTHER PUBLICATIONS

“International Application Serial No. PCT US2020 022343, International Search Report mailed May 28, 2020”, 3 pgs. cited by applicant

“International Application Serial No. PCT US2020 022343, Written Opinion mailed May 28, 2020”, 7 pgs. cited by applicant

“U.S. Appl. No. 16/814,221, Notice of Allowance mailed Jan. 25, 2021”, 20 pgs. cited by applicant

“International Application Serial No. PCT US2020 022343, International Preliminary Report on Patentability mailed Oct. 14, 2021”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/306,179, Non Final Office Action mailed Jan. 20, 2022”, 12 pgs. cited by applicant

“U.S. Appl. No. 17/306,179, Response filed Jun. 20, 2022 to Non Final Office Action mailed Jan. 20, 2022”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/306,179, Final Office Action mailed Aug. 25, 2022”, 33 pgs. cited by applicant

“U.S. Appl. No. 17/306,179, Response filed Nov. 23, 2022 to Final Office Action mailed Aug. 25, 2022”, 10 pgs. cited by applicant

“U.S. Appl. No. 17/306,179, Notice of Allowance mailed Jan. 10, 2023”, 8 pgs. cited by applicant

“European Application Serial No. 20718873.1, Communication Pursuant to Article 94(3) EPC mailed Dec. 22, 2023”, 9 pgs. cited by applicant

Roman, Daniel, “Snapchat New AR Filters”, Youtube, [Online] Retrieved from the Internet:URL:https://www.youtube.com/watch?v=E8NKAPGL1HQ, (Apr. 18, 2017), 2:00 min.; 27 pgs. cited by applicant

“Korean Application Serial No. 10-2021-7034733, Response filed Jul. 12, 2024 to Notice of Preliminary Rejection mailed Apr. 12, 2024”, W/ English Claims, 29 pgs. cited by applicant

“Korean Application Serial No. 10-2021-7034733, Notice of Preliminary Rejection mailed Apr. 12, 2024”, w/ English Translation, 15 pgs. cited by applicant

U.S. Appl. No. 16/949,074 U.S. Pat. No. 11,620,829 filed Oct. 13, 2020, Visual Matching With a Messaging Application. cited by applicant

U.S. Appl. No. 17/378,259 U.S. Pat. No. 11,823,456 filed Jul. 16, 2021, Visual Matching With a Messaging Application. cited by applicant

“U.S. Appl. No. 16/949,074, 312 Amendment filed Feb. 14, 2023”, 7 pgs. cited by applicant

“U.S. Appl. No. 16/949,074, Non Final Office Action mailed Aug. 11, 2022”, 16 pgs. cited by applicant

“U.S. Appl. No. 16/949,074, Notice of Allowance mailed Nov. 18, 2022”, 7 pgs. cited by applicant

“U.S. Appl. No. 16/949,077, Non Final Office Action mailed Oct. 15, 2021”, 10 pgs. cited by applicant

“U.S. Appl. No. 16/949,077, Notice of Allowance mailed Mar. 9, 2022”, 16 pgs. cited by applicant

“U.S. Appl. No. 16/949,077, Response filed Jan. 7, 2022 to Non Final Office Action mailed Oct. 15, 2021”, 9 pgs. cited by applicant

“U.S. Appl. No. 16/949,079, Non Final Office Action mailed Jul. 8, 2021”, 22 pgs. cited by applicant

“U.S. Appl. No. 16/949,079, Notice of Allowability mailed Mar. 3, 2022”, 2 pgs. cited by applicant

“U.S. Appl. No. 16/949,079, Notice of Allowance mailed Feb. 14, 2022”, 10 pgs. cited by applicant

“U.S. Appl. No. 16/949,079, Response filed Oct. 5, 2021 to Non Final Office Action mailed Jul. 8, 2021”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/378,259, Corrected Notice of Allowability mailed Jun. 28, 2023”, 2 pgs. cited by applicant

“U.S. Appl. No. 17/378,259, Non Final Office Action mailed Feb. 22, 2023”, 20 pgs. cited by applicant

“U.S. Appl. No. 17/378,259, Notice of Allowance mailed Jun. 13, 2023”, 9 pgs. cited by applicant

“U.S. Appl. No. 17/378,259, Response filed May 22, 2023 to Non Final Office Action mailed Feb. 22, 2023”, 9 pgs. cited by applicant

“International Application Serial No. PCT/US2024/014615, International Search Report mailed May 8, 2024”, 4 pgs. cited by applicant

“International Application Serial No. PCT/US2024/014615, Written Opinion mailed May 8, 2024”, 11 pgs. cited by applicant

“Response filed Oct. 27, 2022 to Non-Final Office Action dated Aug. 11, 2022.”, 9 pgs. cited by applicant

“U.S. Appl. No. 18/165,747, Non Final Office Action mailed Jan. 21, 2025”, 25 pgs. cited by applicant

“Korean Application Serial No. 10-2021-7034733, Final Office Action mailed Jan. 23, 2025”, w/

Primary Examiner: Martello; Edward

Attorney, Agent or Firm: Schwegman Lundberg & Woessner, P.A.

Background/Summary

PRIORITY (1) This application is a continuation of U.S. application Ser. No. 17/306,179, filed May 3, 2021, which is a continuation of U.S. application Ser. No. 16/814,221, filed Mar. 10, 2020, which claims the benefit of priority to U.S. Provisional Patent application Ser. No. 62/826,679, filed Mar. 29, 2019, each of which is incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) Embodiments of the present disclosure relate generally to mobile computing technology and, more particularly, but not by way of limitation, to systems for generating and displaying dynamic contextual media content at a client device.

BACKGROUND

(2) Augmented reality (AR), is a live direct or indirect view of a physical, real-world environment whose elements are augmented by computer-generated sensory inputs.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.
- (2) In the drawings, which are not necessarily drawn to scale, like numerals may describe similar components in different views. Like numerals having different letter suffixes may represent different instances of similar components. Some embodiments are illustrated by way of example, and not limitation, in the figures of the accompanying drawings in which:
- (3) To easily identify the discussion of any particular element or act, the most significant digit or digits in a reference number refer to the figure number in which that element is first introduced.
- (4) FIG. 1 is a diagrammatic representation of a networked environment in which the present disclosure may be deployed, in accordance with some example embodiments.
- (5) FIG. 2 is a diagrammatic representation of a messaging client application, in accordance with some example embodiments.
- (6) FIG. 3 is a diagrammatic representation of a data structure as maintained in a database, in accordance with some example embodiments.
- (7) FIG. 4 is a diagrammatic representation of a message, in accordance with some example embodiments.
- (8) FIG. 5 is a flowchart for an access-limiting process, in accordance with some example embodiments.
- (9) FIG. 6 is a block diagram illustrating components of the contextual media filter system, according to some example embodiments.
- (10) FIG. 7 is a flowchart depicting a method of causing display of a contextual media filter according to certain example embodiments.

(11) FIG. 8 is a diagrammatic illustration of an object within an image frame, according to some example embodiments.

(12) FIG. 9 is a diagrammatic illustration of a contextual media filter system within a user interface, according to some example embodiments.

(13) FIG. 10 is block diagram showing a software architecture within which the present disclosure may be implemented, in accordance with some example embodiments.

(14) FIG. 11 is a diagrammatic representation of a machine, in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed, in accordance with some example embodiments.

DETAILED DESCRIPTION

(15) For purposes of explanation, specific configurations and details are set forth in order to provide a thorough understanding of the present subject matter. However, it will be apparent to one of ordinary skill in the art that embodiments of the subject matter described may be practiced without the specific details presented herein, or in various combinations, as described herein. Furthermore, well-known features may be omitted or simplified in order not to obscure the described embodiments. Various examples may be given throughout this description. These are merely descriptions of specific embodiments. The scope or meaning of the claims is not limited to the examples given.

(16) AR systems provide users within graphical user interfaces (GUIs) to display a live direct or indirect view of a physical, real-world environment, wherein elements of the view are augmented by computer-generated sensory inputs. For example, an AR interface may present media content at positions within a display of a view of a real-world environment, such that the media content appears to interact with elements in the real-world environment.

(17) Aspects of the present disclosure describe a contextual media filter system configured to generate and display contextual media filters at a client device. For example, the contextual media filter system is configured to perform operations that include, receiving an input onto a graphical user interface at a client device, capturing an image frame at the client device, the image frame comprising a depiction of an object, identifying the object within the image frame, accessing media content associated with the object within a media repository in response to identifying the object, and causing presenting of the media content within the image frame at the client device.

(18) The media content may include animated Graphics Interchange Format (GIF) images, of various shapes, sizes and themes. In some embodiments, the contextual media filter system may be in communication with a media repository that comprises a sorted and labeled collection of the media content, wherein the media content within the collection of media content is labeled or tagged based on attributes of the media content. For example, the media content may be tagged with a label that identifies an object category of the media content, such as “food,” or “basketball,” such that a reference to the object category corresponds with a set of media content from among the collection of media content.

(19) In some embodiments, responsive to receiving an input that selects a user option from among a set of user options, the contextual media filter system captures an image from a client device, wherein the image frame comprises a depiction of one or more objects in a real-world environment. For example, the contextual media filter system may detect one or more local features (e.g., first set of features) within the image frame, wherein the local features identify an object associated with the object depicted in the image frame, or in further embodiments may also employ one or more image and text recognition techniques to identify the object depicted in the image frame. Based on the identification of the object, the contextual media filter system retrieves a set of representative features associated with the local features to compute global features (e.g., second set of features) of the image frame. The contextual media filter system may use the global features and query a media repository to identify media content based on the local features and the representative features. The contextual media filter system further geometrically verifies the media content using

the local features and eliminates false media content from the media content.

(20) In response to identifying the set of media content from the media repository, the contextual media filter system generates and causes display of the set of media content at the client device. In some embodiments, to generate the presentation of the set of media content, the contextual media filter system retrieves a media template that provides a presentation format and layout for the set of media content. For example, the media template may define positions to present the set of media content within the image frame at the client device. In some embodiments, the presentation of the set of media content within the image frame at the client device may be based on a position (or positions) of the objects identified within the image frame.

(21) FIG. 1 is a block diagram showing an example messaging system **100** for exchanging data (e.g., messages and associated content) over a network. The messaging system **100** includes multiple instances of a client device **102**, each of which hosts a number of applications including a messaging client application **104**. Each messaging client application **104** is communicatively coupled to other instances of the messaging client application **104** and a messaging server system **108** via a network **106** (e.g., the Internet).

(22) A messaging client application **104** is able to communicate and exchange data with another messaging client application **104** and with the messaging server system **108** via the network **106**. The data exchanged between messaging client application **104**, and between a messaging client application **104** and the messaging server system **108**, includes functions (e.g., commands to invoke functions) as well as payload data (e.g., text, audio, video or other multimedia data).

(23) The messaging server system **108** provides server-side functionality via the network **106** to a particular messaging client application **104**. While certain functions of the messaging system **100** are described herein as being performed by either a messaging client application **104** or by the messaging server system **108**, the location of certain functionality either within the messaging client application **104** or the messaging server system **108** is a design choice. For example, it may be technically preferable to initially deploy certain technology and functionality within the messaging server system **108**, but to later migrate this technology and functionality to the messaging client application **104** where a client device **102** has a sufficient processing capacity.

(24) The messaging server system **108** supports various services and operations that are provided to the messaging client application **104**. Such operations include transmitting data to, receiving data from, and processing data generated by the messaging client application **104**. This data may include, message content, client device information, geolocation information, media annotation and overlays, message content persistence conditions, social network information, and live event information, as examples. Data exchanges within the messaging system **100** are invoked and controlled through functions available via user interfaces (UIs) of the messaging client application **104**.

(25) Turning now specifically to the messaging server system **108**, an Application Program Interface (API) server **110** is coupled to, and provides a programmatic interface to, an application server **112**. The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the application server **112**.

(26) The Application Program Interface (API) server **110** receives and transmits message data (e.g., commands and message payloads) between the client device **102** and the application server **112**. Specifically, the Application Program Interface (API) server **110** provides a set of interfaces (e.g., routines and protocols) that can be called or queried by the messaging client application **104** in order to invoke functionality of the application server **112**. The Application Program Interface (API) server **110** exposes various functions supported by the application server **112**, including account registration, login functionality, the sending of messages, via the application server **112**, from a particular messaging client application **104** to another messaging client application **104**, the sending of media files (e.g., images or video) from a messaging client application **104** to the

messaging server application **114**, and for possible access by another messaging client application **104**, the setting of a collection of media data (e.g., story), the retrieval of a list of friends of a user of a client device **102**, the retrieval of such collections, the retrieval of messages and content, the adding and deletion of friends to a social graph, the location of friends within a social graph, and opening an application event (e.g., relating to the messaging client application **104**).

(27) The application server **112** hosts a number of applications and subsystems, including a messaging server application **114**, an image processing system **116**, a social network system **122** and a contextual media filter system **124**.

(28) The contextual media filter system **124** is configured to capture an image frame that includes a depiction of an object from a client device **102**, identify one or more objects within the image frame based on the depiction of the object, identify one or more image features based on the object, retrieve a set of media content based on the image features, and cause display of a presentation of the set of media content within the image frame at the client device **102**, according to some example embodiments. Further details of the contextual media filter system **124** can be found in FIG. **6** below.

(29) The messaging server application **114** implements a number of message processing technologies and functions, particularly related to the aggregation and other processing of content (e.g., textual and multimedia content) included in messages received from multiple instances of the messaging client application **104**. As will be described in further detail, the text and media content from multiple sources may be aggregated into collections of content (e.g., called stories or galleries). These collections are then made available, by the messaging server application **114**, to the messaging client application **104**. Other processor and memory intensive processing of data may also be performed server-side by the messaging server application **114**, in view of the hardware requirements for such processing.

(30) The application server **112** also includes an image processing system **116** that is dedicated to performing various image processing operations, typically with respect to images or video received within the payload of a message at the messaging server application **114**.

(31) The social network system **122** supports various social networking functions services and makes these functions and services available to the messaging server application **114**. To this end, the social network system **122** maintains and accesses an entity graph **304** (as shown in FIG. **3**) within the database **120**. Examples of functions and services supported by the social network system **122** include the identification of other users of the messaging system **100** with which a particular user has relationships or is “following”, and also the identification of other entities and interests of a particular user.

(32) The application server **112** is communicatively coupled to a database server **118**, which facilitates access to a database **120** in which is stored data associated with messages processed by the messaging server application **114**.

(33) FIG. **2** is block diagram illustrating further details regarding the messaging system **100**, according to example embodiments. Specifically, the messaging system **100** is shown to comprise the messaging client application **204** and the application server **212**, which in turn embody a number of some subsystems, namely an ephemeral timer system **202**, a collection management system **206** and an annotation system **208**.

(34) The ephemeral timer system **202** is responsible for enforcing the temporary access to content permitted by the messaging client application **204** and the messaging server application **114**. To this end, the ephemeral timer system **202** incorporates a number of timers that, based on duration and display parameters associated with a message, or collection of messages (e.g., a story), selectively display and enable access to messages and associated content via the messaging client application **204**. Further details regarding the operation of the ephemeral timer system **202** are provided below.

(35) The collection management system **206** is responsible for managing collections of media (e.g., collections of text, image video and audio data). In some examples, a collection of content (e.g.,

messages, including images, video, text and audio) may be organized into an “event gallery” or an “event story.” Such a collection may be made available for a specified time period, such as the duration of an event to which the content relates. For example, content relating to a music concert may be made available as a “story” for the duration of that music concert. The collection management system **206** may also be responsible for publishing an icon that provides notification of the existence of a particular collection to the user interface of the messaging client application **204**.

(36) The collection management system **206** furthermore includes a curation interface **210** that allows a collection manager to manage and curate a particular collection of content. For example, the curation interface **210** enables an event organizer to curate a collection of content relating to a specific event (e.g., delete inappropriate content or redundant messages). Additionally, the collection management system **206** employs machine vision (or image recognition technology) and content rules to automatically curate a content collection. In certain embodiments, compensation may be paid to a user for inclusion of user-generated content into a collection. In such cases, the curation interface **210** operates to automatically make payments to such users for the use of their content.

(37) The annotation system **208** provides various functions that enable a user to annotate or otherwise modify or edit media content associated with a message. For example, the annotation system **208** provides functions related to the generation and publishing of media overlays for messages processed by the messaging system **100**. The annotation system **208** operatively supplies a media overlay or supplementation (e.g., an image filter) to the messaging client application **204** based on a geolocation of the client device **102**. In another example, the annotation system **208** operatively supplies a media overlay to the messaging client application **204** based on other information, such as social network information of the user of the client device **102**. A media overlay may include audio and visual content and visual effects. Examples of audio and visual content include pictures, texts, logos, animations, and sound effects. An example of a visual effect includes color overlaying. The audio and visual content or the visual effects can be applied to a media content item (e.g., a photo) at the client device **102**. For example, the media overlay may include text that can be overlaid on top of a photograph taken by the client device **102**. In another example, the media overlay includes an identification of a location overlay (e.g., Venice beach), a name of a live event, or a name of a merchant overlay (e.g., Beach Coffee House). In another example, the annotation system **208** uses the geolocation of the client device **102** to identify a media overlay that includes the name of a merchant at the geolocation of the client device **102**. The media overlay may include other indicia associated with the merchant. The media overlays may be stored in the database **120** and accessed through the database server **118**.

(38) In one example embodiment, the annotation system **208** provides a user-based publication platform that enables users to select a geolocation on a map, and upload content associated with the selected geolocation. The user may also specify circumstances under which a particular media overlay should be offered to other users. The annotation system **208** generates a media overlay that includes the uploaded content and associates the uploaded content with the selected geolocation.

(39) In another example embodiment, the annotation system **208** provides a merchant-based publication platform that enables merchants to select a particular media overlay associated with a geolocation via a bidding process. For example, the annotation system **208** associates the media overlay of a highest bidding merchant with a corresponding geolocation for a predefined amount of time.

(40) FIG. 3 is a schematic diagram illustrating data structures **300** which may be stored in the database **316** of the messaging server system **108**, according to certain example embodiments. While the content of the database **316** is shown to comprise a number of tables, it will be appreciated that the data could be stored in other types of data structures (e.g., as an object-oriented database).

(41) The database **316** includes message data stored within a message table **314**. The entity table **302** stores entity data, including an entity graph **304**. Entities for which records are maintained within the entity table **302** may include individuals, corporate entities, organizations, objects, places, events, etc. Regardless of type, any entity regarding which the messaging server system **108** stores data may be a recognized entity. Each entity is provided with a unique identifier, as well as an entity type identifier (not shown).

(42) The entity graph **304** furthermore stores information regarding relationships and associations between entities. Such relationships may be social, professional (e.g., work at a common corporation or organization) interested-based or activity-based, merely for example.

(43) The database **316** also stores annotation data, in the example form of filters, in an annotation table **312**. Filters for which data is stored within the annotation table **312** are associated with and applied to videos (for which data is stored in a video table **310**) and/or images (for which data is stored in an image table **308**). Filters, in one example, are overlays that are displayed as overlaid on an image or video during presentation to a recipient user. Filters may be of various types, including user-selected filters from a gallery of filters presented to a sending user by the messaging client application **104** when the sending user is composing a message. Other types of filters include geolocation filters (also known as geo-filters) which may be presented to a sending user based on geographic location. For example, geolocation filters specific to a neighborhood or special location may be presented within a user interface by the messaging client application **104**, based on geolocation information determined by a GPS unit of the client device **102**. Another type of filter is a data filter, which may be selectively presented to a sending user by the messaging client application **104**, based on other inputs or information gathered by the client device **102** during the message creation process. Example of data filters include current temperature at a specific location, a current speed at which a sending user is traveling, battery life for a client device **102**, or the current time.

(44) Other annotation data that may be stored within the image table **308** is so-called Lenses® data. Lenses® may be a real-time special effect and sound that may be added to an image or a video.

(45) In a social messaging system, content (e.g. images and video clips) may be communicated as part of the messaging. One way of customizing such content is the use of Lenses® which modifies or transforms the content in some way. For example, complex additions or transformations to the content images may be performed using Lenses® data, such as adding rabbit ears to the head of a person in a video clip, adding floating hearts with background coloring to a video clip, altering the proportions of a person's features within a video clip, or many numerous other such transformations. In order to both provide unique user experiences, to provide attribution to Lenses® creators, and to enable creators to protect various aspects of data within the messaging system, the system may provide tools both for users to generate and share such Lenses®, as well as limiting access to such filters in various ways. As described above, Lenses® in accordance with embodiments described herein refer to modifications that may be made to videos or images. This includes both real-time modification which modifies an image as it is captured using a device sensor and then displayed on a screen of the device with the Lenses® modifications. This also includes modifications to stored content, such as video clips in a gallery that may be modified using Lenses®. For example, in a creator profile with multiple Lenses®, an authorized third party account may use a single video clip with multiple Lenses® to see how the different Lenses® will modify the stored clip. Similarly, real-time video capture may be used with Lenses® to show how video images currently being captured by sensors of a device would modify the captured data. Such data may simply be displayed on the screen and not stored in memory, or the content captured by the device sensors may be recorded and stored in memory with or without the Lenses® modifications (or both).

(46) Lenses® data and various systems to use Lenses® and modify content using Lenses® may thus involve detection of objects (e.g. faces, hands, bodies, cats, dogs, surfaces, objects, etc),

tracking of such objects as they leave, enter, and move around the field of view in video frames, and the modification or transformation of such objects as they are tracked. In various embodiments, different methods for achieving such transformations may be used. For example, some embodiments may involve generating a three-dimensional mesh model of the object or objects, and using transformations and animated textures of the model within the video to achieve the transformation. In other embodiments, tracking of points on an object may be used to place an image or texture (which may be two dimensional or three dimensional) at the tracked position. In still further embodiments, neural network analysis of video frames may be used to place images, models, or textures in content (e.g. images or frames of video). Lenses® data thus refers both to the images, models, and textures used to create transformations in content, as well as to additional modeling and analysis information needed to achieve such transformations with object detection, tracking, and placement.

(47) Real time video processing can be performed with any kind of video data, (e.g. video streams, video files, etc.) saved in a memory of a computerized system of any kind. For example, a user can load video files and save them in a memory of a device, or can generate a video stream using sensors of the device. Additionally, any objects can be processed using Lenses®, such as a human's face and parts of a human body, animals, or non-living things such as chairs, cars, or other objects.

(48) In some embodiments, when a Lenses® is selected along with content to be transformed, elements to be transformed by the Lenses® are identified by the computing device, and then detected and tracked if they are present in the frames of the video. The elements of the object are modified according to the request for modification, thus transforming the frames of the video stream. Transformation of frames of a video stream can be performed by different methods for different kinds of transformation. For example, for transformations of frames mostly referring to changing forms of object's elements characteristic points for each of element of an object are calculated (e.g. using an Active Shape Model (ASM) or other known methods). Then, a mesh based on the characteristic points is generated for each of the at least one element of the object. This mesh is used in the following stage of tracking the elements of the object in the video stream. In the process of tracking, the mentioned mesh for each element is aligned with a position of each element. Then, additional points are generated on the mesh. A first set of first points is generated for each element based on a request for modification, and a set of second points is generated for each element based on the set of first points and the request for modification. Then, the frames of the video stream can be transformed by modifying the elements of the object on the basis of the sets of first and second points and the mesh. In such method a background of the modified object can be changed or distorted as well by tracking and modifying the background.

(49) In one or more embodiments, transformations changing some areas of an object using its elements can be performed by calculating of characteristic points for each element of an object and generating a mesh based on the calculated characteristic points. Points are generated on the mesh, and then various areas based on the points are generated. The elements of the object are then tracked by aligning the area for each element with a position for each of the at least one element, and properties of the areas can be modified based on the request for modification, thus transforming the frames of the video stream. Depending on the specific request for modification properties of the mentioned areas can be transformed in different ways. Such modifications may involve: changing color of areas; removing at least some part of areas from the frames of the video stream; including one or more new objects into areas which are based on a request for modification; and modifying or distorting the elements of an area or object. In various embodiments, any combination of such modifications or other similar modifications may be used.

(50) In some embodiments, Lenses® may provide augmented reality (AR) experiences. For example the AR experiences may provide an interactive experience of a real-world environment where the objects within the real-world environment are enhanced by computer-generated information such as video and audio.

(51) In some embodiments of Lenses® using face detection, the face is detected on an image with use of a specific face detection algorithm (e.g. Viola-Jones). Then, an Active Shape Model (ASM) algorithm is applied to the face region of an image to detect facial feature reference points.

(52) In other embodiments, other methods and algorithms suitable for face detection can be used. For example, in some embodiments, features are located using a landmark which represents a distinguishable point present in most of the images under consideration. For facial landmarks, for example, the location of the left eye pupil may be used. In an initial landmark is not identifiable (e.g. if a person has an eyepatch), secondary landmarks may be used. Such landmark identification procedures may be used for any such objects. In some embodiments, a set of landmarks forms a shape. Shapes can be represented as vectors using the coordinates of the points in the shape. One shape is aligned to another with a similarity transform (allowing translation, scaling, and rotation) that minimizes the average Euclidean distance between shape points. The mean shape is the mean of the aligned training shapes.

(53) In some embodiments, a search for landmarks from the mean shape aligned to the position and size of the face determined by a global face detector is started. Such a search then repeats the steps of suggesting a tentative shape by adjusting the locations of shape points by template matching of the image texture around each point and then conforming the tentative shape to a global shape model until convergence occurs. In some systems, individual template matches are unreliable and the shape model pools the results of the weak template matchers to form a stronger overall classifier. The entire search is repeated at each level in an image pyramid, from coarse to fine resolution.

(54) Embodiments of a transformation system can capture an image or video stream on a client device and perform complex image manipulations locally on a client device such as client device **102** while maintaining a suitable user experience, computation time, and power consumption. The complex image manipulations may include size and shape changes, emotion transfers (e.g., changing a face from a frown to a smile), state transfers (e.g., aging a subject, reducing apparent age, changing gender), style transfers, graphical element application, and any other suitable image or video manipulation implemented by a convolutional neural network that has been configured to execute efficiently on a client device.

(55) In some example embodiments, Lenses® may be used by a system where a user may capture an image or video stream of the user (e.g., a selfie) using a client device **102** having a neural network operating as part of a messaging application **104** operating on the client device **102**. The transform system operating within the messaging application **104** determines the presence of a face within the image or video stream and provides modification icons associated with the Lenses®, or the Lenses® may be present as associated with an interface described herein. The modification icons include changes which may be the basis for modifying the user's face within the image or video stream as part of the Lenses® operation. Once a modification icon is selected, the transform system initiates a process to convert the image of the user to reflect the selected modification icon (e.g., generate a smiling face on the user). In some embodiments, a modified image or video stream may be presented in a graphical user interface displayed on the mobile client device as soon as the image or video stream is captured and a specified modification is selected. The transform system may implement a complex convolutional neural network on a portion of the image or video stream to generate and apply the selected modification. That is, the user may capture the image or video stream and be presented with a modified result in real time or near real time once a modification icon has been selected. Further, the modification may be persistent while the video stream is being captured and the selected modification icon remains toggled. Machine taught neural networks may be used to enable such modifications.

(56) In some embodiments, the graphical user interface, presenting the modification performed by the transform system, may supply the user with additional interaction options. Such options may be based on the interface used to initiate the content capture and Lenses® selection (e.g. initiation

from a content creator user interface) In various embodiments, a modification may be persistent after an initial selection of a modification icon. The user may toggle the modification on or off by tapping or otherwise selecting the face being modified by the transformation system. and store it for later viewing or browse to other areas of the imaging application. Where multiple faces are modified by the transformation system, the user may toggle the modification on or off globally by tapping or selecting a single face modified and displayed within a graphical user interface. In some embodiments, individual faces, among a group of multiple faces, may be individually modified or such modifications may be individually toggled by tapping or selecting the individual face or a series of individual faces displayed within the graphical user interface.

(57) As mentioned above, the video table **310** stores video data which, in one embodiment, is associated with messages for which records are maintained within the message table **314**. Similarly, the image table **308** stores image data associated with messages for which message data is stored in the entity table **302**. The entity table **302** may associate various annotations from the annotation table **312** with various images and videos stored in the image table **308** and the video table **310**.

(58) A story table **306** stores data regarding collections of messages and associated image, video, or audio data, which are compiled into a collection (e.g., a story or a gallery). The creation of a particular collection may be initiated by a particular user (e.g., each user for which a record is maintained in the entity table **302**). A user may create a “personal story” in the form of a collection of content that has been created and sent/broadcast by that user. To this end, the user interface of the messaging client application **104** may include an icon that is user-selectable to enable a sending user to add specific content to his or her personal story.

(59) A collection may also constitute a “live story,” which is a collection of content from multiple users that is created manually, automatically, or using a combination of manual and automatic techniques. For example, a “live story” may constitute a curated stream of user-submitted content from various locations and events. Users whose client devices have location services enabled and are at a common location event at a particular time may, for example, be presented with an option, via a user interface of the messaging client application **104**, to contribute content to a particular live story. The live story may be identified to the user by the messaging client application **104**, based on his or her location. The end result is a “live story” told from a community perspective.

(60) A further type of content collection is known as a “location story”, which enables a user whose client device **102** is located within a specific geographic location (e.g., on a college or university campus) to contribute to a particular collection. In some embodiments, a contribution to a location story may require a second degree of authentication to verify that the end user belongs to a specific organization or other entity (e.g., is a student on the university campus).

(61) FIG. 4 is a schematic diagram illustrating a structure of a message **400**, according to some in some embodiments, generated by a messaging client application **104** for communication to a further messaging client application **204** or the messaging server application **114**. The content of a particular message **400** is used to populate the message table **314** stored within the database **120**, accessible by the messaging server application **114**. Similarly, the content of a message **400** is stored in memory as “in-transit” or “in-flight” data of the client device **102** or the application server **112**. The message **400** is shown to include the following components: A message identifier **402**: a unique identifier that identifies the message **400**. A message text payload **406**: text, to be generated by a user via a user interface of the client device **102** and that is included in the message **400**. A message image payload **408**: image data, captured by a camera component of a client device **102** or retrieved from a memory component of a client device **102**, and that is included in the message **400**. A message video payload **412**: video data, captured by a camera component or retrieved from a memory component of the client device **102** and that is included in the message **400**. A message audio payload **416**: audio data, captured by a microphone or retrieved from a memory component of the client device **102**, and that is included in the message **400**. A message annotations **420**: annotation data (e.g., filters, stickers or other enhancements) that represents annotations to be

applied to message image payload **408**, message video payload **412**, or message audio payload **416** of the message **400**. A message duration parameter **424**: parameter value indicating, in seconds, the amount of time for which content of the message (e.g., the message image payload **408**, message video payload **412**, message audio payload **416**) is to be presented or made accessible to a user via the messaging client application **104**. A message geolocation parameter **426**: geolocation data (e.g., latitudinal and longitudinal coordinates) associated with the content payload of the message. Multiple message geolocation parameter **426** values may be included in the payload, each of these parameter values being associated with respect to content items included in the content (e.g., a specific image into within the message image payload **408**, or a specific video in the message video payload **412**). A message story identifier **428**: identifier values identifying one or more content collections (e.g., “stories”) with which a particular content item in the message image payload **408** of the message **400** is associated. For example, multiple images within the message image payload **408** may each be associated with multiple content collections using identifier values. A message tag **430**: each message **400** may be tagged with multiple tags, each of which is indicative of the subject matter of content included in the message payload. For example, where a particular image included in the message image payload **408** depicts an animal (e.g., a lion), a tag value may be included within the message tag **430** that is indicative of the relevant animal. Tag values may be generated manually, based on user input, or may be automatically generated using, for example, image recognition. A message sender identifier **432**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** on which the message **400** was generated and from which the message **400** was sent A message receiver identifier **434**: an identifier (e.g., a messaging system identifier, email address, or device identifier) indicative of a user of the client device **102** to which the message **400** is addressed.

(62) The contents (e.g., values) of the various components of message **400** may be pointers to locations in tables within which content data values are stored. For example, an image value in the message image payload **408** may be a pointer to (or address of) a location within an image table **414**. Similarly, values within the message video payload **412** may point to data stored within a video table **418**, values stored within the message annotations **420** may point to data stored in an annotation table **422**, values stored within the message story identifier **428** may point to data stored in a story table **410**, and values stored within the message sender identifier **432** and the message receiver identifier **434** may point to user records stored within an entity table **404**.

(63) FIG. 5 is a schematic diagram illustrating an access-limiting process **500**, in terms of which access to content (e.g., an ephemeral message **502**, and associated multimedia payload of data) or a content collection (e.g., an ephemeral message group **506**) may be time-limited (e.g., made ephemeral).

(64) An ephemeral message **502** is shown to be associated with a message duration parameter **508**, the value of which determines an amount of time that the ephemeral message **502** will be displayed to a receiving user of the ephemeral message **502** by the messaging client application **104**. In one embodiment, an ephemeral message **502** is viewable by a receiving user for up to a maximum of 10 seconds, depending on the amount of time that the sending user specifies using the message duration parameter **508**.

(65) The message duration parameter **508** and the message receiver identifier **518** are shown to be inputs to a message timer **514**, which is responsible for determining the amount of time that the ephemeral message **502** is shown to a particular receiving user identified by the message receiver identifier **518**. In particular, the ephemeral message **502** will only be shown to the relevant receiving user for a time period determined by the value of the message duration parameter **508**. The message timer **514** is shown to provide output to a more generalized ephemeral timer system **504**, which is responsible for the overall timing of display of content (e.g., an ephemeral message **502**) to a receiving user.

(66) The ephemeral message **502** is shown in FIG. 5 to be included within an ephemeral message

group **506** (e.g., a collection of messages in a personal story, or an event story). The ephemeral message group **506** has an associated group duration parameter **510**, a value of which determines a time-duration for which the ephemeral message group **506** is presented and accessible to users of the messaging system **100**. The group duration parameter **510**, for example, may be the duration of a music concert, where the ephemeral message group **506** is a collection of content pertaining to that concert. Alternatively, a user (either the owning user or a curator user) may specify the value for the group duration parameter **510** when performing the setup and creation of the ephemeral message group **506**.

(67) Additionally, each ephemeral message **502** within the ephemeral message group **506** has an associated group participation parameter **512**, a value of which determines the duration of time for which the ephemeral message **502** will be accessible within the context of the ephemeral message group **506**. Accordingly, a particular ephemeral message group **506** may “expire” and become inaccessible within the context of the ephemeral message group **506**, prior to the ephemeral message group **506** itself expiring in terms of the group duration parameter **510**. The group duration parameter **510**, group participation parameter **512**, and message receiver identifier **518** each provide input to a group timer **516**, which operationally determines, firstly, whether a particular ephemeral message **502** of the ephemeral message group **506** will be displayed to a particular receiving user and, if so, for how long. Note that the ephemeral message group **506** is also aware of the identity of the particular receiving user as a result of the message receiver identifier **518**.

(68) Accordingly, the group timer **516** operationally controls the overall lifespan of an associated ephemeral message group **506**, as well as an individual ephemeral message **502** included in the ephemeral message group **506**. In one embodiment, each and every ephemeral message **502** within the ephemeral message group **506** remains viewable and accessible for a time-period specified by the group duration parameter **510**. In a further embodiment, a certain ephemeral message **502** may expire, within the context of ephemeral message group **506**, based on a group participation parameter **512**. Note that a message duration parameter **508** may still determine the duration of time for which a particular ephemeral message **502** is displayed to a receiving user, even within the context of the ephemeral message group **506**. Accordingly, the message duration parameter **508** determines the duration of time that a particular ephemeral message **502** is displayed to a receiving user, regardless of whether the receiving user is viewing that ephemeral message **502** inside or outside the context of an ephemeral message group **506**.

(69) The ephemeral timer system **504** may furthermore operationally remove a particular ephemeral message **502** from the ephemeral message group **506** based on a determination that it has exceeded an associated group participation parameter **512**. For example, when a sending user has established a group participation parameter **512** of 24 hours from posting, the ephemeral timer system **504** will remove the relevant ephemeral message **502** from the ephemeral message group **506** after the specified 24 hours. The ephemeral timer system **504** also operates to remove an ephemeral message group **506** either when the group participation parameter **512** for each and every ephemeral message **502** within the ephemeral message group **506** has expired, or when the ephemeral message group **506** itself has expired in terms of the group duration parameter **510**.

(70) In certain use cases, a creator of a particular ephemeral message group **506** may specify an indefinite group duration parameter **510**. In this case, the expiration of the group participation parameter **512** for the last remaining ephemeral message **502** within the ephemeral message group **506** will determine when the ephemeral message group **506** itself expires. In this case, a new ephemeral message **502**, added to the ephemeral message group **506**, with a new group participation parameter **512**, effectively extends the life of an ephemeral message group **506** to equal the value of the group participation parameter **512**.

(71) Responsive to the ephemeral timer system **504** determining that an ephemeral message group **506** has expired (e.g., is no longer accessible), the ephemeral timer system **504** communicates with

the messaging system **100** (and, for example, specifically the messaging client application **104** to cause an indicium (e.g., an icon) associated with the relevant ephemeral message group **506** to no longer be displayed within a user interface of the messaging client application **104**. Similarly, when the ephemeral timer system **202** determines that the message duration parameter **508** for a particular ephemeral message **502** has expired, the ephemeral timer system **504** causes the messaging client application **104** to no longer display an indicium (e.g., an icon or textual identification) associated with the ephemeral message **502**.

(72) FIG. **6** is a block diagram illustrating components of the contextual media filter system **124** that configure the contextual media filter system **124** to capture an image frame that includes a depiction of an object from a client device **102**, identify one or more objects within the image frame based on the depiction of the object, identify one or more image features based on the object, retrieve a set of media content based on the image features, and cause display of a presentation of the set of media content within the image frame at the client device **102**, according to some example embodiments.

(73) The contextual media filter system **124** is shown as including a presentation system **604**, image feature computation system **606**, a search system **608**, and a geometric verification system **610**, all configured to communicate with each other (e.g., via bus, shared memory, or a switch). Any one or more of these systems may be implemented using one or more processors (e.g., by configuring such one or more processors to preform functions described for that system and hence may include one or more processors).

(74) Any one or more of the systems described may be implemented using hardware alone (e.g., one or more of the processors of a machine) or a combination of hardware and software. For example, any system described of the contextual media filter system **124** may physically include an arrangement of one or more of the processors (e.g., a subset of or among the one or more processors of the machine) configured to perform the operations described herein for that system. As another example, any system of the contextual media filter system **124** may include software, hardware, or both, that configure an arrangement of one or more processors (e.g., among the one or more processors of the machine) to perform the operations described herein for that system. Accordingly, different systems of the contextual media filter system **124** may include and configure different arrangements of such processors or a single arrangement of such processors at different points in time. Moreover, any two or more systems of the contextual media filter system **124** may be combined into a single system, and the functions described herein for a single system may be subdivided among multiple systems. Furthermore, according to various example embodiments, systems described herein as being implemented within a single machine, database, or device may be distributed across multiple machines, databases, or devices.

(75) FIG. **7** is a flowchart depicting a method **700** of causing display of a contextual media filter at a client device **102**, according to certain example embodiments. Operations of the method **700** may be performed by the systems described above with respect to FIG. **6**. As showing in FIG. **7**, the method **700** includes one or more operations **702**, **704**, **706**, **708**, and **710**.

(76) At operation **702** the communication system **602** receives an input from the client device **102**. In some embodiments, the client device **102** includes a touch-screen display configured to receive tactile inputs. The input may therefore include a tactile input onto a display of the client device **102**, wherein the tactile input provides an indication of a point or position within the graphical user interface (GUI). For example, a user of the client device **102** may provide an input to identify a location or object depicted within the GUI by providing a tactile input onto a location along the display that corresponds with a position of the location or object within the GUI.

(77) In some embodiments, the input may comprise one or more input properties that include an input pressure, an input duration, and an input location. In such embodiments, the communication system **602** may compare one or more of the input properties against a set of threshold values. For example, responsive to detecting an input property transgress a threshold value, the communication

system **602** may signal one or more systems of the contextual media filter system **124** to perform certain follow-up actions or operations.

(78) At operation **704**, the presentation system **604** causes display of a GUI at the client device **102**, where the GUI comprises a display of live camera data streamed from a camera of or associated with the client device **102**. For example, the client device **102** may include a plurality of cameras such as one or more “front-facing” cameras, and one or more “back-facing” cameras, configured to capture and stream image data. The live camera data generated by the one or more cameras associated with the client device **102** may include image data that comprises a plurality of image features.

(79) At operation **706** the image feature computation system **606** identifies the object within the image frame. The contextual media filter system **124** compares media content within the media repository (e.g., a database) and select those media content which are most visually similar to the object within the image frame. The visual similarity comparison is a unified abstraction and representation of the media content such that the similarity between two media content captured under, for example, different resolutions, angles, illuminations and other factors can be computed using the representation.

(80) The image feature computation system **606** identifies local features that are computed from specific regions within the image frame. The local features are stored in an indexing structure. An indexing structure is a data structure that makes searching a database more efficient. Therefore, querying an index is faster than searching each row in a database.

(81) Each local feature is further analyzed to compute global features of the image frame. Global features are computed from the entire image frame, not specific regions within the image frame. In one example, the global features are computed by quantizing local features of the image frame. Quantization involved in image processing is a technique achieved by compressing a range of values to a single value. The global features are computed by mapping each local feature to a representative feature in a set of representative features. Each representative feature may be referred to as a “word.” The global feature is computed by counting an occurrence of each representative feature in the set of representative features.

(82) For example, a set of representative features may be (A, B, C, D, . . .). The image feature computation system **606** may have computed 5 local features from the image. Two local features are mapped to “word” A, and 3 local features are mapped to “word” D. The global feature can be represented as “2AOBOC3D.”

(83) At operation **708**, the search system **608** accesses media content associated with the object with the media repository in response to identifying the object. The search system **608** uses the global feature to search for media content within the indexing structure to retrieve media content from the media repository associated with object. In some examples, the search system **608** uses the k-nearest neighbors algorithm in performing the search.

(84) At operation **708**, the contextual media filter system **124** further verifies the media content using the geometric verification system **610**. The media content returned by the search performed by the search system **608** may contain false media content matches that are not visually similar to the original object within the image frame. The geometric verification system **610** may use a similarity metric in determining whether a media content item is similar to the original object. The similarity metric may relate to a geometric constraint associated with the geometry of the original object. Therefore, the geometric verification system **610** identifies false media content using geometric verification and removes the false media content from the media content.

(85) At operation **710**, the presentation system **604** causes presentation of the media content within the image frame at the client device **102**. For example, the presentation of the set of media content may include an AR display of the set of media content, such that the retrieved media content appears to interact with elements depicted within the image frame, in real time.

(86) In some embodiments, to generate the presentation of the media content, the presentation

system **604** retrieves a media template, wherein the media template defines a presentation format and layout to be applied to the set of media content. For example, the media template may define positions and orientations to present the media content within the image frame, at the client device **102**. The media content may be tagged with location information or temporal information within the media repository, such that reference to a particular time of day, season, day of week, month, or place, may identify a set of relevant media content.

(87) FIG. **8** is a diagrammatic illustration of an object **800** within an image frame at a client device. In some examples the object is a custom image that can be tracked within the image frame.

(88) FIG. **9** is a diagrammatic illustrations of a contextual media filter system **124** within a user interface **900** of a client device **102**. The contextual media filter system **124** may be initialized by initiating a scan of the image frame. Once the contextual media filter system **124** determines the media content associated with the object within the image frame, the contextual media filter system **124** may display a set of media content **902** that a user of a client device may swipe to select.

(89) Reference in the specification to “one embodiment” or “an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present subject matter. Thus, the appearances of the phrase “in one embodiment” or “in an embodiment” appearing in various places throughout the specification are not necessarily all referring to the same embodiment.

(90) FIG. **10** is a block diagram **1000** illustrating a software architecture **1004**, which can be installed on any one or more of the devices described herein. The software architecture **1004** is supported by hardware such as a machine **1002** that includes processors **1020**, memory **1026**, and I/O components **1038**. In this example, the software architecture **1004** can be conceptualized as a stack of layers, where each layer provides a particular functionality. The software architecture **1004** includes layers such as an operating system **1012**, libraries **1010**, frameworks **1008**, and applications **1006**. Operationally, the applications **1006** invoke API calls **1050** through the software stack and receive messages **1052** in response to the API calls **1050**.

(91) The operating system **1012** manages hardware resources and provides common services. The operating system **1012** includes, for example, a kernel **1014**, services **1016**, and drivers **1022**. The kernel **1014** acts as an abstraction layer between the hardware and the other software layers. For example, the kernel **1014** provides memory management, processor management (e.g., scheduling), component management, networking, and security settings, among other functionality. The services **1016** can provide other common services for the other software layers. The drivers **1022** are responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1022** can include display drivers, camera drivers, BLUETOOTH® or BLUETOOTH® Low Energy drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), WI-FI® drivers, audio drivers, power management drivers, and so forth.

(92) The libraries **1010** provide a low-level common infrastructure used by the applications **1006**. The libraries **1010** can include system libraries **1018** (e.g., C standard library) that provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1010** can include API libraries **1024** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as Moving Picture Experts Group-4 (MPEG4), Advanced Video Coding (H.264 or AVC), Moving Picture Experts Group Layer-3 (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR) audio codec, Joint Photographic Experts Group (JPEG or JPG), or Portable Network Graphics (PNG)), graphics libraries (e.g., an OpenGL framework used to render in two dimensions (2D) and three dimensions (3D) in a graphic content on a display), database libraries (e.g., SQLite to provide various relational database functions), web libraries (e.g., WebKit to provide web browsing functionality), and the like. The libraries **1010** can also include a wide variety of other libraries **1028** to provide many other APIs to the applications **1006**.

(93) The frameworks **1008** provide a high-level common infrastructure that is used by the

applications **1006**. For example, the frameworks **1008** provide various graphical user interface (GUI) functions, high-level resource management, and high-level location services. The frameworks **1008** can provide a broad spectrum of other APIs that can be used by the applications **1006**, some of which may be specific to a particular operating system or platform.

(94) In an example embodiment, the applications **1006** may include a home application **1036**, a contacts application **1030**, a browser application **1032**, a book reader application **1034**, a location application **1042**, a media application **1044**, a messaging application **1046**, a game application **1048**, and a broad assortment of other applications such as third-party applications **1040**. The applications **1006** are programs that execute functions defined in the programs. Various programming languages can be employed to create one or more of the applications **1006**, structured in a variety of manners, such as object-oriented programming languages (e.g., Objective-C, Java, or C++) or procedural programming languages (e.g., C or assembly language). In a specific example, the third-party applications **1040** (e.g., applications developed using the ANDROID™ or IOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as IOS™, ANDROID™, WINDOWS® Phone, or another mobile operating system. In this example, the third-party applications **1040** can invoke the API calls **1050** provided by the operating system **1012** to facilitate functionality described herein.

(95) FIG. **11** is a diagrammatic representation of a machine **1100** within which instructions **1108** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1100** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1108** may cause the machine **1100** to execute any one or more of the methods described herein. The instructions **1108** transform the general, non-programmed machine **1100** into a particular machine **1100** programmed to carry out the described and illustrated functions in the manner described. The machine **1100** may operate as a standalone device or may be coupled (e.g., networked) to other machines. In a networked deployment, the machine **1100** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1100** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), a PDA, an entertainment media system, a cellular telephone, a smart phone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), other smart devices, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1108**, sequentially or otherwise, that specify actions to be taken by the machine **1100**. Further, while only a single machine **1100** is illustrated, the term “machine” shall also be taken to include a collection of machines that individually or jointly execute the instructions **1108** to perform any one or more of the methodologies discussed herein.

(96) The machine **1100** may include processors **1102**, memory **1104**, and I/O components **1142**, which may be configured to communicate with each other via a bus **1144**. In an example embodiment, the processors **1102** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an ASIC, a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1106** and a processor **1110** that execute the instructions **1108**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **11** shows multiple processors **1102**, the machine **1100** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(97) The memory **1104** includes a main memory **1112**, a static memory **1114**, and a storage unit

1116, both accessible to the processors **1102** via the bus **1144**. The main memory **1104**, the static memory **1114**, and storage unit **1116** store the instructions **1108** embodying any one or more of the methodologies or functions described herein. The instructions **1108** may also reside, completely or partially, within the main memory **1112**, within the static memory **1114**, within machine-readable medium **1118** within the storage unit **1116**, within at least one of the processors **1102** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1100**.

(98) The I/O components **1142** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1142** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones may include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1142** may include many other components that are not shown in FIG. **11**. In various example embodiments, the I/O components **1142** may include output components **1128** and input components **1130**. The output components **1128** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **1130** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point-based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or another pointing instrument), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(99) In further example embodiments, the I/O components **1142** may include biometric components **1132**, motion components **1134**, environmental components **1136**, or position components **1138**, among a wide array of other components. For example, the biometric components **1132** include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram-based identification), and the like. The motion components **1134** include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environmental components **1136** include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detection concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1138** include location sensor components (e.g., a GPS receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(100) Communication may be implemented using a wide variety of technologies. The I/O components **1142** further include communication components **1140** operable to couple the machine **1100** to a network **1120** or devices **1122** via a coupling **1124** and a coupling **1126**, respectively. For example, the communication components **1140** may include a network interface component or another suitable device to interface with the network **1120**. In further examples, the communication

components **1140** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), WiFi® components, and other communication components to provide communication via other modalities. The devices **1122** may be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(101) Moreover, the communication components **1140** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1140** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1140**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

(102) The various memories (e.g., memory **1104**, main memory **1112**, static memory **1114**, and/or memory of the processors **1102**) and/or storage unit **1116** may store one or more sets of instructions and data structures (e.g., software) embodying or used by any one or more of the methodologies or functions described herein. These instructions (e.g., the instructions **1108**), when executed by processors **1102**, cause various operations to implement the disclosed embodiments.

(103) The instructions **1108** may be transmitted or received over the network **1120**, using a transmission medium, via a network interface device (e.g., a network interface component included in the communication components **1140**) and using any one of a number of well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1108** may be transmitted or received using a transmission medium via the coupling **1126** (e.g., a peer-to-peer coupling) to the devices **1122**.

Claims

1. A computer-implemented method comprising: capturing an image frame at a client device, the image frame comprising a depiction of an object; identifying the object within the image frame, the identifying the object within the image frame comprising: identifying a first set of image features within the image frame; storing the first set of features in an indexing structure; identifying a second set of image features based on the first set of image features by mapping each feature in the first set of image features to a representative feature in a set of representative features; searching the indexing structure using the second set of image features; accessing media content associated with the object in response to identifying the object within the image frame; verifying the accessed media content based on a geometric constraint associated with a geometry of the object; accessing a media template, the media template defining a set of presentation positions within a graphical user interface of the client device, the set of presentation positions corresponding to presentation positions of the accessed media content; and in response to verifying the accessed media content, causing presentation of the media content within the image frame at the client device based on the accessed media template.
2. The method of claim 1, wherein defining the set of presentation positions comprises defining one or both of a presentation format and a layout of the accessed media content.
3. The method of claim 2, wherein defining the set of presentation positions comprises defining an orientation of the accessed media content.
4. The method of claim 1, wherein the accessed media content comprises a plurality of augmented

reality experience selections.

5. The method of claim 4, wherein the plurality of augmented reality experience selections are configured to interact with the object within the image frame in real time.

6. The method of claim 4, wherein the plurality of augmented reality experience selections is associated with a plurality of special effects, respectively.

7. The method of claim 1, further comprising: receiving an initiation of an input comprising a tactile input onto the graphical user interface of the client device; detecting that a property of the tactile input transgresses a threshold value; and capturing the image frame in response to the property of the tactile input transgressing the threshold value.

8. The method of claim 1, wherein the first set of features are local features identified within predefined regions within the image frame.

9. The method of claim 1, wherein the second set of image features are global features identified using an entirety of the image frame.

10. The method of claim 1, wherein the image frame is received from a messaging application on the client device.

11. A system comprising: a processor; and a memory storing instructions that, when executed by the processor, configure the processor to perform operations comprising: capturing an image frame at a client device, the image frame comprising a depiction of an object; identifying the object within the image frame, the identifying the object within the image frame comprising: identifying a first set of image features within the image frame; storing the first set of features in an indexing structure; identifying a second set of image features based on the first set of image features by mapping each feature in the first set of image features to a representative feature in a set of representative features; searching the indexing structure using the second set of image features; accessing media content associated with the object in response to identifying the object within the image frame; verifying the accessed media content based on a geometric constraint associated with a geometry of the object; accessing a media template, the media template defining a set of presentation positions within a graphical user interface of the client device, the set of presentation positions corresponding to presentation positions of the accessed media content; and in response to verifying the accessed media content, causing presentation of the media content within the image frame at the client device based on the accessed media template.

12. The system of claim 11, wherein defining the set of presentation positions comprises defining one or both of a presentation format and a layout of the accessed media content, wherein defining the set of presentation positions comprises defining one or both of a presentation format and a layout of the accessed media content.

13. The system of claim 12, wherein defining the set of presentation positions comprises defining an orientation of the accessed media content.

14. The system of claim 11, wherein the accessed media content comprises a plurality of augmented reality experience selections.

15. The system of claim 14, wherein the plurality of augmented reality experience selections are configured to interact with the object within the image frame in real time.

16. The system of claim 14, wherein the plurality of augmented reality experience selections is associated with a plurality of special effects, respectively.

17. The system of claim 11, further comprising: receiving an initiation of an input comprising a tactile input onto the graphical user interface of the client device; detecting that a property of the tactile input transgresses a threshold value; and capturing the image frame in response to the property of the tactile input transgressing the threshold value.

18. The system of claim 11, wherein the first set of features are local features identified within predefined regions within the image frame.

19. The system of claim 11, wherein the second set of image features are global features identified using an entirety of the image frame.

20. A non-transitory machine-readable storage medium comprising instructions that, when executed by one or more processors of a machine, cause the machine to perform operations comprising: capturing an image frame at a client device, the image frame comprising a depiction of an object; identifying the object within the image frame, the identifying the object within the image frame comprising: identifying a first set of image features within the image frame; storing the first set of features in an indexing structure; identifying a second set of image features based on the first set of image features by mapping each feature in the first set of image features to a representative feature in a set of representative features; searching the indexing structure using the second set of image features; accessing media content associated with the object in response to identifying the object within the image frame; verifying the accessed media content based on a geometric constraint associated with a geometry of the object; accessing a media template, the media template defining a set of presentation positions within a graphical user interface of the client device, the set of presentation positions corresponding to presentation positions of the accessed media content; and in response to verifying the accessed media content, causing presentation of the media content within the image frame at the client device based on the accessed media template.
