

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12400919
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Hammerschmidt; Dirk

Pressure sensors on flexible substrates for stress decoupling

Abstract

A semiconductor device includes a semiconductor chip including a chip substrate and a MEMS element, wherein the chip substrate includes a first surface and a second surface arranged opposite to the first surface, and wherein the MEMS element is disposed at the first surface of the chip substrate and the MEMS element includes a sensitive area; at least one electrical interconnect structure electrically connected to the first surface of the chip substrate; a chip carrier electrically connected to the at least one electrical interconnect structure; a flexible film provided over the second surface of the chip substrate to form a pocket in which the semiconductor chip resides; and a compressible material arranged between the second surface of the chip substrate and the flexible film.

Inventors:	Hammerschmidt; Dirk (Finkenstein, AT)
Applicant:	Infineon Technologies AG (Neubiberg, DE)
Family ID:	1000008777494
Assignee:	Infineon Technologies AG (Neubiberg, DE)
Appl. No.:	17/851284
Filed:	June 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220328369 A1	Oct. 13, 2022

Related U.S. Application Data

continuation parent-doc US 17143332 20210107 US 11443992 child-doc US 17851284
continuation parent-doc US 16910595 20200624 US 10910283 20210202 child-doc US 17143332
continuation parent-doc US 16294208 20190306 US 10777474 20200915 child-doc US 16910595

Publication Classification

Int. Cl.: H01L23/053 (20060101)

U.S. Cl.:

CPC H01L23/053 (20130101); B81B2201/0264 (20130101)

Field of Classification Search

CPC: H01L (23/053)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5825091	12/1997	Adams	N/A	N/A
6426687	12/2001	Osborn	333/262	H01P 1/127
6869825	12/2004	Chiu	N/A	N/A
7141989	12/2005	Liu	324/661	H01G 5/16
7154175	12/2005	Shrivastava et al.	N/A	N/A
7843021	12/2009	Zhe et al.	N/A	N/A
8552473	12/2012	Tateishi et al.	N/A	N/A
8625832	12/2013	Lillelund	N/A	N/A
9360318	12/2015	Pun et al.	N/A	N/A
10777474	12/2019	Hammerschmidt	N/A	N/A
10910283	12/2020	Hammerschmidt	N/A	N/A
11443992	12/2021	Hammerschmidt	N/A	N/A
2004/0124527	12/2003	Chiu	N/A	N/A
2006/0223227	12/2005	Kubota et al.	N/A	N/A
2007/0013036	12/2006	Zhe et al.	N/A	N/A
2008/0083960	12/2007	Chen	438/51	H04R 1/04
2009/0218668	12/2008	Zhe et al.	N/A	N/A
2014/0342203	12/2013	Elian	N/A	N/A
2015/0353345	12/2014	Heuck et al.	N/A	N/A
2016/0137488	12/2015	Jiang et al.	N/A	N/A
2016/0209285	12/2015	Nakajima	N/A	N/A
2017/0016788	12/2016	Ned et al.	N/A	N/A
2017/0176278	12/2016	Chen et al.	N/A	N/A
2018/0148316	12/2017	Duqi et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
19804748	12/1997	DE	N/A
2017194417	12/2016	WO	N/A

Primary Examiner: Booth; Richard A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/143,332 filed on Jan. 7, 2021, which is a continuation of U.S. patent application Ser. No. 16/910,595 filed on Jun. 24, 2020, now U.S. Pat. No. 10,910,283 issued Feb. 2, 2021, which is a continuation of U.S. patent application Ser. No. 16/294,208 filed Mar. 6, 2019, now U.S. Pat. No. 10,777,474 issued Sep. 15, 2020, which are incorporated by reference as if fully set forth.

FIELD

(1) The present disclosure relates generally to semiconductor devices and a method of manufacturing the same, and, more particularly, microelectromechanical systems (MEMS) elements with a stress relief mechanism.

BACKGROUND

(2) Microelectromechanical system (MEMS) are microscopic devices, particularly those with moving parts. MEMS became practical once they could be fabricated using modified semiconductor device fabrication technologies, normally used to make electronics. Thus, a MEMS may be built into a substrate as a component of an integrated circuit, that is diced into a semiconductor chip that is subsequently mounted in a package.

(3) Mechanical stress and other external mechanical influences introduced to a package may inadvertently be transferred through the package to an integrated MEMS element, such as sensor, and, more particularly, to a pressure sensor. This transferred mechanical stress may affect the operation of the MEMS element or induce an shift (e.g., an offset) in a sensor signal that may lead to incorrect measurements.

(4) For example, semiconductor pressure sensors have a pressure sensitive element arranged to measure an absolute pressure or a relative pressure (e.g. the difference between two pressures). A problem with many pressure sensors is that the sensor measures (or outputs, or gives) a signal, even in the absence of a pressure (or pressure difference) to be measured. This offset may be the result of mechanical stress and/or deformation of the housing (e.g., the packaging) of the sensor. The housing-stress/deformation will typically also cause a stress-component at the sensor surface where the sensitive elements (e.g., piezo-resistors) are located, and thereby cause an offset error, a linearity error, or even a hysteresis error to the output signal.

(5) Therefore, an improved device capable of decoupling mechanical stress from an integrated MEMS element may be desirable.

SUMMARY

(6) One or more embodiments provide a semiconductor device that includes a semiconductor chip including a substrate having a first surface and a second surface arranged opposite to the first surface; and a microelectromechanical systems (MEMS) element, including a sensitive area, disposed at the first surface of the substrate. The semiconductor device further includes at least one electrical interconnect structure electrically connected to the first surface of the substrate, and a flexible carrier electrically connected to the at least one electrical interconnect structure, where the flexible carrier wraps around the semiconductor chip and extends over the second surface of the substrate such that a folded cavity is formed around the semiconductor chip.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments are described herein making reference to the appended drawings.
- (2) FIG. 1 shows a cross-sectional diagram of a pressure sensor package according to one or more embodiments;
- (3) FIGS. 2A-2C show a cross-sectional diagram of a pressure sensor package according to one or more embodiments;
- (4) FIG. 3 shows a cross-sectional diagram of a pressure sensor package according to one or more embodiments;
- (5) FIG. 4 shows a cross-sectional diagram of a pressure sensor package according to one or more embodiments;
- (6) FIG. 5 shows a cross-sectional diagram of a pressure sensor package according to one or more embodiments;
- (7) FIG. 6 shows a top view of the pressure sensor package shown in FIG. 1; and
- (8) FIG. 7 shows a top view of the pressure sensor package according to one or more embodiments.

DETAILED DESCRIPTION

- (9) In the following, various embodiments will be described in detail referring to the attached drawings, where like reference numerals refer to like elements throughout. It should be noted that these embodiments serve illustrative purposes only and are not to be construed as limiting. For example, while embodiments may be described as comprising a plurality of features or elements, this is not to be construed as indicating that all these features or elements are needed for implementing embodiments. Instead, in other embodiments, some of the features or elements may be omitted, or may be replaced by alternative features or elements. Additionally, further features or elements in addition to the ones explicitly shown and described may be provided, for example conventional components of sensor devices.
- (10) Features from different embodiments may be combined to form further embodiments, unless specifically noted otherwise. Variations or modifications described with respect to one of the embodiments may also be applicable to other embodiments. In some instances, well-known structures and devices are shown in block diagram form rather than in detail in order to avoid obscuring the embodiments.
- (11) Further, equivalent or like elements or elements with equivalent or like functionality are denoted in the following description with equivalent or like reference numerals. As the same or functionally equivalent elements are given the same reference numbers in the figures, a repeated description for elements provided with the same reference numbers may be omitted. Hence, descriptions provided for elements having the same or like reference numbers are mutually exchangeable.
- (12) In this regard, directional terminology, such as “top”, “bottom”, “front”, “behind”, “back”, “leading”, “trailing”, “below”, “above” etc., may be used with reference to the orientation of the figures being described. Because parts of embodiments can be positioned in a number of different orientations, the directional terminology is used for purposes of illustration and is in no way limiting. It is to be understood that other embodiments may be utilized and structural or logical changes may be made without departing from the scope defined by the claims. The following detailed description, therefore, is not to be taken in a limiting sense.
- (13) It will be understood that when an element is referred to as being “connected” or “coupled” to another element, it can be directly connected or coupled to the other element or intervening elements may be present. In contrast, when an element is referred to as being “directly connected” or “directly coupled” to another element, there are no intervening elements present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.).
- (14) In embodiments described herein or shown in the drawings, any direct electrical connection or

coupling, i.e., any connection or coupling without additional intervening elements, may also be implemented by an indirect connection or coupling, i.e., a connection or coupling with one or more additional intervening elements, or vice versa, as long as the general purpose of the connection or coupling, for example, to transmit a certain kind of signal or to transmit a certain kind of information, is essentially maintained. Features from different embodiments may be combined to form further embodiments. For example, variations or modifications described with respect to one of the embodiments may also be applicable to other embodiments unless noted to the contrary.

(15) The term “substantially” may be used herein to account for small manufacturing tolerances (e.g., within 5%) that are deemed acceptable in the industry without departing from the aspects of the embodiments described herein.

(16) Embodiments relate to microelectromechanical system (MEMS), and particularly to MEMS pressure sensors, integrated on a semiconductor chip and subsequently mounted to a package. The MEMS may be referred to as a MEMS element, a MEMS cell, or a MEMS device. The side or surface of the chip at which the MEMS element is provided may be referred to as a front side or front surface of the chip, whereas the side or surface of the chip opposite thereto may be referred to as a back side or a back surface of the chip.

(17) The package is adapted to enable the MEMS pressure sensor to detect and/or measure a force imposed thereon. For example, the MEMS pressure sensor may operate as a transducer that generates an electrical signal as a function of the pressure imposed, and the package may have an opening formed in proximity to the MEMS pressure sensor that allows a medium to interact with the MEMS pressure sensor. The medium may be any pressure measurable or pressure inducing entity.

(18) In general, a sensor, as used herein, may refer to a component which converts a physical quantity to be measured to an electric signal, for example a current signal or a voltage signal. The physical quantity may, for example, be pressure as an expression of force imposed on a sensitive area or region of the sensor. Chemicals, humidity, and debris, such as foreign particles, may negatively impact the performance of any sensor. Thus, it is desirable to prevent these and other potential contaminants from reaching the surface of the sensor, and, specifically, from reaching the sensitive area or region of the sensor.

(19) A manufacturing process for semiconductor chip fabrication may include two sequential sub-processes commonly referred to as front-end and back-end production. The back-end production may further include two sequential sub-processes commonly referred to as pre-assembly and assembly.

(20) Front-end production refers primarily to wafer fabrication. A wafer, as used herein, may also be referred to as a substrate. The front-end production may start with a clean disc-shaped silicon wafer that will ultimately become many silicon chips. First, a photomask that defines the circuit patterns for circuit elements (e.g., transistors) and interconnect layers may be created. This mask may then be laid on the clean silicon wafer and is used to map the circuit design. Transistors and other circuit elements may then be formed on the wafer through photolithography.

Photolithography involves a series of steps in which a photosensitive material is deposited on the wafer and exposed to light through a patterned mask; unwanted exposed material is then etched away, leaving only the desired circuit pattern on the wafer. By stacking the various patterns, individual elements of the semiconductor chip may be defined. A MEMS device or MEMS element may also be incorporated onto and/or into the surface of the wafer and connected to one or more circuit elements. During the final phase of the front-end production process, each individual chip on the wafer is electrically tested to identify properly functioning chips for assembly.

(21) Back-end production refers to the assembly and test of individual semiconductor devices or chips. The assembly process is intended to protect the chip, facilitate its integration into electronic systems, limit electrical interference and enable the dissipation of heat from the device. Once the front-end production process is complete, the wafer is sawed or diced into individual

semiconductor chips. This dicing of the wafer into individual semiconductor chips is referred to as pre-assembly.

(22) In an assembly phase of the back-end production, the semiconductor chips are incorporated into a package. For example, these semiconductor chips may be individually attached by means of an alloy or an adhesive to a lead frame, a metallic device used to connect the semiconductor to a circuit board. Leads on the lead frame may then be connected by aluminum or gold wires to the input/output terminals on the semiconductor chip through the use of automated machines known as wire bonders. Each semiconductor device may then be at least partially encapsulated in a plastic molding compound or a ceramic case, forming the package.

(23) Thus, a MEMS element may be built into a substrate as a component of an integrated circuit, the substrate then being diced into semiconductor chips that are each subsequently mounted in a package.

(24) It will be appreciated that while the pre-assembly (i.e., dicing) process may be described as part of the back-end production flow, the chips may be partially singulated during final phase of the front-end production. Thus, in some instances, pre-assembly may begin or may be performed during the front-end production.

(25) According to one or more embodiments, mechanical stress-decoupling is provided to a MEMS element as a stress relief mechanism. A stress-decoupling feature such as one or more trenches (i.e., one or more stress-decoupling trenches) may be provided. In additionally, each stress-decoupling trench is filled with a gel (e.g., a silicone gel) and the gel may additionally be deposited on the MEMS element at the wafer level (i.e., during the front-end production process), or during or subsequent to the pre-assembly process, but prior to assembly (i.e., packaging). The protective material may be deposited on an exposed surface of the MEMS element such that an entire exposed surface of the MEMS element is covered by the protective material.

(26) The exposed surface of the MEMS element may include or may be referred to as a sensitive area that enables the MEMS element to measure a physical quantity. For example, the MEMS element may be a MEMS pressure sensor that is configured to detect or measure a change in pressure in response to a change of force imposed on the exposed surface. The protective material is configured such that, when the MEMS element is covered by the protective material, a sensor functionality of the MEMS element remains intact. For example, the protective material may be a silicone gel that has a viscosity that permits a force exerted thereon to be transferred to the MEMS pressure sensor. Thus, the protective material is flexible enough that when the protective material is depressed, the sensitive area of the MEMS pressure sensor is also depressed proportionally.

(27) More particularly, the protective material permits full sensor functionality of the MEMS element, including mechanical functionality and electrical functionality, while sealing an entire surface of the MEMS element. Even more particularly, the protective material is configured such that no functionality of the MEMS element is impeded by the protective material.

(28) By ensuring that the functionality of the MEMS element remains intact, the protective material may be deposited onto the MEMS element as a permanent material at an early stage of the chip fabrication process. Thus, the MEMS element may already be configured in an operable state (e.g., a final operable state) at the time the protective material is deposited onto the MEMS element, and the protective material may remain completely intact after deposition, including throughout the assembly process, such that it remains a feature in the final product.

(29) As a result of the early deposition of the protective material, the MEMS element is provided early particle and humidity protection from foreign matter that may have been introduced during (pre-)assembly processes that could influence the sensor performance.

(30) While some embodiments provided herein may refer to the protective material as being silicone gel, the protective material is not limited thereto, and may be any material that provides protection from foreign matter while permitting sensor functionality of the MEMS element, and more particularly permits sensor functionality of the MEMS element at the time of deposition of

the protective material. Thus, the protective material may be any material that behaves like a fluid in order to transfer applied pressure to a sensitive membrane of a pressure sensor.

(31) Embodiments include a silicon die on which a MEMS element is integrated, where the silicon die has sufficiently low stress on the MEMS element. The silicon die can be a bare die or a chip size package (CSP) mounted on a flexible carrier that minimizes or prohibits the transfer of mechanical stress to the silicon die, and ultimately to the MEMS element, due to its low mechanical stiffness. The flexible carrier can be a foil printed circuit board (PCB) or a normal PCB with stress relieve structures, such as stress decoupling trenches, that enable the normal PCB to be flexible. Environmental protection is performed by a combination of a protective material (e.g., silicone gel) disposed around the MEMS element with the flexible carrier.

(32) FIG. 1 shows a cross-sectional diagram of a pressure sensor package **100** according to one or more embodiments. The pressure sensor package **100** includes chip **1** bonded to a flexible carrier **2** by bonding balls **3**. The chip **1** may be a bare die or a CSP. Thus, no molding is applied to the package **100** (e.g., to encapsulate the chip). The flexible carrier **2** may be a foil PCB or a normal PCB with stress relieve structures, such as stress decoupling trenches, that enable the normal PCB to be flexible. Thus, the flexible carrier **2** may be referred to as a stress decoupling carrier or substrate. Furthermore, while bonding balls are used in the described examples, it will be appreciated that any electrical interconnect structure may be used to provide contact between the chip **1** and the flexible carrier **2**.

(33) The chip **1** is an integrated circuit (IC) that includes a semiconductor substrate **10** (e.g., a silicon substrate) having a main surface **11** on the front side of the chip **1** and a MEMS element **12** provided at the main surface **11**. The main surface **11** may be referred to as an active chip surface that includes additional circuitry that interfaces with the MEMS element **12**. The bonding balls **3** are coupled to a pad on the main surface **11** of the chip **1** and to the flexible carrier **2**, and is used for carrying electrical signals therebetween. In this arrangement, the chip **1** is assembled face down on the flexible carrier **2** such that a sensitive area of the MEMS element **12** faces towards the flexible carrier.

(34) The MEMS element **12** is a pressure sensor arranged at the main surface **11** such that the MEMS element **12** is capable of sensing a change in pressure applied thereto. Thus, the MEMS element **12** includes a sensitive area that either protrudes from the main surface **11** and/or is located in an opening of the main surface **11** in which the sensitive area resides. The MEMS may also utilize a backside processing of the silicon die (e.g., bulk micro machining or die bonding with other wafers).

(35) The pressure sensor package **100** further includes a flexible protective material **13**, such as silicone gel, disposed and coupled between the MEMS element **12** and the flexible carrier **2**. The flexible protective material **13** may be placed such that an entire exposed surface of the MEMS element **12**, including the sensitive area, is encapsulated by the flexible protective material **13**. Thus, the flexible protective material **13** is placed at least in the region where the MEMS element **12** is located, and the flexible protective material **13** is used to fill the gap the MEMS element **12** and the flexible carrier **2**. By this arrangement, pressure may be applied to the flexible carrier **2** such that it is transferred through the flexible protective material **13** to the MEMS element **12**. Additionally, pressure applied directly to the protective material **13** is transferred through the flexible protective material **13** to the MEMS element **12**, such that the flexible carrier **2** does not influence the measurement. This direct application of pressure to the protective material **13** may be achieved at one or more of the slits or openings **19** that extend through the flexible carrier **2**, or at any other region where the protective material **13** is exposed to the ambient.

(36) As shown, the flexible protective material **13** is further bonded to at least a portion of the main surface **11** of the chip **1**. Thus, the flexible protective material **13** completely fills the gap between the main surface **11**, including the MEMS element **12**, and the flexible carrier **2**.

(37) The flexible carrier **2** may also include a plurality of slits or openings **19** that may increase the

flexibility of the carrier **2** and also reduce the amount of mechanical stress transferred to the inner region of the carrier where the MEMS element is bonded thereto. For example, the slits **19** may be located in proximity of the bonding balls **3**. In some cases, the slits **19** may surround a periphery of the bonding balls **3** in a circular pattern.

(38) FIGS. 2A-2C show a cross-sectional diagram of a pressure sensor package **200** according to one or more embodiments. Similar to the pressure sensor package **100** shown in FIG. 1, the pressure sensor package **200** includes chip **1** bonded to a flexible carrier **2** by bonding balls **3**, with the exception that the flexible carrier **2** is folded around the chip **1** for additional protection. By folding the flexible carrier **2** around the chip **1**, a folded pocket **21** or cavity is formed around the chip **1**. Thus, the flexible carrier **2** encircles at least three sides of the chip **1**, including the main surface **11**, a back surface **14** opposite to the main surface **11**, and a side surface **15** that adjoins the main surface **11** and the back surface **14**.

(39) As shown in FIG. 2B, the folded pocket **21** is at least partially filled with a compressible foam **22** such that a gap between the back surface **14** and the flexible carrier **2** is filled with the foam **22** and such that a gap between the side surface **15** and the flexible carrier **2** is filled with the foam **22**. At the very least, the foam **22** should be porous in order for it to forward pressure unchanged to the protective material **13** and be detected by the pressure sensor. The foam **22** may be pressed into the folded pocket **21** for protection and media filtering.

(40) Alternatively, a soft tissue or a mesh of fibers could be used instead of a foam. Thus, any material that is compressible and porous may be used in place of foam **22**. This material may be referred to as a filling material that is compressible and porous that is configured to forward pressure unchanged to the protective material **13**.

(41) In addition, the foam **22** may cover another side surface **16** of the chip **1** such that the foam **22** encapsulates the chip **1** on all remaining sides of the chip **1**, with the exception of the main surface **11**. As described above, the flexible protective material **13** is used to fill the gap the main surface **11**, including the MEMS element **12**, and the flexible carrier **2**.

(42) Thus, in one example, the flexible carrier **2** may first be folded over to form the folded pocket **21**, and then foam **22** may be injected into the folded pocket **21** to fill the remaining gaps and seal the chip **1**, bonding balls **3**, and the MEMS element **12**.

(43) Alternatively, the foam **22** may be disposed on the chip **1** to encapsulate the exposed surfaces of the chip **1**, and then the flexible carrier **2** may be folded over the dispensed foam **22** to form the structure shown in FIG. 2B.

(44) As another alternative, the foam **22** may be glued to the flexible carrier **2** before being folded over the chip **1**. Once glued, the flexible carrier **2** and the foam **22** may be folded over the chip **1** to achieve the same result depicted in FIG. 2B.

(45) The flexible carrier **2** may further include one or more pressure openings **34** that extend through the portion of the flexible carrier **2** that is folded over the backside of the chip **1**. The pressure openings **34** allow the flexible carrier **2** to be porous so that air pressure can pass therethrough. Thus, the pressure openings **34** serve to dissipate mechanical stress.

(46) As shown in FIG. 2C, the folded pocket **21** is filled with the flexible protective material **13** in an area that entirely encapsulates the chip **1**, including the MEMS element **12**. The compressible foam **22** may be further dispensed at a side region of the package **200** to enclose the chip **1** and the flexible protective material **13** within the folded pocket **21**. That is a remaining portion of the folded pocket **21** is filled with the foam **22**.

(47) Thus, in one example, the flexible carrier **2** may first be folded over to form the folded pocket **21**, and then the flexible protective material **13** may be injected into the folded pocket **21** to fill the remaining gaps and seal the chip **1**, bonding balls **3**, and the MEMS element **12**. Subsequently, the foam **22** may then be injected to seal the flexible protective material **13** inside the folded pocket **21**.

(48) While not shown, the flexible carrier **2** in FIGS. 2A-2C may further include slits similar to slits **19** shown in FIG. 1.

(49) Alternatively, the flexible protective material **13** may be disposed on the chip **1** to encapsulate the exposed surfaces of the chip **1**, and then the flexible carrier **2** may be folded over the dispensed flexible protective material **13** to form the structure shown in FIG. 2C. Subsequently, the foam **22** may then be injected to seal the flexible protective material **13** inside the folded pocket **21**.

(50) FIG. 3 shows a cross-sectional diagram of a pressure sensor package **300** according to one or more embodiments. Similar to the pressure sensor packages **100** and **200** shown in FIGS. 1 and 2A-2C, the pressure sensor package **300** includes chip **1** bonded to a flexible carrier **2** by bonding balls **3**, with the exception that a flexible film sticker **31** is provided over the back side of the chip **1** to form a pocket **32** or cavity in which the chip **1** resides.

(51) In particular, the film sticker **31** may be bonded to the flexible carrier **2** at a perimeter that surrounds the chip **1**. Thus, the film sticker **31** extends from a bonded area of the flexible carrier **2** over a back side of the chip **1**. A compressible foam **22** may then be injected between an inside surface of the film sticker **31** and the chip **1** such that the foam **22** separates the film sticker **31** from the chip **1**. As a result, the pocket **32** is formed or is enlarged by the injection of the foam **22**.

(52) Alternatively, the foam **22** may be first disposed on the chip **1** and the flexible carrier **2** to encapsulate the exposed surfaces of the chip **1**, and then the film sticker **31** may be placed over the foam **22** and bonded to the flexible carrier **2**.

(53) As another alternative, the foam **22** may be glued to the film sticker **31** and then glued over the chip **1**. Thus, the film sticker **31** may be glued to the chip **1** via the foam **22** to achieve the result depicted in FIG. 3.

(54) The film sticker **31** may further include one or more pressure openings **34** that extend through the membrane of the film sticker **31**. The pressure openings **34** allow the film sticker **31** to be porous so that air pressure can pass therethrough. Thus, the pressure openings **34** serve to dissipate mechanical stress. In addition, it is possible to inject the foam through one or more of the pressure openings **34** to fill the pocket **32**.

(55) Similarly, the flexible carrier **2** may include one or more pressure openings **35** that extend through the flexible carrier **2**. The pressure openings **35** are located in a region where the foam **22** is in contact with the flexible carrier. It is possible to inject the foam through one or more of the pressure openings **35** to fill the pocket **32**. The pressure openings **35** allow the flexible carrier **2** to be porous so that air pressure can pass therethrough. Thus, the pressure openings **35** serve to dissipate mechanical stress.

(56) While not shown, the flexible carrier **2** in FIG. 3 may further include slits similar to slits **19** shown in FIG. 1.

(57) FIG. 4 shows a cross-sectional diagram of a pressure sensor package **400** according to one or more embodiments. Similar to the pressure sensor package **100** shown in FIG. 1, the pressure sensor package **400** includes chip **1** bonded to a flexible carrier **2** by bonding balls **3**, with the exception that the bonding balls **3** are coupled to a back surface **14** of the chip **1** and the sensitive area of the MEMS element **12** faces away from the flexible carrier **2**. The flexible carrier **2** may further include slits **19**.

(58) In addition, the MEMS element **12** is arranged at the main surface **11** of the chip **1** and its exposed surface, including the sensitive area, is completely covered with the flexible protective material **13**. The glob of flexible protective material **13** is further surrounded by a structured material **41** that is also disposed on the main surface **11** of the chip **1**. Thus, the structured material **41** is disposed around a peripheral region of the main surface **11**, while the flexible protective material **13** and the MEMS element **12** are disposed at an inner region of the main surface **11**.

(59) The structured material **41** may be a structured synthetic resin, which should be sufficiently flexible to avoid the generation of excessive stress. A resin material that may be used in semiconductor processes is polyimide. The resin provides an opening at an area around the MEMS element **12**, which may support a controlled deposition of the flexible protective material **13**. Thus, the flexible protective material **13** is dispensed within the opening formed by the structured

material **41**.

(60) Alternatively, the structured material **41** may be a structured silicon wafer or a structured glass wafer with a thermally adapted expansion coefficient.

(61) FIG. 5 shows a cross-sectional diagram of a pressure sensor package **500** according to one or more embodiments. Similar to the pressure sensor package **400** shown in FIG. 4, the pressure sensor package **500** includes chip **1** bonded to a flexible carrier **2** by bonding balls **3**, with the exception that the flexible protective material **13** completely encapsulates the chip **1**, including the MEMS element **12**.

(62) In addition, the pressure sensor package **500** includes a boundary frame **51** that is bonding to the flexible carrier **2** with a bonding adhesive **52**, such as glue or solder. The boundary frame **51** entirely surrounds a periphery of the chip **1**, and the flexible protective material **13** is deposited globally over the chip **1** using the boundary frame **51** to retain the flexible protective material **13** within a cavity that is formed between the walls of the boundary frame **51**.

(63) In FIGS. 4 and 5, it will also be appreciated that the flexible carrier **2** may also be folded around the chip **1** to form a folded pocket around the chip in a similar manner described with respect to FIGS. 2A-2C. Thus, FIGS. 4 and 5 may incorporate any of the features described in conjunction with FIGS. 2A-2C.

(64) Similarly, in FIGS. 4 and 5, it will also be appreciated that the film sticker **31** may be bonded to the flexible carrier **2** to enclose the chip **1** within a pocket **32** in a similar manner described with respect to FIG. 3. Thus, FIGS. 4 and 5 may incorporate any of the features described in conjunction with FIG. 3.

(65) FIG. 6 shows a top view of the pressure sensor package **100** shown in FIG. 1. As can be seen, the bonding balls **3** are connected to lead wires **61**. Also, slits or openings **19** formed in the flexible carrier **2** are shown. Multiple openings **19** surround a bonding region of the flexible carrier **2** where a respective bonding ball **3** is bonded thereto.

(66) FIG. 7 shows a top view of the pressure sensor package **700** according to one or more embodiments. In particular, the pressure sensor package **700** uses a regular PCB **72** made of, for example, FR4 or ceramic material instead of a flexible carrier. In addition, the PCB **72** includes stress relieve springs **79** entrenched in the material of the PCB **72**. The stress relieve springs **79** are formed by milling grooves or channels in the PCB **72**. Each stress relieve springs **79** can be seen as two parallel channels that join together at the periphery of a corresponding bonding ball **3** to form one single integral channel.

(67) Each channel wraps around a periphery of a corresponding bonding ball **3** and extends outward towards a periphery of the PCB **72**. A stress relieve spring **79** may extend from a periphery of a corresponding bonding ball **3** and extend to a periphery of the PCB **72** catty-corner from the corresponding bonding ball **3**. For example, one stress relieve spring **79** wraps around the periphery of the bonding ball **3** located at the top left corner of the chip **1**, wraps around a periphery of two adjacent sides of the chip **1** towards a lower right corner of the PCB **72**.

(68) It will be appreciated that the PCB **72** with stress relieve springs **79** may be implemented in FIGS. 1, 3, 4, and 5, replacing the flexible carrier **2**.

(69) Although embodiments described herein relate to MEMS pressure sensors, and, in some cases capacitive pressure sensors, it is to be understood that other implementations may include other types of pressure sensors or other types of MEMS devices or MEMS elements. In addition, although some aspects have been described in the context of an apparatus, it is clear that these aspects also represent a description of the corresponding method, where a block or device corresponds to a method step or a feature of a method step. Analogously, aspects described in the context of a method step also represent a description of a corresponding block or item or feature of a corresponding apparatus. Some or all of the method steps may be executed by (or using) a hardware apparatus, like for example, a microprocessor, a programmable computer or an electronic circuit. In some embodiments, some one or more of the method steps may be executed by such an

apparatus.

(70) Further, it is to be understood that the disclosure of multiple acts or functions disclosed in the specification or claims may not be construed as to be within the specific order. Therefore, the disclosure of multiple acts or functions will not limit these to a particular order unless such acts or functions are not interchangeable for technical reasons. Furthermore, in some embodiments a single act may include or may be broken into multiple sub acts. Such sub acts may be included and part of the disclosure of this single act unless explicitly excluded.

(71) Furthermore, the description and drawings merely illustrate the principles of the disclosure. It will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the principles of the disclosure and are included within its spirit and scope. Furthermore, all examples recited herein are principally intended expressly to be only for pedagogical purposes to aid in the understanding of the principles of the disclosure and the concepts contributed to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions. Moreover, all statements herein reciting principles, aspects, and embodiments of the disclosure, as well as specific examples thereof, are intended to encompass equivalents thereof. Thus, it is understood that modifications and variations of the arrangements and the details described herein will be apparent to others skilled in the art.

(72) Furthermore, the following claims are hereby incorporated into the detailed description, where each claim may stand on its own as a separate example embodiment. While each claim may stand on its own as a separate example embodiment, it is to be noted that—although a dependent claim may refer in the claims to a specific combination with one or more other claims—other example embodiments may also include a combination of the dependent claim with the subject matter of each other dependent or independent claim. Such combinations are proposed herein unless it is stated that a specific combination is not intended. Furthermore, it is intended to include also features of a claim to any other independent claim even if this claim is not directly made dependent to the independent claim.

Claims

1. A semiconductor device, comprising: a semiconductor chip comprising a chip substrate and a MEMS element, wherein the chip substrate includes a first surface and a second surface arranged opposite to the first surface, and wherein the MEMS element is disposed at the first surface of the chip substrate and the MEMS element includes a sensitive area; at least one electrical interconnect structure electrically connected to the first surface of the chip substrate; a chip carrier electrically connected to the at least one electrical interconnect structure; a flexible film provided over the second surface of the chip substrate to form a pocket in which the semiconductor chip resides; and a compressible material arranged between the second surface of the chip substrate and the flexible film.
2. The semiconductor device of claim 1, wherein the flexible film is bonded to the chip carrier in a region peripheral to the semiconductor chip.
3. The semiconductor device of claim 1, wherein the compressible material encapsulates peripheral sides and the second surface of the chip substrate of the semiconductor chip.
4. The semiconductor device of claim 1, wherein the compressible material fills a volume between the chip substrate and the flexible film.
5. The semiconductor device of claim 4, wherein the compressible material fills a volume between the chip carrier and the flexible film.
6. The semiconductor device of claim 1, wherein the flexible film comprises at least one opening that is porous to air pressure.
7. The semiconductor device of claim 1, wherein the chip carrier comprises at least one opening

that is porous to air pressure.

8. The semiconductor device of claim 7, wherein the compressible material extends, in a first volume, between the chip substrate and the flexible film and extends, in a second volume, between the chip carrier and the flexible film such that the compressible material is in contact with the flexible film, with the second surface of the chip substrate, and with the chip carrier, wherein the at least one opening is arranged in a region where the compressible material is in contact with the chip carrier.

9. The semiconductor device of claim 1, further comprising: a flexible protective material disposed between the MEMS element and the chip carrier.

10. The semiconductor device of claim 9, wherein the flexible protective material is bonded to the first surface of the chip substrate and encapsulates the sensitive area of the MEMS element.

11. The semiconductor device of claim 9, wherein the flexible protective material is a silicone-based material.

12. The semiconductor device of claim 9, wherein the sensitive area faces the chip carrier, and wherein pressure is applied directly to the flexible protective material such that the pressure is transferred through the flexible protective material to the MEMS element unchanged.

13. The semiconductor device of claim 1, wherein the MEMS element is a pressure sensor.

14. The semiconductor device of claim 1, wherein semiconductor chip is a bare die or a chip size package.

15. The semiconductor device of claim 1, wherein semiconductor device is free from any molding.

16. The semiconductor device of claim 1, wherein the at least one electrical interconnect structure is a bonding ball.

17. The semiconductor device of claim 9, wherein: the MEMS element is a pressure sensor and the sensitive area is a pressure sensitive membrane that is separated from the chip carrier by a gap, and the flexible protective material extends from the chip carrier to the pressure sensitive membrane, thereby filling the gap between the pressure sensitive membrane and the chip carrier such that the pressure sensitive membrane is encapsulated by the flexible protective material.
