

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414604
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Langvin; Elizabeth et al.

Sole structure for article of footwear

Abstract

A sole structure for an article of footwear includes a bladder and at least one foam insert. The bladder includes an upper surface having a first portion defining a chamber and a second portion defining at least one recess adjacent to the chamber. The at least one foam insert is disposed within the at least one recess and has a top surface that is substantially flush with the first portion of the upper surface of the bladder. The first portion of the upper surface is exposed to the at least one foam insert.

Inventors:	Langvin; Elizabeth (Sherwood, OR), Peyton; Lee D. (Tigard, OR)
Applicant:	NIKE, Inc. (Beaverton, OR)
Family ID:	1000008818108
Assignee:	NIKE, Inc. (Beaverton, OR)
Appl. No.:	18/348095
Filed:	July 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230346077 A1	Nov. 02, 2023

Related U.S. Application Data

continuation parent-doc US 16886963 20200529 US 11730233 child-doc US 18348095
us-provisional-application US 62854520 20190530

Publication Classification

Int. Cl.: A43B13/20 (20060101); A43B13/12 (20060101); A43B13/18 (20060101)

U.S. Cl.:

CPC **A43B13/20** (20130101); **A43B13/187** (20130101); A43B13/12 (20130101)

Field of Classification Search

CPC: A43B (7/1405); A43B (7/148); A43B (7/149); A43B (13/12); A43B (13/125); A43B (13/127); A43B (13/187); A43B (13/188); A43B (13/20); A43B (13/206); A43B (13/186); A43B (13/203); A43B (17/03); A43B (17/035); A43B (21/28); A43B (21/285)

USPC: 36/29; 36/43; 36/71; 36/28; 36/35B; 36/153

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5367791	12/1993	Gross	36/31	A43B 13/26
5469639	12/1994	Sessa	N/A	N/A
5713141	12/1997	Mitchell et al.	N/A	N/A
5952065	12/1998	Mitchell et al.	N/A	N/A
6374514	12/2001	Swigart	36/35B	A43B 13/20
6582786	12/2002	Bonk et al.	N/A	N/A
8650775	12/2013	Peyton	N/A	N/A
8782924	12/2013	Peyton et al.	N/A	N/A
10149513	12/2017	Eldem	N/A	A43B 13/186
10172420	12/2018	James	N/A	N/A
2001/0045028	12/2000	Crane et al.	N/A	N/A
2005/0132607	12/2004	Dojan et al.	N/A	N/A
2005/0133968	12/2004	Foxen	264/255	A43B 21/28
2007/0022630	12/2006	Lundy et al.	N/A	N/A
2009/0151195	12/2008	Forstrom	12/142R	B29D 35/122
2009/0151196	12/2008	Schindler et al.	N/A	N/A
2011/0005101	12/2010	Sills	N/A	N/A
2014/0075777	12/2013	Bruce	36/29	A43B 7/148
2014/0250728	12/2013	Devoe	36/102	A43B 13/20
2015/0223564	12/2014	Peyton et al.	N/A	N/A
2017/0172250	12/2016	Dolan et al.	N/A	N/A
2017/0265566	12/2016	Case et al.	N/A	N/A
2018/0338577	12/2017	Elder et al.	N/A	N/A
2020/0113281	12/2019	Dirsa et al.	N/A	N/A

OTHER PUBLICATIONS

European Patent Office (ISA), International Search Report and Written Opinion for PCT Application No. PCT/US2020/035055, mailed Sep. 16, 2020. cited by applicant

Taiwan Patent Office, Office Action for Application No. 109118337 dated Jun. 3, 2021. cited by applicant

United States Patent and Trademark Office, Final Office Action for U.S. Appl. No. 16/886,963 mailed Jul. 20, 2022. cited by applicant

Taiwan Patent Office, Office Action for Application No. 109118337 dated Nov. 21, 2022. cited by

applicant
USPTO, Notice of Allowance and Fees Due for U.S. Appl. No. 16/886,963, mailed Apr. 6, 2023. cited by applicant
USPTO, Non-Final Office Action for U.S. Appl. No. 16/886,963, mailed Oct. 12, 2022. cited by applicant
USPTO, Final Office Action for U.S. Appl. No. 16/886,963, mailed Jul. 20, 2022. cited by applicant
USPTO, Non-Final Office Action for U.S. Appl. No. 16/886,963, mailed Feb. 9, 2022. cited by applicant

Primary Examiner: Collier; Jameson D

Assistant Examiner: Marchewka; Matthew R

Attorney, Agent or Firm: Honigman LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/886,963, filed May 29, 2020, which claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Patent Application Ser. No. 62/854,520, filed May 30, 2019, the disclosures of which are hereby incorporated by reference in their entirety.

FIELD

(1) The present disclosure relates generally to sole structures for articles of footwear and more particularly to sole structures incorporating a fluid-filled bladder having foam inserts.

BACKGROUND

(2) This section provides background information related to the present disclosure which is not necessarily prior art.

(3) Articles of footwear conventionally include an upper and a sole structure. The upper may be formed from any suitable material(s) to receive, secure, and support a foot on the sole structure. The upper may cooperate with laces, straps, or other fasteners to adjust the fit of the upper around the foot. A bottom portion of the upper, proximate to a bottom surface of the foot, attaches to the sole structure.

(4) Sole structures generally include a layered arrangement extending between a ground surface and the upper. One layer of the sole structure includes an outsole that provides abrasion-resistance and traction with the ground surface. The outsole may be formed from rubber or other materials that impart durability and wear-resistance, as well as enhance traction with the ground surface. Another layer of the sole structure includes a midsole disposed between the outsole and the upper. The midsole provides cushioning for the foot and may be partially formed from a polymer foam material that compresses resiliently under an applied load to cushion the foot by attenuating ground-reaction forces. The midsole may additionally or alternatively incorporate a fluid-filled bladder to increase durability of the sole structure, as well as to provide cushioning to the foot by compressing resiliently under an applied load to attenuate ground-reaction forces. Sole structures may also include a comfort-enhancing insole or a sockliner located within a void proximate to the bottom portion of the upper and a strobel attached to the upper and disposed between the midsole and the insole or sockliner.

(5) Midsoles employing fluid-filled bladders typically include a bladder formed from two barrier layers of polymer material that are sealed or bonded together. The fluid-filled bladders are

pressurized with a fluid such as air, and may incorporate tensile members within the bladder to retain the shape of the bladder when compressed resiliently under applied loads, such as during athletic movements. Generally, bladders are designed with an emphasis on balancing support for the foot and cushioning characteristics that relate to responsiveness as the bladder resiliently compresses under an applied load

Description

DRAWINGS

- (1) The drawings described herein are for illustrative purposes only of selected configurations and are not intended to limit the scope of the present disclosure.
- (2) FIG. 1 is a side elevation view of an article of footwear in accordance with principles of the present disclosure;
- (3) FIG. 2 is an exploded view of the article of footwear of FIG. 1 showing an article of footwear having an upper, a midsole, and an outsole arranged in a layered configuration;
- (4) FIG. 3A is a top perspective view of a sole structure of the article of footwear of FIG. 1, showing a bladder and a plurality of foam inserts in an assembled state;
- (5) FIG. 3B is a top perspective view of the sole structure of FIG. 3A, showing the bladder and the plurality of foam inserts in an exploded state;
- (6) FIG. 4 is a bottom plan view of the sole structure of FIG. 3A, showing a plurality of segments and a web area of the bladder;
- (7) FIG. 5 is a cross-sectional view taken along line 5-5 of FIG. 4, showing segments disposed within a forefoot region of the sole structure and separated from one another by a web area;
- (8) FIG. 6 is a cross-sectional view taken along line 6-6 of FIG. 4, showing segments disposed within a forefoot region of the sole structure and separated from one another by a web area;
- (9) FIG. 7 is a cross-sectional view taken along line 7-7 of FIG. 4, showing segments disposed within a heel region of the sole structure and separated from one another by a web area;
- (10) FIG. 8 is a cross-sectional view taken along line 8-8 of FIG. 4, showing segments arranged along a forefoot region, a mid-foot region, and a heel region;
- (11) FIG. 9 is a side elevation view of an article of footwear in accordance with principles of the present disclosure;
- (12) FIG. 10 is an exploded view of the article of footwear of FIG. 9 showing an article of footwear having an upper, a midsole, and an outsole arranged in a layered configuration;
- (13) FIG. 11A is a top perspective view of a sole structure of the article of footwear of FIG. 9, showing a bladder and a plurality of foam inserts in an assembled state;
- (14) FIG. 11B is a top perspective view of the sole structure of FIG. 11A, showing the bladder and the plurality of foam inserts in an exploded state;
- (15) FIG. 12 is a bottom plan view of the sole structure of FIG. 11A, showing a plurality of segments and a web area of the bladder;
- (16) FIG. 13 is a cross-sectional view taken along line 13-13 of FIG. 12, showing segments disposed within a forefoot region of the sole structure and separated from one another by a web area;
- (17) FIG. 14 is a cross-sectional view taken along line 14-14 of FIG. 12, showing segments disposed within a forefoot region of the sole structure and separated from one another by a web area;
- (18) FIG. 15 is a cross-sectional view taken along line 15-15 of FIG. 12, showing segments disposed within a heel region of the sole structure and separated from one another by a web area; and
- (19) FIG. 16 is a cross-sectional view taken along line 16-16 of FIG. 12, showing segments

arranged along a forefoot region, a mid-foot region, and a heel region.

(20) Corresponding reference numerals indicate corresponding parts throughout the drawings.

DETAILED DESCRIPTION

(21) Example configurations will now be described more fully with reference to the accompanying drawings. Example configurations are provided so that this disclosure will be thorough, and will fully convey the scope of the disclosure to those of ordinary skill in the art. Specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of configurations of the present disclosure. It will be apparent to those of ordinary skill in the art that specific details need not be employed, that example configurations may be embodied in many different forms, and that the specific details and the example configurations should not be construed to limit the scope of the disclosure.

(22) The terminology used herein is for the purpose of describing particular exemplary configurations only and is not intended to be limiting. As used herein, the singular articles “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of features, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. Additional or alternative steps may be employed.

(23) When an element or layer is referred to as being “on,” “engaged to,” “connected to,” “attached to,” or “coupled to” another element or layer, it may be directly on, engaged, connected, attached, or coupled to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly connected to,” “directly attached to,” or “directly coupled to” another element or layer, there may be no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items.

(24) The terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections. These elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as “first,” “second,” and other numerical terms do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example configurations.

(25) In one aspect, a sole structure for an article of footwear includes a bladder and at least one foam insert. The bladder includes an upper surface having a first portion defining a chamber and a second portion defining at least one recess adjacent to the chamber. The at least one foam insert is disposed within the at least one recess and has a top surface that is substantially flush with the first portion of the upper surface of the bladder. The first portion of the upper surface is exposed to the at least one foam insert.

(26) In some implementations, the at least one foam insert is disposed between a first portion of the chamber and a second portion of the chamber. The bladder may include an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber. The web area may define the second portion of the upper surface.

(27) In some implementations, the at least one foam insert includes a first segment and a second segment and the upper surface of the bladder is exposed between the first segment and the second

segment. The at least one foam insert may substantially fill the at least one recess. The top surface of the at least one foam insert may be tangent with the first portion of the chamber. The chamber may be a fluid-filled chamber.

(28) In some implementations, the bladder includes a first recess in a heel region and a second recess in a forefoot region, the at least one foam insert including a first foam insert disposed within the first recess and a second foam insert disposed within the second recess. The first portion of the bladder, a top surface of the first foam insert, and a top surface of the second foam insert may be substantially flush.

(29) In another aspect, a sole structure for an article of footwear includes a bladder and a plurality of foam inserts. The bladder includes a chamber and a plurality of recesses formed in an upper surface of the bladder. The plurality of recesses have peripheral profiles defined by the chamber. The plurality of foam inserts are each disposed within respective ones of the plurality of the recesses and include top surfaces that are substantially flush with the upper surface of the bladder to form a substantially continuous top surface of the sole structure.

(30) In some implementations, each of the plurality of the foam inserts is at least partially surrounded by the chamber. The bladder may include an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber. The web area may define the plurality of the recesses.

(31) In some implementations, the upper surface of the bladder is exposed between the plurality of the foam inserts. The plurality of the foam inserts may substantially fill the plurality of the recesses. The top surfaces of each of the plurality of the foam inserts may be substantially flush with a portion of the upper surface corresponding to the chamber. The chamber may be a fluid-filled chamber.

(32) In some implementations, the plurality of recesses includes a first recess in a heel region of the sole structure and a second recess in a forefoot region of the sole structure, the plurality of foam inserts including a first foam insert disposed within the first recess and a second foam insert disposed within the second recess. The plurality of recesses may include a third recess in a midfoot region of the sole structure. The plurality of foam inserts may include a third foam insert disposed within the third recess.

(33) Referring to FIG. 1, an article of footwear **10** includes an upper **100** and a sole structure **200**. The article of footwear **10** may be divided into one or more regions. The regions may include a forefoot region **12**, a mid-foot region **14**, and a heel region **16**. The forefoot region **12** may be subdivided into a toe portion **12T** corresponding with phalanges, and a ball portion **12B** associated with metatarsal bones of a foot. The mid-foot region **14** may correspond with an arch area of the foot, and the heel region **16** may correspond with rear portions of the foot, including a calcaneus bone.

(34) The footwear **10** may further include an anterior end **18** associated with a forward-most point of the forefoot region **12**, and a posterior end **20** corresponding to a rearward-most point of the heel region **16**. As shown in FIG. 4, a longitudinal axis AF of the footwear **10** extends along a length of the footwear **10** from the anterior end **18** to the posterior end **20**, parallel to a ground surface. The longitudinal axis AF is centrally located along the length of the footwear **10**, and generally divides the footwear **10** into a lateral side **22** and a medial side **24**. Accordingly, the lateral side **22** and the medial side **24** respectively correspond with opposite sides of the footwear **10** and extend through the regions **12**, **14**, **16**. As used herein, a longitudinal direction refers to the direction extending from the anterior end **18** to the posterior end **20**, while a lateral direction refers to the direction transverse to the longitudinal direction and extending from the lateral side **22** and the medial side **24**.

(35) The article of footwear **10**, and more particularly, the sole structure **200**, may be further described as including a peripheral region **26** and an interior region **28**, as signified by the dashed line in FIG. 4. The peripheral region **26** is generally described as being a region between the

interior region **28** and an outer perimeter of the sole structure **200**. Particularly, the peripheral region **26** extends from the forefoot region **12** to the heel region **16** along each of the medial side **24** and the lateral side **22**, and wraps around each of the forefoot region **12** and the heel region **16**. The interior region **28** is circumscribed by the peripheral region **26**, and extends from the forefoot region **12** to the heel region **16** along a central portion of the sole structure **200**.

(36) The upper **100** includes interior surfaces that define an interior void **102** configured to receive and secure a foot for support on the sole structure **200**. The upper **100** may be formed from one or more materials that are stitched or adhesively bonded together to form the interior void **102**.

Suitable materials of the upper **100** may include, but are not limited to, mesh, textiles, foam, leather, and synthetic leather. The materials may be selected and located to impart properties of durability, air-permeability, wear-resistance, flexibility, and comfort.

(37) As best shown in the cross-sectional view of FIG. 5, the upper **100** may include a strobil **104** having a bottom surface **106** opposing the sole structure **200** and an opposing top surface defining a footbed **108** of the interior void **102**. Stitching or adhesives may secure the strobil **104** to the upper **100**. A profile of the footbed **108** is defined by the sole structure **200**, and may be contoured to conform to a profile of the bottom surface (e.g., plantar) of the foot. Optionally, the upper **100** may also incorporate additional layers such as an insole **110** or sockliner that may be disposed upon the strobil **104** and reside within the interior void **102** of the upper **100** to receive a plantar surface of the foot to enhance the comfort of the article of footwear **10**.

(38) Referring again to FIG. 1, an ankle opening **112** in the heel region **16** may provide access to the interior void **102**. For example, the ankle opening **112** may receive a foot to secure the foot within the void **102** and facilitate entry and removal of the foot from and to the interior void **102**. In some examples, one or more fasteners **114** extend along the upper **100** to adjust a fit of the interior void **102** around the foot and to accommodate entry and removal of the foot therefrom. The upper **100** may include apertures **116** such as eyelets and/or other engagement features such as fabric or mesh loops that receive the fasteners **114**. The fasteners **114** may include laces, straps, cords, hook-and-loop, or any other suitable type of fastener. The upper **100** may include a tongue portion that extends between the interior void **102** and the fasteners **114**.

(39) With reference to FIG. 2, the sole structure **200** includes a midsole **202** and an outsole **204**. Generally, the midsole **202** is configured to impart performance characteristics to the sole structure **200**, such as cushioning, responsiveness, and energy distribution. The outsole **204** may be attached to or formed integrally with the midsole **202**, and forms a ground-engaging surface **30** of the article of footwear **10**. Accordingly, the outsole **204** is configured to impart characteristics related to traction and abrasion resistance.

(40) With reference to FIGS. 3A and 3B, the midsole **202** is formed as a composite structure, and includes a bladder **206** and one or more foam inserts **208**, **208a**. As described in greater detail below, the bladder **206** and the foam inserts **208**, **208a** cooperate to form a substantially flush and continuous top surface **210** of the midsole **202**, which defines the shape of the footbed **108**. The midsole **202** further includes a bottom surface **212** formed on an opposite side of the midsole **202** from the top surface **210**. The bottom surface **212** defines a profile of the ground-engaging surface **30** of the sole structure **200**. A peripheral side surface **214** of the midsole **202** extends between the top surface **210** and the bottom surface **212**, and defines an outer peripheral profile of the sole structure **200**.

(41) With reference to FIG. 3B, the bladder **206** is configured to extend from the anterior end **18** to the posterior end **20** of the footwear **10**. The bladder **206** may be described as including an upper surface **216** and a lower surface **218** formed on an opposite side of the bladder **206** from the upper surface **216**. As described in greater detail below, and best shown in FIG. 3B, the upper surface **216** of the bladder **206** may include one or more recesses **220**, **220a** formed therein. In the illustrated example, the upper surface **216** includes a forefoot recess **220** extending through the forefoot region **12** and the mid-foot region **14**, and a heel recess **220a** formed in the heel region **16**. As

described in greater detail below, and illustrated in FIGS. 3A and 3B, when the midsole **202** is assembled, the foam inserts **208**, **208a** are received within the respective recesses **220**, **220a** such that the upper surface **216** of the bladder **206** is exposed and cooperates with top surfaces of the inserts **208**, **208a** to provide a continuous and substantially flush top surface **210** of the midsole **202**.

(42) With continued reference to FIG. 3B, the bladder **206** is constructed of an upper barrier layer **222** and a lower barrier layer **224**, which are joined together with each other at discrete locations to form a chamber **226** and a web area **228**. The chamber **226** is associated with an area of the bladder **206** where interior surfaces of the upper and lower barrier layers **222**, **224** are not joined together and, thus, are separated from one another to define an interior void **230** of the bladder **206**, as shown in the cross-sectional views of FIG. 5-8. Conversely, the web area **228** is associated with areas of the bladder **206** where the upper barrier layer **222** is joined to the lower barrier layer **224**. With reference to FIG. 3B, the chamber **226** and the web area **228** cooperate to define the recesses **220**, **220a** in the upper surface **216** of the bladder **206**, whereby the web area **228** defines a bottom portion of the recesses **220**, **220a** and the chamber **226** defines an outer periphery of the recesses **220**, **220a**.

(43) As used herein, the term “barrier layer” (e.g., barrier layers **222**, **224**) encompasses both monolayer and multilayer films. In some embodiments, one or both of barrier layers **222**, **224** are each produced (e.g., thermoformed or blow molded) from a monolayer film (a single layer). In other embodiments, one or both of the barrier layers **222**, **224** are each produced (e.g., thermoformed or blow molded) from a multilayer film (multiple sublayers). In either aspect, each layer or sublayer can have a film thickness ranging from about 0.2 micrometers to about 1 millimeter. In further embodiments, the film thickness for each layer or sublayer can range from about 0.5 micrometers to about 500 micrometers. In yet further embodiments, the film thickness for each layer or sublayer can range from about 1 micrometer to about 100 micrometers.

(44) One or both of the barrier layers **222**, **224** can independently be transparent, translucent, and/or opaque. As used herein, the term “transparent” for a barrier layer and/or a fluid-filled chamber means that light passes through the barrier layer in substantially straight lines and a viewer can see through the barrier layer. In comparison, for an opaque barrier layer, light does not pass through the barrier layer and one cannot see clearly through the barrier layer at all. A translucent barrier layer falls between a transparent barrier layer and an opaque barrier layer, in that light passes through a translucent layer but some of the light is scattered so that a viewer cannot see clearly through the layer.

(45) The barrier layers **222**, **224** can each be produced from an elastomeric material that includes one or more thermoplastic polymers and/or one or more cross-linkable polymers. In an aspect, the elastomeric material can include one or more thermoplastic elastomeric materials, such as one or more thermoplastic polyurethane (TPU) copolymers, one or more ethylene-vinyl alcohol (EVOH) copolymers, and the like.

(46) As used herein, “polyurethane” refers to a copolymer (including oligomers) that contains a urethane group (—N(C=O)O—). These polyurethanes can contain additional groups such as ester, ether, urea, allophanate, biuret, carbodiimide, oxazolidinyl, isocynaurate, uretdione, carbonate, and the like, in addition to urethane groups. In an aspect, one or more of the polyurethanes can be produced by polymerizing one or more isocyanates with one or more polyols to produce copolymer chains having (—N(C=O)O—) linkages.

(47) Examples of suitable isocyanates for producing the polyurethane copolymer chains include diisocyanates, such as aromatic diisocyanates, aliphatic diisocyanates, and combinations thereof. Examples of suitable aromatic diisocyanates include toluene diisocyanate (TDI), TDI adducts with trimethylolpropane (TMP), methylene diphenyl diisocyanate (MDI), xylene diisocyanate (XDI), tetramethylxylene diisocyanate (TMXDI), hydrogenated xylene diisocyanate (HXDI), naphthalene 1,5-diisocyanate (NDI), 1,5-tetrahydronaphthalene diisocyanate, para-phenylene

diisocyanate (PPDI), 3,3'-dimethyldiphenyl-4,4'-diisocyanate (DDDI), 4,4'-dibenzyl diisocyanate (DBDI), 4-chloro-1,3-phenylene diisocyanate, and combinations thereof. In some embodiments, the copolymer chains are substantially free of aromatic groups.

(48) In particular aspects, the polyurethane polymer chains are produced from diisocyanates including hydrogenated MDI (HMDI), TDI, MDI, hydrogenated (H12) aliphatics, and combinations thereof. In an aspect, the thermoplastic TPU can include polyester-based TPU, polyether-based TPU, polycaprolactone-based TPU, polycarbonate-based TPU, polysiloxane-based TPU, or combinations thereof.

(49) In another aspect, the polymeric layer can be formed of one or more of the following: EVOH copolymers, poly(vinyl chloride), polyvinylidene polymers and copolymers (e.g., polyvinylidene chloride), polyamides (e.g., amorphous polyamides), amide-based copolymers, acrylonitrile polymers (e.g., acrylonitrile-methyl acrylate copolymers), polyethylene terephthalate, polyether imides, polyacrylic imides, and other polymeric materials known to have relatively low gas transmission rates. Blends of these materials as well as with the TPU copolymers described herein and optionally including combinations of polyimides and crystalline polymers, are also suitable.

(50) The barrier layers **222**, **224** may include two or more sublayers (multilayer film) such as shown in Mitchell et al., U.S. Pat. No. 5,713,141 and Mitchell et al., U.S. Pat. No. 5,952,065, the disclosures of which are incorporated by reference in their entirety. In embodiments where the barrier layers **222**, **224** include two or more sublayers, examples of suitable multilayer films include microlayer films, such as those disclosed in Bonk et al., U.S. Pat. No. 6,582,786, which is incorporated by reference in its entirety. In further embodiments, the barrier layers **222**, **224** may each independently include alternating sublayers of one or more TPU copolymer materials and one or more EVOH copolymer materials, where the total number of sublayers in each of the barrier layers **222**, **224** includes at least four (4) sublayers, at least ten (10) sublayers, at least twenty (20) sublayers, at least forty (40) sublayers, and/or at least sixty (60) sublayers.

(51) The chamber **226** can be produced from the barrier layers **222**, **224** using any suitable technique, such as thermoforming (e.g. vacuum thermoforming), blow molding, extrusion, injection molding, vacuum molding, rotary molding, transfer molding, pressure forming, heat sealing, casting, low-pressure casting, spin casting, reaction injection molding, radio frequency (RF) welding, and the like. In an aspect, the barrier layers **222**, **224** can be produced by co-extrusion followed by vacuum thermoforming to produce an inflatable chamber **226**, which can optionally include one or more valves (e.g., one way valves) that allows the chamber **226** to be filled with the fluid (e.g., gas).

(52) The chamber **226** can be provided in a fluid-filled (e.g., as provided in footwear **10**) or in an unfilled state. The chamber **226** can be filled to include any suitable fluid, such as a gas or liquid. In an aspect, the gas can include air, nitrogen (N.sub.2), or any other suitable gas. In other aspects, the chamber **226** can alternatively include other media, such as pellets, beads, ground recycled material, and the like (e.g., foamed beads and/or rubber beads). The fluid provided to the chamber **226** can result in the chamber **226** being pressurized. Alternatively, the fluid provided to the chamber **226** can be at atmospheric pressure such that the chamber **226** is not pressurized but, rather, simply contains a volume of fluid at atmospheric pressure.

(53) The chamber **226** desirably has a low gas transmission rate to preserve its retained gas pressure. In some embodiments, the chamber **226** has a gas transmission rate for nitrogen gas that is at least about ten (10) times lower than a nitrogen gas transmission rate for a butyl rubber layer of substantially the same dimensions. In an aspect, the chamber **226** has a nitrogen gas transmission rate of 15 cubic-centimeter/square-meter.Math.atmosphere.Math.day

(cm.sup.3/m.sup.2.Math.atm.Math.day) or less for an average film thickness of 500 micrometers (based on thicknesses of the barrier layers **222**, **224**). In further aspects, the transmission rate is 10 cm.sup.3/m.sup.2.Math.atm.Math.day or less, 5 cm.sup.3/m.sup.2.Math.atm.Math.day or less, or 1 cm.sup.3/m.sup.2.Math.atm.Math.day or less.

(54) In some examples, the formation of the recesses **220**, **220a** in the upper surface **216** is induced by filling the interior void **230** of the chamber **226** with a pressurized fluid, causing the upper barrier layer **222** to bulge in areas that are not joined to the lower barrier layer **224** (i.e., the chamber **226**). For example, the upper barrier layer **222** of the bladder **206** may be substantially planar, or have a continuous contour when the chamber **226** is in an unfilled or relaxed state. However, when the interior void **230** of the chamber **226** is filled, the upper barrier layer **222** and the lower barrier layer **224** will be biased apart from each other. Even where the upper barrier layer **222** has a naturally flat or continuous profile in the relaxed state, the filling of the interior void **230** will cause the upper barrier layer **222** to bulge in areas that are not joined to the lower barrier layer **224** (i.e., the web area **228**), thereby forming the one or more recesses **220**, **220a** in between adjacent segments of the chamber **226**. In some examples, the upper barrier layer **222** may be molded or pre-formed to include one or more of the recesses **220**, **220a** in areas that are not joined to the lower barrier layer **224**.

(55) As shown in the cross-sectional view of FIGS. **5-8**, exterior surfaces of the upper and lower barrier layers **222**, **224** define the respective upper and lower surfaces **216**, **218** of the bladder **206**. Accordingly, when the interior void **230** of the chamber **226** is filled with a fluid and the upper barrier layer **222** is caused to bulge, the upper surface **216** of the bladder **206** can be described as having an outer portion **232**, an inner portion **234**, and a peripheral portion **236** connecting the outer portion **232** to the inner portion **234**. Generally, the outer portion **232** and the peripheral portion **236** are associated with the chamber **226**, while the inner portion **234** is associated with the web area **228**. The outer portion **232** of the upper surface **216** corresponds to a portion of the upper barrier layer **222** that is spaced farthest away from the lower barrier layer **224** along a direction perpendicular to the ground-engaging surface **30**, while the inner portion **234** is associated with a portion of the upper barrier layer **222** that is disposed closest to the lower barrier layer **224**. In the illustrated example, the inner portion **234** is associated with the portion of the upper barrier layer **222** that is joined to the lower barrier layer **224** (i.e., the web area **228**). The peripheral portion **236** is associated with an intermediate portion of the chamber **226** that extends from the web area **228** (i.e., the inner portion **234**) to the top-most portion of the chamber **226** (i.e., the outer portion **232**). The outer portion **232** includes at least one branch that is disposed between a frontmost end and a rearmost end of the foam insert.

(56) With reference to FIG. **4**, the chamber **226** may be described as including a plurality of sub-chambers **238-238c** each comprising a plurality segments **240** that are at least partially spaced apart from each other by the web area **228** and cooperate to define a profile of the ground-engaging surface **30** of the footwear **10**. The segments **240** of each sub-chamber **238-238c** are in direct fluid communication with each other. Further, a series of the segments **240** are arranged sequentially with each other, as best shown in FIG. **4**. The chamber **226** may further include one or more conduits **242** that provide fluid communication between pairs of the sub-chambers **238-238c**. In some examples, all of the sub-chambers **238-238c** may be in fluid communication with one or more conduits **242** to form a substantially continuous chamber **226** along the length of the sole structure **200**. Accordingly, the chamber **226** may comprise a continuous network of fluidly connected sub-chambers **238-238c**, whereby a change in pressure in a first one of the sub-chambers **238-238c** is transmitted to a second one of the sub-chambers **238-238c**. In other examples, one or more of the sub-chambers **238-238c** may be fluidly isolated, where each sub-chamber **238-238c** includes a plurality of interconnected segments **240** that are isolated from the interconnected segments **240** forming the other sub-chambers **238-238c**.

(57) Each of the segments **240** and the conduits **242** may be filled with a pressurized fluid (i.e., gas, liquid) to provide cushioning and stability for the foot during use of the footwear **10**. In some implementations, compressibility of a first portion of the plurality of segments **240** of the sub-chambers **238-238c** under an applied load provides a responsive-type cushioning, while a second portion of the segments **240** of the sub-chambers **238-238c** may be configured to provide a soft-

type cushioning under an applied load. Accordingly, the sub-chambers **238-238c** may cooperate to provide gradient cushioning to the article of footwear **10** that changes as the applied load changes (i.e., the greater the load, the more the segments **240** are compressed and, thus, the more responsive the footwear **10** performs).

(58) In other implementations, one or more cushioning materials (none shown), such as polymer foam and/or particulate matter, are enclosed by one or more of the segments **240** in place of, or in addition to, the pressurized fluid to provide cushioning for the foot. In these implementations, the cushioning materials may provide one or more of the segments **240** with cushioning properties different from the segments **240** filled with the pressurized fluid. For example, the cushioning materials may be more or less responsive or provide greater impact absorption than the pressurized fluid.

(59) As discussed above, the recesses **220**, **220a** may be formed between bulges in the upper surface **216**, which are created when the interior void **230** of the chamber **226** is filled and the upper barrier layer **222** is biased apart from the lower barrier layer **224**. Accordingly, the profiles of the recesses **220**, **220a** formed in the upper surface **216** correspond to the arrangement of the sub-chambers **238-238c**, segments **240**, and/or conduits **242**. In the example of the bladder **206** shown in FIG. 3B, the chamber **226** forms a forefoot recess **220** in the forefoot region **12**, and a heel recess **220a** in the heel region **16**.

(60) With continued reference to FIG. 3B, the forefoot recess **220** extends continuously from a first end **244** at the anterior end **18** to a second end **246** in the mid-foot region **14** of the sole structure **200**. Here, the forefoot recess **220** may be described as including a plurality of interconnected segments **248**, **250** arranged in a substantially continuous and serpentine manner from the anterior end **18** to the mid-foot region **14**. In other words, the forefoot recess **220** includes a first plurality of laterally extending segments **248** each extending continuously across the width of the bladder **206** from the lateral side **22** to the medial side **24**, and a first plurality of longitudinally extending segments **250** extending between and connecting adjacent ones of the laterally extending segments **248** along the lateral side **22** and the medial side **24**.

(61) Referring still to FIG. 3B, the heel recess **220a** extends continuously from a first end **252** in the mid-foot region **14** to a second end **254** at the posterior end **20**. As with the forefoot recess **220**, the heel recess **220a** includes a plurality of laterally extending segments **256** extending across the width of the bladder **206** from the lateral side **22** to the medial side **24**. The heel recess **220a** also includes longitudinally extending segments **258** extending along the lateral side **22** and/or the medial side **24**, and connecting ends of adjacent ones of the laterally extending segments **256**.

(62) With continued reference to FIGS. 3A and 3B, the illustrated example of the sole structure **200** includes a first foam insert **208** associated with the forefoot recess **220** of the sole structure **200**, and a second foam insert **208a** associated with the heel recess **220a** of the sole structure **200**. Each of the inserts **208**, **208a** includes a top surface **260**, **260a** and a bottom surface **262**, **262a** formed on an opposite side of the foam insert **208**, **208a** from the top surface **260**, **260a**. A peripheral side surface **264**, **264a** of each of the inserts **208**, **208a** extends from the top surface **260**, **260a** to the bottom surface **262**, **262a**.

(63) Generally, each of the foam inserts **208**, **208a** is configured to be received within the respective recesses **220**, **220a**. As described above, the foam inserts **208**, **208a** may cooperate with the outer portion **232** of the upper surface **216** of the bladder **206** to form the top surface **210** of the midsole **202**, which may be contoured to accommodate a profile of a plantar surface of a foot. Accordingly, the foam inserts **208**, **208a** may be formed such that the top surfaces **260**, **260a** merge with the outer portion **232** of the upper surface **216** of the bladder **206** in a substantially tangential relationship, thereby forming a continuous and substantially flush top surface **210** of the midsole **202**. As shown in FIG. 3A, when the foam inserts **208**, **208a** are assembled within the recesses **220**, **220a**, the outer portion **232** of the upper surface **216** of the bladder **206** will be exposed between the segments of the foam inserts **208**, **208a** corresponding to the segments **256**, **258** of the recesses

220, 220a.

(64) With reference to the cross-sectional views of FIGS. 5-8, the foam inserts **208, 208a** are configured to fill the recesses **220, 220a** to form a substantially continuous and flush top surface **210** of the midsole **202**. Accordingly, the bottom surfaces **262, 262a** of the foam inserts **208, 208a** are configured to oppose or interface with the inner portion **234** of the upper surface **216**, while the peripheral side surfaces **264, 264a** are configured to cooperate with the peripheral portion **236** of the upper surface **216**. Accordingly, where the web area **228** is substantially planar, as shown, the bottom surfaces **262, 262a** of the foam inserts **208, 208a** will also be substantially planar. Likewise, where the peripheral portion **236** of the upper surface **216** of the bladder **206** has a convex profile, the peripheral side surfaces **264, 264a** of the inserts **208, 208a** will have a concave profile configured to receive the peripheral portion **236** of the upper surface **216**. As such, the inserts **208, 208a** are shaped to be matingly received by the respective recesses **220, 220a** such that the inserts **208, 208a** substantially fill the respective recesses **220, 220a**.

(65) As described above, the foam inserts **208, 208a** are formed of a resilient polymeric material, such as foam or rubber, to impart properties of cushioning, responsiveness, and energy distribution to the foot of the wearer. In one example, the first foam insert **208** and the second foam insert **208a** are formed of the same material to impart similar performance characteristics to each of the forefoot region **12**, the mid-foot region **14**, and the heel region **16**. In other examples, the first foam insert **208** and the second foam insert **208a** may be formed of different materials to impart different characteristics to at least one of the forefoot region **12**, the mid-foot region **14**, and the heel region **16**.

(66) Example resilient polymeric materials for the inserts **208, 208a** may include those based on foaming or molding one or more polymers, such as one or more elastomers (e.g., thermoplastic elastomers (TPE)). The one or more polymers may include aliphatic polymers, aromatic polymers, or mixtures of both; and may include homopolymers, copolymers (including terpolymers), or mixtures of both.

(67) In some aspects, the one or more polymers may include olefinic homopolymers, olefinic copolymers, or blends thereof. Examples of olefinic polymers include polyethylene, polypropylene, and combinations thereof. In other aspects, the one or more polymers may include one or more ethylene copolymers, such as, ethylene-vinyl acetate (EVA) copolymers, EVOH copolymers, ethylene-ethyl acrylate copolymers, ethylene-unsaturated mono-fatty acid copolymers, and combinations thereof.

(68) In further aspects, the one or more polymers may include one or more polyacrylates, such as polyacrylic acid, esters of polyacrylic acid, polyacrylonitrile, polyacrylic acetate, polymethyl acrylate, polyethyl acrylate, polybutyl acrylate, polymethyl methacrylate, and polyvinyl acetate; including derivatives thereof, copolymers thereof, and any combinations thereof.

(69) In yet further aspects, the one or more polymers may include one or more ionomeric polymers. In these aspects, the ionomeric polymers may include polymers with carboxylic acid functional groups, sulfonic acid functional groups, salts thereof (e.g., sodium, magnesium, potassium, etc.), and/or anhydrides thereof. For instance, the ionomeric polymer(s) may include one or more fatty acid-modified ionomeric polymers, polystyrene sulfonate, ethylene-methacrylic acid copolymers, and combinations thereof.

(70) In further aspects, the one or more polymers may include one or more styrenic block copolymers, such as acrylonitrile butadiene styrene block copolymers, styrene acrylonitrile block copolymers, styrene ethylene butylene styrene block copolymers, styrene ethylene butadiene styrene block copolymers, styrene ethylene propylene styrene block copolymers, styrene butadiene styrene block copolymers, and combinations thereof.

(71) In further aspects, the one or more polymers may include one or more polyamide copolymers (e.g., polyamide-polyether copolymers) and/or one or more polyurethanes (e.g., cross-linked polyurethanes and/or thermoplastic polyurethanes). Examples of suitable polyurethanes include

those discussed above for barrier layers **222**, **224**. Alternatively, the one or more polymers may include one or more natural and/or synthetic rubbers, such as butadiene and isoprene.

(72) When the resilient polymeric material is a foamed polymeric material, the foamed material may be foamed using a physical blowing agent which phase transitions to a gas based on a change in temperature and/or pressure, or a chemical blowing agent which forms a gas when heated above its activation temperature. For example, the chemical blowing agent may be an azo compound such as azodicarbonamide, sodium bicarbonate, and/or an isocyanate.

(73) In some embodiments, the foamed polymeric material may be a crosslinked foamed material. In these embodiments, a peroxide-based crosslinking agent such as dicumyl peroxide may be used. Furthermore, the foamed polymeric material may include one or more fillers such as pigments, modified or natural clays, modified or unmodified synthetic clays, talc glass fiber, powdered glass, modified or natural silica, calcium carbonate, mica, paper, wood chips, and the like.

(74) The resilient polymeric material may be formed using a molding process. In one example, when the resilient polymeric material is a molded elastomer, the uncured elastomer (e.g., rubber) may be mixed in a Banbury mixer with an optional filler and a curing package such as a sulfur-based or peroxide-based curing package, calendared, formed into shape, placed in a mold, and vulcanized.

(75) In another example, when the resilient polymeric material is a foamed material, the material may be foamed during a molding process, such as an injection molding process. A thermoplastic polymeric material may be melted in the barrel of an injection molding system and combined with a physical or chemical blowing agent and optionally a crosslinking agent, and then injected into a mold under conditions which activate the blowing agent, forming a molded foam.

(76) Optionally, when the resilient polymeric material is a foamed material, the foamed material may be a compression molded foam. Compression molding may be used to alter the physical properties (e.g., density, stiffness and/or durometer) of a foam, or to alter the physical appearance of the foam (e.g., to fuse two or more pieces of foam, to shape the foam, etc.), or both.

(77) The compression molding process desirably starts by forming one or more foam preforms, such as by injection molding and foaming a polymeric material, by forming foamed particles or beads, by cutting foamed sheet stock, and the like. The compression molded foam may then be made by placing the one or more preforms formed of foamed polymeric material(s) in a compression mold, and applying sufficient pressure to the one or more preforms to compress the one or more preforms in a closed mold. Once the mold is closed, sufficient heat and/or pressure is applied to the one or more preforms in the closed mold for a sufficient duration of time to alter the preform(s) by forming a skin on the outer surface of the compression molded foam, fuse individual foam particles to each other, permanently increase the density of the foam(s), or any combination thereof. Following the heating and/or application of pressure, the mold is opened and the molded foam article is removed from the mold.

(78) Referring now to FIGS. **9-16**, an article of footwear **10a** is provided and includes an upper **100a** and a sole structure **200a** attached to the upper **100a**. In view of the substantial similarity in structure and function of the components associated with the article of footwear **10a** with respect to the article of footwear **10**, like reference numerals are used hereinafter and in the drawings to identify like components while like reference numerals containing letter extensions are used to identify those components that have been modified.

(79) With reference to FIG. **10**, the sole structure **200a** includes a midsole **202a** and an outsole **204a**. Generally, the midsole **202a** is configured to impart performance characteristics to the sole structure **200a**, such as cushioning, responsiveness, and energy distribution. The outsole **204a** may be attached to or formed integrally with the midsole **202a**, and forms a ground-engaging surface **30** of the article of footwear **10a**. Accordingly, the outsole **204a** is configured to impart characteristics related to traction and abrasion resistance.

(80) With reference to FIGS. **11A** and **11B**, the midsole **202a** is formed as a composite structure,

and includes a bladder **206a** and one or more foam inserts **208b-208d**. As described in greater detail below, the bladder **206a** and the foam inserts **208b-208d** cooperate to form a substantially flush and continuous top surface **210a** of the midsole **202a**, which defines the contours of the footbed **108**. The midsole **202a** further includes a bottom surface **212a** formed on an opposite side of the midsole **202a** from the top surface **210a**, and defines a profile of the ground-engaging surface **30** of the sole structure **200a**. A peripheral side surface **214a** of the midsole **202a** extends between the top surface **210a** and the bottom surface **212a**, and defines an outer peripheral profile of the sole structure **200a**.

(81) With reference to FIG. **11B**, the bladder **206a** is configured to extend from the anterior end **18** to the posterior end **20** of the footwear **10a**. The bladder **206a** may be described as including an upper surface **216a** and a lower surface **218a** formed on an opposite side of the bladder **206a** from the upper surface **216a**. As described in greater detail below, and best shown in FIG. **11B**, the upper surface **216a** may include one or more recesses **220b-220d** formed therein. In the illustrated example, the upper surface **216a** includes a plurality of recesses **220b-220c** spaced along the forefoot region **12** and the mid-foot region **14**, and a longitudinal recess **220d** formed in the heel region **16**. As described in greater detail below, and illustrated in FIGS. **11A** and **11B**, when the midsole **202a** is assembled, the foam inserts **208b-208d** are received within the respective recesses **220b-220d** such that the upper surface **216a** of the bladder **206a** is exposed and cooperates with upper surfaces of the inserts **208b-208d** to provide a continuous and substantially flush top surface **210a** of the midsole **202a**.

(82) With continued reference to FIG. **11B**, the bladder **206a** is constructed of an upper barrier layer **222a** and a lower barrier layer **224a**, which are joined together with each other at discrete locations to form a chamber **226a** and a web area **228a**. The bladder **206a**, and particularly the barrier layers **222a**, **224a** of the bladder **206a**, can be constructed using the same materials and processes described above with respect to the barrier layers **222**, **224** and bladder **206** of the article of footwear **10**.

(83) The chamber **226a** is associated with an area of the bladder **206a** where interior surfaces of the upper and lower barrier layers **222a**, **224a** are not joined together and, thus, are separated from one another to define an interior void **230a** of the bladder **206a**, as shown in the cross-sectional views of FIG. **13-16**. Conversely, the web area **228a** is associated with areas of the bladder **206a** where the upper barrier layer **222a** is joined to the lower barrier layer **224a**. With reference to FIG. **11B**, the chamber **226a** and the web area **228a** cooperate to define the recesses **220b-220d** in the upper surface **216a** of the bladder **206a**, whereby the web area **228a** defines a bottom portion of the recesses **220b-220d** and the chamber **226a** defines an outer periphery of the recesses **220b-220d**.

(84) In some examples, the formation of the recesses **220b-220d** in the upper surface **216a** is induced by filling the interior void **230a** of the chamber **226a** with a pressurized fluid, causing the upper barrier layer **222a** to bulge in areas that are not joined to the lower barrier layer **224a** (i.e., the chamber **226a**). For example, the upper barrier layer **222a** of the bladder **206a** may be substantially planar, or have a continuous contour when the chamber **226a** is in an unfilled or relaxed state. However, when the interior void **230a** of the chamber **226a** is filled, the upper barrier layer **222a** and the lower barrier layer **224a** will be biased apart from each other. Even where the upper barrier layer **222a** has a naturally flat or continuous profile in the relaxed state, the filling of the interior void **230a** will cause the upper barrier layer **222a** to bulge in areas that are not joined to the lower barrier layer **224a** (i.e., the web area **228a**), thereby forming the one or more recesses **220b-220d** in between the chamber **226a**. In some examples, the upper barrier layer **222a** may be molded or pre-formed to include one or more of the recesses **220b-220d** in areas that are not joined to the lower barrier layer **224a**.

(85) As shown in the cross-sectional view of FIGS. **13-16**, exterior surfaces of the upper and lower barrier layers **222a**, **224a** define the respective upper and lower surfaces **216a**, **218a** of the bladder **206a**. When the interior void **230** of the chamber **226a** is filled and the upper barrier layer **222a** is

caused to bulge, the upper surface **216a** of the bladder **206a** can be described as having an outer portion **232**, an inner portion **234**, and a peripheral portion **236** connecting the outer portion **232** to the inner portion **234**. Generally, the outer portion **232** and the peripheral portion **236** are associated with the chamber **226a**, while the inner portion **234** is associated with the web area **228a**. The outer portion **232** of the upper surface **216a** corresponds to a portion of the upper barrier layer **222a** that is spaced farthest away from the lower barrier layer **224a** along a direction perpendicular to the ground-engaging surface **30**, while the inner portion **234** is associated with a portion of the upper barrier layer **222a** that is joined to the lower barrier layer **224a**. The peripheral portion **236** is associated with an intermediate portion of the chamber **226a** that extends from the web area **228a** (i.e., the inner portion **234**) to the top-most portion of the chamber **226a** (i.e., the outer portion **232**).

(86) As best shown in FIG. **12**, the chamber **226a** may be described as including a plurality of sub-chambers **238d-238h** each comprising a plurality segments **240** that are at least partially spaced apart from each other by the web area **228a** and cooperate to define a profile of the ground-engaging surface **30** of the footwear **10a**. The segments **240** of each sub-chamber **238d-238g** are in direct fluid communication with each other. Further, a series of the segments **240** are arranged sequentially with each other along a length of the chamber **226a**, as shown in FIG. **12**. The chamber **226a** may further include one or more conduits **242** configured to provide fluid communication between the sub-chambers **238d-238h**. In some examples, two or more of the sub-chambers **238d-238h** may be in fluid communication via one or more conduits **242**.

(87) Each of the segments **240** and the conduits **242** may be filled with a pressurized fluid (i.e., gas, liquid) to provide cushioning and stability for the foot during use of the footwear **10a**. In some implementations, compressibility of a first portion of the plurality of segments **240** of the sub-chambers **238d-238h** under an applied load provides a responsive-type cushioning, while a second portion of the segments **240** of the sub-chambers **238d-238h** may be configured to provide a soft-type cushioning under an applied load. Accordingly, the sub-chambers **238d-238h** may cooperate to provide gradient cushioning to the article of footwear **10a** that changes as the applied load changes (i.e., the greater the load, the more the segments **240** are compressed and, thus, the more responsive the footwear **10a** performs).

(88) In other implementations, one or more cushioning materials (none shown), such as polymer foam and/or particulate matter, are enclosed by one or more of the segments **240** in place of, or in addition to, the pressurized fluid to provide cushioning for the foot. In these implementations, the cushioning materials may provide one or more of the segments **240** with cushioning properties different from the segments **240** filled with the pressurized fluid. For example, the cushioning materials may be more or less responsive or provide greater impact absorption than the pressurized fluid.

(89) As described in greater detail below, the chamber **226a** may comprise a continuous network of fluidly connected sub-chambers **238d-238h**, whereby a change in pressure in a first one of the sub-chambers **238d-238h** is transmitted to a second one of the sub-chambers **238d-238h**. Alternatively, one or more of the sub-chambers **238d-238h** may be fluidly isolated from others of the sub-chambers **238d-238h**. With continued reference to FIG. **12**, the chamber **226a** includes a toe sub-chamber **238d**, an anterior ball sub-chamber **238e**, a posterior ball sub-chamber **238f** (collectively “the forefoot sub-chambers **238d-238f**”), a mid-foot sub-chamber **238g**, and a heel sub-chamber **238h**. The forefoot sub-chambers **238d-238f** and the mid-foot sub-chamber **238g** are fluidly connected to each other via the conduits **242**, while the heel sub-chamber **238h** is fluidly isolated.

(90) The toe sub-chamber **238d** is disposed adjacent to the anterior end **18** of the sole structure **200a** and defines a first portion of the forefoot recess **220b**. The toe sub-chamber **238d** includes a plurality of the segments **240** sequentially connected in a C-shaped arrangement, whereby a first one of the segments **240** extends continuously along the anterior end **18** of the sole structure **200a** from the lateral side **22** to the medial side **24**, and a pair of segments **240** extend towards each other

from opposite ends of the first one of the segments **240**, such that opposing terminal ends **241** of the segments **240** are spaced apart from each other by the web area **228a**.

(91) The anterior ball sub-chamber **238e** may be described as including a medial portion **238e1** and a lateral portion **238e2** that are spaced apart from each other by the web area **228a**. Here, the medial and lateral portions **238e1**, **238e2** of the anterior ball sub-chamber **238e** cooperate to define a second portion of the forefoot recess **220b**. The lateral portion **238e2** of the anterior ball sub-chamber **238e** includes a first pair of laterally extending segments **240** connected to each other along the lateral side **22** by a longitudinally extending segment **240**, whereby each of the laterally extending segments **240** of the anterior ball sub-chamber **238e** extend towards the medial side **24** to terminal ends **241** in the interior region **28** of the midsole **202a**. Conversely, the medial portion **238e1** of the anterior ball sub-chamber **238e** includes a second pair of laterally extending segments **240** connected to each other along the medial side **24** by a longitudinally extending one of the segments **240**, whereby each of the laterally extending segments **240** of the medial portion **238e1** of the anterior ball sub-chamber **238e** extend towards the lateral side **22** to terminal ends **241** in the interior region **28** of the midsole **202a**. The terminal ends **241** of the lateral portion **238e2** of the anterior ball sub-chamber **238e** are spaced apart from the terminal ends **241** of the medial portion **238e1** of the anterior ball sub-chamber **238e** by the web area **228a**.

(92) The posterior ball sub-chamber **238f** is disposed adjacent to the anterior ball sub-chamber **238e**, and defines a third portion of the forefoot recess **220b**. As shown, the posterior ball sub-chamber **238f** includes a first laterally extending segment **240** extending continuously from the lateral side **22** to the medial side **24**, and an opposing pair of laterally extending segments **240** extending from each of the lateral side **22** and the medial side **24** to respective terminal ends **241** in the interior region **28**. As shown, the terminal ends of the segments **240** oppose each other and are spaced apart from each other by the web area **228a**. The laterally extending segments **240** are connected to each other along each of the lateral side **22** and the medial side **24**, such that the posterior ball sub-chamber **238f** forms a substantially C-shaped sub-chamber extending continuously from the first terminal end **241** to the second terminal end **241**.

(93) The mid-foot chamber **238g** is disposed in the mid-foot region **14**, adjacent to the posterior ball sub-chamber **238f**, and defines a peripheral profile of the mid-foot recess **220c**. As shown, the mid-foot chamber **238g** includes a laterally extending segment **240** extending continuously from the lateral side **22** to the medial side **24** and including respective bulb-shaped terminal ends **241**. The bulb-shaped terminal ends **241** of the mid-foot recess **220c** may be connected to each other across the width of the bladder **206a** by a conduit **242**.

(94) Referring still to FIG. **11B**, the heel sub-chamber **238h** defines a peripheral profile of the heel recess **220d**. As shown, the heel sub-chamber **238h** includes a posterior segment **240** extending around the posterior end **20** of the sole structure **200a** from the lateral side **22** to the medial side **24**, a first longitudinally extending segment **240** extending along the lateral side **22** of the heel region **16** from the posterior segment **240** to a terminal end, and a second longitudinally extending segment **240** extending along the medial side **24** of the heel region **16** from the posterior segment **240** to a second terminal end. Accordingly, the heel chamber **238h** has a substantially horseshoe or U-shaped profile, and defines an elongate recess **220d** extending from the posterior segment **240** to the mid-foot region **14**.

(95) As discussed above, the recesses **220b-220d** may be formed between bulges in the upper surface **216a**, which are created when the interior void **230a** of the chamber **226a** is filled and the upper barrier layer **222a** is biased apart from the lower barrier layer **224a**. Accordingly, the profiles of the recesses **220b-220d** formed in the upper surface **216** correspond to the arrangement of the sub-chambers **238d-238h**, segments **240**, and/or conduits **242**. In the example of the bladder **206a** shown in FIG. **11B**, the chamber **226a** forms a forefoot recess **220b**, a mid-foot recess **220c**, and a heel recess **220d**.

(96) As best shown in FIG. **11B**, a peripheral profile of the forefoot recess **220b** is collectively

defined by the forefoot sub-chambers **238d-238f**. As shown in FIG. **12**, each of the forefoot sub-chambers **238d-238f** includes a plurality of segments **240** arranged in a substantially obround or oval shape, whereby the portions of the forefoot recess **220b** surrounded by the forefoot sub-chambers **238d-238f** have an outer peripheral profile that is substantially obround or oval shaped and includes a major axis extending in a lateral direction from the lateral side **22** to the medial side **24**, transverse to the longitudinal axis AF of the footwear **10**.

(97) As discussed above, each of the forefoot sub-chambers **238d-238f** has segments **240** that extend to terminal ends **241** in the interior region **28**, whereby the web area **228a** extends between the terminal ends **241** of the segments **240**. Accordingly, the forefoot recess **220b** is continuously formed from the toe sub-chamber **238d** to the posterior ball sub-chamber **238f**, whereby the portions of the forefoot recess **220b** surrounded by the respective forefoot sub-chambers **238d-238f** are connected to each other by the portions of the forefoot recess **220b** extending between the terminal ends **241**. The forefoot recess **220b** may also include wing portions **221b** that extend between adjacent ones of the forefoot sub-chambers **238d-238f**. In some examples, the conduits **242** that connect each of the forefoot sub-chambers **238d-238f** may form bulges along the inner portion **234** of the forefoot recess **220b**. The bulges corresponding to the conduits **242** may have a height that is less than the heights of the forefoot sub-chambers **238d-238f**. Regardless, the forefoot recess **220b** is continuous across the conduits **242**.

(98) Referring still to FIG. **11B**, the mid-foot recess **220c** is defined by the cooperation of the mid-foot sub-chamber **238g** and the conduit **242** extending between the bulb-shaped terminal ends **241** of the mid-foot sub-chamber **238g**. As shown in FIG. **12**, the segments **240** of the mid-foot sub-chamber **238g** and the conduit **242** are arranged in a substantially obround or oval shape and the mid-foot recess **220c** has outer peripheral profile that is substantially obround or oval shaped and includes a major axis extending in a lateral direction from the lateral side **22** to the medial side **24**, transverse to the longitudinal axis AF of the footwear **10**.

(99) A peripheral profile of the heel recess **220d** is defined by the heel sub-chamber **238h**. As shown, the heel recess **220d** is continuously formed through the heel region **16**, and extends from the posterior segment **240** of the heel sub-chamber **238h** to the mid-foot region **14**.

(100) With continued reference to FIGS. **11A** and **11B**, the illustrated example of the sole structure **200a** includes a plurality of foam inserts **208b-208d** associated with respective ones of the recesses **220b-220d**. Particularly, the footwear **10a** includes a forefoot insert **208b** received within the forefoot recess **220b**, a mid-foot insert **208c** received within the mid-foot recess **220c**, and a heel insert **208d** received within the heel recess **220d**. Each of the inserts **208b-208d** includes a top surface **260b-260d** and a bottom surface **262b-262d** formed on an opposite side of the foam insert **208b-208d** from the top surface **260b-260d**. A peripheral side surface **264b-264d** of each of the inserts **208b-208d** extends from the top surface **260b-260d** to the bottom surface **262b-262d**.

(101) Generally, each of the foam inserts **208b-208d** is configured to be received within and substantially fill a respective one of the recesses **220b-220d**. As described above, the top surfaces **260b-260d** of the foam inserts **208b-208d** may cooperate with the outer portion **232** of the upper surface **216a** of the bladder **206a** to form the top surface **210a** of the midsole **202a**, which may be contoured to accommodate a profile of a plantar surface of a foot. Accordingly, the foam inserts **208b-208d** may be formed such that the top surfaces **260b-260d** merge with the outer portion **232** of the bladder **206a** in a substantially tangential relationship, thereby forming a continuous and flush top surface **210a** of the midsole **202a**. As shown in FIG. **11A**, when the foam inserts **208b-208d** are assembled within the recesses **220b-220d**, the outer portion **232** of the upper surface **216a** of the bladder **206a** will be exposed between the foam inserts **208b-208d**.

(102) With reference to the cross-sectional views of FIGS. **13-16**, the foam inserts **208b-208d** are configured to fill the recesses **220b-220d** to form a substantially continuous and flush top surface **210a** of the midsole **202a**. Accordingly, the bottom surfaces **262, 262a** of the foam inserts **208b-208d** are configured to oppose or interface with the inner portion **234** of the upper surface **216a**,

while the peripheral side surfaces **264**, **264a** are configured to cooperate with the peripheral portion **236** of the upper surface **216a**. Accordingly, where the web area **228a** is substantially planar, the bottom surfaces **262b-262d** of the foam inserts **208b-208d** will also be substantially planar. However, where the inner portion **234** includes bulges (e.g., where the conduits are formed in the forefoot recess **220b**) or depressions, the bottom surfaces **262b-262d** of the inserts **208b-208d** may include corresponding recesses **266** (see FIG. **11B**) configured to receive the conduits **242**, and/or protuberances configured to be matingly received within the depressions. Likewise, where the peripheral portion **236** has a convex profile, the peripheral side surfaces **264b-264d** of the insert **208b-208d** will have a concave profile configured to receive the peripheral portion **236** of the upper surface **216a**, as shown in FIGS. **13-16**.

(103) In use, the examples of the sole structures **200**, **200a** described above provide improved comfort to the plantar surface of a foot of a wearer by minimizing localized forces that may be imparted by the bladder **206**, **206a** of the sole structure **200**, **200a**. Particularly, by including foam inserts **208-208d** on the upper surface **216**, **216a** of the bladder **206**, **206a**, between the chamber **226**, **226a**, forces imparted to the plantar surface of the foot by the chamber **226**, **226a** may be more evenly distributed along the entire plantar surface of the foot. Simultaneously, the aforementioned concept allows the overall weight of the sole structure **200**, **200b** to be minimized by implementing discrete foam inserts **208-208d** in recesses **220-220d** formed between bulged portions of the chamber **226**. Whereas conventional sole structures may include additional cushioning layers extending over top of the chamber **226**, **226a**, the sole structure **200**, **200a** of the instant disclosure only utilizes localized inserts **208-208d**. Accordingly, the amount of foam used in the sole structure **200**, **200a** is minimized, thereby minimizing overall weight of the sole structure while providing a more comfortable footbed.

(104) The following Clauses provide an exemplary configuration for an article of footwear described above.

(105) Clause 1: A sole structure for an article of footwear, the sole structure comprising a bladder including an upper surface having a first portion defining a chamber and a second portion defining at least one recess adjacent to the chamber and at least one foam insert disposed within the at least one recess and having a top surface that is substantially flush with the first portion of the upper surface of the bladder, the first portion of the upper surface being exposed adjacent to the at least one foam insert.

(106) Clause 2: The sole structure of Clause 1, wherein the at least one foam insert is disposed between a first portion of the chamber and a second portion of the chamber.

(107) Clause 3: The sole structure of Clause 1, wherein the bladder includes an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber.

(108) Clause 4: The sole structure of Clause 3, wherein the web area defines the second portion of the upper surface.

(109) Clause 5: The sole structure of Clause 1, wherein the at least one foam insert includes a first segment and a second segment and the upper surface of the bladder is exposed between the first segment and the second segment.

(110) Clause 6: The sole structure of Clause 1, wherein the at least one foam insert substantially fills the at least one recess.

(111) Clause 7: The sole structure of Clause 1, wherein the top surface of the at least one foam insert is tangent with the first portion of the chamber.

(112) Clause 8: The sole structure of Clause 1, wherein the chamber is a fluid-filled chamber.

(113) Clause 9: The sole structure of Clause 1, wherein the bladder includes a first recess in a heel region and a second recess in a forefoot region, the at least one foam insert including a first foam insert disposed within the first recess and a second foam insert disposed within the second recess.

(114) Clause 10: The sole structure of Clause 9, wherein the first portion of the bladder, a top

surface of the first foam insert, and a top surface of the second foam insert are substantially flush.

(115) Clause 11: A sole structure for an article of footwear, the sole structure comprising a bladder including a chamber and a plurality of recesses formed in an upper surface of the bladder, the plurality of recesses having peripheral profiles defined by the chamber and a plurality of foam inserts each disposed within respective ones of the plurality of the recesses and including top surfaces that are substantially flush with the upper surface of the bladder to form a substantially continuous top surface of the sole structure.

(116) Clause 12: The sole structure of Clause 11, wherein each of the plurality of the foam inserts is at least partially surrounded by the chamber.

(117) Clause 13: The sole structure of Clause 11, wherein the bladder includes an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber.

(118) Clause 14: The sole structure of Clause 13, wherein the web area defines the plurality of the recesses.

(119) Clause 15: The sole structure of Clause 11, wherein the upper surface of the bladder is exposed between the plurality of the foam inserts.

(120) Clause 16: The sole structure of Clause 11, wherein the plurality of the foam inserts substantially fill the plurality of the recesses.

(121) Clause 17: The sole structure of Clause 11, wherein top surfaces of each of the plurality of the foam inserts are substantially flush with a portion of the upper surface corresponding to the chamber.

(122) Clause 18: The sole structure of Clause 11, wherein the chamber is a fluid-filled chamber.

(123) Clause 19: The sole structure of Clause 11, wherein the plurality of recesses includes a first recess in a heel region of the sole structure and a second recess in a forefoot region of the sole structure, the plurality of inserts including a first foam insert disposed within the first recess and a second foam insert disposed within the second recess.

(124) Clause 20: The sole structure of Clause 19, wherein the plurality of recesses includes a third recess in a midfoot region of the sole structure, the plurality of foam inserts including a third foam insert disposed within the third recess.

(125) The foregoing description has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular configuration are generally not limited to that particular configuration, but, where applicable, are interchangeable and can be used in a selected configuration, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

Claims

1. A sole structure for an article of footwear, the sole structure comprising: a bladder including an upper surface having a first portion defining a chamber and a second portion defining a first recess and a second recess each in a top half of the bladder adjacent to the chamber, the first recess and the second recess each having a bottom surface within the top half of the bladder, the first recess extending continuously between a medial side of the bladder and a lateral side of the bladder from a midfoot region of the sole structure to a forefoot region of the sole structure; a first foam insert disposed within the first recess in the top half of the bladder and having a top surface that is flush with the first portion of the upper surface of the bladder; and a second foam insert disposed within the second recess in the top half of the bladder and having a top surface that is flush with the first portion of the upper surface of the bladder, a first portion of the chamber including a first segment that extends between and separates the first foam insert and the second foam insert, wherein the

first portion of the upper surface has a branch that is disposed between a frontmost end and a rearmost end of the first foam insert.

2. The sole structure of claim 1, wherein the first foam insert is disposed between the first portion of the chamber and a second portion of the chamber within a forefoot region of the bladder.
3. The sole structure of claim 2, wherein the second foam insert is disposed between a third portion of the chamber and a fourth portion of the chamber within a heel region of the bladder.
4. The sole structure of claim 1, wherein the bladder includes an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber.
5. The sole structure of claim 4, wherein the web area defines the second portion of the upper surface.
6. The sole structure of claim 1, wherein the first foam insert substantially fills the first recess and the second foam insert substantially fills the second recess.
7. The sole structure of claim 1, wherein the top surface of the first foam insert and the top surface of the second foam insert are tangent with the first portion of the chamber.
8. The sole structure of claim 1, wherein the chamber is a fluid-filled chamber.
9. The sole structure of claim 1, wherein the first segment of the chamber extends from the medial side of the bladder to the lateral side of the bladder within the midfoot region of the sole structure.
10. The sole structure of claim 1, wherein at least one of the first foam insert and the second foam insert includes a serpentine shape.
11. A sole structure for an article of footwear, the sole structure comprising: a bladder including an upper surface having a first portion defining a chamber and a second portion defining a first recess in a forefoot region of the bladder and a second recess in a heel region of the bladder, the first recess and the second recess each in a top half of the bladder and surrounded by segments of the chamber, the first recess and the second recess each having a bottom surface within the top half of the bladder, the first recess extending continuously between a medial side of the bladder and a lateral side of the bladder from a midfoot region of the sole structure to a forefoot region of the sole structure; a first foam insert disposed within the first recess in the top half of the bladder and having a top surface that is flush with the first portion of the upper surface of the bladder; and a second foam insert disposed within the second recess in the top half of the bladder and having a top surface that is flush with the first portion of the upper surface of the bladder, wherein the first portion of the upper surface has a branch that is disposed between a frontmost end and a rearmost end of the first foam insert.
12. The sole structure of claim 11, wherein the first foam insert is disposed between a first portion of the chamber and a second portion of the chamber within the forefoot region of the bladder.
13. The sole structure of claim 12, wherein the second foam insert is disposed between a third portion of the chamber and a fourth portion of the chamber within the heel region of the bladder.
14. The sole structure of claim 11, wherein the bladder includes an upper barrier layer and a lower barrier layer attached to the upper barrier layer to form a web area between segments of the chamber.
15. The sole structure of claim 14, wherein the web area defines the second portion of the upper surface.
16. The sole structure of claim 11, wherein the first foam insert substantially fills the first recess and the second foam insert substantially fills the second recess.
17. The sole structure of claim 11, wherein the top surface of the first foam insert and the top surface of the second foam insert are tangent with a first portion of the chamber.
18. The sole structure of claim 11, wherein the chamber is a fluid-filled chamber.
19. The sole structure of claim 11, wherein a segment of the chamber extends from the medial side of the bladder to the lateral side of the bladder within the midfoot region of the sole structure and separates the first foam insert and the second foam insert.

20. The sole structure of claim 11, wherein at least one of the first foam insert and the second foam insert includes a serpentine shape.
