

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415612
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Zatorski; Darek Tomasz et al.

Hybrid-electric propulsion system equipped with a coupler for switching between modes of operation

Abstract

A propulsion assembly includes a first torque source coupled with a first shaft and a second torque source coupled with a second shaft. A coupler selectively couples the first and second torque sources. When the first and second torque sources are coupled via the coupler, in response to a command to decouple the first torque source, an unloading operation is performed to decrease the torque output provided by the first torque source to a threshold, and when reached, the first shaft is decoupled from the coupler. When the first torque source is coupled with the coupler but the second torque source is not, in response to a command to couple the second torque source, a speed matching operation is performed to increase the speed of the second shaft to match a speed of the first shaft, and when the speeds are matched, the second shaft is coupled to the coupler.

Inventors: Zatorski; Darek Tomasz (Fort Wright, IN), Murrow; Kurt David (Springboro, OH), Gemin; Paul Robert (Cincinnati, OH), Cioffi; Philip M. (Schaghticoke, NY), Yagielski; John Russell (Scotia, NY)

Applicant: General Electric Company (Schenectady, NY)

Family ID: 1000008818122

Assignee: General Electric Company (Evendale, OH)

Appl. No.: 18/351725

Filed: July 13, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240025555 A1	Jan. 25, 2024

Related U.S. Application Data

Publication Classification

Int. Cl.: **B64D35/08** (20250101); **B64D27/10** (20060101); **B64D27/24** (20060101); **B64D27/33** (20240101); **B64D31/18** (20240101); **F01D15/12** (20060101); **F02C7/32** (20060101); **F02C7/36** (20060101); **F02C9/56** (20060101); B64D27/02 (20060101); F01D15/10 (20060101)

U.S. Cl.:

CPC **B64D35/08** (20130101); **B64D27/10** (20130101); **B64D27/24** (20130101); **B64D27/33** (20240101); **B64D31/18** (20240101); **F01D15/12** (20130101); **F02C7/32** (20130101); **F02C7/36** (20130101); **F02C9/56** (20130101); B64D27/026 (20240101); F01D15/10 (20130101); F05D2220/323 (20130101); F05D2240/40 (20130101); F05D2260/403 (20130101); F05D2270/052 (20130101); F05D2270/07 (20130101); F05D2270/335 (20130101); F05D2270/44 (20130101); F05D2270/62 (20130101)

Field of Classification Search

CPC: F02C (27/36); B64D (27/33); B64D (31/18); B64D (35/08); F05D (2270/052)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3675444	12/1971	Whipple	N/A	N/A
4232772	12/1979	Brissey et al.	N/A	N/A
7422543	12/2007	Ransbarger et al.	N/A	N/A
8089179	12/2011	Legros	N/A	N/A
9752509	12/2016	Clayton et al.	N/A	N/A
10415482	12/2018	Marconi et al.	N/A	N/A
10730633	12/2019	Anghel et al.	N/A	N/A
10822100	12/2019	Dindar et al.	N/A	N/A
11091272	12/2020	Kupratis et al.	N/A	N/A
11732639	12/2022	LaTulipe et al.	N/A	N/A
2014/0010652	12/2013	Suntharalingam	475/5	B64D 35/023
2017/0321601	12/2016	Lafargue	N/A	B64D 27/10
2020/0031480	12/2019	Baig et al.	N/A	N/A
2020/0290742	12/2019	Kumar et al.	N/A	N/A
2021/0108569	12/2020	Devendorf	N/A	N/A
2021/0179286	12/2020	Harvey	N/A	F02C 3/113
2022/0033097	12/2021	Botti	N/A	B64U 50/10
2022/0324582	12/2021	LaTulipe	N/A	F02B 41/10
2022/0411082	12/2021	Delbosc et al.	N/A	N/A
2024/0059422	12/2023	Bertrand	N/A	B64D 35/025

Background/Summary

PRIORITY INFORMATION (1) The present application claims priority to U.S. Provisional Patent Application No. 63/390,327 filed on Jul. 19, 2022, which is incorporated by reference herein in its entirety for all purposes.

FIELD

(1) The present disclosure relates to hybrid-electric propulsion systems for aircraft.

BACKGROUND

(2) Hybrid-electric propulsion systems are being developed to improve an efficiency of aircraft. Such propulsion systems can include a gas turbine engine, an electric machine, and a propulsor, such as a fan or propeller. The integration of an electric machine with a gas turbine engine may present certain operational challenges in balancing or shifting the power between the electric machine and the gas turbine engine, maximizing the efficiency of the entire propulsion system, and/or coupling/decoupling these components from one another for safety or other operational purposes. Accordingly, a system designed to address one or more of these challenges would be a welcome addition to the art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A full and enabling disclosure of the present disclosure, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

- (2) FIG. 1 is a schematic top view of an exemplary aircraft having a hybrid-electric propulsion system in accordance with an exemplary aspect of the present disclosure;
- (3) FIG. 2 is a schematic cross-sectional view of a propulsion assembly of the aircraft of FIG. 1;
- (4) FIG. 3 is a cross-sectional view of a coupler of the propulsion assembly of FIG. 2;
- (5) FIG. 4 is a schematic view of the coupler of FIG. 3 and depicts a first mode of operation in which a propulsor shaft, a power turbine shaft, and an electric machine shaft are all mechanically coupled with the coupler;
- (6) FIG. 5 is a schematic view of the coupler of FIG. 3 and depicts a second mode of operation in which the propulsor shaft and the power turbine shaft are mechanically coupled with the coupler while the electric machine shaft is mechanically decoupled from the coupler;
- (7) FIG. 6 is a schematic view of the coupler of FIG. 3 and depicts a third mode of operation in which the propulsor shaft and the electric machine shaft are mechanically coupled with the coupler while the power turbine shaft is mechanically decoupled from the coupler;
- (8) FIG. 7 is a schematic view of the coupler of FIG. 3 and depicts a fourth mode of operation in which the power turbine shaft is mechanically coupled with the coupler while the propulsor shaft and the electric machine shaft are mechanically decoupled from the coupler;
- (9) FIG. 8 is a schematic view of the coupler of FIG. 3 and depicts a fifth mode of operation in which the power turbine shaft and the electric machine shaft are mechanically coupled with the coupler while the propulsor shaft is mechanically decoupled from the coupler;
- (10) FIG. 9 is a schematic view of the coupler of FIG. 3 and depicts a sixth mode of operation in which the power turbine shaft, the propulsor shaft, and the electric machine shaft are mechanically decoupled from the coupler;

- (11) FIG. 10 is a data flow diagram depicting an example manner in which the coupler of FIG. 3 can be controlled to couple/decouple various components to or from the coupler;
- (12) FIG. 11 a flow diagram of a method of decoupling a turbine from a coupler in accordance with an exemplary aspect of the present disclosure;
- (13) FIG. 12 is a graph corresponding to the method of decoupling the turbine from the coupler set forth in FIG. 11 and depicts a speed of the power turbine and a speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time;
- (14) FIG. 13 a flow diagram of a method of coupling a turbine to a coupler in accordance with an exemplary aspect of the present disclosure;
- (15) FIG. 14 is a graph corresponding to the method of coupling the turbine to the coupler set forth in FIG. 13 and depicts a speed of the power turbine and a speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time;
- (16) FIG. 15 a flow diagram of a method of decoupling an electric machine from a coupler in accordance with an exemplary aspect of the present disclosure;
- (17) FIG. 16 is a graph corresponding to the method of decoupling the electric machine from the coupler set forth in FIG. 15 and depicts a speed of the power turbine and a speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time;
- (18) FIG. 17 a flow diagram of a method of coupling an electric machine to a coupler in accordance with an exemplary aspect of the present disclosure;
- (19) FIG. 18 is a graph corresponding to the method of coupling the electric machine to the coupler set forth in FIG. 17 and depicts a speed of the power turbine and a speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time;
- (20) FIG. 19 is a schematic cross-sectional view of a propulsion assembly for an aircraft in accordance with an exemplary aspect of the present disclosure;
- (21) FIG. 20 is a schematic view of a coupler of the propulsion assembly of FIG. 19 and depicts a first mode of operation in which a low pressure shaft and an electric machine shaft are mechanically coupled with the coupler;
- (22) FIG. 21 is a schematic view of the coupler of the propulsion assembly of FIG. 19 and depicts a second mode of operation in which the low pressure shaft is mechanically coupled with the coupler while the electric machine shaft is mechanically decoupled from the coupler;
- (23) FIG. 22 is a schematic view of the coupler of the propulsion assembly of FIG. 19 and depicts a third mode of operation in which the electric machine shaft is mechanically coupled with the coupler while the low pressure shaft is mechanically decoupled from the coupler;
- (24) FIG. 23 is a schematic cross-sectional view of a propulsion assembly for an aircraft in accordance with an exemplary aspect of the present disclosure;
- (25) FIG. 24 is a flow diagram for a method of operating a propulsion assembly to perform a decoupling operation;
- (26) FIG. 25 is a flow diagram for a method of operating a propulsion assembly to perform a coupling operation; and
- (27) FIG. 26 provides a computing system according to example embodiments of the present disclosure.

DETAILED DESCRIPTION

(28) Reference will now be made in detail to present embodiments of the disclosure, one or more examples of which are illustrated in the accompanying drawings. The detailed description uses numerical and letter designations to refer to features in the drawings. Like or similar designations in the drawings and description have been used to refer to like or similar parts of the disclosure.

(29) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any implementation described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other implementations. Additionally, unless specifically identified otherwise, all embodiments described herein should be considered exemplary.

(30) For purposes of the description hereinafter, the terms “upper”, “lower”, “right”, “left”, “vertical”, “horizontal”, “top”, “bottom”, “lateral”, “longitudinal”, and derivatives thereof shall relate to the embodiments as they are oriented in the figures. However, it is to be understood that the embodiments may assume various alternative variations, except where expressly specified to the contrary.

(31) As used herein, the terms “first”, “second”, and “third” may be used interchangeably to distinguish one component from another and are not intended to signify location or importance of the individual components.

(32) The terms “forward” and “aft” refer to relative positions within a gas turbine engine or vehicle, and refer to the normal operational attitude of the gas turbine engine or vehicle.

(33) The terms “upstream” and “downstream” refer to the relative direction with respect to fluid flow in a fluid pathway. For example, “upstream” refers to the direction from which the fluid flows, and “downstream” refers to the direction to which the fluid flows.

(34) The terms “coupled,” “fixed,” “attached to,” and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein.

(35) The singular forms “a”, “an”, and “the” include plural references unless the context clearly dictates otherwise.

(36) The term “at least one of” in the context of, e.g., “at least one of A, B, and C” refers only A, only B, only C, or any combination of A, B, and C.

(37) The term “substantially” means within ten percent (10%) of the stated value.

(38) Here and throughout the specification and claims, range limitations are combined and interchanged, such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise. For example, all ranges disclosed herein are inclusive of the endpoints, and the endpoints are independently combinable with each other.

(39) The term “turbomachine” or “turbomachinery” refers to a machine including one or more compressors, a heat generating section (e.g., a combustion section), and one or more turbines that together generate a torque output.

(40) The term “gas turbine engine” refers to an engine having a turbomachine as all or a portion of its power source. Example gas turbine engines include turbofan engines, turboprop engines, turbojet engines, turboshaft engines, etc.

(41) The term “combustion section” refers to any heat addition system for a turbomachine. For example, the term combustion section may refer to a section including one or more of a deflagrative combustion assembly, a rotating detonation combustion assembly, a pulse detonation combustion assembly, or other appropriate heat addition assembly. In certain example embodiments, the combustion section may include an annular combustor, a can combustor, a cannular combustor, a trapped vortex combustor (TVC), or other appropriate combustion system, or combinations thereof.

(42) The terms “low” and “high”, or their respective comparative degrees (e.g., -er, where applicable), when used with a compressor, a turbine, a shaft, or spool components, etc. each refer to relative speeds within an engine unless otherwise specified. For example, a “low turbine” or “low speed turbine” defines a component configured to operate at a rotational speed, such as a maximum allowable rotational speed, lower than a “high turbine” or “high speed turbine” at the engine.

(43) The integration of an electric machine with a gas turbine engine in a hybrid-electric propulsion system may present operational challenges in balancing or shifting the power between the electric

machine and the gas turbine engine, maximizing the efficiency of the entire propulsion system, and/or coupling/decoupling these components from one another for safety or other operational purposes. In some instances, as one example, it may be desirable to switch the torque source for driving a propulsor of an aircraft from a gas turbine engine to an electric machine, or vice versa. Coupling and/or decoupling components to switch between these modes of operation in a smooth manner has traditionally been challenging. In other instances, as another example, it may be desirable to decouple an electric machine from a spool including a turbine upon detection of an electric machine failure. By decoupling the electric machine from the spool, the electric machine may cease causing parasitic drag or acting as a power drain on the turbine. Traditionally, decoupling an electric machine from a spool with a turbine has been accomplished by using a cutter to “cut” or otherwise permanently decouple the electric machine from the spool. Repair or replacement of the electric machine and spool may require significant effort and time.

(44) Generally, it is desirable to switch a hybrid-electric propulsion system between modes of operation in a safe and reliable manner. It is further desirable to switch between modes of operation with a solution that allows components to be coupled and decoupled as desired without need for more permanent solutions, such as by cutting a shaft of a spool. In accordance with the inventive aspects of the present disclosure, assemblies and methods are disclosed for selectively mechanically coupling/decoupling an electric machine and a spool having a turbine from one another in a smooth manner. As will be explained further herein, this may be accomplished by unloading these components and synchronizing their speeds or torques prior to a decoupling or coupling operation. A coupler is provided to facilitate the selective mechanical coupling/decoupling of these features from one another.

(45) Referring now to the drawings, wherein identical numerals indicate the same elements throughout the figures, FIG. 1 is a schematic top view of an aircraft 10 in accordance with an exemplary aspect of the present disclosure. As shown, the aircraft 10 defines a longitudinal direction L1 and a longitudinal centerline 14 that extends along the longitudinal direction L1 through the aircraft 10. The aircraft 10 also defines a lateral direction L2 extending orthogonal to the longitudinal direction L1. The aircraft 10 extends between a forward end 16 and an aft end 18, e.g., along the longitudinal direction L1.

(46) The aircraft 10 includes a fuselage 12 extending longitudinally from the forward end 16 of the aircraft 10 to the aft end 18 of the aircraft 10. The aircraft 10 includes an empennage 19 at its aft end 18. Additionally, the aircraft 10 includes a wing assembly including a first, port side wing 20 and a second, starboard side wing 22. The first and second wings 20, 22 each extend laterally outward from the fuselage 12 along the lateral direction L2. The first wing 20 and a portion of the fuselage 12 together define a first side 24 of the aircraft 10, and the second wing 22 and another portion of the fuselage 12 together define a second side 26 of the aircraft 10. For this embodiment, the first side 24 of the aircraft 10 is configured as the port side of the aircraft 10 and the second side 26 of the aircraft 10 is configured as the starboard side of the aircraft 10.

(47) Each wing 20, 22 includes various control surfaces, e.g., flaps, ailerons, trim surfaces, etc. for controlling and maneuvering the aircraft 10. The empennage 19 of the aircraft 10 includes a vertical stabilizer having a rudder flap for yaw control and a pair of horizontal stabilizers each having an elevator flap for pitch control. It should be appreciated however, that in other embodiments of the present disclosure, the aircraft 10 may additionally or alternatively include any other suitable configuration. For example, in other embodiments, the aircraft 10 may include any other configuration of stabilizers.

(48) Further, the aircraft 10 of FIG. 1 includes a hybrid-electric propulsion system 50. The hybrid-electric propulsion system 50 includes a first propulsion assembly 60 and a second propulsion assembly 70. For the embodiment depicted, the first propulsion assembly 60 and second propulsion assembly 70 are each configured in a wing-mounted configuration. The first propulsion assembly 60 is mounted to the first wing 20 and the second propulsion assembly 70 is mounted to the second

wing **22**. However, one or both of the first and second propulsion assemblies **60**, **70** may be mounted at any other suitable location in other embodiments.

(49) The first propulsion assembly **60** of the hybrid-electric propulsion system includes a propulsor assembly **61**, an electric machine assembly **64**, and a gas turbine engine **69**. For this embodiment, the propulsor assembly **61**, or propulsor means, has a propulsor **62** and a propulsor shaft **63** (FIG. **2**) to which the propulsor **62** is mechanically coupled. The propulsor **62** can be a propeller or a fan, for example. In some embodiments, the propulsor shaft **63** is a single shaft that is mechanically coupled to a propulsor coupler shaft of a coupler **200** at one end and is mechanically coupled with the propulsor **62** at an opposing end. In other embodiments, optionally, a gearbox **56** can be positioned along the propulsor shaft **63** as shown in FIG. **2**. In this regard, the propulsor shaft **63** can include a first propulsor shaft **57** mechanically coupling the propulsor **62** with the gearbox **56** and a second propulsor shaft **58** mechanically coupling the gearbox **56** with the coupler **200**. The gearbox **56** can include a plurality of gears for stepping down the rotational speed of the propulsor shaft **63** to provide a more efficient rotational speed of the propulsor **62**.

(50) The electric machine assembly **64** includes an electric machine **65**. For this embodiment, the electric machine **65** is a combination motor/generator. In this regard, the electric machine **65** can function as a torque source to drive the propulsor **62** in some modes of operation, e.g., to produce thrust, and may be driven to generate electrical power in other modes of operation. Moreover, for this embodiment, the gas turbine engine **69** is configured as a turboprop engine. As will be provided in more detail herein, the propulsor **62**, the gas turbine engine **69**, and the electric machine **65** of the first propulsion assembly **60** are each selectively mechanically engageable with a coupler. The coupler is operable to transmit mechanical power between the gas turbine engine **69** and the propulsor **62**, between the electric machine **65** and the propulsor **62**, and/or between the electric machine **65** and the gas turbine engine **69** depending on the commanded mode of operation.

(51) The second propulsion assembly **70** is configured in a similar manner as the first propulsion assembly **60**. Particularly, the second propulsion assembly **70** includes a propulsor assembly **71**, an electric machine assembly **74**, and a gas turbine engine **79**. The propulsor assembly **71** has a propulsor **72** and a propulsor shaft to which the propulsor **72** is mechanically coupled. The propulsor **72** can be a propeller or a fan, for example. The electric machine assembly **74** includes an electric machine **75**. The electric machine **65** can be a combination motor/generator. In this regard, the electric machine **75** can function as a torque source to drive the propulsor **72** in some modes of operation, e.g., to produce thrust, and may be driven to generate electrical power in other modes of operation. Moreover, for this embodiment, the gas turbine engine **79** is configured as a turboprop engine just like the gas turbine engine **69** of the first propulsion assembly **60**. The propulsor **72**, the gas turbine engine **79**, and the electric machine **75** of the second propulsion assembly **70** are each selectively mechanically engageable with a coupler. The coupler of the second propulsion assembly **70** is operable to transmit mechanical power between the gas turbine engine **79** and the propulsor **72**, between the electric machine **75** and the propulsor **72**, and/or between the electric machine **75** and the gas turbine engine **79** depending on the commanded mode of operation.

(52) The hybrid-electric propulsion system **50** further includes an electric energy storage system **80**. The electric energy storage system **80** can include one or more electric energy storage devices, such as batteries, supercapacitor arrays, one or more ultracapacitor arrays, some combination of the foregoing, etc. For instance, for this embodiment, the electric energy storage system **80** includes a battery **82**. The battery **82** is electrically coupled with a direct current to direct current (DC/DC) converter **84** or voltage-regulating power supply. In some embodiments, the DC/DC converter **84** can be a bidirectional DC/DC converter. In this regard, the DC/DC converter **84** can control the electrical power drawn from the battery **82** and the electrical power provided to the battery **82** depending on whether it is desired to discharge or charge the battery **82**. The DC/DC converter **84** is electrically coupled with a power bus **86**.

(53) A power distribution unit **88** is positioned along the power bus **86**. The power distribution unit **88** can be controlled to distribute electrical power to various loads of the aircraft **10**. For instance, electrical power drawn from the battery **82** can be directed to the power distribution unit **88** across the power bus **86**, and the power distribution unit **88** can distribute the electrical power to various aircraft loads, such as the electric machine **65** and/or the electric machine **76**. A first alternating current to direct current (AC/DC) converter **90** (or first DC/AC converter **90**) associated with the electric machine **65** can be positioned along the power bus **86** for converting direct current into alternating current or vice versa. Similarly, a second AC/DC converter **92** (or second DC/AC converter) associated with the electric machine **76** can be positioned along the power bus **86** for converting direct current into alternating current or vice versa. The first AC/DC converter **90** and the second AC/DC converter **92** can both be bidirectional converters.

(54) The power distribution unit **88** and other controllable electrical elements of the hybrid-electric propulsion system **50** can be managed by a power management system. The power management system can include a supervisor controller **94** operable to control or provide data to the power distribution unit **88**, the DC/DC converter **84**, the first AC/DC converter **90**, and the second AC/DC converter **92**, among other elements, and based on such data, the switching elements of these devices can perform their respective duty cycles to control the electrical power in the hybrid-electric propulsion system **50**.

(55) As further shown in FIG. **1**, the supervisor controller **94** can form a part of a computing system **96** of the aircraft **10**. The computing system **96** of the aircraft **10** can include one or more processors and one or more memory devices embodied in one or more computing devices. For instance, as depicted in FIG. **1**, the computing system **96** includes the supervisor controller **94** as well as other computing devices, such as computing device **98** and engine controllers **52**, **54** associated with the first propulsion assembly **60** and the second propulsion assembly **70**, respectively. The engine controllers **52**, **54** may be, for example, Electronic Engine Controllers (EEC) or Electronic Control Units (ECU) that form part of a Full Authority Digital Engine Control (FADEC) system. The computing devices of the computing system **96** can be communicatively coupled with one another via a communication network. For instance, the computing device **98** located in the cockpit of the aircraft **10**, the engine controllers **52**, **54**, and the supervisor controller **94** can be communicatively coupled with one another via one or more communication links of the communication network. The communication links can include one or more wired or wireless communication links.

(56) For this embodiment, the computing device **98** is configured to receive and process inputs, e.g., from a pilot or other crew members, and/or other information. In this manner, as one example, the one or more processors of the computing device **98** can receive an input indicating a command to connect or disconnect, or stated another way, mechanically couple or decouple, the propulsor **62**, the gas turbine engine **69**, and/or the electric machine **65** to or from one another and/or the propulsor **72**, the gas turbine engine **79**, and/or the electric machine **76** to or from one another. In response to the input, the computing device **98** can route the command or instructions to the supervisor controller **94** to manage the electrical power in the hybrid-electric propulsion system **50** and to one or both of the engine controllers **52**, **54** so that they may control one or more controllable devices (e.g., one or more actuators) to implement the coupling or decoupling operation in accordance with the command.

(57) The supervisor controller **94** and other computing devices of the computing system **96** of the aircraft **10** may be configured in the same or similar manner as the computing devices of the computing system **1000** described below with reference to FIG. **26**.

(58) FIG. **2** is a schematic cross-sectional view of the first propulsion assembly of FIG. **1**. For the depicted embodiment of FIG. **2**, the propulsor **62** is a propeller, the gas turbine engine **69** is a reverse-flow engine configured as a turboprop, and the electric machine **65** is a combination motor/generator, as previously noted. The second propulsion assembly **70** can be configured in a

same or similar manner as the first propulsion assembly **60** of FIG. **1**.

(59) As shown, the gas turbine engine **69** defines an axial direction A (extending parallel to a longitudinal centerline **102** provided for reference), a radial direction R, and a circumferential direction C disposed about the longitudinal centerline **102**. The gas turbine engine **69** includes a core turbine engine **106**. The core turbine engine **106** includes a tubular cowl that encloses various elements. The core turbine engine **106** includes, in a serial flow relationship, a compressor section **120**, a combustion section **150**, a turbine section **170**, and an exhaust section **180**. The compressor section **120** includes an axial compressor **122** and a centrifugal impeller **130** positioned downstream of the axial compressor **122**. The combustion section **150** includes a combustor **152** and a fuel delivery system, including a plurality of fuel nozzles **154** disposed about the longitudinal centerline **102** and spaced apart along the circumferential direction C (only one fuel nozzle **154** is depicted in FIG. **2**). The combustor **152** defines a combustion chamber **156**.

(60) The turbine section **170** includes a gas generation turbine **172** (or a high pressure turbine) and a free or power turbine **174** (or a low pressure turbine). For this embodiment, the gas generation turbine **172** drives the compressor section **120**, or more particularly, the axial compressor **122** and the centrifugal impeller **130**. The power turbine **174** rotates about its axis of rotation independently of the gas generation turbine **172**. The compressor section **120**, combustion section **150**, turbine section **170**, and the exhaust section **180** are in fluid communication with each other and define a core air flowpath **110**.

(61) A gas generation shaft **112** drivingly connects the gas generation turbine **172** to the axial compressor **122** and the centrifugal impeller **130**. The gas generation shaft **112**, the axial compressor **122**, the centrifugal impeller **130**, and the gas generation turbine **172** collectively form a gas generation spool (or high pressure spool). A power turbine shaft **114** is mechanically coupled with the power turbine **174**. The power turbine shaft **114** and the power turbine **174** collectively form a power spool (or low pressure spool) of the gas turbine engine **69**. The power spool is not mechanically connected to the gas generation spool. The power turbine shaft **114** is spaced from the gas generation shaft **112** along the axial direction A as shown in FIG. **2**.

(62) During operation of the gas turbine engine **69**, incoming air passes through blades of the propulsor **62**, and a volume of air **190** is urged into an inlet **104** of the core turbine engine **106**. The air **190** flows downstream to the compressor section **120**. The axial compressor **122** progressively compresses the air **190**. The impeller **130** further compresses the air **190** and directs the compressed air **190** into the combustion section **150** where the compressed air **190** mixes with fuel. The air/fuel mixture is combusted in the combustor **152** to provide combustion gases **192**.

(63) The combustion gases **192** flow through the gas generation turbine **172**, which includes one or more sequential stages of turbine stator vanes and one or more sequential stages of turbine blades. The turbine blades extract thermal and/or kinetic energy from the combustion gases **192**. Combustion gases **192** subsequently flow through the power turbine **174**, where an additional amount of energy is extracted through additional stages of turbine stator vanes and turbine blades. The energy extraction from the gas generation turbine **172** supports operation of the axial compressor **122** and the impeller **130** through the gas generation shaft **112** and the energy extraction from the power turbine **174** can support operation of the propulsor **62** and/or electric machine **65** as described more fully below. The combustion gases **192** exit the gas turbine engine **69** through the exhaust section **180**.

(64) It should be appreciated that the gas turbine engine **69** depicted in FIG. **2** is provided by way of example only, and that in other embodiments, the gas turbine engine **69** may have other suitable configurations. For instance, in other embodiments, the gas turbine engine **69** may instead be configured as any other suitable turbine engine, such as a turbofan engine, turbojet engine, turboshaft, internal combustion engine, etc. Furthermore, although the gas turbine engine **69** depicted in FIG. **2** and described above is an aeronautical gas turbine engine for use with an aircraft, e.g., the aircraft **10** of FIG. **1**, in other embodiments, the gas turbine engine **69** may be

configured for any number of applications, such as a land-based, industrial gas turbine engine or an aeroderivative gas turbine engine.

(65) As further depicted in FIG. 2, in accordance with inventive aspects of the present disclosure, the first propulsion assembly **60** includes the coupler **200**. The coupler **200** can be selectively mechanically coupled with the power turbine **174**, the propulsor **62**, and the electric machine **65**. In this regard, the coupler **200** is a means for selectively mechanically coupling/decoupling the various torque sources of the first propulsion assembly **60**. Generally, the coupler **200** transmits mechanical power between the power turbine **174**, the propulsor **62**, and the electric machine **65**, depending on which of these elements are mechanically coupled with the coupler **200**. Specifically, the power turbine shaft **114** can be selectively mechanically coupled with the coupler **200**, which selectively mechanically couples the power turbine **174** with the coupler **200**. A propulsor shaft **63** mechanically coupled with the propulsor **62** can be selectively mechanically coupled with the coupler **200**, which selectively mechanically couples the propulsor **62** with the coupler **200**. An electric machine shaft **68** mechanically coupled with the electric machine **65** can be selectively mechanically coupled with the coupler **200**, which selectively mechanically couples the electric machine **65** with the coupler **200**. The electric machine shaft **68** is mechanically coupled with a rotor **66** of the electric machine **65**. The rotor **66** is rotatable about an axis of rotation relative to a stator **67** of the electric machine **65**. In some embodiments, the electric machine shaft **68** can be integral with or form part of the rotor **66** of the electric machine **65**.

(66) When the power turbine **174** and the propulsor **62** are mechanically coupled with the coupler **200**, mechanical power can be transmitted between the power turbine **174** and the propulsor **62**. For instance, the power turbine **174** can drive the propulsor **62** to produce thrust for the aircraft **10** (FIG. 1). When the electric machine **65** is mechanically coupled with the coupler **200** in addition to the power turbine **174** and the propulsor **62**, the electric machine **65** can be used as an electric motor to assist the power turbine **174** with driving the propulsor **62**, or alternatively, the power turbine **174** can drive the electric machine **65** to function as an electrical generator to generate electrical power.

(67) When the electric machine **65** and the propulsor **62** are mechanically coupled with the coupler **200**, but not the power turbine **174**, mechanical power can be transmitted between the electric machine **65** and the propulsor **62**. As one example, the electric machine **65** can be used as an electric motor to drive the propulsor **62**. As another example, the propulsor **62** can be used to drive the electric machine **65** in a generator mode so that the electric machine **65** generates electrical power, e.g., during an approach phase of a flight.

(68) When the electric machine **65** and the power turbine **174** are mechanically coupled with the coupler **200**, but not the propulsor **62**, mechanical power can be transmitted between the electric machine **65** and the power turbine **174**. As one example, the aircraft **10** can be parked on the ground and it may be desirable to charge the battery **82**, and accordingly, the gas turbine engine **69** can be operated so that the power turbine **174** drives the electric machine **65**. In this way, the electric machine **65** can generate electrical power that can be used to charge the battery **82**. It will be appreciated that other coupling scenarios are possible with respect to the power turbine **174**, the propulsor **62**, and the electric machine **65** being mechanically coupled with the coupler **200**.

(69) As further shown in FIG. 2, the first propulsion assembly **60** includes a plurality of sensors, including but not limited to, a resolver **202** associated with the propulsor shaft **63**, a resolver **204** associated with the electric machine shaft **68**, and a resolver **206** associated with the power turbine shaft **114**. The resolvers **202**, **204**, **206** are operable to measure or sense a rotational speed and an angular position of their respective shafts **63**, **68**, **114**. The resolvers **202**, **204**, **206** can output such data, e.g., to the engine controller **52** and/or to one or more processors operable to control coupling/decoupling operation of the coupler **200**. Such data can be used to facilitate smooth coupling and/or decoupling of the propulsor **62**, the electric machine **65**, and/or power turbine **174** to or from the coupler **200** as will be explained in detail herein. The resolvers **202**, **204**, **206** can be

directly mechanically coupled with their respective shafts **63**, **68**, **114** or may be offset therefrom. In alternative embodiments, each shaft **63**, **68**, **114** may include a speed sensor and a separate position sensor.

(70) FIG. **3** is a cross-sectional view of the coupler **200**. As depicted, the coupler **200** includes a housing **210** in which a plurality of components are disposed. The coupler **200** includes a transmission shaft **212** that extends between a first end **214** and a second end **216**, e.g., along the axial direction A. The transmission shaft **212** is rotatable about an axis of rotation AX and is supported by bearings, including a first bearing **218** disposed proximate the first end **214** of the transmission shaft **212** and a second bearing **219** disposed proximate the second end **216** of the transmission shaft **212**.

(71) The first end **214** of the transmission shaft **212** is mechanically coupled with a coupler propulsor shaft **220**. A linear bearing **222** is disposed between the transmission shaft **212** and the coupler propulsor shaft **220**, e.g., along the radial direction R. The linear bearing **222** facilitates linear movement of the coupler propulsor shaft **220** relative to the transmission shaft **212**. The linear bearing **222** can be a ball spline, for example. The coupler propulsor shaft **220** is selectively mechanically engageable with the propulsor shaft **63**. The coupler propulsor shaft **220** can include torque transmitting features that engage with and transmit torque to torque transmitting features of the propulsor shaft **63** (or vice versa). The torque transmitting features of the shafts **220**, **63** can couple the shafts **220**, **63** in, e.g., a dog teeth coupling, a curvic coupling, etc. For this example embodiment, the coupler propulsor shaft **220** includes teeth **224** that can selectively mesh with or otherwise engage with teeth **226** of the propulsor shaft **63**. In this regard, the propulsor shaft **63** is selectively mechanically engageable with the coupler propulsor shaft **220**. In FIG. **3**, the teeth **224** of the coupler propulsor shaft **220** are engaged with the teeth **226** of the propulsor shaft **63**. In FIG. **3**, the teeth **224**, **226** are shown schematically.

(72) The second end **216** of the transmission shaft **212** is mechanically coupled with a coupler turbine shaft **230**. A linear bearing **232** is disposed between the transmission shaft **212** and the coupler turbine shaft **230**, e.g., along the radial direction R. The linear bearing **232** facilitates linear movement of the coupler turbine shaft **230** relative to the transmission shaft **212**. The coupler turbine shaft **230** is selectively mechanically engageable with the power turbine shaft **114**. The coupler turbine shaft **230** can include torque transmitting features that engage with and transmit torque to torque transmitting features of the power turbine shaft **114** (or vice versa). The torque transmitting features of the shafts **230**, **114** can couple the shafts **230**, **114** in, e.g., a dog teeth coupling, a curvic coupling, etc. For this example embodiment, the coupler turbine shaft **230** includes teeth **234** that can selectively mesh with or otherwise engage with teeth **236** of the power turbine shaft **114**. In this regard, the power turbine shaft **114** is selectively mechanically engageable with the coupler turbine shaft **230**. In FIG. **3**, the teeth **234** of the coupler turbine shaft **230** are engaged with the teeth **236** of the power turbine shaft **114**. In FIG. **3**, the teeth **234**, **236** are shown schematically.

(73) The second end **216** of the transmission shaft **212** is also mechanically coupled with a coupler electric machine shaft **240**. A linear bearing **242** is disposed between the coupler turbine shaft **230** and the coupler electric machine shaft **240**, e.g., along the radial direction R. The linear bearing **242** facilitates linear movement of the coupler electric machine shaft **240** relative to the coupler turbine shaft **230**. The coupler electric machine shaft **240** is selectively mechanically engageable with the electric machine shaft **68**. The coupler electric machine shaft **240** can include torque transmitting features that engage with and transmit torque to torque transmitting features of the electric machine shaft **68** (or vice versa). The torque transmitting features of the shafts **240**, **68** can couple the shafts **240**, **68** in, e.g., a dog teeth coupling, a curvic coupling, etc. For the depicted embodiment, the coupler electric machine shaft **240** includes teeth **244** that can selectively mesh with or otherwise engage with teeth **246** of the electric machine shaft **68**. In this way, the electric machine shaft **68** is selectively mechanically engageable with the coupler electric machine shaft **240**. In FIG. **3**, the

teeth **234** of the coupler electric machine shaft **240** are engaged with the teeth **236** of the electric machine shaft **68**. In FIG. 3, the teeth **244**, **246** are shown schematically.

(74) As further depicted in FIG. 3, the coupler **200** includes one or more actuators **250**. For this example embodiment, two linear actuators are shown. The one or more actuators **250** can be controlled to selectively mechanically engage or disengage the propulsor shaft **63**, the power turbine shaft **114**, and/or the electric machine shaft **68** with the coupler **200**. For instance, in some modes of operation, the one or more actuators **250** can be controlled to move the coupler propulsor shaft **220** to connect or engage with the propulsor shaft **63**, e.g., as shown in FIG. 3. In other modes of operation, the one or more actuators **250** can be controlled to move the coupler propulsor shaft **220** to disconnect or disengage from the propulsor shaft **63**, e.g., by moving the coupler propulsor shaft **220** to the right from its position shown in FIG. 3, which would effectively disengage the teeth **224** of the coupler propulsor shaft **220** from the teeth **226** of the propulsor shaft **63**.

(75) Similarly, in some modes of operation, the one or more actuators **250** can be controlled to move the coupler turbine shaft **230** to connect or engage with the power turbine shaft **114**, e.g., as shown in FIG. 3. In other modes of operation, the one or more actuators **250** can be controlled to move the coupler turbine shaft **230** to disconnect or disengage from the power turbine shaft **114**, e.g., by moving the coupler turbine shaft **230** to the left from its position shown in FIG. 3, which would effectively disengage the teeth **234** of the coupler turbine shaft **230** from the teeth **236** of the power turbine shaft **114**. Further, in some modes of operation, the one or more actuators **250** can be controlled to move the coupler electric machine shaft **240** to connect or engage with the electric machine shaft **68**, e.g., as shown in FIG. 3. In other modes of operation, the one or more actuators **250** can be controlled to move the coupler electric machine shaft **240** to disconnect or disengage from the electric machine shaft **68**, e.g., by moving the coupler electric machine shaft **240** to the left from its position shown in FIG. 3, which would effectively disengage the teeth **244** of the coupler electric machine shaft **240** from the teeth **246** of the electric machine shaft **68**.

(76) When the propulsor shaft **63** is connected or mechanically engaged with the coupler **200**, mechanical power can be transmitted between the propulsor **62** and the coupler **200**. Likewise, when the power turbine shaft **114** is connected or mechanically engaged with the coupler **200**, mechanical power can be transmitted between the power turbine **174** and the coupler **200**. In addition, when the electric machine shaft **68** is connected or mechanically engaged with the coupler **200**, mechanical power can be transmitted between the electric machine **65** and the coupler **200**. Mechanical power transmitted to the coupler **200** can in turn be transmitted to any other shaft connected or mechanically engaged thereto.

(77) The propulsor **62**, the power turbine **174**, and the electric machine **65** can be selectively mechanically engaged with the coupler **200** depending on a selected mode of operation of the hybrid-electric propulsion system **50** (FIG. 1). Examples are provided below.

(78) In a first mode of operation, the propulsor shaft **63**, the power turbine shaft **114**, and the electric machine shaft **68** can all be mechanically coupled or engaged with the coupler **200**. Thus, the first mode of operation can be deemed an “all engaged” mode of operation. FIG. 4 is a schematic view of the coupler **200** and depicts a first mode of operation in which the propulsor shaft **63**, the power turbine shaft **114**, and the electric machine shaft **68** are all mechanically coupled or engaged with the coupler **200**. Particularly, as depicted, the teeth **224** of the coupler propulsor shaft **220** are engaged with the teeth **226** of the propulsor shaft **63**. Thus, the propulsor **62** is mechanically coupled with the coupler **200**. The teeth **234** of the coupler turbine shaft **230** are engaged with the teeth **236** of the power turbine shaft **114**. Accordingly, the power turbine **174** is mechanically coupled with the coupler **200**. The teeth **244** of the coupler electric machine shaft **240** are engaged with the teeth **246** of the electric machine shaft **68**. As a result, the electric machine **65** is mechanically coupled with the coupler **200**. FIG. 3 also depicts the “all engaged” mode of operation. In the first mode of operation, the power turbine **174** can drive the propulsor **62** to produce thrust for the aircraft **10**. The power turbine **174** may also drive the electric machine **65** to

generate electrical power. Alternatively, the electric machine **65** can function as a motor to drive the propulsor **62**, e.g., for a power assist operation.

(79) In a second mode of operation, the propulsor shaft **63** and the power turbine shaft **114** can be mechanically coupled with the coupler **200**, while the electric machine shaft **68** can be mechanically decoupled or disengaged from the coupler **200**. FIG. 5 is a schematic view of the coupler **200** and depicts the second mode of operation in which the propulsor shaft **63** and the power turbine shaft **114** are mechanically coupled with the coupler **200** while the electric machine shaft **68** is mechanically decoupled from the coupler **200**. Specifically, as shown in the example of FIG. 5, the teeth **224** of the coupler propulsor shaft **220** are engaged with the teeth **226** of the propulsor shaft **63**. Thus, the propulsor **62** is mechanically coupled with the coupler **200**. The teeth **234** of the coupler turbine shaft **230** are engaged with the teeth **236** of the power turbine shaft **114**. Accordingly, the power turbine **174** is mechanically coupled with the coupler **200**. Notably, the teeth **244** of the coupler electric machine shaft **240** are disengaged from the teeth **246** of the electric machine shaft **68**. The one or more actuators **250** can move the coupler electric machine shaft **240** along the axial direction A (to the left in FIG. 5), causing the teeth **244** of the coupler electric machine shaft **240** to disengage from the teeth **246** of the electric machine shaft **68**. In this way, the electric machine **65** is mechanically decoupled from the coupler **200**. In the second mode of operation, the power turbine **174** can drive the propulsor **62** to produce thrust for the aircraft **10**. The electric machine **65** can be decoupled for various reasons, such as an electric machine failure. By decoupling the electric machine **65**, e.g., in the event of an electric machine failure, the power turbine **174** need not “drag” the electric machine **65** along therewith and permanent solutions for disconnecting the electric machine **65** need not be taken, such as by using a cutter to “cut” the shaft coupling the electric machine **65** to the power turbine **174**.

(80) In a third mode of operation, the propulsor shaft **63** and the electric machine shaft **68** can be mechanically coupled with the coupler **200**, while the power turbine shaft **114** can be mechanically decoupled or disengaged from the coupler **200**. FIG. 6 is a schematic view of the coupler **200** and depicts the third mode of operation in which the propulsor shaft **63** and the electric machine shaft **68** are mechanically coupled with the coupler **200** while the power turbine shaft **114** is mechanically decoupled from the coupler **200**. Specifically, as shown in the example of FIG. 6, the teeth **224** of the coupler propulsor shaft **220** are engaged with the teeth **226** of the propulsor shaft **63**. Thus, the propulsor **62** is mechanically coupled with the coupler **200**. The teeth **244** of the coupler electric machine shaft **240** are engaged with the teeth **246** of the electric machine shaft **68**. Accordingly, the electric machine **65** is mechanically coupled with the coupler **200**. However, the teeth **234** of the coupler turbine shaft **230** are disengaged from the teeth **236** of the power turbine shaft **114**. The one or more actuators **250** can move the coupler turbine shaft **230** along the axial direction A (to the left in FIG. 6), causing the teeth **234** of the coupler turbine shaft **230** to disengage from the teeth **236** of the power turbine shaft **114**. Consequently, the power turbine **174** is mechanically decoupled from the coupler **200**. In the third mode of operation, the electric machine **65** can drive the propulsor **62** to produce thrust for the aircraft **10**, e.g., in an electric drive mode in which the gas turbine engine **69** does not function as a torque source to drive the propulsor **62**. The power turbine **174** can be decoupled for various reasons, such as a mechanical failure, a desire for quieter propulsion, fuel savings, etc. By decoupling the power turbine **174**, the electric machine **65** need not “drag” the power turbine **174** along therewith and permanent solutions for decoupling the power turbine **174** from the propulsor **62** and/or electric machine **65** need not be taken.

(81) In a fourth mode of operation, the power turbine shaft **114** can be mechanically coupled with the coupler **200**, while the propulsor shaft **63** and the electric machine shaft **68** can be mechanically decoupled from the coupler **200**. FIG. 7 is a schematic view of the coupler **200** and depicts the fourth mode of operation in which the power turbine shaft **114** is mechanically coupled with the coupler **200** while the propulsor shaft **63** and the electric machine shaft **68** are mechanically

decoupled from the coupler **200**. Specifically, as shown in the example of FIG. 7, the teeth **234** of the coupler turbine shaft **230** are engaged with the teeth **236** of the power turbine shaft **114**. Thus, the power turbine **174** is mechanically coupled with the coupler **200**. However, teeth **224**, **226** are disengaged and teeth **244**, **246** are disengaged. The one or more actuators **250** can move the coupler propulsor shaft **220** along the axial direction A (to the right in FIG. 7), causing the teeth **224** to disengage from the teeth **226**. In addition, the one or more actuators **250** can move the coupler electric machine shaft **240** along the axial direction A (to the left in FIG. 7), causing the teeth **244** to disengage from the teeth **246**. Accordingly, the propulsor **62** and the electric machine **65** are mechanically decoupled from the coupler **200**. It may be desirable implement the fourth mode of operation in some instances. For instance, it may be advantageous to start or relight the gas turbine engine **69** without any “drag” on the power turbine **174** caused by the electric machine **65** and/or propulsor **62** being mechanically coupled with the coupler **200**.

(82) In a fifth mode of operation, the power turbine shaft **114** and the electric machine shaft **68** can be mechanically coupled with the coupler **200** while the propulsor shaft **63** can be mechanically decoupled from the coupler **200**. FIG. 8 is a schematic view of the coupler **200** and depicts the fifth mode of operation in which the power turbine shaft **114** and the electric machine shaft **68** are mechanically coupled with the coupler **200** while the propulsor shaft **63** is mechanically decoupled from the coupler **200**. The teeth **224**, **226** can be disengaged while the teeth **234**, **236** can be engaged and teeth **244**, **246** can be engaged. In some instances, it may be desirable to implement the fifth mode of operation. For instance, with reference also to FIG. 1, the aircraft **10** can be parked on the ground and it may be desirable to charge the battery **82**. Accordingly, the gas turbine engine **69** can be operated so that the power turbine **174** drives the electric machine **65** without “drag” from the propulsor **62**. In this way, greater efficiency in charging the battery **82** can be achieved.

(83) In a sixth mode of operation, the power turbine shaft **114**, the propulsor shaft **63**, and the electric machine shaft **68** can be mechanically decoupled from the coupler **200**. FIG. 9 is a schematic view of the coupler **200** and depicts the sixth mode of operation in which the power turbine shaft **114**, the propulsor shaft **63**, and the electric machine shaft **68** are mechanically decoupled from the coupler **200**. This may be deemed the “all disengaged mode”. The teeth **224**, **226** can be disengaged from one another, teeth **234**, **236** can be disengaged from one another, and teeth **244**, **246** can be disengaged from one another. It will be appreciated that modes of operation other than those depicted in FIGS. 4 through 9 are possible.

(84) Turning now to FIG. 10 in addition to FIGS. 1, 2, and 3, FIG. 10 is a data flow diagram depicting an example manner in which the coupler **200** can be controlled to couple/decouple the various noted elements to or from the coupler **200**. As depicted, one or more processors of the computing system **96**, e.g., one or more processors of the engine controller **52**, can receive one or more couple/decouple commands **300**. The one or more couple/decouple commands **300** can be, for example, a turbine couple command **302** representing a command to couple the power turbine **174** with the coupler **200**, a turbine decouple command **304** representing a command to decouple the power turbine **174** from the coupler **200**, an electric machine couple command **306** representing a command to couple the electric machine with the coupler **200**, an electric machine decouple command **308** representing a command to decouple the electric machine **65** from the coupler **200**, a propulsor couple command **310** representing a command to couple the propulsor **62** with the coupler **200**, and/or a propulsor decouple command **312** representing a command to decouple the propulsor **62** from the coupler **200**.

(85) The one or more processors of the computing system **96** can also receive data, including data **320** captured by one or more of the resolvers **202**, **204**, **206**. In this regard, the data **320** can include data **322** captured by the resolver **202** that indicates a rotational speed and an angular position associated with the propulsor shaft **63**. The data **320** can also include data **324** captured by the resolver **204** that indicates a rotational speed and an angular position associated with the electric

machine shaft **68**. The data **320** can further include data **326** captured by the resolver **206** that indicates a rotational speed and an angular position associated with the power turbine shaft **114**.

(86) The one or more processors of the computing system **96** can also receive data **330** indicating one or more operating conditions and/or environmental conditions associated with operation of the aircraft **10**, the propulsor **62**, the gas turbine engine **69**, and/or the electric machine **65**. Example operating conditions and/or environmental conditions can include, without limitation, ambient temperature, humidity, or pressure, altitude, particulate matter in the ambient air, a location of the aircraft **10** (e.g., GPS coordinates), electrical power demands of the aircraft **10**, thrust demands for the aircraft **10**, information pertaining to the second propulsion assembly etc.

(87) As shown in FIG. **10**, the one or more couple/decouple commands **300**, the data **320**, and, optionally, the data **330** can be routed to a coupler control module **340**. The coupler control module **340** can be a set of instructions or control logic that can be executed by the one or more processors of the computing system **96** to generate one or more control signals **350**. In this regard, the one or more processors are configured to execute the coupler control module **340**, which causes the one or more processors to generate one or more control signals **350** based at least in part on the couple/decouple command **300**, the data **320**, and optionally, the data **330**. The one or more control signals **350** can be routed to the one or more actuators **250** of the coupler **200**. Based at least in part on the control signals **350**, the one or more actuators **250** may couple or decouple the propulsor **62**, the power turbine **174**, and/or the electric machine **65** to or from the coupler **200**, which consequently couples or decouples these element to or from each other.

(88) With reference now to FIGS. **1**, **2**, **3**, and FIGS. **11** and **12**, an example manner in which a turbine can be decoupled or disengaged from a coupler will be provided. Particularly, FIG. **11** is a flow diagram of a method **400** of decoupling a turbine in accordance with an exemplary aspect of the present disclosure. FIG. **12** is a graph depicting speed of the power turbine and speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time.

(89) At **402**, the method **400** includes providing, by a power turbine, a torque output on a coupler mechanically coupled with a propulsor to drive the propulsor. By way of example, with reference to FIG. **12**, at time t_1 , the propulsor **62**, the power turbine **174**, and the electric machine **65** are all mechanically coupled with the coupler **200**. In this regard, the first propulsion assembly **60** is being operated in the first mode of operation or “all engaged” mode.

(90) Further, from time t_1 to time t_2 , the power turbine **174** is operating in a driving mode. Thus, the power turbine **174** provides a torque output $\tau_{sub.PT}$ on the coupler **200** to drive the propulsor **62**. Stated another way, the gas turbine engine **69** can be operated to cause the power turbine **174** to rotate. Mechanical power can be transmitted from the power turbine **174** to the coupler **200** and from the coupler **200** to the propulsor **62**, e.g., by way of the transmission shaft **212** (FIG. **3**). In this way, the propulsor **62** can produce thrust for the aircraft **10**.

(91) Moreover, from time t_1 to time t_2 , the electric machine **65** acts as an electric generator to generate electrical power. The power turbine **174** drives the electric machine **65**. Mechanical power can be transmitted from the power turbine **174** to the coupler **200** and from the coupler **200** to the electric machine **65**. Accordingly, the electric machine **65** applies “drag” on the power turbine **174**, or rather, applies a generator torque output $\tau_{sub.EM-G}$ on the coupler **200**.

(92) At **404**, the method **400** includes performing, in response to a turbine decouple command, an unloading operation. Wherein performing the unloading operation includes, over an unloading period, increasing a torque output provided by an electric machine on the coupler to increase mechanical power transmission from the electric machine to the propulsor and decreasing the torque output provided by the power turbine on the coupler to decrease mechanical power transmission from the power turbine to the propulsor.

(93) Continuing with the example provided in FIG. **12**, at time t_2 , a turbine decouple command **304** (FIG. **10**) can be received, e.g., by one or more processors of the computing system **96** (FIG. **10**).

In response to the turbine decouple command **304**, an unloading operation can be performed over an unloading period. As depicted in FIG. **12**, at time t_2 , the torque output provided by the electric machine **65** on the coupler **200** increases in response to the turbine decouple command **304**. Specifically, at time t_2 , the electric machine **65** is controlled to cease operating in a generating mode so that the electric machine **65** can operate in a motoring mode to increase its torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200** to ultimately increase mechanical power transmission from the electric machine **65** to the propulsor **62**. At time t_2 , the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** decreases in response to the turbine decouple command **304**. The torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** can be decreased in one or more suitable ways, such as by decreasing the fuel provided to the combustor **152**, changing the position of one or more variable geometry components along the core air flowpath **110**, some combination thereof, etc.

(94) In some implementations, in performing the unloading operation, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is increased linearly over the unloading period. In some implementations, in performing the unloading operation, the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is decreased linearly over the unloading period. In yet other implementations, such as the implementation shown in FIG. **12**, in performing the unloading operation, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is increased linearly over the unloading period and the torque output $\tau_{\text{sub.EM-M}}$ provided by the power turbine **174** on the coupler **200** is decreased linearly over the unloading period.

(95) Further, in some implementations, in performing the unloading operation, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is increased over the unloading period at a rate and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is decreased over the unloading period at or substantially at the rate. In this way, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** and the torque output $\tau_{\text{sub.EM-PT}}$ provided by the power turbine **174** on the coupler **200** change at or substantially the same rate although one torque output is increasing and one is decreasing. This “torque matching” can facilitate stabilization of the first propulsion assembly **60** during decoupling of the power turbine **174**. The matched torques can be linear, exponential, other unique curves, etc.

(96) In addition, in some implementations, in performing the unloading operation, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is increased over the unloading period and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is decreased over the unloading period so that a net torque $\tau_{\text{sub.NET}}$ provided by the electric machine **65** and the power turbine **174** on the coupler **200** is maintained at a constant torque over the unloading period. As shown in FIG. **12**, the net torque $\tau_{\text{sub.NET}}$ provided by the electric machine **65** and the power turbine **174** on the coupler **200** is maintained at a constant torque over the unloading period, e.g., a period of time from time t_2 to time t_3 . This may help the power turbine **174** and electric machine **65** maintain a constant or substantially constant speed over the overloading period.

(97) At **406**, the method **400** includes decoupling the power turbine from the coupler when the torque output provided by the power turbine on the coupler reaches a predetermined threshold. For instance, as shown in FIG. **12**, at time t_3 , the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** reaches a predetermined threshold **TR1**, and consequently, the power turbine **174** is decoupled from the coupler **200** at time t_3 . Inputs received from the resolver **206** associated with the power turbine shaft **114** and the resolver **204** associated with the electric machine shaft **68** can be used to monitor the torque outputs provided by the electric machine and the power turbine **174** on the coupler **200** during the unloading operation. Particularly, these inputs can be used for “torque matching” and for determining when the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** reaches the predetermined threshold **TR1**. The

matched torques can be linear, exponential, other unique curves, etc.

(98) In some implementations, decoupling the power turbine **174** from the coupler **200** includes modulating the one or more actuators **250** to move the coupler turbine shaft **230** of the coupler **200** so that the teeth **234** of the coupler turbine shaft **230** disengage from the teeth **236** of the power turbine shaft **114**, e.g., as shown in FIG. **6**. Once the power turbine **174** is decoupled from the coupler **200** at time t_3 , the power turbine **174** spools down. As shown in FIG. **12**, the rotational speed of the power turbine **174** decreases from time t_3 to time t_4 . At time t_4 , the power turbine **174** ceases rotating while the electric machine **65** acting as a motor maintains its current rotational speed.

(99) In some further implementations of method **400**, when the torque output provided by the power turbine on the coupler reaches the predetermined threshold and the power turbine is decoupled from the coupler, the method **400** includes providing, by the electric machine, a torque output on the coupler to drive the propulsor to a commanded operating point. For instance, as shown in FIG. **12**, when the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** reaches the predetermined threshold TR_1 and the power turbine **174** is decoupled from the coupler **200** at time t_3 , the electric machine **65** provides a torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200** to drive the propulsor **62** to a commanded operating point, such as a commanded rotational speed. Thus, in accordance with FIGS. **11** and **12** and the accompanying text, the torque source for driving the propulsor **62** can be switched in a smooth manner from the gas turbine engine **69** to the electric machine **65**. The smooth transition is accomplished by the controlled “torque matching” of the torque outputs applied on the coupler **200** by the electric machine **65** and the power turbine **174**. Further, no cutting of the shaft or other permanent solutions need be implemented to decouple the power turbine **174**. Thus, if desired, the power turbine **174** may be coupled once again with the coupler **200**, and consequently, the electric machine **65** and/or the propulsor **62** coupled with the coupler **200**.

(100) To summarize, to mechanically decouple the power turbine **174** to switch to an electric drive mode, or to switch from the first mode of operation (FIG. **4**) to the third mode of operation (FIG. **6**), the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is decreased to “unload” the power turbine **174**, while at the same time, a motor torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is increased over the unloading period. When the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** reaches a predetermined threshold TR_1 , the power turbine **174** is mechanically decoupled from the coupler **200**. The controlled “torque matching” of the torque outputs applied on the coupler **200** by the electric machine **65** and the power turbine **174** allows for a smooth decoupling of the power turbine **174** and for a smooth transition to the electric drive mode in which the electric machine **65** is responsible for driving the propulsor **62**.

(101) With reference now to FIGS. **1**, **2**, and **3** in addition to FIGS. **13** and **14**, an example manner in which a turbine can be coupled or engaged with a coupler will be provided. Particularly, FIG. **13** is a flow diagram of a method **500** of coupling a turbine in accordance with an exemplary aspect of the present disclosure. FIG. **14** is a graph depicting speed of the power turbine and speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time.

(102) At **502**, the method **500** includes providing, by an electric machine, a torque output on a coupler mechanically coupled with a propulsor to drive the propulsor. By way of example, with reference to FIG. **14**, at time t_1 , the propulsor **62** and the electric machine **65** are mechanically coupled with the coupler **200** while the power turbine **174** is decoupled from the coupler **200**. In this regard, the first propulsion assembly **60** is being operated in the third mode of operation or the “electric drive” mode at time t_1 . Particularly, at time t_1 , the electric machine **65** acts as an electric motor to drive the propulsor **62**. That is, the electric machine **65** provides a torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200**. Accordingly, mechanical power can be transmitted from the electric machine

65 to the coupler 200 and from the coupler 200 to the propulsor 62. In this way, the propulsor 62 can produce thrust for the aircraft 10. FIG. 6 schematically depicts the coupler 200 in the third mode of operation.

(103) At 504, the method 500 includes performing, in response to a power turbine couple command, a speed matching operation. In certain implementations, performing the speed matching operation includes increasing a rotational speed of a power turbine until the rotational speed of the power turbine shaft matches or is within a predetermined range of a rotational speed of an electric machine shaft that mechanically couples the electric machine to the coupler.

(104) Continuing with the example provided in FIG. 14, at time t_2 , a turbine couple command 302 (FIG. 10) can be received, e.g., by one or more processors of the computing system 96 (FIG. 10). In response to the turbine couple command 302, a speed matching operation can be performed. As depicted in FIG. 14, at time t_2 , the rotational speed $S_{sub.PT}$ of the power turbine 174 begins increasing. The rotational speed $S_{sub.PT}$ of the power turbine 174 is increased until it matches or is within a predetermined range PR of the rotational speed $S_{sub.EM}$ of the electric machine shaft 68 that mechanically couples the electric machine 65 to the coupler 200. In this example, the rotational speed $S_{sub.PT}$ of the power turbine 174 matches or is within a predetermined range PR of the rotational speed $S_{sub.EM}$ of the electric machine shaft 68 at time t_3 . In this regard, the rotational speed $S_{sub.PT}$ of the power turbine 174 increases from time t_2 to time t_3 . The torque output $\tau_{sub.PT}$ of the power turbine 174 increases from time t_2 to time t_3 , but the torque output $\tau_{sub.PT}$ of the power turbine 174 is not applied to the coupler 200 as the power turbine 174 is mechanically decoupled from the coupler 200 during this time period.

(105) In some implementations, the method 500 can include monitoring whether the rotational speed $S_{sub.PT}$ of the power turbine shaft 114 matches or is within the predetermined range PR of the rotational speed $S_{sub.PT}$ of the electric machine shaft 68 based at least in part on one or more inputs received from the resolver 204 associated with the electric machine shaft 68 and one or more inputs received from the resolver 206 associated with the power turbine shaft 114. The inputs provided by the resolvers 204, 206 can indicate a rotational speed and an angular position of their associated shafts 68, 114.

(106) In some implementations, the rotational speed $S_{sub.PT}$ of the power turbine 174 can be increased linearly in the speed matching operation as shown in FIG. 14. This may allow for improved predictions as to when the rotational speed $S_{sub.PT}$ of the power turbine 174 is expected to match or fall within the predetermined range PR of the rotational speed $S_{sub.EM}$ of the electric machine shaft 68. The rotational speed $S_{sub.PT}$ of the power turbine 174 can be increased by increasing the fuel provided to the combustor 152, for example. The one or more processors of the computing system 96 may predict when the rotational speed $S_{sub.PT}$ of the power turbine 174 is expected to match or fall within the predetermined range PR of the rotational speed $S_{sub.EM}$ of the electric machine shaft 68 so that fuel provided to the combustor 152 can be controlled intelligently.

(107) At 506, the method 500 includes, when the rotational speed of the power turbine shaft matches or is within the predetermined range of the rotational speed of the electric machine shaft, mechanically coupling the power turbine to the coupler so that the power turbine drives the propulsor. Accordingly, with the rotational speed $S_{sub.PT}$ of the power turbine 174 matched or within the predetermined range PR of the rotational speed $S_{sub.EM}$ of the electric machine shaft 68, the power turbine 174 can be mechanically coupled with the coupler 200. Mechanically coupling the power turbine 174 to the coupler 200 can include modulating the one or more actuators 250 to move the coupler turbine shaft 230 of the coupler 200 so that the teeth 234 of the coupler turbine shaft 230 engage the teeth 236 of the power turbine shaft 114. When the power turbine 174 is mechanically coupled with the coupler 200 at time t_3 , the power turbine 174 applies or provides a torque output $\tau_{sub.PT}$ on the coupler 200. Accordingly, mechanical power can be transmitted from the power turbine 174 to the coupler 200, and from the coupler 200 to the

propulsor **62**.

(108) In some implementations, after the power turbine **174** is mechanically coupled to the coupler **200**, the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is held constant or substantially constant for a predetermined time. For instance, as shown in FIG. **14**, the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is held constant or substantially constant for a predetermined time, which corresponds to a time period spanning from time t_3 to time t_4 . This may prevent or reduce the chance of an overspeed condition of the power turbine **174**. For instance, this may prevent the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** from reaching an overspeed threshold OTR_1 .

(109) In some implementations, after the power turbine **174** is mechanically coupled to the coupler **200** so that the power turbine **174** drives the propulsor **62**, the method **500** can further include decreasing the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** to decrease mechanical power transmission from the electric machine **65** to the propulsor **62**. In such implementations, the method **500** can further include increasing the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** to increase mechanical power transmission from the power turbine **174** to the propulsor **62**. In this way, the power turbine **174** begins to replace the electric machine **65** as the torque source for driving the propulsor **62**. During the turbine loading period, which corresponds to a time period spanning from time t_4 to time t_5 , the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is shown decreasing and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is shown increasing.

(110) In some implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased linearly, e.g., over the turbine loading period. In some implementations, the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is increased linearly, e.g., over the turbine loading period. In yet other implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased linearly and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is increased linearly, e.g., over the turbine loading period.

(111) In yet other implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is increased so that a net torque $\tau_{\text{sub.NET}}$ provided by the electric machine **65** and the power turbine **174** on the coupler **200** is maintained within a predetermined margin (e.g., within ten percent (10%), within five percent (5%), within two percent (2%), etc.) of a commanded torque for the propulsor **62**. In some further implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is increased so that a net torque $\tau_{\text{sub.NET}}$ provided by the electric machine **65** and the power turbine **174** on the coupler **200** is maintained at or substantially at a constant torque over the turbine loading period. For instance, as shown in FIG. **14**, the net torque $\tau_{\text{sub.NET}}$ provided by the electric machine **65** and the power turbine **174** on the coupler **200** is maintained at or substantially at a constant torque over the turbine loading period, or from time t_4 to time t_5 in this example.

(112) In other implementations, to facilitate “torque matching”, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased at a rate and the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** is increased at or substantially at the rate. In this way, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** and the torque output $\tau_{\text{sub.EM-PT}}$ provided by the power turbine **174** on the coupler **200** change at or substantially the same rate although one torque output is increasing and one is decreasing. This “torque matching” can facilitate stabilization of the first propulsion assembly **60** after coupling of the power turbine **174**. The matched torques can be linear, exponential, other unique curves, etc.

(113) In yet other implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased so that the electric machine **65** may switch from a motoring mode to a generating mode to generate electrical power. For instance, as depicted in FIG. **14**, at time t_5 , the electric machine **65** switches from a motoring mode of operation to a generating mode of operation. Stated another way, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased so that the torque output provided on the coupler **200** switches from a motor torque output $\tau_{\text{sub.EM-M}}$ to a generator torque output $\tau_{\text{sub.EM-G}}$. In the generating mode of operation, the power turbine **174** drives the electric machine **65**. Specifically, mechanical power can be transmitted from the power turbine **174** to the coupler **200**, and from the coupler **200** to the electric machine **65**. When the electric machine **65** switches from motor to generator, the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** remains synchronized with the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174**.

(114) In some alternative implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased so that the electric machine **65** ceases providing a motor torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200**, and when the electric machine **65** ceases to provide a motor torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200**, the method **500** can include mechanically decoupling the electric machine **65** from the coupler **200**. Mechanically decoupling the electric machine **65** from the coupler **200** can include modulating the one or more actuators **250** to move the coupler electric machine shaft **240** of the coupler **200** so that the teeth **244** of the coupler electric machine shaft **240** disengage the teeth **246** of the electric machine shaft **68**.

(115) To summarize, to mechanically couple the power turbine **174** to the coupler **200** to switch from an electric drive mode to an engine drive mode, or to switch from the third mode of operation (FIG. **6**) to the fourth mode of operation (FIG. **4**), the speed of the power turbine **174** is increased whilst the power turbine **174** is decoupled from the coupler **200**. This allows the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** to match or fall within the predetermined range PR_1 of the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65**. When the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** matches or is within the predetermined range PR_1 of the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65**, the power turbine **174** is mechanically coupled with the coupler **200**. In some implementations, in mechanically coupling the power turbine **174** with the coupler **200**, not only must the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** match or fall within the predetermined range PR_1 of the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65**, but the teeth **236** of the power turbine shaft **114** and the teeth **234** of the coupler turbine shaft **230** must be positioned for meshing engagement prior to mechanically connecting the power turbine shaft **114** and the coupler turbine shaft **230**. The synchronization of the speeds of the electric machine **65** and the power turbine **174** and accounting for the position of the teeth **236**, **234** of the respective shafts **114**, **230** allows for smooth coupling operation. The electric machine **65** can be smoothly transitioned to a generator mode to generate electrical power or can be decoupled from the coupler **200** once the torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** has reached a commanded operating point.

(116) With reference now to FIGS. **1**, **2**, **3**, and FIGS. **15** and **16**, an example manner in which an electric machine can be decoupled or disengaged from a coupler will be provided. Particularly, FIG. **15** is a flow diagram of a method **600** of decoupling an electric machine in accordance with an exemplary aspect of the present disclosure. FIG. **16** is a graph depicting speed of the power turbine and speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time.

(117) At **602**, the method **600** includes operating an electric machine in a generator mode, the electric machine being mechanically coupled with a coupler to which a propulsor and a power turbine of a gas turbine engine are also mechanically coupled. By way of example, with reference to FIG. **16**, at time t_1 , the propulsor **62**, the power turbine **174**, and the electric machine **65** are all mechanically coupled with the coupler **200**. In this regard, the first propulsion assembly **60** is being

operated in the first mode of operation or “all engaged” mode.

(118) Further, from time t_1 to time t_2 , the power turbine **174** is operating in a driving mode. Thus, the power turbine **174** provides a torque output $\tau_{\text{sub.PT}}$ on the coupler **200** to drive the propulsor **62**. Stated another way, the gas turbine engine **69** can be operated to cause the power turbine **174** to rotate. Mechanical power can be transmitted from the power turbine **174** to the coupler **200** and from the coupler **200** to the propulsor **62**, e.g., by way of the transmission shaft **212** (FIG. 3). In this way, the propulsor **62** can produce thrust for the aircraft **10**.

(119) In addition, from time t_1 to time t_2 , the electric machine **65** acts as an electric generator to generate electrical power. The power turbine **174** drives the electric machine **65**. Mechanical power can be transmitted from the power turbine **174** to the coupler **200** and from the coupler **200** to the electric machine **65**. Accordingly, the electric machine **65** applies “drag” on the power turbine **174**, or rather, applies a generator torque output $\tau_{\text{sub.EM-G}}$ on the coupler **200**. The power turbine **174** and the electric machine **65** have a same rotational speed from time t_1 to time t_2 , and also from time t_2 to time t_3 as depicted in FIG. 16.

(120) At **604**, the method **600** includes, in response to an electric machine decouple command, decreasing a generator torque output that the electric machine applies on the coupler over an electric machine unloading period. Continuing with the example provided in FIG. 16, at time t_2 , an electric machine decouple command **308** (FIG. 10) can be received, e.g., by one or more processors of the computing system **96** (FIG. 10). In response to the electric machine decouple command **308**, an electric machine unloading operation can be performed. The electric machine unloading operation can include decreasing the generator torque output $\tau_{\text{sub.EM-G}}$ that the electric machine **65** applies on the coupler **200** over the electric machine unloading period. In this regard, the load that the electric machine **65** puts on the power turbine **174** decreases. As depicted, the generator torque output $\tau_{\text{sub.EM-G}}$ that the electric machine **65** applies on the coupler **200** can be decreased linearly over the electric machine unloading period.

(121) In some implementations, the torque output $\tau_{\text{sub.PT}}$ provided on the coupler **200** by the power turbine **174** can decrease, e.g., linearly, over the electric machine unloading period, or a time period spanning from time t_2 to time t_3 in this example. In this way, the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** can be maintained at a constant speed despite the decreasing load or generator torque output $\tau_{\text{sub.EM-G}}$ applied by the electric machine **65** on the coupler **200**. For instance, the fuel flow to the combustor **152** can be decreased to decrease the torque output $\tau_{\text{sub.PT}}$ provided on the coupler **200** by the power turbine **174**. In other implementations, the torque output $\tau_{\text{sub.PT}}$ provided on the coupler **200** by the power turbine **174** can remain constant over the electric machine unloading period.

(122) At **606**, the method **600** includes, decoupling the electric machine from the coupler when the generator torque output that the electric machine applies on the coupler reaches a predetermined threshold. For instance, as shown in FIG. 16, at time t_3 , the generator torque output $\tau_{\text{sub.EM-G}}$ that the electric machine **65** applies on the coupler **200** reaches a predetermined threshold TR_2 . Consequently, at time t_3 , the electric machine **65** is decoupled from the coupler **200**. When the electric machine **65** is decoupled at time t_3 , the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** decreases as the electric machine **65** is no longer mechanically coupled with the coupler **200** and thus mechanical power is being transmitted thereto. At time t_4 , the electric machine ceases rotating while the power turbine **174** maintains its rotational speed $S_{\text{sub.PT}}$. Unloading the generator torque output $\tau_{\text{sub.EM-G}}$ applied by the electric machine **65** on the coupler **200** prior to decoupling the electric machine **65** therefrom facilitates a smooth decoupling operation.

(123) In some implementations, decoupling the electric machine from the coupler **200** includes modulating the one or more actuators **250** to move the coupler electric machine shaft **240** of the coupler **200** so that the teeth **244** of the coupler electric machine shaft **240** disengage from the teeth **246** of the electric machine shaft **68**, e.g., as shown in FIG. 5.

(124) Inputs received from the resolver **206** associated with the power turbine shaft **114** and the

resolver **204** associated with the electric machine shaft **68** can be used to monitor the generator torque output $\tau_{\text{sub.EM-G}}$ provided by the electric machine on the coupler **200** and the torque output provided by the power turbine **174** on the coupler **200** during the electric machine unloading operation. Particularly, these inputs can be used for determining when the generator torque output $\tau_{\text{sub.EM-G}}$ provided by the electric machine **65** on the coupler **200** reaches the predetermined threshold **TR2**.

(125) To summarize, to mechanically decouple the electric machine **65** to switch from the first mode of operation (**FIG. 4**) to the fourth mode of operation (**FIG. 7**), the generator torque output $\tau_{\text{sub.EM-G}}$ provided by the electric machine **65** on the coupler **200** is decreased to “unload” the electric machine **65**. The torque output $\tau_{\text{sub.PT}}$ provided by the power turbine **174** on the coupler **200** can remain the same or can be decreased over the unloading period. When the generator torque output $\tau_{\text{sub.EM-G}}$ provided by the electric machine **65** on the coupler **200** reaches a predetermined threshold **TR2**, the electric machine **65** is mechanically decoupled from the coupler **200**. The controlled unloading of the generator torque output $\tau_{\text{sub.EM-G}}$ allows for a smooth decoupling of the electric machine **65**.

(126) With reference now to **FIGS. 1, 2, 3**, and **FIGS. 17 and 18**, an example manner in which an electric machine can be decoupled or disengaged from a coupler will be provided. Particularly, **FIG. 17** is a flow diagram of a method **700** of coupling an electric machine in accordance with an exemplary aspect of the present disclosure. **FIG. 18** is a graph depicting speed of the power turbine and speed of the electric machine as functions of time and a torque output of the power turbine and a torque output of the electric machine as functions of time.

(127) At **702**, the method **700** includes providing, by a power turbine of a gas turbine engine, a torque output on a coupler mechanically coupled with a propulsor so that the power turbine drives the propulsor. By way of example, with reference to **FIG. 18**, at time **t1**, the propulsor **62** and the power turbine **174** are mechanically coupled with the coupler **200** while the electric machine **65** is decoupled from the coupler **200**. In this regard, the first propulsion assembly **60** is being operated in the second mode of operation or the “engine drive mode” at time **t1**. Particularly, at time **t1**, the power turbine **174** provides a torque output $\tau_{\text{sub.PT}}$ on the coupler **200**. Accordingly, mechanical power can be transmitted from the power turbine **174** to the coupler **200** and from the coupler **200** to the propulsor **62**. In this way, the propulsor **62** can produce thrust for the aircraft **10**. **FIG. 5** schematically depicts the coupler **200** in the second mode of operation, or the “engine drive mode”.

(128) At **704**, the method **700** includes, in response to an electric machine couple command, increasing, while an electric machine is mechanically decoupled from the coupler, a rotational speed of the electric machine to match or be within a predetermined range of a rotational speed of the power turbine.

(129) Continuing with the example provided in **FIG. 18**, at time **t2**, an electric machine couple command **306** (**FIG. 10**) can be received, e.g., by one or more processors of the computing system **96** (**FIG. 10**). In response to the electric machine couple command **306**, a speed matching operation can be performed. As depicted in **FIG. 18**, at time **t2**, the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** begins increasing. To achieve the increase in rotational speed $S_{\text{sub.EM}}$ of the electric machine electrical power can be directed to the electric machine **65**. As one example, electrical power from the battery **82** can be directed to the electric machine **65** so that the electric machine **65** increases speed. As another example, electrical power generated by the electric machine **76** of the second propulsion assembly **70** can be directed to the electric machine **65** so that the electric machine **65** increases speed. The torque output or motoring torque $\tau_{\text{sub.EM-M}}$ of the electric machine **65** increases proportionally with the increase in rotational speed $S_{\text{sub.EM}}$ of the electric machine **65**, however, the motoring torque $\tau_{\text{sub.EM-M}}$ of the electric machine **65** is not applied to the coupler **200** during the speed matching period, or a time spanning between time **t2** and time **t3** in this example, as the electric machine **65** is not yet coupled with the coupler **200** during this time period.

(130) As shown in FIG. 18, the rotational speed $S_{sub.EM}$ of the electric machine 65 is increased until it matches or is within a predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the power turbine 174. In this example, the rotational speed $S_{sub.EM}$ of the electric machine 65 matches or is within a predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the electric machine 65 at time t_3 . In this regard, the rotational speed $S_{sub.EM}$ of the electric machine 65 increases from time t_2 to time t_3 .

(131) In some implementations, the method 700 can include monitoring whether the rotational speed $S_{sub.EM}$ of the electric machine shaft 68 matches or is within the predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the power turbine shaft 114 based at least in part on one or more inputs received from the resolver 204 associated with the electric machine shaft 68 and one or more inputs received from the resolver 206 associated with the power turbine shaft 114. The inputs provided by the resolvers 204, 206 can indicate a rotational speed and an angular position of their associated shafts 68, 114.

(132) In some implementations, the rotational speed $S_{sub.EM}$ of the electric machine can be increased linearly during the speed matching operation as shown in FIG. 18. This may allow for improved predictions as to when the rotational speed $S_{sub.EM}$ of the electric machine 65 is expected to match or fall within the predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the power turbine shaft 114. The one or more processors of the computing system 96 may predict when the rotational speed $S_{sub.EM}$ of the electric machine 65 is expected to match or fall within the predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the power turbine shaft 114 so that the first AC/DC converter 90 and/or other power electronics of the hybrid-electric propulsion system can be controlled intelligently.

(133) At 706, the method 700 includes mechanically coupling the electric machine with the coupler when the rotational speed of the electric machine matches or is within the predetermined range of the rotational speed of the power turbine. Continuing with the example from above, with the rotational speed $S_{sub.EM}$ of the electric machine 65 matched or within the predetermined range PR2 of the rotational speed $S_{sub.PT}$ of the power turbine 174, the electric machine 65 can be mechanically coupled with the coupler 200. Mechanically coupling the electric machine 65 to the coupler 200 can include modulating the one or more actuators 250 to move the coupler electric machine shaft 240 of the coupler 200 so that the teeth 244 of the coupler electric machine shaft 240 engage the teeth 246 of the electric machine shaft 68. When the electric machine 65 is mechanically coupled with the coupler 200, the electric machine 65 applies or provides a motor torque output $\tau_{sub.EM-M}$ on the coupler 200.

(134) In some implementations, after the electric machine 65 is mechanically coupled to the coupler 200, the motor torque output $\tau_{sub.EM-M}$ provided by the electric machine 65 on the coupler 200 can be held constant or substantially constant for a predetermined time. For instance, as shown in FIG. 18, the motor torque output $\tau_{sub.EM-M}$ provided by the electric machine 65 on the coupler 200 is held constant or substantially constant for a predetermined time, which corresponds to a time period spanning from time t_3 to time t_4 . This may prevent or reduce the chance of an overspeed condition of the electric machine 65. For instance, this may prevent the rotational speed $S_{sub.EM}$ of the electric machine 65 from reaching an overspeed threshold OTR2.

(135) In some implementations, after the electric machine 65 is mechanically coupled to the coupler 200, the method 700 can further include decreasing the motor torque output $\tau_{sub.EM-M}$ provided by the electric machine 65 on the coupler 200. For instance, as shown in FIG. 18, after the motor torque output $\tau_{sub.EM-M}$ is held constant from time t_3 to time t_4 , the motor torque output $\tau_{sub.EM-M}$ provided by the electric machine 65 on the coupler 200 is decreased from time t_4 to time t_5 . The motor torque output $\tau_{sub.EM-M}$ can be decreased linearly, for example. At time t_5 , the electric machine ceases applying a motor torque output $\tau_{sub.EM-M}$ on the coupler 200.

Accordingly, in some implementations, the method 700 can include decreasing the motor torque output $\tau_{sub.EM-M}$ provided by the electric machine 65 on the coupler 200 so that the electric

machine **65** ceases providing a motor torque output $\tau_{\text{sub.EM-M}}$ on the coupler **200**.

(136) Further, in some implementations, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased so that the electric machine **65** may switch from a motoring mode to a generating mode, e.g., so that the electric machine **65** generates electrical power. For instance, as depicted in FIG. **18**, at time t_5 , the electric machine **65** switches from a motoring mode of operation to a generating mode of operation. Stated another way, the torque output $\tau_{\text{sub.EM-M}}$ provided by the electric machine **65** on the coupler **200** is decreased so that the torque output provided on the coupler **200** switches from a motor torque output $\tau_{\text{sub.EM-M}}$ to a generator torque output $\tau_{\text{sub.EM-G}}$. In the generating mode of operation, the power turbine **174** drives the electric machine **65**. Specifically, mechanical power can be transmitted from the power turbine **174** to the coupler **200**, and from the coupler **200** to the electric machine **65**. When the electric machine **65** switches from motor to generator, the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** can remain synchronized with the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174** as shown in FIG. **18**.

(137) To summarize, to mechanically couple the electric machine **65** to utilize it for electrical power generation, or to switch from the second mode of operation (FIG. **4**) to the first mode of operation (FIG. **4**), the speed of the electric machine **65** is first increased so that the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** matches or is within the predetermined range PR_2 of the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174**. When the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** matches or is within the predetermined range PR_2 of the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174**, the electric machine **65** is mechanically coupled with the coupler **200**. In some implementations, in mechanically coupling the electric machine **65** with the coupler **200**, not only must the rotational speed $S_{\text{sub.EM}}$ of the electric machine **65** match or fall within the predetermined range PR_2 of the rotational speed $S_{\text{sub.PT}}$ of the power turbine **174**, but the teeth **246** of the electric machine shaft **68** and the teeth **244** of the coupler electric machine shaft **240** must be positioned for meshing engagement prior to mechanically connecting the electric machine shaft **68** and the coupler electric machine shaft **240**. The synchronization of the speeds of the electric machine **65** and the power turbine **174** and accounting for the position of the teeth **246**, **244** of the respective shafts **68**, **240** allows for smooth coupling operation. As the electric machine **65** acts a motor to increase its speed to match the speed of the power turbine **174**, when mechanically coupled, the electric machine **65** applies a motor torque output $\tau_{\text{sub.EM-M}}$ to the coupler **200**. To switch the electric machine **65** from operating in a motor mode to a generator mode, the motor torque output $\tau_{\text{sub.EM-M}}$ applied to the coupler **200** by the electric machine **65** is decreased so that the electric machine **65** can be smoothly transitioned to a generator mode.

(138) FIG. **19** is a schematic cross-sectional view of a propulsion assembly **900** for an aircraft in accordance with an exemplary aspect of the present disclosure. As depicted in the example of FIG. **19**, the propulsion assembly **900** includes a gas turbine engine **910** and an electric machine **930** that is selectively mechanically engageable with a spool thereof by way of a coupler **950**. The gas turbine engine **910** can be a turbofan for an aircraft, for example.

(139) For this embodiment, the gas turbine engine **910** includes a fan **912**, which may be ducted by a fan casing or may be unducted. The gas turbine engine **910** includes core turbine engine that includes, in a serial flow relationship, a compressor section, a combustion section, a turbine section, and an exhaust section. The compressor section includes a booster or low pressure compressor **914** and a high pressure compressor **916**. The combustion section includes a combustor **918**. A fuel system **920** may provide fuel to the combustor **918**. The turbine section includes a high pressure turbine **922** and a low pressure turbine **924**. The low pressure compressor **914** and the low pressure turbine **924** are mechanically coupled by a low pressure shaft **926**. The low pressure compressor **914**, the low pressure turbine **924**, and the low pressure shaft **926** collectively form a low pressure spool. The high pressure compressor **916** and the high pressure turbine **922** are mechanically coupled by a high pressure shaft **928**. The high pressure compressor **916**, the high

pressure turbine **922**, and the high pressure shaft **928** collectively form a high pressure spool. In some embodiments, the gas turbine engine **910** can optionally include a gearbox **915** that mechanically couples the fan **912** with the low pressure shaft **926**. The gearbox **915** can include a plurality of gears for stepping down the rotational speed of the low pressure shaft **926** to provide a more efficient rotational fan speed.

(140) The electric machine **930** has a rotor **932** and a stator **934** and has an associated electric machine shaft **936**. The electric machine **930** and the electric machine shaft **936** form at least a part of an electric machine assembly. The electric machine **930** is operable in a motor mode and a generator mode. The coupler **950** is configured and may be controlled in the same manner as the coupler **200** shown and described herein, except that, for this embodiment, the coupler **950** is a two-way coupler. The coupler **200** provided herein is configured as a three-way coupler. The low pressure shaft **926** and the electric machine shaft **936** associated with the electric machine **930** are both selectively mechanically engageable with the coupler **950**, e.g., with respective coupler shafts of the coupler **950**. In this regard, the electric machine **930** is selectively mechanically engageable with the low pressure spool. A resolver **940** associated with the electric machine shaft **936** can provide speed and position inputs associated with the electric machine shaft **936** and a resolver **942** associated with the low pressure shaft **926** can provide speed and position inputs associated with the low pressure shaft **926**.

(141) Further, optionally, the gas turbine engine **910** can include a brake **929** that is selectively mechanically engageable with a shaft that is selectively mechanically engageable with the coupler **950**. For instance, for the depicted embodiment of FIG. **19**, the brake **929** is selectively mechanically engageable with the low pressure shaft **926**. However, in other embodiments, the brake **929** can be selectively mechanically engageable with the electric machine shaft **936**. The brake **929**, when commanded, can mechanically engage the low pressure shaft **926**, e.g., to reduce the rotational speed thereof. In some other embodiments, the gas turbine engine **910** can include at least two brakes, including a first brake selectively mechanically engageable the low pressure shaft **926** and a second brake selectively mechanically engageable the electric machine shaft **936**. Although the brake **929** is depicted in the illustrated embodiment of FIG. **19**, it will be appreciated that a brake can be incorporated in other embodiments provided herein, such as in the embodiments of FIGS. **2** and **23**.

(142) In a first mode of operation, the low pressure shaft **926** and the electric machine shaft **936** can be mechanically coupled with the coupler **950**. FIG. **20** is a schematic view of the coupler **950** of FIG. **19** and depicts the first mode of operation in which the low pressure shaft **926** and the electric machine shaft **936** are mechanically coupled with the coupler **950**. That is, torque transmitting features of the low pressure shaft **926** are engaged with torque transmitting features of a coupler shaft **960** of the coupler **950** and torque transmitting features of the electric machine shaft **936** are engaged with torque transmitting features of a coupler electric machine shaft **970** of the coupler **950**. Specifically, as shown, teeth **964** of the coupler shaft **960** are engaged with teeth **966** of the low pressure shaft **926**. Thus, the low pressure spool, which includes the low pressure turbine **924** (FIG. **19**), is mechanically coupled with the coupler **950**. Moreover, teeth **974** of the coupler electric machine shaft **970** are engaged with teeth **976** of the electric machine shaft **936**. Thus, the electric machine **930** is mechanically coupled with the coupler **950**. As they electric machine **930** and the low pressure spool are both mechanically coupled with the coupler **950**, they are effectively mechanically coupled with each other and mechanical power can be transmitted therebetween, e.g., by a transmission shaft **952** of the coupler **950**. In the first mode of operation, the electric machine **930** can be driven by the low pressure spool, or rather, the low pressure turbine **924**, to operate in a generator mode. Alternatively, the electric machine **930** can be operated in a motor mode to drive the low pressure spool, e.g., for a power assist during a takeoff or climb phase of flight.

(143) In a second mode of operation, the low pressure shaft **926** can be mechanically coupled with

the coupler **950** while the electric machine shaft **936** is mechanically decoupled from the coupler **950**. FIG. **21** is a schematic view of the coupler **950** of FIG. **19** and depicts the second mode of operation in which the low pressure shaft **926** is mechanically coupled with the coupler **950** while the electric machine shaft **936** is mechanically decoupled from the coupler **950**. Particularly, as shown, the teeth **964** of the coupler shaft **960** are engaged with the teeth **966** of the low pressure shaft **926**. Thus, the low pressure spool, which includes the low pressure turbine **924** (FIG. **19**), is mechanically coupled with the coupler **950**. Moreover, the teeth **974** of the coupler electric machine shaft **970** are disengaged from the teeth **976** of the electric machine shaft **936**. One or more actuators (not shown) can move the coupler electric machine shaft **970** along the axial direction A (to the left in FIG. **21**), causing the teeth **974** of the coupler electric machine shaft **970** to disengage from the teeth **976** of the electric machine shaft **936**. In this way, the electric machine **930** is mechanically decoupled from the coupler **950**, and consequently, the electric machine **930** is mechanically decoupled from the low pressure spool. A linear bearing **972** is disposed between the transmission shaft **952** and the coupler electric machine shaft **970**, e.g., along the radial direction. The linear bearing **972** facilitates linear movement of the coupler electric machine shaft **970** relative to the transmission shaft **952**. The linear bearing **972** can be a ball spline, for example.

(144) The electric machine **930** can be decoupled from the coupler **950** for various reasons, such as detection of an electric machine failure. By decoupling the electric machine **930**, e.g., in the event of an electric machine failure, the low pressure spool need not “drag” the electric machine **930** along therewith and permanent solutions for disconnecting the electric machine **930** need not be taken, such as by using a cutter to “cut” the shaft coupling the electric machine **930** to the low pressure spool.

(145) Moreover, in some embodiments, in response to detection of a failure associated with the electric machine **930**, the electric machine **930** can be mechanically decoupled from the low pressure shaft **926** after an unloading period, and during the unloading period, the brake **929** can be controlled to mechanically engage the low pressure shaft **926** to reduce the rotational speed of the low pressure shaft **926**, and consequently, the rotor **932** of the electric machine **930**. This may prevent damage to the coupler **950** and may also reduce the rotational speed of the electric machine **930** quicker than if the brake **929** was not applied. In yet other embodiments, in response to detection of a failure associated with the electric machine **930**, the electric machine **930** can remain mechanically coupled with the coupler **950** and the brake **929** can be controlled to mechanically engage the low pressure shaft **926** to reduce the rotational speed of the low pressure shaft **926**, and consequently, the rotor **932** of the electric machine **930**. This may help reduce further damage to the electric machine **930** or allow for a health assessment of the electric machine **930** at reduced speed.

(146) In a third mode of operation, the electric machine shaft **936** can be mechanically coupled with the coupler **950** while the low pressure shaft **926** is mechanically decoupled from the coupler **950**. FIG. **22** is a schematic view of the coupler **950** of FIG. **19** and depicts the third mode of operation in which the electric machine shaft **936** is mechanically coupled with the coupler **950** while the low pressure shaft **926** is mechanically decoupled from the coupler **950**. Particularly, as shown, the teeth **974** of the coupler electric machine shaft **970** are engaged with the teeth **976** of the electric machine shaft **936**. In this regard, the electric machine **930** is mechanically coupled with the coupler **950**. Moreover, the teeth **964** of the coupler shaft **960** are disengaged with the teeth **966** of the low pressure shaft **926**. Thus, the low pressure spool, which includes the low pressure turbine **924** (FIG. **19**), is mechanically decoupled from the coupler **950**. One or more actuators (not shown) can move the coupler shaft **960** along the axial direction A (to the right in FIG. **22**), causing the teeth **964** of the coupler shaft **960** to disengage from the teeth **966** of the low pressure shaft **926**. In this way, the low pressure spool is mechanically decoupled from the coupler **950**. A linear bearing **962** is disposed between the transmission shaft **952** and the coupler shaft **960**, e.g., along the radial direction. The linear bearing **962** facilitates linear movement of the coupler shaft **960**

relative to the transmission shaft **952**. The linear bearing **962** can be a ball spline, for example. It may be desirable to implement the third mode of operation as an alternative to implementing the second mode of operation.

(147) It will be appreciated that modes of operation other than those depicted in FIGS. **20** through **22** are possible. For instance, in another mode of operation, all shafts can be disengaged from the coupler **950**.

(148) In one example decoupling scheme, with reference to FIG. **19**, one or more processors of a computing system of an aircraft can be configured to cause the electric machine **930** to operate in a generator mode to generate electrical power. Accordingly, at this instance, the electric machine **930** and the turbine, e.g., the low pressure turbine **924**, are mechanically coupled with the coupler **950**. In response to an electric machine decouple command **308** (FIG. **10**), the one or more processors can cause a decrease in a generator torque output that the electric machine **930** applies on the coupler **950** over an unloading period. When the generator torque output that the electric machine **930** applies on the coupler **950** reaches a predetermined threshold, the one or more processors can cause one or both of the electric machine **930** and the low pressure turbine **924** to mechanically decouple from the coupler **950**. Decoupling either component will effectively decouple the electric machine **930** from the low pressure turbine **924**.

(149) In another example decoupling scheme, one or more processors of a computing system of an aircraft can be configured to cause the electric machine **930** to operate in a generator mode with both the electric machine **930** and the low pressure turbine **924** mechanically coupled with the coupler **950**. In response to an electric machine decouple command **308** (FIG. **10**), which is generated based on a detected failure associated with the electric machine **930** or electrical system generally, the one or more processors can cause a decrease in a generator torque output that the electric machine **930** applies on the coupler **950** over an unloading period. During the unloading period, the one or more processors can activate the brake **929** to mechanically engage the low pressure shaft **926**, e.g., to reduce the rotational speed of the low pressure shaft **926** and the electric machine **930** more rapidly. When the generator torque output that the electric machine **930** applies on the coupler **950** reaches a predetermined threshold, the one or more processors can cause one or both of the electric machine **930** and the low pressure turbine **924** to mechanically decouple from the coupler **950**. Decoupling either component will effectively decouple the electric machine **930** from the low pressure turbine **924**. Once the electric machine **930** is mechanically decoupled from the low pressure turbine **924**, the one or more processors can cause the brake **929** to deactivate or mechanically decouple from the low pressure shaft **926**. The one or more processors can also cause the brake **929** to deactivate or mechanically decouple from the low pressure shaft **926** prior to the mechanically decoupling of the electric machine **930** from the low pressure turbine **924**. For instance, the brake **929** can be caused to deactivate or mechanically decouple from the low pressure shaft **926** after a predetermined time (e.g., after two seconds), upon a condition being satisfied (e.g., the speed of the low pressure shaft **926** reaching a predetermined speed), etc.

(150) In one example coupling scheme, with reference to FIG. **19**, one or more processors of a computing system of an aircraft can be configured to cause the turbine, e.g., the low pressure turbine **924**, to provide a torque output on the coupler **950**. Further, in response to an electric machine couple command **306** (FIG. **10**), the one or more processors cause, while the electric machine **930** is mechanically decoupled from the coupler **950**, an increase in a rotational speed of the electric machine **930** (e.g., a rotational speed of the electric machine shaft **936**) to match or be within a predetermined range of a rotational speed of the low pressure turbine **924** (e.g., a rotational speed of the low pressure shaft **926**). Moreover, when the rotational speed of the electric machine **930** matches or is within the predetermined range of the rotational speed of the low pressure turbine **924**, the one or more processors are configured to cause the electric machine **930** to become mechanically coupled with the coupler **950**.

(151) In some embodiments, when the rotational speed of the electric machine **930** matches or is

within the predetermined range of the rotational speed of the low pressure turbine **924**, the one or more processors cause the electric machine **930** to provide a motor torque output on the coupler **950**, wherein the motor torque output is held constant or substantially constant for a predetermined time after the electric machine **930** is mechanically coupled with the coupler **950**. This may prevent an overspeed condition of the rotating components. In other embodiments, particularly where predictions are made as to when the rotational speed of the electric machine **930** is expected to match or fall within the predetermined range of the rotational speed of the low pressure turbine **924**, the motor torque output need not be held constant or substantially constant for a predetermined time after the electric machine **930** is mechanically coupled with the coupler **950**.

(152) Further, in some embodiments, after the motor torque output provided by the electric machine **930** on the coupler **950** is held constant or substantially constant for the predetermined time or directly after the electric machine **930** is mechanically coupled with the coupler **950**, the one or more processors are further configured to cause the motor torque output provided by the electric machine **930** on the coupler **950** to decrease, e.g., linearly. In some embodiments, the motor torque output provided by the electric machine **930** on the coupler **950** is decreased so that the electric machine **930** ceases providing a motor torque output on the coupler **950**. In other embodiments, the motor torque output provided by the electric machine **930** on the coupler **950** is decreased so that the electric machine **930** switches from a motoring mode to a generating mode to generate electrical power, or rather, so that the electric machine **930** provides a generator torque output on the coupler **950**.

(153) In some embodiments, in causing the electric machine **930** to be mechanically coupled with the coupler **950**, the one or more processors are configured to modulate one or more actuators to move a coupler electric machine shaft of the coupler **950** so that teeth of the coupler electric machine shaft engage teeth of the electric machine shaft **936**.

(154) In some example embodiments, in addition or alternatively to the electric machine **930** and coupler **950**, an electric machine can be selectively mechanically coupled with the high pressure spool of the gas turbine engine **910** of FIG. **19** via a coupler. The coupler can be a two-way coupler, for example. In yet other embodiments, an electric machine can be selectively mechanically coupled with an intermediate pressure spool of a gas turbine engine via a coupler, wherein the gas turbine engine includes a high pressure spool, a low pressure spool, and the intermediate pressure spool.

(155) FIG. **23** provides a schematic view of a propulsion assembly **980** for an aircraft in accordance with an exemplary aspect of the present disclosure. The propulsion assembly **980** includes a propulsor assembly **982** having a propulsor **984** and a propulsor shaft **986** mechanically coupled with the propulsor **984**. The propulsor **984** can be a fan or propeller, for example. The propulsion assembly **980** also includes an electric machine assembly **988** having an electric machine **990** and an electric machine shaft **992** mechanically coupled with the electric machine **990**. The propulsion assembly **980** further includes a coupler **995**. The electric machine shaft **992** is selectively mechanically engageable with the coupler **995**. Also, the propulsor shaft **986** is selectively mechanically engageable with the coupler **995**. The coupler **995** can be a two-way coupler, for example. In this regard, the propulsion assembly **980** of FIG. **23** can be a fully-electric drive propulsion assembly that relies on the electric machine **990** as the torque source for driving the propulsor **984**. The propulsion assembly **980** can include a resolver **996** associated with the propulsor shaft **986** and a resolver **998** associated with the electric machine shaft **992**. Further, in some embodiments, optionally, a gearbox can be positioned between the propulsor **984** and the coupler **995**.

(156) In some embodiments, when the propulsor shaft **986** is mechanically engaged with the coupler **995** and the electric machine shaft **992** is mechanically engaged with the coupler **995**, mechanical power is transmittable between the propulsor **984** and the electric machine **990**. The coupler **995** facilitates the power transmission. However, when at least one of the propulsor shaft

986 and the electric machine shaft **992** is not mechanically engaged with the coupler **995**, mechanical power is not transmittable between the propulsor **984** and the electric machine **990**. (157) In one example control scheme, one or more processors associated with the propulsion assembly **980** can be configured to cause the electric machine **990** to operate in a motor mode to drive the propulsor **984**. In this way, mechanical power is transmitted from the electric machine **990** to the propulsor **984** via the coupler **995**. In response to an electric machine decouple command **308** (FIG. **10**), the one or more processors can be configured to decrease a motor torque output that the electric machine **990** applies on the coupler **995** over an unloading period. Further, when the motor torque output that the electric machine **990** applies on the coupler **995** reaches a predetermined threshold, the one or more processors can cause the electric machine **990** to be mechanically decoupled from the coupler **995**. In some embodiments, the electric machine decouple command **308** (FIG. **1**) can be based at least in part detection of a failure associated with the electric machine **990** and/or a failure with one or more components (e.g., one or more switching devices of an electrical drive or power converter associated with the electric machine **990**) of its associated electrical system. In the event the electric machine **990** is mechanically decoupled from the propulsor **984**, it will be appreciated that thrust from one or more different propulsion assemblies may provide thrust for the aircraft.

(158) Generally, the coupler **995** of the propulsion assembly **980** of FIG. **23** can be selectively mechanically coupled/decoupled with the propulsor shaft **986** and/or with the electric machine shaft **992** in the same manner as the coupler **950** can be selectively mechanically coupled/decoupled with the low pressure shaft **926** and the electric machine **936** as shown in FIGS. **21**, **22**, and **23** and described in the accompanying text.

(159) FIG. **24** is a flow diagram for a method **1100** of operating a propulsion assembly, and more particularly, operating a propulsion assembly to perform a decoupling operation.

(160) At **1102**, the method **1100** includes providing, by a first torque source via a first shaft mechanically coupled with the first torque source and a coupler, a torque output on the coupler.

(161) At **1104**, the method **1100** includes providing, by a second torque source via a second shaft mechanically coupled with the second torque source and the coupler, a torque output on the coupler.

(162) At **1106**, the method **1100** includes performing, in response to a decouple command, an unloading operation, wherein performing the unloading operation comprises, over an unloading period, decreasing, by the first torque source via the first shaft, the torque output on the coupler.

(163) In some implementations, the first torque source is an electric machine and the second torque source is a gas turbine engine. In such implementations, the torque output provided by the first torque source by the first shaft can be a generator torque output. Thus, at **1106**, the generator torque output provided by the first torque source, or electric machine in this implementation, on the coupler via the first shaft is decreased. The generator torque output can be decreased linearly over the unloading period, for example. Further, in such implementations, at **1106A**, the method **1100** further includes maintaining the torque output provided by the second torque source, or gas turbine engine in this implementation, on the coupler constant. In this regard, the torque output provided by the second torque source on the coupler can remain constant during the unloading period.

(164) In some implementations, the first torque source is an electric machine and the second torque source is a gas turbine engine. In such implementations, the torque output provided by the first torque source by the first shaft can be a generator torque output. Thus, at **1106**, the generator torque output provided by the first torque source, or electric machine in this implementation, on the coupler via the first shaft is decreased. The generator torque output can be decreased linearly over the unloading period, for example. Moreover, in such implementations, at **1106B**, the method **1100** further includes decreasing the torque output provided by the second torque source, or gas turbine engine in this implementation, on the coupler. In this manner, the torque output provided by the second torque source on the coupler via the second shaft can decrease during the unloading period.

(165) In such implementations, in some instances, the torque output provided by the second torque source on the coupler via the second shaft is decreased linearly over the unloading period. In other implementations, the generator torque output provided by the first torque source on the coupler via the first shaft is decreased linearly over the unloading period at **1106** and the torque output provided by the second torque source on the coupler via the second shaft at **1106B** is decreased linearly over the unloading period. In further implementations, the generator torque output provided by the first torque source on the coupler via the first shaft is decreased over the unloading period at a first rate and the torque output provided by the second torque source on the coupler is decreased over the unloading period at a second rate, the first rate being different than the second rate.

(166) In alternative implementations, at **1106**, the first torque source is an electric machine and the second torque source is a gas turbine engine. In such implementations, the torque output provided by the first torque source by the first shaft can be a motor torque output. In this regard, both the electric machine and the gas turbine engine can transmit mechanical power to the coupler, e.g., for a power assist operation. Thus, at **1106**, the motor torque output provided by the first torque source, or electric machine in this implementation, on the coupler via the first shaft is decreased. In such implementations, the motor torque output can be decreased linearly over the unloading period. In such implementations, at **1106A**, the method **1100** can further include maintaining the torque output provided by the second torque source, or gas turbine engine in this implementation, on the coupler constant. Or alternatively, at **1106B**, the method **1100** can further include decreasing the torque output provided by the second torque source, or gas turbine engine in this implementation, on the coupler.

(167) In some implementations, the first torque source is a gas turbine engine and the second torque source is an electric machine. In such implementations, at **1106C**, the method **1100** further includes increasing, by the second torque source via the second shaft during the unloading period, the torque output on the coupler to increase mechanical power transmission between the second torque source and the coupler, the torque output provided by the second torque source on the coupler via the second shaft during the unloading period being a motor torque output.

(168) In such implementations, in some instances, in performing the unloading operation, the motor torque output provided by the second torque source on the coupler via the second shaft is increased linearly over the unloading period. In some instances, in performing the unloading operation, the torque output provided by the first torque source on the coupler via the first shaft is decreased linearly over the unloading period. In other instances, in performing the unloading operation, the motor torque output provided by the second torque source on the coupler via the second shaft is increased linearly over the unloading period and the torque output provided by the first torque source on the coupler via the first shaft is decreased linearly over the unloading period.

(169) In further instances, in performing the unloading operation, the motor torque output provided by the second torque source on the coupler via the second shaft is increased over the unloading period and the torque output provided by the first torque source on the coupler via the first shaft is decreased over the unloading period so that a net torque provided by the first torque source and the second torque source on the coupler is maintained within a predetermined margin of a commanded torque. In some instances, in performing the unloading operation, the motor torque output provided by the second torque source on the coupler via the second shaft is increased over the unloading period and the torque output provided by the first torque source on the coupler via the first shaft is decreased over the unloading period so that a net torque provided by the second torque source and the first torque source on the coupler is maintained at a constant torque over the unloading period. In yet other instances, in performing the unloading operation, the motor torque output provided by the second torque source on the coupler via the second shaft is increased over the unloading period at a rate and the torque output provided by the first torque source on the coupler via the first shaft is decreased over the unloading period at or substantially at the rate.

(170) At **1108**, the method **1100** includes, when the torque output provided by first torque source on the coupler reaches a predetermined threshold, decoupling the first shaft from the coupler. In some implementations, decoupling the first shaft from the coupler includes modulating one or more actuators to move a first coupler shaft of the coupler so that torque transmitting features (e.g., teeth) of the first coupler shaft disengage from torque transmitting features (e.g., teeth) of the first shaft.

(171) In some implementations, the first torque source is a gas turbine engine, the second torque source is an electric machine, and the propulsion assembly includes a propulsor mechanically coupled with the coupler via a propulsor shaft. In such implementations, when the torque output provided by the first torque source on the coupler reaches the predetermined threshold and the first shaft is decoupled from the coupler, the method **1100** further includes providing, by the second torque source via the second shaft, the motor torque output on the coupler to drive the propulsor to a commanded operating point.

(172) In some implementations, the first torque source is an electric machine and the second torque source is a gas turbine engine. In such implementations, prior to the unloading period, the torque output provided on the coupler by the first torque source via the first shaft at **1102** is a generator torque output. Further, decreasing the torque output provided by the first torque source on the coupler via the first shaft at **1106** includes decreasing the generator torque output that the first torque source applies on the coupler via the first shaft over the unloading period. In such implementations, decoupling the first shaft from the coupler comprises decoupling the first shaft from the coupler when the generator torque output that the first torque source applies on the coupler via the first shaft reaches the predetermined threshold.

(173) In some implementations, the first torque source is an electric machine and the second torque source is a propulsor. In other implementations, the first torque source is a propulsor and the second torque source is an electric machine.

(174) In some further implementations, the first torque source is a gas turbine, the second torque source is an electric machine, and a propulsor is mechanically coupled with the coupler via a propulsor shaft. In other implementations, the first torque source is an electric machine, the second torque source is a gas turbine engine, and a propulsor is mechanically coupled with the coupler via a propulsor shaft. In such implementations, the propulsor shaft can be a single shaft that is mechanically coupled to a propulsor coupler shaft of the coupler at one end and is mechanically coupled with the propulsor at an opposing end. In other instances, a gear box is positioned along the propulsor shaft between the coupler and the propulsor, the propulsor shaft having a first propulsor shaft mechanically coupling the propulsor with the gearbox and a second propulsor shaft mechanically coupling the gearbox with the coupler.

(175) In one example embodiment, a propulsion assembly is provided. The propulsion assembly includes a first torque source mechanically coupled with a first shaft and a second torque source mechanically coupled with a second shaft. The propulsion assembly also includes a coupler. Further, the propulsion assembly includes a computing system having one or more memory devices and one or more processors. The one or more processors are configured to: cause, with the first shaft mechanically coupled to the coupler, the first torque source via the first shaft to provide a torque output on the coupler; cause, with the second shaft mechanically coupled to the coupler, the second torque source via the second shaft to provide a torque output on the coupler; in response to a decouple command, cause an unloading operation to be performed, wherein in causing the unloading operation to be performed, the one or more processors are configured to cause, by the first torque source via the first shaft, the torque output on the coupler to decrease over an unloading period; and when the torque output provided by the first torque source on the coupler reaches a predetermined threshold, cause the first shaft to become mechanically decoupled from the coupler.

(176) In another example embodiment, a non-transitory computer readable medium is provided. The non-transitory computer readable medium includes computer-executable instructions, which, when executed by one or more processors of a computing system associated with a propulsion

assembly of an aircraft, cause the one or more processors to: cause, by a first torque source via a first shaft mechanically coupled with the first torque source and a coupler, the first torque source via the first shaft to provide a torque output on the coupler; cause, by a second torque source via a second shaft mechanically coupled with the second torque source and the coupler, the second torque source via the second shaft to provide a torque output on the coupler; in response to a decouple command, cause an unloading operation to be performed, wherein in causing the unloading operation to be performed, the one or more processors are configured to cause, by the first torque source via the first shaft, the torque output on the coupler to decrease over an unloading period; and when the torque output provided by the first torque source on the coupler reaches a predetermined threshold, cause the first shaft to become mechanically decoupled from the coupler. (177) In yet another embodiment, a propulsion assembly is provided. The propulsion assembly includes a first torque source mechanically coupled with a first shaft and a second torque source mechanically coupled with a second shaft. The propulsion assembly also includes a coupler. Further, the propulsion assembly includes a computing system having one or more memory devices and one or more processors configured to: in response to a decouple command, cause an unloading operation to be performed, wherein in causing the unloading operation, the one or more processors are configured to: i) cause, by the second torque source via the second shaft over an unloading period, an increase in a torque output on the coupler to increase mechanical power transmission from the second torque source to the coupler; and ii) cause, by the first torque source via the first shaft over the unloading period, a decrease in a torque output on the coupler to decrease mechanical power transmission from the first torque source to the coupler; and when the torque output provided by the first torque source on the coupler reaches a predetermined threshold, cause the first shaft to become mechanically decoupled from the coupler.

(178) In a further embodiment, a non-transitory computer readable medium is provided. The non-transitory computer readable medium includes computer-executable instructions, which, when executed by one or more processors of a computing system associated with a propulsion assembly of an aircraft, cause the one or more processors to: in response to a decouple command, cause an unloading operation to be performed, wherein in causing the unloading operation to be performed, the one or more processors are configured to: i) cause, by a second torque source of the propulsion assembly via a second shaft mechanically coupled with the second torque source and a coupler over an unloading period, an increase in a torque output on a coupler to increase mechanical power transmission from the second torque source to the coupler; and ii) cause, by a first torque source of the propulsion assembly via a first shaft mechanically coupled with the first torque source and the coupler over the unloading period, a decrease in a torque output provided on the coupler to decrease mechanical power transmission from the first torque source to the coupler; and when the torque output provided by the first torque source on the coupler reaches a predetermined threshold, cause the first shaft to become mechanically decoupled from the coupler.

(179) FIG. 25 is a flow diagram for a method **1200** of operating a propulsion assembly, and more particularly, operating a propulsion assembly to perform a coupling operation.

(180) At **1202**, the method **1200** includes providing, by a first torque source via a first shaft mechanically coupled with the first torque source and a coupler, a torque output on the coupler.

(181) At **1204**, the method **1200** includes performing, in response to a couple command, a speed matching operation, wherein performing the speed matching operation comprises increasing a rotational speed of a second shaft mechanically coupled with a second torque source but mechanically decoupled from the coupler until the rotational speed of the second shaft matches or is within a predetermined range of a rotational speed of the first shaft. In some implementations, in performing the speed matching operation, the method **1200** includes monitoring whether the rotational speed of the first shaft matches or is within the predetermined range of the rotational speed of the second shaft based at least in part on one or more inputs received from a resolver associated with the second shaft and one or more inputs received from a resolver associated with

the first shaft.

(182) At **1206**, the method **1200** includes, when the rotational speed of the second shaft matches or is within the predetermined range of the rotational speed of the first shaft, mechanically coupling the first shaft to the coupler. In some implementations, mechanically coupling the first shaft to the coupler can include modulating one or more actuators to move a first coupler shaft of the coupler so that torque transmitting features (e.g., teeth) of the first coupler shaft engage torque transmitting features (e.g., teeth) of the first shaft.

(183) In some implementations of method **1200**, the first torque source is a gas turbine engine and the second torque source is an electric machine. In such implementations, after the first shaft is mechanically coupled to the coupler, a torque output provided by the first shaft on the coupler is held constant or substantially constant for a predetermined time.

(184) In some further implementations of method **1200** where the first torque source is a gas turbine engine and the second torque source is an electric machine, after the first shaft is mechanically coupled to the coupler, the method **1200** further comprises i) decreasing the torque output, the torque output being a motor torque output, provided by the second torque source via the second shaft on the coupler to decrease mechanical power transmission from the second torque source to the coupler; and ii) increasing the torque output provided by the first torque source via the first shaft on the coupler to increase mechanical power transmission from the first torque source to the coupler. In such implementations, in some instances, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased linearly. In such implementations, in other instances, the torque output provided by the first torque source via the first shaft on the coupler is increased linearly. In such implementations, in yet other instances, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased linearly and the torque output provided by the first torque source via the first shaft on the coupler is increased linearly after the first shaft is mechanically coupled to the coupler.

(185) Further, in some implementations of method **1200** where the first torque source is a gas turbine engine and the second torque source is an electric machine, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased and the torque output provided by the first torque source via the first shaft on the coupler is increased so that a net torque provided by the second torque source via the second shaft and the first torque source via the first shaft on the coupler is maintained within a predetermined margin of a commanded torque. In other implementations, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased and the torque output provided by the first torque source via the first shaft on the coupler is increased so that a net torque provided by the second torque source via the second shaft and the first torque source via the first shaft on the coupler is maintained at or substantially at a constant torque over a loading period. In some further implementations, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased at a rate and the torque output provided by the first torque source via the first shaft on the coupler is increased at or substantially at the rate.

(186) In some further implementations of method **1200** where the first torque source is a gas turbine engine and the second torque source is an electric machine, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased so that the second torque source, or electric machine in such implementations, switches from a motoring mode to a generating mode to generate electrical power. In other implementations, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased so that the electric machine provides a generator torque output on the coupler. In other implementations, the motor torque output provided by the second torque source via the second shaft on the coupler is decreased so that the second shaft ceases providing the motor torque output on the coupler, and when the second shaft ceases providing the motor torque output on the coupler, the method **1200** further includes mechanically decoupling the second shaft from the coupler. Mechanically

decoupling the second shaft from the coupler can include modulating one or more actuators to move a second coupler shaft of the coupler so that torque transmitting features (e.g., teeth) of the second coupler shaft disengage from torque transmitting features (e.g., teeth) of the second shaft. (187) In some implementations of method **1200**, the first torque source is an electric machine and the second torque source is a gas turbine engine. In such implementations, when the rotational speed of the first shaft matches or is within the predetermined range of the rotational speed of the second shaft, a motor torque output provided by the first torque source via the first shaft on the coupler is held constant or substantially constant for a predetermined time after the first shaft is mechanically coupled with the coupler. In such implementations, in some instances, after the motor torque output provided by the first torque source via the first shaft on the coupler is held constant or substantially constant for the predetermined time, the method **1200** further includes decreasing the motor torque output provided by the first torque source via the first shaft on the coupler to decrease mechanical power transmission from the first torque source to the coupler. In such implementations, in some instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased so that the first shaft ceases providing a motor torque output on the coupler. In such implementations, in some instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased linearly.

(188) In some implementations where the first torque source is an electric machine and the second torque source is a gas turbine engine, after the first shaft is mechanically coupled with the coupler, the method **1200** further includes decreasing a motor torque output provided by the first torque source via the first shaft on the coupler to decrease mechanical power transmission from the first torque source to the coupler. In such implementations, in some instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased so that the first shaft ceases providing a motor torque output on the coupler. In such implementations, in other instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased linearly. In such implementations, in yet other instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased so that the first torque source, or electric machine in such implementations, switches from a motoring mode to a generating mode to generate electrical power. In such implementations, in some instances, the motor torque output provided by the first torque source via the first shaft on the coupler is decreased so that the electric machine provides a generator torque output on the coupler.

(189) In some implementations where the first torque source is an electric machine and the second torque source is a gas turbine engine, after the first shaft is mechanically coupled with the coupler, the method **1200** further includes mechanically decoupling the second shaft from the coupler.

(190) In some implementations, the first torque source is an electric machine and the second torque source is a propulsor. In other implementations, the first torque source is a propulsor and the second torque source is an electric machine.

(191) In some further implementations, the first torque source is a gas turbine, the second torque source is an electric machine, and a propulsor is mechanically coupled with the coupler via a propulsor shaft. In other implementations, the first torque source is an electric machine, the second torque source is a gas turbine engine, and a propulsor is mechanically coupled with the coupler via a propulsor shaft. In such implementations, the propulsor shaft can be a single shaft that is mechanically coupled to a propulsor coupler shaft of the coupler at one end and is mechanically coupled with the propulsor at an opposing end. In other instances, a gear box is positioned along the propulsor shaft between the coupler and the propulsor, the propulsor shaft having a first propulsor shaft mechanically coupling the propulsor with the gearbox and a second propulsor shaft mechanically coupling the gearbox with the coupler.

(192) In one example embodiment, a propulsion assembly is provided, such as any one of the propulsion assemblies provided herein. The propulsion assembly includes a first torque source mechanically coupled with a first shaft and a second torque source mechanically coupled with a

second shaft. The propulsion assembly also includes a coupler. Further, the propulsion assembly has a computing system having one or more memory devices and one or more processors. The one or more processors are configured to: cause the first torque source via the first shaft to provide a torque output on the coupler; in response to a couple command, cause a speed matching operation to be performed, wherein in causing the speed matching operation, the one or more processors are configured to increase, with the second shaft mechanically decoupled from the coupler, a rotational speed of the second shaft until the rotational speed of the second shaft matches or is within a predetermined range of a rotational speed of the first shaft; and when the rotational speed of the second shaft matches or is within the predetermined range of the rotational speed of the first shaft, cause the first shaft to become mechanically coupled to the coupler.

(193) In another example embodiment, a non-transitory computer readable medium is provided. The non-transitory computer readable medium includes computer-executable instructions, which, when executed by one or more processors of a computing system associated with a propulsion assembly of an aircraft, cause the one or more processors to: cause a first torque source of the propulsion assembly via a first shaft mechanically coupled with the first torque source and a coupler to provide a torque output on the coupler; in response to a couple command, cause a speed matching operation to be performed, wherein in causing the speed matching operation, the one or more processors are configured to increase, with a second shaft mechanically coupled with a second torque source but mechanically decoupled from the coupler, a rotational speed of the second shaft until the rotational speed of the second shaft matches or is within a predetermined range of a rotational speed of the first shaft; and when the rotational speed of the second shaft matches or is within the predetermined range of the rotational speed of the first shaft, cause the first shaft to become mechanically coupled to the coupler.

(194) FIG. 26 provides a computing system **1000** according to example embodiments of the present disclosure. The computing system **96** of the aircraft **10** can be configured in a same or similar manner as the computing system **1000**, for example. As shown, the computing system **1000** can include one or more computing device(s) **1110**. The computing devices/controllers **94, 98, 52, 54** can be configured in the same or similar manner as the computing device(s) **1110**. As shown, the computing device(s) **1110** can include one or more processor(s) **1112** and one or more memory device(s) **1114**. The one or more processor(s) **1112** can include any suitable processing device, such as a microprocessor, microcontroller, integrated circuit, logic device, and/or other suitable processing device. The one or more memory device(s) **1114** can include one or more computer-executable or computer-readable media, including, but not limited to, non-transitory computer-readable media, RAM, ROM, hard drives, flash drives, and/or other memory devices.

(195) The one or more memory device(s) **1114** can store information accessible by the one or more processor(s) **1112**, including computer-readable or computer-executable instructions **1116** that can be executed by the one or more processor(s) **1112**. The instructions **1116** can be any set of instructions that, when executed by the one or more processor(s) **1112**, cause the one or more processor(s) **1112** to perform operations. In some embodiments, the instructions **1116** can be executed by the one or more processor(s) **1112** to cause the one or more processor(s) **1112** to perform operations, such as any of the operations and functions for which the computing system **1000** and/or the computing device(s) **1110** are configured. The instructions **1116** can be software written in any suitable programming language or can be implemented in hardware. Additionally, and/or alternatively, the instructions **1116** can be executed in logically and/or virtually separate threads on processor(s) **1112**. The memory device(s) **1114** can further store data **1118** that can be accessed by the processor(s) **1112**. For example, the data **1118** can include models, lookup tables, databases, etc.

(196) The computing device(s) **1110** can also include a network **1120** used to communicate, for example, with the other components of system **1000** (e.g., via a communication network). The network **1120** can include any suitable components for interfacing with one or more network(s),

including for example, transmitters, receivers, ports, controllers, antennas, and/or other suitable components. One or more devices can be configured to receive one or more commands from the computing device(s) **1110** or provide one or more commands to the computing device(s) **1110**.

(197) The technology discussed herein makes reference to computer-based systems and actions taken by and information sent to and from computer-based systems. It will be appreciated that the inherent flexibility of computer-based systems allows for a great variety of possible configurations, combinations, and divisions of tasks and functionality between and among components. For instance, processes discussed herein can be implemented using a single computing device or multiple computing devices working in combination. Databases, memory, instructions, and applications can be implemented on a single system or distributed across multiple systems. Distributed components can operate sequentially or in parallel.

(198) The inventive aspects of the present disclosure may provide certain advantages, benefits, and/or technical effects. For instance, the assemblies and methods disclosed herein may enable a hybrid-electric propulsion system or fully-electric propulsion system to switch between modes of operation in a safe and reliable manner, and without need for more permanent solutions, such as shaft cutting. As disclosed herein, smooth transitions between operating modes may be accomplished by unloading/loading components and synchronizing their speeds or torques prior to decoupling or coupling a component from the coupler.

(199) This written description uses examples to disclose the present disclosure, including the best mode, and also to enable any person skilled in the art to practice the disclosure, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the disclosure is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal languages of the claims.

Claims

1. A propulsion assembly, comprising: a propulsor assembly having a propulsor and a propulsor shaft mechanically coupled with the propulsor; an electric machine assembly having an electric machine and an electric machine shaft mechanically coupled with the electric machine; a gas turbine engine including a spool having a turbine and a shaft mechanically coupled with the turbine; and a coupler, the electric machine shaft being selectively mechanically engageable with the coupler, the propulsor shaft being selectively mechanically engageable with the coupler, and the shaft being selectively mechanically engageable with the coupler, wherein the coupler includes a transmission shaft that extends along an axis of rotation between a first end at least partially mechanically coupled to the propulsor shaft and a second end at least partially mechanically coupled to the shaft and the electric machine shaft, and wherein the propulsor shaft, the shaft, and the electric machine shaft extend at least partially along the axis of rotation.
2. The propulsion assembly of claim 1, wherein when the propulsor shaft, the electric machine shaft, and the shaft are mechanically engaged with the coupler, mechanical power is transmittable between the propulsor, the electric machine, and the turbine.
3. The propulsion assembly of claim 1, wherein when the propulsor shaft and the electric machine shaft are mechanically engaged with the coupler but the shaft is not, mechanical power is transmittable between the propulsor and the electric machine.
4. The propulsion assembly of claim 1, wherein when the propulsor shaft and the shaft are mechanically engaged with the coupler but the electric machine shaft is not, mechanical power is transmittable between the propulsor and the turbine.
5. The propulsion assembly of claim 1, wherein when the electric machine shaft and the shaft are

mechanically engaged with the coupler but the propulsor shaft is not, mechanical power is transmittable between the electric machine and the turbine.

6. The propulsion assembly of claim 1, wherein the coupler includes a coupler propulsor shaft, and wherein when the propulsor shaft is mechanically engaged with the coupler, torque transmitting features of the propulsor shaft engage torque transmitting features of the coupler propulsor shaft.

7. The propulsion assembly of claim 1, wherein the coupler includes a coupler electric machine shaft, and wherein when the electric machine shaft is mechanically engaged with the coupler, torque transmitting features of the electric machine shaft engage torque transmitting features of the coupler electric machine shaft.

8. The propulsion assembly of claim 1, wherein the coupler includes a coupler turbine shaft, and wherein when the shaft is mechanically engaged with the coupler, torque transmitting features of the shaft engage torque transmitting features of the coupler turbine shaft.

9. The propulsion assembly of claim 1, wherein the transmission shaft mechanically couples a coupler turbine shaft and a coupler electric machine shaft with a coupler propulsor shaft, wherein the coupler turbine shaft is selectively mechanically engageable with the shaft, wherein the coupler electric machine shaft is selectively mechanically engageable with the electric machine shaft, and wherein the coupler propulsor shaft is selectively mechanically engageable with the propulsor shaft.

10. The propulsion assembly of claim 1, wherein the gas turbine engine includes a gas generation spool having a gas generation shaft and a compressor and a gas generation turbine both mechanically coupled with the gas generation shaft, wherein the gas generation shaft is spaced from the shaft along an axial direction defined by the gas turbine engine.

11. The propulsion assembly of claim 1, further comprising: one or more processors configured to: cause the turbine to provide a torque output on the coupler mechanically coupled with the propulsor to drive the propulsor; cause, in response to a turbine decouple command, an unloading operation to be performed, wherein performing the unloading operation comprises, over an unloading period, increasing a motor torque output provided by the electric machine on the coupler to increase mechanical power transmission from the electric machine to the propulsor and decreasing the torque output provided by the turbine on the coupler to decrease mechanical power transmission from the turbine to the propulsor; and when the torque output provided by the turbine on the coupler reaches a predetermined threshold, cause the turbine to decouple from the coupler.

12. The propulsion assembly of claim 1, further comprising: one or more processors configured to: cause the electric machine to provide a motor torque output on the coupler so that mechanical power is transmitted from the electric machine to the propulsor through the coupler; in response to a turbine couple command, cause a speed matching operation to be performed, wherein performing the speed matching operation comprises increasing a rotational speed of a turbine until the rotational speed of the shaft matches or is within a predetermined range of a rotational speed of an electric machine shaft that mechanically couples the electric machine to the coupler; and when the rotational speed of the shaft matches or is within the predetermined range of the rotational speed of the electric machine shaft, cause the turbine to become mechanically coupled with the coupler so that the turbine drives the propulsor.

13. The propulsion assembly of claim 1, further comprising: one or more processors configured to: cause the electric machine to operate in a generator mode to generate electrical power, the electric machine and the turbine being mechanically coupled with the coupler; in response to an electric machine decouple command, cause a decrease in a generator torque output that the electric machine applies on the coupler over an unloading period; and when the generator torque output that the electric machine applies on the coupler reaches a predetermined threshold, cause the electric machine to decouple from the coupler.

14. The propulsion assembly of claim 1, further comprising: one or more processors configured to: cause the turbine to provide a torque output on the coupler so that the turbine drives the propulsor;

in response to an electric machine couple command, cause, while the electric machine is mechanically decoupled from the coupler, an increase in a rotational speed of the electric machine to match or be within a predetermined range of a rotational speed of the turbine; and when the rotational speed of the electric machine matches or is within the predetermined range of the rotational speed of the turbine, cause the electric machine to become mechanically coupled with the coupler.

15. The propulsion assembly of claim 1, wherein the propulsion assembly is mounted to an aircraft.

16. The propulsion assembly of claim 1, wherein the coupler is a three-way coupler.

17. A propulsion assembly, comprising: a propulsor assembly having a propulsor and a propulsor shaft mechanically coupled with the propulsor; an electric machine assembly having an electric machine and an electric machine shaft mechanically coupled with the electric machine; a coupler, the electric machine shaft being selectively mechanically engageable with the coupler and the propulsor shaft being selectively mechanically engageable with the coupler, wherein the coupler includes a transmission shaft that couples the electric machine shaft with the propulsor shaft; and one or more processors configured to: cause an electric machine to operate to drive the propulsor, mechanical power being transmitted from the electric machine to the propulsor via the coupler; in response to an electric machine decouple command, decreasing a motor torque output that the electric machine applies on the coupler over an unloading period; and when the motor torque output that the electric machine applies on the coupler reaches a predetermined threshold, cause the electric machine to be mechanically decoupled from the coupler.

18. The propulsion assembly of claim 17, wherein when the propulsor shaft is mechanically engaged with the coupler and the electric machine shaft is mechanically engaged with the coupler, mechanical power is transmittable between the propulsor and the electric machine, and wherein when at least one of the propulsor shaft and the electric machine shaft is not mechanically engaged with the coupler, mechanical power is not transmittable between the propulsor and the electric machine.

19. A propulsion assembly, comprising: a propulsor assembly having a propulsor and a propulsor shaft mechanically coupled with the propulsor; an electric machine assembly having an electric machine and an electric machine shaft mechanically coupled with the electric machine; a coupler, the electric machine shaft being selectively mechanically engageable with the coupler and the propulsor shaft being selectively mechanically engageable with the coupler; and one or more processors configured to: cause an electric machine to operate in a motor mode to drive the propulsor, mechanical power being transmitted from the electric machine to the propulsor via the coupler; in response to an electric machine decouple command, decreasing a motor torque output that the electric machine applies on the coupler over an unloading period; and when the motor torque output that the electric machine applies on the coupler reaches a predetermined threshold, cause the electric machine to be mechanically decoupled from the coupler.
