

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12417596
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Chand; Jesse et al.

User interfaces for managing live communication sessions

Abstract

The present disclosure generally relates to managing live communication sessions. A computer system optionally displays an option to invite the respective user to join the ongoing communication session. A computer system optionally one or more options to modify an appearance of an avatar representing the user of the computer system. A computer system optionally transitions a communication session from a spatial communication session to a non-spatial communication session. A computer system optionally displays information about a participant in a communication session.

Inventors: Chand; Jesse (San Francisco, CA), Bauerly; Kristi E. (Los Altos, CA), Lemay; Stephen O. (Palo Alto, CA), Dascola; Jonathan R. (San Francisco, CA), Chiu; Shih-Sang (San Francisco, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 1000008818085

Assignee: Apple Inc. (Cupertino, CA)

Appl. No.: 18/367418

Filed: September 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240104859 A1	Mar. 28, 2024

Related U.S. Application Data

us-provisional-application US 63470882 20230603
us-provisional-application US 63409583 20220923

Publication Classification

Int. Cl.: **G06T19/00** (20110101); **G06T19/20** (20110101); **H04N7/15** (20060101)

U.S. Cl.:

CPC **G06T19/006** (20130101); **G06T19/20** (20130101); **H04N7/152** (20130101); **H04N7/157** (20130101); **G06T2219/2004** (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5146231	12/1991	Ghaem et al.	N/A	N/A
5303286	12/1993	Wiedeman	N/A	N/A
5446465	12/1994	Diefes et al.	N/A	N/A
5583514	12/1995	Fulop	N/A	N/A
5587717	12/1995	Jang	N/A	N/A
5812932	12/1997	Wiedeman et al.	N/A	N/A
5863057	12/1998	Wessels	N/A	N/A
5937349	12/1998	Andresen	N/A	N/A
5995041	12/1998	Bradley et al.	N/A	N/A
6006068	12/1998	Elkin et al.	N/A	N/A
6052587	12/1999	Moraes et al.	N/A	N/A
6108538	12/1999	Blasiak et al.	N/A	N/A
6147644	12/1999	Castles et al.	N/A	N/A
6157896	12/1999	Castles et al.	N/A	N/A
6169881	12/2000	Astrom et al.	N/A	N/A
6208858	12/2000	Antonio et al.	N/A	N/A
6240366	12/2000	Nagatsuma et al.	N/A	N/A
6263280	12/2000	Stingone, Jr.	N/A	N/A
6272316	12/2000	Wiedeman et al.	N/A	N/A
6278861	12/2000	Ward et al.	N/A	N/A
6317689	12/2000	Lee	N/A	N/A
6397054	12/2001	Hoirup et al.	N/A	N/A
6549848	12/2002	Green et al.	N/A	N/A
6580452	12/2002	Gangitano	N/A	N/A
6690934	12/2003	Conrad et al.	N/A	N/A
6763226	12/2003	Mczeal, Jr.	N/A	N/A
6992991	12/2005	Duske et al.	N/A	N/A
7057625	12/2005	Kamata et al.	N/A	N/A
7184744	12/2006	Schnabel	N/A	N/A
7233795	12/2006	Ryden	N/A	N/A
7311608	12/2006	Danieli et al.	N/A	N/A
7865205	12/2010	Lundy et al.	N/A	N/A

8095665	12/2011	Bau	N/A	N/A
8249585	12/2011	Tronc et al.	N/A	N/A
8254970	12/2011	Oshinsky et al.	N/A	N/A
8521122	12/2012	Scott et al.	N/A	N/A
8584031	12/2012	Moore et al.	N/A	N/A
8594374	12/2012	Bozarth	N/A	N/A
8676121	12/2013	Monte et al.	N/A	N/A
8732609	12/2013	Bayersdorfer et al.	N/A	N/A
8855012	12/2013	Suri	N/A	N/A
8971946	12/2014	Ahmed et al.	N/A	N/A
8983846	12/2014	Di Profio et al.	N/A	N/A
8996639	12/2014	Faaborg et al.	N/A	N/A
9037164	12/2014	Keerthi	N/A	N/A
9235923	12/2015	Robinson et al.	N/A	N/A
9298257	12/2015	Hwang et al.	N/A	N/A
9325852	12/2015	Forstall et al.	N/A	N/A
9349414	12/2015	Furment et al.	N/A	N/A
9369832	12/2015	Noble et al.	N/A	N/A
9408077	12/2015	David et al.	N/A	N/A
9411506	12/2015	Marra et al.	N/A	N/A
9430186	12/2015	Faaborg et al.	N/A	N/A
9489074	12/2015	Oonishi	N/A	N/A
9503177	12/2015	Shi et al.	N/A	N/A
9521378	12/2015	Palaganas et al.	N/A	N/A
9575720	12/2016	Faaborg et al.	N/A	N/A
9947363	12/2017	Moon et al.	N/A	N/A
9965039	12/2017	Kwon	N/A	N/A
10116893	12/2017	Reis et al.	N/A	N/A
10199051	12/2018	Binder et al.	N/A	N/A
10289265	12/2018	Kulkarni	N/A	N/A
10325417	12/2018	Scapel et al.	N/A	N/A
10375313	12/2018	Van OS et al.	N/A	N/A
10376153	12/2018	Tzvieli et al.	N/A	N/A
10419712	12/2018	Arrasvuori et al.	N/A	N/A
10459504	12/2018	Veloso et al.	N/A	N/A
10496244	12/2018	Reynolds et al.	N/A	N/A
10505726	12/2018	Andon et al.	N/A	N/A
10511707	12/2018	Johnson et al.	N/A	N/A
10560562	12/2019	Tandon	N/A	N/A
10623451	12/2019	Rathod	N/A	N/A
10645561	12/2019	Guo et al.	N/A	N/A
10659405	12/2019	Chang et al.	N/A	N/A
10791536	12/2019	Murphy	N/A	N/A
10796480	12/2019	Chen et al.	N/A	N/A
10797785	12/2019	Rhee	N/A	N/A
10802582	12/2019	Clements	N/A	N/A
10853410	12/2019	Herz	N/A	N/A
10959074	12/2020	Shuman et al.	N/A	N/A
10984569	12/2020	Bondich et al.	N/A	N/A
11003315	12/2020	Sung et al.	N/A	N/A

11106280	12/2020	Bigham et al.	N/A	N/A
11144176	12/2020	Chang et al.	N/A	N/A
11217036	12/2021	Albuz et al.	N/A	N/A
11349559	12/2021	Reuss et al.	N/A	N/A
11361521	12/2021	Lee et al.	N/A	N/A
11455078	12/2021	Goodrich et al.	N/A	N/A
11467713	12/2021	Buzyn et al.	N/A	N/A
11907421	12/2023	Clements	N/A	N/A
2001/0019330	12/2000	Bickmore et al.	N/A	N/A
2002/0000931	12/2001	Petronic et al.	N/A	N/A
2002/0006117	12/2001	Duske et al.	N/A	N/A
2002/0180797	12/2001	Bachmann	N/A	N/A
2003/0054814	12/2002	Karabinis et al.	N/A	N/A
2003/0074647	12/2002	Andrew et al.	N/A	N/A
2003/0083816	12/2002	Imakado et al.	N/A	N/A
2003/0206170	12/2002	Bickmore et al.	N/A	N/A
2004/0166811	12/2003	Moon	N/A	N/A
2004/0179039	12/2003	Blattner et al.	N/A	N/A
2004/0192368	12/2003	Edwards et al.	N/A	N/A
2004/0257275	12/2003	Yee et al.	N/A	N/A
2005/0125744	12/2004	Hubbard et al.	N/A	N/A
2005/0143135	12/2004	Brems et al.	N/A	N/A
2005/0168566	12/2004	Tada et al.	N/A	N/A
2006/0017612	12/2005	Nagatani	N/A	N/A
2006/0030334	12/2005	Hashimoto	N/A	N/A
2006/0035632	12/2005	Sorvari et al.	N/A	N/A
2006/0055700	12/2005	Niles et al.	N/A	N/A
2006/0095563	12/2005	Benjamin et al.	N/A	N/A
2006/0247915	12/2005	Bradford et al.	N/A	N/A
2006/0258365	12/2005	Cha et al.	N/A	N/A
2007/0024579	12/2006	Rosenberg	N/A	N/A
2007/0047697	12/2006	Drewry et al.	N/A	N/A
2007/0097113	12/2006	Lee et al.	N/A	N/A
2007/0109186	12/2006	Fujiwara et al.	N/A	N/A
2007/0123252	12/2006	Tronc et al.	N/A	N/A
2007/0130606	12/2006	Jeong	N/A	N/A
2007/0162872	12/2006	Hong et al.	N/A	N/A
2007/0188380	12/2006	Duong et al.	N/A	N/A
2007/0216572	12/2006	Schnabel	N/A	N/A
2008/0030496	12/2007	Lee	345/418	G06F 3/04842
2008/0046839	12/2007	Mehra et al.	N/A	N/A
2008/0082934	12/2007	Kocienda et al.	N/A	N/A
2008/0153538	12/2007	Oshaughnessy et al.	N/A	N/A
2008/0155428	12/2007	Lee	N/A	N/A
2008/0158232	12/2007	Shuster	N/A	N/A
2008/0165022	12/2007	Herz et al.	N/A	N/A
2008/0166011	12/2007	Sever et al.	N/A	N/A
2008/0168361	12/2007	Forstall et al.	N/A	N/A
2008/0168379	12/2007	Forstall et al.	N/A	N/A

2008/0186135	12/2007	Boling et al.	N/A	N/A
2008/0218641	12/2007	Kjeldsen et al.	N/A	N/A
2008/0250315	12/2007	Eronen et al.	N/A	N/A
2008/0303715	12/2007	Wang et al.	N/A	N/A
2008/0309677	12/2007	Fleury et al.	N/A	N/A
2008/0313686	12/2007	Matvey	N/A	N/A
2008/0316227	12/2007	Fleury et al.	N/A	N/A
2009/0044113	12/2008	Jones et al.	N/A	N/A
2009/0049905	12/2008	Lawwhite et al.	N/A	N/A
2009/0083382	12/2008	Rosenberg et al.	N/A	N/A
2009/0100342	12/2008	Jakobson et al.	N/A	N/A
2009/0135062	12/2008	Hori	N/A	N/A
2009/0144639	12/2008	Nims et al.	N/A	N/A
2009/0191854	12/2008	Beason	N/A	N/A
2009/0191893	12/2008	Smith	N/A	N/A
2009/0205041	12/2008	Michalske	N/A	N/A
2009/0231356	12/2008	Barnes et al.	N/A	N/A
2009/0249247	12/2008	Tseng et al.	N/A	N/A
2009/0254624	12/2008	Baudin et al.	N/A	N/A
2009/0262033	12/2008	King et al.	N/A	N/A
2009/0267828	12/2008	Kobayashi et al.	N/A	N/A
2009/0300525	12/2008	Jolliff et al.	N/A	N/A
2009/0325701	12/2008	Andres Del Valle	N/A	N/A
2010/0026640	12/2009	Kim et al.	N/A	N/A
2010/0030660	12/2009	Edwards	N/A	N/A
2010/0062749	12/2009	Yasuda et al.	N/A	N/A
2010/0083159	12/2009	Mountain et al.	N/A	N/A
2010/0085255	12/2009	Wakabayashi	N/A	N/A
2010/0097375	12/2009	Tadaishi et al.	N/A	N/A
2010/0113020	12/2009	Subramanian et al.	N/A	N/A
2010/0123724	12/2009	Moore et al.	N/A	N/A
2010/0125811	12/2009	Moore et al.	N/A	N/A
2010/0156807	12/2009	Stallings et al.	N/A	N/A
2010/0167672	12/2009	Ahn et al.	N/A	N/A
2010/0251176	12/2009	Fong et al.	N/A	N/A
2010/0271312	12/2009	Alameh et al.	N/A	N/A
2010/0302138	12/2009	Poot et al.	N/A	N/A
2010/0311385	12/2009	Hurwitz	N/A	N/A
2011/0004524	12/2010	Paul et al.	N/A	N/A
2011/0013075	12/2010	Kim et al.	N/A	N/A
2011/0016425	12/2010	Homburg et al.	N/A	N/A
2011/0032274	12/2010	Miyata	N/A	N/A
2011/0057903	12/2010	Yamano et al.	N/A	N/A
2011/0061017	12/2010	Ullrich et al.	N/A	N/A
2011/0092158	12/2010	Plamondon	N/A	N/A
2011/0130113	12/2010	Takuno	N/A	N/A
2011/0136428	12/2010	Ritter	N/A	N/A
2011/0157046	12/2010	Lee et al.	N/A	N/A
2011/0175832	12/2010	Miyazawa et al.	N/A	N/A
2011/0205182	12/2010	Miyazawa et al.	N/A	N/A

2011/0230161	12/2010	Newman	N/A	N/A
2011/0248992	12/2010	Van et al.	N/A	N/A
2011/0252344	12/2010	Van	N/A	N/A
2011/0265002	12/2010	Hong et al.	N/A	N/A
2011/0285656	12/2010	Yaksick et al.	N/A	N/A
2011/0302518	12/2010	Zhang	N/A	N/A
2011/0306292	12/2010	Wilson et al.	N/A	N/A
2012/0011449	12/2011	Sasson et al.	N/A	N/A
2012/0059787	12/2011	Brown et al.	N/A	N/A
2012/0068899	12/2011	Ayotte et al.	N/A	N/A
2012/0075328	12/2011	Goossens	N/A	N/A
2012/0081356	12/2011	Filippov	345/419	G06F 3/0412
2012/0084692	12/2011	Bae	N/A	N/A
2012/0102399	12/2011	Nicholson	N/A	N/A
2012/0105444	12/2011	Tokuda	N/A	N/A
2012/0105486	12/2011	Lankford et al.	N/A	N/A
2012/0113008	12/2011	Makinen et al.	N/A	N/A
2012/0124516	12/2011	Friedman	N/A	N/A
2012/0135715	12/2011	Kang et al.	N/A	N/A
2012/0140767	12/2011	Brothers et al.	N/A	N/A
2012/0158515	12/2011	K	N/A	N/A
2012/0189273	12/2011	Folgnier et al.	N/A	N/A
2012/0237002	12/2011	Sennett et al.	N/A	N/A
2012/0239822	12/2011	Poulson et al.	N/A	N/A
2012/0254318	12/2011	Poniatowski	N/A	N/A
2012/0254989	12/2011	Levien et al.	N/A	N/A
2012/0256967	12/2011	Baldwin et al.	N/A	N/A
2012/0293686	12/2011	Karn et al.	N/A	N/A
2012/0295708	12/2011	Hernandez-Abrego et al.	N/A	N/A
2012/0314047	12/2011	Kasahara et al.	N/A	N/A
2012/0316876	12/2011	Jang et al.	N/A	N/A
2013/0010093	12/2012	Redmann et al.	N/A	N/A
2013/0014019	12/2012	Kim et al.	N/A	N/A
2013/0015946	12/2012	Lau et al.	N/A	N/A
2013/0024781	12/2012	Douillet et al.	N/A	N/A
2013/0024802	12/2012	Zeng et al.	N/A	N/A
2013/0036380	12/2012	Symons	N/A	N/A
2013/0038759	12/2012	Jo et al.	N/A	N/A
2013/0063366	12/2012	Paul	N/A	N/A
2013/0067391	12/2012	Pittappilly et al.	N/A	N/A
2013/0109425	12/2012	Kerger et al.	N/A	N/A
2013/0113956	12/2012	Anderson et al.	N/A	N/A
2013/0114043	12/2012	Balan et al.	N/A	N/A
2013/0117383	12/2012	Hymel et al.	N/A	N/A
2013/0127665	12/2012	Miller et al.	N/A	N/A
2013/0135146	12/2012	Ransom et al.	N/A	N/A
2013/0141365	12/2012	Lynn et al.	N/A	N/A
2013/0157729	12/2012	Tabé	N/A	N/A

2013/0183924	12/2012	Saigh et al.	N/A	N/A
2013/0197951	12/2012	Watson et al.	N/A	N/A
2013/0198210	12/2012	Lee et al.	N/A	N/A
2013/0205350	12/2012	Ling et al.	N/A	N/A
2013/0225118	12/2012	Jang et al.	N/A	N/A
2013/0227596	12/2012	Pettis et al.	N/A	N/A
2013/0231077	12/2012	Cahill	N/A	N/A
2013/0263043	12/2012	Sarbin et al.	N/A	N/A
2013/0271319	12/2012	Trerise	N/A	N/A
2013/0271320	12/2012	Trerise	N/A	N/A
2013/0275875	12/2012	Gruber et al.	N/A	N/A
2013/0286161	12/2012	Lv et al.	N/A	N/A
2013/0293686	12/2012	Blow et al.	N/A	N/A
2013/0295872	12/2012	Guday et al.	N/A	N/A
2013/0295982	12/2012	Lee et al.	N/A	N/A
2013/0301521	12/2012	Abdi	N/A	N/A
2013/0307771	12/2012	Parker et al.	N/A	N/A
2013/0315108	12/2012	Lindner et al.	N/A	N/A
2013/0342730	12/2012	Lee et al.	N/A	N/A
2014/0015784	12/2013	Oonishi	N/A	N/A
2014/0022192	12/2013	Hatanaka	N/A	N/A
2014/0039894	12/2013	Shostak	N/A	N/A
2014/0064463	12/2013	Reddy	N/A	N/A
2014/0078144	12/2013	Berriman et al.	N/A	N/A
2014/0123005	12/2013	Forstall et al.	N/A	N/A
2014/0134969	12/2013	Jin et al.	N/A	N/A
2014/0143682	12/2013	Druck et al.	N/A	N/A
2014/0143693	12/2013	Goossens et al.	N/A	N/A
2014/0149878	12/2013	Mischari et al.	N/A	N/A
2014/0157167	12/2013	Zhu	N/A	N/A
2014/0164955	12/2013	Thiruvadam et al.	N/A	N/A
2014/0181219	12/2013	Wang et al.	N/A	N/A
2014/0195918	12/2013	Friedlander	N/A	N/A
2014/0195972	12/2013	Lee et al.	N/A	N/A
2014/0213214	12/2013	Reis	N/A	N/A
2014/0213236	12/2013	Jimbo et al.	N/A	N/A
2014/0218371	12/2013	Du et al.	N/A	N/A
2014/0222436	12/2013	Binder et al.	N/A	N/A
2014/0237393	12/2013	Van Wie et al.	N/A	N/A
2014/0267543	12/2013	Kerger et al.	N/A	N/A
2014/0267618	12/2013	Esteban et al.	N/A	N/A
2014/0306898	12/2013	Cueto	N/A	N/A
2014/0350924	12/2013	Zurek et al.	N/A	N/A
2014/0351720	12/2013	Mn	N/A	N/A
2014/0354539	12/2013	Skogo et al.	N/A	N/A
2015/0011220	12/2014	Buckle et al.	N/A	N/A
2015/0018040	12/2014	He et al.	N/A	N/A
2015/0036883	12/2014	Deri et al.	N/A	N/A
2015/0040012	12/2014	Faaborg et al.	N/A	N/A
2015/0052462	12/2014	Kulkarni	N/A	N/A

2015/0063428	12/2014	Lever	N/A	N/A
2015/0077502	12/2014	Jordan et al.	N/A	N/A
2015/0089398	12/2014	Song et al.	N/A	N/A
2015/0091896	12/2014	Tarquini et al.	N/A	N/A
2015/0097687	12/2014	Sloo et al.	N/A	N/A
2015/0100537	12/2014	Grieves et al.	N/A	N/A
2015/0109191	12/2014	Johnson et al.	N/A	N/A
2015/0113435	12/2014	Phillips	N/A	N/A
2015/0135309	12/2014	Karmarkar et al.	N/A	N/A
2015/0137972	12/2014	Nepo	N/A	N/A
2015/0141072	12/2014	Mumick	N/A	N/A
2015/0149899	12/2014	Bernstein et al.	N/A	N/A
2015/0153952	12/2014	Grossman et al.	N/A	N/A
2015/0154001	12/2014	Knox et al.	N/A	N/A
2015/0169053	12/2014	Bozarth et al.	N/A	N/A
2015/0189091	12/2014	Forstall et al.	N/A	N/A
2015/0195179	12/2014	Skare et al.	N/A	N/A
2015/0213604	12/2014	Li et al.	N/A	N/A
2015/0248235	12/2014	Offenberg et al.	N/A	N/A
2015/0257126	12/2014	Herz	N/A	N/A
2015/0261496	12/2014	Faaborg et al.	N/A	N/A
2015/0271317	12/2014	Nelson et al.	N/A	N/A
2015/0281145	12/2014	Ji	N/A	N/A
2015/0312175	12/2014	Langholz	N/A	N/A
2015/0338524	12/2014	Ben Moshe et al.	N/A	N/A
2015/0341759	12/2014	Kerger et al.	N/A	N/A
2015/0358790	12/2014	Nasserbakht	N/A	N/A
2015/0366293	12/2014	Clarkson	N/A	N/A
2015/0370323	12/2014	Cieplinski et al.	N/A	N/A
2015/0370529	12/2014	Zambetti et al.	N/A	N/A
2016/0005211	12/2015	Sarkis et al.	N/A	N/A
2016/0014059	12/2015	Rathod	N/A	N/A
2016/0034133	12/2015	Wilson et al.	N/A	N/A
2016/0056525	12/2015	Hansryd et al.	N/A	N/A
2016/0062540	12/2015	Yang et al.	N/A	N/A
2016/0065669	12/2015	Van Dijkman et al.	N/A	N/A
2016/0066277	12/2015	Yang et al.	N/A	N/A
2016/0088455	12/2015	Bozik et al.	N/A	N/A
2016/0117147	12/2015	Zambetti et al.	N/A	N/A
2016/0150215	12/2015	Chen et al.	N/A	N/A
2016/0183098	12/2015	Lim	N/A	N/A
2016/0191694	12/2015	Kim et al.	N/A	N/A
2016/0192163	12/2015	Miner et al.	N/A	N/A
2016/0217601	12/2015	Tsuda et al.	N/A	N/A
2016/0234664	12/2015	Vendrow et al.	N/A	N/A
2016/0253745	12/2015	Lee	N/A	N/A
2016/0277903	12/2015	Poosala et al.	N/A	N/A
2016/0284123	12/2015	Hare et al.	N/A	N/A
2016/0302083	12/2015	Durick et al.	N/A	N/A
2016/0306051	12/2015	Hirabayashi et al.	N/A	N/A

2016/0306533	12/2015	Agarwal et al.	N/A	N/A
2016/0320838	12/2015	Teller et al.	N/A	N/A
2016/0357720	12/2015	Thimbleby	N/A	N/A
2016/0374047	12/2015	Reis	N/A	N/A
2017/0004828	12/2016	Lee et al.	N/A	N/A
2017/0006620	12/2016	Reis	N/A	N/A
2017/0021260	12/2016	Willett et al.	N/A	N/A
2017/0026110	12/2016	Richardson et al.	N/A	N/A
2017/0026509	12/2016	Rand	N/A	N/A
2017/0045623	12/2016	Zlogar et al.	N/A	N/A
2017/0068439	12/2016	Mohseni	N/A	N/A
2017/0069124	12/2016	Tong et al.	N/A	N/A
2017/0085600	12/2016	Carter et al.	N/A	N/A
2017/0123571	12/2016	Huang et al.	N/A	N/A
2017/0124751	12/2016	Ross et al.	N/A	N/A
2017/0150060	12/2016	Herz	N/A	N/A
2017/0171636	12/2016	Devlin et al.	N/A	N/A
2017/0180964	12/2016	Mehta et al.	N/A	N/A
2017/0195307	12/2016	Jones-McFadden et al.	N/A	N/A
2017/0223162	12/2016	Wilder et al.	N/A	N/A
2017/0235361	12/2016	Rigazio et al.	N/A	N/A
2017/0236298	12/2016	Vetter	N/A	N/A
2017/0323266	12/2016	Seo	N/A	N/A
2017/0332035	12/2016	Shah et al.	N/A	N/A
2017/0332045	12/2016	Metter et al.	N/A	N/A
2017/0336867	12/2016	Wilairat et al.	N/A	N/A
2017/0352091	12/2016	Chen et al.	N/A	N/A
2018/0018514	12/2017	Azam et al.	N/A	N/A
2018/0024726	12/2017	Hviding	N/A	N/A
2018/0024846	12/2017	Wu et al.	N/A	N/A
2018/0035922	12/2017	Kim et al.	N/A	N/A
2018/0040951	12/2017	Uchiyama	N/A	N/A
2018/0047200	12/2017	O'Hara et al.	N/A	N/A
2018/0063249	12/2017	Nguyen	N/A	N/A
2018/0074693	12/2017	Jones et al.	N/A	N/A
2018/0081515	12/2017	Block et al.	N/A	N/A
2018/0088242	12/2017	Eagling	N/A	N/A
2018/0091732	12/2017	Wilson et al.	N/A	N/A
2018/0092057	12/2017	Yamashita et al.	N/A	N/A
2018/0095635	12/2017	Valdivia et al.	N/A	N/A
2018/0096690	12/2017	Mixter et al.	N/A	N/A
2018/0176362	12/2017	Cohen	N/A	N/A
2018/0192264	12/2017	Kwok et al.	N/A	N/A
2018/0233139	12/2017	Finkelstein et al.	N/A	N/A
2018/0262834	12/2017	Cho et al.	N/A	N/A
2018/0268747	12/2017	Braun	N/A	N/A
2018/0270000	12/2017	Reis et al.	N/A	N/A
2018/0316416	12/2017	Reis et al.	N/A	N/A
2018/0316885	12/2017	Reis et al.	N/A	N/A

2018/0329587	12/2017	Ko et al.	N/A	N/A
2018/0335930	12/2017	Scapel et al.	N/A	N/A
2018/0336715	12/2017	Rickwald et al.	N/A	N/A
2018/0338026	12/2017	Jon et al.	N/A	N/A
2018/0338035	12/2017	Johnson et al.	N/A	N/A
2018/0338237	12/2017	Maheswaranathan	N/A	N/A
2018/0349795	12/2017	Boyle et al.	N/A	N/A
2018/0365898	12/2017	Costa	N/A	N/A
2019/0020992	12/2018	Romano	N/A	N/A
2019/0049592	12/2018	Koontz et al.	N/A	N/A
2019/0080066	12/2018	Van Os et al.	N/A	N/A
2019/0080070	12/2018	Van Os et al.	N/A	N/A
2019/0138092	12/2018	Song	N/A	N/A
2019/0155382	12/2018	Ikuta et al.	N/A	N/A
2019/0158735	12/2018	Wilson et al.	N/A	N/A
2019/0190591	12/2018	Wang et al.	N/A	N/A
2019/0235247	12/2018	Norden	N/A	N/A
2019/0266775	12/2018	Lee et al.	N/A	N/A
2019/0266807	12/2018	Lee et al.	N/A	N/A
2019/0280788	12/2018	Hardy et al.	N/A	N/A
2019/0295056	12/2018	Wright	N/A	N/A
2019/0318283	12/2018	Kelly et al.	N/A	N/A
2019/0333508	12/2018	Rao et al.	N/A	N/A
2019/0339847	12/2018	Scapel et al.	N/A	N/A
2019/0342507	12/2018	Dye et al.	N/A	N/A
2019/0354265	12/2018	Winnemoeller	N/A	N/A
2019/0369836	12/2018	Faulkner et al.	N/A	N/A
2019/0371033	12/2018	Scapel et al.	N/A	N/A
2019/0371323	12/2018	Kao et al.	N/A	N/A
2019/0387092	12/2018	Tessier	N/A	N/A
2020/0025944	12/2019	Mellier et al.	N/A	N/A
2020/0034025	12/2019	Brady et al.	N/A	N/A
2020/0042083	12/2019	Min	N/A	N/A
2020/0053641	12/2019	Lee et al.	N/A	N/A
2020/0075015	12/2019	Taki et al.	N/A	N/A
2020/0103963	12/2019	Kelly et al.	N/A	N/A
2020/0117900	12/2019	Deng et al.	N/A	N/A
2020/0119984	12/2019	Bouvet et al.	N/A	N/A
2020/0132644	12/2019	Micalizzi et al.	N/A	N/A
2020/0187295	12/2019	Li et al.	N/A	N/A
2020/0196209	12/2019	Cui et al.	N/A	N/A
2020/0201540	12/2019	Zambetti et al.	N/A	N/A
2020/0213436	12/2019	Mumick	N/A	N/A
2020/0225746	12/2019	Bar-Zeev et al.	N/A	N/A
2020/0234481	12/2019	Scapel et al.	N/A	N/A
2020/0234508	12/2019	Shaburov et al.	N/A	N/A
2020/0244673	12/2019	Stockdale et al.	N/A	N/A
2020/0252780	12/2019	Mcclendon et al.	N/A	N/A
2020/0264738	12/2019	Lee et al.	N/A	N/A
2020/0265234	12/2019	Lee et al.	N/A	N/A

2020/0304444	12/2019	Aneja et al.	N/A	N/A
2020/0358725	12/2019	Scapel et al.	N/A	N/A
2020/0367069	12/2019	Struhsaker et al.	N/A	N/A
2020/0379560	12/2019	Krasadakis	N/A	N/A
2020/0401686	12/2019	Duchastel	N/A	N/A
2020/0402304	12/2019	Hwang et al.	N/A	N/A
2020/0409533	12/2019	Blackstock et al.	N/A	N/A
2021/0006287	12/2020	Peeters et al.	N/A	N/A
2021/0011173	12/2020	Rhee	N/A	N/A
2021/0027790	12/2020	Choi et al.	N/A	N/A
2021/0048883	12/2020	Kelly et al.	N/A	N/A
2021/0051444	12/2020	Ryu et al.	N/A	N/A
2021/0058149	12/2020	Nuttall et al.	N/A	N/A
2021/0120394	12/2020	Martin et al.	N/A	N/A
2021/0144539	12/2020	Edge et al.	N/A	N/A
2021/0168581	12/2020	Van Den Dungen	N/A	N/A
2021/0175963	12/2020	Chang et al.	N/A	N/A
2021/0243072	12/2020	Peterson et al.	N/A	N/A
2021/0255269	12/2020	Lv et al.	N/A	N/A
2021/0286502	12/2020	Lemay et al.	N/A	N/A
2021/0311203	12/2020	Reis et al.	N/A	N/A
2021/0311609	12/2020	Dandoko	N/A	N/A
2021/0349612	12/2020	Triverio	N/A	N/A
2021/0405831	12/2020	Mourkogiannis et al.	N/A	N/A
2022/0066048	12/2021	Diggelen et al.	N/A	N/A
2022/0091737	12/2021	Bower et al.	N/A	N/A
2022/0100270	12/2021	Pastrana Vicente et al.	N/A	N/A
2022/0100812	12/2021	Anvaripour et al.	N/A	N/A
2022/0116105	12/2021	Robinson et al.	N/A	N/A
2022/0131822	12/2021	Jon et al.	N/A	N/A
2022/0206675	12/2021	Hawkes	N/A	N/A
2022/0207840	12/2021	Cansizoglu et al.	N/A	N/A
2022/0214743	12/2021	Dascola et al.	N/A	N/A
2022/0229546	12/2021	Lee et al.	N/A	N/A
2022/0230379	12/2021	Shriram et al.	N/A	N/A
2022/0237660	12/2021	Balondona	N/A	N/A
2022/0253136	12/2021	Holder et al.	N/A	N/A
2022/0256631	12/2021	Jain et al.	N/A	N/A
2022/0291793	12/2021	Zambetti et al.	N/A	N/A
2022/0301041	12/2021	Lee et al.	N/A	N/A
2022/0319075	12/2021	Hu et al.	N/A	N/A
2022/0359064	12/2021	Pierson et al.	N/A	N/A
2022/0374137	12/2021	Triverio et al.	N/A	N/A
2022/0413605	12/2021	Liu et al.	N/A	N/A
2023/0063173	12/2022	Caro et al.	N/A	N/A
2023/0065219	12/2022	Caro et al.	N/A	N/A
2023/0066232	12/2022	Caro et al.	N/A	N/A
2023/0071037	12/2022	Kim et al.	N/A	N/A
2023/0081032	12/2022	Ardaud et al.	N/A	N/A
2023/0185373	12/2022	Kelly et al.	N/A	N/A

2023/0214107	12/2022	Zambetti et al.	N/A	N/A
2023/0254152	12/2022	Ratnakaram et al.	N/A	N/A
2023/0273985	12/2022	Suchan et al.	N/A	N/A
2023/0305688	12/2022	Triverio et al.	N/A	N/A
2023/0308538	12/2022	Caro et al.	N/A	N/A
2023/0328171	12/2022	Caro et al.	N/A	N/A
2023/0379573	12/2022	Wilson et al.	N/A	N/A
2023/0384860	12/2022	Dedonato et al.	N/A	N/A
2024/0028110	12/2023	Aurongzeb et al.	N/A	N/A
2024/0028177	12/2023	Pastrana Vicente et al.	N/A	N/A
2024/0036717	12/2023	Triverio	N/A	N/A
2024/0085707	12/2023	Schowengerdt	N/A	N/A
2024/0103616	12/2023	Yerkes et al.	N/A	N/A
2024/0103617	12/2023	Yerkes et al.	N/A	N/A
2024/0103678	12/2023	Dryer et al.	N/A	N/A
2024/0118746	12/2023	Yerkes et al.	N/A	N/A
2024/0257486	12/2023	El Asmar et al.	N/A	N/A
2024/0259676	12/2023	Wilson et al.	N/A	N/A
2024/0427417	12/2023	Kelly et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2792987	12/2010	CA	N/A
101042618	12/2006	CN	N/A
101098535	12/2007	CN	N/A
101203821	12/2007	CN	N/A
102012738	12/2010	CN	N/A
102163098	12/2010	CN	N/A
102271241	12/2010	CN	N/A
102446059	12/2011	CN	N/A
102622085	12/2011	CN	N/A
102790826	12/2011	CN	N/A
102854979	12/2012	CN	N/A
102905244	12/2012	CN	N/A
103092469	12/2012	CN	N/A
101938287	12/2012	CN	N/A
103516894	12/2013	CN	N/A
103703438	12/2013	CN	N/A
103713843	12/2013	CN	N/A
103744671	12/2013	CN	N/A
103927190	12/2013	CN	N/A
104182741	12/2013	CN	N/A
104246793	12/2013	CN	N/A
104641318	12/2014	CN	N/A
105190700	12/2014	CN	N/A
105283840	12/2015	CN	N/A
105453025	12/2015	CN	N/A
105611275	12/2015	CN	N/A
105786394	12/2015	CN	N/A

105874405	12/2015	CN	N/A
106104677	12/2015	CN	N/A
108574773	12/2017	CN	N/A
108718447	12/2017	CN	N/A
110046020	12/2018	CN	N/A
112634416	12/2020	CN	N/A
0963061	12/1998	EP	N/A
1215867	12/2001	EP	N/A
1736931	12/2005	EP	N/A
1777611	12/2006	EP	N/A
2040146	12/2008	EP	N/A
2302493	12/2010	EP	N/A
2437148	12/2011	EP	N/A
2615607	12/2012	EP	N/A
2653961	12/2012	EP	N/A
2677775	12/2012	EP	N/A
2720126	12/2013	EP	N/A
2782297	12/2013	EP	N/A
2981000	12/2015	EP	N/A
3047884	12/2015	EP	N/A
3190563	12/2016	EP	N/A
3248180	12/2016	EP	N/A
2801972	12/2017	EP	N/A
3373132	12/2017	EP	N/A
3676972	12/2021	EP	N/A
2370208	12/2001	GB	N/A
9-9072	12/1996	JP	N/A
9-81309	12/1996	JP	N/A
9-172401	12/1996	JP	N/A
10-191423	12/1997	JP	N/A
10-293860	12/1997	JP	N/A
11-312159	12/1998	JP	N/A
2000-40990	12/1999	JP	N/A
2000-76460	12/1999	JP	N/A
2001-320449	12/2000	JP	N/A
2003-75525	12/2002	JP	N/A
2003-219217	12/2002	JP	N/A
2004-96265	12/2003	JP	N/A
2004-519033	12/2003	JP	N/A
2005-532607	12/2004	JP	N/A
2006-102327	12/2005	JP	N/A
2006520053	12/2005	JP	N/A
2008-97202	12/2007	JP	N/A
2008-257363	12/2007	JP	N/A
2010-211742	12/2009	JP	N/A
2011-209787	12/2010	JP	N/A
2011-209887	12/2010	JP	N/A
2011-530101	12/2010	JP	N/A
2012-18569	12/2011	JP	N/A
2012-123475	12/2011	JP	N/A

2013-97760	12/2012	JP	N/A
2013-239979	12/2012	JP	N/A
2014-230061	12/2013	JP	N/A
2016-15624	12/2015	JP	N/A
2016-508007	12/2015	JP	N/A
2016-76799	12/2015	JP	N/A
2016-136324	12/2015	JP	N/A
2017-527917	12/2016	JP	N/A
6238381	12/2016	JP	N/A
2018-513515	12/2017	JP	N/A
2018-532298	12/2017	JP	N/A
2019-505117	12/2018	JP	N/A
2019-155115	12/2018	JP	N/A
2020-504376	12/2019	JP	N/A
2020-149336	12/2019	JP	N/A
2020-187775	12/2019	JP	N/A
6853820	12/2020	JP	N/A
2021-533512	12/2020	JP	N/A
2022-03545	12/2021	JP	N/A
2022-8997	12/2021	JP	N/A
2022-23406	12/2021	JP	N/A
10-2004-0009115	12/2003	KR	N/A
10-2004-0046272	12/2003	KR	N/A
10-2008-0050336	12/2007	KR	N/A
10-2010-0086052	12/2009	KR	N/A
10-2011-0028581	12/2010	KR	N/A
10-2014-0033088	12/2013	KR	N/A
10-2014-0049340	12/2013	KR	N/A
10-2014-0073232	12/2013	KR	N/A
10-2015-0067197	12/2014	KR	N/A
10-2015-0068013	12/2014	KR	N/A
10-1540544	12/2014	KR	N/A
10-2015-0094197	12/2014	KR	N/A
10-1587115	12/2015	KR	N/A
10-2016-0018109	12/2015	KR	N/A
10-2016-0097913	12/2015	KR	N/A
10-2017-0065563	12/2016	KR	N/A
10-2020-0101206	12/2019	KR	N/A
10-2020-0132995	12/2019	KR	N/A
99/66394	12/1998	WO	N/A
99/66395	12/1998	WO	N/A
03/058589	12/2002	WO	N/A
2004/010672	12/2003	WO	N/A
2004/079530	12/2003	WO	N/A
2005/057890	12/2004	WO	N/A
2006/094308	12/2005	WO	N/A
2007/139580	12/2006	WO	N/A
2009/073607	12/2008	WO	N/A
2009/125481	12/2008	WO	N/A
2009/133710	12/2008	WO	N/A

2011/127309	12/2010	WO	N/A
2011/130849	12/2011	WO	N/A
2012/128361	12/2011	WO	N/A
2012/170354	12/2011	WO	N/A
2013/120851	12/2012	WO	N/A
2013/169851	12/2012	WO	N/A
2013/169854	12/2012	WO	N/A
2013/169870	12/2012	WO	N/A
2013/169877	12/2012	WO	N/A
2014/024000	12/2013	WO	N/A
2014/053063	12/2013	WO	N/A
2014/105279	12/2013	WO	N/A
2014/124332	12/2013	WO	N/A
2014/197339	12/2013	WO	N/A
2014/200729	12/2013	WO	N/A
2015/017043	12/2014	WO	N/A
2015/088141	12/2014	WO	N/A
2016/036218	12/2015	WO	N/A
2016/036522	12/2015	WO	N/A
2016/042926	12/2015	WO	N/A
2016/060848	12/2015	WO	N/A
2016/116814	12/2015	WO	N/A
2016/189390	12/2015	WO	N/A
2017/068422	12/2016	WO	N/A
2018/109751	12/2017	WO	N/A
2018/125563	12/2017	WO	N/A
2018/226265	12/2017	WO	N/A
2019/118020	12/2018	WO	N/A
2019/216999	12/2018	WO	N/A
2020/028236	12/2019	WO	N/A
2020/226785	12/2019	WO	N/A
2021/071532	12/2020	WO	N/A
2022/086580	12/2021	WO	N/A
2022/147146	12/2021	WO	N/A

OTHER PUBLICATIONS

Corrected Notice of Allowance received for U.S. Appl. No. 18/230,465, mailed on Nov. 5, 2024, 2 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023270278, mailed on Oct. 30, 2024, 3 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010295272.4, mailed on Oct. 10, 2024, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/899,510, mailed on Dec. 10, 2024, 3 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/023273, mailed on Dec. 5, 2024, 13 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/898,342, mailed on Dec. 12, 2024, 12 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023219926, mailed on Dec. 3, 2024, 4 pages. cited by applicant

Office Action received for European Patent Application No. 22197430.6, mailed on Dec. 3, 2024, 8 pages. cited by applicant

Office Action received for European Patent Application No. 22198902.3, mailed on Dec. 12, 2024, 8 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,510, mailed on Jan. 4, 2024, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,510, mailed on Nov. 22, 2023, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/105,191, mailed on Jan. 17, 2024, 2 pages. cited by applicant

Board Decision received for Chinese Patent Application No. 202010295272.4, mailed on Dec. 14, 2023, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 17/899,530, mailed on Nov. 8, 2023, 3 pages. cited by applicant

Decision on Appeal received for U.S. Appl. No. 16/259,771, mailed on Feb. 8, 2024, 18 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 17853657.9, mailed on Feb. 2, 2024, 17 pages. cited by applicant

Decision to Refuse received for European Patent Application No. 19212057.4, mailed on Feb. 5, 2024, 18 pages. cited by applicant

Examiner's Answer to Appeal Brief received for U.S. Appl. No. 18/119,789, mailed on Jan. 22, 2024, 45 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/899,510, mailed on Nov. 30, 2023, 21 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 18/105,191, mailed on Feb. 20, 2024, 20 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/029811, mailed on Nov. 30, 2023, 10 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/042069, mailed on Mar. 14, 2024, 15 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/023273, mailed on Sep. 15, 2023, 19 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033372, mailed on Jan. 12, 2024, 21 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033376, mailed on Mar. 18, 2024, 21 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/033540, mailed on Feb. 6, 2024, 25 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/033372, mailed on Nov. 22, 2023, 13 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/033376, mailed on Jan. 24, 2024, 13 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/033540, mailed on Dec. 12, 2023, 17 pages. cited by applicant

Krumm et al., "Multi-camera multi-person tracking for easyliving", Third IEEE International Workshop on Visual Surveillance, Available online at: <http://mesh.brown.edu/en193s05-2004/pdfs/KrummEtAl-iwvs00.pdf>, Jul. 1, 2000, 8 pages. cited by applicant

Minutes of the Oral Proceedings received for European Patent Application No. 19212057.4, mailed on Jan. 31, 2024, 6 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 17/899,510, mailed on Mar. 27, 2024, 22

pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,510, mailed on Oct. 26, 2023, 18 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/105,191, mailed on Oct. 13, 2023, 23 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022231779, mailed on Feb. 5, 2024, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2022235630, mailed on Sep. 28, 2023, 3 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/899,530, mailed on Oct. 19, 2023, 13 pages. cited by applicant
Office Action received for Australian Patent Application No. 2022231779, mailed on Nov. 6, 2023, 3 pages. cited by applicant
Office Action received for Chinese Patent Application No. 202010295272.4, mailed on Aug. 28, 2023, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant
Office Action received for Chinese Patent Application No. 202010295272.4, mailed on Feb. 5, 2024, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2022-170806, mailed on Nov. 17, 2023, 14 pages (7 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2023-001790, mailed on Mar. 4, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2023-7039673, mailed on Feb. 20, 2024, 11 pages (2 pages of English Translation and 9 pages of Official Copy). cited by applicant
Record of Oral Hearing received for U.S. Appl. No. 16/259,771, mailed on Feb. 4, 2024, 15 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/899,510, mailed on Oct. 21, 2024, 16 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/230,465, mailed on Oct. 17, 2024, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/230,465, mailed on Oct. 24, 2024, 2 pages. cited by applicant
Decision to Grant received for European Patent Application No. 23173355.1, mailed on Oct. 24, 2024, 3 pages. cited by applicant
Extended European Search Report received for European Patent Application No. 24203946.9, mailed on Oct. 24, 2024, 9 pages. cited by applicant
Extended European Search Report received for European Patent Application No. 24204114.3, mailed on Dec. 23, 2024, 10 pages. cited by applicant
Intention to Grant received for European Patent Application No. 22729935.1, mailed on Nov. 22, 2024, 9 pages. cited by applicant
Office Action received for European Patent Application No. 22769872.7, mailed on Nov. 15, 2024, 11 pages. cited by applicant
Office Action received for Korean Patent Application No. 10-2023-7039602, mailed on Nov. 14, 2024, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant
Advisory Action received for U.S. Appl. No. 14/833,014, mailed on Jan. 27, 2017, 3 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/259,771, mailed on Feb. 26, 2020, 3 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/259,771, mailed on Jul. 14, 2020, 6 pages. cited by applicant
Advisory Action received for U.S. Appl. No. 16/806,981, mailed on Jun. 14, 2021, 6 pages. cited

by applicant

Advisory Action received for U.S. Appl. No. 17/093,408, mailed on Jun. 5, 2023, 4 pages. cited by applicant

Applicant Initiated Interview Summary received for U.S. Appl. No. 16/259,771, mailed on May 5, 2020, 10 pages. cited by applicant

Applicant Initiated Interview Summary received for U.S. Appl. No. 16/553,622, mailed on Aug. 3, 2020, 3 pages. cited by applicant

Applicant Initiated Interview Summary received for U.S. Appl. No. 16/806,981, mailed on Jan. 28, 2022, 4 pages. cited by applicant

Applicant Initiated Interview Summary received for U.S. Appl. No. 17/079,216, mailed on May 8, 2023, 2 pages. cited by applicant

Applicant Initiated Interview Summary received for U.S. Appl. No. 17/899,510, mailed on Apr. 27, 2023, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 16/259,771, mailed on Apr. 18, 2022, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/087,855, mailed on Feb. 28, 2022, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/087,855, mailed on Jul. 5, 2022, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/087,855, mailed on Nov. 5, 2021, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/093,408, mailed on Jan. 5, 2023, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/093,408, mailed on Jul. 1, 2022, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/093,408, mailed on Mar. 1, 2022, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/093,408, mailed on May 10, 2023, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/093,408, mailed on May 25, 2023, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/746,179, mailed on Nov. 28, 2022, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,315, mailed on Jan. 24, 2023, 3 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,510, mailed on Aug. 2, 2023, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,530, mailed on Aug. 3, 2023, 5 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,530, mailed on Feb. 3, 2023, 6 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,530, mailed on Jul. 3, 2023, 6 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/119,789, mailed on Jul. 31, 2023, 4 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/119,789, mailed on Sep. 27, 2023, 3 pages. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No. 20176616.9, mailed on Jun. 9, 2022, 1 page. cited by applicant

Brief Communication Regarding Oral Proceedings received for European Patent Application No.

20176616.9, mailed on May 27, 2022, 1 page. cited by applicant
Certificate of Examination received for Australian Patent Application No. 2019100525, mailed on Aug. 6, 2019, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 15/713,490, mailed on May 1, 2019, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 16/553,622, mailed on Sep. 23, 2020, 5 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/079,216, mailed on Aug. 3, 2023, 4 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/079,216, mailed on May 19, 2023, 3 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/087,855, mailed on Jan. 12, 2023, 6 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/087,855, mailed on Jan. 25, 2023, 4 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/093,408, mailed on Sep. 13, 2023, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/093,408, mailed on Sep. 20, 2023, 3 pages. cited by applicant
Decision on Appeal received for Korean Patent Application No. 10-2021-7002582, mailed on May 13, 2022, 29 pages (2 pages of English Translation and 27 pages of Official Copy). cited by applicant
Decision on Appeal received for U.S. Appl. No. 14/833,014, mailed on Oct. 30, 2019, 10 pages. cited by applicant
Decision on Appeal received for U.S. Appl. No. 16/259,771, mailed on Aug. 19, 2021, 12 pages. cited by applicant
Decision to Grant received for Danish Patent Application No. PA201670320, mailed on Oct. 18, 2018, 2 pages. cited by applicant
Decision to Grant received for Danish Patent Application No. PA201870383, mailed on Jun. 3, 2020, 2 pages. cited by applicant
Decision to Grant received for European Patent Application No. 15759998.6, mailed on Jun. 18, 2020, 2 pages. cited by applicant
Decision to Grant received for European Patent Application No. 19769336.9, mailed on Oct. 7, 2022, 2 pages. cited by applicant
European Search Report received for European Patent Application No. 21179101.7, mailed on Sep. 28, 2021, 5 pages. cited by applicant
Examiner Interview Summary received for U.S. Appl. No. 16/806,981, mailed on Mar. 26, 2021, 2 pages. cited by applicant
Examiner-Initiated Interview Summary received for U.S. Appl. No. 16/806,981, mailed on Jan. 13, 2022, 4 pages. cited by applicant
Examiner-Initiated Interview Summary received for U.S. Appl. No. 16/806,981, mailed on May 24, 2021, 4 pages. cited by applicant
Examiner's Answer to Appeal Brief received for U.S. Appl. No. 14/833,014, mailed on Nov. 2, 2017, 48 pages. cited by applicant
Examiner's Answer to Appeal Brief received for U.S. Appl. No. 16/259,771, mailed on May 26, 2023, 23 pages. cited by applicant
Examiner's Answer to Appeal Brief received for U.S. Appl. No. 16/259,771, mailed on Oct. 23, 2020, 15 pages. cited by applicant
Examiner's Pre-Review Report received for Japanese Patent Application No. 2019-215503, mailed on Aug. 20, 2021, 15 pages (8 pages of English Translation and 7 pages of Official Copy). cited by

applicant

Extended European Search Report received for European Patent Application No. 17853657.9, mailed on May 28, 2020, 9 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 19212057.4, mailed on Feb. 27, 2020, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 20176616.9, mailed on Sep. 8, 2020, 7 Pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22179347.4, mailed on Oct. 13, 2022, 7 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22197430.6, mailed on Jan. 26, 2023, 8 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22197456.1, mailed on Feb. 2, 2023, 9 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 22198902.3, mailed on Jan. 20, 2023, 9 pages. cited by applicant

Extended European Search Report received for European Patent Application No. 23173355.1, mailed on Aug. 4, 2023, 8 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 14/833,014, mailed on Oct. 26, 2016, 32 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 15/352,215, mailed on Mar. 7, 2019, 22 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/259,771, mailed on Aug. 12, 2022, 25 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/259,771, mailed on Nov. 18, 2019, 13 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/806,981, mailed on Apr. 14, 2021, 24 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 16/806,981, mailed on Mar. 1, 2022, 33 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/087,855, mailed on Mar. 31, 2022, 23 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/093,408, mailed on Mar. 2, 2023, 51 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/093,408, mailed on May 18, 2022, 41 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/899,510, mailed on Jun. 2, 2023, 15 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 17/899,530, mailed on Mar. 8, 2023, 68 pages. cited by applicant

Final Office Action received for U.S. Appl. No. 18/119,789, mailed on Aug. 30, 2023, 29 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201670320, mailed on May 17, 2018, 2 pages. cited by applicant

Intention to Grant received for Danish Patent Application No. PA201870383, mailed on Feb. 11, 2020, 2 pages. cited by applicant

Intention to Grant received for European Patent Application No. 15759998.6, mailed on Apr. 17, 2020, 10 pages. cited by applicant

Intention to Grant received for European Patent Application No. 15759998.6, mailed on Nov. 21, 2019, 12 pages. cited by applicant

Intention to Grant received for European Patent Application No. 19769336.9, mailed on May 31,

2022, 13 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2015/046262, mailed on Mar. 16, 2017, 26 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2017/049795, mailed on Apr. 4, 2019, 16 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2018/033051, mailed on Nov. 28, 2019, 15 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2019/049239, mailed on Apr. 8, 2021, 12 pages. cited by applicant
International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2021/031096, mailed on Nov. 24, 2022, 11 pages. cited by applicant
International Search Report and Written Opinion received for PCT Application No. PCT/US2017/049795, mailed on Dec. 27, 2017., 26 pages. cited by applicant
International Search Report and Written Opinion Received for PCT Patent Application No. PCT/US2018/033051, mailed on Nov. 22, 2018, 22 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2019/049239, mailed on Jan. 22, 2020, 18 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2021/031096, mailed on Oct. 13, 2021, 16 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/029811, mailed on Nov. 7, 2022, 15 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/042069, mailed on Feb. 14, 2023, 22 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/043183, mailed on Jan. 23, 2023, 17 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2022/044637, mailed on Mar. 15, 2023, 19 pages. cited by applicant
International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2023/14067, mailed on Aug. 4, 2023, 17 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2018/033051, mailed on Sep. 20, 2018, 14 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2022/029811, mailed on Sep. 14, 2022, 9 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2022/042069, mailed on Dec. 22, 2022, 14 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2022/044637, mailed on Jan. 20, 2023, 12 pages. cited by applicant
Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2023/14067, mailed on Jun. 14, 2023, 16 pages. cited by applicant
Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2017/049795, mailed on Nov. 3, 2017, 3 pages. cited by applicant
Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2019/049239, mailed on Dec. 4, 2019, 10 pages. cited by applicant
Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2021/031096, mailed on Aug. 19, 2021, 8 pages. cited by applicant
Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2022/043183, mailed on Nov. 30, 2022, 10 pages. cited by applicant
Invitation to Pay Search Fees received for European Patent Application No. 18730555.2, mailed on May 14, 2020, 3 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 15/352,215, mailed on Sep. 20, 2018, 31

pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 15/981,828, mailed on Jan. 7, 2020, 8 pages.
cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/259,771, mailed on Jan. 25, 2022, 20
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/259,771, mailed on May 8, 2019, 11 pages.
cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/553,622, mailed on May 29, 2020, 11
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/806,981, mailed on Nov. 13, 2020, 22
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 16/806,981, mailed on Sep. 1, 2021, 27 pages.
cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/079,216, mailed on Jan. 11, 2023, 15
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/087,855, mailed on Dec. 24, 2021, 21
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/087,855, mailed on Jul. 12, 2021, 17
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/087,855, mailed on Jul. 21, 2022, 23
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/093,408, mailed on Dec. 8, 2021, 37
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/093,408, mailed on Sep. 14, 2022, 46
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/746,179, mailed on Oct. 25, 2022, 18
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/827,004, mailed on Nov. 9, 2022, 27
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,315, mailed on Dec. 22, 2022, 20
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,315, mailed on Nov. 4, 2022, 20
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,510, mailed on Mar. 16, 2023, 16
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,530, mailed on Jan. 3, 2023, 67 pages.
cited by applicant
Non-Final Office Action received for U.S. Appl. No. 17/899,530, mailed on May 25, 2023, 68
pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/119,789, mailed on Jun. 28, 2023, 31
pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2017330212, mailed on Apr.
28, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2018269510, mailed on Apr.
17, 2020, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2019346842, mailed on Jan.
21, 2021, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020210262, mailed on Jan.
20, 2022, 3 pages. cited by applicant
Notice of Acceptance received for Australian Patent Application No. 2020213402, mailed on Sep.

21, 2020, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2020294208, mailed on Mar. 2, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2021202352, mailed on Jun. 6, 2022, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022200965, mailed on May 11, 2023, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2022202360, mailed on Apr. 14, 2023, 3 pages. cited by applicant

Notice of Acceptance received for Australian Patent Application No. 2023204622, mailed on Aug. 10, 2023, 3 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201510557356.X, mailed on Mar. 5, 2020, 2 pages (1 page of English Translation and 1 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201780058426.4, mailed on Jun. 30, 2023, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201880036526.1, mailed on Apr. 22, 2021, 2 pages (1 page of English Translation and 1 page of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201910315328.5, mailed on Aug. 24, 2022, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Chinese Patent Application No. 201980041865.3, mailed on Aug. 16, 2022, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Danish Patent Application No. PA201570563, mailed on May 24, 2016, 2 pages. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2018-107114, mailed on Mar. 22, 2019, 4 pages (1 page of English Translation and 3 pages of Official Copy. cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2019-215503, mailed on Aug. 26, 2022, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2019-511767, mailed on Mar. 30, 2020, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2020-569806, mailed on Jul. 12, 2021, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-092483, mailed on Sep. 30, 2022, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2021-131310, mailed on Dec. 9, 2022, 4 pages (1 pages of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2019-7005369, mailed on Oct. 26, 2020, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2020-7036748, mailed on Jan. 25, 2021, 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2021-7010306, mailed on Aug. 14, 2023, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2022-7003364, mailed on Jul. 28, 2023, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant

Notice of Allowance received for Netherland Patent Application No. 2019753, mailed on Jul. 6, 2018, 6 pages (2 pages of English Translation and 4 pages of Official copy). cited by applicant

Notice of Allowance received for Taiwanese Patent Application No. 104128684, mailed on Feb. 23, 2017, 3 pages (Official Copy only) (See Communication under 37 CFR § 1.98(a) (3)). cited by applicant

Notice of Allowance received for U.S. Appl. No. 14/833,014, mailed on Nov. 20, 2019, 5 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/352,215, mailed on Nov. 27, 2019, 20 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/713,490, mailed on Mar. 20, 2019, 15 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 15/981,828, mailed on Jul. 13, 2020, 8 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 16/553,622, mailed on Sep. 11, 2020, 8 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/079,216, mailed on Apr. 27, 2023, 6 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/079,216, mailed on May 5, 2023, 3 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/087,855, mailed on Nov. 25, 2022, 8 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/093,408, mailed on Aug. 30, 2023, 59 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/746,179, mailed on Mar. 6, 2023, 8 pages.
cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/899,315, mailed on Feb. 24, 2023, 9 pages.
cited by applicant

Office Action received for Australian Patent Application No. 2017330212, mailed on Feb. 21,
2020, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2018269510, mailed on Feb. 21,
2020, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020210262, mailed on Jul. 28, 2021,
6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2020294208, mailed on Dec. 17,
2021, 2 pages. cited by applicant

Office Action received for Australian Patent Application No. 2021202352, mailed on Mar. 15,
2022, 3 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022200965, mailed on Feb. 14,
2023, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022202360, mailed on Feb. 17,
2023, 4 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022231779, mailed on Aug. 7, 2023,
5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022235630, mailed on Jul. 21, 2023,
6 pages. cited by applicant

Office Action received for Australian Patent Application No. 2022235630, mailed on May 17,
2023, 3 pages. cited by applicant

Office Action received for Chinese Patent Application No. 201510557356.X, mailed on Aug. 15,
2019, 12 pages (7 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201510557356.X, mailed on Dec. 29,
2017, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201510557356.X, mailed on Nov. 23,
2018, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201520679198.0, mailed on Jun. 24,
2016, 5 pages (3 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201621208900.6, mailed on Apr. 26, 2017, 2 pages (Official Copy only) (See Communication under 37 CFR § 1.98(a)(3)). cited by applicant

Office Action received for Chinese Patent Application No. 201780058426.4, mailed on Dec. 2, 2022, 11 pages (5 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201810411708.4, mailed on Feb. 24, 2022, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201810411708.4, mailed on Feb. 26, 2021, 16 pages (8 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201810411708.4, mailed on Nov. 12, 2021, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201880036526.1, mailed on Aug. 21, 2020, 8 pages (3 pages of English Translation and 5 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201910315328.5, mailed on Nov. 30, 2021, 21 pages (10 pages of English Translation and 11 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201911199054.4, mailed on Jan. 20, 2021, 19 pages (11 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201911199054.4, mailed on Jul. 3, 2020, 15 pages (9 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201911199054.4, mailed on Jun. 10, 2021, 13 pages (7 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201980041865.3, mailed on Apr. 13, 2022, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 201980041865.3, mailed on May 24, 2021, 14 pages (8 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202010295272.4, mailed on Feb. 27, 2023, 15 pages (6 pages of English Translation and 9 pages of Official Copy). cited by applicant

Office Action received for Danish Patent Application No. PA201670319, mailed on Aug. 2, 2016, 6 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670319, mailed on Jun. 21, 2017, 6 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670319, mailed on Nov. 24, 2016, 7 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670320, mailed on Aug. 4, 2016, 9 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670320, mailed on Dec. 5, 2016, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670320, mailed on Jan. 18, 2018, 2 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201670320, mailed on Jul. 3, 2017, 4 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770395, mailed on Apr. 11, 2019, 10 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201770395, mailed on May 25, 2018, 10 pages. cited by applicant

Office Action received for Danish Patent Application No. PA201870383, mailed on Aug. 26, 2019, 3 pages. cited by applicant

Office Action received for Danish Patent Application No. PA202070167, mailed on Jul. 2, 2021, 5 pages. cited by applicant

Office Action received for European Patent Application No. 15759998.6, mailed on Dec. 19, 2018,

6 pages. cited by applicant
Office Action received for European Patent Application No. 15759998.6, mailed on Jul. 16, 2018, 6 pages. cited by applicant
Office Action received for European Patent Application No. 15759998.6, mailed on May 29, 2019, 6 pages. cited by applicant
Office Action received for European Patent Application No. 17853657.9, mailed on Apr. 1, 2021, 6 pages. cited by applicant
Office Action received for European Patent Application No. 18730555.2, mailed on Feb. 25, 2021, 9 pages. cited by applicant
Office Action received for European Patent Application No. 18730555.2, mailed on Sep. 7, 2020, 11 pages. cited by applicant
Office Action received for European Patent Application No. 19212057.4, mailed on Mar. 9, 2021, 6 pages. cited by applicant
Office Action received for European Patent Application No. 19769336.9, mailed on Nov. 4, 2021, 6 pages. cited by applicant
Office Action received for European Patent Application No. 20176616.9, mailed on Jun. 10, 2021, 4 pages. cited by applicant
Office Action received for European Patent Application No. 21179101.7, mailed on Jul. 7, 2023, 8 pages. cited by applicant
Office Action received for European Patent Application No. 21179101.7, mailed on Oct. 8, 2021, 10 pages. cited by applicant
Office Action received for Japanese Patent Application No. 2017-510631, mailed on Mar. 2, 2018, 12 pages (7 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2018-107114, mailed on Oct. 9, 2018, 4 pages (2 pages of English Translation and 2 pages of Official copy). cited by applicant
Office Action received for Japanese Patent Application No. 2019-215503, mailed on Feb. 5, 2021, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2019-215503, mailed on Jul. 3, 2020, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2021-092483, mailed on Apr. 1, 2022, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2021-131310, mailed on Sep. 2, 2022, 9 pages (5 pages of English Translation and 4 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2019-7005369, mailed on Mar. 13, 2020, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2021-7002582, mailed on Apr. 16, 2021, 13 pages (6 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2021-7002582, mailed on Oct. 29, 2021, 6 pages (3 pages of English Translation and 3 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2021-7010306, mailed on Feb. 15, 2023, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2022-7003364, mailed on Apr. 22, 2022, 14 pages (6 pages of English Translation and 8 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2022-7003364, mailed on Dec. 26, 2022, 8 pages (3 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Netherland Patent Application No. 2019753, mailed on Apr. 12, 2018, 8 pages (3 page of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Taiwanese Patent Application No. 104128684, mailed on Nov. 8, 2016, 24 pages (9 pages of English Translation and 15 pages of Official Copy). cited by applicant
Qualcomm Toq-smartwatch-User Manual, Available Online At: URL:

https://toq.qualcomm.com/sites/default/files/qualcomm_toq_user_manual.pdf [retrieved on Jun. 25, 2015], Nov. 27, 2013, pp. 1-38. cited by applicant

Record of Oral Hearing received for U.S. Appl. No. 16/259,771, mailed on Aug. 4, 2021, 15 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201770395, mailed on Sep. 5, 2017, 14 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA201870383, mailed on Sep. 7, 2018, 8 pages. cited by applicant

Search Report and Opinion received for Danish Patent Application No. PA202070167, mailed on Nov. 25, 2020, 9 pages. cited by applicant

Search Report and Opinion received for Netherlands Patent Application No. 2015364, issued on Jul. 4, 2017, 12 pages (5 pages of English Translation of Search Opinion and 7 pages of official copy). cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 17853657.9, mailed on May 2, 2023, 8 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 19212057.4, mailed on Apr. 19, 2023, 9 pages. cited by applicant

Summons to Attend Oral Proceedings received for European Patent Application No. 20176616.9, mailed on Dec. 17, 2021, 7 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 14/833,014, mailed on Mar. 12, 2020, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 15/713,490, mailed on May 30, 2019, 2 pages. cited by applicant

Supplemental Notice of Allowance received for U.S. Appl. No. 17/746,179, mailed on Apr. 3, 2023, 2 pages. cited by applicant

Non Final Office Action received for U.S. Appl. No. 14/833,014, mailed on Mar. 21, 2016, 26 pages. cited by applicant

Office Action Received for Australian Patent Application No. 2015101183, issued on Nov. 6, 2015, 4 pages. cited by applicant

Office Action received for Chinese Patent Application No. 2015206791980, mailed on Mar. 7, 2016, 6 pages (4 pages of English Translation and 2 pages of Official Copy). cited by applicant

Office Action Received for Chinese Patent Application No. 2015206791980, mailed on Nov. 18, 2015, 4 pages (2 pages English Translation and 2 pages Official copy). cited by applicant

Applivgames, "Super Mario Run" Stickers for iMessage: Free Delivery Started!, Available online at: <<https://games.app-liv.jp/archives/178627>>, Sep. 13, 2016, 3 pages (Official Copy Only) (See Communication under 37 CFR § 1.98(a) (3)). cited by applicant

Clark Mitchell, "Qualcomm's going toe-to-toe with Apple's satellite messaging feature", Available online at: <https://www.theverge.com/2023/1/5/23538207/qualcomm-satellite-messaging-snapdragon-android>, Jan. 6, 2023, 18 pages. cited by applicant

Contents Pocket, "Line Stamp Information", Available online at: <<https://web.archive.org/web/20150404080541/http://contents-pocket.net/linestamp.html>>, Apr. 2015, 2 pages (Official Copy Only) (See Communication under 37 CFR § 1.98(a) (3)). cited by applicant

Exultationpictures, "Align Satellite Dish on Astra 19.2 with the App Satellite Finder (Pro) and DUR Line SF4000", Online available at: <https://www.youtube.com/watch?v=n5EEZ6rcYcQ>, Mar. 29, 2021, 2 pages. cited by applicant

Fono et al., "Eye Windows: Evaluation of Eye-Controlled Zooming Windows for Focus Selection", CHI 2005, Conference Proceedings, Conference On Human Factors In Computing Systems, Apr. 2-7, 2005, pp. 151-160. cited by applicant

Horowitz Paul, "Always Show Scroll Bars in Mac OS X", OS X Daily, available online at: URL:

<http://jiosxdaily.com/2011/08/03/show-scroll-bars-mac-os-x-lion/>, Aug. 3, 2011, 7 pages. cited by applicant

Krotov Ilya, “Bellus3D app experience”, Available online at: <https://www.youtube.com/watch?v=aSu688IY26c&t=45s>, Aug. 17, 2021, 2 pages. cited by applicant

Motorola Solutions, “Wave 7000 Push-to-Talk for Mobile Devices”, XP055709564, Retrieved from the Internet: URL: <https://learning.motorolasolutions.com/es/node/2426/download>, Jul. 2016, pp. 1-54. cited by applicant

Intention To Grant received for Danish Patent Application No. PA201570563, mailed on Mar. 17, 2016, 7 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2015/046262, mailed on Mar. 15, 2016, 34 pages. cited by applicant

Invitation to Pay Additional Fees received for PCT Patent Application No. PCT/US2015/046262, mailed on Nov. 23, 2015, 7 pages. cited by applicant

Peters Jay, “The iPhone 13's rumored satellite link sounds like it's just for emergencies”, The Verge, Available online at: <https://apple.news/A-xX1QS6IT2m818PPKtL52Q>, Aug. 30, 2021, 2 pages. cited by applicant

Pocketnow, “AT&T Enhanced Push To Talk: A Guided Tour | Pocketnow”, Retrieved from <https://www.youtube.com/watch?v=aagcgg07EEc>, Dec. 25, 2012, 1 page. cited by applicant

ProPTT2 Wearable App with Apple Watch, Retrieved from the Internet:

<<https://www.youtube.com/watch?v=iqOT30irl4A>>, Mar. 29, 2017, 3 pages. cited by applicant

Singh Lovepreet, “Samsung Galaxy Watch: How to Change Watch Face—Tips and Tricks”, Online available at: <<https://www.youtube.com/watch?pp=desktop&v=IN7gPxTZ1qU>>, Dec. 4, 2018, 80 pages. cited by applicant

Team on the Run, “Push-To-Talk Feature for Android”, Retrieved from the Internet:

<https://www.youtube.com/watch?v=_dlrC7q92KQ>, Oct. 14, 2016, 3 pages. cited by applicant

Theunlockr, “Galaxy Watch Complete Walkthrough: The Best Watch They've Made So Far”, Available online at: <https://www.youtube.com/watch?v=xiECIf1SN4>, Sep. 11, 2018, 27 pages. cited by applicant

Wikipedia, “Emoji”, Online Available at:

<https://web.archive.org/web/20140829025736/https://en.wikipedia.org/wiki/Emoji>, 2014, 13 pages. cited by applicant

ZY News, “Generate Cartoon Face within Three Seconds, You are the New-generation Expression Emperor”, Online available at: <<http://inews.ifeng.com/48551936/news.shtml>>, Apr. 22, 2016, 3 pages (Official Copy Only) (See Communication under 37 CFR § 1.98(a) (3)). cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 17/899,510, mailed on Jun. 5, 2024, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/105,191, mailed on Apr. 30, 2024, 2 pages. cited by applicant

Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/204,908, mailed on Jul. 2, 2024, 4 pages. cited by applicant

Board Opinion received for Chinese Patent Application No. 201911199054.4, mailed on May 10, 2024, 24 pages (13 pages of English Translation and 11 pages of Official Copy). cited by applicant

Corrected Notice of Allowance received for U.S. Appl. No. 18/105,191, mailed on Aug. 6, 2024, 5 pages. cited by applicant

Decision to Grant received for European Patent Application No. 22197456.1, mailed on Aug. 29, 2024, 3 pages. cited by applicant

Decision to Grant received for Japanese Patent Application No. 2023-572180. mailed on Apr. 22, 2024. 3 pages (1 page of English Translation and 2 pages of Official Copy). cited by applicant

Intention to Grant received for European Patent Application No. 22197456.1, mailed on Apr. 16, 2024, 9 pages. cited by applicant

Intention to Grant received for European Patent Application No. 23173355.1, mailed on Jun. 28, 2024, 9 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/043183, mailed on Mar. 28, 2024, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2022/044637, mailed on Apr. 4, 2024, 12 pages. cited by applicant

International Preliminary Report on Patentability received for PCT Patent Application No. PCT/US2023/014067, mailed on Sep. 12, 2024, 12 pages. cited by applicant

International Search Report and Written Opinion received for PCT Patent Application No. PCT/US2024/012658, mailed on Jun. 21, 2024, 22 pages. cited by applicant

Invitation to Pay Additional Fees and Partial International Search Report received for PCT Patent Application No. PCT/US2024/012658, mailed on Apr. 30, 2024, 13 pages. cited by applicant

Invitation to Pay Search Fees received for European Patent Application No. 21727979.3, mailed on Jul. 10, 2024, 4 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/204,908, mailed on Jun. 5, 2024, 16 pages. cited by applicant

Non-Final Office Action received for U.S. Appl. No. 18/230,465, mailed on Aug. 15, 2024, 37 pages. cited by applicant

Notice of Allowance received for Chinese Patent Application No. 202110666978.1, mailed on Jun. 28, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-170806, mailed on Aug. 9, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2022-557929, mailed on Aug. 5, 2024, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant

Notice of Allowance received for Japanese Patent Application No. 2023-001790, mailed on Jul. 5, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for Korean Patent Application No. 10-2023-7039673, mailed on Aug. 21, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant

Notice of Allowance received for U.S. Appl. No. 17/899,510, mailed on Sep. 11, 2024, 20 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/105,191, mailed on May 22, 2024, 8 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/204,908, mailed on Jul. 24, 2024, 6 pages. cited by applicant

Notice of Allowance received for U.S. Appl. No. 18/230,465, mailed on Sep. 16, 2024, 5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023219926, mailed on Aug. 24, 2024, 5 pages. cited by applicant

Office Action received for Australian Patent Application No. 2023270278, mailed on Sep. 17, 2024, 3 pages. cited by applicant

Office Action received for Chinese Patent Application No. 202010295272.4, mailed on Jun. 11, 2024, 12 pages (5 pages of English Translation and 7 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202280036173.1, mailed on Jul. 21, 2024, 12 pages (6 pages of English Translation and 6 pages of Official Copy). cited by applicant

Office Action received for Chinese Patent Application No. 202280036173.1, mailed on May 10, 2024, 16 pages (8 pages of English Translation and 8 pages of Official Copy). cited by applicant

Office Action received for European Patent Application No. 22729935.1, mailed on May 10, 2024, 7 pages. cited by applicant

Office Action received for Japanese Patent Application No. 2022-170806, mailed on May 13, 2024,

4 pages (2 pages of English Translation and 2 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2022-557929, mailed on Mar. 29, 2024, 8 pages (4 pages of English Translation and 4 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2023-001269, mailed on Mar. 22, 2024, 14 pages (7 pages of English Translation and 7 pages of Official Copy). cited by applicant
Office Action received for Japanese Patent Application No. 2023-001270, mailed on Mar. 22, 2024, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Korean Patent Application No. 10-2023-7037034, mailed on Jul. 22, 2024, 23 pages (11 pages of English Translation and 12 pages of Official Copy). cited by applicant
Supplemental Notice of Allowance received for U.S. Appl. No. 18/204,908, mailed on Aug. 13, 2024, 2 pages. cited by applicant
Board Decision received for Chinese Patent Application No. 201911199054.4, mailed on Sep. 25, 2024, 24 pages (1 page of English Translation and 23 pages of Official Copy). cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/899,510, mailed on Oct. 1, 2024, 3 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/230,465, mailed on Oct. 9, 2024, 2 pages. cited by applicant
Notice of Allowance received for Japanese Patent Application No. 2023-001270, mailed on Sep. 30, 2024, 4 pages (1 page of English Translation and 3 pages of Official Copy). cited by applicant
Office Action received for European Patent Application No. 21727979.3, mailed on Sep. 26, 2024, 11 pages. cited by applicant
Office Action received for Japanese Patent Application No. 2023-001269, mailed on Sep. 20, 2024, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant
Supplemental Notice of Allowance received for U.S. Appl. No. 18/204,908, mailed on Oct. 9, 2024, 2 pages. cited by applicant
Supplemental Notice of Allowance received for U.S. Appl. No. 18/204,908, mailed on Sep. 26, 2024, 2 pages. cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 18/378,470, mailed on May 29, 2025, 2 pages. cited by applicant
Kxowls, "Face Unlock Not Working", Online available at: <https://youtube.com/shorts/EF8WgD...9Oiw?si=i-4X8OAGPLHgMfvz>, Nov. 2, 2020, 2 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/167,767, mailed on Jun. 4, 2025, 32 pages. cited by applicant
Office Action received for Korean Patent Application No. 10-2023-7039602, mailed on May 28, 2025, 9 pages (4 pages of English Translation and 5 pages of Official Copy). cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/374,562, mailed on Jul. 22, 2025, 2 pages. cited by applicant
Final Office Action received for U.S. Appl. No. 17/941,400, mailed on Jul. 17, 2025, 8 pages. cited by applicant
Intention to Grant received for European Patent Application No. 22197430.6, mailed on Jul. 22, 2025, 12 pages. cited by applicant
Intention to Grant received for European Patent Application No. 22785843.8, mailed on Jul. 10, 2025, 8 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/371,403, mailed on Jul. 21, 2025, 23 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/371,406, mailed on Jul. 15, 2025, 15 pages. cited by applicant
Notice of Allowance received for U.S. Appl. No. 17/898,342, mailed on Jul. 29, 2025, 9 pages. cited by applicant
Office Action received for European Patent Application No. 22198902.3, mailed on Jul. 9, 2025, 7

pages. cited by applicant
Office Action received for Japanese Patent Application No. 2024-083562, mailed on Jun. 26, 2025, 5 pages (3 pages of English Translation and 2 pages of Official Copy). cited by applicant
Corrected Notice of Allowance received for U.S. Appl. No. 17/898,342, mailed on Aug. 8, 2025, 3 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/201,411, mailed on Aug. 11, 2025, 18 pages. cited by applicant
Office Action received for Australian Patent Application No. 2022352756, mailed on Aug. 8, 2025, 4 pages. cited by applicant
Applicant-Initiated Interview Summary received for U.S. Appl. No. 18/131,833, mailed on Jun. 27, 2025, 2 pages. cited by applicant
Extended European Search Report received for European Patent Application No. 25160012.8, mailed on Jun. 10, 2025, 8 pages. cited by applicant
Extended European Search Report received for European Patent Application No. 25169286.9, mailed on Jun. 26, 2025, 12 pages. cited by applicant
Non-Final Office Action received for U.S. Appl. No. 18/829,038, mailed on Jun. 23, 2025, 12 pages. cited by applicant
Notice of Allowance received for Japanese Patent Application No. 2025-048996, mailed on Jun. 23, 2025, 5 pages (1 page of English Translation and 4 pages of Official Copy). cited by applicant
Notice of Allowance received for Korean Patent Application No. 10-2023-7037034, mailed on May 28, 2025, 7 pages (2 pages of English Translation and 5 pages of Official Copy). cited by applicant
Office Action received for Australian Patent Application No. 2024203238, mailed on Jun. 25, 2025, 5 pages. cited by applicant
Office Action received for Japanese Patent Application No. 2024-550636, mailed on Jun. 20, 2025, 10 pages (5 pages of English Translation and 5 pages of Official Copy). cited by applicant

Primary Examiner: Craddock; Robert J

Attorney, Agent or Firm: DLA Piper LLP (US)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application claims priority to U.S. Provisional Patent Application 63/470,882, entitled “USER INTERFACES FOR MANAGING LIVE COMMUNICATION SESSIONS,” filed Jun. 3, 2023 and U.S. Provisional Patent Application 63/409,583, entitled “USER INTERFACES FOR MANAGING LIVE COMMUNICATION SESSIONS,” filed Sep. 23, 2022, the contents of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

(1) The present disclosure relates generally to computer systems that are in communication with a display generation component and, optionally, one or more sensors that provide computer-generated experiences, including, but not limited to, electronic devices that provide virtual reality and mixed reality experiences via a display.

BACKGROUND

(2) The development of computer systems for augmented reality has increased significantly in recent years. Example augmented reality environments include at least some virtual elements that replace or augment the physical world. Input devices, such as cameras, controllers, joysticks, touch-sensitive surfaces, and touch-screen displays for computer systems and other electronic

computing devices are used to interact with virtual/augmented reality environments. Example virtual elements include virtual objects, such as digital images, video, text, icons, and control elements such as buttons and other graphics.

SUMMARY

(3) Some methods and interfaces for managing live communication sessions, such as those including at least some virtual elements (e.g., applications, augmented reality environments, mixed reality environments, and virtual reality environments) are cumbersome, inefficient, and limited. For example, systems that provide insufficient controls for performing actions associated with virtual objects, systems that require a series of inputs to achieve a desired outcome in an augmented reality environment, and systems in which manipulation of virtual objects are complex, tedious, and error-prone, create a significant cognitive burden on a user, and detract from the experience with the virtual/augmented reality environment. In addition, these methods take longer than necessary, thereby wasting energy of the computer system. This latter consideration is particularly important in battery-operated devices.

(4) Accordingly, there is a need for computer systems with improved methods and interfaces for managing live communication sessions that are more efficient and intuitive for a user. Such methods and interfaces optionally complement or replace conventional methods for managing live communication sessions. Such methods and interfaces reduce the number, extent, and/or nature of the inputs from a user by helping the user to understand the connection between provided inputs and device responses to the inputs, thereby creating a more efficient human-machine interface.

(5) The above deficiencies and other problems associated with user interfaces for computer systems are reduced or eliminated by the disclosed systems. In some embodiments, the computer system is a desktop computer with an associated display. In some embodiments, the computer system is a portable device (e.g., a notebook computer, tablet computer, or handheld device). In some embodiments, the computer system is a personal electronic device (e.g., a wearable electronic device, such as a watch, or a head-mounted device). In some embodiments, the computer system has a touchpad. In some embodiments, the computer system has one or more cameras. In some embodiments, the computer system has a touch-sensitive display (also known as a “touch screen” or “touch-screen display”). In some embodiments, the computer system has one or more eye-tracking components. In some embodiments, the computer system has one or more hand-tracking components. In some embodiments, the computer system has one or more output devices in addition to the display generation component, the output devices including one or more tactile output generators and/or one or more audio output devices. In some embodiments, the computer system has a graphical user interface (GUI), one or more processors, memory and one or more modules, programs or sets of instructions stored in the memory for performing multiple functions. In some embodiments, the user interacts with the GUI through a stylus and/or finger contacts and gestures on the touch-sensitive surface, movement of the user's eyes and hand in space relative to the GUI (and/or computer system) or the user's body as captured by cameras and other movement sensors, and/or voice inputs as captured by one or more audio input devices. In some embodiments, the functions performed through the interactions optionally include image editing, drawing, presenting, word processing, spreadsheet making, game playing, telephoning, video conferencing, e-mailing, instant messaging, workout support, digital photographing, digital videoing, web browsing, digital music playing, note taking, and/or digital video playing. Executable instructions for performing these functions are, optionally, included in a transitory and/or non-transitory computer readable storage medium or other computer program product configured for execution by one or more processors.

(6) There is a need for electronic devices with improved methods and interfaces for managing live communication sessions. Such methods and interfaces may complement or replace conventional methods for managing live communication sessions. Such methods and interfaces reduce the number, extent, and/or the nature of the inputs from a user and produce a more efficient human-

machine interface. For battery-operated computing devices, such methods and interfaces conserve power and increase the time between battery charges.

(7) In some embodiments, a computer system displays a set of controls associated with controlling playback of media content (e.g., transport controls and/or other types of controls) in response to detecting a gaze and/or gesture of the user. In some embodiments, the computer system initially displays a first set of controls in a reduced-prominence state (e.g., with reduced visual prominence) in response to detecting a first input, and then displays a second set of controls (which optionally includes additional controls) in an increased-prominence state in response to detecting a second input. In this manner, the computer system optionally provides feedback to the user that they have begun to invoke display of the controls without unduly distracting the user from the content (e.g., by initially displaying controls in a less visually prominent manner), and then, based on detecting a user input indicating that the user wishes to further interact with the controls, displaying the controls in a more visually prominent manner to allow for easier and more-accurate interactions with the computer system.

(8) Example methods are described herein. An example method includes, at a computer system that is in communication with a display generation component and one or more sensors: displaying, via the display generation component, representations of a plurality of users; receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(9) An example method includes, at a computer system that is in communication with a display generation component and one or more sensors: displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and in response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(10) An example method includes, at a computer system that is in communication with a display generation component: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via

the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(11) An example method includes, at a computer system that is in communication with a display generation component and one or more sensors: while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(12) Example non-transitory computer-readable storage media are described herein. An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: displaying, via the display generation component, representations of a plurality of users; receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(13) An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and in response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(14) An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and includes instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein

displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(15) An example non-transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(16) Example transitory computer-readable storage media are described herein. An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: displaying, via the display generation component, representations of a plurality of users; receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(17) An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and in response to detecting the one or more inputs that include

the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(18) An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and includes instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(19) An example transitory computer-readable storage medium stores one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors and includes instructions for: while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(20) Example computer systems are described herein. An example computer system is configured to communicate with a display generation component and one or more sensors and includes: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, via the display generation component, representations of a plurality of users; receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(21) An example computer system is configured to communicate with a display generation

component and one or more sensors and includes: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and in response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(22) An example computer system is configured to communicate with a display generation component and includes: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(23) An example computer system is configured to communicate with a display generation component and one or more sensors and includes: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(24) An example computer system is configured to communicate with a display generation component and one or more sensors and includes means for displaying, via the display generation

component, representations of a plurality of users; means for receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and means for, in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(25) An example computer system is configured to communicate with a display generation component and one or more sensors and includes means for displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; means for, while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; means for detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and means for, in response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(26) An example computer system is configured to communicate with a display generation component and includes means for, while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; means for, while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and means for, in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(27) An example computer system is configured to communicate with a display generation component and one or more sensors and includes means for, while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and means for, in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet

the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(28) Example computer program products are described herein. An example computer program product includes one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors, the one or more programs including instructions for: displaying, via the display generation component, representations of a plurality of users; receiving, via the one or more sensors, selection of a representation of a respective user of the plurality of users; and in response to receiving selection of the representation of the respective user: in accordance with a determination that there is an ongoing communication session, displaying, via the display generation component, an option to invite the respective user to join the ongoing communication session; and in accordance with a determination that there is no ongoing communication session, forgoing display of the option to invite the respective user to join the ongoing communication session.

(29) An example computer program product includes one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors, the one or more programs including instructions for: displaying, via the display generation component, a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with movement, detected by the one or more sensors, of the user of the computer system; while displaying the communication user interface, displaying, via the display generation component, a selectable user interface object; detecting, via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object; and in response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, concurrently displaying, via the display generation component, an avatar editing user interface that includes: the avatar representing the user of the computer system; and one or more options to modify an appearance of the avatar representing the user of the computer system.

(30) An example computer program product includes one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, the one or more programs including instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

(31) An example computer program product includes one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component and one or more sensors, the one or more programs including instructions for: while in a communication session with one or more participants in the communication session, detecting, via the one or more sensors, gaze input of a user of the computer system; and in response to detecting the gaze input: in accordance with a determination that the gaze input meets a set of one or more gaze criteria, displaying, via the display generation component, information about a first participant in the communication session; and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, forgoing display of the information about the first participant in the communication session.

(32) Note that the various embodiments described above can be combined with any other embodiments described herein. The features and advantages described in the specification are not all inclusive and, in particular, many additional features and advantages will be apparent to one of ordinary skill in the art in view of the drawings, specification, and claims. Moreover, it should be noted that the language used in the specification has been principally selected for readability and instructional purposes, and may not have been selected to delineate or circumscribe the inventive subject matter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) For a better understanding of the various described embodiments, reference should be made to the Description of Embodiments below, in conjunction with the following drawings in which like reference numerals refer to corresponding parts throughout the figures.

(2) FIG. 1A is a block diagram illustrating an operating environment of a computer system for providing XR experiences in accordance with some embodiments.

(3) FIGS. 1B-1P are examples of a computer system for providing XR experiences in the operating environment of FIG. 1A.

(4) FIG. 2 is a block diagram illustrating a controller of a computer system that is configured to manage and coordinate a XR experience for the user in accordance with some embodiments.

(5) FIG. 3 is a block diagram illustrating a display generation component of a computer system that is configured to provide a visual component of the XR experience to the user in accordance with some embodiments.

(6) FIG. 4 is a block diagram illustrating a hand tracking unit of a computer system that is configured to capture gesture inputs of the user in accordance with some embodiments.

(7) FIG. 5 is a block diagram illustrating an eye tracking unit of a computer system that is configured to capture gaze inputs of the user in accordance with some embodiments.

(8) FIG. 6 is a flow diagram illustrating a glint-assisted gaze tracking pipeline in accordance with some embodiments.

(9) FIGS. 7A-7Q illustrate example techniques for managing live communication sessions, in accordance with some embodiments.

(10) FIG. 8 is a flow diagram of methods of managing live communication sessions, in accordance with various embodiments.

(11) FIG. 9 is a flow diagram of methods of providing avatars in live communication sessions, in accordance with various embodiments.

(12) FIGS. 10A-10E illustrate example techniques for providing representations in live communication sessions, in accordance with some embodiments.

(13) FIG. 11 is a flow diagram of methods of providing representations in live communication sessions, in accordance with various embodiments.

(14) FIGS. 12A-12F illustrate example techniques for providing information in live communication sessions, in accordance with some embodiments.

(15) FIG. 13 is a flow diagram of methods of providing information in live communication sessions, in accordance with various embodiments.

DESCRIPTION OF EMBODIMENTS

(16) The present disclosure relates to user interfaces for providing an extended reality (XR) experience to a user, in accordance with some embodiments.

(17) The systems, methods, and GUIs described herein improve user interface interactions with virtual/augmented reality environments in multiple ways.

(18) In some embodiments, a computer system allows for live communication between users. The computer system displays representations of a plurality of users and receives selection of a representation of a respective user of the plurality of users. In response to receiving selection of the representation of the respective user, in accordance with a determination that there is an ongoing communication session, the computer system displays an option to invite the respective user to join the ongoing communication session, and in accordance with a determination that there is no ongoing communication session, the computer system forgoes display of the option to invite the respective user to join the ongoing communication session.

(19) In some embodiments, a computer system provides options for a user to change an appearance of the user's avatar. The computer system displays a communication user interface for communicating with other users in a real-time communication session. During the real-time communication session, the user is represented by an avatar that moves during the real-time communication session in accordance with movement of the user of the computer system. While displaying the communication user interface, the computer system concurrently displays a selectable user interface object. While concurrently displaying the communication user interface and selectable user interface object, the computer system detects one or more inputs that include a selection input directed to the selectable user interface object. In response to detecting the one or more inputs that include the selection input directed to the selectable user interface object, the computer system concurrently displays an avatar editing user interface that includes the avatar representing the user of the computer system and one or more options to modify an appearance of the avatar representing the user of the computer system.

(20) In some embodiments, a computer system switches between spatial and non-spatial communication sessions. While participating in a communication session that is a spatial communication session that includes the computer system displays representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment. Displaying the plurality of participants in the spatially distributed arrangement includes displaying the representations of the plurality of participants spaced apart from each other and the user by at least a threshold amount in a first non-vertical direction in the 3D environment and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction. While displaying the representations of the plurality of participants distributed in the 3D environment, the computer system detects an event, and in response to detecting the event, the computer system transitions the communication session from the spatial communication session to a non-spatial communication session. Transitioning to the non-spatial communication session includes displaying representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement. In the grouped arrangement, the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment, a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement, and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially

distributed arrangement.

(21) In some embodiments, a computer system provides information during a live communication session based on a user's gaze. While in a communication session with one or more participants in the communication session, the computer system detects gaze input of a user of the computer system. In response to detecting the gaze input, in accordance with a determination that the gaze input meets a set of one or more gaze criteria, the computer system displays information about a first participant in the communication session, and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, the computer system forgoes display of the information about the first participant in the communication session.

(22) In some embodiments, a computer system displays content in a first region of a user interface. In some embodiments, while the computer system is displaying the content and while a first set of controls are not displayed in a first state, the computer system detects a first input from a first portion of a user. In some embodiments, in response to detecting the first input, and in accordance with a determination that a gaze of the user is directed to a second region of the user interface when the first input is detected, the computer system displays, in the user interface, the first set of one or more controls in the first state, and in accordance with a determination that the gaze of the user is not directed to the second region of the user interface when the first input is detected, the computer system forgoes displaying the first set of one or more controls in the first state.

(23) In some embodiments, a computer system displays content in a user interface. In some embodiments, while displaying the content, the computer system detects a first input based on movement of a first portion of a user of the computer system. In some embodiments, in response to detecting the first input, the computer system displays, in the user interface, a first set of one or more controls, where the first set of one or more controls are displayed in a first state and are displayed within a first region of the user interface. In some embodiments, while displaying the first set of one or more controls in the first state: in accordance with a determination that one or more first criteria are satisfied, including a criterion that is satisfied when attention of the user is directed to the first region of the user interface based on a movement of a second portion of the user that is different from the first portion of the user, the computer system transitions from displaying the first set of one or more controls in the first state to displaying a second set of one or more controls in a second state, where the second state is different from the first state.

(24) FIGS. 1A-6 provide a description of example computer systems for providing XR experiences to users. FIGS. 7A-7Q illustrate example techniques for managing live communication sessions, in accordance with some embodiments. FIG. 8 is a flow diagram of methods of managing live communication sessions, in accordance with various embodiments. FIG. 9 is a flow diagram of methods of providing avatars in live communication sessions, in accordance with various embodiments. The user interfaces in FIGS. 7A-7Q are used to illustrate the processes in FIG. 8 and FIG. 9. FIGS. 10A-10E illustrate example techniques for providing representations in live communication sessions, in accordance with some embodiments. FIG. 11 is a flow diagram of methods of providing representations in live communication sessions, in accordance with various embodiments. The user interfaces in FIGS. 10A-10E are used to illustrate the processes in FIG. 11. FIGS. 12A-12F illustrate example techniques for providing information in live communication sessions, in accordance with some embodiments. FIG. 13 is a flow diagram of methods of providing information in live communication sessions, in accordance with various embodiments. The user interfaces in FIGS. 10A-10E are used to illustrate the processes in FIG. 11.

(25) The processes described below enhance the operability of the devices and make the user-device interfaces more efficient (e.g., by helping the user to provide proper inputs and reducing user mistakes when operating/interacting with the device) through various techniques, including by providing improved visual feedback to the user, reducing the number of inputs needed to perform an operation, providing additional control options without cluttering the user interface with additional displayed controls, performing an operation when a set of conditions has been met

without requiring further user input, improving privacy and/or security, providing a more varied, detailed, and/or realistic user experience while saving storage space, and/or additional techniques. These techniques also reduce power usage and improve battery life of the device by enabling the user to use the device more quickly and efficiently. Saving on battery power, and thus weight, improves the ergonomics of the device. These techniques also enable real-time communication, allow for the use of fewer and/or less precise sensors resulting in a more compact, lighter, and cheaper device, and enable the device to be used in a variety of lighting conditions. These techniques reduce energy usage, thereby reducing heat emitted by the device, which is particularly important for a wearable device where a device well within operational parameters for device components can become uncomfortable for a user to wear if it is producing too much heat.

(26) In addition, in methods described herein where one or more steps are contingent upon one or more conditions having been met, it should be understood that the described method can be repeated in multiple repetitions so that over the course of the repetitions all of the conditions upon which steps in the method are contingent have been met in different repetitions of the method. For example, if a method requires performing a first step if a condition is satisfied, and a second step if the condition is not satisfied, then a person of ordinary skill would appreciate that the claimed steps are repeated until the condition has been both satisfied and not satisfied, in no particular order. Thus, a method described with one or more steps that are contingent upon one or more conditions having been met could be rewritten as a method that is repeated until each of the conditions described in the method has been met. This, however, is not required of system or computer readable medium claims where the system or computer readable medium contains instructions for performing the contingent operations based on the satisfaction of the corresponding one or more conditions and thus is capable of determining whether the contingency has or has not been satisfied without explicitly repeating steps of a method until all of the conditions upon which steps in the method are contingent have been met. A person having ordinary skill in the art would also understand that, similar to a method with contingent steps, a system or computer readable storage medium can repeat the steps of a method as many times as are needed to ensure that all of the contingent steps have been performed.

(27) In some embodiments, as shown in FIG. 1A, the XR experience is provided to the user via an operating environment **100** that includes a computer system **101**. The computer system **101** includes a controller **110** (e.g., processors of a portable electronic device or a remote server), a display generation component **120** (e.g., a head-mounted device (HMD), a display, a projector, a touch-screen, etc.), one or more input devices **125** (e.g., an eye tracking device **130**, a hand tracking device **140**, other input devices **150**), one or more output devices **155** (e.g., speakers **160**, tactile output generators **170**, and other output devices **180**), one or more sensors **190** (e.g., image sensors, light sensors, depth sensors, tactile sensors, orientation sensors, proximity sensors, temperature sensors, location sensors, motion sensors, velocity sensors, etc.), and optionally one or more peripheral devices **195** (e.g., home appliances, wearable devices, etc.). In some embodiments, one or more of the input devices **125**, output devices **155**, sensors **190**, and peripheral devices **195** are integrated with the display generation component **120** (e.g., in a head-mounted device or a handheld device).

(28) When describing an XR experience, various terms are used to differentially refer to several related but distinct environments that the user may sense and/or with which a user may interact (e.g., with inputs detected by a computer system **101** generating the XR experience that cause the computer system generating the XR experience to generate audio, visual, and/or tactile feedback corresponding to various inputs provided to the computer system **101**). The following is a subset of these terms:

(29) Physical environment: A physical environment refers to a physical world that people can sense and/or interact with without aid of electronic systems. Physical environments, such as a physical park, include physical articles, such as physical trees, physical buildings, and physical people.

People can directly sense and/or interact with the physical environment, such as through sight, touch, hearing, taste, and smell.

(30) Extended reality: In contrast, an extended reality (XR) environment refers to a wholly or partially simulated environment that people sense and/or interact with via an electronic system. In XR, a subset of a person's physical motions, or representations thereof, are tracked, and, in response, one or more characteristics of one or more virtual objects simulated in the XR environment are adjusted in a manner that comports with at least one law of physics. For example, a XR system may detect a person's head turning and, in response, adjust graphical content and an acoustic field presented to the person in a manner similar to how such views and sounds would change in a physical environment. In some situations (e.g., for accessibility reasons), adjustments to characteristic(s) of virtual object(s) in a XR environment may be made in response to representations of physical motions (e.g., vocal commands). A person may sense and/or interact with a XR object using any one of their senses, including sight, sound, touch, taste, and smell. For example, a person may sense and/or interact with audio objects that create a 3D or spatial audio environment that provides the perception of point audio sources in 3D space. In another example, audio objects may enable audio transparency, which selectively incorporates ambient sounds from the physical environment with or without computer-generated audio. In some XR environments, a person may sense and/or interact only with audio objects.

(31) Examples of XR include virtual reality and mixed reality.

(32) Virtual reality: A virtual reality (VR) environment refers to a simulated environment that is designed to be based entirely on computer-generated sensory inputs for one or more senses. A VR environment comprises a plurality of virtual objects with which a person may sense and/or interact. For example, computer-generated imagery of trees, buildings, and avatars representing people are examples of virtual objects. A person may sense and/or interact with virtual objects in the VR environment through a simulation of the person's presence within the computer-generated environment, and/or through a simulation of a subset of the person's physical movements within the computer-generated environment.

(33) Mixed reality: In contrast to a VR environment, which is designed to be based entirely on computer-generated sensory inputs, a mixed reality (MR) environment refers to a simulated environment that is designed to incorporate sensory inputs from the physical environment, or a representation thereof, in addition to including computer-generated sensory inputs (e.g., virtual objects). On a virtuality continuum, a mixed reality environment is anywhere between, but not including, a wholly physical environment at one end and virtual reality environment at the other end. In some MR environments, computer-generated sensory inputs may respond to changes in sensory inputs from the physical environment. Also, some electronic systems for presenting an MR environment may track location and/or orientation with respect to the physical environment to enable virtual objects to interact with real objects (that is, physical articles from the physical environment or representations thereof). For example, a system may account for movements so that a virtual tree appears stationary with respect to the physical ground.

(34) Examples of mixed realities include augmented reality and augmented virtuality.

(35) Augmented reality: An augmented reality (AR) environment refers to a simulated environment in which one or more virtual objects are superimposed over a physical environment, or a representation thereof. For example, an electronic system for presenting an AR environment may have a transparent or translucent display through which a person may directly view the physical environment. The system may be configured to present virtual objects on the transparent or translucent display, so that a person, using the system, perceives the virtual objects superimposed over the physical environment. Alternatively, a system may have an opaque display and one or more imaging sensors that capture images or video of the physical environment, which are representations of the physical environment. The system composites the images or video with virtual objects, and presents the composition on the opaque display. A person, using the system,

indirectly views the physical environment by way of the images or video of the physical environment, and perceives the virtual objects superimposed over the physical environment. As used herein, a video of the physical environment shown on an opaque display is called “pass-through video,” meaning a system uses one or more image sensor(s) to capture images of the physical environment, and uses those images in presenting the AR environment on the opaque display. Further alternatively, a system may have a projection system that projects virtual objects into the physical environment, for example, as a hologram or on a physical surface, so that a person, using the system, perceives the virtual objects superimposed over the physical environment. An augmented reality environment also refers to a simulated environment in which a representation of a physical environment is transformed by computer-generated sensory information. For example, in providing pass-through video, a system may transform one or more sensor images to impose a select perspective (e.g., viewpoint) different than the perspective captured by the imaging sensors. As another example, a representation of a physical environment may be transformed by graphically modifying (e.g., enlarging) portions thereof, such that the modified portion may be representative but not photorealistic versions of the originally captured images. As a further example, a representation of a physical environment may be transformed by graphically eliminating or obfuscating portions thereof.

(36) Augmented virtuality: An augmented virtuality (AV) environment refers to a simulated environment in which a virtual or computer-generated environment incorporates one or more sensory inputs from the physical environment. The sensory inputs may be representations of one or more characteristics of the physical environment. For example, an AV park may have virtual trees and virtual buildings, but people with faces photorealistically reproduced from images taken of physical people. As another example, a virtual object may adopt a shape or color of a physical article imaged by one or more imaging sensors. As a further example, a virtual object may adopt shadows consistent with the position of the sun in the physical environment.

(37) In an augmented reality, mixed reality, or virtual reality environment, a view of a three-dimensional environment is visible to a user. The view of the three-dimensional environment is typically visible to the user via one or more display generation components (e.g., a display or a pair of display modules that provide stereoscopic content to different eyes of the same user) through a virtual viewport that has a viewport boundary that defines an extent of the three-dimensional environment that is visible to the user via the one or more display generation components. In some embodiments, the region defined by the viewport boundary is smaller than a range of vision of the user in one or more dimensions (e.g., based on the range of vision of the user, size, optical properties or other physical characteristics of the one or more display generation components, and/or the location and/or orientation of the one or more display generation components relative to the eyes of the user). In some embodiments, the region defined by the viewport boundary is larger than a range of vision of the user in one or more dimensions (e.g., based on the range of vision of the user, size, optical properties or other physical characteristics of the one or more display generation components, and/or the location and/or orientation of the one or more display generation components relative to the eyes of the user). The viewport and viewport boundary typically move as the one or more display generation components move (e.g., moving with a head of the user for a head mounted device or moving with a hand of a user for a handheld device such as a tablet or smartphone). A viewpoint of a user determines what content is visible in the viewport, a viewpoint generally specifies a location and a direction relative to the three-dimensional environment, and as the viewpoint shifts, the view of the three-dimensional environment will also shift in the viewport. For a head mounted device, a viewpoint is typically based on a location and direction of the head, face, and/or eyes of a user to provide a view of the three-dimensional environment that is perceptually accurate and provides an immersive experience when the user is using the head-mounted device. For a handheld or stationed device, the viewpoint shifts as the handheld or stationed device is moved and/or as a position of a user relative to the handheld or stationed device

changes (e.g., a user moving toward, away from, up, down, to the right, and/or to the left of the device). For devices that include display generation components with virtual passthrough, portions of the physical environment that are visible (e.g., displayed, and/or projected) via the one or more display generation components are based on a field of view of one or more cameras in communication with the display generation components which typically move with the display generation components (e.g., moving with a head of the user for a head mounted device or moving with a hand of a user for a handheld device such as a tablet or smartphone) because the viewpoint of the user moves as the field of view of the one or more cameras moves (and the appearance of one or more virtual objects displayed via the one or more display generation components is updated based on the viewpoint of the user (e.g., displayed positions and poses of the virtual objects are updated based on the movement of the viewpoint of the user)). For display generation components with optical passthrough, portions of the physical environment that are visible (e.g., optically visible through one or more partially or fully transparent portions of the display generation component) via the one or more display generation components are based on a field of view of a user through the partially or fully transparent portion(s) of the display generation component (e.g., moving with a head of the user for a head mounted device or moving with a hand of a user for a handheld device such as a tablet or smartphone) because the viewpoint of the user moves as the field of view of the user through the partially or fully transparent portions of the display generation components moves (and the appearance of one or more virtual objects is updated based on the viewpoint of the user).

(38) In some embodiments a representation of a physical environment (e.g., displayed via virtual passthrough or optical passthrough) can be partially or fully obscured by a virtual environment. In some embodiments, the amount of virtual environment that is displayed (e.g., the amount of physical environment that is not displayed) is based on an immersion level for the virtual environment (e.g., with respect to the representation of the physical environment). For example, increasing the immersion level optionally causes more of the virtual environment to be displayed, replacing and/or obscuring more of the physical environment, and reducing the immersion level optionally causes less of the virtual environment to be displayed, revealing portions of the physical environment that were previously not displayed and/or obscured. In some embodiments, at a particular immersion level, one or more first background objects (e.g., in the representation of the physical environment) are visually de-emphasized (e.g., dimmed, blurred, and/or displayed with increased transparency) more than one or more second background objects, and one or more third background objects cease to be displayed. In some embodiments, a level of immersion includes an associated degree to which the virtual content displayed by the computer system (e.g., the virtual environment and/or the virtual content) obscures background content (e.g., content other than the virtual environment and/or the virtual content) around/behind the virtual content, optionally including the number of items of background content displayed and/or the visual characteristics (e.g., colors, contrast, and/or opacity) with which the background content is displayed, the angular range of the virtual content displayed via the display generation component (e.g., 60 degrees of content displayed at low immersion, 120 degrees of content displayed at medium immersion, or 180 degrees of content displayed at high immersion), and/or the proportion of the field of view displayed via the display generation component that is consumed by the virtual content (e.g., 33% of the field of view consumed by the virtual content at low immersion, 66% of the field of view consumed by the virtual content at medium immersion, or 100% of the field of view consumed by the virtual content at high immersion). In some embodiments, the background content is included in a background over which the virtual content is displayed (e.g., background content in the representation of the physical environment). In some embodiments, the background content includes user interfaces (e.g., user interfaces generated by the computer system corresponding to applications), virtual objects (e.g., files or representations of other users generated by the computer system) not associated with or included in the virtual environment and/or virtual content, and/or

real objects (e.g., pass-through objects representing real objects in the physical environment around the user that are visible such that they are displayed via the display generation component and/or a visible via a transparent or translucent component of the display generation component because the computer system does not obscure/prevent visibility of them through the display generation component). In some embodiments, at a low level of immersion (e.g., a first level of immersion), the background, virtual and/or real objects are displayed in an unobscured manner. For example, a virtual environment with a low level of immersion is optionally displayed concurrently with the background content, which is optionally displayed with full brightness, color, and/or translucency. In some embodiments, at a higher level of immersion (e.g., a second level of immersion higher than the first level of immersion), the background, virtual and/or real objects are displayed in an obscured manner (e.g., dimmed, blurred, or removed from display). For example, a respective virtual environment with a high level of immersion is displayed without concurrently displaying the background content (e.g., in a full screen or fully immersive mode). As another example, a virtual environment displayed with a medium level of immersion is displayed concurrently with darkened, blurred, or otherwise de-emphasized background content. In some embodiments, the visual characteristics of the background objects vary among the background objects. For example, at a particular immersion level, one or more first background objects are visually de-emphasized (e.g., dimmed, blurred, and/or displayed with increased transparency) more than one or more second background objects, and one or more third background objects cease to be displayed. In some embodiments, a null or zero level of immersion corresponds to the virtual environment ceasing to be displayed and instead a representation of a physical environment is displayed (optionally with one or more virtual objects such as application, windows, or virtual three-dimensional objects) without the representation of the physical environment being obscured by the virtual environment. Adjusting the level of immersion using a physical input element provides for quick and efficient method of adjusting immersion, which enhances the operability of the computer system and makes the user-device interface more efficient.

(39) Viewpoint-locked virtual object: A virtual object is viewpoint-locked when a computer system displays the virtual object at the same location and/or position in the viewpoint of the user, even as the viewpoint of the user shifts (e.g., changes). In embodiments where the computer system is a head-mounted device, the viewpoint of the user is locked to the forward facing direction of the user's head (e.g., the viewpoint of the user is at least a portion of the field-of-view of the user when the user is looking straight ahead); thus, the viewpoint of the user remains fixed even as the user's gaze is shifted, without moving the user's head. In embodiments where the computer system has a display generation component (e.g., a display screen) that can be repositioned with respect to the user's head, the viewpoint of the user is the augmented reality view that is being presented to the user on a display generation component of the computer system. For example, a viewpoint-locked virtual object that is displayed in the upper left corner of the viewpoint of the user, when the viewpoint of the user is in a first orientation (e.g., with the user's head facing north) continues to be displayed in the upper left corner of the viewpoint of the user, even as the viewpoint of the user changes to a second orientation (e.g., with the user's head facing west). In other words, the location and/or position at which the viewpoint-locked virtual object is displayed in the viewpoint of the user is independent of the user's position and/or orientation in the physical environment. In embodiments in which the computer system is a head-mounted device, the viewpoint of the user is locked to the orientation of the user's head, such that the virtual object is also referred to as a "head-locked virtual object."

(40) Environment-locked virtual object: A virtual object is environment-locked (alternatively, "world-locked") when a computer system displays the virtual object at a location and/or position in the viewpoint of the user that is based on (e.g., selected in reference to and/or anchored to) a location and/or object in the three-dimensional environment (e.g., a physical environment or a virtual environment). As the viewpoint of the user shifts, the location and/or object in the

environment relative to the viewpoint of the user changes, which results in the environment-locked virtual object being displayed at a different location and/or position in the viewpoint of the user. For example, an environment-locked virtual object that is locked onto a tree that is immediately in front of a user is displayed at the center of the viewpoint of the user. When the viewpoint of the user shifts to the right (e.g., the user's head is turned to the right) so that the tree is now left-of-center in the viewpoint of the user (e.g., the tree's position in the viewpoint of the user shifts), the environment-locked virtual object that is locked onto the tree is displayed left-of-center in the viewpoint of the user. In other words, the location and/or position at which the environment-locked virtual object is displayed in the viewpoint of the user is dependent on the position and/or orientation of the location and/or object in the environment onto which the virtual object is locked. In some embodiments, the computer system uses a stationary frame of reference (e.g., a coordinate system that is anchored to a fixed location and/or object in the physical environment) in order to determine the position at which to display an environment-locked virtual object in the viewpoint of the user. An environment-locked virtual object can be locked to a stationary part of the environment (e.g., a floor, wall, table, or other stationary object) or can be locked to a moveable part of the environment (e.g., a vehicle, animal, person, or even a representation of portion of the users body that moves independently of a viewpoint of the user, such as a user's hand, wrist, arm, or foot) so that the virtual object is moved as the viewpoint or the portion of the environment moves to maintain a fixed relationship between the virtual object and the portion of the environment.

(41) In some embodiments a virtual object that is environment-locked or viewpoint-locked exhibits lazy follow behavior which reduces or delays motion of the environment-locked or viewpoint-locked virtual object relative to movement of a point of reference which the virtual object is following. In some embodiments, when exhibiting lazy follow behavior the computer system intentionally delays movement of the virtual object when detecting movement of a point of reference (e.g., a portion of the environment, the viewpoint, or a point that is fixed relative to the viewpoint, such as a point that is between 5-300 cm from the viewpoint) which the virtual object is following. For example, when the point of reference (e.g., the portion of the environment or the viewpoint) moves with a first speed, the virtual object is moved by the device to remain locked to the point of reference but moves with a second speed that is slower than the first speed (e.g., until the point of reference stops moving or slows down, at which point the virtual object starts to catch up to the point of reference). In some embodiments, when a virtual object exhibits lazy follow behavior the device ignores small amounts of movement of the point of reference (e.g., ignoring movement of the point of reference that is below a threshold amount of movement such as movement by 0-5 degrees or movement by 0-50 cm). For example, when the point of reference (e.g., the portion of the environment or the viewpoint to which the virtual object is locked) moves by a first amount, a distance between the point of reference and the virtual object increases (e.g., because the virtual object is being displayed so as to maintain a fixed or substantially fixed position relative to a viewpoint or portion of the environment that is different from the point of reference to which the virtual object is locked) and when the point of reference (e.g., the portion of the environment or the viewpoint to which the virtual object is locked) moves by a second amount that is greater than the first amount, a distance between the point of reference and the virtual object initially increases (e.g., because the virtual object is being displayed so as to maintain a fixed or substantially fixed position relative to a viewpoint or portion of the environment that is different from the point of reference to which the virtual object is locked) and then decreases as the amount of movement of the point of reference increases above a threshold (e.g., a "lazy follow" threshold) because the virtual object is moved by the computer system to maintain a fixed or substantially fixed position relative to the point of reference. In some embodiments the virtual object maintaining a substantially fixed position relative to the point of reference includes the virtual object being displayed within a threshold distance (e.g., 1, 2, 3, 5, 15, 20, 50 cm) of the point of reference in one or more dimensions (e.g., up/down, left/right, and/or forward/backward relative to

the position of the point of reference).

(42) Hardware: There are many different types of electronic systems that enable a person to sense and/or interact with various XR environments. Examples include head-mounted systems, projection-based systems, heads-up displays (HUDs), vehicle windshields having integrated display capability, windows having integrated display capability, displays formed as lenses designed to be placed on a person's eyes (e.g., similar to contact lenses), headphones/earphones, speaker arrays, input systems (e.g., wearable or handheld controllers with or without haptic feedback), smartphones, tablets, and desktop/laptop computers. A head-mounted system may include speakers and/or other audio output devices integrated into the head-mounted system for providing audio output. A head-mounted system may have one or more speaker(s) and an integrated opaque display. Alternatively, a head-mounted system may be configured to accept an external opaque display (e.g., a smartphone). The head-mounted system may incorporate one or more imaging sensors to capture images or video of the physical environment, and/or one or more microphones to capture audio of the physical environment. Rather than an opaque display, a head-mounted system may have a transparent or translucent display. The transparent or translucent display may have a medium through which light representative of images is directed to a person's eyes. The display may utilize digital light projection, OLEDs, LEDs, uLEDs, liquid crystal on silicon, laser scanning light source, or any combination of these technologies. The medium may be an optical waveguide, a hologram medium, an optical combiner, an optical reflector, or any combination thereof. In one embodiment, the transparent or translucent display may be configured to become opaque selectively. Projection-based systems may employ retinal projection technology that projects graphical images onto a person's retina. Projection systems also may be configured to project virtual objects into the physical environment, for example, as a hologram or on a physical surface. In some embodiments, the controller **110** is configured to manage and coordinate a XR experience for the user. In some embodiments, the controller **110** includes a suitable combination of software, firmware, and/or hardware. The controller **110** is described in greater detail below with respect to FIG. 2. In some embodiments, the controller **110** is a computing device that is local or remote relative to the scene **105** (e.g., a physical environment). For example, the controller **110** is a local server located within the scene **105**. In another example, the controller **110** is a remote server located outside of the scene **105** (e.g., a cloud server, central server, etc.). In some embodiments, the controller **110** is communicatively coupled with the display generation component **120** (e.g., an HMD, a display, a projector, a touch-screen, etc.) via one or more wired or wireless communication channels **144** (e.g., BLUETOOTH, IEEE 802.11x, IEEE 802.16x, IEEE 802.3x, etc.). In another example, the controller **110** is included within the enclosure (e.g., a physical housing) of the display generation component **120** (e.g., an HMD, or a portable electronic device that includes a display and one or more processors, etc.), one or more of the input devices **125**, one or more of the output devices **155**, one or more of the sensors **190**, and/or one or more of the peripheral devices **195**, or share the same physical enclosure or support structure with one or more of the above.

(43) In some embodiments, the display generation component **120** is configured to provide the XR experience (e.g., at least a visual component of the XR experience) to the user. In some embodiments, the display generation component **120** includes a suitable combination of software, firmware, and/or hardware. The display generation component **120** is described in greater detail below with respect to FIG. 3. In some embodiments, the functionalities of the controller **110** are provided by and/or combined with the display generation component **120**.

(44) According to some embodiments, the display generation component **120** provides a XR experience to the user while the user is virtually and/or physically present within the scene **105**.

(45) In some embodiments, the display generation component is worn on a part of the user's body (e.g., on his/her head, on his/her hand, etc.). As such, the display generation component **120** includes one or more XR displays provided to display the XR content. For example, in various embodiments, the display generation component **120** encloses the field-of-view of the user. In some

embodiments, the display generation component **120** is a handheld device (such as a smartphone or tablet) configured to present XR content, and the user holds the device with a display directed towards the field-of-view of the user and a camera directed towards the scene **105**. In some embodiments, the handheld device is optionally placed within an enclosure that is worn on the head of the user. In some embodiments, the handheld device is optionally placed on a support (e.g., a tripod) in front of the user. In some embodiments, the display generation component **120** is a XR chamber, enclosure, or room configured to present XR content in which the user does not wear or hold the display generation component **120**. Many user interfaces described with reference to one type of hardware for displaying XR content (e.g., a handheld device or a device on a tripod) could be implemented on another type of hardware for displaying XR content (e.g., an HMD or other wearable computing device). For example, a user interface showing interactions with XR content triggered based on interactions that happen in a space in front of a handheld or tripod mounted device could similarly be implemented with an HMD where the interactions happen in a space in front of the HMD and the responses of the XR content are displayed via the HMD. Similarly, a user interface showing interactions with XR content triggered based on movement of a handheld or tripod mounted device relative to the physical environment (e.g., the scene **105** or a part of the user's body (e.g., the user's eye(s), head, or hand)) could similarly be implemented with an HMD where the movement is caused by movement of the HMD relative to the physical environment (e.g., the scene **105** or a part of the user's body (e.g., the user's eye(s), head, or hand)).

(46) While pertinent features of the operating environment **100** are shown in FIG. **1A**, those of ordinary skill in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity and so as not to obscure more pertinent aspects of the example embodiments disclosed herein.

(47) FIGS. **1A-1P** illustrate various examples of a computer system that is used to perform the methods and provide audio, visual and/or haptic feedback as part of user interfaces described herein. In some embodiments, the computer system includes one or more display generation components (e.g., first and second display assemblies **1-120a**, **1-120b** and/or first and second optical modules **11.1.1-104a** and **11.1.1-104b**) for displaying virtual elements and/or a representation of a physical environment to a user of the computer system, optionally generated based on detected events and/or user inputs detected by the computer system. User interfaces generated by the computer system are optionally corrected by one or more corrective lenses **11.3.2-216** that are optionally removably attached to one or more of the optical modules to enable the user interfaces to be more easily viewed by users who would otherwise use glasses or contacts to correct their vision. While many user interfaces illustrated herein show a single view of a user interface, user interfaces in a HMD are optionally displayed using two optical modules (e.g., first and second display assemblies **1-120a**, **1-120b** and/or first and second optical modules **11.1.1-104a** and **11.1.1-104b**), one for a user's right eye and a different one for a user's left eye, and slightly different images are presented to the two different eyes to generate the illusion of stereoscopic depth, the single view of the user interface would typically be either a right-eye or left-eye view and the depth effect is explained in the text or using other schematic charts or views. In some embodiments, the computer system includes one or more external displays (e.g., display assembly **1-108**) for displaying status information for the computer system to the user of the computer system (when the computer system is not being worn) and/or to other people who are near the computer system, optionally generated based on detected events and/or user inputs detected by the computer system. In some embodiments, the computer system includes one or more audio output components (e.g., electronic component **1-112**) for generating audio feedback, optionally generated based on detected events and/or user inputs detected by the computer system. In some embodiments, the computer system includes one or more input devices for detecting input such as one or more sensors (e.g., one or more sensors in sensor assembly **1-356**, and/or FIG. **1I**) for detecting information about a physical environment of the device which can be used (optionally in conjunction with one or more

illuminators such as the illuminators described in FIG. 1I) to generate a digital passthrough image, capture visual media corresponding to the physical environment (e.g., photos and/or video), or determine a pose (e.g., position and/or orientation) of physical objects and/or surfaces in the physical environment so that virtual objects can be placed based on a detected pose of physical objects and/or surfaces. In some embodiments, the computer system includes one or more input devices for detecting input such as one or more sensors for detecting hand position and/or movement (e.g., one or more sensors in sensor assembly **1-356**, and/or FIG. 1I) that can be used (optionally in conjunction with one or more illuminators such as the illuminators **6-124** described in FIG. 1I) to determine when one or more air gestures have been performed. In some embodiments, the computer system includes one or more input devices for detecting input such as one or more sensors for detecting eye movement (e.g., eye tracking and gaze tracking sensors in FIG. 1I) which can be used (optionally in conjunction with one or more lights such as lights **11.3.2-110** in FIG. 1O) to determine attention or gaze position and/or gaze movement which can optionally be used to detect gaze-only inputs based on gaze movement and/or dwell. A combination of the various sensors described above can be used to determine user facial expressions and/or hand movements for use in generating an avatar or representation of the user such as an anthropomorphic avatar or representation for use in a real-time communication session where the avatar has facial expressions, hand movements, and/or body movements that are based on or similar to detected facial expressions, hand movements, and/or body movements of a user of the device. Gaze and/or attention information is, optionally, combined with hand tracking information to determine interactions between the user and one or more user interfaces based on direct and/or indirect inputs such as air gestures or inputs that use one or more hardware input devices such as one or more buttons (e.g., first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**), knobs (e.g., first button **1-128**, button **11.1.1-114**, and/or dial or button **1-328**), digital crowns (e.g., first button **1-128** which is depressible and twistable or rotatable, button **11.1.1-114**, and/or dial or button **1-328**), trackpads, touch screens, keyboards, mice and/or other input devices. One or more buttons (e.g., first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**) are optionally used to perform system operations such as recentering content in three-dimensional environment that is visible to a user of the device, displaying a home user interface for launching applications, starting real-time communication sessions, or initiating display of virtual three-dimensional backgrounds. Knobs or digital crowns (e.g., first button **1-128** which is depressible and twistable or rotatable, button **11.1.1-114**, and/or dial or button **1-328**) are optionally rotatable to adjust parameters of the visual content such as a level of immersion of a virtual three-dimensional environment (e.g., a degree to which virtual-content occupies the viewport of the user into the three-dimensional environment) or other parameters associated with the three-dimensional environment and the virtual content that is displayed via the optical modules (e.g., first and second display assemblies **1-120a**, **1-120b** and/or first and second optical modules **11.1.1-104a** and **11.1.1-104b**).

(48) FIG. 1B illustrates a front, top, perspective view of an example of a head-mountable display (HMD) device **1-100** configured to be donned by a user and provide virtual and altered/mixed reality (VR/AR) experiences. The HMD **1-100** can include a display unit **1-102** or assembly, an electronic strap assembly **1-104** connected to and extending from the display unit **1-102**, and a band assembly **1-106** secured at either end to the electronic strap assembly **1-104**. The electronic strap assembly **1-104** and the band **1-106** can be part of a retention assembly configured to wrap around a user's head to hold the display unit **1-102** against the face of the user.

(49) In at least one example, the band assembly **1-106** can include a first band **1-116** configured to wrap around the rear side of a user's head and a second band **1-117** configured to extend over the top of a user's head. The second strap can extend between first and second electronic straps **1-105a**, **1-105b** of the electronic strap assembly **1-104** as shown. The strap assembly **1-104** and the band assembly **1-106** can be part of a securement mechanism extending rearward from the display unit

1-102 and configured to hold the display unit **1-102** against a face of a user.

(50) In at least one example, the securement mechanism includes a first electronic strap **1-105a** including a first proximal end **1-134** coupled to the display unit **1-102**, for example a housing **1-150** of the display unit **1-102**, and a first distal end **1-136** opposite the first proximal end **1-134**. The securement mechanism can also include a second electronic strap **1-105b** including a second proximal end **1-138** coupled to the housing **1-150** of the display unit **1-102** and a second distal end **1-140** opposite the second proximal end **1-138**. The securement mechanism can also include the first band **1-116** including a first end **1-142** coupled to the first distal end **1-136** and a second end **1-144** coupled to the second distal end **1-140** and the second band **1-117** extending between the first electronic strap **1-105a** and the second electronic strap **1-105b**. The straps **1-105a-b** and band **1-116** can be coupled via connection mechanisms or assemblies **1-114**. In at least one example, the second band **1-117** includes a first end **1-146** coupled to the first electronic strap **1-105a** between the first proximal end **1-134** and the first distal end **1-136** and a second end **1-148** coupled to the second electronic strap **1-105b** between the second proximal end **1-138** and the second distal end **1-140**.

(51) In at least one example, the first and second electronic straps **1-105a-b** include plastic, metal, or other structural materials forming the shape the substantially rigid straps **1-105a-b**. In at least one example, the first and second bands **1-116**, **1-117** are formed of elastic, flexible materials including woven textiles, rubbers, and the like. The first and second bands **1-116**, **1-117** can be flexible to conform to the shape of the user's head when donning the HMD **1-100**.

(52) In at least one example, one or more of the first and second electronic straps **1-105a-b** can define internal strap volumes and include one or more electronic components disposed in the internal strap volumes. In one example, as shown in FIG. 1B, the first electronic strap **1-105a** can include an electronic component **1-112**. In one example, the electronic component **1-112** can include a speaker. In one example, the electronic component **1-112** can include a computing component such as a processor.

(53) In at least one example, the housing **1-150** defines a first, front-facing opening **1-152**. The front-facing opening is labeled in dotted lines at **1-152** in FIG. 1B because the display assembly **1-108** is disposed to occlude the first opening **1-152** from view when the HMD **1-100** is assembled. The housing **1-150** can also define a rear-facing second opening **1-154**. The housing **1-150** also defines an internal volume between the first and second openings **1-152**, **1-154**. In at least one example, the HMD **1-100** includes the display assembly **1-108**, which can include a front cover and display screen (shown in other figures) disposed in or across the front opening **1-152** to occlude the front opening **1-152**. In at least one example, the display screen of the display assembly **1-108**, as well as the display assembly **1-108** in general, has a curvature configured to follow the curvature of a user's face. The display screen of the display assembly **1-108** can be curved as shown to compliment the user's facial features and general curvature from one side of the face to the other, for example from left to right and/or from top to bottom where the display unit **1-102** is pressed.

(54) In at least one example, the housing **1-150** can define a first aperture **1-126** between the first and second openings **1-152**, **1-154** and a second aperture **1-130** between the first and second openings **1-152**, **1-154**. The HMD **1-100** can also include a first button **1-128** disposed in the first aperture **1-126** and a second button **1-132** disposed in the second aperture **1-130**. The first and second buttons **1-128**, **1-132** can be depressible through the respective apertures **1-126**, **1-130**. In at least one example, the first button **1-128** and/or second button **1-132** can be twistable dials as well as depressible buttons. In at least one example, the first button **1-128** is a depressible and twistable dial button and the second button **1-132** is a depressible button.

(55) FIG. 1C illustrates a rear, perspective view of the HMD **1-100**. The HMD **1-100** can include a light seal **1-110** extending rearward from the housing **1-150** of the display assembly **1-108** around a perimeter of the housing **1-150** as shown. The light seal **1-110** can be configured to extend from the housing **1-150** to the user's face around the user's eyes to block external light from being visible. In

one example, the HMD **1-100** can include first and second display assemblies **1-120a**, **1-120b** disposed at or in the rearward facing second opening **1-154** defined by the housing **1-150** and/or disposed in the internal volume of the housing **1-150** and configured to project light through the second opening **1-154**. In at least one example, each display assembly **1-120a-b** can include respective display screens **1-122a**, **1-122b** configured to project light in a rearward direction through the second opening **1-154** toward the user's eyes.

(56) In at least one example, referring to both FIGS. **1B** and **1C**, the display assembly **1-108** can be a front-facing, forward display assembly including a display screen configured to project light in a first, forward direction and the rear facing display screens **1-122a-b** can be configured to project light in a second, rearward direction opposite the first direction. As noted above, the light seal **1-110** can be configured to block light external to the HMD **1-100** from reaching the user's eyes, including light projected by the forward facing display screen of the display assembly **1-108** shown in the front perspective view of FIG. **1B**. In at least one example, the HMD **1-100** can also include a curtain **1-124** occluding the second opening **1-154** between the housing **1-150** and the rear-facing display assemblies **1-120a-b**. In at least one example, the curtain **1-124** can be elastic or at least partially elastic.

(57) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **1B** and **1C** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. **1D-1F** and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. **1D-1F** can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIGS. **1B** and **1C**.

(58) FIG. **1D** illustrates an exploded view of an example of an HMD **1-200** including various portions or parts thereof separated according to the modularity and selective coupling of those parts. For example, the HMD **1-200** can include a band **1-216** which can be selectively coupled to first and second electronic straps **1-205a**, **1-205b**. The first securement strap **1-205a** can include a first electronic component **1-212a** and the second securement strap **1-205b** can include a second electronic component **1-212b**. In at least one example, the first and second straps **1-205a-b** can be removably coupled to the display unit **1-202**.

(59) In addition, the HMD **1-200** can include a light seal **1-210** configured to be removably coupled to the display unit **1-202**. The HMD **1-200** can also include lenses **1-218** which can be removably coupled to the display unit **1-202**, for example over first and second display assemblies including display screens. The lenses **1-218** can include customized prescription lenses configured for corrective vision. As noted, each part shown in the exploded view of FIG. **1D** and described above can be removably coupled, attached, re-attached, and changed out to update parts or swap out parts for different users. For example, bands such as the band **1-216**, light seals such as the light seal **1-210**, lenses such as the lenses **1-218**, and electronic straps such as the straps **1-205a-b** can be swapped out depending on the user such that these parts are customized to fit and correspond to the individual user of the HMD **1-200**.

(60) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **1D** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. **1B**, **1C**, and **1E-1F** and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. **1B**, **1C**, and **1E-1F** can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **1D**.

(61) FIG. **1E** illustrates an exploded view of an example of a display unit **1-306** of a HMD. The display unit **1-306** can include a front display assembly **1-308**, a frame/housing assembly **1-350**, and a curtain assembly **1-324**. The display unit **1-306** can also include a sensor assembly **1-356**,

logic board assembly **1-358**, and cooling assembly **1-360** disposed between the frame assembly **1-350** and the front display assembly **1-308**. In at least one example, the display unit **1-306** can also include a rear-facing display assembly **1-320** including first and second rear-facing display screens **1-322a**, **1-322b** disposed between the frame **1-350** and the curtain assembly **1-324**.

(62) In at least one example, the display unit **1-306** can also include a motor assembly **1-362** configured as an adjustment mechanism for adjusting the positions of the display screens **1-322a-b** of the display assembly **1-320** relative to the frame **1-350**. In at least one example, the display assembly **1-320** is mechanically coupled to the motor assembly **1-362**, with at least one motor for each display screen **1-322a-b**, such that the motors can translate the display screens **1-322a-b** to match an interpupillary distance of the user's eyes.

(63) In at least one example, the display unit **1-306** can include a dial or button **1-328** depressible relative to the frame **1-350** and accessible to the user outside the frame **1-350**. The button **1-328** can be electronically connected to the motor assembly **1-362** via a controller such that the button **1-328** can be manipulated by the user to cause the motors of the motor assembly **1-362** to adjust the positions of the display screens **1-322a-b**.

(64) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **1E** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. **1B-1D** and **1F** and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. **1B-1D** and **1F** can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **1E**.

(65) FIG. **1F** illustrates an exploded view of another example of a display unit **1-406** of a HMD device similar to other HMD devices described herein. The display unit **1-406** can include a front display assembly **1-402**, a sensor assembly **1-456**, a logic board assembly **1-458**, a cooling assembly **1-460**, a frame assembly **1-450**, a rear-facing display assembly **1-421**, and a curtain assembly **1-424**. The display unit **1-406** can also include a motor assembly **1-462** for adjusting the positions of first and second display sub-assemblies **1-420a**, **1-420b** of the rear-facing display assembly **1-421**, including first and second respective display screens for interpupillary adjustments, as described above.

(66) The various parts, systems, and assemblies shown in the exploded view of FIG. **1F** are described in greater detail herein with reference to FIGS. **1B-1E** as well as subsequent figures referenced in the present disclosure. The display unit **1-406** shown in FIG. **1F** can be assembled and integrated with the securement mechanisms shown in FIGS. **1B-1E**, including the electronic straps, bands, and other components including light seals, connection assemblies, and so forth.

(67) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **1F** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. **1B-1E** and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. **1B-1E** can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **1F**.

(68) FIG. **1G** illustrates a perspective, exploded view of a front cover assembly **3-100** of an HMD device described herein, for example the front cover assembly **3-1** of the HMD **3-100** shown in FIG. **1G** or any other HMD device shown and described herein. The front cover assembly **3-100** shown in FIG. **1G** can include a transparent or semi-transparent cover **3-102**, shroud **3-104** (or "canopy"), adhesive layers **3-106**, display assembly **3-108** including a lenticular lens panel or array **3-110**, and a structural trim **3-112**. The adhesive layer **3-106** can secure the shroud **3-104** and/or transparent cover **3-102** to the display assembly **3-108** and/or the trim **3-112**. The trim **3-112** can secure the various components of the front cover assembly **3-100** to a frame or chassis of the HMD

device.

(69) In at least one example, as shown in FIG. 1G, the transparent cover **3-102**, shroud **3-104**, and display assembly **3-108**, including the lenticular lens array **3-110**, can be curved to accommodate the curvature of a user's face. The transparent cover **3-102** and the shroud **3-104** can be curved in two or three dimensions, e.g., vertically curved in the Z-direction in and out of the Z-X plane and horizontally curved in the X-direction in and out of the Z-X plane. In at least one example, the display assembly **3-108** can include the lenticular lens array **3-110** as well as a display panel having pixels configured to project light through the shroud **3-104** and the transparent cover **3-102**. The display assembly **3-108** can be curved in at least one direction, for example the horizontal direction, to accommodate the curvature of a user's face from one side (e.g., left side) of the face to the other (e.g., right side). In at least one example, each layer or component of the display assembly **3-108**, which will be shown in subsequent figures and described in more detail, but which can include the lenticular lens array **3-110** and a display layer, can be similarly or concentrically curved in the horizontal direction to accommodate the curvature of the user's face.

(70) In at least one example, the shroud **3-104** can include a transparent or semi-transparent material through which the display assembly **3-108** projects light. In one example, the shroud **3-104** can include one or more opaque portions, for example opaque ink-printed portions or other opaque film portions on the rear surface of the shroud **3-104**. The rear surface can be the surface of the shroud **3-104** facing the user's eyes when the HMD device is donned. In at least one example, opaque portions can be on the front surface of the shroud **3-104** opposite the rear surface. In at least one example, the opaque portion or portions of the shroud **3-104** can include perimeter portions visually hiding any components around an outside perimeter of the display screen of the display assembly **3-108**. In this way, the opaque portions of the shroud hide any other components, including electronic components, structural components, and so forth, of the HMD device that would otherwise be visible through the transparent or semi-transparent cover **3-102** and/or shroud **3-104**.

(71) In at least one example, the shroud **3-104** can define one or more apertures transparent portions **3-120** through which sensors can send and receive signals. In one example, the portions **3-120** are apertures through which the sensors can extend or send and receive signals. In one example, the portions **3-120** are transparent portions, or portions more transparent than surrounding semi-transparent or opaque portions of the shroud, through which sensors can send and receive signals through the shroud and through the transparent cover **3-102**. In one example, the sensors can include cameras, IR sensors, LUX sensors, or any other visual or non-visual environmental sensors of the HMD device.

(72) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1G can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described herein can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1G.

(73) FIG. 1H illustrates an exploded view of an example of an HMD device **6-100**. The HMD device **6-100** can include a sensor array or system **6-102** including one or more sensors, cameras, projectors, and so forth mounted to one or more components of the HMD **6-100**. In at least one example, the sensor system **6-102** can include a bracket **1-338** on which one or more sensors of the sensor system **6-102** can be fixed/secured.

(74) FIG. 1I illustrates a portion of an HMD device **6-100** including a front transparent cover **6-104** and a sensor system **6-102**. The sensor system **6-102** can include a number of different sensors, emitters, receivers, including cameras, IR sensors, projectors, and so forth. The transparent cover **6-104** is illustrated in front of the sensor system **6-102** to illustrate relative positions of the various sensors and emitters as well as the orientation of each sensor/emitter of the system **6-102**. As

referenced herein, “sideways,” “side,” “lateral,” “horizontal,” and other similar terms refer to orientations or directions as indicated by the X-axis shown in FIG. 1J. Terms such as “vertical,” “up,” “down,” and similar terms refer to orientations or directions as indicated by the Z-axis shown in FIG. 1J. Terms such as “frontward,” “rearward,” “forward,” “backward,” and similar terms refer to orientations or directions as indicated by the Y-axis shown in FIG. 1J.

(75) In at least one example, the transparent cover **6-104** can define a front, external surface of the HMD device **6-100** and the sensor system **6-102**, including the various sensors and components thereof, can be disposed behind the cover **6-104** in the Y-axis/direction. The cover **6-104** can be transparent or semi-transparent to allow light to pass through the cover **6-104**, both light detected by the sensor system **6-102** and light emitted thereby.

(76) As noted elsewhere herein, the HMD device **6-100** can include one or more controllers including processors for electrically coupling the various sensors and emitters of the sensor system **6-102** with one or more mother boards, processing units, and other electronic devices such as display screens and the like. In addition, as will be shown in more detail below with reference to other figures, the various sensors, emitters, and other components of the sensor system **6-102** can be coupled to various structural frame members, brackets, and so forth of the HMD device **6-100** not shown in FIG. 1I. FIG. 1I shows the components of the sensor system **6-102** unattached and un-coupled electrically from other components for the sake of illustrative clarity.

(77) In at least one example, the device can include one or more controllers having processors configured to execute instructions stored on memory components electrically coupled to the processors. The instructions can include, or cause the processor to execute, one or more algorithms for self-correcting angles and positions of the various cameras described herein overtime with use as the initial positions, angles, or orientations of the cameras get bumped or deformed due to unintended drop events or other events.

(78) In at least one example, the sensor system **6-102** can include one or more scene cameras **6-106**. The system **6-102** can include two scene cameras **6-106** disposed on either side of the nasal bridge or arch of the HMD device **6-100** such that each of the two cameras **6-106** correspond generally in position with left and right eyes of the user behind the cover **6-103**. In at least one example, the scene cameras **6-106** are oriented generally forward in the Y-direction to capture images in front of the user during use of the HMD **6-100**. In at least one example, the scene cameras are color cameras and provide images and content for MR video pass through to the display screens facing the user's eyes when using the HMD device **6-100**. The scene cameras **6-106** can also be used for environment and object reconstruction.

(79) In at least one example, the sensor system **6-102** can include a first depth sensor **6-108** pointed generally forward in the Y-direction. In at least one example, the first depth sensor **6-108** can be used for environment and object reconstruction as well as user hand and body tracking. In at least one example, the sensor system **6-102** can include a second depth sensor **6-110** disposed centrally along the width (e.g., along the X-axis) of the HMD device **6-100**. For example, the second depth sensor **6-110** can be disposed above the central nasal bridge or accommodating features over the nose of the user when donning the HMD **6-100**. In at least one example, the second depth sensor **6-110** can be used for environment and object reconstruction as well as hand and body tracking. In at least one example, the second depth sensor can include a LIDAR sensor.

(80) In at least one example, the sensor system **6-102** can include a depth projector **6-112** facing generally forward to project electromagnetic waves, for example in the form of a predetermined pattern of light dots, out into and within a field of view of the user and/or the scene cameras **6-106** or a field of view including and beyond the field of view of the user and/or scene cameras **6-106**. In at least one example, the depth projector can project electromagnetic waves of light in the form of a dotted light pattern to be reflected off objects and back into the depth sensors noted above, including the depth sensors **6-108**, **6-110**. In at least one example, the depth projector **6-112** can be used for environment and object reconstruction as well as hand and body tracking.

(81) In at least one example, the sensor system **6-102** can include downward facing cameras **6-114** with a field of view pointed generally downward relative to the HMD device **6-100** in the Z-axis. In at least one example, the downward cameras **6-114** can be disposed on left and right sides of the HMD device **6-100** as shown and used for hand and body tracking, headset tracking, and facial avatar detection and creation for display a user avatar on the forward facing display screen of the HMD device **6-100** described elsewhere herein. The downward cameras **6-114**, for example, can be used to capture facial expressions and movements for the face of the user below the HMD device **6-100**, including the cheeks, mouth, and chin.

(82) In at least one example, the sensor system **6-102** can include jaw cameras **6-116**. In at least one example, the jaw cameras **6-116** can be disposed on left and right sides of the HMD device **6-100** as shown and used for hand and body tracking, headset tracking, and facial avatar detection and creation for display a user avatar on the forward facing display screen of the HMD device **6-100** described elsewhere herein. The jaw cameras **6-116**, for example, can be used to capture facial expressions and movements for the face of the user below the HMD device **6-100**, including the user's jaw, cheeks, mouth, and chin. for hand and body tracking, headset tracking, and facial avatar

(83) In at least one example, the sensor system **6-102** can include side cameras **6-118**. The side cameras **6-118** can be oriented to capture side views left and right in the X-axis or direction relative to the HMD device **6-100**. In at least one example, the side cameras **6-118** can be used for hand and body tracking, headset tracking, and facial avatar detection and re-creation.

(84) In at least one example, the sensor system **6-102** can include a plurality of eye tracking and gaze tracking sensors for determining an identity, status, and gaze direction of a user's eyes during and/or before use. In at least one example, the eye/gaze tracking sensors can include nasal eye cameras **6-120** disposed on either side of the user's nose and adjacent the user's nose when donning the HMD device **6-100**. The eye/gaze sensors can also include bottom eye cameras **6-122** disposed below respective user eyes for capturing images of the eyes for facial avatar detection and creation, gaze tracking, and iris identification functions.

(85) In at least one example, the sensor system **6-102** can include infrared illuminators **6-124** pointed outward from the HMD device **6-100** to illuminate the external environment and any object therein with IR light for IR detection with one or more IR sensors of the sensor system **6-102**. In at least one example, the sensor system **6-102** can include a flicker sensor **6-126** and an ambient light sensor **6-128**. In at least one example, the flicker sensor **6-126** can detect overhead light refresh rates to avoid display flicker. In one example, the infrared illuminators **6-124** can include light emitting diodes and can be used especially for low light environments for illuminating user hands and other objects in low light for detection by infrared sensors of the sensor system **6-102**.

(86) In at least one example, multiple sensors, including the scene cameras **6-106**, the downward cameras **6-114**, the jaw cameras **6-116**, the side cameras **6-118**, the depth projector **6-112**, and the depth sensors **6-108**, **6-110** can be used in combination with an electrically coupled controller to combine depth data with camera data for hand tracking and for size determination for better hand tracking and object recognition and tracking functions of the HMD device **6-100**. In at least one example, the downward cameras **6-114**, jaw cameras **6-116**, and side cameras **6-118** described above and shown in FIG. **1I** can be wide angle cameras operable in the visible and infrared spectrums. In at least one example, these cameras **6-114**, **6-116**, **6-118** can operate only in black and white light detection to simplify image processing and gain sensitivity.

(87) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. **1I** can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. **1J-1L** and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. **1J-1L** can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. **1I**.

(88) FIG. 1J illustrates a lower perspective view of an example of an HMD **6-200** including a cover or shroud **6-204** secured to a frame **6-230**. In at least one example, the sensors **6-203** of the sensor system **6-202** can be disposed around a perimeter of the HMD **6-200** such that the sensors **6-203** are outwardly disposed around a perimeter of a display region or area **6-232** so as not to obstruct a view of the displayed light. In at least one example, the sensors can be disposed behind the shroud **6-204** and aligned with transparent portions of the shroud allowing sensors and projectors to allow light back and forth through the shroud **6-204**. In at least one example, opaque ink or other opaque material or films/layers can be disposed on the shroud **6-204** around the display area **6-232** to hide components of the HMD **6-200** outside the display area **6-232** other than the transparent portions defined by the opaque portions, through which the sensors and projectors send and receive light and electromagnetic signals during operation. In at least one example, the shroud **6-204** allows light to pass therethrough from the display (e.g., within the display region **6-232**) but not radially outward from the display region around the perimeter of the display and shroud **6-204**.

(89) In some examples, the shroud **6-204** includes a transparent portion **6-205** and an opaque portion **6-207**, as described above and elsewhere herein. In at least one example, the opaque portion **6-207** of the shroud **6-204** can define one or more transparent regions **6-209** through which the sensors **6-203** of the sensor system **6-202** can send and receive signals. In the illustrated example, the sensors **6-203** of the sensor system **6-202** sending and receiving signals through the shroud **6-204**, or more specifically through the transparent regions **6-209** of the (or defined by) the opaque portion **6-207** of the shroud **6-204** can include the same or similar sensors as those shown in the example of FIG. 1I, for example depth sensors **6-108** and **6-110**, depth projector **6-112**, first and second scene cameras **6-106**, first and second downward cameras **6-114**, first and second side cameras **6-118**, and first and second infrared illuminators **6-124**. These sensors are also shown in the examples of FIGS. 1K and 1L. Other sensors, sensor types, number of sensors, and relative positions thereof can be included in one or more other examples of HMDs.

(90) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1J can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. 1I and 1K-1L and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. 1I and 1K-1L can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1J.

(91) FIG. 1K illustrates a front view of a portion of an example of an HMD device **6-300** including a display **6-334**, brackets **6-336**, **6-338**, and frame or housing **6-330**. The example shown in FIG. 1K does not include a front cover or shroud in order to illustrate the brackets **6-336**, **6-338**. For example, the shroud **6-204** shown in FIG. 1J includes the opaque portion **6-207** that would visually cover/block a view of anything outside (e.g., radially/peripherally outside) the display/display region **6-334**, including the sensors **6-303** and bracket **6-338**.

(92) In at least one example, the various sensors of the sensor system **6-302** are coupled to the brackets **6-336**, **6-338**. In at least one example, the scene cameras **6-306** include tight tolerances of angles relative to one another. For example, the tolerance of mounting angles between the two scene cameras **6-306** can be 0.5 degrees or less, for example 0.3 degrees or less. In order to achieve and maintain such a tight tolerance, in one example, the scene cameras **6-306** can be mounted to the bracket **6-338** and not the shroud. The bracket can include cantilevered arms on which the scene cameras **6-306** and other sensors of the sensor system **6-302** can be mounted to remain undeformed in position and orientation in the case of a drop event by a user resulting in any deformation of the other bracket **6-226**, housing **6-330**, and/or shroud.

(93) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1K can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. 1I-1J and 1L and described

herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. 1I-1J and 1L can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1K.

(94) FIG. 1L illustrates a bottom view of an example of an HMD **6-400** including a front display/cover assembly **6-404** and a sensor system **6-402**. The sensor system **6-402** can be similar to other sensor systems described above and elsewhere herein, including in reference to FIGS. 1I-1K. In at least one example, the jaw cameras **6-416** can be facing downward to capture images of the user's lower facial features. In one example, the jaw cameras **6-416** can be coupled directly to the frame or housing **6-430** or one or more internal brackets directly coupled to the frame or housing **6-430** shown. The frame or housing **6-430** can include one or more apertures/openings **6-415** through which the jaw cameras **6-416** can send and receive signals.

(95) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1L can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIGS. 1I-1K and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIGS. 1I-1K can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1L.

(96) FIG. 1M illustrates a rear perspective view of an inter-pupillary distance (IPD) adjustment system **11.1.1-102** including first and second optical modules **11.1.1-104a-b** slidably engaging/coupled to respective guide-rods **11.1.1-108a-b** and motors **11.1.1-110a-b** of left and right adjustment subsystems **11.1.1-106a-b**. The IPD adjustment system **11.1.1-102** can be coupled to a bracket **11.1.1-112** and include a button **11.1.1-114** in electrical communication with the motors **11.1.1-110a-b**. In at least one example, the button **11.1.1-114** can electrically communicate with the first and second motors **11.1.1-110a-b** via a processor or other circuitry components to cause the first and second motors **11.1.1-110a-b** to activate and cause the first and second optical modules **11.1.1-104a-b**, respectively, to change position relative to one another.

(97) In at least one example, the first and second optical modules **11.1.1-104a-b** can include respective display screens configured to project light toward the user's eyes when donning the HMD **11.1.1-100**. In at least one example, the user can manipulate (e.g., depress and/or rotate) the button **11.1.1-114** to activate a positional adjustment of the optical modules **11.1.1-104a-b** to match the inter-pupillary distance of the user's eyes. The optical modules **11.1.1-104a-b** can also include one or more cameras or other sensors/sensor systems for imaging and measuring the IPD of the user such that the optical modules **11.1.1-104a-b** can be adjusted to match the IPD.

(98) In one example, the user can manipulate the button **11.1.1-114** to cause an automatic positional adjustment of the first and second optical modules **11.1.1-104a-b**. In one example, the user can manipulate the button **11.1.1-114** to cause a manual adjustment such that the optical modules **11.1.1-104a-b** move further or closer away, for example when the user rotates the button **11.1.1-114** one way or the other, until the user visually matches her/his own IPD. In one example, the manual adjustment is electronically communicated via one or more circuits and power for the movements of the optical modules **11.1.1-104a-b** via the motors **11.1.1-110a-b** is provided by an electrical power source. In one example, the adjustment and movement of the optical modules **11.1.1-104a-b** via a manipulation of the button **11.1.1-114** is mechanically actuated via the movement of the button **11.1.1-114**.

(99) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1M can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in any other figures shown and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to any other figure

shown and described herein, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1M.

(100) FIG. 1N illustrates a front perspective view of a portion of an HMD **11.1.2-100**, including an outer structural frame **11.1.2-102** and an inner or intermediate structural frame **11.1.2-104** defining first and second apertures **11.1.2-106a**, **11.1.2-106b**. The apertures **11.1.2-106a-b** are shown in dotted lines in FIG. 1N because a view of the apertures **11.1.2-106a-b** can be blocked by one or more other components of the HMD **11.1.2-100** coupled to the inner frame **11.1.2-104** and/or the outer frame **11.1.2-102**, as shown. In at least one example, the HMD **11.1.2-100** can include a first mounting bracket **11.1.2-108** coupled to the inner frame **11.1.2-104**. In at least one example, the mounting bracket **11.1.2-108** is coupled to the inner frame **11.1.2-104** between the first and second apertures **11.1.2-106a-b**.

(101) The mounting bracket **11.1.2-108** can include a middle or central portion **11.1.2-109** coupled to the inner frame **11.1.2-104**. In some examples, the middle or central portion **11.1.2-109** may not be the geometric middle or center of the bracket **11.1.2-108**. Rather, the middle/central portion **11.1.2-109** can be disposed between first and second cantilevered extension arms extending away from the middle portion **11.1.2-109**. In at least one example, the mounting bracket **108** includes a first cantilever arm **11.1.2-112** and a second cantilever arm **11.1.2-114** extending away from the middle portion **11.1.2-109** of the mount bracket **11.1.2-108** coupled to the inner frame **11.1.2-104**.

(102) As shown in FIG. 1N, the outer frame **11.1.2-102** can define a curved geometry on a lower side thereof to accommodate a user's nose when the user dons the HMD **11.1.2-100**. The curved geometry can be referred to as a nose bridge **11.1.2-111** and be centrally located on a lower side of the HMD **11.1.2-100** as shown. In at least one example, the mounting bracket **11.1.2-108** can be connected to the inner frame **11.1.2-104** between the apertures **11.1.2-106a-b** such that the cantilevered arms **11.1.2-112**, **11.1.2-114** extend downward and laterally outward away from the middle portion **11.1.2-109** to compliment the nose bridge **11.1.2-111** geometry of the outer frame **11.1.2-102**. In this way, the mounting bracket **11.1.2-108** is configured to accommodate the user's nose as noted above. The nose bridge **11.1.2-111** geometry accommodates the nose in that the nose bridge **11.1.2-111** provides a curvature that curves with, above, over, and around the user's nose for comfort and fit.

(103) The first cantilever arm **11.1.2-112** can extend away from the middle portion **11.1.2-109** of the mounting bracket **11.1.2-108** in a first direction and the second cantilever arm **11.1.2-114** can extend away from the middle portion **11.1.2-109** of the mounting bracket **11.1.2-10** in a second direction opposite the first direction. The first and second cantilever arms **11.1.2-112**, **11.1.2-114** are referred to as “cantilevered” or “cantilever” arms because each arm **11.1.2-112**, **11.1.2-114**, includes a distal free end **11.1.2-116**, **11.1.2-118**, respectively, which are free of affixation from the inner and outer frames **11.1.2-102**, **11.1.2-104**. In this way, the arms **11.1.2-112**, **11.1.2-114** are cantilevered from the middle portion **11.1.2-109**, which can be connected to the inner frame **11.1.2-104**, with distal ends **11.1.2-102**, **11.1.2-104** unattached.

(104) In at least one example, the HMD **11.1.2-100** can include one or more components coupled to the mounting bracket **11.1.2-108**. In one example, the components include a plurality of sensors **11.1.2-110a-f**. Each sensor of the plurality of sensors **11.1.2-110a-f** can include various types of sensors, including cameras, IR sensors, and so forth. In some examples, one or more of the sensors **11.1.2-110a-f** can be used for object recognition in three-dimensional space such that it is important to maintain a precise relative position of two or more of the plurality of sensors **11.1.2-110a-f**. The cantilevered nature of the mounting bracket **11.1.2-108** can protect the sensors **11.1.2-110a-f** from damage and altered positioning in the case of accidental drops by the user. Because the sensors **11.1.2-110a-f** are cantilevered on the arms **11.1.2-112**, **11.1.2-114** of the mounting bracket **11.1.2-108**, stresses and deformations of the inner and/or outer frames **11.1.2-104**, **11.1.2-102** are not transferred to the cantilevered arms **11.1.2-112**, **11.1.2-114** and thus do not affect the relative positioning of the sensors **11.1.2-110a-f** coupled/mounted to the mounting bracket **11.1.2-108**.

(105) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1N can be included, either alone or in any combination, in any of the other examples of devices, features, components, and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described herein can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1N.

(106) FIG. 1O illustrates an example of an optical module **11.3.2-100** for use in an electronic device such as an HMD, including HMD devices described herein. As shown in one or more other examples described herein, the optical module **11.3.2-100** can be one of two optical modules within an HMD, with each optical module aligned to project light toward a user's eye. In this way, a first optical module can project light via a display screen toward a user's first eye and a second optical module of the same device can project light via another display screen toward the user's second eye.

(107) In at least one example, the optical module **11.3.2-100** can include an optical frame or housing **11.3.2-102**, which can also be referred to as a barrel or optical module barrel. The optical module **11.3.2-100** can also include a display **11.3.2-104**, including a display screen or multiple display screens, coupled to the housing **11.3.2-102**. The display **11.3.2-104** can be coupled to the housing **11.3.2-102** such that the display **11.3.2-104** is configured to project light toward the eye of a user when the HMD of which the display module **11.3.2-100** is a part is donned during use. In at least one example, the housing **11.3.2-102** can surround the display **11.3.2-104** and provide connection features for coupling other components of optical modules described herein.

(108) In one example, the optical module **11.3.2-100** can include one or more cameras **11.3.2-106** coupled to the housing **11.3.2-102**. The camera **11.3.2-106** can be positioned relative to the display **11.3.2-104** and housing **11.3.2-102** such that the camera **11.3.2-106** is configured to capture one or more images of the user's eye during use. In at least one example, the optical module **11.3.2-100** can also include a light strip **11.3.2-108** surrounding the display **11.3.2-104**. In one example, the light strip **11.3.2-108** is disposed between the display **11.3.2-104** and the camera **11.3.2-106**. The light strip **11.3.2-108** can include a plurality of lights **11.3.2-110**. The plurality of lights can include one or more light emitting diodes (LEDs) or other lights configured to project light toward the user's eye when the HMD is donned. The individual lights **11.3.2-110** of the light strip **11.3.2-108** can be spaced about the strip **11.3.2-108** and thus spaced about the display **11.3.2-104** uniformly or non-uniformly at various locations on the strip **11.3.2-108** and around the display **11.3.2-104**.

(109) In at least one example, the housing **11.3.2-102** defines a viewing opening **11.3.2-101** through which the user can view the display **11.3.2-104** when the HMD device is donned. In at least one example, the LEDs are configured and arranged to emit light through the viewing opening **11.3.2-101** and onto the user's eye. In one example, the camera **11.3.2-106** is configured to capture one or more images of the user's eye through the viewing opening **11.3.2-101**.

(110) As noted above, each of the components and features of the optical module **11.3.2-100** shown in FIG. 1O can be replicated in another (e.g., second) optical module disposed with the HMD to interact (e.g., project light and capture images) of another eye of the user.

(111) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1O can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts shown in FIG. 1P or otherwise described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described with reference to FIG. 1P or otherwise described herein can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1O.

(112) FIG. 1P illustrates a cross-sectional view of an example of an optical module **11.3.2-200** including a housing **11.3.2-202**, display assembly **11.3.2-204** coupled to the housing **11.3.2-202**, and a lens **11.3.2-216** coupled to the housing **11.3.2-202**. In at least one example, the housing

11.3.2-202 defines a first aperture or channel **11.3.2-212** and a second aperture or channel **11.3.2-214**. The channels **11.3.2-212**, **11.3.2-214** can be configured to slidably engage respective rails or guide rods of an HMD device to allow the optical module **11.3.2-200** to adjust in position relative to the user's eyes for match the user's interpupillary distance (IPD). The housing **11.3.2-202** can slidably engage the guide rods to secure the optical module **11.3.2-200** in place within the HMD. (113) In at least one example, the optical module **11.3.2-200** can also include a lens **11.3.2-216** coupled to the housing **11.3.2-202** and disposed between the display assembly **11.3.2-204** and the user's eyes when the HMD is donned. The lens **11.3.2-216** can be configured to direct light from the display assembly **11.3.2-204** to the user's eye. In at least one example, the lens **11.3.2-216** can be a part of a lens assembly including a corrective lens removably attached to the optical module **11.3.2-200**. In at least one example, the lens **11.3.2-216** is disposed over the light strip **11.3.2-208** and the one or more eye-tracking cameras **11.3.2-206** such that the camera **11.3.2-206** is configured to capture images of the user's eye through the lens **11.3.2-216** and the light strip **11.3.2-208** includes lights configured to project light through the lens **11.3.2-216** to the users' eye during use. (114) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIG. 1P can be included, either alone or in any combination, in any of the other examples of devices, features, components, and parts and described herein. Likewise, any of the features, components, and/or parts, including the arrangements and configurations thereof shown and described herein can be included, either alone or in any combination, in the example of the devices, features, components, and parts shown in FIG. 1P.

(115) FIG. 2 is a block diagram of an example of the controller **110** in accordance with some embodiments. While certain specific features are illustrated, those skilled in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the embodiments disclosed herein. To that end, as a non-limiting example, in some embodiments, the controller **110** includes one or more processing units **202** (e.g., microprocessors, application-specific integrated-circuits (ASICs), field-programmable gate arrays (FPGAs), graphics processing units (GPUs), central processing units (CPUs), processing cores, and/or the like), one or more input/output (I/O) devices **206**, one or more communication interfaces **208** (e.g., universal serial bus (USB), FIREWIRE, THUNDERBOLT, IEEE 802.3x, IEEE 802.11x, IEEE 802.16x, global system for mobile communications (GSM), code division multiple access (CDMA), time division multiple access (TDMA), global positioning system (GPS), infrared (IR), BLUETOOTH, ZIGBEE, and/or the like type interface), one or more programming (e.g., I/O) interfaces **210**, a memory **220**, and one or more communication buses **204** for interconnecting these and various other components.

(116) In some embodiments, the one or more communication buses **204** include circuitry that interconnects and controls communications between system components. In some embodiments, the one or more I/O devices **206** include at least one of a keyboard, a mouse, a touchpad, a joystick, one or more microphones, one or more speakers, one or more image sensors, one or more displays, and/or the like.

(117) The memory **220** includes high-speed random-access memory, such as dynamic random-access memory (DRAM), static random-access memory (SRAM), double-data-rate random-access memory (DDR RAM), or other random-access solid-state memory devices. In some embodiments, the memory **220** includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid-state storage devices. The memory **220** optionally includes one or more storage devices remotely located from the one or more processing units **202**. The memory **220** comprises a non-transitory computer readable storage medium. In some embodiments, the memory **220** or the non-transitory computer readable storage medium of the memory **220** stores the following programs, modules and data structures, or a subset thereof including an optional operating system **230** and a XR experience module **240**.

(118) The operating system **230** includes instructions for handling various basic system services and for performing hardware dependent tasks. In some embodiments, the XR experience module **240** is configured to manage and coordinate one or more XR experiences for one or more users (e.g., a single XR experience for one or more users, or multiple XR experiences for respective groups of one or more users). To that end, in various embodiments, the XR experience module **240** includes a data obtaining unit **241**, a tracking unit **242**, a coordination unit **246**, and a data transmitting unit **248**.

(119) In some embodiments, the data obtaining unit **241** is configured to obtain data (e.g., presentation data, interaction data, sensor data, location data, etc.) from at least the display generation component **120** of FIG. 1A, and optionally one or more of the input devices **125**, output devices **155**, sensors **190**, and/or peripheral devices **195**. To that end, in various embodiments, the data obtaining unit **241** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(120) In some embodiments, the tracking unit **242** is configured to map the scene **105** and to track the position/location of at least the display generation component **120** with respect to the scene **105** of FIG. 1A, and optionally, to one or more of the input devices **125**, output devices **155**, sensors **190**, and/or peripheral devices **195**. To that end, in various embodiments, the tracking unit **242** includes instructions and/or logic therefor, and heuristics and metadata therefor. In some embodiments, the tracking unit **242** includes hand tracking unit **244** and/or eye tracking unit **243**. In some embodiments, the hand tracking unit **244** is configured to track the position/location of one or more portions of the user's hands, and/or motions of one or more portions of the user's hands with respect to the scene **105** of FIG. 1A, relative to the display generation component **120**, and/or relative to a coordinate system defined relative to the user's hand. The hand tracking unit **244** is described in greater detail below with respect to FIG. 4. In some embodiments, the eye tracking unit **243** is configured to track the position and movement of the user's gaze (or more broadly, the user's eyes, face, or head) with respect to the scene **105** (e.g., with respect to the physical environment and/or to the user (e.g., the user's hand)) or with respect to the XR content displayed via the display generation component **120**. The eye tracking unit **243** is described in greater detail below with respect to FIG. 5.

(121) In some embodiments, the coordination unit **246** is configured to manage and coordinate the XR experience presented to the user by the display generation component **120**, and optionally, by one or more of the output devices **155** and/or peripheral devices **195**. To that end, in various embodiments, the coordination unit **246** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(122) In some embodiments, the data transmitting unit **248** is configured to transmit data (e.g., presentation data, location data, etc.) to at least the display generation component **120**, and optionally, to one or more of the input devices **125**, output devices **155**, sensors **190**, and/or peripheral devices **195**. To that end, in various embodiments, the data transmitting unit **248** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(123) Although the data obtaining unit **241**, the tracking unit **242** (e.g., including the eye tracking unit **243** and the hand tracking unit **244**), the coordination unit **246**, and the data transmitting unit **248** are shown as residing on a single device (e.g., the controller **110**), it should be understood that in other embodiments, any combination of the data obtaining unit **241**, the tracking unit **242** (e.g., including the eye tracking unit **243** and the hand tracking unit **244**), the coordination unit **246**, and the data transmitting unit **248** may be located in separate computing devices.

(124) Moreover, FIG. 2 is intended more as functional description of the various features that may be present in a particular implementation as opposed to a structural schematic of the embodiments described herein. As recognized by those of ordinary skill in the art, items shown separately could be combined and some items could be separated. For example, some functional modules shown separately in FIG. 2 could be implemented in a single module and the various functions of single

functional blocks could be implemented by one or more functional blocks in various embodiments. The actual number of modules and the division of particular functions and how features are allocated among them will vary from one implementation to another and, in some embodiments, depends in part on the particular combination of hardware, software, and/or firmware chosen for a particular implementation.

(125) FIG. 3 is a block diagram of an example of the display generation component **120** in accordance with some embodiments. While certain specific features are illustrated, those skilled in the art will appreciate from the present disclosure that various other features have not been illustrated for the sake of brevity, and so as not to obscure more pertinent aspects of the embodiments disclosed herein. To that end, as a non-limiting example, in some embodiments the display generation component **120** (e.g., HMD) includes one or more processing units **302** (e.g., microprocessors, ASICs, FPGAs, GPUs, CPUs, processing cores, and/or the like), one or more input/output (I/O) devices and sensors **306**, one or more communication interfaces **308** (e.g., USB, FIREWIRE, THUNDERBOLT, IEEE 802.3x, IEEE 802.11x, IEEE 802.16x, GSM, CDMA, TDMA, GPS, IR, BLUETOOTH, ZIGBEE, and/or the like type interface), one or more programming (e.g., I/O) interfaces **310**, one or more XR displays **312**, one or more optional interior- and/or exterior-facing image sensors **314**, a memory **320**, and one or more communication buses **304** for interconnecting these and various other components.

(126) In some embodiments, the one or more communication buses **304** include circuitry that interconnects and controls communications between system components. In some embodiments, the one or more I/O devices and sensors **306** include at least one of an inertial measurement unit (IMU), an accelerometer, a gyroscope, a thermometer, one or more physiological sensors (e.g., blood pressure monitor, heart rate monitor, blood oxygen sensor, blood glucose sensor, etc.), one or more microphones, one or more speakers, a haptics engine, one or more depth sensors (e.g., a structured light, a time-of-flight, or the like), and/or the like.

(127) In some embodiments, the one or more XR displays **312** are configured to provide the XR experience to the user. In some embodiments, the one or more XR displays **312** correspond to holographic, digital light processing (DLP), liquid-crystal display (LCD), liquid-crystal on silicon (LCoS), organic light-emitting field-effect transitory (OLET), organic light-emitting diode (OLED), surface-conduction electron-emitter display (SED), field-emission display (FED), quantum-dot light-emitting diode (QD-LED), micro-electro-mechanical system (MEMS), and/or the like display types. In some embodiments, the one or more XR displays **312** correspond to diffractive, reflective, polarized, holographic, etc. waveguide displays. For example, the display generation component **120** (e.g., HMD) includes a single XR display. In another example, the display generation component **120** includes a XR display for each eye of the user. In some embodiments, the one or more XR displays **312** are capable of presenting MR and VR content. In some embodiments, the one or more XR displays **312** are capable of presenting MR or VR content.

(128) In some embodiments, the one or more image sensors **314** are configured to obtain image data that corresponds to at least a portion of the face of the user that includes the eyes of the user (and may be referred to as an eye-tracking camera). In some embodiments, the one or more image sensors **314** are configured to obtain image data that corresponds to at least a portion of the user's hand(s) and optionally arm(s) of the user (and may be referred to as a hand-tracking camera). In some embodiments, the one or more image sensors **314** are configured to be forward-facing so as to obtain image data that corresponds to the scene as would be viewed by the user if the display generation component **120** (e.g., HMD) was not present (and may be referred to as a scene camera). The one or more optional image sensors **314** can include one or more RGB cameras (e.g., with a complimentary metal-oxide-semiconductor (CMOS) image sensor or a charge-coupled device (CCD) image sensor), one or more infrared (IR) cameras, one or more event-based cameras, and/or the like.

(129) The memory **320** includes high-speed random-access memory, such as DRAM, SRAM, DDR

RAM, or other random-access solid-state memory devices. In some embodiments, the memory **320** includes non-volatile memory, such as one or more magnetic disk storage devices, optical disk storage devices, flash memory devices, or other non-volatile solid-state storage devices. The memory **320** optionally includes one or more storage devices remotely located from the one or more processing units **302**. The memory **320** comprises a non-transitory computer readable storage medium. In some embodiments, the memory **320** or the non-transitory computer readable storage medium of the memory **320** stores the following programs, modules and data structures, or a subset thereof including an optional operating system **330** and a XR presentation module **340**.

(130) The operating system **330** includes instructions for handling various basic system services and for performing hardware dependent tasks. In some embodiments, the XR presentation module **340** is configured to present XR content to the user via the one or more XR displays **312**. To that end, in various embodiments, the XR presentation module **340** includes a data obtaining unit **342**, a XR presenting unit **344**, a XR map generating unit **346**, and a data transmitting unit **348**.

(131) In some embodiments, the data obtaining unit **342** is configured to obtain data (e.g., presentation data, interaction data, sensor data, location data, etc.) from at least the controller **110** of FIG. **1A**. To that end, in various embodiments, the data obtaining unit **342** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(132) In some embodiments, the XR presenting unit **344** is configured to present XR content via the one or more XR displays **312**. To that end, in various embodiments, the XR presenting unit **344** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(133) In some embodiments, the XR map generating unit **346** is configured to generate a XR map (e.g., a 3D map of the mixed reality scene or a map of the physical environment into which computer-generated objects can be placed to generate the extended reality) based on media content data. To that end, in various embodiments, the XR map generating unit **346** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(134) In some embodiments, the data transmitting unit **348** is configured to transmit data (e.g., presentation data, location data, etc.) to at least the controller **110**, and optionally one or more of the input devices **125**, output devices **155**, sensors **190**, and/or peripheral devices **195**. To that end, in various embodiments, the data transmitting unit **348** includes instructions and/or logic therefor, and heuristics and metadata therefor.

(135) Although the data obtaining unit **342**, the XR presenting unit **344**, the XR map generating unit **346**, and the data transmitting unit **348** are shown as residing on a single device (e.g., the display generation component **120** of FIG. **1A**), it should be understood that in other embodiments, any combination of the data obtaining unit **342**, the XR presenting unit **344**, the XR map generating unit **346**, and the data transmitting unit **348** may be located in separate computing devices.

(136) Moreover, FIG. **3** is intended more as a functional description of the various features that could be present in a particular implementation as opposed to a structural schematic of the embodiments described herein. As recognized by those of ordinary skill in the art, items shown separately could be combined and some items could be separated. For example, some functional modules shown separately in FIG. **3** could be implemented in a single module and the various functions of single functional blocks could be implemented by one or more functional blocks in various embodiments. The actual number of modules and the division of particular functions and how features are allocated among them will vary from one implementation to another and, in some embodiments, depends in part on the particular combination of hardware, software, and/or firmware chosen for a particular implementation.

(137) FIG. **4** is a schematic, pictorial illustration of an example embodiment of the hand tracking device **140**. In some embodiments, hand tracking device **140** (FIG. **1A**) is controlled by hand tracking unit **244** (FIG. **2**) to track the position/location of one or more portions of the user's hands, and/or motions of one or more portions of the user's hands with respect to the scene **105** of FIG. **1A** (e.g., with respect to a portion of the physical environment surrounding the user, with respect to the

display generation component **120**, or with respect to a portion of the user (e.g., the user's face, eyes, or head), and/or relative to a coordinate system defined relative to the user's hand). In some embodiments, the hand tracking device **140** is part of the display generation component **120** (e.g., embedded in or attached to a head-mounted device). In some embodiments, the hand tracking device **140** is separate from the display generation component **120** (e.g., located in separate housings or attached to separate physical support structures).

(138) In some embodiments, the hand tracking device **140** includes image sensors **404** (e.g., one or more IR cameras, 3D cameras, depth cameras, and/or color cameras, etc.) that capture three-dimensional scene information that includes at least a hand **406** of a human user. The image sensors **404** capture the hand images with sufficient resolution to enable the fingers and their respective positions to be distinguished. The image sensors **404** typically capture images of other parts of the user's body, as well, or possibly all of the body, and may have either zoom capabilities or a dedicated sensor with enhanced magnification to capture images of the hand with the desired resolution. In some embodiments, the image sensors **404** also capture 2D color video images of the hand **406** and other elements of the scene. In some embodiments, the image sensors **404** are used in conjunction with other image sensors to capture the physical environment of the scene **105**, or serve as the image sensors that capture the physical environments of the scene **105**. In some embodiments, the image sensors **404** are positioned relative to the user or the user's environment in a way that a field of view of the image sensors or a portion thereof is used to define an interaction space in which hand movement captured by the image sensors are treated as inputs to the controller **110**.

(139) In some embodiments, the image sensors **404** output a sequence of frames containing 3D map data (and possibly color image data, as well) to the controller **110**, which extracts high-level information from the map data. This high-level information is typically provided via an Application Program Interface (API) to an application running on the controller, which drives the display generation component **120** accordingly. For example, the user may interact with software running on the controller **110** by moving his hand **406** and changing his hand posture.

(140) In some embodiments, the image sensors **404** project a pattern of spots onto a scene containing the hand **406** and capture an image of the projected pattern. In some embodiments, the controller **110** computes the 3D coordinates of points in the scene (including points on the surface of the user's hand) by triangulation, based on transverse shifts of the spots in the pattern. This approach is advantageous in that it does not require the user to hold or wear any sort of beacon, sensor, or other marker. It gives the depth coordinates of points in the scene relative to a predetermined reference plane, at a certain distance from the image sensors **404**. In the present disclosure, the image sensors **404** are assumed to define an orthogonal set of x, y, z axes, so that depth coordinates of points in the scene correspond to z components measured by the image sensors. Alternatively, the image sensors **404** (e.g., a hand tracking device) may use other methods of 3D mapping, such as stereoscopic imaging or time-of-flight measurements, based on single or multiple cameras or other types of sensors.

(141) In some embodiments, the hand tracking device **140** captures and processes a temporal sequence of depth maps containing the user's hand, while the user moves his hand (e.g., whole hand or one or more fingers). Software running on a processor in the image sensors **404** and/or the controller **110** processes the 3D map data to extract patch descriptors of the hand in these depth maps. The software matches these descriptors to patch descriptors stored in a database **408**, based on a prior learning process, in order to estimate the pose of the hand in each frame. The pose typically includes 3D locations of the user's hand joints and finger tips.

(142) The software may also analyze the trajectory of the hands and/or fingers over multiple frames in the sequence in order to identify gestures. The pose estimation functions described herein may be interleaved with motion tracking functions, so that patch-based pose estimation is performed only once in every two (or more) frames, while tracking is used to find changes in the pose that

occur over the remaining frames. The pose, motion and gesture information are provided via the above-mentioned API to an application program running on the controller **110**. This program may, for example, move and modify images presented on the display generation component **120**, or perform other functions, in response to the pose and/or gesture information.

(143) In some embodiments, a gesture includes an air gesture. An air gesture is a gesture that is detected without the user touching (or independently of) an input element that is part of a device (e.g., computer system **101**, one or more input device **125**, and/or hand tracking device **140**) and is based on detected motion of a portion (e.g., the head, one or more arms, one or more hands, one or more fingers, and/or one or more legs) of the user's body through the air including motion of the user's body relative to an absolute reference (e.g., an angle of the user's arm relative to the ground or a distance of the user's hand relative to the ground), relative to another portion of the user's body (e.g., movement of a hand of the user relative to a shoulder of the user, movement of one hand of the user relative to another hand of the user, and/or movement of a finger of the user relative to another finger or portion of a hand of the user), and/or absolute motion of a portion of the user's body (e.g., a tap gesture that includes movement of a hand in a predetermined pose by a predetermined amount and/or speed, or a shake gesture that includes a predetermined speed or amount of rotation of a portion of the user's body).

(144) In some embodiments, input gestures used in the various examples and embodiments described herein include air gestures performed by movement of the user's finger(s) relative to other finger(s) (or part(s) of the user's hand) for interacting with an XR environment (e.g., a virtual or mixed-reality environment), in accordance with some embodiments. In some embodiments, an air gesture is a gesture that is detected without the user touching an input element that is part of the device (or independently of an input element that is a part of the device) and is based on detected motion of a portion of the user's body through the air including motion of the user's body relative to an absolute reference (e.g., an angle of the user's arm relative to the ground or a distance of the user's hand relative to the ground), relative to another portion of the user's body (e.g., movement of a hand of the user relative to a shoulder of the user, movement of one hand of the user relative to another hand of the user, and/or movement of a finger of the user relative to another finger or portion of a hand of the user), and/or absolute motion of a portion of the user's body (e.g., a tap gesture that includes movement of a hand in a predetermined pose by a predetermined amount and/or speed, or a shake gesture that includes a predetermined speed or amount of rotation of a portion of the user's body).

(145) In some embodiments in which the input gesture is an air gesture (e.g., in the absence of physical contact with an input device that provides the computer system with information about which user interface element is the target of the user input, such as contact with a user interface element displayed on a touchscreen, or contact with a mouse or trackpad to move a cursor to the user interface element), the gesture takes into account the user's attention (e.g., gaze) to determine the target of the user input (e.g., for direct inputs, as described below). Thus, in implementations involving air gestures, the input gesture is, for example, detected attention (e.g., gaze) toward the user interface element in combination (e.g., concurrent) with movement of a user's finger(s) and/or hands to perform a pinch and/or tap input, as described in more detail below.

(146) In some embodiments, input gestures that are directed to a user interface object are performed directly or indirectly with reference to a user interface object. For example, a user input is performed directly on the user interface object in accordance with performing the input gesture with the user's hand at a position that corresponds to the position of the user interface object in the three-dimensional environment (e.g., as determined based on a current viewpoint of the user). In some embodiments, the input gesture is performed indirectly on the user interface object in accordance with the user performing the input gesture while a position of the user's hand is not at the position that corresponds to the position of the user interface object in the three-dimensional environment while detecting the user's attention (e.g., gaze) on the user interface object. For

example, for direct input gesture, the user is enabled to direct the user's input to the user interface object by initiating the gesture at, or near, a position corresponding to the displayed position of the user interface object (e.g., within 0.5 cm, 1 cm, 5 cm, or a distance between 0-5 cm, as measured from an outer edge of the option or a center portion of the option). For an indirect input gesture, the user is enabled to direct the user's input to the user interface object by paying attention to the user interface object (e.g., by gazing at the user interface object) and, while paying attention to the option, the user initiates the input gesture (e.g., at any position that is detectable by the computer system) (e.g., at a position that does not correspond to the displayed position of the user interface object).

(147) In some embodiments, input gestures (e.g., air gestures) used in the various examples and embodiments described herein include pinch inputs and tap inputs, for interacting with a virtual or mixed-reality environment, in accordance with some embodiments. For example, the pinch inputs and tap inputs described below are performed as air gestures.

(148) In some embodiments, a pinch input is part of an air gesture that includes one or more of: a pinch gesture, a long pinch gesture, a pinch and drag gesture, or a double pinch gesture. For example, a pinch gesture that is an air gesture includes movement of two or more fingers of a hand to make contact with one another, that is, optionally, followed by an immediate (e.g., within 0-1 seconds) break in contact from each other. A long pinch gesture that is an air gesture includes movement of two or more fingers of a hand to make contact with one another for at least a threshold amount of time (e.g., at least 1 second), before detecting a break in contact with one another. For example, a long pinch gesture includes the user holding a pinch gesture (e.g., with the two or more fingers making contact), and the long pinch gesture continues until a break in contact between the two or more fingers is detected. In some embodiments, a double pinch gesture that is an air gesture comprises two (e.g., or more) pinch inputs (e.g., performed by the same hand) detected in immediate (e.g., within a predefined time period) succession of each other. For example, the user performs a first pinch input (e.g., a pinch input or a long pinch input), releases the first pinch input (e.g., breaks contact between the two or more fingers), and performs a second pinch input within a predefined time period (e.g., within 1 second or within 2 seconds) after releasing the first pinch input.

(149) In some embodiments, a pinch and drag gesture that is an air gesture includes a pinch gesture (e.g., a pinch gesture or a long pinch gesture) performed in conjunction with (e.g., followed by) a drag input that changes a position of the user's hand from a first position (e.g., a start position of the drag) to a second position (e.g., an end position of the drag). In some embodiments, the user maintains the pinch gesture while performing the drag input, and releases the pinch gesture (e.g., opens their two or more fingers) to end the drag gesture (e.g., at the second position). In some embodiments, the pinch input and the drag input are performed by the same hand (e.g., the user pinches two or more fingers to make contact with one another and moves the same hand to the second position in the air with the drag gesture). In some embodiments, the pinch input is performed by a first hand of the user and the drag input is performed by the second hand of the user (e.g., the user's second hand moves from the first position to the second position in the air while the user continues the pinch input with the user's first hand). In some embodiments, an input gesture that is an air gesture includes inputs (e.g., pinch and/or tap inputs) performed using both of the user's two hands. For example, the input gesture includes two (e.g., or more) pinch inputs performed in conjunction with (e.g., concurrently with, or within a predefined time period of) each other. For example, a first pinch gesture performed using a first hand of the user (e.g., a pinch input, a long pinch input, or a pinch and drag input), and, in conjunction with performing the pinch input using the first hand, performing a second pinch input using the other hand (e.g., the second hand of the user's two hands). In some embodiments, movement between the user's two hands (e.g., to increase and/or decrease a distance or relative orientation between the user's two hands).

(150) In some embodiments, a tap input (e.g., directed to a user interface element) performed as an

air gesture includes movement of a user's finger(s) toward the user interface element, movement of the user's hand toward the user interface element optionally with the user's finger(s) extended toward the user interface element, a downward motion of a user's finger (e.g., mimicking a mouse click motion or a tap on a touchscreen), or other predefined movement of the user's hand. In some embodiments a tap input that is performed as an air gesture is detected based on movement characteristics of the finger or hand performing the tap gesture movement of a finger or hand away from the viewpoint of the user and/or toward an object that is the target of the tap input followed by an end of the movement. In some embodiments the end of the movement is detected based on a change in movement characteristics of the finger or hand performing the tap gesture (e.g., an end of movement away from the viewpoint of the user and/or toward the object that is the target of the tap input, a reversal of direction of movement of the finger or hand, and/or a reversal of a direction of acceleration of movement of the finger or hand).

(151) In some embodiments, attention of a user is determined to be directed to a portion of the three-dimensional environment based on detection of gaze directed to the portion of the three-dimensional environment (optionally, without requiring other conditions). In some embodiments, attention of a user is determined to be directed to a portion of the three-dimensional environment based on detection of gaze directed to the portion of the three-dimensional environment with one or more additional conditions such as requiring that gaze is directed to the portion of the three-dimensional environment for at least a threshold duration (e.g., a dwell duration) and/or requiring that the gaze is directed to the portion of the three-dimensional environment while the viewpoint of the user is within a distance threshold from the portion of the three-dimensional environment in order for the device to determine that attention of the user is directed to the portion of the three-dimensional environment, where if one of the additional conditions is not met, the device determines that attention is not directed to the portion of the three-dimensional environment toward which gaze is directed (e.g., until the one or more additional conditions are met).

(152) In some embodiments, the detection of a ready state configuration of a user or a portion of a user is detected by the computer system. Detection of a ready state configuration of a hand is used by a computer system as an indication that the user is likely preparing to interact with the computer system using one or more air gesture inputs performed by the hand (e.g., a pinch, tap, pinch and drag, double pinch, long pinch, or other air gesture described herein). For example, the ready state of the hand is determined based on whether the hand has a predetermined hand shape (e.g., a pre-pinch shape with a thumb and one or more fingers extended and spaced apart ready to make a pinch or grab gesture or a pre-tap with one or more fingers extended and palm facing away from the user), based on whether the hand is in a predetermined position relative to a viewpoint of the user (e.g., below the user's head and above the user's waist and extended out from the body by at least 15, 20, 25, 30, or 50 cm), and/or based on whether the hand has moved in a particular manner (e.g., moved toward a region in front of the user above the user's waist and below the user's head or moved away from the user's body or leg). In some embodiments, the ready state is used to determine whether interactive elements of the user interface respond to attention (e.g., gaze) inputs.

(153) In scenarios where inputs are described with reference to air gestures, it should be understood that similar gestures could be detected using a hardware input device that is attached to or held by one or more hands of a user, where the position of the hardware input device in space can be tracked using optical tracking, one or more accelerometers, one or more gyroscopes, one or more magnetometers, and/or one or more inertial measurement units and the position and/or movement of the hardware input device is used in place of the position and/or movement of the one or more hands in the corresponding air gesture(s). In scenarios where inputs are described with reference to air gestures, it should be understood that similar gestures could be detected using a hardware input device that is attached to or held by one or more hands of a user. User inputs can be detected with controls contained in the hardware input device such as one or more touch-sensitive input elements, one or more pressure-sensitive input elements, one or more buttons, one or more knobs, one or

more dials, one or more joysticks, one or more hand or finger coverings that can detect a position or change in position of portions of a hand and/or fingers relative to each other, relative to the user's body, and/or relative to a physical environment of the user, and/or other hardware input device controls, where the user inputs with the controls contained in the hardware input device are used in place of hand and/or finger gestures such as air taps or air pinches in the corresponding air gesture(s). For example, a selection input that is described as being performed with an air tap or air pinch input could be alternatively detected with a button press, a tap on a touch-sensitive surface, a press on a pressure-sensitive surface, or other hardware input. As another example, a movement input that is described as being performed with an air pinch and drag could be alternatively detected based on an interaction with the hardware input control such as a button press and hold, a touch on a touch-sensitive surface, a press on a pressure-sensitive surface, or other hardware input that is followed by movement of the hardware input device (e.g., along with the hand with which the hardware input device is associated) through space. Similarly, a two-handed input that includes movement of the hands relative to each other could be performed with one air gesture and one hardware input device in the hand that is not performing the air gesture, two hardware input devices held in different hands, or two air gestures performed by different hands using various combinations of air gestures and/or the inputs detected by one or more hardware input devices that are described above.

(154) In some embodiments, the software may be downloaded to the controller **110** in electronic form, over a network, for example, or it may alternatively be provided on tangible, non-transitory media, such as optical, magnetic, or electronic memory media. In some embodiments, the database **408** is likewise stored in a memory associated with the controller **110**. Alternatively or additionally, some or all of the described functions of the computer may be implemented in dedicated hardware, such as a custom or semi-custom integrated circuit or a programmable digital signal processor (DSP). Although the controller **110** is shown in FIG. **4**, by way of example, as a separate unit from the image sensors **404**, some or all of the processing functions of the controller may be performed by a suitable microprocessor and software or by dedicated circuitry within the housing of the image sensors **404** (e.g., a hand tracking device) or otherwise associated with the image sensors **404**. In some embodiments, at least some of these processing functions may be carried out by a suitable processor that is integrated with the display generation component **120** (e.g., in a television set, a handheld device, or head-mounted device, for example) or with any other suitable computerized device, such as a game console or media player. The sensing functions of image sensors **404** may likewise be integrated into the computer or other computerized apparatus that is to be controlled by the sensor output.

(155) FIG. **4** further includes a schematic representation of a depth map **410** captured by the image sensors **404**, in accordance with some embodiments. The depth map, as explained above, comprises a matrix of pixels having respective depth values. The pixels **412** corresponding to the hand **406** have been segmented out from the background and the wrist in this map. The brightness of each pixel within the depth map **410** corresponds inversely to its depth value, i.e., the measured *z* distance from the image sensors **404**, with the shade of gray growing darker with increasing depth. The controller **110** processes these depth values in order to identify and segment a component of the image (i.e., a group of neighboring pixels) having characteristics of a human hand. These characteristics, may include, for example, overall size, shape and motion from frame to frame of the sequence of depth maps.

(156) FIG. **4** also schematically illustrates a hand skeleton **414** that controller **110** ultimately extracts from the depth map **410** of the hand **406**, in accordance with some embodiments. In FIG. **4**, the hand skeleton **414** is superimposed on a hand background **416** that has been segmented from the original depth map. In some embodiments, key feature points of the hand (e.g., points corresponding to knuckles, finger tips, center of the palm, end of the hand connecting to wrist, etc.) and optionally on the wrist or arm connected to the hand are identified and located on the hand

skeleton **414**. In some embodiments, location and movements of these key feature points over multiple image frames are used by the controller **110** to determine the hand gestures performed by the hand or the current state of the hand, in accordance with some embodiments.

(157) FIG. 5 illustrates an example embodiment of the eye tracking device **130** (FIG. 1A). In some embodiments, the eye tracking device **130** is controlled by the eye tracking unit **243** (FIG. 2) to track the position and movement of the user's gaze with respect to the scene **105** or with respect to the XR content displayed via the display generation component **120**. In some embodiments, the eye tracking device **130** is integrated with the display generation component **120**. For example, in some embodiments, when the display generation component **120** is a head-mounted device such as headset, helmet, goggles, or glasses, or a handheld device placed in a wearable frame, the head-mounted device includes both a component that generates the XR content for viewing by the user and a component for tracking the gaze of the user relative to the XR content. In some embodiments, the eye tracking device **130** is separate from the display generation component **120**. For example, when display generation component is a handheld device or a XR chamber, the eye tracking device **130** is optionally a separate device from the handheld device or XR chamber. In some embodiments, the eye tracking device **130** is a head-mounted device or part of a head-mounted device. In some embodiments, the head-mounted eye-tracking device **130** is optionally used in conjunction with a display generation component that is also head-mounted, or a display generation component that is not head-mounted. In some embodiments, the eye tracking device **130** is not a head-mounted device, and is optionally used in conjunction with a head-mounted display generation component. In some embodiments, the eye tracking device **130** is not a head-mounted device, and is optionally part of a non-head-mounted display generation component.

(158) In some embodiments, the display generation component **120** uses a display mechanism (e.g., left and right near-eye display panels) for displaying frames including left and right images in front of a user's eyes to thus provide 3D virtual views to the user. For example, a head-mounted display generation component may include left and right optical lenses (referred to herein as eye lenses) located between the display and the user's eyes. In some embodiments, the display generation component may include or be coupled to one or more external video cameras that capture video of the user's environment for display. In some embodiments, a head-mounted display generation component may have a transparent or semi-transparent display through which a user may view the physical environment directly and display virtual objects on the transparent or semi-transparent display. In some embodiments, display generation component projects virtual objects into the physical environment. The virtual objects may be projected, for example, on a physical surface or as a holograph, so that an individual, using the system, observes the virtual objects superimposed over the physical environment. In such cases, separate display panels and image frames for the left and right eyes may not be necessary.

(159) As shown in FIG. 5, in some embodiments, eye tracking device **130** (e.g., a gaze tracking device) includes at least one eye tracking camera (e.g., infrared (IR) or near-IR (NIR) cameras), and illumination sources (e.g., IR or NIR light sources such as an array or ring of LEDs) that emit light (e.g., IR or NIR light) towards the user's eyes. The eye tracking cameras may be pointed towards the user's eyes to receive reflected IR or NIR light from the light sources directly from the eyes, or alternatively may be pointed towards "hot" mirrors located between the user's eyes and the display panels that reflect IR or NIR light from the eyes to the eye tracking cameras while allowing visible light to pass. The eye tracking device **130** optionally captures images of the user's eyes (e.g., as a video stream captured at 60-120 frames per second (fps)), analyze the images to generate gaze tracking information, and communicate the gaze tracking information to the controller **110**. In some embodiments, two eyes of the user are separately tracked by respective eye tracking cameras and illumination sources. In some embodiments, only one eye of the user is tracked by a respective eye tracking camera and illumination sources.

(160) In some embodiments, the eye tracking device **130** is calibrated using a device-specific

calibration process to determine parameters of the eye tracking device for the specific operating environment **100**, for example the 3D geometric relationship and parameters of the LEDs, cameras, hot mirrors (if present), eye lenses, and display screen. The device-specific calibration process may be performed at the factory or another facility prior to delivery of the AR/VR equipment to the end user. The device-specific calibration process may be an automated calibration process or a manual calibration process. A user-specific calibration process may include an estimation of a specific user's eye parameters, for example the pupil location, fovea location, optical axis, visual axis, eye spacing, etc. Once the device-specific and user-specific parameters are determined for the eye tracking device **130**, images captured by the eye tracking cameras can be processed using a glint-assisted method to determine the current visual axis and point of gaze of the user with respect to the display, in accordance with some embodiments.

(161) As shown in FIG. 5, the eye tracking device **130** (e.g., **130A** or **130B**) includes eye lens(es) **520**, and a gaze tracking system that includes at least one eye tracking camera **540** (e.g., infrared (IR) or near-IR (NIR) cameras) positioned on a side of the user's face for which eye tracking is performed, and an illumination source **530** (e.g., IR or NIR light sources such as an array or ring of NIR light-emitting diodes (LEDs)) that emit light (e.g., IR or NIR light) towards the user's eye(s) **592**. The eye tracking cameras **540** may be pointed towards mirrors **550** located between the user's eye(s) **592** and a display **510** (e.g., a left or right display panel of a head-mounted display, or a display of a handheld device, a projector, etc.) that reflect IR or NIR light from the eye(s) **592** while allowing visible light to pass (e.g., as shown in the top portion of FIG. 5), or alternatively may be pointed towards the user's eye(s) **592** to receive reflected IR or NIR light from the eye(s) **592** (e.g., as shown in the bottom portion of FIG. 5).

(162) In some embodiments, the controller **110** renders AR or VR frames **562** (e.g., left and right frames for left and right display panels) and provides the frames **562** to the display **510**. The controller **110** uses gaze tracking input **542** from the eye tracking cameras **540** for various purposes, for example in processing the frames **562** for display. The controller **110** optionally estimates the user's point of gaze on the display **510** based on the gaze tracking input **542** obtained from the eye tracking cameras **540** using the glint-assisted methods or other suitable methods. The point of gaze estimated from the gaze tracking input **542** is optionally used to determine the direction in which the user is currently looking.

(163) The following describes several possible use cases for the user's current gaze direction, and is not intended to be limiting. As an example use case, the controller **110** may render virtual content differently based on the determined direction of the user's gaze. For example, the controller **110** may generate virtual content at a higher resolution in a foveal region determined from the user's current gaze direction than in peripheral regions. As another example, the controller may position or move virtual content in the view based at least in part on the user's current gaze direction. As another example, the controller may display particular virtual content in the view based at least in part on the user's current gaze direction. As another example use case in AR applications, the controller **110** may direct external cameras for capturing the physical environments of the XR experience to focus in the determined direction. The autofocus mechanism of the external cameras may then focus on an object or surface in the environment that the user is currently looking at on the display **510**. As another example use case, the eye lenses **520** may be focusable lenses, and the gaze tracking information is used by the controller to adjust the focus of the eye lenses **520** so that the virtual object that the user is currently looking at has the proper vergence to match the convergence of the user's eyes **592**. The controller **110** may leverage the gaze tracking information to direct the eye lenses **520** to adjust focus so that close objects that the user is looking at appear at the right distance.

(164) In some embodiments, the eye tracking device is part of a head-mounted device that includes a display (e.g., display **510**), two eye lenses (e.g., eye lens(es) **520**), eye tracking cameras (e.g., eye tracking camera(s) **540**), and light sources (e.g., illumination sources **530** (e.g., IR or NIR LEDs)),

mounted in a wearable housing. The light sources emit light (e.g., IR or NIR light) towards the user's eye(s) **592**. In some embodiments, the light sources may be arranged in rings or circles around each of the lenses as shown in FIG. 5. In some embodiments, eight illumination sources **530** (e.g., LEDs) are arranged around each lens **520** as an example. However, more or fewer illumination sources **530** may be used, and other arrangements and locations of illumination sources **530** may be used.

(165) In some embodiments, the display **510** emits light in the visible light range and does not emit light in the IR or NIR range, and thus does not introduce noise in the gaze tracking system. Note that the location and angle of eye tracking camera(s) **540** is given by way of example, and is not intended to be limiting. In some embodiments, a single eye tracking camera **540** is located on each side of the user's face. In some embodiments, two or more NIR cameras **540** may be used on each side of the user's face. In some embodiments, a camera **540** with a wider field of view (FOV) and a camera **540** with a narrower FOV may be used on each side of the user's face. In some embodiments, a camera **540** that operates at one wavelength (e.g., 850 nm) and a camera **540** that operates at a different wavelength (e.g., 940 nm) may be used on each side of the user's face.

(166) Embodiments of the gaze tracking system as illustrated in FIG. 5 may, for example, be used in computer-generated reality, virtual reality, and/or mixed reality applications to provide computer-generated reality, virtual reality, augmented reality, and/or augmented virtuality experiences to the user.

(167) FIG. 6 illustrates a glint-assisted gaze tracking pipeline, in accordance with some embodiments. In some embodiments, the gaze tracking pipeline is implemented by a glint-assisted gaze tracking system (e.g., eye tracking device **130** as illustrated in FIGS. 1A and 5). The glint-assisted gaze tracking system may maintain a tracking state. Initially, the tracking state is off or "NO". When in the tracking state, the glint-assisted gaze tracking system uses prior information from the previous frame when analyzing the current frame to track the pupil contour and glints in the current frame. When not in the tracking state, the glint-assisted gaze tracking system attempts to detect the pupil and glints in the current frame and, if successful, initializes the tracking state to "YES" and continues with the next frame in the tracking state.

(168) As shown in FIG. 6, the gaze tracking cameras may capture left and right images of the user's left and right eyes. The captured images are then input to a gaze tracking pipeline for processing beginning at **610**. As indicated by the arrow returning to element **600**, the gaze tracking system may continue to capture images of the user's eyes, for example at a rate of 60 to 120 frames per second. In some embodiments, each set of captured images may be input to the pipeline for processing. However, in some embodiments or under some conditions, not all captured frames are processed by the pipeline.

(169) At **610**, for the current captured images, if the tracking state is YES, then the method proceeds to element **640**. At **610**, if the tracking state is NO, then as indicated at **620** the images are analyzed to detect the user's pupils and glints in the images. At **630**, if the pupils and glints are successfully detected, then the method proceeds to element **640**. Otherwise, the method returns to element **610** to process next images of the user's eyes.

(170) At **640**, if proceeding from element **610**, the current frames are analyzed to track the pupils and glints based in part on prior information from the previous frames. At **640**, if proceeding from element **630**, the tracking state is initialized based on the detected pupils and glints in the current frames. Results of processing at element **640** are checked to verify that the results of tracking or detection can be trusted. For example, results may be checked to determine if the pupil and a sufficient number of glints to perform gaze estimation are successfully tracked or detected in the current frames. At **650**, if the results cannot be trusted, then the tracking state is set to NO at element **660**, and the method returns to element **610** to process next images of the user's eyes. At **650**, if the results are trusted, then the method proceeds to element **670**. At **670**, the tracking state is set to YES (if not already YES), and the pupil and glint information is passed to element **680** to

estimate the user's point of gaze.

(171) FIG. 6 is intended to serve as one example of eye tracking technology that may be used in a particular implementation. As recognized by those of ordinary skill in the art, other eye tracking technologies that currently exist or are developed in the future may be used in place of or in combination with the glint-assisted eye tracking technology describe herein in the computer system 101 for providing XR experiences to users, in accordance with various embodiments.

(172) In some embodiments, the captured portions of real world environment 602 are used to provide a XR experience to the user, for example, a mixed reality environment in which one or more virtual objects are superimposed over representations of real world environment 602.

(173) Thus, the description herein describes some embodiments of three-dimensional environments (e.g., XR environments) that include representations of real world objects and representations of virtual objects. For example, a three-dimensional environment optionally includes a representation of a table that exists in the physical environment, which is captured and displayed in the three-dimensional environment (e.g., actively via cameras and displays of a computer system, or passively via a transparent or translucent display of the computer system). As described previously, the three-dimensional environment is optionally a mixed reality system in which the three-dimensional environment is based on the physical environment that is captured by one or more sensors of the computer system and displayed via a display generation component. As a mixed reality system, the computer system is optionally able to selectively display portions and/or objects of the physical environment such that the respective portions and/or objects of the physical environment appear as if they exist in the three-dimensional environment displayed by the computer system. Similarly, the computer system is optionally able to display virtual objects in the three-dimensional environment to appear as if the virtual objects exist in the real world (e.g., physical environment) by placing the virtual objects at respective locations in the three-dimensional environment that have corresponding locations in the real world. For example, the computer system optionally displays a vase such that it appears as if a real vase is placed on top of a table in the physical environment. In some embodiments, a respective location in the three-dimensional environment has a corresponding location in the physical environment. Thus, when the computer system is described as displaying a virtual object at a respective location with respect to a physical object (e.g., such as a location at or near the hand of the user, or at or near a physical table), the computer system displays the virtual object at a particular location in the three-dimensional environment such that it appears as if the virtual object is at or near the physical object in the physical world (e.g., the virtual object is displayed at a location in the three-dimensional environment that corresponds to a location in the physical environment at which the virtual object would be displayed if it were a real object at that particular location).

(174) In some embodiments, real world objects that exist in the physical environment that are displayed in the three-dimensional environment (e.g., and/or visible via the display generation component) can interact with virtual objects that exist only in the three-dimensional environment. For example, a three-dimensional environment can include a table and a vase placed on top of the table, with the table being a view of (or a representation of) a physical table in the physical environment, and the vase being a virtual object.

(175) In a three-dimensional environment (e.g., a real environment, a virtual environment, or an environment that includes a mix of real and virtual objects), objects are sometimes referred to as having a depth or simulated depth, or objects are referred to as being visible, displayed, or placed at different depths. In this context, depth refers to a dimension other than height or width. In some embodiments, depth is defined relative to a fixed set of coordinates (e.g., where a room or an object has a height, depth, and width defined relative to the fixed set of coordinates). In some embodiments, depth is defined relative to a location or viewpoint of a user, in which case, the depth dimension varies based on the location of the user and/or the location and angle of the viewpoint of the user. In some embodiments where depth is defined relative to a location of a user that is

positioned relative to a surface of an environment (e.g., a floor of an environment, or a surface of the ground), objects that are further away from the user along a line that extends parallel to the surface are considered to have a greater depth in the environment, and/or the depth of an object is measured along an axis that extends outward from a location of the user and is parallel to the surface of the environment (e.g., depth is defined in a cylindrical or substantially cylindrical coordinate system with the position of the user at the center of the cylinder that extends from a head of the user toward feet of the user). In some embodiments where depth is defined relative to viewpoint of a user (e.g., a direction relative to a point in space that determines which portion of an environment that is visible via a head mounted device or other display), objects that are further away from the viewpoint of the user along a line that extends parallel to the direction of the viewpoint of the user are considered to have a greater depth in the environment, and/or the depth of an object is measured along an axis that extends outward from a line that extends from the viewpoint of the user and is parallel to the direction of the viewpoint of the user (e.g., depth is defined in a spherical or substantially spherical coordinate system with the origin of the viewpoint at the center of the sphere that extends outwardly from a head of the user). In some embodiments, depth is defined relative to a user interface container (e.g., a window or application in which application and/or system content is displayed) where the user interface container has a height and/or width, and depth is a dimension that is orthogonal to the height and/or width of the user interface container. In some embodiments, in circumstances where depth is defined relative to a user interface container, the height and or width of the container are typically orthogonal or substantially orthogonal to a line that extends from a location based on the user (e.g., a viewpoint of the user or a location of the user) to the user interface container (e.g., the center of the user interface container, or another characteristic point of the user interface container) when the container is placed in the three-dimensional environment or is initially displayed (e.g., so that the depth dimension for the container extends outward away from the user or the viewpoint of the user). In some embodiments, in situations where depth is defined relative to a user interface container, depth of an object relative to the user interface container refers to a position of the object along the depth dimension for the user interface container. In some embodiments, multiple different containers can have different depth dimensions (e.g., different depth dimensions that extend away from the user or the viewpoint of the user in different directions and/or from different starting points). In some embodiments, when depth is defined relative to a user interface container, the direction of the depth dimension remains constant for the user interface container as the location of the user interface container, the user and/or the viewpoint of the user changes (e.g., or when multiple different viewers are viewing the same container in the three-dimensional environment such as during an in-person collaboration session and/or when multiple participants are in a real-time communication session with shared virtual content including the container). In some embodiments, for curved containers (e.g., including a container with a curved surface or curved content region), the depth dimension optionally extends into a surface of the curved container. In some situations, z-separation (e.g., separation of two objects in a depth dimension), z-height (e.g., distance of one object from another in a depth dimension), z-position (e.g., position of one object in a depth dimension), z-depth (e.g., position of one object in a depth dimension), or simulated z dimension (e.g., depth used as a dimension of an object, dimension of an environment, a direction in space, and/or a direction in simulated space) are used to refer to the concept of depth as described above.

(176) In some embodiments, a user is optionally able to interact with virtual objects in the three-dimensional environment using one or more hands as if the virtual objects were real objects in the physical environment. For example, as described above, one or more sensors of the computer system optionally capture one or more of the hands of the user and display representations of the hands of the user in the three-dimensional environment (e.g., in a manner similar to displaying a real world object in three-dimensional environment described above), or in some embodiments, the

hands of the user are visible via the display generation component via the ability to see the physical environment through the user interface due to the transparency/translucency of a portion of the display generation component that is displaying the user interface or due to projection of the user interface onto a transparent/translucent surface or projection of the user interface onto the user's eye or into a field of view of the user's eye. Thus, in some embodiments, the hands of the user are displayed at a respective location in the three-dimensional environment and are treated as if they were objects in the three-dimensional environment that are able to interact with the virtual objects in the three-dimensional environment as if they were physical objects in the physical environment. In some embodiments, the computer system is able to update display of the representations of the user's hands in the three-dimensional environment in conjunction with the movement of the user's hands in the physical environment.

(177) In some of the embodiments described below, the computer system is optionally able to determine the “effective” distance between physical objects in the physical world and virtual objects in the three-dimensional environment, for example, for the purpose of determining whether a physical object is directly interacting with a virtual object (e.g., whether a hand is touching, grabbing, holding, etc. a virtual object or within a threshold distance of a virtual object). For example, a hand directly interacting with a virtual object optionally includes one or more of a finger of a hand pressing a virtual button, a hand of a user grabbing a virtual vase, two fingers of a hand of the user coming together and pinching/holding a user interface of an application, and any of the other types of interactions described here. For example, the computer system optionally determines the distance between the hands of the user and virtual objects when determining whether the user is interacting with virtual objects and/or how the user is interacting with virtual objects. In some embodiments, the computer system determines the distance between the hands of the user and a virtual object by determining the distance between the location of the hands in the three-dimensional environment and the location of the virtual object of interest in the three-dimensional environment. For example, the one or more hands of the user are located at a particular position in the physical world, which the computer system optionally captures and displays at a particular corresponding position in the three-dimensional environment (e.g., the position in the three-dimensional environment at which the hands would be displayed if the hands were virtual, rather than physical, hands). The position of the hands in the three-dimensional environment is optionally compared with the position of the virtual object of interest in the three-dimensional environment to determine the distance between the one or more hands of the user and the virtual object. In some embodiments, the computer system optionally determines a distance between a physical object and a virtual object by comparing positions in the physical world (e.g., as opposed to comparing positions in the three-dimensional environment). For example, when determining the distance between one or more hands of the user and a virtual object, the computer system optionally determines the corresponding location in the physical world of the virtual object (e.g., the position at which the virtual object would be located in the physical world if it were a physical object rather than a virtual object), and then determines the distance between the corresponding physical position and the one of more hands of the user. In some embodiments, the same techniques are optionally used to determine the distance between any physical object and any virtual object. Thus, as described herein, when determining whether a physical object is in contact with a virtual object or whether a physical object is within a threshold distance of a virtual object, the computer system optionally performs any of the techniques described above to map the location of the physical object to the three-dimensional environment and/or map the location of the virtual object to the physical environment.

(178) In some embodiments, the same or similar technique is used to determine where and what the gaze of the user is directed to and/or where and at what a physical stylus held by a user is pointed. For example, if the gaze of the user is directed to a particular position in the physical environment, the computer system optionally determines the corresponding position in the three-dimensional

environment (e.g., the virtual position of the gaze), and if a virtual object is located at that corresponding virtual position, the computer system optionally determines that the gaze of the user is directed to that virtual object. Similarly, the computer system is optionally able to determine, based on the orientation of a physical stylus, to where in the physical environment the stylus is pointing. In some embodiments, based on this determination, the computer system determines the corresponding virtual position in the three-dimensional environment that corresponds to the location in the physical environment to which the stylus is pointing, and optionally determines that the stylus is pointing at the corresponding virtual position in the three-dimensional environment. (179) Similarly, the embodiments described herein may refer to the location of the user (e.g., the user of the computer system) and/or the location of the computer system in the three-dimensional environment. In some embodiments, the user of the computer system is holding, wearing, or otherwise located at or near the computer system. Thus, in some embodiments, the location of the computer system is used as a proxy for the location of the user. In some embodiments, the location of the computer system and/or user in the physical environment corresponds to a respective location in the three-dimensional environment. For example, the location of the computer system would be the location in the physical environment (and its corresponding location in the three-dimensional environment) from which, if a user were to stand at that location facing a respective portion of the physical environment that is visible via the display generation component, the user would see the objects in the physical environment in the same positions, orientations, and/or sizes as they are displayed by or visible via the display generation component of the computer system in the three-dimensional environment (e.g., in absolute terms and/or relative to each other). Similarly, if the virtual objects displayed in the three-dimensional environment were physical objects in the physical environment (e.g., placed at the same locations in the physical environment as they are in the three-dimensional environment, and having the same sizes and orientations in the physical environment as in the three-dimensional environment), the location of the computer system and/or user is the position from which the user would see the virtual objects in the physical environment in the same positions, orientations, and/or sizes as they are displayed by the display generation component of the computer system in the three-dimensional environment (e.g., in absolute terms and/or relative to each other and the real world objects).

(180) In the present disclosure, various input methods are described with respect to interactions with a computer system. When an example is provided using one input device or input method and another example is provided using another input device or input method, it is to be understood that each example may be compatible with and optionally utilizes the input device or input method described with respect to another example. Similarly, various output methods are described with respect to interactions with a computer system. When an example is provided using one output device or output method and another example is provided using another output device or output method, it is to be understood that each example may be compatible with and optionally utilizes the output device or output method described with respect to another example. Similarly, various methods are described with respect to interactions with a virtual environment or a mixed reality environment through a computer system. When an example is provided using interactions with a virtual environment and another example is provided using mixed reality environment, it is to be understood that each example may be compatible with and optionally utilizes the methods described with respect to another example. As such, the present disclosure discloses embodiments that are combinations of the features of multiple examples, without exhaustively listing all features of an embodiment in the description of each example embodiment.

(181) User Interfaces and Associated Processes

(182) Attention is now directed towards embodiments of user interfaces (“UI”) and associated processes that may be implemented on a computer system, such as a portable multifunction device or a head-mounted device, in communication with a display generation component and (optionally) one or more sensors.

(183) Examples described herein illustrate the manner in which a user of a computer system (e.g., device **700**) may initiate and/or modify a live communication session in which the user communicates with one or more users of other respective computer systems. In some embodiments, a live communication session is an audio communication session (e.g., voice call or phone call). In some embodiments, a live communication session is a video communication session (e.g., video telephony and/or video conferencing). In some embodiments, a live communication session is an XR communication session, such as a spatial communication session or a non-spatial communication session. During a spatial communication session, one or more users are represented in the XR environment by three-dimensional (3D) representations (e.g., avatars) corresponding to the user(s), respectively. In some embodiments, a 3D representation has spatial agency such that the 3D representation can move within the XR environment relative to other elements and/or users in the XR environment. During a non-spatial communication session, one or more users are represented in the XR environment by two-dimensional (2D) representations corresponding to the user(s), respectively. In some embodiments, a 2D representation includes a video feed of a user and optionally, has a fixed position (e.g., location) within the XR environment.

(184) FIGS. 7A-7Q illustrate examples of managing live communication sessions. FIG. 8 is a flow diagram of an exemplary method **800** for managing live communication sessions. FIG. 9 is a flow diagram of an exemplary method **900** for providing avatars in live communication sessions. The user interfaces in FIGS. 7A-7Q are used to illustrate the processes described below, including the processes in FIG. 8 and/or FIG. 9.

(185) While FIGS. 7A-7Q illustrate a device **700** as a handheld device having a display **702** (e.g., a tablet, a smart phone, or a laptop), in some embodiments, device **700** is a head-mounted device (HMD). The HMD is configured to be worn on a head of a user of device **700** and includes display **702** on and/or in an interior portion of the HMD. Display **702** is visible to the user when device **700** is worn on the head of the user. For instance, in some embodiments, the HMD at least partially covers eyes of the user when worn on the head of the user, such that display **702** is positioned over and/or in front of the eyes of the user. In such embodiments, display **702** is configured to display an XR environment during a live communication session in which the user of the HMD is participating.

(186) In FIG. 7A, device **700** displays, on display **702**, XR environment **704** including elements (e.g., virtual elements and/or physical elements), such as table **704a** and couch **704b**. While displaying XR environment **704**, device **700** receives a request to display a communication interface. In some embodiments, the request to display a communication interface is a press of button **703** of device **700**. As shown in FIG. 7B, in response to receiving the request, device **700** displays communication interface **710**. In some embodiments, communication interface **710** is displayed within XR environment **704**.

(187) Generally, communication interface **710** can be used to initiate and/or modify a live communication session (e.g., audio communication session, video communication session, or XR communication session). Communication interface **710** includes pinned contacts **712** (e.g., pinned contacts **712a-712g**) and recent contacts **714** (e.g., recent contacts **714a-714i**). In some embodiments, pinned contacts **712** are a set of contacts selected (e.g., contacts favorited or pinned) by the user of device **700** to be included in communication interface **710**. In some embodiments, recent contacts **714** are contacts with which the user of device **700** has recently communicated (e.g., via text, phone, and/or live communication session) using device **700**, and optionally, one or more other devices associated with the user of device **700**. In some embodiments, recent contacts **714** are arranged (e.g., ordered or ranked) based on recency of communications between recent contacts **714** and the user of device **700**.

(188) In some embodiments, one or more pinned contacts **712** and/or recent contacts **714** correspond to a defined group of contacts. As an example, pinned contact **712d** corresponds to a group of contacts “Surfers”. As another example, recent contact **714d** corresponds to a group of

contacts “Lake Crew”.

(189) In some embodiments, pinned contacts **712** and/or recent contacts **714** indicate the most recent communications between the user of device **700** and various contacts. As an example, pinned contact **712b** (“John”) indicates that the contact last sent a text message 1 minute ago. Optionally, communication interface **710** includes preview **716b** indicating the content of the text message sent by pinned user **712b**. As another example, pinned user **712c** indicates that the contact last sent a text reaction (e.g., a “heart” reaction) at a time of 2:10. As yet another example, recent contact **714a** (“Mom”) indicates that the user of device **700** most recently communicated with contact **714a** in an XR communication session (e.g., a spatial live communication session or a non-spatial live communication session) at a time of 3:32. As yet another example, recent contact **714e** (“Uncle Bob”) indicates that the user of device **700** most recently communicated with contact **714e** in an audio communication session (e.g., phone call) at a time of 9:41.

(190) In some embodiments, pinned contacts **712** and/or recent contacts **714** indicate pending invitations to live communication sessions. As an example, recent contact **714b** (“Dad”) indicates that the user of device **700** can join a live communication session with recent contact **714b**. As yet another example, recent contact **714d** (“Lake Crew”) indicates that three members of the group are currently in an ongoing live communication session that the user of device **700** has been invited to join.

(191) In some embodiments, contacts **712** and **714** of communication interface **710** can be used to manage contacts. By way of example, while displaying communication interface **710**, device **700** detects selection of contact **712e** (“Jo”). In some embodiments, the selection of contact **712e** is a tap gesture **705b** on contact **712e**. In some embodiments, the selection of contact **712e** is an air gesture, for instance, indicating a selection of contact **712e**. As shown in FIG. 7C1 and/or FIG. 7C2, in response to detecting selection of contact **712e**, device **700** displays contact menu **720** associated with contact **712e**.

(192) Contact menu **720** includes invite option **720a** and expand option **720b**. Invite option **720a**, when selected, causes device **700** to invite contact **712e** to an XR communication session. Expand option **720b**, when selected, causes device **700** to display one or more additional options for managing contact **712e**. For example, while displaying contact menu **720**, device **700** detects selection of expand option **720b**. In some embodiments, the selection of expand option **720b** is a tap gesture **705c** on expand option **720b**. In some embodiments, the selection of expand option **720b** is an air gesture, for instance, indicating a selection of expand option **720b**. As shown in FIG. 7D, in response to detecting selection of expand option **720b**, device **700** expands contact menu **720** to display (e.g., replace display of expand option **720b** with) one or more additional options (e.g., options **720c-720f**).

(193) In some embodiments, when expanded, contact menu **720** includes audio option **720c**, message option **720d**, info option **720e**, and edit option **720f**. Audio option **720c**, when selected, causes device **700** to initiate an audio communication session (e.g., that does not have a live video component) with contact **712e**. In some embodiments, device **700** is not capable of communicating over a cellular network and/or is configured to use an external device for audio calls. Accordingly, in some examples, device **700** initiates an audio communication session using a nearby device (e.g., mobile phone and/or a tablet) (e.g., that is capable of communicating over a cellular network). Edit option **720f**, when selected, allows a user of device **700** to remove contact **712e** from pinned contacts **712** (or add contact **712e** to pinned contacts in embodiments in which contact **712e** is not already a pinned contact). Message option **720d**, when selected, allows for a user to send a message to contact **712e**. For example, while displaying contact menu **720**, device **700** detects selection of message option **720d**. In some embodiments, the selection of message option **720d** is a tap gesture **705d** on message option **720d**. In some embodiments, the selection of message option **720d** is an air gesture, for instance, indicating a selection of message option **720d**. As shown in FIG. 7E, in response to detecting selection of message option **720d**, device **700** displays (e.g., replaces display

of communications interface **710** with) message interface **730**. Thereafter, message interface **730** can be used to send messages to contact **712e**.

(194) With reference once again to FIG. 7D, info option **720e**, when selected, causes device **700** to display information corresponding to contact **712e** (e.g., without displaying additional information corresponding to other contacts). For example, while displaying contact menu **720**, device **700** detects selection of info option **720e**. In some embodiments, the selection of info option **720e** is a tap gesture **707d** on info option **720e**. In some embodiments, the selection of info option **720e** is an air gesture, for instance, indicating a selection of info option **720e**. As shown in FIG. 7F, in response to detecting selection of info option **720e**, device **700** displays info interface **740**. Info interface **740** includes various details corresponding to contact **712e**, including but not limited to name and contact information.

(195) In some embodiments, a device of a contact is not capable of participating in an XR communication session with device **700**. Accordingly, in some embodiments, one or more options of a contact menu may be omitted, de-emphasized (e.g., grayed out or darkened), and/or replaced to accurately reflect capabilities of a device of a contact. For example, with reference once again to FIG. 7B, while displaying communications interface **710**, device **700** detects selection of contact **712g** (“Sam”). In some embodiments, the selection of contact **712g** is a tap gesture **709b** on contact **712g**. In some embodiments, the selection of contact **712g** is an air gesture, for instance, indicating a selection of contact **712g**. As shown in FIG. 7C1, in response to detecting selection of contact **712g**, device **700** displays contact menu **722** associated with contact **712g**.

(196) Because, in some embodiments, a device of contact **712g** is not capable of communicating in an XR communication session with device **700**, menu **722** does not include an invite option (e.g., invite option **720a**) and instead includes audio option **722a**. Audio option **722a**, when selected, causes device **700** to initiate an audio communication session with contact **712g**. Menu **722** further includes expand option **722b**, which when selected, causes device **700** to display one or more additional options for contact **712g**.

(197) In some embodiments, a contact menu associated with a contact includes one or more additional options based on a state of device **700**. As an example, in some embodiments, in instances in which device **700** is participating in a live communication session (e.g., XR communication session or an audio communication session), a contact menu includes an option to invite a contact to the live communication session. For example, with reference to FIG. 7B, while participating in an XR communication session and while displaying communication interface **710**, device **700** detects selection of contact **714g** (“Dylan”). In some embodiments, the selection of contact **714g** is a tap gesture **711b** on contact **714g**. In some embodiments, the selection of contact **714g** is an air gesture, for instance, indicating a selection of contact **714f**. As shown in FIG. 7C1, in response to detecting selection of contact **714g**, device **700** displays contact menu **724** associated with contact **714g**.

(198) Contact menu **724** includes invite option **724a**, invite option **724b**, and expand option **724c**. Invite option **724a**, when selected (e.g., tap gesture **709c**), causes device **700** to invite contact **714g** to a new live communication session. Invite option **724b**, when selected, causes device **700** to invite contact **714g** to the live communication session in which device **700** is currently participating. Expand option **720c**, when selected, causes device **700** to display one or more additional options for contact **714g**.

(199) In some embodiments, inviting a contact to a new live communication session (e.g., in response to selection of option **724a**) will cause device **700** to disconnect from and/or terminate the live communication session in which device **700** is currently participating. In some embodiments, prior to terminating an existing live communication session in this manner, device **700** confirms that a user wishes to disconnect from the current live communication session prior to initiating a new live communication session. For example, as shown in FIG. 7G, in response to selection of invite option **724a**, device **700** displays confirmation interface **740** including confirm affordance

742. In response to selection of confirm affordance **742**, device **700** terminates the current live communication session and invites contact **714f** to a new live communication session.

(200) In some embodiments, a user optionally sends messages to contacts using communication interface **710**. For example, with reference to FIG. 7B, while displaying communication interface **710**, device **700** detects selection of preview **716b** associated with pinned contact **712b**. In some embodiments, the selection of preview **716b** is a tap gesture **707b** on preview **716b**. In some embodiments, the selection of preview **716b** is an air gesture, for instance, indicating a selection of preview **716b**. As shown in FIG. 7C1, in response to detecting selection of preview **716b**, device **700** expands preview **716b** to display reply option **718**.

(201) Reply option **718**, when selected, causes device **700** to display a reply interface for sending a message to contact **712b**. For example, while displaying reply option **718** in preview **716b**, device **700** detects selection of reply option **718**. In some embodiments, the selection of reply option **718** is a tap gesture **707c** on reply option **718**. In some embodiments, the selection of reply option **718** is an air gesture, for instance, indicating a selection of reply option **718**. As shown in FIG. 7H, in response to detecting selection of reply option **718**, device **700** displays reply interface **750**, which can be used to send messages to contact **712b**.

(202) In some embodiments, the techniques and user interface(s) described in FIG. 7C1 are provided by one or more of the devices described in FIGS. 1A-1P. FIG. 7C2 illustrates an embodiment in which communication interface **X710** (e.g., as described in FIGS. 7B and 7C1) is displayed on display module **X702** of head-mounted device (HMD) **X700**. In some embodiments, device **X700** includes a pair of display modules that provide stereoscopic content to different eyes of the same user. For example, HMD **X700** includes display module **X702** (which provides content to a left eye of the user) and a second display module (which provides content to a right eye of the user). In some embodiments, the second display module displays a slightly different image than display module **X702** to generate the illusion of stereoscopic depth.

(203) As shown in FIG. 7C2, in response to detecting selection of contact **X712e**, HMD **X700** displays contact menu **X720** associated with contact **X712e**. In some embodiments, HMD **X700** detects selection of contact **X712e** based on an air gesture performed by a user of HMD **X700**. In some embodiments, HMD **X700** detects hands **X750a** and/or **X750b** of the user of HMD **X700** and determines whether motion of hands **X750a** and/or **X750b** perform a predetermined air gesture corresponding to selection of contact **X712e**. In some embodiments, the predetermined air gesture selecting contact **X712e** includes a pinch gesture. In some embodiments, the pinch gesture includes detecting movement of finger **X750c** and thumb **X750d** toward one another. In some embodiments, HMD **X700** detects selection of contact **X712e** based on a gaze and air gesture input performed by the user of HMD **X700**. In some embodiments, the gaze and air gesture input includes detecting that the user of HMD **X700** is looking at contact **X712e** (e.g., for more than a predetermined amount of time) and hands **X750a** and/or **X750b** of the user of HMD **X700** perform a pinch gesture.

(204) Contact menu **X720** includes invite option **X720a** and expand option **X720b**. Invite option **X720a**, when selected (e.g., via an air gesture, such as a pinch gesture and/or via a gaze and pinch gesture), causes HMD **X700** to invite contact **X712e** to an XR communication session. Expand option **X720b**, when selected, causes HMD **X700** to display one or more additional options for managing contact **X712e**. For example, while displaying contact menu **X720**, HMD **X700** detects selection of expand option **X720b**. In some embodiments, the selection of expand option **X720b** is an air gesture (e.g., a pinch gesture and/or a gaze and pinch gesture), for instance, indicating a selection of expand option **X720b**. In response to detecting selection of expand option **X720b**, HMD **X700** expands contact menu **X720** to display (e.g., replace display of expand option **X720b** with) one or more additional options (e.g., options **720c-720f**, as illustrated in FIG. 7D).

(205) In some embodiments, when expanded, contact menu **X720** includes an audio option (e.g., **720c**), a message option (e.g., **720d**), an info option (e.g., **720e**), and an edit option (e.g., **720f**),

e.g., as described with respect to FIG. 7D. The audio option, when selected, causes HMD X700 to initiate an audio communication session (e.g., that does not have a live video component) with contact X712e. In some embodiments, HMD X700 is not capable of communicating over a cellular network and/or is configured to use an external device for audio calls. Accordingly, in some examples, HMD X700 initiates an audio communication session using a nearby device (e.g., mobile phone and/or a tablet) (e.g., that is capable of communicating over a cellular network). The edit option, when selected, allows a user of HMD X700 to remove contact X712e from pinned contacts X712 (or add contact X712e to pinned contacts in embodiments in which contact X712e is not already a pinned contact), e.g., as described with respect to FIG. 7D. The message option, when selected, allows for a user to send a message to contact X712e, e.g., as described with respect to FIG. 7D. For example, while displaying expanded contact menu X720, HMD X700 detects selection of the message option (e.g., 720d). In some embodiments, the selection of the message option is an air gesture (e.g., a pinch gesture and/or a gaze and pinch gesture), for instance, indicating a selection of the message option. In some embodiments, as shown in FIG. 7E, in response to detecting selection of the message option (e.g., 720d), HMD X700 displays (e.g., replaces display of communications interface X710 with) a message interface (e.g., 730). Thereafter, the message interface can be used to send messages to contact X712e.

(206) In some embodiments, a contact menu associated with a contact includes one or more additional options based on a state of HMD X700. As an example, in some embodiments, in instances in which HMD X700 is participating in a live communication session (e.g., XR communication session or an audio communication session), a contact menu includes an option to invite a contact to the live communication session. For example, while participating in an XR communication session and while displaying communication interface X710, HMD X700 detects selection of contact X714g (“Dylan”). In some embodiments, the selection of contact X714g is an air gesture (e.g., a pinch gesture and/or a gaze and pinch gesture), for instance, indicating a selection of contact X714f. As shown in FIG. 7C2, in response to detecting selection of contact X714g, HMD X700 displays contact menu X724 associated with contact X714g.

(207) Contact menu X724 includes invite option X724a, invite option X724b, and expand option X724c. Invite option X724a, when selected (e.g., via an air gesture, such as a pinch gesture and/or a gaze and pinch gesture), causes HMD X700 to invite contact X714g to a new live communication session. Invite option X724b, when selected (e.g., via an air gesture, such as a pinch gesture and/or a gaze and pinch gesture), causes HMD X700 to invite contact X714g to the live communication session in which HMD X700 is currently participating. Expand option X720c, when selected, causes HMD X700 to display one or more additional options for contact X714g.

(208) In some embodiments, inviting a contact to a new live communication session (e.g., in response to selection of option X724a) will cause HMD X700 to disconnect from and/or terminate the live communication session in which HMD X700 is currently participating. In some embodiments, prior to terminating an existing live communication session in this manner, HMD X700 confirms that a user wishes to disconnect from the current live communication session prior to initiating a new live communication session. For example, as shown in FIG. 7G, in response to selection of invite option X724a, HMD X700 can display confirmation interface 740 including confirm affordance 742. In response to selection (e.g., via an air gesture, such as a pinch gesture and/or a gaze and pinch gesture) of confirm affordance 742, HMD X700 terminates the current live communication session and invites contact X714f to a new live communication session.

(209) In some embodiments, a user optionally sends messages to contacts using communication interface X710. For example, while displaying communication interface X710, HMD X700 detects selection of preview 716b (e.g., as shown in FIG. 7B) associated with pinned contact X712b. In some embodiments, the selection of preview 716b is an air gesture (e.g., a pinch gesture and/or a gaze and pinch gesture), for instance, indicating a selection of preview 716b. As shown in FIG. 7C2, in response to detecting selection of preview 716b, HMD X700 expands preview 716b to

display reply option **X718**.

(210) Reply option **X718**, when selected, causes HMD **X700** to display a reply interface for sending a message to contact **X712b**. For example, while displaying reply option **X718** in preview **716b**, HMD **X700** detects selection of reply option **X718**. In some embodiments, the selection of reply option **X718** is an air gesture (e.g., a pinch gesture and/or a gaze and pinch gesture), for instance, indicating a selection of reply option **X718**. As shown in FIG. 7H, in response to detecting selection of reply option **X718**, HMD **X700** can display reply interface **750**, which can be used to send messages to contact **X712b**.

(211) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 1B-1P can be included, either alone or in any combination, in HMD **X700**. For example, in some embodiments, HMD **X700** includes any of the features, components, and/or parts of HMD **1-100**, **1-200**, **3-100**, **6-100**, **6-200**, **6-300**, **6-400**, **11.1.1-100**, and/or **11.1.2-100**, either alone or in any combination. In some embodiments, display module **X702** includes any of the features, components, and/or parts of display unit **1-102**, display unit **1-202**, display unit **1-306**, display unit **1-406**, display generation component **120**, display screens **1-122a-b**, first and second rear-facing display screens **1-322a**, **1-322b**, display **11.3.2-104**, first and second display assemblies **1-120a**, **1-120b**, display assembly **1-320**, display assembly **1-421**, first and second display sub-assemblies **1-420a**, **1-420b**, display assembly **3-108**, display assembly **11.3.2-204**, first and second optical modules **11.1.1-104a** and **11.1.1-104b**, optical module **11.3.2-100**, optical module **11.3.2-200**, lenticular lens array **3-110**, display region or area **6-232**, and/or display/display region **6-334**, either alone or in any combination. In some embodiments, HMD **X700** includes a sensor that includes any of the features, components, and/or parts of any of sensors **190**, sensors **306**, image sensors **314**, image sensors **404**, sensor assembly **1-356**, sensor assembly **1-456**, sensor system **6-102**, sensor system **6-202**, sensors **6-203**, sensor system **6-302**, sensors **6-303**, sensor system **6-402**, and/or sensors **11.1.2-110a-f**, either alone or in any combination. In some embodiments, input device **X703** includes any of the features, components, and/or parts of any of first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**, either alone or in any combination. In some embodiments, HMD **X700** includes one or more audio output components (e.g., electronic component **1-112**) for generating audio feedback (e.g., audio output), optionally generated based on detected events and/or user inputs detected by the HMD **X700**.

(212) In some embodiments, communication interface **710** is used to generate an avatar. In some embodiments, the avatar serves as a representation (e.g., 3D representation) of the user of device **700** in XR communication sessions. For example, with reference to FIG. 7B, while displaying communication interface **710**, device **700** detects selection of avatar option **715**. In some embodiments, the selection of avatar option **715** is a tap gesture **713b** on avatar option **715**. In some embodiments, the selection of avatar option **715** is an air gesture, for instance, indicating a selection of avatar option **715**. As shown in FIG. 7I, in response to detecting selection of avatar option **715**, device **700** displays avatar interface **760**.

(213) At FIG. 7I, avatar interface **760** first option **762** (e.g., that is more realistic than a second option) and second option **764** (e.g., that is less realistic than the first option). First option **762**, when enabled, causes an avatar of a user of device **700** to reflect an appearance of the user. For example, in some embodiments, when first option **762** is enabled, an avatar includes one or more visual characteristics that correspond to one or more physical characteristics of the user. Second option **764**, when enabled, causes an avatar of a user of device **700** to indicate motion of a user (e.g., during live communication sessions) without reflecting an appearance of the user. For example, in some embodiments, when second option **764** is enabled, an avatar having a default appearance is used. In some embodiments, when first option **762** is enabled (as compared to second option **764**), the avatar of the user of device **700** is represented by a first representation style and the avatar is displayed with a first level of detail (e.g., a first level of detail with respect to the appearance of the user and/or one or more portions of the user) and indicates a position and

movement of a first user portion of the user relative to a position and movement of a second user portion of the user in a first manner. In some embodiments, when second option **764** is enabled (as compared to first option **762**), the avatar of the user of device **700** is represented by a second representation style that is different from the first representation style and the avatar is displayed with a second level of detail (e.g., a second level of detail with respect to the appearance of the user and/or one or more portions of the user) that is lower than (e.g., less than and/or mimics the appearance of the user with less detail and/or a lower amount of detail) the first level of detail and indicates the position and movement of the first user portion of the user relative to the position and movement of the second user portion of the user in a second manner that is different from the first manner.

(214) Avatar interface **760** further includes menu option **766**, which when selected, causes device **700** to display an avatar menu, as shown in FIG. 7I. For example, at FIG. 7I, while displaying avatar interface **760**, device **700** detects selection of menu option **766**. In some embodiments, the selection of menu option **766** is a tap gesture **705i** on menu option **766**. In some embodiments, the selection of menu option **766** is an air gesture, for instance, indicating a selection of menu option **766**. As shown in FIG. 7J, in response to detecting selection of menu option **766**, device **700** displays avatar menu **768**.

(215) At FIG. 7J, avatar menu **768** includes edit option **768a**, create option **768b**, and/or delete option **768c**. In some embodiments, if an avatar has not yet been created for a user of device **700**, avatar menu **768** includes create option **768b** and does not include edit option **768a** and delete option **768c**. In some embodiments, if an avatar has been created for a user of device **700**, avatar menu **768** includes edit option **768a** and delete option **768c** and does not include create option **768b**.

(216) At FIG. 7J, while displaying avatar menu **768**, device **700** detects selection of create option **768b**. In some embodiments, the selection of create option **768b** is a tap gesture **705j** on create option **768b**. In some embodiments, the selection of create option **768b** is an air gesture, for instance, indicating a selection of create option **768b**. As shown in FIG. 7K, in response to detecting selection of create option **768b**, device **700** displays setup interface **770**.

(217) At FIG. 7K, setup interface **770** includes setup option **772**, which when selected, causes device **700** to display an avatar editing interface. For example, while displaying setup interface **770**, device **700** detects selection of setup affordance **772**. In some embodiments, the selection of setup affordance **772** is a tap gesture **705k** on setup affordance **772**. In some embodiments, the selection of setup affordance **772** is an air gesture, for instance, indicating a selection of setup affordance **772**. As shown in FIG. 7L1, in response to detecting selection of setup affordance **772**, device **700** displays avatar editing interface **780**.

(218) At FIG. 7L-1, avatar editing interface **780** includes live view **781** of an avatar of a user of device **700**. In some embodiments, device **700** displays live view **781**, which is updated in real-time, of avatar editing interface **780** according to movement and/or mannerisms of the user of device **700**, as detected by device **700**. Avatar editing interface **780** further includes various settings and/or parameters by which visual characteristics of the avatar are adjusted. As an example, avatar editing interface **780** includes settings **782**, which include a brightness setting **782a** and a warmth setting **782b**. Brightness setting **782a** and warmth setting **782b** are used to adjust simulated lighting and temperature of skin of an avatar, respectively. As another example, avatar editing interface **780** includes a color palette **783** including a set of one or more colors and/or shades from which a color of the skin of the avatar is selected.

(219) In some embodiments, as illustrated in FIG. 7L1, avatar editing interface **780** includes a set of parameters **784**, such as shirt parameter **784a** and headwear parameter **784b**. In some embodiments, selecting a parameter allows for visual characteristics of one or more aspects of the avatar to be selected. With reference to FIG. 7M, for instance, selection of shirt parameter **784a** (e.g., a tap input **7051** or an air gesture corresponding to a location of parameter **784a**) causes

device **700** to display parameter menu **790** from which a user can select from any number of options for shirt parameter **784a** (e.g., options **790a-790c**). With reference to FIG. 7N, once an option has been selected (e.g., a tap input **705m** or an air gesture corresponding to a location of option **790b**), a user can select from styles **792** (e.g., **792a-792f**) of the selected option, and visual characteristics of the avatar are updated accordingly. Similarly, in some embodiments, selection of headwear parameter **784b** causes device **700** to display headwear options for headwear parameter **784b**, and selection of an option causes device **700** to display types for the selected option.

(220) While description is made herein with respect to parameters **784a** and **784b** corresponding to shirts and headwear, respectively, it will be appreciated that, in some embodiments, parameters of avatar editing interface **780** optionally corresponds to other/additional visual aspects of an avatar. By way of example, in some embodiments, parameters **784** are used to select one or more aspects of eyewear of an avatar (e.g., parameter **784a** corresponds to eyeglasses and parameter **784b** corresponds to eyepatches). In an example in which device **700** receives a user selection of parameter **784a** corresponding to eyeglasses, device **700** displays options for various designs of eyeglasses (e.g., frameless, thin frames, thick frames, etc.). Once device **600** receives a user selection of a design, device **700** displays various styles of the selected design as types **792** for selection by the user. In an example in which device **700** receives a user selection of eyepatches, device **700** displays options for various designs of eyepatches (e.g., left eye patch or right eye patch). Once device **600** receives a user selection of a design, device **700** displays various styles of the selected design as types **792** for selection by the user.

(221) In some embodiments, avatar editing interface **780** includes a set of parameters **786**. As shown, in some embodiments, parameters **786** are used to select one or more aspects of hair. By way of example, parameter **786a** corresponds to hair style, parameter **786b** corresponds to hair color, and parameter **786c** corresponds to hair highlights. In other embodiments, parameters **786** are used to select one or more aspects of accessibility features. By way of example, in some embodiments, parameter **786a** corresponds to hand prosthetics, parameter **786b** corresponds to hearing aids, and parameter **786c** corresponds to wheelchairs.

(222) In some embodiments, the techniques and user interface(s) described in FIG. 7L1 are provided by one or more of the devices described in FIGS. 1A-1P. FIG. 7L2 illustrates an embodiment in which avatar editing interface **X780** (e.g., as described in FIGS. 7L1-7N) is displayed on display module **X702** of head-mounted device (HMD) **X700**. In some embodiments, device **X700** includes a pair of display modules that provide stereoscopic content to different eyes of the same user. For example, HMD **X700** includes display module **X702** (which provides content to a left eye of the user) and a second display module (which provides content to a right eye of the user). In some embodiments, the second display module displays a slightly different image than display module **X702** to generate the illusion of stereoscopic depth.

(223) At FIG. 7L2, avatar editing interface **X780** includes live view **X781** of an avatar of a user of HMD **X700**. In some embodiments, HMD **X700** displays live view **X781**, which is updated in real-time, of avatar editing interface **X780** according to movement and/or mannerisms of the user of HMD **X700**, as detected by HMD **X700**. Avatar editing interface **X780** further includes various settings and/or parameters by which visual characteristics of the avatar are adjusted. As an example, avatar editing interface **X780** includes settings **X782**, which include a brightness setting **X782a** and a warmth setting **X782b**. Brightness setting **X782a** and warmth setting **X782b** are used to adjust simulated lighting and temperature of skin of an avatar, respectively. As another example, avatar editing interface **X780** includes a color palette **X783** including a set of one or more colors and/or shades from which a color of the skin of the avatar is selected.

(224) In some embodiments, as illustrated in FIG. 7L2, avatar editing interface **X780** includes a set of parameters **X784**, such as shirt parameter **X784a** and headwear parameter **X784b**. In some embodiments, selecting a parameter allows for visual characteristics of one or more aspects of the avatar to be selected. For instance, selection of shirt parameter **X784a** (e.g., a gaze and pinch

gesture, where gaze is represented by gaze indicator X705L, corresponding to a location of parameter X784a) causes HMD X700 to display parameter menu 790 from which a user can select from any number of options for shirt parameter X784a (e.g., options 790a-790c), as shown in FIG. 7M.

(225) In some embodiments, HMD X700 detects selection of shirt parameter X784a based on an air gesture performed by a user of HMD X700. In some embodiments, HMD X700 detects hands X750a and/or X750b of the user of HMD X700 and determines whether motion of hands X750a and/or X750b perform a predetermined air gesture corresponding to selection of shirt parameter X784a. In some embodiments, the predetermined air gesture selecting shirt parameter X784a includes a pinch gesture. In some embodiments, the pinch gesture includes detecting movement of finger X750c and thumb X750d toward one another. In some embodiments, HMD X700 detects selection of shirt parameter X784a based on a gaze and air gesture input performed by the user of HMD X700. In some embodiments, the gaze and air gesture input includes detecting that the user of HMD X700 is looking at shirt parameter X784a (e.g., for more than a predetermined amount of time) and hands X750a and/or X750b of the user of HMD X700 perform a pinch gesture.

(226) With reference to FIG. 7N, once an option has been selected (e.g., a tap input 705m or an air gesture corresponding to a location of option 790b), a user can select from styles 792 (e.g., 792a-792f) of the selected option, and visual characteristics of the avatar are updated accordingly. Similarly, in some embodiments, selection of headwear parameter 784b causes device 700 to display headwear options for headwear parameter 784b, and selection of an option causes device 700 to display types for the selected option.

(227) While description is made herein with respect to parameters X784a and X784b corresponding to shirts and headwear, respectively, it will be appreciated that, in some embodiments, parameters of avatar editing interface X780 optionally corresponds to other/additional visual aspects of an avatar. By way of example, in some embodiments, parameters X784 are used to select one or more aspects of eyewear of an avatar (e.g., parameter X784a corresponds to eyeglasses and parameter X784b corresponds to eyepatches). In an example in which HMD X700 receives a user selection of parameter X784a corresponding to eyeglasses, HMD X700 displays options for various designs of eyeglasses (e.g., frameless, thin frames, thick frames, etc.). Once HMD X700 receives a user selection of a design, HMD X700 displays various styles of the selected design as types 792 for selection by the user. In an example in which HMD X700 receives a user selection of eyepatches, HMD X700 displays options for various designs of eyepatches (e.g., left eye patch or right eye patch). Once HMD X700 receives a user selection of a design, HMD X700 displays various styles of the selected design as types 792 for selection by the user.

(228) In some embodiments, avatar editing interface X780 includes a set of parameters X786. As shown, in some embodiments, parameters X786 are used to select one or more aspects of hair. By way of example, parameter X786a corresponds to hair style, parameter X786b corresponds to hair color, and parameter X786c corresponds to hair highlights. In other embodiments, parameters X786 are used to select one or more aspects of accessibility features. By way of example, in some embodiments, parameter X786a corresponds to hand prosthetics, parameter X786b corresponds to hearing aids, and parameter X786c corresponds to wheelchairs.

(229) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 1B-1P can be included, either alone or in any combination, in HMD X700. For example, in some embodiments, HMD X700 includes any of the features, components, and/or parts of HMD 1-100, 1-200, 3-100, 6-100, 6-200, 6-300, 6-400, 11.1.1-100, and/or 11.1.2-100, either alone or in any combination. In some embodiments, display module X702 includes any of the features, components, and/or parts of display unit 1-102, display unit 1-202, display unit 1-306, display unit 1-406, display generation component 120, display screens 1-122a-b, first and second rear-facing display screens 1-322a, 1-322b, display 11.3.2-104, first and second display assemblies

1-120a, **1-120b**, display assembly **1-320**, display assembly **1-421**, first and second display sub-assemblies **1-420a**, **1-420b**, display assembly **3-108**, display assembly **11.3.2-204**, first and second optical modules **11.1.1-104a** and **11.1.1-104b**, optical module **11.3.2-100**, optical module **11.3.2-200**, lenticular lens array **3-110**, display region or area **6-232**, and/or display/display region **6-334**, either alone or in any combination. In some embodiments, HMD **X700** includes a sensor that includes any of the features, components, and/or parts of any of sensors **190**, sensors **306**, image sensors **314**, image sensors **404**, sensor assembly **1-356**, sensor assembly **1-456**, sensor system **6-102**, sensor system **6-202**, sensors **6-203**, sensor system **6-302**, sensors **6-303**, sensor system **6-402**, and/or sensors **11.1.2-110a-f**, either alone or in any combination. In some embodiments, input device **X703** includes any of the features, components, and/or parts of any of first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**, either alone or in any combination. In some embodiments, HMD **X700** includes one or more audio output components (e.g., electronic component **1-112**) for generating audio feedback (e.g., audio output), optionally generated based on detected events and/or user inputs detected by the HMD **X700**.

(230) With reference to FIG. **7N**, while displaying the avatar editing interface **780**, device **700** detects selection of save option **788**. In some embodiments, the selection of save option **788** is a tap gesture **705n** on save option **788**. In some embodiments, the selection of save option **788** is an air gesture, for instance, indicating a selection of save option **788**. In response to detecting selection of save option **788**, device **700** stores (e.g., locally stores and/or remotely stores) the selected configuration of the avatar for the user of device **700** for subsequent use in XR communication sessions. As shown in FIG. **7O**, further in response to detecting selection of setup affordance **772**, device **700** displays completion interface **795** indicating that the user has successfully created and/or updated the avatar of the user.

(231) In FIG. **7P**, a user of device **700** is participating in an XR communication session with a contact **712f** (“Ann”, FIG. **7B**) within XR environment **704**. In some embodiments, the XR communication session is a spatial communication session. Accordingly, in some embodiments, contact **712f** and/or the user of device **700** are represented in XR environment **704** by 3D representations (e.g., avatars). For example, as shown in FIG. **7P**, the user of device **700** is represented by representation **700A** (as shown in self preview **706A**) and contact **712f** is represented by representation **701A**.

(232) In some embodiments, the view of XR environment **704** for the user of device **700** is provided from the perspective of representation **700A** within XR environment **704**. Because this can preclude the user from otherwise viewing representation **700A**, device **700** displays self preview **706A** including a live view of representation **700A** in XR environment **704**. While self preview **706A** is shown as being located in a lower, righthand corner of display **702**, it will be appreciated that self preview **706A** is optionally displayed at any location on display **702**. By way of example, in some embodiments, self preview **706A** is located adjacent to a representation of a contact in the XR communication session. In some embodiments, self-preview **706A** is located, for instance, at a position **708A** proximate to representation **701A**.

(233) In some embodiments, participants represented by 3D representations in an XR environment have spatial agency. Accordingly, during the XR communication session, 3D representations optionally move within XR environment **704** such that 3D representations move relative to elements (e.g., table **704a** and couch **704b**) and/or other participants in XR environment **704**. In some embodiments, 3D representations move according to movement of corresponding devices. By way of example, 3D representation **700A** can move within XR environment **704** in response to movement of device **700**. In some embodiments, 3D representations move in a manner that corresponds to the movement of devices. If, for instance, device **700** first moves in a first direction (e.g., left) and thereafter moves in a second direction (e.g., right), 3D representation **700A** will move in the first and second directions within XR environment **704** in an analogous manner.

(234) In some embodiments, while participating in an XR communication session, device **700**

displays a set of controls **704A** for managing one or more aspects of the XR communication session, as shown in FIG. 7P. The set of controls **704A** includes a message option **704Aa**, an info option **704Ab**, a microphone option **704Ac**, an avatar option **704Ad**, a camera option **704Ae**, and a terminate option **704Af**. Message option **704Aa**, when selected, causes device **700** to display a message interface for sending messages to contact **712f**. Info option **704Ab**, when selected, causes device **700** to display an info interface corresponding to contact **712f**. Microphone option **704Ac**, when selected, toggles a state of (e.g., enables or disables) a microphone of device **700**. In some embodiments, disabling a microphone of device **700** precludes device **700** from providing audio during an XR communication session. Camera option **704Ae**, when selected, toggles a state of (e.g., enables or disables) a camera of device **700**. In some embodiments, disabling a camera of device **700** precludes device **700** from providing video (e.g., a video feed of a user of device **700** and/or movement of the representation of the user of device **700**) during an XR communication session. Terminate option **704Af**, when selected, causes device **700** to disconnect from the XR communication session.

(235) Avatar option **704Ad**, when selected, toggles (e.g., enables or disables) the use of 3D representations in XR environment **704**. For example, while displaying XR environment **704**, device **700** detects selection of avatar option **704Ad**. In some embodiments, the selection of avatar option **704Ad** is a tap gesture **705p** on avatar option **704Ad**. In some embodiments, the selection of avatar option **704Ad** is an air gesture, for instance, indicating a selection of avatar option **704Ad**. As shown in FIG. 7Q, in response to selection of avatar option **704Ad**, device **700** disables the use of 3D representations in XR environment **704**.

(236) In some embodiments, when toggling the use of 3D representations in XR environment **704**, device **700** transitions an XR communication session between spatial communication sessions and non-spatial communication sessions. Disabling the use of 3D representations causes device **700** to transition the XR communication session from a spatial communication session to a non-spatial communication session. Enabling the use of 3D representations causes device **700** to transition the XR communication session from a non-spatial communication session to a spatial communication session.

(237) In some embodiments, in a non-spatial communication session, participants in the XR communication session are represented by 2D representations. By way of example, as shown in FIG. 7Q, the user of device **700** is represented by 2D representation **710A** (as shown in self preview **706A**) and contact **712f** is represented by 2D representation **712A**.

(238) In some embodiments, 2D representations include a video feed (e.g., live video feed) of users. In some embodiments, if a video feed of a user is not available (e.g., a camera of a device is disabled), the 2D representation of the user instead includes an image (e.g., thumbnail) associated with the user, a monogram corresponding to the user, and/or another 2D representation. In some embodiments, users represented by 2D representations in an XR environment do not have spatial agency and are, optionally, positioned at one or more predetermined locations in XR environment **704**. In some embodiments, device **600** is configured to move a 2D representation of a remote participant in the XR environment based on user input received at device **700** (e.g., input to drag the representation from a first location to a second location). In some embodiments, device **600** is not configured to move a 3D representation of a remote participant in the XR environment based on user input received at device **700**.

(239) Additional descriptions regarding FIGS. 7A-7Q are provided below in reference to method **800** and method **900**, each of which is described with respect to FIGS. 7A-7Q.

(240) FIG. 8 is a flow diagram of an exemplary method **800** for managing live communication sessions, in accordance with some embodiments. In some embodiments, method **800** is performed at a computer system (e.g., computer system **101** in FIG. 1A, computer system **700**, and/or HMD **X700**) (e.g., a smartphone, tablet, and/or head-mounted device) that is in communication with a display generation component (e.g., display generation component **120** in FIGS. 1A, 3, and 4,

display **702**, and/or display **X702**) (e.g., a visual output device, a 3D display, a display having at least a portion that is transparent or translucent on which images can be projected (e.g., a see-through display), a projector, a heads-up display, and/or a display controller) and one or more sensors (e.g., a touch-sensitive surface, a gyroscope, an accelerometer, a motion sensor, a movement sensor, a microphone, an infrared sensor, a camera sensor, a depth camera, a visible light camera, an eye-tracking sensor, a gaze-tracking sensor, a physiological sensor, and/or an image sensor). In some embodiments, the method **800** is governed by instructions that are stored in a non-transitory (or transitory) computer-readable storage medium and that are executed by one or more processors of a computer system, such as the one or more processors **202** of computer system **101** (e.g., control **110** in FIG. **1A**). Some operations in method **800** are, optionally, combined and/or the order of some operations is, optionally, changed.

(241) The computer system (e.g., **700** and/or **X700**) displays (**802**), via the display generation component, representations (e.g., **712a-712g** and **714a-714i**) (e.g., static avatars, animated avatars, images, and/or monograms) of a plurality of users (e.g., users that are not operating the computer system (remote users) and/or users other than the user of the computer system).

(242) The computer system (e.g., **700** and/or **X700**) receives (**804**), via the one or more sensors, selection (e.g., **705b** and/or **711b**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of a representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) (e.g., a static avatar, an animated avatar, an image, and/or a monogram) of a respective user of the plurality of users.

(243) In response to (**806**) receiving selection of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user and in accordance with a determination that there is an ongoing (e.g., active and/or currently established) communication session (e.g., a video communication session, an audio communication session, an extended reality communication session, a spatial communication session, and/or a non-spatial communication session), the computer system (e.g., **700** and/or **X700**) displays (**808**), via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **724b** at FIG. **7C-1** and/or **X724b** at FIG. **7C-2**) to invite the respective user to join the ongoing communication session.

(244) In response to (**806**) receiving selection of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user and in accordance with a determination that there is no ongoing communication session, the computer system (e.g., **700** and/or **X700**) forgoes display (**810**) of the option to invite the respective user to join the ongoing communication session (e.g., as in menu **720** at FIG. **7C1** and/or menu **X720** at FIG. **7C2**). Conditionally displaying an option to invite the respective user to join the ongoing communication session enables the user of the computer system to invite the respective user with needing to navigate to a different user interface, thereby reducing the number of inputs needed to perform the invite operation.

(245) In some embodiments, in response to receiving selection of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user (e.g., independent of the determination whether there is an ongoing communication session), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **720a** and/or **724a** at FIG. **7C1** and/or **X720a** and/or **X724a** at FIG. **7C2**) to initiate a new spatial communication session with the respective user, and an option for additional features (e.g., **720b** and/or **724c** at FIG. **7C1** and/or **X720b** and/or **X724c** at FIG. **7C2**) (e.g., without displaying options for transmitting a textual message to the respective user and/or displaying additional information about the respective user). In some embodiments, while displaying the option (e.g., **720a** and/or **724a** at FIG. **7C1** and/or **X720a** and/or **X724a** at FIG. **7C2**) for additional features, the computer system (e.g., **700** and/or **X700**) receives selection (e.g., **705c** and/or **709d**) of the option (e.g., **720a** and/or **724a** at FIG. **7C1** and/or **x720a** and/or **x724a** at FIG. **7C2**) for additional features. In some embodiments, in response to receiving selection of the option for additional features, the computer system (e.g., **700** and/or **X700**) displays (e.g., by replacing display of the option to invite the respective user to join the ongoing communication session), via the display generation component (e.g., **702** and/or

X702), one or more options (e.g., 720c-720f at FIG. 7D) associated with the respective user (e.g., one or more options for communicating with the respective user such as by transmitting a textual message to the respective user and/or displaying additional information about the respective user). In some embodiments, a spatial communication session is a communication session with at least some (e.g., less than all, a plurality of, and/or all) representations of users participating in the communication session distributed in a 3D environment. Displaying the option to initiate a new spatial communication session with the respective user and an option to access additional features enables the user of the computer system to quickly access the option to initiate the new spatial communication session without cluttering the user interface, while still providing access to additional (and potentially less often used) features, thereby improving the man-machine interface.

(246) In some embodiments, in response to receiving selection of the representation of the respective user (e.g., independent of the determination whether there is an ongoing communication session), the computer system (e.g., 700 and/or X700) displays, via the display generation component (e.g., 702 and/or X702), an option (e.g., 720b at FIG. 7C1 and/or X720b at FIG. 7C2) for additional features (e.g., without displaying options for transmitting a textual message to the respective user and/or displaying additional information about the respective user). In some embodiments, while displaying the option (e.g., 720b at FIG. 7C1 and/or X720b at FIG. 7C2) for additional features, the computer system (e.g., 700 and/or X700) receives, via the one or more sensors, selection (e.g., 705c) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., 720b at FIG. 7C1 and/or X720b at FIG. 7C2) for additional features. In some embodiments, in response to receiving selection of the option (e.g., 720b at FIG. 7C1 and/or X720b at FIG. 7C2) for additional features, the computer system (e.g., 700 and/or X700) displays (e.g., by replacing display of the option to invite the respective user to join the ongoing communication session), via the display generation component (e.g., 702 and/or X702), an option (e.g., 720c at FIG. 7D) to initiate an audio communication session with the respective user (e.g., that does not include a live visual representation of the participants and/or that does not include a video component) (e.g., as part of the one or more options associated with the respective user). In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., 720c at FIG. 7D) to initiate an audio communication session with the respective user. In some embodiments, in response to receiving selection of the option (e.g., 720c at FIG. 7D) to initiate an audio communication session with the respective user, the computer system (e.g., 700 and/or X700) initiates an audio communication session (e.g., that does not include a live visual representation of the participants and/or that does not include a video component) with the respective user (e.g., and not with other users). Displaying an option to initiate an audio communication session enables the user of the computer system to start a communication session that does not include a live visual representation of the user without the need to initiate a video communication session and separately disabling the video portion, thereby reducing the number of inputs required to initiate the audio communication session.

(247) In some embodiments, the computer system initiates an audio communication session includes initiating an audio call (e.g., a voice call and/or a telephone call) using an external electronic device (e.g., a smart phone and/or a cellular phone) that is within a predetermined range (e.g., distance and/or wireless range) of the computer system (e.g., 700 and/or X700). In some embodiments, the option to initiate an audio communication session is displayed for respective users that do not have an account (or do not have an active account) with a particular online service (e.g., the user of the computer system has an account with the particular online service used for video and/or extended reality communications, but the respective user does not). Initiating the audio communication session via an audio call using an external electronic device enables the computer system to use the resources (e.g., cellular connection of and/or CPU processing of) the external computer system, thereby improving the functionality of the computer system while

reducing the workload of the computer system.

(248) In some embodiments, in response to receiving selection (e.g., **705c** and/or **711b**) of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user (e.g., independent of the determination whether there is an ongoing communication session), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features (e.g., without displaying options for initiating a process to send a message to the respective user and/or displaying additional information about the respective user). In some embodiments, while displaying the option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g., **705c**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **720b** and/or **X720b**) for additional features. In some embodiments, in response to receiving selection (e.g., **705c**) of the option (e.g., **720b** and/or **X720b**) for additional features, the computer system (e.g., **700** and/or **X700**) displays (e.g., by replacing display of the option to invite the respective user to join the ongoing communication session), via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **720d**) to initiate a process to send a message (e.g., that does not include live transmission of audio and/or video) to the respective user (e.g., as part of the one or more options associated with the respective user). In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., **705d**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **720d**) to initiate a process to send a message to the respective user. In some embodiments, in response to receiving selection (e.g., **705d**) of the option (e.g., **720d**) to initiate a process to send a message to the respective user, the computer system (e.g., **700** and/or **X700**) initiates a process to send a message (e.g., **730** at FIG. 7E and/or **750** at FIG. 7H) (e.g., that does not include a live visual representation of the participants and/or that does not include a video component) to the respective user (e.g., without sending the message to other users). In some embodiments, initiating a process to send the message to the respective user includes displaying a user interface that includes a conversation between the user of the computer system and the respective user, displaying a keyboard, and/or displaying a text entry field for entering the message. Providing an option, via the additional features selection, to initiate a process to send a message to the respective user enables to the user of the computer system to quickly initiate the process without needing to specify the recipient, thereby reducing the number of inputs required to send the message.

(249) In some embodiments, in response to receiving selection (e.g., **705c** and/or **711b**) of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user (e.g., independent of the determination whether there is an ongoing communication session), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features (e.g., without displaying options for initiating a process to send a message to the respective user and/or displaying additional information about the respective user). In some embodiments, while displaying the option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features, the computer system receives, via the one or more sensors, selection (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features. In some embodiments, in response to receiving selection of the option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features, the computer system displays (e.g., by replacing display of the option to invite the respective user to join the ongoing communication session), via the display generation component, an option (e.g., **720e**) to display additional information about the respective user (e.g., without displaying additional information about other users) (e.g., as part of the one or more options associated with the respective user). In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., **707d**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **720e**) to display additional

information about the respective user. In some embodiments, in response to receiving selection (e.g., **707d**) of the option (e.g., **720e**) to display additional information about the respective user, the computer system (e.g., **700** And/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), additional information (e.g., **740** at FIG. 7F) (e.g., prior communication history with the respective user, a phone number of the respective user, and/or an email address of the respective user) (e.g., that was not displayed when the option for additional features was selected and/or was not displayed when the option for additional information was selected) about the respective user (e.g., without displaying additional information about other users). Providing the user with additional information about the respective user provides the user of the computer system with feedback about the respective user and/or devices of the respective user, thereby providing improved visual feedback.

(250) In some embodiments, in response to receiving selection (e.g., **705c** and/or **711b**) of the representation (e.g., **712e**, **X712e**, **714g**, and/or **X714g**) of the respective user (e.g., independent of the determination whether there is an ongoing communication session), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features (e.g., without displaying options for initiating a process to send a message to the respective user and/or displaying additional information about the respective user). In some embodiments, while displaying the option (e.g., **720b**, **X720b**, **724c**, and/or **X724c**) for additional features, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g., **705c**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option for additional features. In some embodiments, in response to receiving selection (e.g., **705c**) of the option (e.g., **720b** and/or **X720b**) for additional features, the computer system displays (e.g., by replacing display of the option to invite the respective user to join the ongoing communication session), via the display generation component, an option (e.g., **720f**) to remove the respective user (e.g., without removing other users) from favorites (e.g., a list or group of favorite users) (e.g., as part of the one or more options associated with the respective user). In some embodiments, removing the respective user from favorites includes ceasing to display the representation of the respective user as part of the representations (e.g., static avatars, animated avatars, images, and/or monograms) of the plurality of users (e.g., which are optionally displayed as part of a home user interface). In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **720f**) to remove the respective user from favorites (e.g., **712**). In some embodiments, in response to receiving selection of the option (e.g., **720f**) to remove the respective user from favorites (e.g., **712**), the computer system (e.g., **700** and/or **X700**) initiates a process to remove the respective user from favorites (e.g., requesting confirmation to remove the respective user from favorites and/or removing the respective user from favorites). Initiating a process to remove the respective user from favorites enables the user to limit the users that are accessible via the favorites and/or the home user interface, thereby reducing visual cluttering and enabling other users to be added to favorites, thereby providing improved visual feedback.

(251) In some embodiments, in response to receiving selection (e.g., **711b**) of the representation (e.g., **714g** and/or **X714g**) of the respective user and in accordance with a determination that there is an ongoing (e.g., active and/or currently established) communication session (e.g., a video communication session, an audio communication session, an extended reality communication session, a spatial communication session, and/or a non-spatial communication session), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and concurrently with the option (e.g., **724b** and/or **X724b**) to invite the respective user to join the ongoing communication session, an option (e.g., **724a** and/or **X724a**) to initiate a process to start a new communication session with the respective user. In some embodiments, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g.,

709c) (e.g., via a touchinput on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **724a** and/or **X724a**) to initiate a process to start a new communication session with the respective user. In some embodiments, in response to receiving selection (e.g., **709c**) of the option (e.g., **724a** and/or **X724a**) to initiate the process to start a new communication session with the respective user, the computer system (e.g., **700** and/or **X700**) initiates a process to end the ongoing communication session (e.g., **740** at FIG. 7G) and start the new communication session with the respective user. In some embodiments, in response to receiving selection of the option to initiate the process to start the new communication session with the respective user, the computer system automatically (e.g., without requiring and/or receiving additional input from the user and/or without request user confirmation) ends the ongoing communication session and starts the new communication session with the respective user. Providing an option to start a new communication session with the respective user enables the computer system to both end the ongoing communication session and start the new communication session without requiring separate user inputs directed to ending the ongoing communication session and starting the new communication session, thereby reducing the number of inputs required to perform the operations.

(252) In some embodiments, during the process (e.g., **740** at FIG. 7G) to start the new communication session with the respective user, the computer system (e.g., **700** and/or **X700**) prompts (e.g., **742**) (e.g., via audio using a speaker and/or via display using the display generation component) to confirm ending the ongoing communication session. In some embodiments, the computer system (e.g., **700** and/or **X700**) receives (e.g., while displaying a prompt to confirm ending the ongoing communication session), via the one or more sensors, confirmation to end the ongoing communication session. In some embodiments, in response to receiving confirmation to end the ongoing communication session, the computer system ends the ongoing communication session (and, optionally, starting the new communication session with the respective user). Requesting confirmation from the user of the computer system to end the ongoing communication session enables the computer system to avoid the user unintentionally ending the ongoing communication session, thereby improving the man-machine interface.

(253) In some embodiments, the representations (e.g., static avatars, animated avatars, images, and/or monograms) of the plurality of users are displayed as part of a home user interface (e.g., as shown in FIGS. 7B-7D) (e.g., that optionally includes representations of contacts recently communicated with) and displaying the option (e.g., **724b** and/or **X724b**) to invite the respective user to join the ongoing communication session and/or displaying the one or more options associated with the respective user (e.g., **720a-720b**, **X720a-X720b**, **724a-724c**, and/or **X724a-X724c**) includes obscuring (e.g., partially blocking display of, blurring, and/or otherwise partially obscuring) the home user interface. In some embodiments, the home user interface includes a plurality of user interface objects for displaying respective applications (e.g., a first user interface object that, when activated, causes display of a user interface of a first application and a second user interface object that, when activated, causes display of a user interface of a second application that is different from the first application). In some embodiments, in response to detecting a respective user input (e.g., detecting a press of a physical button and/or detecting a respective gesture, such as an air gesture), the computer system displays the home user interface (e.g., without regard to what the computer system is displaying when the respective user input is received). In some embodiments, subsequent to the computer system exiting (e.g., waking) from a low power mode and/or receiving user inputs that unlock the computer system, the computer system automatically displays the home user interface. Continuing to display the home user interface (while obscured) provides the user with context about the content the user is accessing, including information (e.g., name and/or contact information) about the respective user.

(254) In some embodiments, the one or more options associated with the respective user includes an option (e.g., **720d**) to initiate a process to send a message (e.g., that does not include live transmission of audio and/or video) to the respective user (e.g., as part of the one or more options

associated with the respective user). In some embodiments, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g., **705d**) of the option (e.g., **720d**) to initiate a process to send a message to the respective user. In some embodiments, in response to receiving (e.g., **705d**) of the option (e.g., **720d**) to initiate a process to send a message to the respective user (and, optionally, in accordance with a determination that a message from the respective user was not being displayed when selection of the representation of the respective user was received), the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), a messaging user interface (e.g., **730** at FIG. 7E) (for messaging with the respective user) with a first appearance (e.g., a messaging user interface of a first size and/or a messaging user interface that includes a displayed keyboard) without displaying the home user interface. Displaying the messaging user interface with the first appearance and without displaying the home user interface provides the user with feedback that the messaging user interface is in a first state, thereby providing the user with improved visual feedback.

(255) In some embodiments, the one or more options associated with the respective user includes an option (e.g., **718** and/or **X718**) to initiate a process to send a message (e.g., that does not include live transmission of audio and/or video) to the respective user (e.g., as part of the one or more options associated with the respective user). In some embodiments, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g., **707c**) of the option (e.g., **718** and/or **X718**) to initiate a process to send a message to the respective user. In some embodiments, in response to receiving selection (e.g., **707c**) of the option (e.g., **718** and/or **X718**) to initiate a process to send a message to the respective user (and, optionally in accordance with a determination that a message from the respective user was being displayed when selection of the representation of the respective user was received), the computer system (e.g., **700** and/or **X700**) concurrently displays, via the display generation component, a messaging user interface (e.g., **750**) (for messaging with the respective user) with a second appearance (e.g., a messaging user interface of a second size that is smaller than the first size and/or a messaging user interface that does not include a displayed keyboard) (e.g., that is different from the first appearance) and at least a portion of the home user interface (e.g., as shown in FIG. 7H) (e.g., displaying an obscured home user interface). Displaying the messaging user interface with the second appearance and with a portion of the home user interface provides the user with feedback that the messaging user interface is in a second state, thereby providing the user with improved visual feedback.

(256) In some embodiments, the home user interface is not user-moveable and wherein the messaging user interface (e.g., **750**) (e.g., with the first appearance and/or with the second appearance) is user-moveable. Enabling the user to move the messaging user interface without enabling the user to move the home user interface provides the user with feedback about which elements are part of the home user interface and which elements are not, thereby providing the user with improved visual feedback.

(257) In some embodiments, displaying, via the display generation component (e.g., **702** and/or **X702**), representations (e.g., **712a-712g** and **714a-714i**) of the plurality of users includes displaying, via the display generation component (e.g., **702** and/or **X702**), a first group (e.g., **712**) of a first plurality of representations of a first plurality of users, wherein the first plurality (e.g., **712a-712g**) of users is selected to be included as part of the representations of the plurality of users independent of recency of communication between a user of the computer system and the first plurality of users (e.g., included to be displayed based on being manually selected as part of favorite contacts and/or based on frequency of communication). In some embodiments, displaying, via the display generation component, representations (e.g., **712a-712g** and **714a-714i**) of the plurality of users includes displaying, via the display generation component (e.g., **702** and/or **X702**), a second group (e.g., **714**) of a second plurality of representations of a second plurality of users, wherein the second plurality (e.g., **714a-714i**) of users is selected to be included as part of the plurality of users based on recency of communication between the user of the computer system

and the second plurality of users (e.g., included to be displayed based on being the most recent users communicated with). In some embodiments, an order of the second plurality of representations of the second plurality of users is based on recency of communication between the user of the computer system and the second plurality of users. In some embodiments, displaying, via the display generation component, representations of the plurality of users includes: displaying, via the display generation component, a first group of a first plurality of representations of a first plurality of users, wherein the first plurality of users is selected to be included as part of the representations of the plurality of users independent of recency of communication between a user of the computer system and the first plurality of users and a second group of a second plurality of representations of a second plurality of users, wherein: in accordance with a determination that recent communications by the user of the computer system includes communications with a first set of one or more users without including communications with a second set of one or more users, the second plurality of users includes the first set of one or more users without including the second set of one or more users, and in accordance with a determination that recent communications by the user of the computer system includes communications with the second set of one or more users without including communications with the first set of one or more users, the second plurality of users includes the second set of one or more users without including the first set of one or more users. Grouping the first plurality of users together and the second plurality of users together enables the computer system to provide the user with feedback about which users were selected independent of recency of communication and which users were included based on recency of communication, thereby providing improved visual feedback.

(258) In some embodiments, the recency of communication between a user of the computer system (e.g., **700** and/or **X700**) and the second plurality of users is based on a plurality of modes of communication (e.g., textual messaging, phone calls, and/or a communication session (e.g., a video communication session, an audio communication session, an extended reality communication session, a spatial communication session, and/or a non-spatial communication session)). Grouping the second plurality of users together based on recency of communication using a plurality of modes of communication enables the computer system to group recent contacts regardless of how the communication occurred, thereby providing improved visual feedback.

(259) In some embodiments, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and concurrently with the option (e.g., **724b** and/or **X724b**) to invite the respective user to join the ongoing communication session and/or the one or more options associated with the respective user (e.g., **724a**, **X724a**, **724c**, and/or **X724c**), an indication (e.g., **714f** and/or **X714f**) of recent communication activity between a user of the computer system and the respective user (e.g., information about a recent call or communication, information about an active call or communication, and/or information about recent messages). Displaying an indication of recent communication activity along with the one or more options enables the user to see what recent communication method was used and quickly select a communication method for another communication session, thereby reducing the number of inputs required to initiate the appropriate type of communication session.

(260) In some embodiments, the one or more options (e.g., **720c-720f**) associated with the respective user includes an option (e.g., **724a** and/or **X724a**) to initiate a spatial communication session (e.g., a communication session with at least some (e.g., less than all, a plurality of, and/or all) representations of users participating in the communication session distributed in a 3D environment) with the respective user. In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., **709c**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **724a** and/or **X724a**) to initiate a spatial communication session with the respective user. In some embodiments, in response to receiving selection (e.g., **709c**) of the option (e.g., **724a** and/or **X724a**) to initiate a spatial communication session with the respective user, the computer system (e.g., **700** and/or **X700**) initiates a spatial

communication session with the respective user (e.g., such as in FIG. 7P). Providing an option to initiate a spatial communication session with the respective user enables the computer system to start the communication session without requiring separate user inputs directed to selecting the user with which to participate in the communication session, thereby reducing the number of inputs required to perform the operations.

(261) In some embodiments, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and concurrently with the representations (e.g., **712a-712g** and **714a-714i**) of the plurality of users, an option (e.g., **715**) to preview and/or edit an avatar of a user of the computer system. In some embodiments, the computer system (e.g., **700** and/or **X700**) receives, via the one or more sensors, selection (e.g., **713b**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **715**) to preview and/or edit the avatar of the user of the computer system. In some embodiments, in response to receiving selection (e.g., **713b**) of the option (e.g., **715**) to preview and/or edit the avatar of the user of the computer system, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), a user interface (e.g., **760**) for previewing (e.g., via an avatar self-view that moves in conjunction with movement of the user) and/or editing the avatar of the user of the computer system. Displaying a user interface to preview and/or edit the avatar of the user of the computer provides the user with visual feedback about the visual characteristics of the avatar and the editing that can be done, thereby providing improved visual feedback.

(262) In some embodiments, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and concurrently with the representations (e.g., **712a-712g** and **714a-714i**) of the plurality of users, a first indication (e.g., 9:41 at **714e** at FIG. 7B) (e.g., display adjacent to the representation of the first user or displayed overlapping the representation of the first user) of a most recent communication (e.g., a text message, an established call, and/or a missed call) between a user of the computer system and a first user of the plurality of users and a second indication (e.g., 2:21 at **714f** at FIG. 7B) (e.g., display adjacent to the representation of the second user or displayed overlapping the representation of the second user) of a most recent communication (e.g., a text message, an established call, and/or a missed call) between the user of the computer system (e.g., **700** and/or **X700**) and a second user, different from the first user, of the plurality of users. Displaying an indication of a most recent communication between the user of the computer system and other respective users provides the user with visual feedback about the recent communications, thereby providing improved visual feedback.

(263) In some embodiments, a first representation, corresponding to a first user, of the representations of the plurality of users includes a recent message (e.g., **716b**) (e.g., a portion of a recent message, a received textual message, and/or received image) from the first user. In some embodiments, a second representation, corresponding to a second user, of the representations of the plurality of users includes a recent message (e.g., received textual message and/or received image) from the second user. Displaying a recent message from the first user provides the user of the computer system feedback about the recent message, thereby providing enhanced visual feedback.

(264) In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., **707b**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the recent message (e.g., **716b**) from the first user; and in response to receiving selection (e.g., **707b**) of the recent message (e.g., **716b**) from the first user, displays, via the display generation component (e.g., **702** and/or **X702**), an option (e.g., **718** at FIG. 7C1 and/or **X718** at FIG. 7C2) to reply to the recent message. In some embodiments, in response to receiving selection of the recent message from the first user, the display of the recent message expands to display additional content from the recent message from the first user. Displaying an option to reply to the recent message in response to receiving selection of the recent message enables the user of the computer system to quickly reply to the message without having to first open a separate application, thereby reducing the

number of inputs required to reply to the message.

(265) In some embodiments, the computer system receives, via the one or more sensors, selection (e.g., **707c**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **718** and/or **X718**) to reply to the recent message from the first user. In some embodiments, in response to receiving selection (e.g., **707c**) of the option (e.g., **718** and/or **X718**) to reply to the recent message from the first user, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), a user interface (e.g., **750**) (e.g., a messages user interface, a keyboard for entering a message, a text entry field for entering a message) for replying to the recent message from the first user. Displaying an option to reply to the recent message in response to receiving selection of the recent message enables the user of the computer system to quickly reply to the message without having to first open a separate application, thereby reducing the number of inputs required to reply to the message.

(266) In some embodiments, the representations (e.g., **712a-712g** and **714a-714i**) (e.g., static avatars, animated avatars, images, and/or monograms) of the plurality of users are displayed as part of a home user interface (e.g., as shown in FIGS. 7B-7D) (e.g., that optionally includes representations of contacts recently communicated with). In some embodiments, the home user interface (including the representations of the plurality of users) is displayed in response to detecting activation of a hardware button (e.g., **703**) (e.g., a depressible button, a capacitive button, and/or a button that is not displayed by the display generation component). Displaying the home user interface in response to detecting activation of the hardware button enables the user to quickly access the home user interface (e.g., regardless of the content displayed via the display generation component), thereby reducing the number of inputs required to access the home user interface.

(267) In some embodiments, aspects/operations of methods **800**, **900**, **1100**, and/or **1300** may be interchanged, substituted, and/or added between these methods. For example, the home screen of FIG. 7B is the same home screen of FIG. 10A. For another example, the real-time communication session of FIG. 10C is the same as the real-time communication session of FIG. 12A. For brevity, these details are not repeated here.

(268) FIG. 9 is a flow diagram of an exemplary method **900** for providing avatars in live communication sessions, in some embodiments. In some embodiments, method **900** is performed at a computer system (e.g., computer system **101** in FIG. 1A, computer system **700**, and/or HMD **X700**) (e.g., a smartphone, tablet, and/or head-mounted device) that is in communication with a display generation component (e.g., display generation component **120** in FIGS. 1A, 3, and 4, display **702**, and/or display **X702**) (e.g., a visual output device, a 3D display, a display having at least a portion that is transparent or translucent on which images can be projected (e.g., a see-through display), a projector, a heads-up display, and/or a display controller) and one or more sensors (e.g., a touch-sensitive surface, a gyroscope, an accelerometer, a motion sensor, a movement sensor, a microphone, an infrared sensor, a camera sensor, a depth camera, a visible light camera, an eye-tracking sensor, a gaze-tracking sensor, a physiological sensor, and/or an image sensor). In some embodiments, the method **900** is governed by instructions that are stored in a non-transitory (or transitory) computer-readable storage medium and that are executed by one or more processors of a computer system, such as the one or more processors **202** of computer system **101** (e.g., control **110** in FIG. 1A). Some operations in method **900** are, optionally, combined and/or the order of some operations is, optionally, changed.

(269) The computer system (e.g., **700** and/or **X700**) displays (**902**), via the display generation component (e.g., **702** and/or **X702**), a communication user interface for communicating with other users in a real-time communication session, wherein during the real-time communication session a user of the computer system is represented by an avatar that moves, during the real-time communication session, in accordance with (e.g., in conjunction with and/or based on) movement, detected by the one or more sensors, of the user of the computer system (e.g., one or more cameras of the computer system detect the movements, such as head, eye, mouth, arm, and/or hand

movements, of the user and the avatar moves in accordance with the detected movement).

(270) While displaying the communication user interface (e.g., **760** and/or **770**), the computer system displays (**904**), via the display generation component, a selectable user interface object (e.g., **762**, **764**, **768**, and/or **772**).

(271) The computer system (e.g., while concurrently displaying the communication user interface and selectable user interface object, or while not concurrently displaying the communication user interface and selectable user interface object) detects (**906**), via the one or more sensors, one or more inputs that include a selection input directed to the selectable user interface object (e.g., **762**, **764**, **768**, and/or **772**). In some embodiments, at least one of the one or more inputs is detected while concurrently displaying the communication user interface and selectable user interface object (e.g., the selection input directed to the selectable user interface object and/or a different input of the one or more inputs).

(272) In response to detecting the one or more inputs that include the selection input directed to the selectable user interface object (e.g., **762**, **764**, **768**, and/or **772**), the computer system (e.g., **700** and/or **X700**) concurrently displays (**908**), via the display generation component, an avatar editing user interface (**910**) (e.g., **760**, **780**, and/or **X780**) that includes the avatar (e.g., show on left side of **780** and/or **X780**) representing the user of the computer system (e.g., **700** and/or **X700**) and one or more options (**912**) (e.g., **782**, **X782**, **784**, **X784**, **786**, **X786**, and/or **790**) to modify an appearance of the avatar (e.g., show on left side of **780** and/or **X780**) representing the user of the computer system (e.g., **700** and/or **X700**). Displaying an avatar editing user interface, including the avatar and options to modify the appearance of the avatar, in response to the one or more inputs provides the user with visual feedback about the state of the computer system, and in particular the appearance of the avatar and the options available to modify the appearance of the avatar, thereby providing improved visual feedback.

(273) In some embodiments, the real-time communication session is an extended reality communication session that is conducted in an extended reality environment. In some embodiments, the communication user interface (e.g., as shown in FIGS. 7P and/or 7Q) is displayed in the extended reality environment. In some embodiments, the avatar editing user interface (e.g., **760**, **780**, and/or **X780**) is displayed in the extended reality environment. In some embodiments, the user can traverse the extended reality environment to view the communication user interface and/or the avatar editing user interface from different viewpoints from within the extended reality environment. Displaying the communication user interface and the avatar editing user interface in the extended reality environment provides the user with feedback about the communication session and the avatar being used, thereby providing improved visual feedback.

(274) In some embodiments, subsequent to displaying the selectable user interface object (e.g., **762**, **764**, **768**, and/or **772**) (and/or the avatar editing user interface), the computer system (e.g., **700** and/or **X700**) participates in a communication session using the avatar (e.g., **700A**) representing the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, the selectable user interface object and/or the avatar editing user interface are displayed prior to the user entering a communication session, thereby providing the user an opportunity to modify the appearance of the avatar representing the user of the computer system. Displaying the selectable user interface objection prior to the user participating in the communication session using the avatar provides the user with an opportunity to edit the avatar before participating in the communication session, thereby reducing the need to navigate user interfaces to modify the avatar, and thus reducing the number of inputs required. In some embodiments, the computer system receives users input (e.g., via voice input, touch input, gestures, air gestures, gaze, and/or button activation) requesting to initiate a communication session. In some embodiments, in response to receiving user input requesting to initiate the communication session, the computer system displays the selectable user interface object and/or the avatar editing user interface object. In some embodiments, after (or without) receiving user input modifying the appearance of the avatar representing the user of the

computer system, the computer system receives user input (e.g., via voice input, touch input, gestures, air gestures, gaze, and/or button activation) to proceed with initiating the communication session and, in response to receiving the user input to proceed with initiating the communication session, initiates the communication session.

(275) In some embodiments, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and concurrently with the selectable user interface object (e.g., **762**, **764**, **768**, and/or **772**), an option to initiate a communication session (e.g., a video communication session, an audio communication session, an extended reality communication session, a spatial communication session, and/or a non-spatial communication session). In some embodiments, the computer system (e.g., **700** and/or **X700**) detects, via the one or more sensors, a selection input directed to the option to initiate a communication session. In some embodiments, in response to detecting the selection input directed to the option to initiate a communication session, the computer system initiates a communication session. Displaying the option to initiate the communication session concurrently with the selectable user interface object enables the user to alternatively participate in a communication session or modify the visual characteristics of the avatar, thereby reducing the number of inputs required.

(276) In some embodiments, the selectable user interface object is displayed during an ongoing communication session (e.g., at FIG. 7P) (e.g., a video communication session, an audio communication session, an extended reality communication session, a spatial communication session, and/or a non-spatial communication session). Displaying the selectable user interface object during the ongoing communication session enables the user to participate in the communication session and have the option to modify the visual characteristics of the avatar, thereby reducing the number of inputs required.

(277) In some embodiments, the computer system detects, via the one or more sensors, input (e.g., touch input, gestures, air gestures, gaze, and/or button activation) directed to the one or more options (e.g., **782**, **X782**, **784**, **X784**, **786**, **X786**, and/or **790**) to modify the appearance of the avatar (e.g., as shown in FIG. 7M) representing the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, in response to detecting input directed to the one or more options (e.g., **782**, **X782**, **784**, **X784**, **786**, **X786**, and/or **790**) to modify the appearance of the avatar representing the user of the computer system (e.g., **700** and/or **X700**), the computer system (e.g., **700** and/or **X700**) modifies the appearance of the avatar (e.g., as in FIGS. 7L1-7N), wherein modifying the appearance of the avatar includes editing the avatar. Modifying the appearance of the avatar by editing the avatar provides the user with visual feedback about the modifications made to the avatar, thereby providing the user with improved visual feedback.

(278) In some embodiments, a first option (e.g., **792**) (e.g., accessories and/or lighting) of the avatar (e.g., as shown in FIG. 7M) representing the user of the computer system is editable via the avatar editing user interface and a second option (e.g., hair color, skin color, and/or eye color) of the avatar representing the user of the computer system is not editable via the avatar editing user interface. In some embodiments, the second option of the avatar is editable via a different user interface. Limiting the options of the avatar that are editable using the avatar editing user interface reduces the complexity of the avatar editing user interface, thereby improving the man-machine interface.

(279) In some embodiments, editing the avatar representing the user of the computer system (e.g., **700** and/or **X700**) includes adding eyewear (e.g., glasses with different sizes, shapes, and/or frame type) to the avatar representing the user of the computer system (e.g., **700** and/or **X700**). Adding eyewear to the avatar enables the user to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(280) In some embodiments, the one or more options (e.g., **782**, **X782**, **784**, **X784**, **786**, **X786**, and/or **790**) to modify the appearance of the avatar (e.g., as shown in FIG. 7M) representing the

user of the computer system (e.g., **700** and/or **X700**) includes an option for a first eyewear template and an option for a second eyewear template that is different from the first eyewear template. In some embodiments, the first eyewear template is a first shape and the second eyewear template is a second shape, thereby enabling the user to select different types of glasses for the avatar (and then, optionally, selecting a color for the glasses). Providing eyewear templates enables the user to select a style of eyewear and to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(281) In some embodiments, editing the avatar (e.g., as shown in FIG. 7M) representing the user of the computer system (e.g., **700** and/or **X700**) includes adding one or more accessibility options (e.g., eye patch, prosthetic, hearing aid, and/or wheelchair) to the avatar representing the user of the computer system. Providing accessibility options for modifying the avatar enables the user to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(282) In some embodiments, adding one or more accessibility options to the avatar (e.g., as shown in FIG. 7M) representing the user of the computer system (e.g., **700** and/or **X700**) includes adding an accessibility option (e.g., an eye patch and/or a prosthetic eye) to a first (e.g., left) eye of the avatar without adding an accessibility option to the second (e.g., right) eye of the avatar. Enabling the user to add an accessibility option to a first or second eye of the avatar enables the user to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(283) In some embodiments, the one or more options include one or more options to change simulated lighting (e.g., **782** at FIG. 7M). In some embodiments, the computer system (e.g., **700** and/or **X700**) detects, via the one or more sensors, input directed to the one or more options to change simulated lighting (e.g., **782** at FIG. 7M). In some embodiments, in response to detecting input directed to the one or more options to change simulated lighting, the computer system modifies the appearance of the avatar representing the user of the computer system, wherein modifying the appearance of the avatar includes changing simulated lighting (e.g., simulated lighting in an extended reality environment). Enabling the user to change the simulated lighting that lights the avatar enables the user to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(284) In some embodiments, changing simulated lighting includes changing exposure settings (e.g., **782a** and/or **X782a**). In some embodiments, changing exposure settings directly changes the appearance of the avatar and/or changes the processing of the image data used to generate the avatar (e.g., increasing the exposure of image data and generating the avatar based on the modified image data). In some embodiments, changing exposure settings helps to correct errors in capturing skin tone due to challenging lighting in an environment in which image data (e.g., of the user of the computer system) was captured to enroll the avatar. Enabling the user to change the expose settings for the simulated lighting enables the user to modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(285) In some embodiments, changing simulated lighting includes changing color temperature settings (e.g., **782b** and/or **X782b**). In some embodiments, changing color temperature settings directly changes the appearance of the avatar and/or changes the processing of the image data used to generate the avatar (e.g., changing the color temperature of the image data and generating the avatar based on the modified image data). In some embodiments, changing color temperature settings helps to correct errors in capturing skin tone due to challenging lighting in an environment in which image data (e.g., of the user of the computer system) was captured to enroll the avatar. Enabling the user to change color temperature settings for the simulated lighting enables the user to

modify the avatar to more closely resemble the visual appearance of the user, thereby making the avatar a more accurate representation of the user and providing improved visual feedback.

(286) In some embodiments, the one or more options include one or more options (e.g., **762** and/or **764**) to change a fidelity of the avatar representing the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, the computer system (e.g., **700** and/or **X700**) detects, via the one or more sensors, input directed to the one or more options (e.g., **762** and/or **764**) to change the fidelity of the avatar representing the user of the computer system. In some embodiments, in response to detecting input directed to the one or more options to change the fidelity of the avatar representing the user of the computer system, the computer system (e.g., **700** and/or **X700**) modifies the fidelity of the avatar (e.g., changing how life-like the avatar appears and/or changing the number of features of the avatar). Changing the fidelity of the avatar enables the user of the computer system to change how closely the avatar reflects the visual appearance of the user, thereby allowing the user to quickly modify the avatar to look less like the user without needing to manually change distinct visual characteristics of the avatar, thereby reducing the number of inputs required.

(287) In some embodiments, the avatar representing the user of the computer system (e.g., **700** and/or **X700**) is a simulated three-dimensional avatar. In some embodiments, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**) and during the real-time communication session while the user is represented by the avatar that moves in accordance with (e.g., in conjunction with and/or based on) movement of the user of the computer system (e.g., **700** and/or **X700**), an option (e.g., **704Ad** at FIG. 7P) to cease use (e.g., cease display of at the computer system and/or cease display of at participant devices) of the avatar in the real-time communication session. In some embodiments, the computer system detects, via the one or more sensors, selection (e.g., **705p**) (e.g., via a touch input on a touch-sensitive surface and/or via an air gesture) of the option (e.g., **704Ad** at FIG. 7P) to cease use of the avatar in the real-time communication session. In some embodiments, in response to detecting selection (e.g., **705p**) of the option (e.g., **704Ad** at FIG. 7P) to cease use of the avatar in the real-time communication session, the computer system ceases use of the avatar in the real-time communication session (e.g., switching to using a static image, a two-dimensional avatar, and/or a monogram). Providing an option to cease using the avatar in the real-time communication session enables the user to quickly stop other participants from seeing the avatar without the need to navigate numerous user interfaces, thereby reducing the number of inputs needed.

(288) In some embodiments, the avatar editing user interface (e.g., **760**, **780**, and/or **X780**) includes one or more avatar management options (e.g., **768**). Providing one or more avatar management options as part of the avatar editing user interface enables the user to quickly manage avatars without the need to navigate numerous user interfaces, thereby reducing the number of inputs needed.

(289) In some embodiments, the one or more avatar management options (e.g., **768**) includes an option (e.g., **768b**) to create a new avatar representing the user of the computer system. In some embodiments, the computer system detects, via the one or more sensors, selection (e.g., **705j**) of the option (e.g., **768b**) to create a new avatar representing the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, in response to detecting selection (e.g., **705j**) of the option (e.g., **768b**) to create a new avatar representing the user of the computer system (e.g., **700** and/or **X700**), the computer system (e.g., **700** and/or **X700**) initiates a process (e.g., displays setup interface **770**) to create a new avatar representing the user of the computer system. In some embodiments, initiating the process to create a new avatar representing the user of the computer system includes using the computer system to capture information about one or more physical characteristics of the user of the computer system (e.g., data (e.g., image data, sensor data, and/or depth data) that represents a size, shape, position, pose, color, depth, and/or other characteristics of one or more body parts and/or features of body parts of the user) using a first sensor (e.g., via the

one or more cameras) that is optionally positioned on a same side of the computer system as a first display generation component of the one or more display generation components and prompting (e.g., a visual prompt displayed by the first display generation component, an audio prompt output via a speaker of the computer system, and/or a haptic prompt) the user of the computer system to move a position of a head of the user relative to the computer system. In some embodiments, the computer system outputs feedback (e.g., a non-visual indication, one or more audio indications, and/or one or more haptic indications) confirming that a threshold (e.g., sufficient) amount of information about the one or more physical characteristics (e.g., facial features, facial expressions, and/or body features) of the user has been captured. In some embodiments, after capturing (e.g., during the enrollment process) information about the one or more physical characteristics (e.g., data (e.g., image data, sensor data, and/or depth data) that represents a size, shape, position, pose, color, depth, and/or other characteristics of one or more body parts and/or features of body parts of the user) of the user of the computer system, the computer system displays a representation of the user generated based on information captured about the one or more physical characteristics of the user. Providing an option to create a new avatar as part of the avatar editing user interface enables the user to quickly manage avatars without the need to navigate numerous user interfaces, thereby reducing the number of inputs needed.

(290) In some embodiments, the one or more avatar management options (e.g., **768**) includes an option (e.g., **768c**) to delete an avatar representing the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, the computer system detects, via the one or more sensors, selection of the option (e.g., **768c**) to delete an avatar representing the user of the computer system. In some embodiments, in response to detecting selection of the option (e.g., **768c**) to delete an avatar representing the user of the computer system (e.g., **700** and/or **X700**), the computer system (e.g., **700** and/or **X700**) initiates a process to delete (e.g., deleting and/or requesting confirmation to delete) an avatar representing the user of the computer system. Providing an option to delete an avatar as part of the avatar editing user interface enables the user to quickly manage avatars without the need to navigate numerous user interfaces, thereby reducing the number of inputs needed.

(291) In some embodiments, a simulated three-dimensional avatar representing the user of the computer system (e.g., **700** and/or **X700**) is not available (e.g., has been deleted or was not created). In some embodiments, the computer system (e.g., **700** and/or **X700**) uses, during the real-time communication session while a simulated three-dimensional avatar representing the user of the computer system (e.g., **700** and/or **X700**) is not available, a representation of the user of the computer system (e.g., **700** and/or **X700**) that moves in accordance with (e.g., in conjunction with and/or based on) movement of the user of the computer system (e.g., **700** and/or **X700**) without reflecting an appearance of the user of the computer system (e.g., **700** and/or **X700**) (e.g., the representation does not have a visual appearance that corresponds to the appearance of the user of the computer system). In some embodiments, the representation of the user of the computer system that moves in accordance with (e.g., in conjunction with and/or based on) movement of the user of the computer system without reflecting the appearance of the user of the computer system (e.g., without including user-specific features of the user of the computer system, such as facial features, skin color, eye color, and/or hair color) is displayed, via the displayed generation component, thereby enabling the user to see what the avatar looks like. Providing a representation of the user of the computer system that moves in accordance with movement of the user of the computer system without reflecting the appearance of the user of the computer system enables participants of the communication session to view the user's movements when a more realistic avatar is not available, thereby providing improved visual feedback.

(292) In some embodiments, in accordance with a determination that the avatar representing the user of the computer system (e.g., **700** and/or **X700**) is a simulated three-dimensional avatar, the computer system (e.g., **700** and/or **X700**) enables participation, by the user of the computer system (e.g., **700** and/or **X700**), in spatial communication sessions (e.g., as shown in FIG. 7P) (e.g., by

displaying and/or enabling controls for initiating and/or joining a spatial communication session). In some embodiments, in accordance with a determination that the avatar representing the user of the computer system is not a simulated three-dimensional avatar (e.g., is a two-dimensional avatar, is an image, and/or is a monogram), the computer system forgoes enabling participation, by the user of the computer system (e.g., **700** and/or **X700**), in spatial communication sessions (e.g., by forgoing to display, ceasing to display, forgoing enabling, and/or ceasing enabling controls for initiating and/or joining a spatial communication session). In some embodiments, a spatial communication session is a communication session with at least some (e.g., less than all, a plurality of, and/or all) representations of users participating in the communication session distributed in a 3D environment. Enabling the user to participant in a spatial communication session when the avatar representing the user is a simulated three-dimensional avatar and forgoing enabling participation, by the user of the computer system, in spatial communication sessions when the avatar representing the user of the computer system is not a simulated three-dimensional avatar provides the user with feedback about the avatar currently representing the user, thereby providing improved feedback.

(293) In some embodiments, while a simulated three-dimensional avatar representing the user of the computer system (e.g., **700** and/or **X700**) is not available (e.g., has been deleted or was not created) and in response to at least a portion of the detected one or more inputs, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component, an option (e.g., **772**) to create an avatar representing the user of the computer system. In some embodiments, in response to detecting selection (e.g., **705k**) of the option (e.g., **772**) to create an avatar representing the user of the computer system, the computer system (e.g., **700** and/or **X700**) initiates a process (e.g., including display of **780** and/or **X780**) to create an avatar representing the user of the computer system. In some embodiments, in accordance with a determination that a (e.g., simulated three-dimensional or two-dimensional) avatar representing the user of the computer system is not available, the computer system displays the option to create an avatar representing the user of the computer system, and in accordance with a determination that an avatar representing the user of the computer system is available, the computer system forgoes display of the option to create an avatar representing the user of the computer system. Automatically displaying an option to create an avatar representing the user of the computer system when a simulated three-dimensional avatar representing the user of the computer system is not available enables the computer system to provide the user with feedback about the status of the avatar and provide quick access to create the avatar, thereby providing improved visual feedback and reducing the number of inputs required to create the avatar.

(294) In some embodiments, while a simulated three-dimensional avatar representing the user of the computer system is not available (e.g., has been deleted or was not created) and in response to at least a portion of the detected one or more inputs, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component, an option to use a default avatar to represent the user of the computer system (e.g., **700** and/or **X700**). In some embodiments, in response to detecting selection of the option to use the default avatar to represent the user of the computer system (e.g., **700** and/or **X700**), the computer system (e.g., **700** and/or **X700**) uses the default avatar to represent the user of the computer system (e.g., **700** and/or **X700**). Providing an option to use a default avatar when a simulated three-dimensional avatar is not available for the user enables the computer system to provide the user feedback about the availability of avatars and to enable the user to quickly use a default avatar, thereby providing improved feedback and reducing the number of inputs required to use a default avatar.

(295) In some embodiments, the default avatar moves in accordance with (e.g., in conjunction with and/or based on) movement of the user of the computer system (e.g., **700** and/or **X700**) without reflecting an appearance of the user of the computer system (e.g., **700** and/or **X700**) (e.g., the representation does not have a visual appearance that corresponds to the appearance of the user of

the computer system). Providing a default avatar that moves in accordance with movement of the user of the computer system without reflecting the appearance of the user of the computer system enables participants of the communication session to view the user's movements, thereby providing improved visual feedback.

(296) In some embodiments, the default avatar represents users of the computer system (e.g., **700** and/or **X700**) when the computer system (e.g., **700** and/or **X700**) is in a guest mode (e.g., a mode in which an un-registered user is using the computer system, a mode in which an unrecognized user is using the computer system, a mode in which a user that has not logged into an account is using the computer system, and/or a mode in which a first set of features (e.g., a set of content and/or functions) are made accessible to and/or are unlocked for the guest user (without making a second set of feature accessible to the guest user) without successful user authentication of the guest user (e.g., based on a set of criteria being met that optionally includes a first criterion that is satisfied if a most recent user of the computer system other than the current user (e.g., the most recent user that used the computer system prior to the user) is an authorized user and/or a second criterion that is satisfied if the computer system has been in the locked state (e.g., has been continuously and/or uninterruptedly in the locked state) for less than a threshold duration of time since the last time the computer system was in an unlocked state)). Using a default avatar when a guest is using the computer system enables the computer system to provide visual feedback about who is using the computer system, thereby providing enhanced visual feedback.

(297) In some embodiments, aspects/operations of methods **800**, **900**, **1100**, and/or **1300** may be interchanged, substituted, and/or added between these methods. For example, the home screen of FIG. 7B is the same home screen of FIG. 10A. For another example, the real-time communication session of FIG. 10C is the same as the real-time communication session of FIG. 12A. For brevity, these details are not repeated here.

(298) FIGS. 10A-10E illustrate examples of providing representations in live communication sessions. FIG. 11 is a flow diagram of an exemplary method **1100** for providing representations in live communication sessions. The user interfaces in FIGS. 10A-10E are used to illustrate the processes described below, including the processes in FIG. 11.

(299) FIGS. 10A-10E illustrate a device **700** having a display **702** (e.g., a tablet, a smart phone, or a laptop). While device **700** is illustrated as a handheld device, in some embodiments, device **700** is a head-mounted device (HMD). The HMD is configured to be worn on a head of a user of device **700** and includes display **702** on and/or in an interior portion of the HMD. Display **702** is visible to the user when device **700** is worn on the head of the user. For instance, in some embodiments, the HMD at least partially covers eyes of the user when worn on the head of the user, such that display **702** is positioned over and/or in front of the eyes of the user. In such embodiments, display **702** is configured to display an XR environment during a live communication session in which the user of the HMD is participating.

(300) In FIG. 10A, device **700** displays, on display **702**, a communication interface **1010** within an XR environment **1004**. XR environment **1004** includes elements (e.g., virtual elements and/or physical elements), such as table **1004a** and couch **1004b**. Communication interface **1010** includes pinned contacts **1012** (e.g., pinned contacts **1012a-1012g**) and recent contacts **1014** (e.g., recent contacts **1014a-1014i**), such as described above with respect to FIGS. 7B-7D.

(301) While displaying communication interface **1010**, device **700** detects selection of contact **1012d**, corresponding to a group of contacts named “Surfers”. In some embodiments, the selection of contact **1012d** is a tap gesture **1005a** on contact **1012d**. In some embodiments, the selection of contact **1012d** is an air gesture, for instance, indicating a selection of contact **1012d**. As shown in FIG. 10A, in response to detecting selection of contact **1012d**, device **700** displays contact menu **1016** including invite option **1016a** and expand option **1016b**.

(302) While displaying communication interface **1010**, device **700** detects selection of invite option **1016a**. In some embodiments, the selection of invite option **1016a** is a tap gesture **1007a** on invite

option **1016a**. In some embodiments, the selection of invite option **1016a** is an air gesture, for instance, indicating a selection of invite option **1016a**. As shown in FIG. **10B**, in response to selection of invite option **1014a**, device **700** initiates a XR communication session with members of the group of contacts “Surfers”.

(303) In FIG. **10B**, device **700** displays XR environment **1004** for the initiated XR communication session. Optionally, device **700** displays notification **1018**, indicating that the XR communication session is a spatial communication session.

(304) As shown in FIG. **10B**, XR environment **1004** includes 3D representations **1020a** and **1020b** corresponding to users of the group “Surfers” that have accepted the invite from device **700** and have joined the live communication session. In some embodiments, because the XR communication session is a spatial communication session, remote users corresponding to 3D representations **1020a** and **1020b** have spatial agency.

(305) At FIG. **10B**, XR environment **1004** further includes representation **1020c** corresponding to a third user of “Surfers”. Because the user is in the process of joining the XR communication session, as indicated by status **1024**, the user corresponding to representation **1020c** does not have spatial agency. In some embodiments, in a spatial communication session, representations of users joining a session are 3D representations (e.g., an avatar associated with the user or a default avatar), and in other embodiments, representations of users joining a session are 2D representations.

(306) In some embodiments, device **700** displays self preview **1022** including a live view of representation **1019** in XR environment **1004**, as shown in FIG. **10B**. While self preview **1019** is shown in FIG. **10B** as being located in a lower, righthand corner of display **702**, it will be appreciated that self preview **1019** may be displayed at any location on display **702**.

(307) In FIG. **10C**, device **700** displays XR environment **1004** after the third user and a fourth user of “Surfers” has joined the XR communication session. In some embodiments, when users join an XR communication session, one or more representations are initially arranged according to a template. For example, with reference to FIGS. **10B-10C**, in response to the fourth member of “Surfers” joining the XR communication session, positions of representations **1020a-1020c** are, optionally, adjusted, to provide adequate spacing for representation **1020d** in XR environment **1004**.

(308) In some embodiments, when a number of 3D representations in an XR environment exceeds a threshold amount (e.g., 3, 4, 5, or 10), device **700** transitions the XR communication session from a spatial communication session to a non-spatial communication session. In FIG. **10D1**, for example, a fifth user of “Surfers” has joined the XR communication session, exceeding a threshold number (e.g., five) of 3D representations permitted in the XR communication session. In response, as shown in FIG. **10D1**, device **700** transitions the XR communication session to a non-spatial communication session and displays notification **1028**, indicating that the XR communication session is currently a non-spatial communication session.

(309) In some embodiments, because device **700** transitions the XR live communication to a non-spatial communication session, 3D representations **1020a-1020d** are transitioned to 2D representations **1030a-1030d**, respectively, and the fifth user is represented by 2D representation **1030e**. In some embodiments, 2D representations are arranged in XR environment **1004** according to one or more templates. For example, as shown in FIG. **10D1**, 2D representations **1030a-1030e** are centered and/or arranged such that the distance between the representations is substantially equal. In some embodiments, representations are spaced such that the distance between representations satisfies a threshold distance in one or more non-vertical directions and/or a vertical direction.

(310) In some embodiments, a user can move one or more 2D representations within XR environment **1004**. By way of example, representations **1030a-1030e** can simultaneously be moved by moving grabber **1034**.

(311) In some embodiments, the techniques and user interface(s) described in FIG. **10D1** are

provided by one or more of the devices described in FIGS. 1A-1P. FIG. 10D2 illustrates an embodiment in which a non-spatial communication session (e.g., as described in FIGS. 10B-10D1) is displayed in XR environment X1004 on display module X702 of head-mounted device (HMD) X700. In some embodiments, device X700 includes a pair of display modules that provide stereoscopic content to different eyes of the same user. For example, HMD X700 includes display module X702 (which provides content to a left eye of the user) and a second display module (which provides content to a right eye of the user). In some embodiments, the second display module displays a slightly different image than display module X702 to generate the illusion of stereoscopic depth.

(312) As set forth above with reference to FIG. 10D1, in some embodiments, when a number of 3D representations in an XR environment exceeds a threshold amount (e.g., 3, 4, 5, or 10), HMD X700 transitions the XR communication session from a spatial communication session to a non-spatial communication session. In FIG. 10D2, for example, a fifth user of “Surfers” has joined the XR communication session, exceeding a threshold number (e.g., five) of 3D representations permitted in the XR communication session. In response, as shown in FIG. 10D-2, HMD X700 transitions the XR communication session to a non-spatial communication session and displays notification X1028, indicating that the XR communication session is currently a non-spatial communication session.

(313) In some embodiments, because HMD X700 transitions the XR live communication to a non-spatial communication session, 3D representations 1020a-1020d (e.g., as shown in FIG. 10C) are transitioned to 2D representations X1030a-X1030d, respectively, and the fifth user is represented by 2D representation X1030e. In some embodiments, 2D representations are arranged in XR environment X1004 according to one or more templates. For example, as shown in FIG. 10D2, 2D representations X1030a-X1030e are centered and/or arranged such that the distance between the representations is substantially equal. In some embodiments, representations are spaced such that the distance between representations satisfies a threshold distance in one or more non-vertical directions and/or a vertical direction.

(314) In some embodiments, a user can move one or more 2D representations within XR environment X1004. By way of example, representations X1030a-X1030e can simultaneously be moved by moving grabber X1034.

(315) In some embodiments, HMD X700 detects selection of grabber X1034 based on an air gesture performed by a user of HMD X700. In some embodiments, HMD X700 detects hands X750a and/or X750b of the user of HMD X700 and determines whether motion of hands X750a and/or X750b perform a predetermined air gesture corresponding to selection of grabber X1034. In some embodiments, the predetermined air gesture selecting grabber X1034 includes a pinch gesture. In some embodiments, the pinch gesture includes detecting movement of finger X750c and thumb X750d toward one another. In some embodiments, HMD X700 detects selection of grabber X1034 based on a gaze and air gesture input performed by the user of HMD X700. In some embodiments, the gaze and air gesture input includes detecting that the user of HMD X700 is looking at grabber X1034 (e.g., for more than a predetermined amount of time) and hands X750a and/or X750b of the user of HMD X700 perform a pinch gesture.

(316) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. 1B-1P can be included, either alone or in any combination, in HMD X700. For example, in some embodiments, HMD X700 includes any of the features, components, and/or parts of HMD 1-100, 1-200, 3-100, 6-100, 6-200, 6-300, 6-400, 11.1.1-100, and/or 11.1.2-100, either alone or in any combination. In some embodiments, display module X702 includes any of the features, components, and/or parts of display unit 1-102, display unit 1-202, display unit 1-306, display unit 1-406, display generation component 120, display screens 1-122a-b, first and second rear-facing display screens 1-322a, 1-322b, display 11.3.2-104, first and second display assemblies 1-120a, 1-120b, display assembly 1-320, display assembly 1-421, first and second display sub-

assemblies **1-420a**, **1-420b**, display assembly **3-108**, display assembly **11.3.2-204**, first and second optical modules **11.1.1-104a** and **11.1.1-104b**, optical module **11.3.2-100**, optical module **11.3.2-200**, lenticular lens array **3-110**, display region or area **6-232**, and/or display/display region **6-334**, either alone or in any combination. In some embodiments, HMD **X700** includes a sensor that includes any of the features, components, and/or parts of any of sensors **190**, sensors **306**, image sensors **314**, image sensors **404**, sensor assembly **1-356**, sensor assembly **1-456**, sensor system **6-102**, sensor system **6-202**, sensors **6-203**, sensor system **6-302**, sensors **6-303**, sensor system **6-402**, and/or sensors **11.1.2-110a-f**, either alone or in any combination. In some embodiments, input device **X703** includes any of the features, components, and/or parts of any of first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**, either alone or in any combination. In some embodiments, HMD **X700** includes one or more audio output components (e.g., electronic component **1-112**) for generating audio feedback (e.g., audio output), optionally generated based on detected events and/or user inputs detected by the HMD **X700**.

(317) FIG. **10E** illustrates another exemplary arrangement for 2D representations in a non-spatial communication session. As shown in FIG. **10E**, representations **1030a-1030e** are partially overlapped in an ordered stack. In some embodiments, the order of the ordered stack is static. In some embodiments, the order is dynamic, and the representations are ordered according to which user most recently communicated in the XR communication session.

(318) In some embodiments, 2D representations **1030a-1030e** can rotate along one or more axes during the XR communication session. By way of example, 2D representations **1030a-1030e** can rotate along any one or more of X-, Y-, and Z-axes. In some embodiments, rotation of 2D representations **1030a-1030e** is based on movement of users corresponding to the 2D representations **1030a-1030e**. As an example, if a user corresponding to representation **1030a** tilts their head to a side, representation **1030a** rotates in an analogous manner along a z-axis, as indicated by rotational indicator **1032a**. As another example, if the user corresponding to representation **1030a** leans forward, representation **1030a** rotates in an analogous manner along an x-axis, as indicated by rotational indicator **1032b**. As yet another example, if the user corresponding to representation **1030a** turns their head to a side (e.g., looks left or right), representation **1030a** can rotate in an analogous manner along a y-axis, as indicated by rotational indicator **1032c**.

(319) Description is made herein with respect to device **700** transitioning an XR communication session from a spatial communication session to a non-spatial communication session when a threshold number of 3D representations are exceeded in the spatial communication. It will be appreciated that in some embodiments device **700** transitions an XR communication session from a non-spatial communication session to spatial communication session as well. For example, with reference to FIG. **10D1**, if one or more users disconnects from the XR communication session such that the number of 3D representations no longer exceeds the threshold number, device **700** can, optionally, transition the XR communication session from a non-spatial communication session to a spatial communication session.

(320) In some embodiments, spatial communication sessions include both 3D and 2D representations. Accordingly, with reference once again to FIG. **10D1**, if one or more users were to disable use of their 3D representation (e.g., using an avatar option, such as avatar option **704Ad** of FIG. **7P** or another option) such that the number of 3D representations would no longer exceed the threshold number, device **700** can, optionally, transition the XR communication session from a non-spatial communication session to a spatial communication session. Thereafter, those users that disabled use of 3D representations would be represented by 2D representations and other users by 3D representations.

(321) Additional descriptions regarding FIGS. **10A-10E** are provided below in reference to method **1100** described with respect to FIGS. **10A-10E**.

(322) FIG. **11** is a flow diagram of an exemplary method **1100** for providing representations in live

communication sessions, in some embodiments. In some embodiments, method **1100** is performed at a computer system (e.g., computer system **101** in FIG. **1A**, computer system **700**, and/or HMD **X700**) (e.g., a smartphone, tablet, and/or head-mounted device) that is in communication with a display generation component (e.g., display generation component **120** in FIGS. **1A**, **3**, and **4**, display **702**, and/or display **X702**) (e.g., a visual output device, a 3D display, a display having at least a portion that is transparent or translucent on which images can be projected (e.g., a see-through display), a projector, a heads-up display, and/or a display controller). In some embodiments, the method **1100** is governed by instructions that are stored in a non-transitory (or transitory) computer-readable storage medium and that are executed by one or more processors of a computer system, such as the one or more processors **202** of computer system **101** (e.g., control **110** in FIG. **1A**). Some operations in method **1100** are, optionally, combined and/or the order of some operations is, optionally, changed.

(323) While participating (**1102**) in a communication session that is a spatial communication session (e.g., at FIGS. **10B** and **10C**) (e.g., a communication session with at least some (e.g., less than all, a plurality of, and/or all) representations of users participating in the communication session distributed in a 3D environment) that includes displaying, via the display generation component, representations (e.g., **1020a-1020d**) (e.g., other than a representation of the user of the computer system that is participating in the communication session or including a representation of the user of the computer system that is participating in the communication session) of a plurality of (e.g., less than all, a plurality of, and/or all) participants in the communication session in a spatially distributed arrangement in a 3D environment.

(324) Displaying the plurality of participants in the spatially distributed arrangement includes displaying the representations (e.g., **1020a-1020d**) of the plurality of participants spaced apart from each other and a user (e.g., **1022**) of the computer system by at least a threshold amount in a first non-vertical direction (**1104**) in the 3D environment (e.g., a 3D virtual reality environment or a 3D mixed reality environment).

(325) Displaying the plurality of participants in the spatially distributed arrangement includes displaying the representations (e.g., **1020a-1020d**) of the plurality of participants spaced apart from each other and the user (e.g., **1022**) by at least the threshold amount in a second non-vertical direction (**1106**) that is different from the first non-vertical direction.

(326) While displaying the representations (e.g., **1020a-1020d**) of the plurality of participants distributed in the 3D environment, the computer system (e.g., **700** and/or **X700**) detects (**1108**) an event. In some embodiments, spatial communication sessions are displayed such that the representations of some of the users appear to be located at different positions (including, for example, different depths) within the 3D environment.

(327) In response to detecting the event, the computer system transitions (**1110**) the communication session from the spatial communication session to a non-spatial communication session (e.g., as shown in FIGS. **10D1**, **10D2**, and/or **10E**) (e.g., a communication session where representations of users participating in the communication session are not distributed in 3D space (are distributed in 1D space (on a line) or in 2D space (on a single plane)) that includes displaying, via the display generation component, representations (e.g., **1030a-1030e** and/or **X1030a-X1030e**) of at least a subset (e.g., less than all, all, and/or all remaining) of the plurality of participants of the communication session in a grouped arrangement.

(328) In the grouped arrangement: the representations (e.g., **1030a-1030e** and/or **X1030a-X1030e**) of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction (**1112**) in the 3D environment (e.g., as in FIGS. **10D1**, **10D2**, and **10E**), a representation (**1114**) of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement, and a (**1116**) representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement. In some

embodiments, transitioning the communication session from the spatial communication session to the non-spatial communication session includes reducing the number of axes in which the representations of the users participating in the communication session are located (e.g., reducing the representations from being distributed in 3D space to being distributed in 2D space). Switching from a spatial communication session to a non-spatial communication session when the event is detected provides the user with visual feedback that the event has been detected, thereby providing the user with improved visual feedback.

(329) In some embodiments, in the non-spatial communication session (e.g., as shown in FIGS. **10D1**, **10D2**, and/or **10E**) a representation of a first participant of the plurality of participants is in a first window region (e.g., **1030a** and/or **X1030a**) and a representation of a second participant of the plurality of participants is in a second window region (e.g., **1030b** and/or **X1030b**) that is different from the first window region. In some embodiments, in the spatial communication session a representation of the first participant of the plurality of participants is not in a window region and a representation of the second participant of the plurality of participants is not in a window region (e.g., as in FIGS. **10B** and **10C**). In some embodiments, in the non-spatial communication session, each representation is in a separate window and in the spatial communication session, representations are not in separate windows. Displaying representations in window regions in non-spatial communication sessions and displaying representations without window regions in spatial communication sessions provides the user with feedback about the type of communication session, thereby providing improved visual feedback.

(330) In some embodiments, the representation of the first participant is a simulated three-dimensional representation (e.g., a 3D avatar) and the representation of the second participant is a two-dimensional representation (e.g., a 2D avatar). In some embodiments, the representations of the participants are a mix of 2D and 3D representations/avatars. Displaying participants as both three-dimensional representations and two-dimensional representations provides the user of the computer system with feedback about the type of representation being used by the participants, thereby providing improved visual feedback.

(331) In some embodiments, the plurality of participants are two-dimensional representations (e.g., as in FIGS. **10D1** and/or **10D2**). In some embodiments, all representations of users participating in the communication session are 2D representations. Displaying participants as two-dimensional representations provides the user of the computer system with visual feedback about the representation being used by the participants, thereby providing improved visual feedback.

(332) In some embodiments, the plurality of participants are three-dimensional representations (e.g., as in FIG. **10C**). In some embodiments, all representations of users participating in the communication session are 3D representations. Displaying participants as three-dimensional representations provides the user of the computer system with visual feedback about the representation being used by the participants, thereby providing improved visual feedback.

(333) In some embodiments, the event is a request (e.g., initiated by a user of the computer system or not initiated by the user of the computer system) received during the communication session to transition a representation of the user of the computer system (e.g., **700** and/or **X700**) from a 3D representation to a 2D representation. Automatically switching from the spatial communication session to the non-spatial communication session when the user switches to a 2D representation provides the user with feedback that the user has changed their representation, thereby providing improved visual feedback.

(334) In some embodiments, the request is based on an input (e.g., via voice input, touch input, gestures, air gestures, gaze, and/or button activation) in a communication session control region. Switching from the spatial communication session to the non-spatial communication session when the user provides input at a communication session control region provides the user with feedback that the input has been received, thereby providing improved visual feedback.

(335) In some embodiments, the communication session control region (e.g., such as a control

region for FIG. 10B) includes an option to transition the representation of the user of the computer system from the 3D representation to the 2D representation and one or more options corresponding to other communication session controls (e.g., mute the communication session, send a textual message as part of the communication session, display information about the communication session, and/or leave the communication session). Providing additional controls concurrently with the option to representation of the user of the computer system from the 3D representation to the 2D representation enables the user to control more aspects of the communication session, thereby improving the man-machine interface.

(336) In some embodiments, the event is a request (e.g., initiated by a user of the computer system or not initiated by the user of the computer system) received during the communication session (e.g., as in FIGS. 10D1 and/or 10D2) to transition the communication session from the spatial communication session to the non-spatial communication session (e.g., while maintaining the representation of the user of the computer system as a 3D representation or while changing the representation of the user from a 3D representation to a 2D representation). Switching from the spatial communication session to the non-spatial communication session based on a user request enables the user to control the type of communication session, thereby improving the man-machine interface.

(337) In some embodiments, the event is an additional participant joining the communication session (e.g., as in FIGS. 10D1 and/or 10D2) (e.g., where the event is triggered when the additional participant joining causes the number of participants to exceed the threshold number of participants who can participate in a spatial communication session or where the event is triggered independent of the number of participants). In some embodiments, while in a spatial communication session, an additional user requests to join the communication session and, in response, in accordance with a determination that the additional user joining would exceed the threshold number of participants, the communication session changes to a non-spatial communication session; and in accordance with a determination that the additional user joining would not exceed the threshold number of participants, the communication session does not change to a non-spatial communication session (stays a spatial communication session). Switching from the spatial communication session to the non-spatial communication session based on an additional participant joining reducing the computing resources required and conserves battery power.

(338) In some embodiments, the additional participant joining the communication session (e.g., as in FIGS. 10D1 and/or 10D2) causes the number of participants represented by simulated three-dimensional representations to exceed a threshold number of participants (e.g., independent of the number of participants represented by two-dimensional representations). In some embodiments, when the number of spatial participants exceeds the threshold number, the communication session changes to a non-spatial communication session. Including only 3D representations (and not 2D representations) as part of the threshold improves computer resource management because the 3D representations are more computing intensive as compared to the non-3D representations.

(339) In some embodiments, while the communication session is a non-spatial communication session (e.g., as in FIGS. 10D1 and/or 10D2), shifting the position of a respective window region (e.g., 1030a-1030e and/or X1030a-X1030e) corresponding to a respective participant based on the respective participant moving. In some embodiments, as participants move during a non-spatial communication session, the window displaying the representation of the participant shifts based on the detected movement. Shifting respective window regions as respective participants move provides the user with visual feedback about the movement of the participant, thereby providing improved visual feedback.

(340) In some embodiments, the respective window region (e.g., 1030a-1030e and/or X1030a-X1030e) moves forward and/or backward in a virtual environment based on a head position of respective participant. Shifting respective window regions as respective participants move provides the user with visual feedback about the movement of the participant, thereby providing improved

visual feedback.

(341) In some embodiments, the respective window region (e.g., **1030a-1030e** and/or **X1030a-X1030e**) tilts (e.g., clockwise and/or counterclockwise) based on a head position of respective participant. Shifting respective window regions as respective participants move provides the user with visual feedback about the movement of the participant, thereby providing improved visual feedback.

(342) In some embodiments, a first window (e.g., **1030a-1030e** and/or **X1030a-X1030e**) region shifts (e.g., moves forward, backward, and/or tilts) in a first direction based on movement of a participant displayed in the first window and a second window (e.g., **1030a-1030e** and/or **X1030a-X1030e**) shifts (e.g., moves forward, backward, and/or tilts) in a second direction, different from the first direction, based on movement of a participant displayed in the second window. In some embodiments, movements of various participants cause movements of the respective window regions of the various participants. Shifting respective window regions as respective participants move provides the user with visual feedback about the movement of the particular participants, thereby providing improved visual feedback.

(343) In some embodiments, while participating in the communication session that is a non-spatial communication session (e.g., as in FIGS. **10D1** and/or **10D2**), the computer system (e.g., **700** and/or **X700**) detects a second event. In some embodiments, in response to detecting the second event, the computer system (e.g., **700** and/or **X700**) transitions the communication session from the non-spatial communication session to the spatial communication session (e.g., from FIG. **10D-1** and/or **10D-2** back to FIG. **10C**). Switching from the non-spatial communication session to the spatial communication session when the second event is detected provides the user with visual feedback that the second event has been detected, thereby providing the user with improved visual feedback.

(344) In some embodiments, the second event is a participant leaving the communication session (e.g., where the event is triggered when the participant leaves because the number of participants falls below the threshold number of participants who can participate in a spatial communication session). In some embodiments, while in a non-spatial communication session, a user leaves the communication session and, in response, in accordance with a determination that the participants after the user leaving would exceed the threshold number of participants, the communication session stays a non-spatial communication session; and in accordance with a determination that the participants after the user leaving would not exceed the threshold number of participants, the communication session changes to a spatial communication session. Switching from the non-spatial communication session to the spatial communication session based on a participant leaving provides the user with visual feedback that the participant has left. In addition, the participant leaving reduces the computational resources required for the communication session, thereby allowing more computational resources to be used to make the communication session a spatial communication session.

(345) In some embodiments, the second event is a request (e.g., initiated by a user of the computer system or not initiated by the user of the computer system) received during the communication session to transition a representation of the user of the computer system (e.g., **700** and/or **X700**) from a 2D representation to a 3D representation. In some embodiments, the request is based on via voice input, touch input, gestures, air gestures, gaze, and/or button activation. Automatically switching from the non-spatial communication session to the spatial communication session when the user switches to a 3D representation provides the user with feedback that the user has changed their representation, thereby providing improved visual feedback.

(346) In some embodiments, the second event is a request (e.g., initiated by a user of the computer system or not initiated by the user of the computer system) received during the communication session to transition the communication session from a non-spatial communication session to a spatial communication session (e.g., from FIGS. **20D1** and/or **10D2** back to FIG. **10C**). In some

embodiments, the request is based via voice input, touch input, gestures, air gestures, gaze, and/or button activation. Switching from the spatial communication session to the non-spatial communication session when the user provides input (e.g., at the communication session control region) requesting the change provides the user with feedback that the input has been received, thereby providing improved visual feedback.

(347) In some embodiments, while in a spatial communication session, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), a self-view (e.g., **1019**) of a representation (e.g., a 3D representation or a 2D representation) of the user of the computer system (e.g., **700** and/or **X700**) in a self-view window region (e.g., **1022**). Displaying a self-view of the representation of the user provides the user with visual feedback about what the representation of the user looks like, thereby providing the user with improved visual feedback.

(348) In some embodiments, the self-view window region (e.g., **1022**) overlaps a window region that includes a representation of another participant of an ongoing communication session (e.g., in accordance with the communication session being between the user of the computer system and the other participant and no other participants). In some embodiments, the self-view window region is the same size as the window region that includes the representation of the other participant. Overlapping the self-view window region with a window region of a representation of another participant provides the user with feedback about which window region is a self-view window region and which window region is a representation of another participant, thereby providing improved visual feedback.

(349) In some embodiments, the self-view window region (e.g., **1022**) is smaller than a window region (e.g., **1020a-1020c**) that includes a representation of another participant (e.g., in accordance with the communication session being between the user of the computer system and a plurality of other participants). In some embodiments, the self-view window region is smaller than window regions of one or more (or all) other participants of the communication session. Providing the self-view window region in a size that is different from a window region of a representation of another participant provides the user with feedback about which window region is a self-view window region and which window region is a representation of another participant, thereby providing improved visual feedback.

(350) In some embodiments, during a spatial communication session (e.g., at FIGS. **10B** and **10C**), a first participant of the communication session is enabled to move a respective representation of the first participant and a second participant of the communication session is enabled to move a respective representation of the second participant (e.g., the participants can move their own representation relative to representations of other participants, and/or move in an extended reality environment). In some embodiments, during a spatial communication session, the user of the computer system cannot move respective representations of the participants.

(351) In some embodiments, during a non-spatial communication session (e.g., at FIGS. **10D1** and/or **10D2**), a user of the computer system is enabled to move respective window regions that include respective representations of the plurality of participants of the communication session (e.g., relative to window regions that include representations of other participants). In some embodiments, during a non-spatial communication session, participants of the communication session are not enabled to move their own respective representations (e.g., the participants do not have spatial agency, cannot move their own representation relative to representations of other participants, and/or cannot move in an extended reality environment). Enabling users to move about in an extended reality environment during a spatial communication session provides the user with feedback about the type of communication session, thereby providing improved feedback.

(352) In some embodiments, the computer system (e.g., **700** and/or **X700**) detects (e.g., during a non-spatial communication session), via the one or more sensors, user input (e.g., via **1034** of FIG. **10D1** and/or **X1034** of FIG. **10D2**) to reposition a respective window region that includes a respective representation of a participant. In some embodiments, in response to detecting the user

input to reposition the respective window region that includes the respective representation of the participant, the computer system repositions a plurality of (e.g., all of or less than all of) window regions of the plurality of participants. In some embodiments, during a non-spatial communication session, multiple (e.g., some or all) windows of (e.g., some or all) participants move together. Moving multiple window regions together enables all representations to remain grouped together and more easily viewable without the need for the user to move each window region independently, thereby reducing the number of inputs required.

(353) In some embodiments, the respective representations of the participants are placed (e.g., in 2D space or in 3D space) in an initial placement (e.g., at the start of a spatial communication session or at the start of a non-spatial communication session) based on predetermined placement rules (e.g., at FIG. 10B and/or at FIGS. 10D1 and 10D2). In some embodiments, the initial placement is a first placement that is conducive to conversation, wherein in the first placement representations of participants are distributed across from each other, such as in a circular or semi-circular arrangement facing toward each other. In some embodiments, the initial placement is a second placement that is conducive to viewing shared content, wherein in the second placement representations of participants are distributed facing the same direction or location, such as in a linear or arc shaped arrangement facing toward the shared content. Automatically initially placing respective representations of users based on predetermined placement rules reduces the need for the user to provide input to place the users, thereby reducing the number of inputs required.

(354) In some embodiments, the computer system (e.g., 700 and/or X700) displays, via the display generation component (e.g., 702 and/or X702), a representation (e.g., 1020c) of an invited user that is not currently a participant in the communication session (e.g., a placeholder). In some embodiments, accordance with a determination that the communication session is a non-spatial communication session (and/or that the representation of the invited user that is not currently a participant in the communication session is a non-spatial representation), the computer system enables a user of the computer system to reposition the representation of the invited user that is not currently a participant. In some embodiments, in accordance with a determination that the communication session is a spatial communication session (and/or that the representation of the invited user that is not currently a participant in the communication session is a spatial representation), the computer system forgoes enabling the user of the computer system to reposition the representation of the invited user that is not currently a participant. In some embodiments, while displaying the representation of the invited user that is not currently a participant in the communication session, receiving a request (e.g., via voice input, touch input, gestures, air gestures, gaze, and/or button activation) from the user of the computer system to reposition the representation of the invited user that is not currently a participant. In response to receiving the request from the user of the computer system to reposition the representation of the invited user that is not currently a participant: in accordance with a determination that the communication session is a non-spatial communication session (and/or that the representation of the invited user that is not currently a participant in the communication session is a non-spatial representation), repositioning the representation of the invited user that is not currently a participant, and in accordance with a determination that the communication session is a spatial communication session (and/or that the representation of the invited user that is not currently a participant in the communication session is a spatial representation), forgoing repositioning the representation of the invited user that is not currently a participant. Enabling a user of the computer system to move the representation of the invited user based on the type of communication session and/or the type of representation provides the user with feedback about the type of communication session and/or the type of representation, thereby providing improved visual feedback.

(355) In some embodiments, in response to changing between a spatial communication (e.g., at FIG. 10C) and a non-spatial communication session (e.g., at FIGS. 10D1 and/or 10D2), the computer system (e.g., 700 and/or X700) displays, via the display generation component (e.g., 702

and/or **X702**), an indication (e.g., **1028**, **X1028**, and/or **1018**) that a mode of the communication session has changed. In some embodiments, the computer system indicates that the mode is changing to the spatial or non-spatial communication session. Displaying a notification when changing the communication session between spatial and non-spatial modes provides the user with visual feedback about the change, thereby providing improved visual feedback.

(356) In some embodiments, aspects/operations of methods **800**, **900**, **1100**, and/or **1300** may be interchanged, substituted, and/or added between these methods. For example, the home screen of FIG. 7B is the same home screen of FIG. 10A. For another example, the real-time communication session of FIG. 10C is the same as the real-time communication session of FIG. 12A. For brevity, these details are not repeated here.

(357) FIGS. 12A-12F illustrate examples of providing information in live communication sessions. FIG. 13 is a flow diagram of an exemplary method **1300** for providing information in live communication sessions. The user interfaces in FIGS. 12A-12F are used to illustrate the processes described below, including the processes in FIG. 13.

(358) FIGS. 12A-12F illustrate a device **700** having a display **702** (e.g., a tablet, a smart phone, or a laptop). While device **700** is illustrated as a handheld device, in some embodiments, device **700** is a head-mounted device (HMD). The HMD is configured to be worn on a head of a user of device **700** and includes display **702** on and/or in an interior portion of the HMD. Display **702** is visible to the user when device **700** is worn on the head of the user. For instance, in some embodiments, the HMD at least partially covers eyes of the user when worn on the head of the user, such that display **702** is positioned over and/or in front of the eyes of the user. In such embodiments, display **702** is configured to display an XR environment during a live communication session in which the user of the HMD is participating.

(359) In FIG. 12A, device **700** is participating in an XR communication session with users represented by 3D representations **1220a-1220d** and 2D representation **1230a** in XR environment **1204**. In some embodiments, because a threshold number of 3D representations (e.g., five) has not been exceeded, the XR communication session is a spatial communication session and users corresponding to 3D representations **1220a-1220d** have spatial agency.

(360) In some embodiments, device **700** displays self preview **1216** including a live view of representation **1218** in XR environment **1204**. While self preview **1216** is shown as being located in a lower, righthand corner of display **702**, it will be appreciated that self preview **1216** is optionally displayed at any location on display **702**.

(361) In some embodiments, while participating in an XR communication session, device **700** displays status indicator **1208**, as shown in FIG. 12A. In some embodiments, status indicator **1208** indicates a state of the XR communication session. For example, status indicator **1208** indicates when a pending invitation remains for the XR communication session such that the user of device **700** is aware that one or more additional users could join the XR communication session. In some embodiments, status indicator **1208** is displayed with a first visual characteristic (e.g., is displayed using a particular color such as yellow or green) to indicate that one or more pending invitations remain. In some embodiments, status indicator **1208** indicates when device **700** is transmitting audio to participants of the XR communication session (e.g., using a microphone of device **700**). In some embodiments, status indicator **1208** is displayed with a second visual characteristic (e.g., is displayed using a particular color such as orange or purple) to indicate an invitation for the XR communication session is currently pending.

(362) While displaying XR environment **1204** during the XR communication session, device **700** detects selection of control bar **1240**. In some embodiments, the selection of control bar is a press (e.g., tap gesture or tap and hold gesture) on control bar **1240**. In some embodiments, the selection of control bar **1240** is detected based on a gaze **1205a** of the user of device **700**, as shown in FIG. 12A. Gaze indicators **1205a** and **1205c**, which indicate where the gaze of the user is directed, is illustrated for ease of understanding, and is not visually displayed as part of the user interfaces of

device **700**. In embodiments where device **700** is an HMD, device **700** is enabled to perform operations based on a gaze of the user. If for, example, device **700** determines that the user's gaze meets a first set of gaze criteria, control bar **1240** is selected (e.g., independent of other gestures, such as hand gestures, performed by the user). In some embodiments, the first set of gaze criteria is met when the user of device **700** looks at control bar **1240** (or a particular portion thereof) for a predetermined amount of time. As shown in FIG. **12B1**, in response to selection of control bar **1240**, device **700** displays information about one or more users in the XR communication session. In some embodiments, information displayed in this manner is displayed for a predetermined amount of time (e.g., 5 seconds or 10 seconds) and then ceases to be displayed.

(363) In some embodiments, information displayed by device **700** includes names of one or more users in the XR communication session. As an example, device **700** displays information indicating that representation **1220a** corresponds to a user “Jane”, representation **1220b** corresponds to a user “Ann”, representation **1220d** corresponds to a user “Jesse”, and representation **1230a** corresponds to a user “Calvin”.

(364) In some embodiments, information displayed by device **700** includes statuses of one or more users in the XR communication session. As an example, device **700** displays information indicating that the user corresponding to representation **1220a** (“Jane”) is currently away. In embodiments in which a device is an HMD, an away status can, optionally, indicate that a user is not wearing the device. As another example, device **700** displays information indicating that a device of user corresponding to representation **1220b** (“Ann”) is reconnecting to the XR communication session. As yet another example, device **700** displays information indicating that a user corresponding to representation **1220c** is using a device associated with another user (“John”). In some embodiments, a 3D representation corresponding to a guest user differs from the 3D representation of the user associated with a user (e.g., owner) of the device.

(365) While description is made herein with respect to displaying information in response to selection of control bar **1240**, in some embodiments, selection of a representation (e.g., via a tap input or gaze) causes device **700** to display information for the user corresponding to the representation.

(366) While displaying XR environment **1204** during the XR communication session, device **700** determines whether the detected selection of control bar **1240** persists for a threshold amount of time. In embodiments in which the selection of control bar **1240** is a press (e.g., tap gesture or tap and hold gesture) on control bar **1240**, device **700** determines whether the press persists for the threshold amount of time. In embodiments in which the selection of control bar **1240** is based on gaze **1205a**, device **700** determines whether the user's gaze **1205a** meets a second set of gaze criteria. In some embodiments, the second set of gaze criteria is met when the user of device **700** continues to look at control bar **1240** (or a particular portion thereof) for a threshold amount of time. As shown in FIG. **12C**, in response to device **700** determining that selection of control bar **1240** persists for the threshold amount of time, device **700** displays set of controls **1250**. In some embodiments, one or more options **1250a-1250f** of the set of controls correspond to options **704Aa-740Af** of the set of controls **704A** (FIG. **7P**), respectively. Thus, when device **700** detects the user's gaze directed at control bar **1240** for a first amount of time, information about one or more participants is displayed, as illustrated in FIG. **12B1**, and when device **700** detects the user's gaze is directed at control bar **1240** for a second amount of time (longer than the first amount of time), set of controls **1250** is displayed, as illustrated in FIG. **12C**.

(367) In some embodiments, the techniques and user interface(s) described in FIG. **12B1** are provided by one or more of the devices described in FIGS. **1A-1P**. FIG. **12B2** illustrates an embodiment in which information about one or more users in an XR communication session (e.g., as described in FIG. **12B1**) is displayed on display module **X702** of head-mounted device (HMD) **X700**. In some embodiments, device **X700** includes a pair of display modules that provide stereoscopic content to different eyes of the same user. For example, HMD **X700** includes display

module **X702** (which provides content to a left eye of the user) and a second display module (which provides content to a right eye of the user). In some embodiments, the second display module displays a slightly different image than display module **X702** to generate the illusion of stereoscopic depth.

(368) While displaying XR environment **X1204** during the XR communication session, HMD **X700** detects selection of control bar **X1240**. In some embodiments, the selection of control bar is detected based on a gaze **X1205a** of the user of HMD **X700**. Gaze indicator **X1205a**, which indicate where the gaze of the user is directed, is illustrated for ease of understanding, and is not visually displayed as part of the user interfaces of HMD **X700**. In embodiments, HMD **X700** is enabled to perform operations based on a gaze of the user. If for, example, HMD **X700** determines that the user's gaze meets a first set of gaze criteria, control bar **X1240** is selected (e.g., independent of other gestures, such as hand gestures, performed by the user). In some embodiments, the first set of gaze criteria is met when the user of HMD **X700** looks at control bar **X1240** (or a particular portion thereof) for a predetermined amount of time. As shown in FIG. **12B2**, in response to selection of control bar **X1240**, HMD **X700** displays information about one or more users in the XR communication session. In some embodiments, information displayed in this manner is displayed for a predetermined amount of time (e.g., 5 seconds or 10 seconds) and then ceases to be displayed.

(369) In some embodiments, information displayed by HMD **X700** includes names of one or more users in the XR communication session. As an example, HMD **X700** displays information indicating that representation **X1220a** corresponds to a user “Jane”, representation **X1220b** corresponds to a user “Ann”, representation **X1220d** corresponds to a user “Jesse”, and representation **X1230a** corresponds to a user “Calvin”.

(370) In some embodiments, information displayed by HMD **X700** includes statuses of one or more users in the XR communication session. As an example, HMD **X700** displays information indicating that the user corresponding to representation **X1220a** (“Jane”) is currently away. In embodiments, an away status can, optionally, indicate that a user is not wearing an HMD. As another example, HMD **X700** displays information indicating that a device of user corresponding to representation **X1220b** (“Ann”) is reconnecting to the XR communication session. As yet another example, HMD **X700** displays information indicating that a user corresponding to representation **X1220c** is using a device associated with another user (“John”). In some embodiments, a 3D representation corresponding to a guest user differs from the 3D representation of the user associated with a user (e.g., owner) of the device.

(371) While description is made herein with respect to displaying information in response to selection of control bar **X1240**, in some embodiments, selection of a representation (e.g., via a tap input or gaze) causes HMD **X700** to display information for the user corresponding to the representation.

(372) While displaying XR environment **X1204** during the XR communication session, HMD **X700** determines whether the detected selection of control bar **X1240** persists for a threshold amount of time. In some embodiments, HMD **X700** determines whether the user's gaze, as indicated by gaze indicator **X1205a**, meets a second set of gaze criteria. In some embodiments, the second set of gaze criteria is met when the user of HMD **X700** continues to look at control bar **X1240** (or a particular portion thereof) for a threshold amount of time. In some embodiments, in response to HMD **X700** determining that selection of control bar **X1240** persists for the threshold amount of time, HMD **X700** displays set of controls **1250**, as shown in FIG. **12C**. In some embodiments, one or more options **1250a-1250f** of the set of controls correspond to options **704Aa-740Af** of the set of controls **704A** (FIG. **7P**), respectively. Thus, when HMD **X700** detects the user's gaze directed at control bar **X1240** for a first amount of time, information about one or more participants is displayed, as illustrated in FIG. **12B2**, and when HMD **X700** detects the user's gaze is directed at control bar **X1240** for a second amount of time (longer than the first amount of time),

set of controls **1250** can be displayed, as illustrated in FIG. **12C**.

(373) Any of the features, components, and/or parts, including the arrangements and configurations thereof shown in FIGS. **1B-1P** can be included, either alone or in any combination, in HMD **X700**. For example, in some embodiments, HMD **X700** includes any of the features, components, and/or parts of HMD **1-100**, **1-200**, **3-100**, **6-100**, **6-200**, **6-300**, **6-400**, **11.1.1-100**, and/or **11.1.2-100**, either alone or in any combination. In some embodiments, display module **X702** includes any of the features, components, and/or parts of display unit **1-102**, display unit **1-202**, display unit **1-306**, display unit **1-406**, display generation component **120**, display screens **1-122a-b**, first and second rear-facing display screens **1-322a**, **1-322b**, display **11.3.2-104**, first and second display assemblies **1-120a**, **1-120b**, display assembly **1-320**, display assembly **1-421**, first and second display sub-assemblies **1-420a**, **1-420b**, display assembly **3-108**, display assembly **11.3.2-204**, first and second optical modules **11.1.1-104a** and **11.1.1-104b**, optical module **11.3.2-100**, optical module **11.3.2-200**, lenticular lens array **3-110**, display region or area **6-232**, and/or display/display region **6-334**, either alone or in any combination. In some embodiments, HMD **X700** includes a sensor that includes any of the features, components, and/or parts of any of sensors **190**, sensors **306**, image sensors **314**, image sensors **404**, sensor assembly **1-356**, sensor assembly **1-456**, sensor system **6-102**, sensor system **6-202**, sensors **6-203**, sensor system **6-302**, sensors **6-303**, sensor system **6-402**, and/or sensors **11.1.2-110a-f**, either alone or in any combination. In some embodiments, input device **X703** includes any of the features, components, and/or parts of any of first button **1-128**, button **11.1.1-114**, second button **1-132**, and or dial or button **1-328**, either alone or in any combination. In some embodiments, HMD **X700** includes one or more audio output components (e.g., electronic component **1-112**) for generating audio feedback (e.g., audio output), optionally generated based on detected events and/or user inputs detected by the HMD **X700**.

(374) While displaying set of controls **1250**, device **700** detects selection of the set of controls **1250**. In some embodiments, the selection of control bar is a tap gesture on controls **1250**. In some embodiments, the selection of the set of controls **1250** is detected based on a gaze **1205c** of the user of device **700**. If, for example, device **700** detects the user of device **700** looking at set of controls **1250** (or a particular portion thereof) for a threshold amount of time, set of controls **1250** is selected. As shown in FIG. **12D**, in response to the selection of set of controls **1250**, device **700** displays a set of system controls **1260** for managing various aspects of device **700** including but not limited to networking, volume, and display brightness, as illustrated in FIG. **12D**.

(375) In some embodiments, device **700** indicates which users, if any, are experiencing connection disruptions during an XR communication session. In FIG. **12E**, for example, a visual characteristic of representation **1220b** is modified (e.g., “greyed out” or otherwise darkened) indicating that the device of the user (“Ann”) corresponding to representation **1220b** has poor and/or intermittent connectivity with one or more other devices participating in the XR communication session. In some embodiments, representations of users experiencing connection disruptions have limited or no spatial agency until such disruptions have been resolved.

(376) In some embodiments, if connectivity worsens such that a threshold connection quality (e.g., as determined by latency, bandwidth, loss and/or throughput) is not met, a 3D representation corresponding to the device experiencing connectivity issues is removed from XR environment **1204** and optionally, replaced by a 2D representation. In some embodiments, this indicates that devices participating in the XR communication session are attempting to establish an adequate connection with the device of the user (e.g., “recovering position”), and optionally, serving as a placeholder until a connection is reestablished. In FIG. **12F**, for example, 3D representation **1220b** is replaced by 2D representation **1230b** indicating that connectivity for the user corresponding to the 3D representation **1220b** has worsened such that the threshold connection quality is not met.

(377) Additional descriptions regarding FIGS. **12A-12F** are provided below in reference to method **1300** described with respect to FIGS. **12A-12F**.

(378) FIG. **13** is a flow diagram of an exemplary method **1300** for providing information in live

communication sessions, in accordance with some embodiments. In some embodiments, method **1300** is performed at a computer system (e.g., computer system **101** in FIG. **1A**, computer system **700**, and/or HMD **X700**) (e.g., a smartphone, tablet, and/or head-mounted device) that is in communication with a display generation component (e.g., display generation component **120** in FIGS. **1A**, **3**, and **4**, display **702**, and/or display **X702**) (e.g., a visual output device, a 3D display, a display having at least a portion that is transparent or translucent on which images can be projected (e.g., a see-through display), a projector, a heads-up display, and/or a display controller) and one or more sensors (e.g., a touch-sensitive surface, a gyroscope, an accelerometer, a motion sensor, a movement sensor, a microphone, an infrared sensor, a camera sensor, a depth camera, a visible light camera, an eye-tracking sensor, a gaze-tracking sensor, a physiological sensor, and/or an image sensor). In some embodiments, the method **1300** is governed by instructions that are stored in a non-transitory (or transitory) computer-readable storage medium and that are executed by one or more processors of a computer system, such as the one or more processors **202** of computer system **101** (e.g., control **110** in FIG. **1A**). Some operations in method **1300** are, optionally, combined and/or the order of some operations is, optionally, changed.

(379) While in a communication session (e.g., as in FIGS. **12A-12F**) (e.g., a spatial communication session, a non-spatial communication session, a video communication session, and/or an audio communication session) with one or more participants (e.g., one user, two users, or 5 users) in the communication session, the computer system (e.g., **700** and/or **X700**) detects (**1302**), via the one or more sensors, gaze input (e.g., **1205a** and/or **X1205a**) (e.g., a gaze input directed to a predetermined area, a gaze input directed to an area or a displayed object, and/or a gaze input away from an area or a displayed object) of a user of the computer system (e.g., **700** and/or **X700**).

(380) In response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) meets a set of one or more gaze criteria, the computer system displays (**1306**), via the display generation component (e.g., **702** and/or **X702**), information (e.g., names of participants, as in FIGS. **12B1** and/or **12B2**) about a first participant in the communication session.

(381) In response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input does not meet the set of one or more gaze criteria, the computer system forgoes display (**1308**) of the information about the first participant in the communication session. Displaying information about the first participant in response to detecting the gaze input provides the user with feedback about the first participant, thereby providing improved visual feedback.

(382) In some embodiments, the set of one or more gaze criteria includes a first location criterion that is met when the gaze input (e.g., **1205a** and/or **X1205a**) is directed to a location corresponding to the first participant. In some embodiments, the gaze is directed to a location corresponding to one of the participants in order for the set of one or more gaze criteria to be met. In some embodiments, information is displayed for a respective participant when the gaze is directed to a location corresponding to the respective participant. In some embodiments, the first location criterion is met for a first participant (and not a second participant) when the gaze is directed to the first participant. In some embodiments, a second set of one or more gaze criteria includes a third location criterion that is met when the gaze input is directed to the second participant. In some embodiments, in response to detecting the gaze input: in accordance with a determination that the gaze input meets the second set of one or more gaze criteria, displaying, via the display generation component, information about the second participant in the communication session (e.g., without displaying information about the first participant); and in accordance with a determination that the gaze input does not meet the second set of one or more gaze criteria, forgoing display of the information about the second participant in the communication session. Displaying information about the first participant in response to detecting the gaze input directed to the location of the first participant provides the user with feedback about the first participant, thereby providing improved

visual feedback.

(383) In some embodiments, in response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) meets the set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) displays information (e.g., names of participants, as in FIGS. **12B1** and/or **12B2**) about a second participant (e.g., **1220b** and/or **X1220b**) in the communication session that is different from the first participant (e.g., **1220a** and/or **X1220a**). In some embodiments, the computer system displays information about the participant being gazed at without displaying information about other participants. Displaying information about the first participant in response to detecting the gaze input directed to the location of the first participant, without providing information about other participants, provides the user with feedback about which participant the user is looking at, thereby providing improved visual feedback.

(384) In some embodiments, the set of one or more gaze criteria includes a second location criterion that is met when the gaze input is directed to a location (e.g., **1240** and/or **X1240**) that does not correspond to the first participant (e.g., **1220a** and/or **X1220a**) (e.g., a location that is away from representations of participants). Displaying information about the first participant in response to detecting the gaze input directed to a location that does not correspond to the first participant provides the user with feedback about the first participant without requiring the user to look at the first participant, thereby providing improved visual feedback.

(385) In some embodiments, the location that does not correspond to the first participant is a location of a system user interface element (e.g., **1240** and/or **X1240**). In some embodiments, the second location criterion is met when the gaze input is directed to the system user interface element (e.g., and if the gaze input is not directed to the system user interface element, the second location criteria is not met). Displaying information about the first participant in response to detecting the gaze input directed to a system user interface element provides the user with feedback about the first participant without requiring the user to look at the first participant, thereby providing improved visual feedback.

(386) In some embodiments, in response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) meets a second set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), controls (e.g., **1250a-12500**) for the communication session. In some embodiments, the second set of one or more gaze criteria includes the set of one or more gaze criteria and includes a duration criterion that is met when the gaze input (e.g., **1205a** and/or **X1205a**) continues to be directed to the location of the system user interface element (e.g., **1240** and/or **X1240**) for a predefined duration of time (e.g., after the set of one or more gaze criteria has been met). In some embodiments, the computer system detects the user gazing at the location of the system user interface element and displays information about the first participant, then as the user continues to gaze at the location of the system user interface element, the computer system displays controls for the communication session. Displaying controls for the communication session based on the user continuing to gaze at the system user interface element provides the user with easy access to the controls and provides the user with feedback that the gaze is being detected.

(387) In some embodiments, in response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) meets a third set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), system controls (e.g., **1260**) for the computer system (e.g., that do not correspond to controls for the communication session). In some embodiments, the third set of one or more gaze criteria includes the set of one or more gaze criteria and includes a second duration criterion that is met when the gaze input continues to be directed to the location of the system user interface element (e.g., **1240** and/or **X1240**) for a second predefined

duration of time (e.g., after the set of one or more gaze criteria has been met). In some embodiments, the computer system detects the user gazing at the location of the system user interface element and displays information about the first participant, then as the user continues to gaze at the location of the system user interface element, the computer system displays the system controls (e.g., enable/disable Wi-Fi, enable/disable Bluetooth, change system volume, and/or turn on/off airplane mode). In some embodiments, in response to detecting the gaze input and in accordance with a determination that the gaze input does not meet the third set of one or more gaze criteria, forgoing display of system controls for the computer system. Displaying system controls based on the user continuing to gaze at the system user interface element provides the user with easy access to the controls and provides the user with feedback that the gaze is being detected.

(388) In some embodiments, the system user interface element (e.g., **1240** and/or **X1240**) indicates (e.g., via **1208**) a state (e.g., connecting, active, paused, audio muted, and/or microphone muted) of the communication session. Providing an indication of the state of the communication session provides the user with improved visual feedback about the state of the communication session.

(389) In some embodiments, a color of the system user interface element (e.g., **1240** and/or **X1240**) indicates the state of the communication session (e.g., green for open invitation to communication session and/or orange for open audio channel). Using different colors for different states for the communication session provides the user with improved visual feedback about the state of the communication session.

(390) In some embodiments, subsequent to displaying the information (e.g., names as in FIGS. **12B1** and/or **12B2**) about the first participant in the communication session, the computer system automatically ceases to display the information about the first participant in the communication session (e.g., as in FIG. **12E**). In some embodiments, the information about the participants is displayed temporarily (e.g., the information fades out after a predetermination period of time). Temporarily displaying the information about the first participant provides the user with feedback about the first participant without continuing to take up display space, thereby providing the user with improved visual feedback.

(391) In some embodiments, in response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) meets the set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), information (e.g., name information) about a second participant (e.g., **1220b** and/or **X1220b**) in the communication session that is different from the first participant in the communication session. In some embodiments, the computer system displays information about a plurality of participants of the communication session. In some embodiments, the computer system displays information about all participants of the communication session.

(392) In some embodiments, in response to detecting the gaze input (e.g., **1205a** and/or **X1205a**) and in accordance with a determination that the gaze input (e.g., **1205a** and/or **X1205a**) does not meet the set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) forgoes display of the information about the second participant in the communication session. Displaying information about multiple participants provides the user with additional information about the participants of the communication session, thereby providing improved visual feedback.

(393) In some embodiments, the information about the first participant includes a name of the first participant (e.g., as in FIGS. **12B1** and/or **12B2**). In some embodiments, the information includes respective names for a plurality of (e.g., all of) the participants of the communication session. Displaying names of participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(394) In some embodiments, the information about the first participant is displayed near (e.g., adjacent to or overlapping) a representation (e.g., an avatar) of the first participant (e.g., as in FIGS. **12B1** and/or **12B2**). In some embodiments, information about a respective participant is displayed

near (e.g., adjacent to or overlapping) a respective representation of the respective participant. Displaying the information about the participants of the communication session near the representations of the participants provides the user with feedback about what information corresponds to what participant, thereby providing improved visual feedback.

(395) In some embodiments, the information about the first participant includes a connection status (e.g., connected, connecting, or not connected) of the first participant (e.g., “reconnecting” as in FIG. 12C). In some embodiments, the information includes connection statuses for a plurality of (e.g., all of) the participants of the communication session. Displaying connection status of participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(396) In some embodiments, the information about the first participant includes an availability status (e.g., as in “away” in FIG. 12C) (e.g., away, in a meeting, and/or available) of the first participant. In some embodiments, the information includes availability statuses for a plurality of (e.g., all of) the participants of the communication session. Displaying availability status and/or away status of participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(397) In some embodiments, an availability status (e.g., as in “away” in FIG. 12C) of a respective participant (e.g., 1220a and/or X1220a) is based on whether the respective participant is wearing an electronic device. In some embodiments, the status of a user that ceases to wear the electronic device being used to join the communication session is automatically changed to away. Displaying availability status and/or away status of participants based on the respective participants wearing (r not wearing) an electronic device provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(398) In some embodiments, the information about the first participant includes a microphone status (e.g., muted or not muted) of the first participant. In some embodiments, the information includes microphone statuses for a plurality of (e.g., all of) the participants of the communication session. Displaying audio information and/or microphone status of participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(399) In some embodiments, the information about the first participant includes an indication of whether the first participant is a guest (e.g., as in “Guest” in FIG. 12D). In some embodiments, the information includes indications of whether a plurality of (e.g., all of) the participants of the communication session are guests. In some embodiments, an un-registered user is using an electronic device to participant in the communication session is identified as a guest. In some embodiments, a user that has not logged into an account of the device that is participating in the communication session is identified as a guest. Displaying whether a participant is a guest (or not) provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(400) In some embodiments, the information about the first participant includes an identifier (e.g., a name of the device being used for the communication session or an owner of the device) associated with a device of the first participant (e.g., as in “Using John's device” in FIG. 12D) (e.g., when the first participant is a guest or regardless of whether the first participant is a guest). In some embodiments, the information includes identifiers associated with respective devices of a plurality of participants (e.g., that are guests). Displaying an identifier associate with the device (e.g., computer system and/or smart phone) of the respective participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(401) In some embodiments, while in the communication session (e.g., a spatial communication session, a non-spatial communication session, a video communication session, and/or an audio communication session) with the one or more participants (e.g., one user, two users, or 5 users) in

the communication session and in accordance with a determination that the first participant is the owner of a device (and/or is logged into the device) being used to connect to the communication session, the computer system (e.g., **700** and/or **X700**) displays a first representation of the first participant. In some embodiments, while in the communication session (e.g., a spatial communication session, a non-spatial communication session, a video communication session, and/or an audio communication session) with the one or more participants (e.g., one user, two users, or 5 users) in the communication session and in accordance with a determination that the first participant is not the owner of the device (and/or is not logged into the device) being used to connect to the communication session, the computer system (e.g., **700** and/or **X700**) displays a second representation of the first participant. In some embodiments, guest participants are represented with an avatar that is different from an avatar of the owner of the device that the guest participant is using to participate in the communication session. Displaying different avatars for participants based on whether they are a guest user or owner of the device used to connect to the communication session provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(402) In some embodiments, the second representation is a default or placeholder avatar that has not been customized to include facial features of the first participant (that is a guest participant). In some embodiments, the first representation is an avatar that has been customized to include facial features of the first participant (that is the owner of the device). Displaying a default or placeholder avatar for guest participants provides the user with information about the participants of the communication session, thereby providing improved visual feedback.

(403) In some embodiments, the computer system (e.g., **700** and/or **X700**) detects a change in state of a second participant in the communication session. In some embodiments, in response to detecting the change in the state (e.g., away, available, connecting, and/or in a meeting) of the second participant, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), information about (e.g., an indication of the state of, a name of, and/or a connection status of) the second participant (e.g., as in “Ann Smith” in FIG. **12F**). Automatically displaying information about the second participant provides the user with information about the participants of the communication session without requiring the user to provide input, thereby providing improved visual feedback and reducing the number of inputs required.

(404) In some embodiments, in response to detecting the gaze input and in accordance with a determination that the gaze input meets a set of one or more gaze criteria, the computer system (e.g., **700** and/or **X700**) displays, via the display generation component (e.g., **702** and/or **X702**), respective information (e.g., names of participants as in FIG. **12C**) about a plurality of respective participants of the one or more participants in the communication session. In some embodiments, in response to detecting the change in the state of the second participant, the computer system (e.g., **700** and/or **X700**) forgoes displaying, via the display generation component, information about a third participant that is different from the second participant. In some embodiments, when the computer system detects a gaze input that meets the set of one or more gaze criteria, the computer system displays information about each of the participants in the communication session. In some embodiments, when the computer system detects a change in the state of a particular participant, the computer system displays information about that particular participant without displaying information about participants that did not have a state change. Displaying information about multiple participants based on gaze input and displaying information about a particular participant based on a state change provides the user with information about the participants and indicates to the user that that gaze was detected and/or that the state of the particular participant changed.

(405) In some embodiments, in response to detecting that tracking has been lost for a respective participant in the communication session (e.g., as in for **1220b** in FIG. **12E**), the computer displays an indication (e.g., as in “recovering position” in FIG. **12F**) that tracking has been lost for the

respective participant. In some embodiments, the indication that tracking has been lost for the respective participant includes displaying a representation of the respective participant as a low fidelity avatar (e.g., as compared to participants that have not lost tracking), a placeholder/default avatar (e.g., monogram avatar), and/or a colored shape (e.g., square or circle). In some embodiments, in response to detecting that tracking has been lost for a respective participant in the communication session: in accordance with a determination that the respective participant is a first participant, displaying an indication that tracking has been lost for the first participant (e.g., without displaying that tracking has been lost for a second participant), and in accordance with a determination that the respective participant is a second participant, displaying an indication that tracking has been lost for the second participant (e.g., without displaying that tracking has been lost for the first participant). Displaying an indication that tracking has been lost for a participant of the communication session provides the user with visual feedback about the state of the participants, thereby providing improved visual feedback.

(406) In some embodiments, aspects/operations of methods **800**, **900**, **1100**, and/or **1300** may be interchanged, substituted, and/or added between these methods. For example, the home screen of FIG. 7B is the same home screen of FIG. 10A. For another example, the real-time communication session of FIG. 10C is the same as the real-time communication session of FIG. 12A. For brevity, these details are not repeated here.

(407) The foregoing description, for purpose of explanation, has been described with reference to specific embodiments. However, the illustrative discussions above are not intended to be exhaustive or to limit the invention to the precise forms disclosed. Many modifications and variations are possible in view of the above teachings. The embodiments were chosen and described in order to best explain the principles of the invention and its practical applications, to thereby enable others skilled in the art to best use the invention and various described embodiments with various modifications as are suited to the particular use contemplated.

(408) As described above, one aspect of the present technology is the gathering and use of data available from various sources to improve management of live communication sessions. The present disclosure contemplates that in some instances, this gathered data may include personal information data that uniquely identifies or can be used to contact or locate a specific person. Such personal information data can include demographic data, location-based data, telephone numbers, email addresses, twitter IDs, home addresses, data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information), date of birth, or any other identifying or personal information.

(409) The present disclosure recognizes that the use of such personal information data, in the present technology, can be used to the benefit of users. For example, the personal information data can be used to improve management of live communication sessions. Further, other uses for personal information data that benefit the user are also contemplated by the present disclosure. For instance, health and fitness data may be used to provide insights into a user's general wellness, or may be used as positive feedback to individuals using technology to pursue wellness goals.

(410) The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal information data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should occur after receiving the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal

information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. In addition, policies and practices should be adapted for the particular types of personal information data being collected and/or accessed and adapted to applicable laws and standards, including jurisdiction-specific considerations. For instance, in the US, collection of or access to certain health data may be governed by federal and/or state laws, such as the Health Insurance Portability and Accountability Act (HIPAA); whereas health data in other countries may be subject to other regulations and policies and should be handled accordingly. Hence different privacy practices should be maintained for different personal data types in each country.

(411) Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the use of, or access to, personal information data. That is, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to such personal information data. For example, in the case of live communication sessions, the present technology can be configured to allow users to select to “opt in” or “opt out” of participation in the collection of personal information data during registration for services or anytime thereafter. In another example, users can select not to provide data for customization of services. In yet another example, users can select to limit the length of time data is maintained or entirely prohibit the development of a customized service. In addition to providing “opt in” and “opt out” options, the present disclosure contemplates providing notifications relating to the access or use of personal information. For instance, a user may be notified upon downloading an app that their personal information data will be accessed and then reminded again just before personal information data is accessed by the app.

(412) Moreover, it is the intent of the present disclosure that personal information data should be managed and handled in a way to minimize risks of unintentional or unauthorized access or use. Risk can be minimized by limiting the collection of data and deleting data once it is no longer needed. In addition, and when applicable, including in certain health related applications, data de-identification can be used to protect a user's privacy. De-identification may be facilitated, when appropriate, by removing specific identifiers (e.g., date of birth, etc.), controlling the amount or specificity of data stored (e.g., collecting location data a city level rather than at an address level), controlling how data is stored (e.g., aggregating data across users), and/or other methods.

(413) Therefore, although the present disclosure broadly covers use of personal information data to implement one or more various disclosed embodiments, the present disclosure also contemplates that the various embodiments can also be implemented without the need for accessing such personal information data. That is, the various embodiments of the present technology are not rendered inoperable due to the lack of all or a portion of such personal information data. For example, a live communication session can be provided based on non-personal information data or a bare minimum amount of personal information, such as the content being requested by the device associated with a user, other non-personal information available to the service, or publicly available information.

Claims

1. A computer system configured to communicate with a display generation component, the computer system comprising: one or more processors; and memory storing one or more programs configured to be executed by the one or more processors, the one or more programs including instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart

from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

2. The computer system of claim 1, wherein: in the non-spatial communication session: a representation of a first participant of the plurality of participants is in a first window region, and a representation of a second participant of the plurality of participants is in a second window region that is different from the first window region; and in the spatial communication session: a representation of the first participant of the plurality of participants is not in a window region, and a representation of the second participant of the plurality of participants is not in a window region.

3. The computer system of claim 2, wherein the representation of the first participant is a simulated three-dimensional representation and the representation of the second participant is a two-dimensional representation.

4. The computer system of claim 2, wherein the plurality of participants are two-dimensional representations.

5. The computer system of claim 2, wherein the plurality of participants are three-dimensional representations.

6. The computer system of claim 1, wherein the event is a request received during the communication session to transition a representation of the user of the computer system from a 3D representation to a 2D representation.

7. The computer system of claim 6, wherein the request is based on an input in a communication session control region.

8. The computer system of claim 7, wherein the communication session control region includes an option to transition the representation of the user of the computer system from the 3D representation to the 2D representation and one or more options corresponding to other communication session controls.

9. The computer system of claim 1, wherein the event is a request received during the communication session to transition the communication session from the spatial communication session to the non-spatial communication session.

10. The computer system of claim 1, wherein the event is an additional participant joining the communication session.

11. The computer system of claim 10, wherein the additional participant joining the communication session causes a number of participants represented by simulated three-dimensional representations to exceed a threshold number of participants.

12. The computer system of claim 1, the one or more programs further including instructions for: while the communication session is a non-spatial communication session, shifting a position of a respective window region corresponding to a respective participant based on the respective participant moving.

13. The computer system of claim 12, wherein the respective window region moves forward and/or

backward in a virtual environment based on a head position of respective participant.

14. The computer system of claim 12, wherein the respective window region tilts based on a head position of respective participant.

15. The computer system of claim 12, wherein a first window shifts in a first direction based on movement of a participant displayed in the first window and a second window shifts in a second direction, different from the first direction, based on movement of a participant displayed in the second window.

16. The computer system of claim 1, the one or more programs further including instructions for: while participating in the communication session that is a non-spatial communication session, detecting a second event; and in response to detecting the second event, transitioning the communication session from the non-spatial communication session to the spatial communication session.

17. The computer system of claim 16, wherein the second event is a participant leaving the communication session.

18. The computer system of claim 16, wherein the second event is a request received during the communication session to transition a representation of the user of the computer system from a 2D representation to a 3D representation.

19. The computer system of claim 16, wherein the second event is a request received during the communication session to transition the communication session from a non-spatial communication session to a spatial communication session.

20. The computer system of claim 1, the one or more programs further including instructions for: while in a spatial communication session, displaying, via the display generation component, a self-view of a representation of the user of the computer system in a self-view window region.

21. The computer system of claim 20, wherein the self-view window region overlaps a window region that includes a representation of another participant of an ongoing communication session.

22. The computer system of claim 20, wherein the self-view window region is smaller than a window region that includes a representation of another participant.

23. The computer system of claim 1, wherein: during a spatial communication session, a first participant of the communication session is enabled to move a respective representation of the first participant and a second participant of the communication session is enabled to move a respective representation of the second participant; and during a non-spatial communication session, a user of the computer system is enabled to move respective window regions that include respective representations of the plurality of participants of the communication session.

24. The computer system of claim 23, wherein the computer system is configured to communicate with one or more sensors, the one or more programs further including instructions for: detecting, via the one or more sensors, user input to reposition a respective window region that includes a respective representation of a participant; and in response to detecting the user input to reposition the respective window region that includes the respective representation of the participant, repositioning a plurality of window regions of the plurality of participants.

25. The computer system of claim 23, wherein the respective representations of the plurality of participants are placed in an initial placement based on predetermined placement rules.

26. The computer system of claim 23, the one or more programs further including instructions for: displaying, via the display generation component, a representation of an invited user that is not currently a participant in the communication session; in accordance with a determination that the communication session is a non-spatial communication session, enabling a user of the computer system to reposition the representation of the invited user that is not currently a participant; and in accordance with a determination that the communication session is a spatial communication session, forgoing enabling the user of the computer system to reposition the representation of the invited user that is not currently a participant.

27. The computer system of claim 1, the one or more programs further including instructions for: in

response to changing between a spatial communication and a non-spatial communication session, displaying, via the display generation component, an indication that a mode of the communication session has changed.

28. A non-transitory computer-readable storage medium storing one or more programs configured to be executed by one or more processors of a computer system that is in communication with a display generation component, the one or more programs including instructions for: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

29. A method, comprising: at a computer system that is in communication with a display generation component: while participating in a communication session that is a spatial communication session that includes displaying, via the display generation component, representations of a plurality of participants in the communication session in a spatially distributed arrangement in a 3D environment, wherein displaying the plurality of participants in the spatially distributed arrangement includes displaying: the representations of the plurality of participants spaced apart from each other and a user of the computer system by at least a threshold amount in a first non-vertical direction in the 3D environment; and the representations of the plurality of participants spaced apart from each other and the user by at least the threshold amount in a second non-vertical direction that is different from the first non-vertical direction; while displaying the representations of the plurality of participants distributed in the 3D environment, detecting an event; and in response to detecting the event, transitioning the communication session from the spatial communication session to a non-spatial communication session that includes displaying, via the display generation component, representations of at least a subset of the plurality of participants of the communication session in a grouped arrangement, wherein in the grouped arrangement: the representations of the plurality of participants are spaced apart from each other by less than the threshold amount in the first non-vertical direction in the 3D environment; a representation of a first participant in the grouped arrangement has a different position than a representation of the first participant in the spatially distributed arrangement; and a representation of a second participant in the grouped arrangement has a different position than a representation of the second participant in the spatially distributed arrangement.

30. The non-transitory computer-readable storage medium of claim 28, wherein: in the non-spatial communication session: a representation of a first participant of the plurality of participants is in a first window region, and a representation of a second participant of the plurality of participants is in

a second window region that is different from the first window region; and in the spatial communication session: a representation of the first participant of the plurality of participants is not in a window region, and a representation of the second participant of the plurality of participants is not in a window region.

31. The non-transitory computer-readable storage medium of claim 28, wherein the event is a request received during the communication session to transition a representation of the user of the computer system from a 3D representation to a 2D representation.

32. The non-transitory computer-readable storage medium of claim 28, wherein the event is a request received during the communication session to transition the communication session from the spatial communication session to the non-spatial communication session.

33. The non-transitory computer-readable storage medium of claim 28, wherein the event is an additional participant joining the communication session.

34. The non-transitory computer-readable storage medium of claim 28, the one or more programs further including instructions for: while the communication session is a non-spatial communication session, shifting a position of a respective window region corresponding to a respective participant based on the respective participant moving.

35. The non-transitory computer-readable storage medium of claim 28, the one or more programs further including instructions for: while participating in the communication session that is a non-spatial communication session, detecting a second event; and in response to detecting the second event, transitioning the communication session from the non-spatial communication session to the spatial communication session.

36. The non-transitory computer-readable storage medium of claim 28, the one or more programs further including instructions for: while in a spatial communication session, displaying, via the display generation component, a self-view of a representation of the user of the computer system in a self-view window region.

37. The non-transitory computer-readable storage medium of claim 28, wherein: during a spatial communication session, a first participant of the communication session is enabled to move a respective representation of the first participant and a second participant of the communication session is enabled to move a respective representation of the second participant; and during a non-spatial communication session, a user of the computer system is enabled to move respective window regions that include respective representations of the plurality of participants of the communication session.

38. The non-transitory computer-readable storage medium of claim 28, the one or more programs further including instructions for: in response to changing between a spatial communication and a non-spatial communication session, displaying, via the display generation component, an indication that a mode of the communication session has changed.

39. The method of claim 29, wherein: in the non-spatial communication session: a representation of a first participant of the plurality of participants is in a first window region, and a representation of a second participant of the plurality of participants is in a second window region that is different from the first window region; and in the spatial communication session: a representation of the first participant of the plurality of participants is not in a window region, and a representation of the second participant of the plurality of participants is not in a window region.

40. The method of claim 29, wherein the event is a request received during the communication session to transition a representation of the user of the computer system from a 3D representation to a 2D representation.

41. The method of claim 29, wherein the event is a request received during the communication session to transition the communication session from the spatial communication session to the non-spatial communication session.

42. The method of claim 29, wherein the event is an additional participant joining the communication session.

43. The method of claim 29, further comprising: while the communication session is a non-spatial communication session, shifting a position of a respective window region corresponding to a respective participant based on the respective participant moving.
44. The method of claim 29, further comprising: while participating in the communication session that is a non-spatial communication session, detecting a second event; and in response to detecting the second event, transitioning the communication session from the non-spatial communication session to the spatial communication session.
45. The method of claim 29, further comprising: while in a spatial communication session, displaying, via the display generation component, a self-view of a representation of the user of the computer system in a self-view window region.
46. The method of claim 29, wherein: during a spatial communication session, a first participant of the communication session is enabled to move a respective representation of the first participant and a second participant of the communication session is enabled to move a respective representation of the second participant; and during a non-spatial communication session, a user of the computer system is enabled to move respective window regions that include respective representations of the plurality of participants of the communication session.
47. The method of claim 29, further comprising: in response to changing between a spatial communication and a non-spatial communication session, displaying, via the display generation component, an indication that a mode of the communication session has changed.
-