

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12418571

Kind Code

B2

Date of Patent

September 16, 2025

Inventor(s)

Le; Van Bang et al.

Method and electronic apparatus for forwarding call from sending electronic apparatus

Abstract

A first electronic device and a method for forwarding a call from a second electronic device are provided. A first electronic device includes a transceiver, memory storing instructions, and one or more processors configured to execute the instructions to receive from a server a first session initiation protocol (SIP) invite message generated at the second electronic device, through the transceiver, determine whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtain contact information related to the call forwarding from the second electronic device, generate a response message comprising the contact information related to the call forwarding, and transmit the response message to the server to provide the response message comprising the contact information from the server to the second electronic device through the transceiver, wherein the contact information in the response message transmitted to the server is used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

Inventors: Le; Van Bang (Bac Ninh, VN), Le; Anh Tuan (Bac Ninh, VN), Vuong; Dinh Quan (Bac Ninh, VN), Duong; Van Thong (Bac Ninh, VN)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008818105

Assignee: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Appl. No.: 18/414800

Filed: January 17, 2024

Prior Publication Data

Document Identifier

US 20240244095 A1

Publication Date

Jul. 18, 2024

Foreign Application Priority Data

KR	10-2023-0007175	Jan. 18, 2023
KR	10-2023-0011873	Jan. 30, 2023

Publication Classification

Int. Cl.: H04L65/1096 (20220101); H04L65/1069 (20220101); H04L65/1104 (20220101)

U.S. Cl.:

CPC H04L65/1096 (20130101); H04L65/1069 (20130101); H04L65/1104 (20220501)

Field of Classification Search

CPC: H04L (65/1069); H04L (65/1096); H04L (65/1104)

USPC: 709/238

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7095838	12/2005	Kanerva et al.	N/A	N/A
7860230	12/2009	Martin	379/212.01	H04W 4/12
8094800	12/2011	Smith	379/211.01	H04M 3/42059
11683411	12/2022	Koster	379/266.07	H04M 3/42034
2009/0067606	12/2008	Li	N/A	N/A
2013/0102298	12/2012	Goodman et al.	N/A	N/A
2017/0163803	12/2016	Russell	N/A	H04L 65/1016
2017/0324870	12/2016	Cao et al.	N/A	N/A
2021/0203700	12/2020	Asveren	N/A	H04L 65/1069
2022/0094548	12/2021	Asveren	N/A	H04L 9/3213
2022/0272190	12/2021	Gayaldo	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2411394	12/2021	KR	N/A
2020/076344	12/2019	WO	N/A

Primary Examiner: Madamba; Glenford J

Attorney, Agent or Firm: Jefferson IP Law, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application is based on and claims priority under 35 U.S.C. § 119(a) of a Korean patent

application number 10-2023-0007175, filed on Jan. 18, 2023, in the Korean Intellectual Property office and of a Korean patent application number 10-2023-0011873, filed on Jan. 30, 2023, in the Korean Intellectual Property Office, the disclosure of each of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(2) The disclosure relates to an electronic device and a method for forwarding a call from a calling electronic device. More particularly, the disclosure relates to an electronic device and a method for forwarding a call based on a response message including contact information.

2. Description of Related Art

(3) In recent, a communication technology for providing a service to a user using voice and data advances, and a user may use a call service between users based on various multimedia data. However, if the user forwards an incoming call from a called electronic device to another called electronic device, a conventional call service has difficulty in effectively providing call forwarding information to a calling electronic device and the another called electronic device and managing the electronic devices related to the call forwarding.

(4) The above information is presented as background information only to assist with an understanding of the disclosure. No determination has been made, and no assertion is made, as to whether any of the above might be applicable as prior art with regard to the disclosure.

SUMMARY

(5) Aspects of the disclosure are to address at least the above mentioned problems and/or disadvantages and to provide at least the advantages described below. Accordingly, an aspect of the disclosure is to provide an electronic device and a method for forwarding a call based on a response message including contact information.

(6) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments.

(7) In accordance with an aspect of the disclosure, a first electronic device (ex: a called electronic device) for forwarding a call from a second electronic device (ex: a calling electronic device) to third electronic device (ex: another called electronic device) is provided. A first electronic device includes a transceiver, memory storing instructions, and one or more processors configured to execute the instructions to receive from a server a first session initiation protocol (SIP) invite message generated at the second electronic device, through the transceiver, determine whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtain contact information related to the call forwarding from the second electronic device, generate a response message comprising the contact information related to the call forwarding, and transmit the response message to the server to provide the response message comprising the contact information from the server to the second electronic device through the transceiver, wherein the contact information in the response message transmitted to the server is used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(8) In accordance with another aspect of the disclosure, a method at a first electronic device (ex: a called electronic device) for forwarding a call from a second electronic device (ex: a calling electronic device) to third electronic device (ex: another called electronic device) is provided. The method includes receiving from a server a first SIP invite message generated at the second electronic device through a transceiver of the first electronic device, determining whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, generating a response message including the contact information related to the call forwarding, and transmitting the response message to the server to provide the response message including the contact information

from the server to the second electronic device through the transceiver of the first electronic device. The contact information in the response message transmitted to the server may be used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(9) In accordance with another aspect of the disclosure, one or more non-transitory computer-readable recording media storing one or more computer programs including computer-executable instructions that, when executed by one or more processors, cause a called electronic device to perform operations are provided. The operations include receiving from a server a first SIP invite message generated at the second electronic device through a transceiver of the first electronic device, determining whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, generating a response message including the contact information related to the call forwarding, and transmitting the response message to the server to provide the response message including the contact information from the server to the second electronic device through the transceiver of the first electronic device. The contact information in the response message transmitted to the server may be used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(10) Other aspects, advantages, and salient features of the disclosure will become apparent to those skilled in the art from the following detailed description, which, taken in conjunction with the annexed drawings, discloses various embodiments of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a simplified diagram of a system for forwarding a call from a calling electronic device according to an embodiment of the disclosure;
- (3) FIG. 2 is a flowchart of a method for forwarding a call of a calling electronic device from a called electronic device to another called electronic device according to an embodiment of the disclosure;
- (4) FIG. 3 is a flowchart of a method of a first called electronic device for generating a response message to forward a call from a calling electronic device according to an embodiment of the disclosure;
- (5) FIG. 4 is a flowchart of a method of a second called electronic device for receiving a call forwarded from a first called electronic device according to an embodiment of the disclosure;
- (6) FIG. 5 is a flowchart of a method of a calling electronic device for displaying contact information related to a forwarded call on an outgoing call screen using contacts of the calling electronic device according to an embodiment of the disclosure;
- (7) FIG. 6 is a flowchart of a method of a second called electronic device for displaying contact information related to a forwarded call on an incoming call screen by utilizing contacts stored in an electronic device according to an embodiment of the disclosure;
- (8) FIG. 7 is a diagram of a graphical user interface (GUI) example for setting call forwarding according to an embodiment of the disclosure;
- (9) FIG. 8 is a diagram of a response message example including contact information and call blocking information according to an embodiment of the disclosure;
- (10) FIG. 9 is a diagram of a second session initiation protocol (SIP) invite message example including contact information and call blocking information according to an embodiment of the

disclosure;

(11) FIG. 10 is a diagram of an example of displaying call forwarding information on an outgoing call screen of a calling electronic device according to an embodiment of the disclosure;

(12) FIG. 11 is a diagram of an example of displaying call forwarding information on an incoming call screen of a second called electronic device according to an embodiment of the disclosure;

(13) FIG. 12 is a diagram of an example of call forwarding history information stored in a calling electronic device and displayed on a screen of the calling electronic device according to an embodiment of the disclosure;

(14) FIG. 13 is a diagram of an example of call forwarding history information stored in a first called electronic device and displayed on a screen of the first called electronic device according to an embodiment of the disclosure;

(15) FIG. 14 is a diagram of an example of call forwarding history information stored in a second called electronic device and displayed on a screen of the second called electronic device according to an embodiment of the disclosure; and

(16) FIG. 15 is a block diagram of an electronic device in a network environment, according to an embodiment of the disclosure.

(17) Throughout the drawings, it should be noted that like reference numbers are used to depict the same or similar elements, features, and structures.

DETAILED DESCRIPTION

(18) The following description with reference to the accompanying drawings is provided to assist in a comprehensive understanding of various embodiments of the disclosure as defined by the claims and their equivalents. It includes various specific details to assist in that understanding but these are to be regarded as merely exemplary. Accordingly, those of ordinary skill in the art will recognize that various changes and modifications of the various embodiments described herein can be made without departing from the scope and spirit the disclosure. In addition, descriptions of well-known functions and constructions may be omitted for clarity and conciseness.

(19) The terms and words used in the following description and claims are not limited to the bibliographical meanings, but, are merely used by the inventor to enable a clear and consistent understanding of the disclosure. Accordingly, it should be apparent to those skilled in the art that the following description of various embodiments of the disclosure is provided for illustration purpose only and not for the purpose of limiting the disclosure as defined by the appended claims and their equivalents.

(20) It is to be understood that the singular forms “a,” “an,” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, reference to “a component surface” includes reference to one or more of such surfaces.

(21) Also, terms such as first and second may be used to describe various components, but the components should not be limited by these terms. These terms are used to distinguish one component from another component.

(22) Throughout the specification, if a part is “connected” to another part, it embraces not only “directly connected”, but also “electrically connected” between other element in between. In addition, if a part “includes” a certain component, this means that it may further include another component, without excluding other component unless otherwise stated.

(23) The expression “in an embodiment” and the like appearing in various parts of the disclosure are not intended to indicate the same embodiment.

(24) An embodiment of the disclosure may be represented by functional block configurations and various operations. Some or all of the functional blocks may be implemented by various numbers of hardware and/or software configurations for performing specific functions. For example, the functional blocks of the disclosure is implemented by one or more microprocessors or by circuit configurations for a specific function. For example, the functional blocks of the disclosure are implemented in various programming or scripting languages. The functional blocks may be

implemented in an algorithm executed by one or more processors. In addition, the disclosure may employ conventional art for electronic environment configuration, signal processing, and/or data processing. Terms such as “mechanism”, “element”, “means” and “configuration” may be widely used, and are not limited to mechanical and physical configurations.

(25) In addition, connection lines or connection members between the components shown in the drawings are merely illustrative of functional connections and/or physical or circuit connections. An actual device may represent connections between components using various functional connections, physical connections, or circuit connections which are replaceable or added.

(26) Hereinafter, the disclosure will be elucidated with reference to the accompanying drawings.

(27) According to an embodiment of the disclosure, a first electronic device (ex: a called electronic device) for forwarding a call from a second electronic device (ex: a calling electronic device) to third electronic device (ex: another called electronic device) may include a transceiver, a memory for storing instructions, and a processor operatively coupled with the transceiver and the memory and executing the instructions, and the processor may be configured to, by executing the instructions, receive from a server a first SIP invite message generated at the second electronic device, determine whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtain contact information related to the call forwarding from the second electronic device, generate a response message including the contact information related to the call forwarding, and transmit the response message to the server to provide the response message including the contact information from the server to the second electronic device.

(28) In addition, the contact information in the response message transmitted to the server may be used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(29) In addition, the processor may be configured to, by executing the instructions, identify whether the call from the second electronic device is blocked, and generate call blocking information indicating whether the call from the second electronic device is blocked.

(30) In addition, the processor may be configured to, by executing the instructions, generate the response message including the contact information related to the call forwarding and the call blocking information.

(31) In addition, the contact information related to the call forwarding may include contact information of the second electronic device, contact information of the first electronic device and contact information of the third electronic device.

(32) Hence, the first electronic device may provide the server with the contact information of the second electronic device, the first electronic device and the third electronic device in the response message for the call forwarding, and the contact information of the second electronic device, the first electronic device and the third electronic may be effectively utilized in the call forwarding.

(33) In addition, the call blocking information may include an identifier indicating whether the call from the second electronic device is blocked by the first electronic device.

(34) In addition, based on the contact information related to the call forwarding in the response message provided to the second electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device may be displayed on an outgoing call screen of the second electronic device.

(35) Thus, based on the contact information of the second electronic device, the first electronic device and the third electronic device provided from the first electronic device, users of the second electronic device and the third electronic device may effectively identify electronic devices related to the call forwarding, in the call forwarding.

(36) In addition, the second SIP invite message may include the contact information and the call blocking information of the response message transmitted to the server.

(37) In addition, based on the contact information in the second SIP invite message provided to the

third electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device may be displayed on an incoming call screen of the third electronic device.

(38) In addition, based on the call blocking information in the second SIP invite message, the call forwarded to the third electronic device may be ignored by the third electronic device.

(39) In addition, the processor may be configured to, by executing the instructions, generate history information of the call forwarding.

(40) In addition, the history information of the call forwarding may include contact information of the second electronic device, contact information of the third electronic device, information indicating that the second electronic device originates the call, information indicating that the first electronic device forwards the call, and information indicating that the third electronic device receives the forwarded call.

(41) Hence, if the history information of the call forwarding is provided, users of the second electronic device, the first electronic device and the third electronic device may effectively identify the contact information of the second electronic device, the first electronic device and the third electronic device, provided from the first electronic device.

(42) In addition, according to an embodiment of the disclosure, a method of a first electronic device (ex: a called electronic device) for forwarding a call from a second electronic device (ex: a calling electronic device) to third electronic device (ex: another called electronic device) may include receiving from a server a first SIP invite message generated at the second electronic device, determining whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, generating a response message including the contact information related to the call forwarding, and transmitting the response message to the server to provide the response message including the contact information from the server to the second electronic device.

(43) In addition, the contact information in the response message transmitted to the server may be used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(44) In addition, the method may further include identifying whether the call from the second electronic device is blocked, and generating call blocking information indicating whether the call from the second electronic device is blocked.

(45) In addition, generating the response message may include generating the response message including the contact information related to the call forwarding and the call blocking information.

(46) In addition, the contact information related to the call forwarding may include contact information of the second electronic device, contact information of the first electronic device and contact information of the third electronic device.

(47) In addition, the call blocking information may include an identifier indicating whether the call from the second electronic device is blocked by the first electronic device.

(48) In addition, based on the contact information related to the call forwarding in the response message provided to the second electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device may be displayed on an outgoing call screen of the second electronic device.

(49) In addition, the second SIP invite message may include the contact information and the call blocking information of the response message transmitted to the server.

(50) In addition, based on the contact information in the second SIP invite message provided to the third electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device may be displayed on an incoming call screen of the third electronic device.

(51) In addition, based on the call blocking information in the second SIP invite message, the call forwarded to the third electronic device may be ignored by the third electronic device.

(52) In addition, the method may further include generating history information of the call

forwarding.

(53) Also, according to an embodiment of the disclosure, a computer-readable recording medium which records a program for executing a method for forwarding a call from a second electronic device (ex: a calling electronic device) to third electronic device (ex: another called electronic device) may be provided. The method may include receiving from a server a first SIP invite message generated at the second electronic device, determining whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, generating a response message including the contact information related to the call forwarding, and transmitting the response message to the server to provide the response message including the contact information from the server to the second electronic device, and the contact information in the response message transmitted to the server may be used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

(54) Also, according to an embodiment of the disclosure, a method of a server for forwarding a call from a calling electronic device to a first called electronic device may include receiving a first session initiation protocol (SIP) invite message generated at the calling electronic device, from the calling electronic device, transmitting the first SIP invite message to the first called electronic device, receiving a response message including contact information for forwarding the call to another called electronic device, from the first called electronic device, generating a second SIP invite message including the contact information of the response message, transmitting a response message including the contact information to the calling electronic device, and transmitting the generated second SIP invite message to the second called electronic device, and at least a part of the contact information may be displayed on an outgoing call screen of the calling electronic device and an incoming call screen of the second called electronic device.

(55) It should be appreciated that the blocks in each flowchart and combinations of the flowcharts may be performed by one or more computer programs which include instructions. The entirety of the one or more computer programs may be stored in a single memory or the one or more computer programs may be divided with different portions stored in different multiple memories.

(56) Any of the functions or operations described herein can be processed by one processor or a combination of processors. The one processor or the combination of processors is circuitry performing processing and includes circuitry like an application processor (AP, e.g. a central processing unit (CPU)), a communication processor (CP, e.g., a modem), a graphics processing unit (GPU), a neural processing unit (NPU) (e.g., an artificial intelligence (AI) chip), a Wi-Fi chip, a Bluetooth® chip, a global positioning system (GPS) chip, a near field communication (NFC) chip, connectivity chips, a sensor controller, a touch controller, a finger-print sensor controller, a display drive integrated circuit (IC), an audio CODEC chip, a universal serial bus (USB) controller, a camera controller, an image processing IC, a microprocessor unit (MPU), a system on chip (SoC), an integrated circuit (IC), or the like.

(57) FIG. 1 is a simplified diagram of a system for forwarding a call from a calling electronic device according to an embodiment of the disclosure.

(58) Referring to FIG. 1, the system for forwarding a call from a calling electronic device **1100** may include the calling electronic device **1100**, a first called electronic device **1200**, a second called electronic device **1300** and a server **2000**. The calling electronic device **1100**, the first called electronic device **1200**, the second called electronic device **1300** and the server **2000** may transmit and receive data for the call forwarding through a session initiation protocol (SIP). The calling electronic device **1100** may be a mobile originated (MO) device, the first called electronic device **1200** may be a mobile forwarding (MF) device, and the second called electronic device **1300** may be a mobile terminated (MT) device.

(59) The calling electronic device **1100** may transmit a first SIP invite message to the first called

electronic device **1200** via the server **2000** to perform a call with the first called electronic device **1200**, and the first called electronic device **1200** may forward a call requested from the calling electronic device **1100** to the second called electronic device **1300**.

(60) The first called electronic device **1200** may provide a response message including contact information of the second called electronic device **1300** to the server **2000**, thus allowing the calling electronic device **1100** and the second called electronic device **1300** each to display call forwarding information on their screen.

(61) The calling electronic device **1100** may display a graphical user interface (GUI) indicating the call forwarded from the first called electronic device **1200** to the second called electronic device **1300**, on an outgoing call screen.

(62) The second called electronic device **1300** may display a GUI indicating the call forwarded from the first called electronic device **1200** to the second called electronic device **1300**, on an incoming call screen.

(63) The calling electronic device **1100**, the first called electronic device **1200**, and the second called electronic device **1300** includes, for example, a mobile communication device (e.g., a smartphone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. The calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** according to an embodiment of the disclosure are not limited those devices.

(64) In addition, the disclosure has described, but not limited to, that the calling electronic device **1100** requests the call from the first called electronic device **1200** and the first called electronic device **1200** forwards the call to the second called electronic device **1300** to ease the understanding. The calling electronic device **1100** may serve as the first called electronic device **1200** or the second called electronic device **1300**, the first called electronic device **1200** may serve as the calling electronic device **1100** or the second called electronic device **1300**, or the second called electronic device **1300** may serve as the calling electronic device **1100** or the first called electronic device **1200**.

(65) FIG. 2 is a flowchart of a method for forwarding a call of a calling electronic device from a called electronic device to another called electronic device according to an embodiment of the disclosure.

(66) Referring to FIG. 2, in operation **200**, the calling electronic device **1100** may generate a first SIP invite message. The calling electronic device **1100** may generate the first SIP invite message for a call with the first called electronic device **1200**, and the first SIP invite message may include an identifier (ID) value of the calling electronic device **1100** and an ID value of the first called electronic device **1200**. The SIP invite message includes, for example, but not limited to, a phone number of the calling electronic device **1100** and a phone number of the first called electronic device **1200**.

(67) The calling electronic device **1100** may transmit the first SIP invite message to the server **2000** in operation **205**, and the server **2000** may transmit the first SIP invite message to the first called electronic device **1200** in operation **210**.

(68) In operation **215**, the first called electronic device **1200** may determine whether to forward the call from the calling electronic device **1100**. According to an embodiment, during a call with other electronic device (not shown), the first called electronic device **1200** may determine to forward the call from the calling electronic device **1100**. For example, if the first called electronic device **1200** receives the first SIP invite message from the server **2000** during the call with other electronic device (not shown), the first called electronic device **1200** determines to forward the call from the calling electronic device **1100**.

(69) According to an embodiment, if the first called electronic device **1200** receives a user input for rejecting the call with the calling electronic device **1100**, the first called electronic device **1200** may determine to forward the call from the calling electronic device **1100**. For example, if the first

called electronic device **1200** receiving the first SIP invite message receives the user input for rejecting the call or forwarding the call, the first called electronic device **1200** determines to forward the call from the calling electronic device **1100**.

(70) According to an embodiment, if the first called electronic device **1200** satisfies a condition preset by the user for the call forwarding, the first called electronic device **1200** may determine to forward the call from the calling electronic device **1100**. For example, if a phone number for the call forwarding is preset and the first called electronic device **1200** receives the first SIP invite message from the calling electronic device **1100** having the preset phone number, the first called electronic device **1200** determines to forward the call from the calling electronic device **1100**. In this case, the preset phone number may be, but not limited to, a phone number selected by the user for the call forwarding or a phone number blocked by the user. For example, if the first called electronic device **1200** is configured to forward every call of the first called electronic device **1200** and receives the first SIP invite message from the calling electronic device **1100**, the first called electronic device **1200** determines to forward the call from the calling electronic device **1100**.

(71) If determining not to forward the call from the calling electronic device **1110** in operation **215**, the first called electronic device **1200** may perform the call with the calling electronic device **1100** in operation **217**. For example, the first called electronic device **1200** provides '180: ringing' code and '200 OK' code to the calling electronic device **1100** via the server **2000**, and establish a real-time transport protocol (RTP) session with the calling electronic device **1100**.

(72) If determining to forward the call from the calling electronic device **1110** in operation **215**, the first called electronic device **1200** may obtain contact information in operation **220**. The first called electronic device **1200** may obtain the contact information related to the call forwarding. The contact information may include an ID value of the electronic device for the call connection, for example, but not limited to, a phone number of the electronic device, a user name of the electronic device and a user nickname of the electronic device.

(73) According to an embodiment, the first called electronic device **1200** may obtain contact information of the calling electronic device **1100**, based on the phone number of the calling electronic device **1100** in the first SIP invite message. For example, the first called electronic device **1200** obtains the contact information corresponding to the calling electronic device **1100** from a phonebook of the user of the first called electronic device **1200**. The phonebook of the user of the first called electronic device **1200** may be stored in the first called electronic device **1200** or another server (not shown). The contact information of the calling electronic device **1100** includes, for example, but not limited to, the phone number of the calling electronic device **1100**, a user name of the calling electronic device **1100** and a nickname of the calling electronic device **1100**.

(74) According to an embodiment, the first called electronic device **1200** may obtain contact information of the second called electronic device **1300** for receiving the forwarded call. In this case, for example, the first called electronic device **1200** presets the second called electronic device **1300** for receiving the forwarded call, and the first called electronic device **1200** may obtain the contact information of the second called electronic device **1300** which is preset. Alternatively, for example, the first called electronic device **1200** may display a GUI for selecting the second called electronic device **1300** for receiving the forwarded call, and select the second called electronic device **1300** based on a user input for the GUI. The first called electronic device **1200** may obtain the contact information of the second called electronic device **1300** selected by the user, from a user's phonebook. The contact information of the second called electronic device **1300** includes, for example, but not limited to, a phone number of the second called electronic device **1300**, a user name of the second called electronic device **1300** and a nickname of the second called electronic device **1300**.

(75) According to an embodiment, the first called electronic device **1200** may obtain the contact information of the first called electronic device **1200** which forwards the call. The contact information of the first called electronic device **1200** includes, for example, but not limited to, the

phone number of the first called electronic device **1200**, the name user and the nickname of the first called electronic device **1200**.

(76) In operation **225**, the first called electronic device **1200** may generate a response message including the contact information. The response message including the contact information includes, for example, a 'Via' header, a 'From' header, a 'To' header, a 'Call-ID' header, a 'CSeq' header, a 'Contact' header, a 'Content-length' header and a 'Call-info' header. The first called electronic device **1200** may generate the response message including the contact information, by adding a separate header where the contact information is recorded, to the response message. For example, the first called electronic device **1200** generates the response message including the contact information by adding to the response message the 'Call-info' header where the contact information is recorded. In this case, the response message generated by the first called electronic device **1200** may include, as a value corresponding to the 'Call-info' header, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200** and the contact information of the second called electronic device **1300**.

(77) For example, the first called electronic device **1200** generates a response message further including call blocking information. The call blocking information may include a value indicating whether the call from the calling electronic device **1100** is blocked by the first called electronic device **1200**. In this case, the response message may include, as the value corresponding to the 'Call-info' header, the call blocking information indicating whether the call of the calling electronic device **1100** is blocked.

(78) The response message including the contact information shall be explained in, for example, FIG. 8.

(79) The first called electronic device **1200** may transmit the response message to the server **2000** in operation **230**, and the server **2000** may transmit the response message to the calling electronic device **1100** in operation **235**.

(80) In operation **240**, the server **2000** may generate a second SIP invite message including the contact information. The second SIP invite message may be transmitted from the server **2000** to the second called electronic device **1300** for the call forwarding. The server **2000** may obtain the contact information from the response message received from the first called electronic device **1200**, and generate the second SIP invite message including the contact information by using at least part of the obtained contact information.

(81) The second SIP invite message including the contact information includes, for example, the 'Via' header, the 'From' header, the 'To' header, the 'Call-ID' header, the 'CSeq' header, the 'Contact' header, the 'Content-length' header and the 'Call-info' header. The server **2000** may generate the second SIP invite message including the contact information, by adding a separate header recording the contact information to the second SIP invite message. For example, the server **2000** generates the second SIP invite message including the contact information by adding to the second SIP invite message the 'Call-info' header where the contact information is recorded. In this case, the second SIP invite message generated by the server **2000** may include, as the value corresponding to the 'Call-info' header, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200** and the contact information of the second called electronic device **1300**.

(82) For example, the server **2000** generates the second SIP invite message further including the call blocking information. The call blocking information may include the value indicating whether the call from the calling electronic device **1100** is blocked by the first called electronic device **1200**. In this case, the second SIP invite message may further include, as the value corresponding to the 'Call-info' header, the call blocking information indicating whether the call of the calling electronic device **1100** is blocked.

(83) The second SIP invite message including the contact information shall be explained in, for example, FIG. 8.

(84) In operation **245**, the server **2000** may transmit the second SIP invite message to the second called electronic device **1300**.

(85) In operation **250**, the calling electronic device **1100** may extract the contact information from the response message. The calling electronic device **1100** may extract the contact information from the response message, and identify from the extracted contact information whether the first called electronic device **1200** attempts to forward the call to the second called electronic device **1300**. For example, the calling electronic device **1100** obtains the contact information of the first called electronic device **1200** which forwards the call and the contact information of the second called electronic device **1300** which is to receive the forwarded call, from the response message.

(86) In operation **255**, the calling electronic device **1100** may display the contact information on the outgoing call screen. The calling electronic device **1100** may display the outgoing call screen after transmitting the first SIP invite message for the sake of the call with the first called electronic device **1200**, and if receiving the response message including the contact information from the server **2000** while displaying the outgoing call screen, display the contact information obtained from the received response message on the outgoing call screen. For example, the calling electronic device **1100** displays a text indicating that the call for the first called electronic device **1200** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**, on the outgoing call screen.

(87) In operation **260**, the second called electronic device **1300** may extract the contact information from the second SIP invite message. The second called electronic device **1300** may extract the contact information from the second SIP invite message, and identify from the extracted contact information whether the first called electronic device **1200** attempts to forward the call to the second called electronic device **1300**. For example, the second called electronic device **1300** obtains the contact information of the calling electronic device **1100** which originates the call to the first called electronic device **1200** and the contact information of the first called electronic device **1200** which forwards the call, from the second SIP invite message.

(88) In operation **265**, the second called electronic device **1300** may display the contact information on the incoming call screen. If receiving the second SIP invite message from the server **2000**, the second called electronic device **1300** may display the incoming call screen indicating that the forwarded call is incoming. The second called electronic device **1300** may display the contact information obtained from the received second SIP invite message on the incoming call screen. For example, the second called electronic device **1300** displays a text indicating that the call from the calling electronic device **1100** to the first called electronic device **1200** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**, on the incoming call screen.

(89) The second called electronic device **1300** may transmit a SIP response code (e.g., 200 OK) to the server **2000** in operation **270**, and the server **2000** may transmit the SIP response code (e.g., 200 OK) to the calling electronic device **1100** in operation **275**. The SIP response code (e.g., 200 OK) may request the call connection with the calling electronic device **1100**.

(90) In operation **280**, the calling electronic device **1100** may establish an RTP session for the call with the second called electronic device **1300**. As the RTP session is established, the calling electronic device **1100** may conduct the call with the second called electronic device **1300**.

(91) In operation **285**, the server **2000** may generate history information of the call forwarding. The call forwarding history information generated by the server **2000** includes, for example, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200**, the contact information of the second called electronic device **1300**, information indicating that the calling electronic device **1100** originates the call, information indicating that the first called electronic device **1200** forwards the call, and information indicating that the second called electronic device **1300** receives the forwarded call. If the second called electronic device **1300** rejects the forwarded call, the server **2000** may not generate history

information of the rejected forwarded call.

(92) In operation **290**, the calling electronic device **1100** may generate history information of the call forwarding. The call forwarding history information generated by the calling electronic device **1100** includes, for example, the contact information of the first called electronic device **1200**, the contact information of the second called electronic device **1300**, information indicating that the calling electronic device **1100** originates the call, information indicating that the first called electronic device **1200** forwards the call, and information indicating that the second called electronic device **1300** receives the forwarded call.

(93) In operation **292**, the first called electronic device **1200** may generate history information of the call forwarding. The call forwarding history information generated by the first called electronic device **1200** includes, for example, the contact information of the calling electronic device **1100**, the contact information of the second called electronic device **1300**, information indicating that the calling electronic device **1100** originates the call, information indicating that the first called electronic device **1200** forwards the call, and information indicating that the second called electronic device **1300** receives the forwarded call.

(94) In operation **294**, the second called electronic device **1300** may generate history information of the call forwarding. The call forwarding history information generated by the second called electronic device **1300** includes, for example, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200**, information indicating that the calling electronic device **1100** originates the call, information indicating that the first called electronic device **1200** forwards the call, and information indicating that the second called electronic device **1300** receives the forwarded call.

(95) It has been described, but not limited to, that the server **2000**, the calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** each generate the call forwarding history information. According to an embodiment, at least one of the server **2000**, the calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** may not generate the call forwarding history information. For example, at least one of the calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** do not generate the call forwarding history information, wherein an electronic device not generating the call forwarding history information may receive from the server **2000** the history information generated by the server **2000**.

(96) The call forwarding history information may be generated and managed apart from history information of normal calls not forwarded.

(97) FIG. **3** is a flowchart of a method of a first called electronic device for generating a response message to forward a call from a calling electronic device according to an embodiment of the disclosure. Operation **300** through operation **340** of FIG. **3** may correspond to operation **215** through operation **225** of FIG. **2**.

(98) Referring to FIG. **3**, in operation **300**, the first called electronic device **1200** may obtain the phone number of the calling electronic device **1100** from the first SIP invite message. The first called electronic device **1200** may obtain the phone number of the calling electronic device **1100** contained in the first SIP invite message, from the first SIP invite message.

(99) In operation **305**, the first called electronic device **1200** may determine whether a call forwarding function is enabled. The first called electronic device **1200** may preset whether to enable the call forwarding function, and determine whether the call forwarding function is enabled, based on the setting. In this case, the first called electronic device **1200** may enable the call forwarding function according to a user input through a GUI for enabling the call forwarding function. If the call forwarding function of the first called electronic device **1200** is not enabled, the first called electronic device **1200** may display the GUI for enabling the call forwarding function and receive a user input for the GUI, in response to receiving the first SIP invite message. The GUI for enabling the call forwarding function shall be described in, for example, FIG. **7**.

(100) According to an embodiment, the first called electronic device **1200** may enable the call forwarding function for each phone number of the calling electronic device **1100**. In this case, the first called electronic device **1200** may determine whether the call forwarding function is enabled for the calling electronic device **1100**, based on the phone number of the calling electronic device **1100**.

(101) If determining that the call forwarding function is not enabled in operation **305**, the first called electronic device **1200** may terminate the call forwarding operation in operation **340**.

(102) If determining that the call forwarding function is enabled in operation **305**, the first called electronic device **1200** may determine whether a contact information sharing function is enabled in operation **310**. The contact information sharing function may be a function for sharing the contact information related to the call forwarding, with at least one of the calling electronic device **1100**, the server **2000** and the second called electronic device **1300** if the first called electronic device **1200** performs the call forwarding.

(103) The first called electronic device **1200** may preset whether to enable the contact information sharing function, and determine based on the setting whether the contact information sharing function is enabled. In this case, the first called electronic device **1200** may enable the contact information sharing function according to a user input through a GUI for enabling the contact information sharing function. If the contact information sharing function of the first called electronic device **1200** is not enabled, in response to receiving the first SIP invite message, the first called electronic device **1200** may display the GUI for enabling the contact information sharing function and receive a user input for the GUI. The GUI for enabling the contact information sharing function shall be described in, for example, FIG. 7.

(104) According to an embodiment, the first called electronic device **1200** may enable the contact information sharing function for each phone number of the calling electronic device **1100**. In so doing, the first called electronic device **1200** may determine whether the contact information sharing function is enabled for the calling electronic device **1100**, based on the phone number of the calling electronic device **1100**.

(105) If determining that the contact information sharing function is not enabled in operation **310**, the first called electronic device **1200** may generate a response message not including the call forwarding contact information in operation **315**. For example, the first called electronic device **1200** generates the response message not including a separate header containing the contact information to be displayed on the outgoing call screen of the calling electronic device **1100** and the incoming call screen of the second called electronic device **1300**. For example, the first called electronic device **1200** generates the response message not including the 'Call-info' header where the contact information is recorded.

(106) If determining that the contact information sharing function is enabled in operation **310**, the first called electronic device **1200** may generate the call blocking information indicating whether to block a call from the calling electronic device **1100** in operation **320**. For example, if the phone number of the calling electronic device **1100** is set to be blocked by the first called electronic device **1200**, the first called electronic device **1200** generates the call blocking information indicating that the call from the calling electronic device **1100** is blocked. Alternatively, for example, if the phone number of the calling electronic device **1100** is not set to be blocked by the first called electronic device **1200**, the first called electronic device **1200** generates the call blocking information indicating that the call from the calling electronic device **1100** is not blocked.

(107) In operation **325**, the first called electronic device **1200** may select the second called electronic device **1300**. The first called electronic device **1200** may select the second called electronic device **1300** as the electronic device for receiving the forwarded call, based on a preset criterion. If the second called electronic device **1300** for receiving the forwarded call is preset, the first called electronic device **1200** may select the second called electronic device **1300** according to the setting. In this case, for example, the second called electronic device **1300** for receiving the

forwarded call is preset, per calling electronic device **1100**. Alternatively, for example, the electronic device for receiving the forwarded call is set to the second called electronic device **1300** with respect to every call requested from the first called electronic device **1200**. Alternatively, for example, the second called electronic device **1300** is preset regardless of the phone number of the calling electronic device **1100**.

(108) According to an embodiment, the first called electronic device **1200** may select the second called electronic device **1300** according to a user input. The first called electronic device **1200** receiving the first SIP invite message may display a list for selecting the second called electronic device **1300**, and select the second called electronic device **1300** for receiving the forwarded call, according to a user input for the list. For example, the first called electronic device **1200** displays a GUI inquiring whether to forward the call and a GUI for selecting the second called electronic device **1300** to receive the forwarded call, on the incoming call screen indicating whether the call from the calling electronic device **1100** is requested, and select the second called electronic device **1300** based on user inputs through the GUIs.

(109) In operation **330**, the first called electronic device **1200** may determine whether to conduct the call with the calling electronic device **1100**, based on a status of the first called electronic device **1200**. For example, if the first called electronic device **1200** is engaged in a call, the first called electronic device **1200** does not respond, the first called electronic device **1200** is in absence, or the first called electronic device **1200** receive a user input for rejecting the call connection, the first called electronic device **1200** determines not to perform the call with the calling electronic device **1100**. Alternatively, for example, if receiving a user input for accepting the call from the calling electronic device **1100**, the first called electronic device **1200** determines to conduct the call with the calling electronic device **1100**.

(110) If determining to perform the call with the calling electronic device **1100** in operation **330**, the first called electronic device **1200** may terminate the call forwarding operation in operation **340**.

(111) If determining not to perform the call with the calling electronic device **1100** in operation **330**, the first called electronic device **1200** may generate a response message including the contact information related to the call forwarding in operation **335**.

(112) The response message including the contact information includes, for example, the 'Via' header, the 'From' header, the 'To' header, the 'Call-ID' header, the 'CSeq' header, the 'Contact' header, the 'Content-length' header and the 'Call-info' header. The first called electronic device **1200** may generate the response message including the contact information, by adding a separate header recording the contact information to the response message. For example, the first called electronic device **1200** generates the response message including the contact information by adding to the response message the 'Call-info' header where the contact information is recorded. In this case, the response message generated by the first called electronic device **1200** may include, as the value corresponding to the 'Call-info' header, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200** and the contact information of the second called electronic device **1300**.

(113) For example, the first called electronic device **1200** generates a response message further including the call blocking information. The call blocking information may include the value indicating whether the call from the calling electronic device **1100** is blocked by the first called electronic device **1200**. In this case, the response message may further include, as the value corresponding to the 'Call-info' header, the call blocking information indicating whether the call of the calling electronic device **1100** is blocked.

(114) FIG. **4** is a flowchart of a method of a second called electronic device for receiving a call forwarded from a first called electronic device according to an embodiment of the disclosure. Operation **400** through operation **450** of FIG. **4** may correspond to operation **260** through operation **265** of FIG. **2**.

(115) Referring to FIG. 4, in operation 400, the second called electronic device 1300 may obtain the call blocking information from the second SIP invite message. The second called electronic device 1300 may extract the value indicating whether a call from the calling electronic device 1100 is set to be blocked at the first called electronic device 1200, from the second SIP invite message. For example, the second called electronic device 1300 identifies the call blocking information indicating whether the calling electronic device 1100 is blocked, in the value corresponding to the 'Call-info' header of the second SIP invite message.

(116) In operation 410, the second called electronic device 1300 may determine whether the forwarded call is blocked by the first called electronic device 1200. Based on the call blocking information obtained from the second SIP invite message, the second called electronic device 1300 may identify whether the call forwarded to the second called electronic device 1300 is blocked by the first called electronic device 1200.

(117) If determining that the forwarded call is blocked by the first called electronic device 1200 in operation 410, the second called electronic device 1300 may ignore the forwarded call in operation 450. For example, the second called electronic device 1300 does not display the incoming call screen indicating that the forwarded call is incoming. If ignoring the forwarded call, the second called electronic device 1300 may not generate history information of the ignored forwarded call.

(118) If determining that the forwarded call is not blocked by the first called electronic device 1200 in operation 410, the second called electronic device 1300 may obtain the contact information of the calling electronic device 1100 from the second SIP invite message in operation 420. For example, the second called electronic device 1300 identifies at least one of the phone number of the calling electronic device 1100, the user name of the calling electronic device 1100 or the user nickname of the calling electronic device 1100, in the value corresponding to the 'Call-info' header of the second SIP invite message.

(119) In operation 430, the second called electronic device 1300 may obtain the contact information of the first called electronic device 1200 from the second SIP invite message. For example, the second called electronic device 1300 may identify at least one of the phone number of the first called electronic device 1200, the user name of the calling electronic device 1100 or the user nickname of the calling electronic device 1100, in the value corresponding to the 'Call-info' header of the second SIP invite message.

(120) In operation 440, the second called electronic device 1300 may display the contact information related to the forwarded call, on the incoming call screen. The second called electronic device 1300 may display on the incoming call screen, information indicating that the call from the calling electronic device 1100 to the first called electronic device 1200 is forwarded by the first called electronic device 1200 to the second called electronic device 1300. For example, the second called electronic device 1300 displays the contact information of the calling electronic device 1100 which originates the call and the contact information of the first called electronic device 1200 which forwards the call, on the incoming call screen.

(121) The incoming call screen of the second called electronic device 1300 displaying the contact information related to the forwarded call shall be explained in, for example, FIG. 12.

(122) FIG. 5 is a flowchart of a method of a calling electronic device for displaying contact information related to a forwarded call on an outgoing screen using contacts of the calling electronic device according to an embodiment of the disclosure. Operation 500 through operation 540 of FIG. 5 may correspond to operation 250 through operation 255 of FIG. 2.

(123) Referring to FIG. 5, in operation 500, the calling electronic device 1100 may obtain the contact information from the response message. The calling electronic device 1100 may obtain the contact information related to the call forwarding from the header recording the contact information in the response message. For example, the calling electronic device 1100 identifies at least one of the phone number of the second called electronic device 1300, the user name of the second called electronic device 1300 or the user nickname of the second called electronic device

1300 from the 'Call-info' header.

(124) In operation **510**, the calling electronic device **1100** may determine whether contact information corresponding to the contact information obtained from the response message is included in the contacts of the calling electronic device **1100**. The calling electronic device **1100** may determine whether contact information corresponding to the contact information of the second called electronic device **1300** receiving the forwarded call is included in the contacts of the calling electronic device **1100**. For example, the calling electronic device **1100** determines whether contact information corresponding to at least one of the phone number of the second called electronic device **1300**, the user name of the second called electronic device **1300** or the user nickname of the second called electronic device **1300** is included in the contacts of the calling electronic device **1100**.

(125) If determining that the contact information corresponding to the contact information obtained from the response message is not included in the contacts of the calling electronic device **1100** in operation **510**, the calling electronic device **1100** may display the contact information obtained from the response message on the outgoing call screen in operation **540**.

(126) If determining that the contact information corresponding to the contact information obtained from the response message is included in the contacts of the calling electronic device **1100** in operation **510**, the calling electronic device **1100** may identify contact information corresponding to the contact information obtained from the response message from the calling electronic device **1100** in the contacts in operation **520**.

(127) In operation **530**, the calling electronic device **1100** may display the contact information identified from the contacts of the calling electronic device **1100** on the outgoing call screen. In so doing, based on the contact information included in the contacts of the calling electronic device **1100**, the calling electronic device **1100** may display information indicating that the call from the calling electronic device **1100** is forwarded by the first called electronic device **1200** and transmitted to the second called electronic device **1300**, on the outgoing call screen.

(128) FIG. **6** is a flowchart of a method of a second called electronic device for displaying contact information related to a forwarded call on an incoming call screen by utilizing contacts stored in the electronic device according to an embodiment of the disclosure. Operation **600** through operation **640** of FIG. **6** may correspond to operation **260** through operation **265** of FIG. **2**.

(129) Referring to FIG. **6**, in operation **600**, the second called electronic device **1300** may obtain the contact information from the second SIP invite message. The second called electronic device **1300** may obtain the contact information related to the call forwarding from the header recording the contact information included in the second SIP invite message. For example, the second called electronic device **1300** identifies at least one of the phone number of the calling electronic device **1100**, the user name of the calling electronic device **1100** or the user nickname of the calling electronic device **1100** from the 'Call-info' header.

(130) In operation **610**, the second called electronic device **1300** may determine whether contact information corresponding to the contact information obtained from the second SIP invite message is included in the contacts of the second called electronic device **1300**. The second called electronic device **1300** may determine whether the contact information corresponding to the contact information of the calling electronic device **1100** is included in the contacts of the second called electronic device **1300**. For example, the second called electronic device **1300** determines whether the contact information corresponding to at least one of the phone number of the calling electronic device **1100**, the user name of the calling electronic device **1100** or the user nickname of the calling electronic device **1100** is included in the contacts of the second called electronic device **1300**.

(131) If determining that the contact information corresponding to the contact information obtained from the second SIP invite message is not included in the contacts of the second called electronic device **1300** in operation **610**, the second called electronic device **1300** may display the contact information obtained from the second SIP invite message on the incoming call screen in operation

640.

(132) If determining that the contact information corresponding to the contact information obtained from the second SIP invite message is included in the contacts of the second called electronic device **1300** in operation **610**, the second called electronic device **1300** may identify contact information corresponding to the contact information obtained from the second SIP invite message from the contacts of the second called electronic device **1300** in operation **620**.

(133) In operation **630**, the second called electronic device **1300** may display the contact information identified from the contacts of the second called electronic device **1300** on the incoming call screen. In so doing, based on the contact information included in the contacts of the second called electronic device **1300**, the second called electronic device **1300** may display information indicating that the call from the calling electronic device **1100** is forwarded by the first called electronic device **1200** and transmitted to the second called electronic device **1300**, on the incoming call screen.

(134) FIG. **7** is a diagram of a GUI example for setting call forwarding according to an embodiment of the disclosure.

(135) Referring to FIG. **7**, a GUI **70** for setting the call forwarding may include a button **72** for enabling/disabling the call forwarding function and a button **74** for enabling/disabling the contact information sharing function.

(136) The GUI **70** for setting the call forwarding may be displayed on the screen of the first called electronic device **1200**. The call forwarding function of the first called electronic device **1200** may be enabled/disabled based on a user input for the button **72** of the GUI **70** displayed on the screen of the first called electronic device **1200**. The contact information sharing function of the first called electronic device **1200** may be enabled/disabled based on a user input for the button **74** displayed on the screen of the first called electronic device **1200**.

(137) FIG. **8** is a diagram of a response message example including contact information and call blocking information according to an embodiment of the disclosure.

(138) Referring to FIG. **8**, a response message **80** may include the contact information related to the call forwarding and the call blocking information. The response message **80** includes, for example, a 'Via' header, a 'From' header, a 'To' header, a 'Call-ID' header, a 'CSeq' header, a 'Contact' header, a 'Content-length' header and a 'Call-info' header. The first called electronic device **1200** may generate the response message **80** including the contact information, by adding the 'Call-info' header which is a separate header recording the contact information to the response message **80**. For example, a value corresponding to the 'Call-info' header includes the contact information (e.g., "contactA") of the calling electronic device **1100**, the contact information (e.g., "contactB") of the first called electronic device **1200** and the contact information (e.g., "contactC") of the second called electronic device **1300**.

(139) For example, the response message **80** further includes the call blocking information. For example, the value corresponding to the 'Call-info' header added to the response message **80** further includes the call blocking information (e.g., "block_status: true") indicating whether the calling electronic device **1100** is blocked.

(140) FIG. **9** is a diagram of a second SIP invite message example including contact information and call blocking information according to an embodiment of the disclosure.

(141) Referring to FIG. **9**, a second SIP invite message **90** may include the contact information related to the call forwarding and the call blocking information. The second SIP invite message **90** includes, for example, a 'Via' header, a 'From' header, a 'To' header, a 'Call-ID' header, a 'CSeq' header, a 'Contact' header, a 'Content-length' header and a 'Call-info' header. The server **2000** may generate the second SIP invite message **90** including the contact information, by adding a separate header recording the contact information to the second SIP invite message **90**. For example, a value corresponding to the 'Call-info' header includes the contact information (e.g., "contactA") of the calling electronic device **1100**, the contact information (e.g., "contactB") of the first called

electronic device **1200** and the contact information (e.g., “contactC”) of the second called electronic device **1300**.

(142) For example, the second SIP invite message **90** further includes the call blocking information. For example, the value corresponding to the ‘Call-info’ header added to the second SIP invite message **90** further includes the call blocking information (e.g., “block_status: true”) indicating whether the calling electronic device **1100** is blocked.

(143) FIG. **10** is a diagram of an example of displaying call forwarding information on an outgoing call screen of a calling electronic device according to an embodiment of the disclosure.

(144) Referring to FIG. **10**, an outgoing call screen **100** of the calling electronic device **1100** may display information indicating that a call from the calling electronic device **1100** is forwarded to the second called electronic device **1300**.

(145) The outgoing call screen **100** of the calling electronic device **1100** may display the user name (e.g., “contact B”) and the phone number (e.g., “88888888”) of the first called electronic device **1200**.

(146) In addition, the outgoing call screen **100** of the calling electronic device **1100** may display a phrase (e.g., “Call forwarded to Contact C(99999999)”) indicating that the call of the calling electronic device **1100** is forwarded to the second called electronic device **1300**. The phrase indicating that the call from the calling electronic device **1100** is forwarded to the second called electronic device **1300** may include the name (e.g., “contact B”) of the second called electronic device **1300** and the phone number (e.g., “99999999”) of the second called electronic device **1300**.

(147) FIG. **11** is a diagram of an example of displaying call forwarding information on an incoming call screen of a second called electronic device according to an embodiment of the disclosure.

(148) Referring to FIG. **11**, an incoming call screen **110** of the second called electronic device **1300** may display information indicating that a call from the calling electronic device **1100** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**.

(149) The incoming call screen **110** of the second called electronic device **1300** may display the user name (e.g., “Contact A”) and the phone number (e.g., “77777777”) of the calling electronic device **1100**.

(150) In addition, the incoming call screen **110** of the second called electronic device **1300** may display a phrase (e.g., “Call forwarded by Contact B(88888888)”) indicating that the call of the calling electronic device **1100** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**. The phrase indicating that the call of the calling electronic device **1100** is forwarded by the first called electronic device **1200** to the second called electronic device **1300** may include the name (e.g., “Contact A”) of the first called electronic device **1200** and the phone number (e.g., “88888888”) of the first called electronic device **1200**.

(151) FIG. **12** is a diagram of an example of call forwarding history information stored in a calling electronic device and displayed on a screen of the calling electronic device according to an embodiment of the disclosure.

(152) Referring to FIG. **12**, a call forwarding history table **120** stored in the calling electronic device **1100** may include a field **122** recording a type of the forwarded call, a field **123** recording an electronic device which forwards the call, a field **124** recording an electronic device which originates the call and a field **125** recording an electronic device which receives the forwarded call. For example, the field **122** contains “OUTGOING” indicating that the type of the forwarded call is a call originated by the calling electronic device **1100**, the field **123** may contain “CONTACT B” which is the user name of the first called electronic device **1200** forwarding the call, the field **124** may contain a value “NULL”, and the field **125** may contain “CONTACT C” which is the name of the second called electronic device **1300** receiving the forwarded call.

(153) Based on the call forwarding history table **120**, the calling electronic device **1100** may display history information **127** of the forwarded call on the screen. For example, as the forwarded call history information **127**, the calling electronic device **1100** displays a phrase “Outgoing call”

indicating that the forwarded call is the originated call, a phrase “Call forwarded to Contact C” indicating that the call is forwarded to the second called electronic device **1300**, “99999999” which is the phone number of the second called electronic device **1300**, and “10:34” which is an outgoing call time.

(154) According to an embodiment, for example, if the user name of the first called electronic device **1200** is Contact B, the history information **127** of the call forwarded by the user Contact B of the first called electronic device **1200** is displayed on the outgoing call screen of the calling electronic device **1100**, while the calling electronic device **1100** makes the call to the first called electronic device **1200**.

(155) FIG. **13** is a diagram of an example of call forwarding history information stored in a first called electronic device and displayed on a screen of the first called electronic device according to an embodiment of the disclosure.

(156) Referring to FIG. **13**, a call forwarding history table **130** stored in the first called electronic device **1200** may include a field **132** recording the type of the forwarded call, a field **133** recording an electronic device which forwards the call, a field **134** recording an electronic device which originates the call and a field **135** recording an electronic device which receives the forwarded call. For example, the field **132** contains “IN-FORWARDING” indicating that the type of the forwarded call is a call forwarded by the first called electronic device **1200**, the field **133** contains a value “NULL”, the field **134** contains “CONTACT A” which is the user name of the calling electronic device **1100** originating the call, and the field **135** contains “CONTACT C” which is the name of the second called electronic device **1300** receiving the forwarded call.

(157) Based on the call forwarding history table **130**, the first called electronic device **1200** display history information **137** of the forwarded call on the screen. For example, as the forwarded call history information **137**, the first called electronic device **1200** displays a phrase “Call forwarded to Contact C” indicating that the call is forwarded to the second called electronic device **1300**, “99999999” which is the phone number of the second called electronic device **1300**, and “10:36” which is a call forwarding time.

(158) According to an embodiment, for example, if the user name of the calling electronic device **1100** is Contact A, the call forwarding history information **137** of the call from the calling electronic device **1100** is displayed on the incoming call screen of the first called electronic device **1200**, while the first called electronic device **1200** receives the call request from the calling electronic device **1100**.

(159) FIG. **14** is a diagram of an example of call forwarding history information stored in a second called electronic device and displayed on a screen of the second called electronic device according to an embodiment of the disclosure.

(160) Referring to FIG. **14**, a call forwarding history table **140** stored in the second called electronic device **1300** may include a field **142** recording the type of the forwarded call, a field **143** recording an electronic device which forwards the call, a field **144** recording an electronic device which originates the call and a field **145** recording an electronic device which receives the forwarded call. For example, the field **142** contains “INCOMING” indicating that the type of the forwarded call is a call forwarded to the second called electronic device **1300**, the field **143** contains “CONTACT B” which is the user name of the first called electronic device **1200** forwarding the call, the field **144** contains “CONTACT A” which is the user name of the electronic device **1100** originating the call, and the field **145** contains a value “NULL”.

(161) Based on the call forwarding history table **140**, the second called electronic device **1300** may display history information **147** of the forwarded call on the screen. For example, as the forwarded call history information **147**, the second called electronic device **1300** displays on the screen, a phrase “INCOMING” indicating that the forwarded call is the call received at the second called electronic device **1300**, a phrase “Call forwarded by Contact B” indicating that the call is forwarded by the first called electronic device **1200**, “88888888” which is the phone number of the

first called electronic device **1200**, and “10:36” which is a time at which the forwarded call is received.

(162) According to an embodiment, for example, if the user name of the calling electronic device **1100** is Contact A, the call forwarding history information **147** is displayed on the incoming call screen of the second called electronic device **1300**, while the second called electronic device **1300** receives the forwarded call from the calling electronic device **1100**.

(163) FIGS. **12**, **13**, and **14** have described that the calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** each generate the call forwarding history information, but it is not limited thereto. For example, at least one of the calling electronic device **1100**, the first called electronic device **1200** and the second called electronic device **1300** do not generate the call forwarding history information, wherein an electronic device not generating the call forwarding history information may receive from the server **2000** and use the history information generated by the server **2000**. In this case, the call forwarding history table of the server **2000** may include a field recording the type of the forwarded call, a field recording the call forwarding electronic device, a field recording the call originating electronic device and a field recording the electronic device which receives the forwarded call. In addition, a valid value other than the value “null” may be recorded in every field of the call forwarding history table by the server **2000**.

(164) FIG. **15** is a block diagram illustrating an electronic device **1501** in a network environment **1500** according to an embodiment of the disclosure.

(165) Referring to FIG. **15**, the electronic device **1501** in the network environment **1500** may communicate with an electronic device **1502** via a first network **1598** (e.g., a short-range wireless communication network), or at least one of an electronic device **1504** or a server **1508** via a second network **1599** (e.g., a long-range wireless communication network). According to an embodiment, the electronic device **1501** may communicate with the electronic device **1504** via the server **1508**. According to an embodiment, the electronic device **1501** may include a processor **1520**, memory **1530**, an input module **1550**, a sound output module **1555**, a display module **1560**, an audio module **1570**, a sensor module **1576**, an interface **1577**, a connecting terminal **1578**, a haptic module **1579**, a camera module **1580**, a power management module **1588**, a battery **1589**, a communication module **1590**, a subscriber identification module (SIM) **1596**, or an antenna module **1597**. In some embodiments, at least one of the components (e.g., the connecting terminal **1578**) may be omitted from the electronic device **1501**, or one or more other components may be added in the electronic device **1501**. In some embodiments, some of the components (e.g., the sensor module **1576**, the camera module **1580**, or the antenna module **1597**) may be implemented as a single component (e.g., the display module **1560**).

(166) The processor **1520** executes, for example, software (e.g., a program **1540**) to control at least one other component (e.g., a hardware or software component) of the electronic device **1501** coupled with the processor **1520**, and performs various data processing or computation. According to one embodiment, as at least part of the data processing or computation, the processor **1520** may store a command or data received from another component (e.g., the sensor module **1576** or the communication module **1590**) in volatile memory **1532**, process the command or the data stored in the volatile memory **1532**, and store resulting data in non-volatile memory **1534**. According to an embodiment, the processor **1520** may include a main processor **1521** (e.g., a central processing unit (CPU) or an application processor (AP)), or an auxiliary processor **1523** (e.g., a graphics processing unit (GPU), a neural processing unit (NPU), an image signal processor (ISP), a sensor hub processor, or a communication processor (CP)) that is operable independently from, or in conjunction with, the main processor **1521**. For example, when the electronic device **1501** includes the main processor **1521** and the auxiliary processor **1523**, the auxiliary processor **1523** is adapted to consume less power than the main processor **1521**, or to be specific to a specified function. The auxiliary processor **1523** may be implemented as separate from, or as part of the main processor

1521.

(167) The auxiliary processor **1523** may control at least some of functions or states related to at least one component (e.g., the display module **1560**, the sensor module **1576**, or the communication module **1590**) among the components of the electronic device **1501**, instead of the main processor **1521** while the main processor **1521** is in an inactive (e.g., sleep) state, or together with the main processor **1521** while the main processor **1521** is in an active state (e.g., executing an application). According to an embodiment, the auxiliary processor **1523** (e.g., an image signal processor or a communication processor) may be implemented as part of another component (e.g., the camera module **1580** or the communication module **1590**) functionally related to the auxiliary processor **1523**. According to an embodiment, the auxiliary processor **1523** (e.g., the neural processing unit) may include a hardware structure specified for artificial intelligence model processing. An artificial intelligence model may be generated by machine learning. Such learning may be performed, e.g., by the electronic device **1501** where the artificial intelligence is performed or via a separate server (e.g., the server **1508**). Learning algorithms may include, but are not limited to, e.g., supervised learning, unsupervised learning, semi-supervised learning, or reinforcement learning. The artificial intelligence model may include a plurality of artificial neural network layers. The artificial neural network may be a deep neural network (DNN), a convolutional neural network (CNN), a recurrent neural network (RNN), a restricted Boltzmann machine (RBM), a deep belief network (DBN), a bidirectional recurrent deep neural network (BRDNN), deep Q-network or a combination of two or more thereof but is not limited thereto. The artificial intelligence model may, additionally or alternatively, include a software structure other than the hardware structure.

(168) The memory **1530** may store various data used by at least one component (e.g., the processor **1520** or the sensor module **1576**) of the electronic device **1501**. The various data includes, for example, software (e.g., the program **1540**) and input data or output data for a command related thereto. The memory **1530** may include the volatile memory **1532** or the non-volatile memory **1534**.

(169) The program **1540** may be stored in the memory **1530** as software, and includes, for example, an operating system (OS) **1542**, middleware **1544**, or an application **1546**.

(170) The input module **1550** may receive a command or data to be used by another component (e.g., the processor **1520**) of the electronic device **1501**, from the outside (e.g., a user) of the electronic device **1501**. The input module **1550** includes, for example, a microphone, a mouse, a keyboard, a key (e.g., a button), or a digital pen (e.g., a stylus pen).

(171) The sound output module **1555** may output sound signals to the outside of the electronic device **1501**. The sound output module **1555** includes, for example, a speaker or a receiver. The speaker may be used for general purposes, such as playing multimedia or playing record. The receiver may be used for receiving incoming calls. According to an embodiment, the receiver may be implemented as separate from, or as part of the speaker.

(172) The display module **1560** may visually provide information to the outside (e.g., a user) of the electronic device **1501**. The display module **1560** includes, for example, a display, a hologram device, or a projector and control circuitry to control a corresponding one of the display, hologram device, and projector. According to an embodiment, the display module **1560** may include a touch sensor adapted to detect a touch, or a pressure sensor adapted to measure the intensity of force incurred by the touch.

(173) The audio module **1570** may convert a sound into an electrical signal and vice versa. According to an embodiment, the audio module **1570** may obtain the sound via the input module **1550**, or output the sound via the sound output module **1555** or a headphone of an external electronic device (e.g., an electronic device **1502**) directly (e.g., wiredly) or wirelessly coupled with the electronic device **1501**.

(174) The sensor module **1576** may detect an operational state (e.g., power or temperature) of the electronic device **1501** or an environmental state (e.g., a state of a user) external to the electronic

device **1501**, and then generate an electrical signal or data value corresponding to the detected state. According to an embodiment, the sensor module **1576** includes, for example, a gesture sensor, a gyro sensor, an atmospheric pressure sensor, a magnetic sensor, an acceleration sensor, a grip sensor, a proximity sensor, a color sensor, an infrared (IR) sensor, a biometric sensor, a temperature sensor, a humidity sensor, or an illuminance sensor.

(175) The interface **1577** may support one or more specified protocols to be used for the electronic device **1501** to be coupled with the external electronic device (e.g., the electronic device **1502**) directly (e.g., wiredly) or wirelessly. According to an embodiment, the interface **1577** includes, for example, a high definition multimedia interface (HDMI), a universal serial bus (USB) interface, a secure digital (SD) card interface, or an audio interface.

(176) A connecting terminal **1578** may include a connector via which the electronic device **1501** may be physically connected with the external electronic device (e.g., the electronic device **1502**). According to an embodiment, the connecting terminal **1578** includes, for example, an HDMI connector, a USB connector, an SD card connector, or an audio connector (e.g., a headphone connector).

(177) The haptic module **1579** may convert an electrical signal into a mechanical stimulus (e.g., a vibration or a movement) or electrical stimulus which may be recognized by a user via his tactile sensation or kinesthetic sensation. According to an embodiment, the haptic module **1579** includes, for example, a motor, a piezoelectric element, or an electric stimulator.

(178) The camera module **1580** may capture a still image or moving images. According to an embodiment, the camera module **1580** may include one or more lenses, image sensors, image signal processors, or flashes.

(179) The power management module **1588** may manage power supplied to the electronic device **1501**. According to one embodiment, the power management module **1588** may be implemented as at least part of, for example, a power management integrated circuit (PMIC).

(180) The battery **1589** may supply power to at least one component of the electronic device **1501**. According to an embodiment, the battery **1589** includes, for example, a primary cell which is not rechargeable, a secondary cell which is rechargeable, or a fuel cell.

(181) The communication module **1590** may support establishing a direct (e.g., wired) communication channel or a wireless communication channel between the electronic device **1501** and the external electronic device (e.g., the electronic device **1502**, the electronic device **1504**, or the server **1508**) and performing communication via the established communication channel. The communication module **1590** may include one or more communication processors that are operable independently from the processor **1520** (e.g., the application processor (AP)) and supports a direct (e.g., wired) communication or a wireless communication. According to an embodiment, the communication module **1590** may include a wireless communication module **1592** (e.g., a cellular communication module, a short-range wireless communication module, or a global navigation satellite system (GNSS) communication module) or a wired communication module **1594** (e.g., a local area network (LAN) communication module or a power line communication (PLC) module). A corresponding one of these communication modules may communicate with the external electronic device via the first network **1598** (e.g., a short-range communication network, such as Bluetooth™ wireless-fidelity (Wi-Fi) direct, or infrared data association (IrDA)) or the second network **1599** (e.g., a long-range communication network, such as a legacy cellular network, a fifth generation (5G) network, a next-generation communication network, the Internet, or a computer network (e.g., LAN or wide area network (WAN))). These various types of communication modules may be implemented as a single component (e.g., a single chip), or may be implemented as multi components (e.g., multi chips) separate from each other. The wireless communication module **1592** may identify and authenticate the electronic device **1501** in a communication network, such as the first network **1598** or the second network **1599**, using subscriber information (e.g., international mobile subscriber identity (IMSI)) stored in the subscriber identification module **1596**.

(182) The wireless communication module **1592** may support a 5G network, after a fourth generation (4G) network, and next-generation communication technology, e.g., new radio (NR) access technology. The NR access technology may support enhanced mobile broadband (eMBB), massive machine type communications (mMTC), or ultra-reliable and low-latency communications (URLLC). The wireless communication module **1592** may support a high-frequency band (e.g., the millimeter wave (mmWave) band) to achieve, e.g., a high data transmission rate. The wireless communication module **1592** may support various technologies for securing performance on a high-frequency band, such as, e.g., beamforming, massive multiple-input and multiple-output (massive MIMO), full dimensional MIMO (FD-MIMO), array antenna, analog beam-forming, or large scale antenna. The wireless communication module **1592** may support various requirements specified in the electronic device **1501**, an external electronic device (e.g., the electronic device **1504**), or a network system (e.g., the second network **1599**). According to an embodiment, the wireless communication module **1592** may support a peak data rate (e.g., 20 gigabits per second (Gbps) or more) for implementing eMBB, loss coverage (e.g., 164 dB or less) for implementing mMTC, or U-plane latency (e.g., 0.5 milliseconds (ms) or less for each of downlink (DL) and uplink (UL), or a round trip of 1ms or less) for implementing URLLC.

(183) The antenna module **1597** may transmit or receive a signal or power to or from the outside (e.g., the external electronic device) of the electronic device **1501**. According to an embodiment, the antenna module **1597** may include an antenna including a radiating element composed of a conductive material or a conductive pattern formed in or on a substrate (e.g., a printed circuit board (PCB)). According to an embodiment, the antenna module **1597** may include a plurality of antennas (e.g., array antennas). In such a case, at least one antenna appropriate for a communication scheme used in the communication network, such as the first network **1598** or the second network **1599**, is selected, for example, by the communication module **1590** (e.g., the wireless communication module **1592**) from the plurality of antennas. The signal or the power may then be transmitted or received between the communication module **1590** and the external electronic device via the selected at least one antenna. According to an embodiment, another component (e.g., a radio frequency integrated circuit (RFIC)) other than the radiating element may be additionally formed as part of the antenna module **1597**.

(184) According to various embodiments, the antenna module **1597** may form a mmWave antenna module. According to an embodiment, the mmWave antenna module may include a printed circuit board, a RFIC disposed on a first surface (e.g., the bottom surface) of the printed circuit board, or adjacent to the first surface and capable of supporting a designated high-frequency band (e.g., the mmWave band), and a plurality of antennas (e.g., array antennas) disposed on a second surface (e.g., the top or a side surface) of the printed circuit board, or adjacent to the second surface and capable of transmitting or receiving signals of the designated high-frequency band.

(185) At least some of the above-described components may be coupled mutually and communicate signals (e.g., commands or data) therebetween via an inter-peripheral communication scheme (e.g., a bus, general purpose input and output (GPIO), serial peripheral interface (SPI), or mobile industry processor interface (MIPI)).

(186) According to an embodiment, commands or data may be transmitted or received between the electronic device **1501** and the external electronic device **1504** via the server **1508** coupled with the second network **1599**. Each of the electronic devices **1502** or **1504** may be a device of a same type as, or a different type, from the electronic device **1501**. According to an embodiment, all or some of operations to be executed at the electronic device **1501** may be executed at one or more of the external electronic devices **1502** or **1504**, or the server **1508**. For example, if the electronic device **1501** should perform a function or a service automatically, or in response to a request from a user or another device, the electronic device **1501**, instead of, or in addition to, executing the function or the service, requests the one or more external electronic devices to perform at least part of the function or the service. The one or more external electronic devices receiving the request may

perform the at least part of the function or the service requested, or an additional function or an additional service related to the request, and transfer an outcome of the performing to the electronic device **1501**. The electronic device **1501** may provide the outcome, with or without further processing of the outcome, as at least part of a reply to the request. To that end, a cloud computing, distributed computing, mobile edge computing (MEC), or client-server computing technology may be used, for example. The electronic device **1501** may provide ultra-low-latency services using, e.g., distributed computing or mobile edge computing. In another embodiment, the external electronic device **1504** may include an internet-of-things (IoT) device. The server **1508** may be an intelligent server using machine learning and/or a neural network. According to an embodiment, the external electronic device **1504** or the server **1508** may be included in the second network **1599**. The electronic device **1501** may be applied to intelligent services (e.g., smart home, smart city, smart car, or healthcare) based on 5G communication technology or IoT-related technology.

(187) The electronic device **1501** of FIG. **15** may be the calling electronic device **1100**, the first called electronic device **1200** or the second called electronic device **1300**, and the server **1508** may be the server **2000** of FIG. **1**.

(188) According to an embodiment, if the electronic device **1501** of FIG. **15** is the calling electronic device **1100**, the electronic device **1501** may perform the operations of the calling electronic device **1100** of FIGS. **1** through **14**.

(189) In this case, the electronic device **1501** may generate a first SIP invite message. The electronic device **1501** may generate the first SIP invite message for a call with the first called electronic device **1200**, and the first SIP invite message may include an ID value of the electronic device **1501** and an ID value of the first called electronic device **1200**. The SIP invite message includes, for example, but not limited to, the phone number of the electronic device **1501** and the phone number of the first called electronic device **1200**.

(190) The electronic device **1501** may transmit the first SIP invite message to the server **2000**, and receive a response message including contact information generated by the first called electronic device **1200** from the server **2000**.

(191) The electronic device **1501** may extract the contact information from the response message. The electronic device **1501** may extract the contact information included in the response message, and identify from the extracted contact information, that the first called electronic device **1200** is trying to forward the call to the second called electronic device **1300**. For example, the electronic device **1501** obtains from the response message, contact information of the first called electronic device **1200** which forwards the call and contact information of the second called electronic device **1300** which is to receive the forwarded call.

(192) The electronic device **1501** may display the contact information on the outgoing call screen. The electronic device **1501** may display the outgoing call screen after transmitting the first SIP invite message for the call with the first called electronic device **1200**, and if receiving the response message including the contact information from the server **2000** while displaying the outgoing call screen, display the contact information obtained from the received response message on the outgoing call screen. For example, the electronic device **1501** displays on the outgoing call screen, a text indicating that the call to the first called electronic device **1200** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**.

(193) The electronic device **1501** may receive a SIP response code (e.g., 200 OK) from the second called electronic device **1300**, from the server **2000**. The SIP response code (e.g., 200 OK) may request call connection with the electronic device **1501**.

(194) The electronic device **1501** may establish an RTP session for the call with the second called electronic device **1300**. As the RTP session is established, the electronic device **1501** may perform the call with the second called electronic device **1300**.

(195) The electronic device **1501** may generate history information of the call forwarding. The call forwarding history information generated by the electronic device **1501** includes, for example, the

contact information of the first called electronic device **1200**, the contact information of the second called electronic device **1300**, the information indicating that the electronic device **1501** originates the call, the information indicating that the first called electronic device **1200** forwards the call, and the information indicating that the second called electronic device **1300** receives the forwarded call. (196) According to an embodiment, the electronic device **1501** may obtain the contact information from the response message. The electronic device **1501** may obtain the contact information related to the call forwarding from a header recording the contact information included in the response message. For example, the electronic device **1501** identifies at least one of a phone number of the second called electronic device **1300**, a user name of the second called electronic device **1300** or a user nickname of the second called electronic device **1300**, from the 'Call-info' header.

(197) The electronic device **1501** may determine whether contact information corresponding to the contact information obtained from the response message is included in contacts of the electronic device **1501**. The electronic device **1501** may determine whether contact information corresponding to the contact information of the second called electronic device **1300** which receives the forwarded call is included in the contacts of the electronic device **1501**. For example, the electronic device **1501** determines whether the contact information corresponding to at least one the phone number of the second called electronic device **1300**, the user name of the second called electronic device **1300** or the user nickname of the second called electronic device **1300** is included in the contacts of the electronic device **1501**.

(198) If determining whether the contact information corresponding to the contact information obtained from the response message is not included in the contacts of the electronic device **1501**, the electronic device **1501** may display the contact information obtained from the response message on the outgoing call screen.

(199) If determining whether the contact information corresponding to the contact information obtained from the response message is included in the contacts of the electronic device **1501**, the electronic device **1501** may identify contact information corresponding to the contact information obtained from the response message from the contacts of the electronic device **1501**.

(200) The electronic device **1501** may display the contact information identified from the contacts of the electronic device **1501** on the outgoing call screen. In so doing, based on the contact information included in the contacts of the electronic device **1501**, the electronic device **1501** may display information indicating that the call from the electronic device **1501** is forwarded by the first called electronic device **1200** to the second called electronic device **1300**, on the outgoing call screen.

(201) Meanwhile, according to an embodiment, if the electronic device **1501** of FIG. 15 is the first called electronic device **1200**, the electronic device **1501** may perform the operations of the first called electronic device **1200** of FIGS. 1 through 14.

(202) In this case, the electronic device **1501** may receive the first SIP invite message generated by the calling electronic device **1100**, from the server **2000**. The electronic device **1501** may determine whether to forward the call from the calling electronic device **1100**. According to an embodiment, during a call with other electronic device (not shown), the electronic device **1501** may determine whether to forward the call from the calling electronic device **1100**. For example, if receiving a first invite message from the server **2000** during the call with other electronic device (not shown), the electronic device **1501** determines to forward the call from the calling electronic device **1100**.

(203) According to an embodiment, if receiving a user input for not performing the call with the calling electronic device **1100**, the electronic device **1501** may determine to forward the call from the calling electronic device **1100**. For example, if the electronic device **1501** receiving the first invite message receives a user input for rejecting the call or a user input for forwarding the call, the electronic device **1501** determines to forward the call from the calling electronic device **1100**.

(204) According to an embodiment, if satisfying a condition which is preset by the user for the call forwarding, the electronic device **1501** may determine to forward the call from the calling

electronic device **1100**. For example, if a phone number for the call forwarding is preset and the electronic device **1501** receives the first invite message from the calling electronic device **1100** having the preset phone number, the electronic device **1501** determines to forward the call from the calling electronic device **1100**. In this case, the preset phone number may be, but not limited to, a phone number selected by the user for the call forwarding or a phone number call-blocked by the user. For example, if the electronic device **1501** is configured to forward its every call and receives a first invite message from the calling electronic device **1100**, the electronic device **1501** determines to forward the call from the calling electronic device **1100**.

(205) If determining not to forward the call from the calling electronic device **1100**, the electronic device **1501** may perform the call with the calling electronic device **1100**. For example, the electronic device **1501** provides '180: ringing' code and '200 OK' code to the calling electronic device **1100** via the server **2000**, and establish an RTP session with the calling electronic device **1100**.

(206) If determining to forward the call from the calling electronic device **1100**, the electronic device **1501** may obtain contact information. The contact information may include the ID value of the electronic device for the call connection, for example, but not limited to, the phone number of the electronic device, the user name of the electronic device and the user nickname of the electronic device.

(207) According to an embodiment, based on the phone number of the calling electronic device **1100** in the first invite message, the electronic device **1501** may obtain the contact information of the calling electronic device **1100**. For example, the electronic device **1501** obtains the contact information corresponding to the calling electronic device **1100** from a user's phonebook of the electronic device **1501**. The user's phonebook may be stored in the electronic device **1501** or another server (not shown). The contact information of the calling electronic device **1100** includes, for example, but not limited to, the phone number of the calling electronic device **1100**, the user name and the nickname of the calling electronic device **1100**.

(208) According to an embodiment, the electronic device **1501** may obtain the contact information of the second called electronic device **1300** for receiving the forwarded call. In this case, for example, the electronic device **1501** presets the second called electronic device **1300** for receiving the forwarded call, and obtain the contact information of the second called electronic device **1300** which is preset. Alternatively, for example, the electronic device **1501** displays a GUI for selecting the second called electronic device **1300** for receiving the forwarded call, and select the second called electronic device **1300** based on a user input for the GUI. The electronic device **1501** may obtain the contact information of the second called electronic device **1300** selected by the user from the user's phonebook. The contact information of the second called electronic device **1300** may include, for example, but not limited to, the phone number of the second called electronic device **1300**, the user name and the nickname of the second called electronic device **1300**.

(209) According to an embodiment, the electronic device **1501** may obtain the contact information of the electronic device **1501** which forwards the call. The contact information of the electronic device **1501** includes, for example, but not limited to, the phone number of the electronic device **1501**, the user name and the nickname of the electronic device **1501**.

(210) The electronic device **1501** may generate a response message including the contact information. The response message including the contact information includes, for example, a 'Via' header, a 'From' header, a 'To' header, a 'Call-ID' header, a 'CSeq' header, a 'Contact' header, a 'Content-length' header and a 'Call-info' header. The electronic device **1501** may generate the response message including the contact information, by adding a separate header where the contact information is recorded, to the response message. For example, the electronic device **1501** generates the response message including the contact information by adding to the response message the 'Call-info' header where the contact information is recorded. In this case, the response message generated by the electronic device **1501** may include, as a value corresponding to the

'Call-info' header, the contact information of the calling electronic device **1100**, the contact information of the electronic device **1501** and the contact information of the second called electronic device **1300**.

(211) For example, the electronic device **1501** generates the response message further including the call blocking information. The call blocking information may include a value indicating whether the call from the calling electronic device **1100** is blocked by the electronic device **1501**. In this case, the response message may include, as the value corresponding to the 'Call-info' header, the call blocking information indicating whether the calling electronic device **1100** is blocked.

(212) The electronic device **1501** may transmit the response message to the server **2000**.

(213) The electronic device **1501** may generate the call forwarding history information. The call forwarding history information generated by the electronic device **1501** includes, for example, the contact information of the calling electronic device **1100**, the contact information of the second called electronic device **1300**, information indicating that the calling electronic device **1100** originates the call, information indicating that the electronic device **1501** forwards the call, and information indicating that the second called electronic device **1300** receives the forwarded call.

(214) According to an embodiment, the electronic device **1501** may obtain the phone number of the calling electronic device **1100** from the first SIP invite message. The electronic device **1501** may obtain the phone number of the calling electronic device **1100** contained in the first SIP invite message, from the first SIP invite message.

(215) The electronic device **1501** may determine whether the call forwarding function is enabled. The electronic device **1501** may preset whether to enable the call forwarding function, and determine whether the call forwarding function is enabled, based on the setting. In this case, the electronic device **1501** may enable the call forwarding function according to a user input through the GUI for enabling the call forwarding function. If the call forwarding function of the electronic device **1501** is not enabled, in response to receiving the first SIP invite message, the electronic device **1501** may display the GUI for enabling the call forwarding function and receive a user input for the GUI.

(216) The electronic device **1501** may enable the call forwarding function for each phone number of the calling electronic device **1100**. In this case, the electronic device **1501** may determine whether the call forwarding function is enabled for the calling electronic device **1100**, based on the phone number of the calling electronic device **1100**.

(217) If determining that the call forwarding function is not enabled, the electronic device **1501** may terminate the call forwarding operation.

(218) If determining that the call forwarding function is enabled, the electronic device **1501** may determine whether the contact information sharing function is enabled. The contact information sharing function may be a function for sharing the contact information related to the call forwarding, with at least one of the calling electronic device **1100**, the server **2000** and the second called electronic device **1300** if the electronic device **1501** performs the call forwarding.

(219) The electronic device **1501** may preset whether to enable the contact information sharing function, and determine based on the setting whether the contact information sharing function is enabled. In this case, the first called electronic device **1200** may enable the contact information sharing function according to a user input through the GUI for enabling the contact information sharing function. If the contact information sharing function of the electronic device **1501** is not enabled, in response to receiving the first SIP invite message, the electronic device **1501** may display the GUI for enabling the contact information sharing function and receive a user input for the GUI.

(220) The electronic device **1501** may enable the contact information sharing function for each phone number of the calling electronic device **1100**. In so doing, the electronic device **1501** may determine whether the contact information sharing function is enabled for the calling electronic device **1100**, based on the phone number of the calling electronic device **1100**.

(221) If determining that the contact information sharing function is not enabled, the electronic device **1501** may generate a response message without adding the call forwarding contact information. For example, the electronic device **1501** generates the response message not including the separate header containing the contact information to be displayed on the outgoing call screen of the calling electronic device **1100** and the incoming call screen of the second called electronic device **1300**. For example, the electronic device **1501** generates the response message not including the 'Call-info' header where the contact information is recorded.

(222) If determining that the contact information sharing function is enabled, the electronic device **1501** may generate the call blocking information indicating whether to block a call from the calling electronic device **1100**. For example, if the phone number of the calling electronic device **1100** is set to be blocked by the electronic device **1501**, the electronic device **1501** generates the call blocking information indicating that the call from the calling electronic device **1100** is blocked. Alternatively, for example, if the phone number of the calling electronic device **1100** is not set to be blocked by the electronic device **1501**, the electronic device **1501** generates the call blocking information indicating that the call from the calling electronic device **1100** is not blocked.

(223) The electronic device **1501** may select the second called electronic device **1300**. The electronic device **1501** may select the second called electronic device **1300** as the electronic device for receiving the forwarded call, based on a preset criterion. If the second called electronic device **1300** for receiving the forwarded call is preset, the electronic device **1501** may select the second called electronic device **1300** according to the setting. In this case, for example, the second called electronic device **1300** for receiving the forwarded call may be preset, for each calling electronic device **1100**. Alternatively, for example, the electronic device for receiving the forwarded call is set to the second called electronic device **1300** with respect to every call requested from the electronic device **1501**. Alternatively, for example, the second called electronic device **1300** is preset regardless of the phone number of the calling electronic device **1100**.

(224) According to an embodiment, the electronic device **1501** may select the second called electronic device **1300** according to a user input. The electronic device **1501** receiving the first SIP invite message may display a list for selecting the second called electronic device **1300**, and select the second called electronic device **1300** for receiving the forwarded call, according to the user input for the list. For example, the electronic device **1501** displays a GUI inquiring whether to forward the call and a GUI for selecting the second called electronic device **1300** to receive the forwarded call, on the incoming call screen indicating whether the call from the calling electronic device **1100** is requested, and select the second called electronic device **1300** based on user inputs through the GUIs.

(225) The electronic device **1501** may determine to perform the call with the calling electronic device **1100**, based on a status of the electronic device **1501**. For example, if the electronic device **1501** is engaged in a call, the electronic device **1501** does not respond, the electronic device **1501** is in absence, or the electronic device **1501** receives a user input for rejecting the call connection, the electronic device **1501** determines not to perform the call with the calling electronic device **1100**. Alternatively, for example, if receiving a user input for accepting the call from the calling electronic device **1100**, the electronic device **1501** determines to perform the call with the calling electronic device **1100**.

(226) If determining to perform the call with the calling electronic device **1100**, the electronic device **1501** may terminate the call forwarding operation.

(227) If determining not to perform the call with the calling electronic device **1100**, the electronic device **1501** may generate a response message including the contact information related to the call forwarding and the call blocking information.

(228) Meanwhile, according to an embodiment, if the electronic device **1501** of FIG. 15 is the second called electronic device **1300**, the electronic device **1501** may perform the operations of the second called electronic device **1300** of FIGS. 1 through 14. The electronic device **1501** may

receive the second SIP invite message generated by the server **2000**, from the server **2000**.

(229) The electronic device **1501** may extract the contact information from the second SIP invite message. The electronic device **1501** may extract the contact information from the response message, and identify from the extracted contact information whether the first called electronic device **1200** tries to forward the call to the electronic device **1501**. For example, the electronic device **1501** obtains the contact information of the calling electronic device **1100** which attempts the call to the first called electronic device **1200** and the contact information of the first called electronic device **1200** which forwards the call, from the response message.

(230) The electronic device **1501** may display the contact information on the incoming call screen. If receiving the second SIP invite message from the server **2000**, the electronic device **1501** may display the incoming call screen indicating that the forwarded call is incoming. The electronic device **1501** may display the contact information obtained from the received second SIP invite message on the incoming call screen. For example, the electronic device **1501** displays a text indicating that the call from the calling electronic device **1100** to the first called electronic device **1200** is forwarded by the first called electronic device **1200** to the electronic device **1501**, on the incoming call screen.

(231) The electronic device **1501** may generate the call forwarding history information. The call forwarding history information generated by the electronic device **1501** includes, for example, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200**, information indicating that the calling electronic device **1100** originates the call, information indicating that the first called electronic device **1200** forwards the call, and information indicating that the electronic device **1501** receives the forwarded call.

(232) Meanwhile, according to an embodiment, if the server **1508** of FIG. **15** is the server **2000** of FIG. **1**, the server **1508** may perform the operations of the server **2000** of FIGS. **1** through **14**.

(233) In this case, the server **1508** may receive the first SIP invite message from the calling electronic device **1100**, and transmit the first SIP invite message to the first called electronic device **1200**.

(234) The server **1508** may receive the response message including the contact information from the first called electronic device **1200**, and transmit the received response message to the calling electronic device **1100**.

(235) The server **1508** may generate the second SIP invite message including the contact information. The second SIP invite message may be a SIP invite message to be transmitted from the server **1508** to the second called electronic device **1300** for the call forwarding. The server **1508** may obtain the contact information from the response message received from the first called electronic device **1200**, and generate the second SIP invite message including the contact information using at least a part of the obtained contact information.

(236) The second SIP invite message including the contact information includes, for example, the 'Via' header, the 'From' header, the 'To' header, the 'Call-ID' header, the 'CSeq' header, the 'Contact' header, the 'Content-length' header and the 'Call-info' header. The server **1508** may generate the second SIP invite message including the contact information, by adding a separate header where the contact information is recorded, to the second SIP invite message. For example, the server **1508** generates the second SIP invite message including the contact information by adding to the second SIP invite message the 'Call-info' header recording the contact information. In this case, the second SIP invite message generated by the server **1508** may include, as the value corresponding to the 'Call-info' header, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200** and the contact information of the second called electronic device **1300**.

(237) For example, the server **1508** generates the second SIP invite message further including the call blocking information. The call blocking information may include the value indicating whether the call from the calling electronic device **1100** is blocked by the first called electronic device **1200**.

In this case, the second SIP invite message may include, as the value corresponding to the ‘Call-info’ header, the call blocking information indicating whether the calling electronic device **1100** is blocked.

(238) The server **1508** may transmit the second SIP invite message to the second called electronic device **1300**.

(239) The server **1508** may receive the SIP response code (e.g., 200 OK) from the second called electronic device **1300**, and transmit the SIP response code (e.g., 200 OK) to the calling electronic device **1100**. The SIP response code (e.g., 200 OK) may request the call connection with the calling electronic device **1100**.

(240) The server **1508** may generate the call forwarding history information. The call forwarding history information generated by the server **1508** may include, for example, the contact information of the calling electronic device **1100**, the contact information of the first called electronic device **1200**, the contact information of the second called electronic device **1300**, the information indicating that the calling electronic device **1100** originates the call, the information indicating that the first called electronic device **1200** forwards the call, and the information indicating that the second called electronic device **1300** receives the forwarded call.

(241) The electronic device according to various embodiments disclosed in the disclosure may be a device of various types. The electronic devices includes, for example, a portable communication device (e.g., a smart phone), a computer device, a portable multimedia device, a portable medical device, a camera, a wearable device, or a home appliance. According to an embodiment of the disclosure, the electronic devices are not limited to those described above.

(242) It should be appreciated that various embodiments of the disclosure and the terms used therein are not intended to limit technological features disclosed in this document to particular embodiments, and include various changes, equivalents, or replacements for a corresponding embodiment. As used herein, each of such phrases as “A or B,” “at least one of A and B,” “at least one of A or B,” “A, B, or C,” “at least one of A, B, and C,” and “at least one of A, B, or C,” may include one, or all possible combinations of the items enumerated together in a corresponding one of the phrases. Such terms as “1st” and “2nd,” or “first” and “second” may be used to simply distinguish a corresponding component from another, and does not limit the components in other aspect (e.g., importance or order). If an element (e.g., a first element) is referred to, with or without the term “operatively” or “communicatively”, as “coupled with,” “coupled to,” “connected with,” or “connected to” another element (e.g., a second element), it means that the element may be coupled with the other element directly (e.g., wiredly), wirelessly, or via a third element.

(243) The term “module” used in various embodiments of the disclosure may include a unit implemented in hardware, software or firmware, and may be interchangeably used with other term, for example, logic, a logic block, a part, or circuitry. The module may be a single integral component, or a minimum unit or part thereof, for performing one or more functions. For example, according to an embodiment, the module may be implemented in a form of an application-specific integrated circuit (ASIC).

(244) Various embodiments of the disclosure may be implemented as software (e.g., the program **1540**) including one or more instructions which are stored in a storage medium (e.g., the internal memory **1536** or the external memory **1538**) readable by a machine (e.g., the electronic device **1501**). For example, a processor (e.g., the processor **1520**) of the machine (e.g., the electronic device **1501**) invokes at least one of the one or more instructions stored in the storage medium, and execute it or them. This allows the machine to be operated to perform at least one function according to the at least one instruction invoked. The one or more instructions may include a code generated by a compiler or a code executable by an interpreter. The machine-readable storage medium may be provided in the form of a non-transitory storage medium. Herein, ‘non-transitory’ simply means that the storage medium is a tangible device, and does not include a signal (e.g., an electromagnetic wave), but this term does not differentiate between a case where data is semi-

permanently stored in the storage medium and a case where the data is temporarily stored.

(245) According to an embodiment, a method according to various embodiments of the disclosure may be included and provided in a computer program product. The computer program product may be traded as a product between a seller and a buyer. The computer program product may be distributed in the form of a machine-readable storage medium (e.g., compact disc read only memory (CD-ROM)), or be distributed (e.g., downloaded or uploaded) directly or online via an application store (e.g., Play Store™), or between two user devices (e.g., smart phones). If distributed online, at least part of the computer program product may be temporarily stored in the machine-readable storage medium such as a memory of a manufacturer's server, a server of the application store, or a relay server, or may be temporarily generated.

(246) According to various embodiments, each component (e.g., a module or a program) of the above-described components may include a single entity or multiple entities, and some of the multiple entities may be separately deployed in different components. According to various embodiments, one or more component or operations of the above-described components may be omitted, or one or more other components or operations may be added. Alternatively or additionally, a plurality of components (e.g., modules or programs) may be integrated as a single component. In this case, the integrated component may perform one or more functions of each component of the plurality of components in the same or similar manner as they are performed by a corresponding component of the plurality of components before the integration. According to various embodiments, operations performed by the module, the program, or other component may be carried out sequentially, in parallel, repeatedly, or heuristically, or one or more of the operations may be executed in a different order or omitted, or one or more other operations may be added.

(247) While the disclosure has been shown and described with reference to various embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the disclosure as defined by the appended claims and their equivalents.

Claims

1. A first electronic device for forwarding a call from a second electronic device to third electronic device, the first electronic device comprising: a transceiver; memory storing instructions; and one or more processors configured to execute the instructions to: receive from a server a first session initiation protocol (SIP) invite message generated at the second electronic device, through the transceiver, determine whether to forward the call from the second electronic device, in response to receiving the first SIP invite message, upon determining to forward the call from the second electronic device, obtain contact information related to the call forwarding from the second electronic device, wherein the contact information includes a user name of the second electronic device and obtained from a phonebook of a user of the first electronic device, generate a response message comprising the contact information related to the call forwarding, and transmit the response message to the server having provided the first SIP message for providing the response message comprising the contact information from the server to the second electronic device through the transceiver, wherein the contact information in the response message transmitted to the server is used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

2. The first electronic device of claim 1, wherein the one or more processors is further configured to execute the instructions to: identify whether the call from the second electronic device is blocked, and generate call blocking information indicating whether the call from the second electronic device is blocked.

3. The first electronic device of claim 2, wherein the one or more processors is further configured to execute the instructions to: generate the response message comprising the contact information

related to the call forwarding and the call blocking information.

4. The first electronic device of claim 3, wherein the contact information related to the call forwarding comprises contact information of the second electronic device, contact information of the first electronic device, and contact information of the third electronic device, and wherein the call blocking information comprises an identifier that indicates whether the call from the second electronic device is blocked by the first electronic device.

5. The first electronic device of claim 4, wherein, based on the contact information related to the call forwarding in the response message provided to the second electronic device, a graphical user interface (GUI) guiding that the call is forwarded by the first electronic device to the third electronic device is displayed on an outgoing call screen of the second electronic device.

6. The first electronic device of claim 2, wherein the second SIP invite message comprises the contact information and the call blocking information of the response message transmitted to the server.

7. The first electronic device of claim 6, wherein, based on the contact information in the second SIP invite message provided to the third electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device is displayed on an incoming call screen of the third electronic device.

8. The first electronic device of claim 6, wherein, based on the call blocking information in the second SIP invite message, the call forwarded to the third electronic device is ignored by the third electronic device.

9. The first electronic device of claim 1, wherein the one or more processors is further configured to execute the instructions to: generate history information of the call forwarding.

10. The first electronic device of claim 9, wherein the history information of the call forwarding comprises contact information of the second electronic device, contact information of the third electronic device, information indicating that the second electronic device originates the call, information indicating that the first electronic device forwards the call, and information indicating that the third electronic device receives the forwarded call.

11. A method at a first electronic device for forwarding a call from a second electronic device to third electronic device, the method comprising: receiving from a server a first session initiation protocol (SIP) invite message generated at the second electronic device through a transceiver of the first electronic device; determining whether to forward the call from the second electronic device, in response to receiving the first SIP invite message; upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, wherein the contact information includes a user name of the second electronic device and obtained from a phonebook of a user of the first electronic device; generating a response message comprising the contact information related to the call forwarding; and transmitting the response message to the server having provided the first SIP message for providing the response message comprising the contact information from the server to the second electronic device through the transceiver of the first electronic device, wherein the contact information in the response message transmitted to the server is used by the server to generate a second SIP invite message to be transmitted to the third electronic device.

12. The method of claim 11, further comprising: identifying whether the call from the second electronic device is blocked; and generating call blocking information indicating whether the call from the second electronic device is blocked.

13. The method of claim 12, wherein generating the response message comprises: generating the response message comprising the contact information related to the call forwarding and the call blocking information.

14. The method of claim 13, wherein the contact information related to the call forwarding comprises contact information of the second electronic device, contact information of the first electronic device, and contact information of the third electronic device, and wherein the call

blocking information comprises an identifier that indicates whether the call from the second electronic device is blocked by the first electronic device.

15. The method of claim 14, wherein, based on the contact information related to the call forwarding in the response message provided to the second electronic device, a graphical user interface (GUI) guiding that the call is forwarded by the first electronic device to the third electronic device is displayed on an outgoing call screen of the second electronic device.

16. The method of claim 12, wherein the second SIP invite message comprises the contact information and the call blocking information of the response message transmitted to the server.

17. The method of claim 16, wherein, based on the contact information in the second SIP invite message provided to the third electronic device, a GUI guiding that the call is forwarded by the first electronic device to the third electronic device is displayed on an incoming call screen of the third electronic device.

18. The method of claim 16, wherein, based on the call blocking information in the second SIP invite message, the call forwarded to the third electronic device is ignored by the third electronic device.

19. The method of claim 11, further comprising: generating history information of the call forwarding.

20. One or more non-transitory computer-readable recording media storing one or more computer programs including computer-executable instructions that, when executed by one or more processors, cause a first electronic device to perform operations, the operations comprising: receiving from a server a first session initiation protocol (SIP) invite message generated at a second electronic device through a transceiver of the first electronic device; determining whether to forward a call from the second electronic device, in response to receiving the first SIP invite message; upon determining to forward the call from the second electronic device, obtaining contact information related to the call forwarding from the second electronic device, wherein the contact information includes a user name of the second electronic device and obtained from a phonebook of a user of the first electronic device; generating a response message comprising the contact information related to the call forwarding; and transmitting the response message to the server having provided the first SIP message for providing the response message comprising the contact information from the server to the second electronic device through the transceiver of the first electronic device, wherein the contact information in the response message transmitted to the server is used by the server to generate a second SIP invite message to be transmitted to a third electronic device.
